# Engineering Evaluation Report Marin Coffee Roasters Plant # 22434 Application Number 26261

#### I. BACKGROUND

Marin Coffee Roasters (MRC) is applying for an Authority to Construct and/or Permit to Operate the following equipment:

# S-1 Coffee Roaster, San Francisco 2S, 0.1 MMBTU/hr; abated by A-1 Afterburner with Cyclone, San Francisco, 2S-250, 0.25 MMBTU/hr

MRC has requested an annual roasting throughput limit of 35,000 pounds (17.5 tons) of green coffee.

#### II. EMISSIONS SUMMARY

#### Basis:

#### S-1

- 100 lbs/hr
- Coffee Throughput = 35,000 lb/yr
- Operation hours = 35,000 lbs/yr/100 lb/hr = 350 hours/yr
- Roaster Firing Rate = 0.1 MM BTU/hr
- Afterburner Firing Rate = 0.25 MMBTU/hr
- Total fuel throughput = 0.35 MMBTU/hr(350 hrs/yr) = 122.5 MMBTU/yr
- Heat capacity = 1,050 MMBtu/10<sup>6</sup> ft<sup>3</sup> natural gas
- A-1 VOC Destruction Efficiency 90% by weight

Emission factors taken from AP-42, Table 1.4-2 (revised 7/1/98) for small boiler <100 MMBtu/hr are taken for NOx, CO, SO2, and NPOC for the combustion of natural gas:

NOx = (100 lb/ MMscf)/ (1050 MMBtu/ $10^6$  ft³) = 0.095 lb/MMBtu CO = (84 lb/ MMscf)/ (1050 MMBtu/ $10^6$  ft³) = 0.08 lb/MMBtu SO2 = (0.6 lb/MMscf)/ (1050 MMBtu/ $10^6$  ft³) = 5.7 x  $10^{-4}$  lb/MMBtu NPOC = (2.3 lb/7MMscf)/ (1050 MMBTU/ $10^6$  ft³) = 0.00219 lb/MMBtu

### **Combustion Emission Calculations: (Total)**

Pollutant	Emission Factor (lb/MMBtu)	S-1 Emissions (lb/yr)
NOx	0.095	11.6
CO	0.08	9.8
SO2	0.00057	0.07
NPOC	0.00219	0.3

Table 9.13.2-1 and 9.13.2-2 from AP-42 Chapter 9.13.2 (Coffee Roasting) provides the following emission factors for particulate (as PM10), volatile organics (VOC), and carbon monoxide from the coffee roasting process:

PLANT NAME: Marin Roasting Company

STREET ADDRESS: 1551 South Novato

Boulevard

CITY, STATE: Novato, CA

**ZIP CODE**: 94945



**PLANT NO.:** 26261

**DATE:** 30 July 2014

PAGE NO.: Page 2 of 5

**Emission Factors for Coffee Roasting Operations** 

Green coffee bean screening, handling, and storage	PM10 = 0.059 lb/ton
Batch roaster	VOC = 0.86 lb/ton
Batch roaster with thermal oxidizer	VOC = 0.047 lb/ton
	PM10 = 0.12 lb/ton

### Emission from coffee roaster:

Emission factors (batch roaster abated by thermal oxidizer) for emissions of particulate and organics are taken from AP-42 Table 9.13.2-1.

Pollutant	Emission Factors (lb/ton)	Annual Emissions (lb/yr)
PM10	0.12	
	+0.059	3.13
POC (abated)	0.047	0.8

#### **Emissions Summary:**

Pollutants	Emissions (lb/yr)	Total Emissions (TPY)
NOx	11.6	0.01
CO	9.8	0.01
SO2	0.07	Neg
PM10	3.13	0.002
POC	0.8	0.0004
NPOC	0.3	Neg

# Compliance with Regulation 6 -310 Particulate Weight Limitations:

# Limitation of 0.15 grain/dscf

Basis: 1 hour of roaster operation

231 lbs/hr roaster capacity

Roaster emission point: 600 acfm @ 1200°F

349 scfm @ 70°F

# Grain loading calculation from coffee roasting process:

[3.13 lb PM<sub>10</sub>/yr X 7000 grain/lb] / [60 min/hr X 350 hr/yr X 349 dscfm]

= 0.003 grain/dscf

PLANT NAME: Marin Roasting Company

STREET ADDRESS: 1551 South Novato

Boulevard

CITY, STATE: Novato, CA

**ZIP CODE**: 94945



**APPLICATION NO.:** 26261 **PLANT NO.:** 22434

**DATE:** 30 July 2014

PAGE NO.: Page 3 of 5

#### III. PLANT CUMULATIVE INCREASE

Pollutant	Current (TPY)	New (TPY)	Total TPY
NOx	0	0.01	0.01
CO	0	0.01	0.01
SO2	0	Neg	Neg
PM10	0	0.002	0.002
POC	0	0.0004	0.0004
NPOC	0	Neg	Neg

### IV. TOXIC RISK SCREENING

According to Chapter 9.13.2, Coffee Roasting of AP-42, the roaster (S-1) is the main source of gaseous pollutants, including aldehydes and acrolein. However, the California Air Resources Board has invalidated the source test method for acrolein. Until CARB approves a new test method and acrolein emissions are estimated from factors developed using the new test method, the District is not evaluating risk for acrolein.

There are no California Air Toxics Emission Factors (CATEF) factors for the aldehydes from coffee roasting. However, Puget Sound Clean Air Agency did some source testing of a coffee roaster and determined the following toxic emission factors:

Formaldehyde = 0.062 lb/ton Acetaldehyde = 0.036 lb/ton Acrolein = 0.018 lb/ton \*

### **Summary of Toxic Pollutants**

Pollutant	Emission Factors (lb/ton)	Throughput (ton/yr)	Annual Emissions (lb/yr)	Hourly Emissions (lb/hr)	Trigger Level (lb/hr)	Trigger Level (lb/yr)
Formaldehyde	0.062	17.5	1.1	Neg.	0.21	30
Acetaldehyde	0.036	17.5	0.6			64

**Note:** \* The California Air Resources Board has invalidated the source test method for acrolein. Until CARB approves a new test method and acrolein emissions are estimated from factors developed using the new test method, the District is not evaluating risk for acrolein, per the Risk Screening Memo.

A toxic risk screen is not triggered.

#### V. BEST AVAILABLE CONTROL TECHNOLOGY

BACT is not triggered since emissions are less than 10 lbs per day for all pollutants.

PLANT NAME: Marin Roasting Company

STREET ADDRESS: 1551 South Novato

Boulevard

CITY, STATE: Novato, CA

**ZIP CODE**: 94945



APPLICATION NO.: 26261

**PLANT NO.:** 22434

**DATE**: 30 July 2014

PAGE NO.: Page 4 of 5

#### VI. OFFSETS

Offsets are not required since the facility's POC and NOx emissions do not exceed 10 ton/yr per Regulation 2-2-302.

#### VII. CEQA

This application is considered to be ministerial under the District's CEQA guidelines (Regulation 2-1-311) and therefore is not subject to CEQA review. The engineering review for this project requires only the application of standard permit conditions and standard emission factors in accordance with Permit Handbook Chapter 11.3.

#### VIII. STATEMENT OF COMPLIANCE

S-1 will comply with the following requirements:

- Regulation 6 -1-301 Ringelmann No. 1 Limitation
- Regulation 6 -1-302 Opacity Limitation
- Regulation 6 -1-310 Grain loading < 0.15 gr/dscf

NSPS, PSD, and NESHAPS are not triggered

MRC is located within 1000 feet of Rancho Elementary School and 0.25 miles of Marin Oaks High School. As a result, per Regulation 2-1-412, school notification is triggered.

#### IX. PERMIT CONDITIONS

# S-1 shall be subject to the following permit conditions:

- 1. The owner/operator shall not roast more than 35,000 pounds of green coffee beans at S-1 Coffee Roaster with Afterburner with Cyclone (A-1) in any consecutive 12-month period. [Basis: Cumulative Increase]
- 2. The owner/operator of S-1 shall set the minimum furnace temperature of the Afterburner (A-1) at 1200 degrees Fahrenheit (° F) or higher. [Basis: Regulation 2-1-403]
- 3. The owner/operator shall ensure that Afterburner (A-1) is equipped with a temperature-measuring device capable of continuously measuring and recording the temperature in the afterburner. This device shall be accurate to within 10 degrees Fahrenheit (° F) and shall be maintained in accordance with

PLANT NAME: Marin Roasting Company
STREET ADDRESS: 1551 South Novato
Boulevard

Boulevard

CITY, STATE: Novato, CA

**ZIP CODE**: 94945



APPLICATION NO.: 26261
PLANT NO.: 22434

**DATE:** 30 July 2014 **PAGE NO.:** Page 5 of 5

manufacturer's recommendations. This temperature monitor shall be used to determine compliance with the temperature requirements in Part 2. [Basis: Regulation 1-521]

- 4. To demonstrate compliance with the above conditions, the owner/operator shall maintain the following records and provide all of the data necessary to evaluate compliance with the above conditions, including the following information:
  - a. Monthly records of the quantity of green coffee beans roasted at S-1.
  - b. Monthly usage records shall be totaled for each consecutive 12-month period.
  - c. Records of continuous temperature measurements of the integrated afterburner whenever S-1 Coffee Roaster is in operation.
  - d. Monthly natural gas usage for A-1 and S-1 (estimate from facility total monthly natural gas usage is acceptable).

All records shall be retained onsite for two years from the date of entry, and made available for inspection by District staff upon request. These recordkeeping requirements shall not replace the recordkeeping requirements contained in any applicable District Regulations.

[Basis: Cumulative Increase]

#### X. RECOMMENDATION

This District has reviewed the material contained in the permit application for the proposed project and has made a preliminary determination that the project is expected to comply with all applicable requirements of District, state, and federal air quality-related regulations. The preliminary recommendation is to issue an Authority to Construct for the equipment listed below. However, the proposed source will be located within 1000 feet of a school, which triggers public notification requirements of District Regulation 2-1-412.6. After the comments are received and reviewed, the District will make a final determination on the permit.

I recommend that the District initiate a public notice and consider any comments received prior to taking any final action on issuance of an Authority to Construct for the following source:

S-1	Coffee Roaster, San Francisco 2S, 0.1 MMBTU/hr; abated by Afterburner with Cyclone, San Francisco, 2S-250, 0.25 MMBTU/hr	y A-1
By: _	Date:	
, –	M.K. Carol Lee Senior Air Quality Engineer	