

Bay Area Air Quality Management District

939 Ellis Street
San Francisco, CA 94109
(415) 771-6000

FINAL

MAJOR FACILITY REVIEW PERMIT

Issued To:

Criterion Catalysts & Technologies, L.P.
Facility #A0227

Facility Address:

2840 Willow Pass Road
Pittsburg, CA 94565

Mailing Address:

P.O. Box 5159
Pittsburg, CA 94565-0659

Responsible Official

Alvin G. Lim, Plant Site Manager
(925) 458-7200

Facility Contact

Alvin G. Lim, Plant Site Manager
(925) 458-7200

Type of Facility: Catalyst Manufacturing

BAAQMD Engineering Division
Contact: Dharam Singh

Primary SIC: 2819

Product: Catalyst

ISSUED BY THE BAY AREA AIR QUALITY MANAGEMENT DISTRICT

Signed by Jeff McKay for Jack P. Broadbent
Jack P. Broadbent, Executive Officer/Air Pollution Control Officer

February 14, 2012
Date

TABLE OF CONTENTS

I.	STANDARD CONDITIONS.....	3
II.	EQUIPMENT.....	7
III.	GENERALLY APPLICABLE REQUIREMENTS.....	16
IV.	SOURCE-SPECIFIC APPLICABLE REQUIREMENTS.....	19
V.	SCHEDULE OF COMPLIANCE.....	51
VI.	PERMIT CONDITIONS.....	51
VII.	APPLICABLE LIMITS & COMPLIANCE MONITORING REQUIREMENTS.....	68
VIII.	TEST METHODS.....	99
IX.	PERMIT SHIELD.....	101
X.	REVISION HISTORY.....	102
XI.	GLOSSARY.....	103

I. STANDARD CONDITIONS

A. Administrative Requirements

The permit holder shall comply with all applicable requirements in the following regulations:

- BAAQMD Regulation 1 - General Provisions and Definitions
(as amended by the District Board on 5/2/01);
- SIP Regulation 1 - General Provisions and Definitions
(as approved by EPA through 6/28/99);
- BAAQMD Regulation 2, Rule 1 - Permits, General Requirements
(as amended by the District Board on 6/15/05);
- SIP Regulation 2, Rule 1 - Permits, General Requirements
(as approved by EPA through 1/26/99);
- BAAQMD Regulation 2, Rule 2 - Permits, New Source Review
(as amended by the District Board on 6/15/05);
- SIP Regulation 2, Rule 2 - Permits, New Source Review and Prevention of Significant Deterioration
(as approved by EPA through 1/26/99);
- BAAQMD Regulation 2, Rule 4 - Permits, Emissions Banking
(as amended by the District Board on 12/21/04);
- SIP Regulation 2, Rule 4 - Permits, Emissions Banking
(as approved by EPA through 1/26/99); and
- BAAQMD Regulation 2, Rule 6 - Permits, Major Facility Review
(as amended by the District Board on 4/16/03).

B. Conditions to Implement Regulation 2, Rule 6, Major Facility Review

1. This Major Facility Review Permit was issued on December 15, 2008 and expires on December 14, 2013. The permit holder shall submit a complete application for renewal of this Major Facility Review Permit no later than June 14, 2013, and no earlier than December 14, 2012. **If a complete application for renewal has not been submitted in accordance with this deadline, the facility may not operate after December 14, 2013.** If the permit renewal has not been issued by December 14, 2013, but a complete application for renewal has been submitted in accordance with the above deadlines, the existing permit will continue in force until the District takes final action on the renewal application. (Regulation 2-6-307, 404.2, 407,& 409.6; MOP Volume II, Part 3, §4.2)
2. The permit holder shall comply with all conditions of this permit. The permit consists of this document and all appendices. Any non-compliance with the terms and conditions of this permit will constitute a violation of the law and will be grounds for enforcement action; permit termination, revocation and re-issuance, or modification; or denial of a permit renewal application. (Regulation 2-6-307; MOP Volume II, Part 3, §4.11)
3. In the event any enforcement action is brought as a result of a violation of any term or condition of this permit, the fact that it would have been necessary for the permittee to halt or reduce the permitted activity in order to maintain compliance with such term or condition shall not be a defense to such enforcement action. (MOP Volume II, Part 3, §4.11)

I. Standard Conditions

4. This permit may be modified, revoked, reopened and reissued, or terminated for cause. (Regulation 2-6-307, 409.8, 415; MOP Volume II, Part 3, §4.11)
5. The filing of a request by the facility for a permit modification, revocation and re-issuance, or termination, or the filing of a notification of planned changes or anticipated non-compliance does not stay the applicability of any permit condition. (Regulation 2-6-409.7; MOP Volume II, Part 3, §4.11)
6. This permit does not convey any property rights of any sort, or any exclusive privilege. (Regulation 2-6-409.7; MOP Volume II, Part 3, §4.11)
7. The permit holder shall supply within 30 days any information that the District requests in writing to determine whether cause exists for modifying, revoking and reissuing, or terminating the permit or to determine compliance with the permit. (Regulation 1-441, Regulation 2-6-409.4 & 501; MOP Volume II, Part 3, §4.11)
8. Any records required to be maintained pursuant to this permit which the permittee considers to contain proprietary or trade secret information shall be prominently designated as such. Copies of any such proprietary or trade secret information which are provided to the District shall be maintained by the District in a locked confidential file, provided, however, that requests from the public for the review of any such information shall be handled in accordance with the District's procedures set forth in Section 11 of the District's Administrative Code. (Regulation 2-6-419; MOP Volume II, Part 3, §4.11)
9. Proprietary or trade secret information provided to EPA will be subject to the requirements of 40 CFR Part 2, Subpart B - Public Information, Confidentiality of Business Information. (40 CFR Part 2)
10. The emissions inventory submitted with the application for this Major Facility Review Permit is an estimate of actual emissions for the time period stated and is included only as one means of determining applicable requirements for emission sources. It does not establish, or constitute a basis for establishing, any new emission limitations. (MOP Volume II, Part 3, §4.11)
11. The responsible official shall certify all documents submitted by the facility pursuant to the major facility review permit. The certification shall state that based on information and belief formed after reasonable inquiry, the statements and information in the document are true, accurate, and complete. The certifications shall be signed by a responsible official for the facility. (Regulation 2-6-409.20, MOP Volume II, Part 3, §4.11)
12. The permit holder is responsible for compliance, and certification of compliance, with all conditions of the permit, regardless whether it acts through employees, agents, contractors, or subcontractors. (Regulation 2-6-307)

I. Standard Conditions

C. Requirement to Pay Fees

The permit holder shall pay annual fees in accordance with District Regulation 3, including Schedule P. (Regulation 2-6-402 & 409.13, Regulation 3; MOP Volume II, Part 3, §4.12)

D. Inspection and Entry

Access to Facility: The permit holder shall provide reasonable access to the facility and equipment which is subject to this permit to the APCO and/or to his or her designee. (Regulation 1-440, Regulation 2-6-409.3; MOP Volume II, Part 3, §4.14)

E. Records

1. The permit holder must provide any information, records, and reports requested or specified by the APCO. (Regulation 1-441, Regulation 2-6-409.4)
2. Notwithstanding the specific wording in any requirement, all records for federally enforceable requirements shall be maintained for at least five years from the date of creation of the record. (Regulation 2-6-501, MOP Volume II, Part 3, §4.7)

F. Monitoring Reports

Reports of all required monitoring must be submitted to the District at least once every six months, except where an applicable requirement specifies more frequent reporting. Monitoring reports shall be for the following periods: May 1st through October 31st and November 1st through April 30th, and are due on the last day of the month after the end of the reporting period. All instances of non-compliance shall be clearly identified in these reports. The reports shall be certified by the responsible official as true, accurate, and complete. In addition, all instances of non-compliance with the permit shall be reported in writing to the District's Compliance and Enforcement Division within 10 calendar days of the discovery of the incident. Within 30 calendar days of the discovery of any incident of non-compliance, the facility shall submit a written report including the probable cause of non-compliance and any corrective or preventative actions. The reports shall be sent to the following address:

Director of Compliance and Enforcement
Bay Area Air Quality Management District
939 Ellis Street
San Francisco, CA 94109
Attn: Title V Reports

(Regulation 2-6-502, MOP Volume II, Part 3, §4.7)

G. Compliance Certification

Compliance certifications shall be submitted annually by the responsible official of this facility to the Bay Area Air Quality Management District and to the Environmental Protection Agency. The certification period will be November 1st through October 31st. The certification shall be submitted by November 30th of each year. The certification must list each applicable requirement, the compliance status, whether compliance was continuous or intermittent, the method used to determine compliance, and any other

I. Standard Conditions

specific information required by the permit. The permit holder may satisfy this requirement through submittal of District-generated compliance certification forms. The certification should be directed to the District's Compliance and Enforcement Division at the address above, and a copy of the certification should be sent to the Environmental Protection Agency at the following address:

Director of the Air Division
USEPA, Region IX
75 Hawthorne Street
San Francisco, CA94105
Attention: Air-3

(MOP Volume II, Part 3, §4.5 and 4.15)

H. Emergency Provisions

1. The permit holder may seek relief from enforcement action in the event of a breakdown, as defined by Regulation 1-208 of the District's Rules and Regulations, by following the procedures contained in Regulations 1-431 and 1-432. The District will thereafter determine whether breakdown relief will be granted in accordance with Regulation 1-433. (MOP Volume II, Part 3, §4.8)
2. The permit holder may seek relief from enforcement action for a violation of any of the terms and conditions of this permit by applying to the District's Hearing Board for a variance pursuant to Health and Safety Code Section 42350. The Hearing Board will determine after notice and hearing whether variance relief should be granted in accordance with the procedures and standards set forth in Health and Safety Code Section 42350 et seq. (MOP Volume II, Part 3, §4.8)
3. The granting by the District of breakdown relief or the issuance by the Hearing Board of a variance will not provide relief from federal enforcement. (MOP Volume II, Part 3, §4.8)

I. Severability

In the event that any provision of this permit is invalidated by a court or tribunal of competent jurisdiction, or by the Administrator of the EPA, all remaining portions of the permit shall remain in full force and effect. (Regulation 2-6-409.5; MOP Volume II, Part 3, §4.10)

J. Miscellaneous Conditions

1. The maximum capacity for each source as shown in Table II-A is the maximum allowable capacity. Exceedance of the maximum allowable capacity for any source is a violation of Regulation 2, Rule 1, Section 301. (Regulation 2-1-301)

K. Accidental Release

This facility is subject to 40 CFR Part 68, Chemical Accident Prevention Provisions. The permit holder shall submit a risk management plan (RMP) by the date specified in §68.10. The permit holder shall also certify compliance with the requirements of Part 68 as part of the annual compliance certification, as required by Regulation 2, Rule 6. (40 CFR Part 68, Regulation 2, Rule 6)

II. EQUIPMENT

Table II A - Permitted Sources

Each of the following sources has been issued a permit to operate pursuant to the requirements of BAAQMD Regulation 2, Permits. The capacities in this table are the maximum allowable capacities for each source, pursuant to Standard Condition I.J and Regulation 2-1-301. All stated process weight capacities are on a “dry basis”, except where it is specifically identified as on a “wet basis”.

S-#	Description	Make or Type	Model	Capacity
1	X1 Muller	Simpson	3UD	36 ton/day max.
2	X1 Dryer (Natural gas)	Wysmont	Q-16	5.724 MMBTU/hr max, 36 ton/day max.
3	X1 Dried Product Elevator	Link Belt		36 ton/day max.
4	X1 Dried Product Screener	Rotex	#242	36 ton/day max.
5	X1 Longs Breaker	Shell Development	CLOB #1	36 ton/day max.
6	X1 Kiln Feed Conveyor System	Link Belt		36 ton/day max.
7	X1 Kiln (Natural gas)	B/S Rotary	F-82	8.0 MMBTU/hr max., 36 ton/day max.
8	X1 Calcined Product Elevator	Link Belt		36 ton/day max.
9	X1 Calcined Product Screener	Rotex	#242	36 ton/day max.
10	X1 Calcined Product Packaging	Toledo Scale		36 ton/day max.
11	X1 Calcined Product Conveyor	Custom made		36 ton/day max.
19	X1 Recycle Station	Custom made		36 ton/day max.
104	H1 Blending Tank T-1	Open Tank		480 gallon capacity, 36 tons/day max.
105	H1 Blending Tank T-2	Open Tank		480 gallon capacity, 36 tons/day max.
106	H1 Blending Tank T-3	Open Tank		160 gallon capacity, 36 ton/day max.
107	H1 Liquid/Solids Blender	Patterson Foundry	#58-2971	140 cu. ft., 36 tons/day max.
111	04 Calcined Product Elevator	Universal	C2-175	36 ton/day max.
112	04 Calcined Product Screener	Rotex	242	36 ton/day max.
113	04 Calcined Product Packaging	Toledo Scale		36 ton/day max.
114	04 Kiln Hopper	Frederiksen Engineering		36 ton/day max.
303	Alumina Receiving Fluidstat Station	Buhler-Miag, Inc.		100 cu. ft., 100 ton/day max.
304	Alumina Silo 1	Custom made		15,000 cu. ft.
305	Alumina Silo 2	Custom made		15,000 cu. ft.
306	Alumina Silo 3	Custom made		8,500 cu. ft.

II. Equipment

Table II A - Permitted Sources

Each of the following sources has been issued a permit to operate pursuant to the requirements of BAAQMD Regulation 2, Permits. The capacities in this table are the maximum allowable capacities for each source, pursuant to Standard Condition I.J and Regulation 2-1-301. All stated process weight capacities are on a “dry basis”, except where it is specifically identified as on a “wet basis”.

S-#	Description	Make or Type	Model	Capacity
307	Alumina Silo 4	Custom made		8,500 cu. ft.
308	Alumina Silo 5	Custom made		15,000 cu. ft.
309	Alumina Recirculation Fluidstat Station	Buhler-Miag, Inc.		180 cu. ft.
310	Alumina Measuring Fluidstat Station	Buhler-Miag, Inc.		150 cu. ft., 112.5 ton/day max.
311	Alumina Bulk Bag Unloader	Buhler-Miag, Inc.		48 ton/day max.
312	Alumina Repackaging Station	W.W. Sly		32 ton/day max.
313	Fines Grinder Feed Hopper System	Custom made		140 cu. ft., 12 ton/day max.
314	Reground Fines Storage Silo TK-70112	Custom made		750 cu. ft., 12 ton/day max.
315	Reground Fines Storage Silo TK-70113	Custom made		750 cu. ft., 12 ton/day max.
316	Reground Fines Storage Silo TK-70114	Custom made		750 cu. ft., 12 ton/day max.
317	Reground Fines Storage Silo TK-70115	Custom made		750 cu. ft., 12 ton/day max.
318	Fines Weigh Hopper Blow Pot	Smoot	V-70102	25 cu. ft., 12 ton/day max.
319	Fines Bagout Station No. 1 & No. 2			1.0 ton supersacks; 55-gallon drums, 12 ton/day max.
320	Fines Grinder	Micro-Pulverizer	60 ACM	12 ton/day max.
321	Alumina Storage Silo			15,000 cu. ft.
322	Fines Tanker Truck Delivery System	Custom Made		40,000 lb
323	Fines Grinder Feed Hopper System (secondary)	Custom Made		
401	X2 Muller	Simpson	3UD	39 ton/day max.
407	X2 Dryer (Natural gas)	Wysmont	#Q-16	5.7 MMBTU/hr max., 39 ton/day max.
408	X2 Dried Product Elevator	Link Belt, Bucket		39 ton/day max.
409	X2 Dried Product Screener	Rotex	#242	39 ton/day max.

II. Equipment

Table II A - Permitted Sources

Each of the following sources has been issued a permit to operate pursuant to the requirements of BAAQMD Regulation 2, Permits. The capacities in this table are the maximum allowable capacities for each source, pursuant to Standard Condition I.J and Regulation 2-1-301. All stated process weight capacities are on a “dry basis”, except where it is specifically identified as on a “wet basis”.

S-#	Description	Make or Type	Model	Capacity
410	X2 Longs Breaker	Shell Development	CLOB #1	39 ton/day max.
412	X2 Kiln Feed Conveyor	Link Belt, Covered		39 ton/day max.
413	X2 Kiln	B/S, Rotary		8.1 MMBTU/hr max., 39 ton/day max.
414	X2 Calcined Product Elevator	Link Belt or equal		39 ton/day max.
415	X2 Calcined Product Screener	Rotex	#242	39 ton/day max.
416	X2 Calcined Product Packaging	Toledo Scale or equal		39 ton/day max.
417	X2 Calcined Product Conveyor	Custom made		39 ton/day max.
418	X2 Recycle Station	Custom made		39 ton/day max.
420	Cold Cleaner	Shell Design		11 gallon
502	Nickel Solution Tank			15,000 gallon
504	H2 Blending Tank T-1	Heated		500 gallon, 52 ton/day max.
505	H2 Blending Tank T-2	Heated		625 gallon, 52 ton/day max.
506	H2 Blending Tank T-3	Heated		300 gallon, 52 ton/day max.
507	H2 Liquids/Solids Blender			115 cu. ft., 52 ton/day max.
509	H2 Kiln Feed Conveyor	Bucket elevator		52 ton/day max.
510	H2 Kiln (Natural gas)	B/S, Rotary		8.6 MMBTU/hr max., 52 ton/day max.
511	H2 Product Conveyor	Link Belt, Bucket elevator		52 ton/day max.
512	H2 Product Screener	Rotex	#242	52 ton/day max.
513	H2 Product Packaging	Toledo Scale		52 ton/day max.
514	H2 Kiln Bypass Chute & Hopper w/dusthood	Custom made		57 ton/day max.
515	H2 Solid Additive Hopper A	Young, custom		60 ton/day max.
516	H2 Solid Additive Hopper B	Young, custom		60 tons/day max.
517	H2 Product Recycle System	Custom made		52 ton/day max.
518	H2 Calcined Feed System	Custom made		52 ton/day max.
519	H2 Spherical Hopper System	Paystar, custom		52 ton/day max.

II. Equipment

Table II A - Permitted Sources

Each of the following sources has been issued a permit to operate pursuant to the requirements of BAAQMD Regulation 2, Permits. The capacities in this table are the maximum allowable capacities for each source, pursuant to Standard Condition I.J and Regulation 2-1-301. All stated process weight capacities are on a “dry basis”, except where it is specifically identified as on a “wet basis”.

S-#	Description	Make or Type	Model	Capacity
520	H2 Calcined Feed Bagout Station	Custom made		52 ton/day max.
600	X3 Dried Extruder Screener, Conveyors			36 ton/day max.
601	X3 Fines Surge Hopper			36 ton/day max.
602	X3 Alumina Surge Hopper			36 ton/day max.
603	X3 Extruder	Warner Pflidder		36 ton/day max.
604	X3 Dryer (Natural gas)			6.1 MMBTU/hr max., 36 ton/day max.
606	X3 Calciner (Natural gas)	Heyl & Patterson Inc., Custom made		8.718 MMBTU/hr max., 36 ton/day max.

II. Equipment

Table II B – Abatement Devices

A-#	Description	Source(s) Controlled	Applicable Requirement	Operating Parameters	Limit or Efficiency
2	X1 Kiln Baghouse, Reverse Jet, Micro Pul 144-S-10	S7	BAAQMD Reg. 6-1-301, 6-1-310, SIP Reg. 6-301, 6-310, and Cond # 13100	None	Outlet grain loading shall not exceed 0.006 grain/dscf
3	X1 Nuisance Dust Baghouse, Reverse Jet, Flex-Kleen 36BV-25	S3, S4, S5, S6, S8, S9, S10, S11	BAAQMD Reg. 6-1-301, 6-1-310, SIP Reg. 6-301, 6-310, and Cond # 16736	None	Outlet grain loading shall not exceed 0.15 grain/dscf
4	X1 Area Dust Collector, Pulse Jet, Flex-Kleen 120 BVTC, 383 sq. ft., 1116 acfm	S1, S318 (via S1)	BAAQMD Reg. 6-1-301, 6-1-310, SIP Reg. 6-301, 6-310, and Cond # 8444	None	Outlet grain loading shall not exceed 0.006 grain/dscf
6	X1 Dryer Baghouse, Reverse Jet, Flex-Kleen, 10,000 scfm	S2	BAAQMD Reg. 6-1-301, 6-1-310, SIP Reg. 6-301, 6-310, and Cond # 13099	None	Outlet grain loading shall not exceed 0.006 grain/dscf
14	04 Plant Nuisance Dust Baghouse, Pulse Jet, Mikro-Pulsaire, 156S-10-20-TR, 7500 acfm	S110, S111, S112, S113, S114	BAAQMD Reg. 6-1-301, 6-1-310, SIP Reg. 6-301, 6-310, and Cond # 13138	None	Outlet grain loading shall not exceed 0.006 grain/dscf
32	Alumina Receiving Dust Collector, Reverse Jet, Flex-Kleen 84 CT-24, 240 sq. ft.	S303	BAAQMD Reg. 6-1-301, 6-1-310, SIP Reg. 6-301, 6-310,	None	Outlet grain loading shall not exceed 0.15 grain/dscf

II. Equipment

Table II B – Abatement Devices

A-#	Description	Source(s) Controlled	Applicable Requirement	Operating Parameters	Limit or Efficiency
33	Silo 1 Vent Filter, Reverse Jet, Flex-Kleen 84 BV-16, 160 sq. ft.	S304	BAAQMD Reg. 6-1-301, 6-1-310, SIP Reg. 6-301, 6-310,	None	Outlet grain loading shall not exceed 0.15 grain/dscf
34	Silo 2 Vent Filter, Reverse Jet, Flex-Kleen 84 BV-16, 160 sq. ft.	S305	BAAQMD Reg. 6-1-301, 6-1-310, SIP Reg. 6-301, 6-310,	None	Outlet grain loading shall not exceed 0.15 grain/dscf
35	Silo 3 Vent Filter, Reverse Jet, Flex-Kleen 84 BV-16, 160 sq. ft.	S306	BAAQMD Reg. 6-1-301, 6-1-310, SIP Reg. 6-301, 6-310,	None	Outlet grain loading shall not exceed 0.15 grain/dscf
36	Silo 4 Vent Filter, Reverse Jet, Flex-Kleen 84 BV-16, 160 sq. ft.	S307	BAAQMD Reg. 6-1-301, 6-1-310, SIP Reg. 6-301, 6-310,	None	Outlet grain loading shall not exceed 0.15 grain/dscf
37	Silo 5 Vent Filter, Reverse Jet, Flex-Kleen 84 BV-16, 160 sq. ft.	S308	BAAQMD Reg. 6-1-301, 6-1-310, SIP Reg. 6-301, 6-310,	None	Outlet grain loading shall not exceed 0.15 grain/dscf
38	Alumina Recirculation Blowpot Baghouse, Reverse Jet, Flex-Kleen 84 CT-46, 460 sq. ft.	S309	BAAQMD Reg. 6-1-301, 6-1-310, SIP Reg. 6-301, 6-310,	None	Outlet grain loading shall not exceed 0.15 grain/dscf
39	Alumina measuring Blowpot Baghouse, Reverse Jet, Flex-Kleen 84 CT-30, 300 sq. ft.	S310	BAAQMD Reg. 6-1-301, 6-1-310, SIP Reg. 6-301, 6-310,	None	Outlet grain loading shall not exceed 0.15 grain/dscf
40	Repackaging Baghouse, Reverse Jet, Flex-Kleen WRTS-64, 6200 acfm.	S311, S312, S313, S318, S323	Cond # 3344	None	Outlet grain loading shall not exceed 0.005 grain/dscf

II. Equipment

Table II B – Abatement Devices

A-#	Description	Source(s) Controlled	Applicable Requirement	Operating Parameters	Limit or Efficiency
42	X2 Extrudate II Dust Collector - Nuisance Baghouse, Reverse Jet, Mikro Pul 100-S-10-20	S408, S409, S410, S412, S414, S415, S416, S417, S418	BAAQMD Reg. 6-1-301, 6-1-310, SIP Reg. 6-301, 6-310,	None	Outlet grain loading shall not exceed 0.15 grain/dscf
43	X2 Extrudate II Kiln Baghouse, Reverse Jet, Mikro Pul 144-S-10	S413	Cond # 13100	None	Outlet grain loading shall not exceed 0.006 grain/dscf
44	Reground Fines Silo Dust Collector, Pulse Jet, Mikro-Pulsaire 100-S12-TR-B, 1414 sq. ft.	S314, S319 (via S314), S320	Cond # 8468	None	Outlet grain loading shall not exceed 0.005 grain/dscf
45	Reground Fines Silo Dust Collector, Pulse Jet, Mikro-Pulsaire 100-S12-TR-B, 1414 sq. ft.	S315, S320	Cond # 8468	None	Outlet grain loading shall not exceed 0.005 grain/dscf
46	Reground Fines Silo Dust Collector, Pulse Jet, Mikro-Pulsaire 100-S12-TR-B, 1414 sq. ft.	S316, S320	Cond # 8468	None	Outlet grain loading shall not exceed 0.005 grain/dscf
47	Reground Fines Silo Dust Collector, Pulse Jet, Mikro-Pulsaire 100-S12-TR-B, 1414 sq. ft.	S317, S319 (via S317), S320	Cond # 8468	None	Outlet grain loading shall not exceed 0.005 grain/dscf
48	X2 Muller Filter Receiver, Pulse Jet, Flex-Kleen 120 BVTC, 383 sq. ft., 1116 acfm	S318 (via S401), S401	Cond # 8445	None	Outlet grain loading shall not exceed 0.006 grain/dscf
49	H1 Blending Tank Baghouse, Pulse Jet, Mikro-Pulsaire 64S10-20TRC, 3500 acfm	S104, S105, S106	Cond # 9984	None	Outlet grain loading shall not exceed 0.006 grain/dscf
50	Alumina Silo 6 Vent Filter, Pulse Jet, Flex-Kleen 84-BV-16, 160 sq. ft.	S321	Cond # 13092	None	Outlet grain loading shall not exceed 0.006 grain/dscf

II. Equipment

Table II B – Abatement Devices

A-#	Description	Source(s) Controlled	Applicable Requirement	Operating Parameters	Limit or Efficiency
52	H2 Solid Additive Hopper A Filter Receiver, Young Almos, 1200 acfm	S515	BAAQMD Reg. 6-1-301, 6-1-310, SIP Reg. 6-301, 6-310,	None	Outlet grain loading shall not exceed 0.15 grain/dscf
53	H2 Solid Additive Hopper B Filter Receiver, Young Almos, 1200 acfm	S516	BAAQMD Reg. 6-1-301, 6-1-310, SIP Reg. 6-301, 6-310,	None	Outlet grain loading shall not exceed 0.15 grain/dscf
54	H2 Kiln Baghouse, Reverse Jet, Mikro Pul 144-S-8	S504, S505, S506, S507, S510, S514	Cond # 9315	None	Outlet grain loading shall not exceed 0.006 grain/dscf
55	H2 Nuisance Baghouse, Reverse Jet, Mikro Pul 144-S-5	S509, S511, S512, S513, S517, S518, S519, S520	BAAQMD Reg. 6-1-301, 6-1-310, SIP Reg. 6-301, 6-310,	None	Outlet grain loading shall not exceed 0.15 grain/dscf
56	H2 Afterburner - H2 Rotary Kiln Exhaust, Model 1215-10-TR, 8.0 MMBTU/hr max. (Natural gas)	S504, S505, S506, S507, S510, A54	Cond # 9315	Minimum operating temperature of 1400 degree F	CO = 400 ppm @3% Oxygen; NOx = 120 lb/day; NH3 = 200 lb/day
57	X2 Dryer Baghouse, Reverse Jet, Flex-Kleen 10,000 scfm	S407	Cond # 13099	None	Outlet grain loading shall not exceed 0.006 grain/dscf
58	X1/X2 Kiln SCR, Shell DeNOx, 17,000 acfm	S7, S413, A2, A43	Cond # 13100	None	NOx = 58 lb/day or 21,000 lb/yr
320	Alumina Receiving Station Blowpot Dry In-line Filter, Dollinger, 1000 cfm	A32	BAAQMD Reg. 6-1-301, 6-1-310, SIP Reg. 6-301, 6-310,	None	Outlet grain loading shall not exceed 0.15 grain/dscf
380	Alumina Recirculation Station Blowpot Dry In-line Filter, Dollinger, 2000 cfm	A38	BAAQMD Reg. 6-1-301, 6-1-310, SIP Reg. 6-301, 6-310,	None	Outlet grain loading shall not exceed 0.15 grain/dscf

II. Equipment

Table II B – Abatement Devices

A-#	Description	Source(s) Controlled	Applicable Requirement	Operating Parameters	Limit or Efficiency
390	Alumina Measuring Station Blowpot Dry In-line Filter, Dollinger, 2000 cfm	A39	BAAQMD Reg. 6-1-301, 6-1-310, SIP Reg. 6-301, 6-310,	None	Outlet grain loading shall not exceed 0.15 grain/dscf
601	X3 Fines Surge Hopper Baghouse, Pulse Jet, Flex- Kleen, 148 sq. ft.	S318 (via S601), S601	Cond # 13094	None	Outlet grain loading shall not exceed 0.006 grain/dscf
602	X3 Alumina Surge Hopper Baghouse, Pulse Jet, Flex- Kleen, 148 sq. ft.	S602	Cond # 13095	None	Outlet grain loading shall not exceed 0.006 grain/dscf
603	X3 Dryer Baghouse, Reverse Jet, Flex-Kleen, 12,000 scfm	S604	Cond # 13097	Pressure drop to be determined	Outlet grain loading shall not exceed 0.006 grain/dscf
604	X3 Calciner Baghouse, Reverse Jet, Hosakawa Micropul, 2,000 scfm	S606 (tube side)	Cond # 15672	Bag failure warning device	Outlet grain loading shall not exceed 0.006 grain/dscf
605	X3 Calciner SCR, Shell DeNOx, 3,100 dscfm	S606 (tube side)	Cond # 15672	None	NOx = 51 lb/day or 18,500 lb/yr; NH3 = 490 lb/day or 48,000 lb/yr
606	X3 Calciner CO Catalyst, Custom made	S606 (tube side)	Cond # 15672	None	CO abatement efficiency at least 90% and inlet conc. not to exceed 200 ppmv; CO outlet conc. not to exceed 25 ppmv
607	X3 Dust Collector – Nuisance Baghouse, Turbo Jet, Unit BH70343STJ- 131115-8, 8000 scfm	S600	Cond.# 13093	None	Exhaust routed to A603 via S606(shell side) & S604

III. GENERALLY APPLICABLE REQUIREMENTS

The permit holder shall comply with all applicable requirements, including those specified in the BAAQMD and SIP Rules and Regulations and other federal requirements cited below. These requirements apply in a general manner to the facility and/or to sources exempt from the requirement to obtain a District Permit to Operate. The District has determined that these requirements will not be violated under normal, routine operations, and that no additional periodic monitoring or reporting to demonstrate compliance is warranted. In cases where a requirement, in addition to being generally applicable, is also specifically applicable to one or more sources, the requirement and the source are also included in Section IV, Source-Specific Applicable Requirements, of this permit. This section also contains provisions that may apply to temporary sources.

The dates in parentheses in the “Regulation Title or Description of Requirement” column identify the versions of the regulations being cited and are, as applicable:

1. BAAQMD regulation(s): The date(s) of adoption or most recent amendment of the regulation by the District Board of Directors
2. Any federal requirement, including a version of a District regulation that has been approved into the SIP: The most recent date of EPA approval of any portion of the rule, encompassing all actions on the rule through that date

The full language of the current SIP requirements are posted on the EPA Region 9 website at: <http://yosemite.epa.gov/r9/r9sips.nsf/Agency?ReadForm&count=500&state=California&cat=Bay+Area+Air+Quality+Management+District-Agency-Wide+Provisions>.

NOTE:

There are differences between the current BAAQMD rules and the versions of the rules in the SIP. All sources must comply with both versions of the rule until US EPA has reviewed and approved the District’s revision of the regulation.

**Table III
 Generally Applicable Requirements**

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)
BAAQMD Regulation 1	General Provisions and Definitions (5/17/01)	N
SIP Regulation 1	General Provisions and Definitions (6/28/99)	Y
BAAQMD Regulation 2, Rule 1	General Requirements (6/15/05)	N
BAAQMD 2-1-429	Federal Emissions Statement (6/7/95)	Y
SIP Regulation 2, Rule 1	General Requirements (1/26/99)	Y
BAAQMD Regulation 2, Rule 5	New Source Review of Toxic Air Contaminants (6/15/05)	N
BAAQMD Regulation 4	Air Pollution Episode Plan (3/20/91)	N
SIP Regulation 4	Air Pollution Episode Plan (8/06/90)	Y
BAAQMD Regulation 5	Open Burning (3/6/02)	N

III. Generally Applicable Requirements

Table III
Generally Applicable Requirements

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)
SIP Regulation 5	Open Burning (9/4/98)	Y
BAAQMD Regulation 6, Rule 1	Particulate Matter, General Requirements (12/5/2007)	N
SIP Regulation 6	Particulate Matter and Visible Emissions (9/4/98)	Y
BAAQMD Regulation 7	Odorous Substances (3/17/82)	N
BAAQMD Regulation 8, Rule 1	Organic Compounds - General Provisions (6/15/94)	Y
BAAQMD Regulation 8, Rule 2	Organic Compounds – Miscellaneous Operations (7/20/05)	N
SIP Regulation 8, Rule 2	Organic Compounds – Miscellaneous Operations (3/22/95)	Y
BAAQMD Regulation 8, Rule 3	Organic Compounds - Architectural Coatings (11/21/01)	Y
BAAQMD Regulation 8, Rule 4	Organic compounds - General Solvent and Surface Coating Operations (10/16/02)	Y
BAAQMD Regulation 8, Rule 15	Organic Compounds – Emulsified and Liquid Asphalts (6/1/94)	Y
BAAQMD Regulation 8, Rule 40	Organic Compounds - Aeration of Contaminated Soil and Removal of Underground Storage Tanks (6/15/05)	N
SIP Regulation 8, Rule 40	Organic Compounds - Aeration of Contaminated Soil and Removal of Underground Storage Tanks (4/16/2001)	Y
BAAQMD Regulation 8, Rule 47	Organic Compounds - Air Stripping and Soil Vapor Extraction Operations (6/15/05)	N
SIP Regulation 8, Rule 47	Organic Compounds - Air Stripping and Soil Vapor Extraction Operations (4/26/95)	Y
BAAQMD Regulation 8, Rule 49	Organic Compounds - Aerosol Paint Products (12/20/95)	N
SIP Regulation 8, Rule 49	Organic Compounds - Aerosol Paint Products (3/22/95)	Y
BAAQMD Regulation 8, Rule 51	Organic Compounds - Adhesive and Sealant Products (7/17/02)	N
SIP Regulation 8, Rule 51	Organic Compounds - Adhesive and Sealant Products (2/26/02)	Y
BAAQMD Regulation 9, Rule 1	Inorganic Gaseous Pollutants - Sulfur Dioxide (3/15/95)	N
SIP Regulation 9, Rule 1	Inorganic Gaseous Pollutants - Sulfur Dioxide (5/20/92)	Y
BAAQMD Regulation 11, Rule 2	Hazardous Pollutants - Asbestos Demolition, Renovation and Manufacturing (10/7/98)	N
BAAQMD Regulation 12, Rule 4	Miscellaneous Standards of Performance - Sandblasting (7/11/90)	N
SIP Regulation 12, Rule 4	Miscellaneous Standards of Performance - Sandblasting (9/2/81)	Y

III. Generally Applicable Requirements

Table III
Generally Applicable Requirements

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)
California Health and Safety Code Section 41750 et seq.	Portable Equipment	N
California Health and Safety Code Section 44300 et seq.	Air Toxics "Hot Spots" Information and Assessment Act of 1987	N
California Health and Safety Code Title 17, Section 93115	Airborne Toxic Control Measure for Stationary Compression Ignition Engines	N
California Health and Safety Code Title 17, Section 93116	Airborne Toxic Control Measure for Diesel Particulate Matter from Portable Engines Rated at 50 Horsepower and Greater	N
40 CFR Part 61, Subpart M	National Emission Standards for Hazardous Air Pollutants – National Emission Standard for Asbestos (6/19/95)	Y
EPA Regulation 40 CFR 82	Protection of Stratospheric Ozone (2/21/95)	
Subpart F, 40 CFR 82.156	Leak Repair	Y
Subpart F, 40 CFR 82.161	Certification of Technicians	Y
Subpart F, 40 CFR 82.166	Records of Refrigerant	Y

IV. SOURCE-SPECIFIC APPLICABLE REQUIREMENTS

The permit holder shall comply with all applicable requirements, including those specified in the BAAQMD and SIP Rules and Regulations and other federal requirements cited below. The requirements cited in the following tables apply in a specific manner to the indicated source(s).

The dates in parentheses in the Title column identify the versions of the regulations being cited and are, as applicable:

1. BAAQMD regulation(s): The date(s) of adoption or most recent amendment of the regulation by the District Board of Directors
2. Any federal requirement, including a version of a District regulation that has been approved into the SIP: The most recent date of EPA approval of any portion of the rule, encompassing all actions on the rule through that date

The full text of each permit condition cited is included in Section VI, Permit Conditions, of this permit. The full language of the current SIP requirements are posted on the EPA Region 9 website at:

<http://yosemite.epa.gov/r9/r9sips.nsf/Agency?ReadForm&count=500&state=California&cat=Bay+Area+Air+Quality+Management+District-Agency-Wide+Provisions>. All other text may be found in the regulations themselves.

Table IV - A
Source-specific Applicable Requirements
S1 – X1 MULLER

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
BAAQMD Regulation 6, Rule 1	Particulate Matter , General Requirements (12/5/2007)		
6-1-301	Ringelmann 1 Limitation	N	
6-1-305	Visible Particles	N	
6-1-310	Particle Weight Limitation	N	
6-1-311	General Operations	N	
6-1-401	Appearance of Emissions	N	
SIP Regulation 6	Particulate Matter and Visible Emissions (9/4/98)		
6-301	Ringelmann 1 Limitation	Y	
6-305	Visible Particles	Y	
6-310	Particle Weight Limitation	Y	
6-311	General Operations	Y	
6-401	Appearance of Emissions	Y	

IV. Source-specific Applicable Requirements

**Table IV - A
 Source-specific Applicable Requirements
 S1 – X1 MULLER**

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
BAAQMD Condition #8444			
Part 1	Visible emissions limit requirement (basis: Regulation 6-1-301, SIP Regulation 6-301)	Y	
Part 2	A4 Area dust collector air flow rate and exhaust grain loading requirement (basis: cumulative increase)	Y	
Part 3	Abatement requirement, and device failure warning requirement (basis: cumulative increase)	Y	

**Table IV - B
 Source-specific Applicable Requirements
 S2 – X1 DRYER,
 S407 – X2 DRYER**

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
BAAQMD Regulation 6, Rule 1	Particulate Matter , General Requirements (12/5/2007)		
6-1-301	Ringelmann 1 Limitation	N	
6-1-305	Visible Particles	N	
6-1-310	Particle Weight Limitation	N	
6-1-311	General Operations	N	
6-1-401	Appearance of Emissions	N	
SIP Regulation 6	Particulate Matter and Visible Emissions (9/4/98)		
6-301	Ringelmann 1 Limitation	Y	
6-305	Visible Particles	Y	
6-310	Particle Weight Limitation	Y	
6-311	General Operations	Y	
6-401	Appearance of Emissions	Y	

IV. Source-specific Applicable Requirements

**Table IV - B
 Source-specific Applicable Requirements
 S2 – X1 DRYER,
 S407 – X2 DRYER**

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
BAAQMD Regulation 9, Rule 1	Inorganic Gaseous Pollutants, Sulfur Dioxide (3/15/95)		
9-1-301	Limitations on ground level concentrations	N	
9-1-311	Emission Limitations for Catalyst Manufacturing Plants	N	
9-1-311.2	SO2 Emission Limit	N	
SIP Regulation 9, Rule 1	Inorganic Gaseous Pollutants, Sulfur Dioxide (6/8/99)		
9-1-301	Limitations on ground level concentrations	Y	
9-1-311	Emission Limitations for Catalyst Manufacturing Plants	Y	
9-1-311.2	SO2 Emission Limit	Y	
BAAQMD Condition #13099			
Part 1	Visible emissions limit requirement (basis: Regulation 6-1-301, SIP Regulation 6-301, 1-301)	Y	
Part 2	Abatement requirement, and device failure warning requirement (basis: Reg. 6-1-301, 6-1-310, 6-1-311, SIP Regulation 6-301, 6-310, 6-311, cumulative increase)	Y	
Part 3	A6 and A57 Baghouses air flow rate and exhaust grain loading requirement (basis: cumulative increase)	Y	

IV. Source-specific Applicable Requirements

Table IV - C
Source-specific Applicable Requirements
S3 - X1 DRIED PRODUCT ELEVATOR, S4-X1 DRIED PRODUCT SCREENER,
S5-X1 LONGS BREAKER, S6-X1 KILN FEED CONVEYOR SYSTEM,
S8-X1 CALCINED PRODUCT ELEVATOR, S9-X1 CALCINED PRODUCT SCREENER,
S10-X1 CALCINED PRODUCT PACKAGING

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
BAAQMD Regulation 6, Rule 1	Particulate Matter , General Requirements (12/5/2007)		
6-1-301	Ringelmann 1 Limitation	N	
6-1-305	Visible Particles	N	
6-1-310	Particle Weight Limitation	N	
6-1-311	General Operations	N	
6-1-401	Appearance of Emissions	N	
SIP Regulation 6	Particulate Matter and Visible Emissions (9/4/98)		
6-301	Ringelmann 1 Limitation	Y	
6-305	Visible Particles	Y	
6-310	Particle Weight Limitation	Y	
6-311	General Operations	Y	
6-401	Appearance of Emissions	Y	

Table IV - D
Source-specific Applicable Requirements
S7 - X1 KILN, S413 - X2 KILN

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
BAAQMD Regulation 6, Rule 1	Particulate Matter , General Requirements (12/5/2007)		
6-1-301	Ringelmann 1 Limitation	N	
6-1-305	Visible Particles	N	
6-1-310	Particle Weight Limitation	N	
6-1-311	General Operations	N	
6-1-401	Appearance of Emissions	N	

IV. Source-specific Applicable Requirements

**Table IV - D
 Source-specific Applicable Requirements
 S7 - X1 KILN, S413 - X2 KILN**

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
SIP Regulation 6	Particulate Matter and Visible Emissions (9/4/98)		
6-301	Ringelmann 1 Limitation	Y	
6-305	Visible Particles	Y	
6-310	Particle Weight Limitation	Y	
6-311	General Operations	Y	
6-401	Appearance of Emissions	Y	
BAAQMD Regulation 9, Rule 1	Inorganic Gaseous Pollutants, Sulfur Dioxide (3/15/95)		
9-1-301	Limitations on ground level concentrations	N	
9-1-311	Emission Limitations for Catalyst Manufacturing Plants	N	
9-1-311.2	SO2 Emission Limit	N	
SIP Regulation 9, Rule 1	Inorganic Gaseous Pollutants, Sulfur Dioxide (6/8/99)		
9-1-301	Limitations on ground level concentrations	Y	
9-1-311	Emission Limitations for Catalyst Manufacturing Plants	Y	
9-1-311.2	SO2 Emission Limit	Y	
BAAQMD Condition #13100			
Part 1	Visible emissions limit requirement (basis: Regulation 1-301, 6-1-301, SIP Regulation 6-301)	Y	
Part 2	Abatement requirement, and device failure warning requirement (basis: Regulation 6-1-301, 6-1-310, SIP Regulation 6-301, 6-310, BACT)	Y	
Part 3	A2 and A43 Baghouses air flow rate and exhaust grain loading requirement (basis: cumulative increase)	Y	
Part 4	Fuel and fuel usage limits at S7 (basis: cumulative increase)	Y	
Part 5	Fuel and fuel usage limits at S413 (basis: cumulative increase)	Y	
Part 6	NOx daily and annual emission limits (basis: cumulative increase)	Y	
Part 7	Grain loading source test requirement (basis: cumulative increase)	Y	
Part 8	NOx continuous emission monitor (CEM) requirement (basis: cumulative increase)	Y	
Part 9	Fuel meter requirement (basis: cumulative increase)	Y	

IV. Source-specific Applicable Requirements

**Table IV - D
 Source-specific Applicable Requirements
 S7 - X1 KILN, S413 - X2 KILN**

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
Part 10	Fuel usage record keeping requirement (basis: Regulation 2-6-501, cumulative increase)	Y	

**Table IV - E
 Source-specific Applicable Requirements
 S11 - X1 CALCINED PRODUCT CONVEYOR**

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
BAAQMD Regulation 6, Rule 1	Particulate Matter , General Requirements (12/5/2007)		
6-1-301	Ringelmann 1 Limitation	N	
6-1-305	Visible Particles	N	
6-1-310	Particle Weight Limitation	N	
6-1-311	General Operations	N	
6-1-401	Appearance of Emissions	N	
SIP Regulation 6	Particulate Matter and Visible Emissions (9/4/98)		
6-301	Ringelmann 1 Limitation	Y	
6-305	Visible Particles	Y	
6-310	Particle Weight Limitation	Y	
6-311	General Operations	Y	
6-401	Appearance of Emissions	Y	
BAAQMD Condition #16736			
Part 1	Throughput limit (basis: cumulative increase)	Y	
Part 5	Visible emissions limit requirement (basis: Regulation 6-1-301, SIP Regulation 6-301)	Y	
Part 6	Record keeping requirement (basis: cumulative increase)	Y	

IV. Source-specific Applicable Requirements

**Table IV - F
 Source-specific Applicable Requirements
 S19 - X1 RECYCLE STATION**

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
BAAQMD Regulation 6, Rule 1	Particulate Matter , General Requirements (12/5/2007)		
6-1-301	Ringelmann 1 Limitation	N	
6-1-305	Visible Particles	N	
6-1-310	Particle Weight Limitation	N	
6-1-311	General Operations	N	
6-1-401	Appearance of Emissions	N	
SIP Regulation 6	Particulate Matter and Visible Emissions (9/4/98)		
6-301	Ringelmann 1 Limitation	Y	
6-305	Visible Particles	Y	
6-310	Particle Weight Limitation	Y	
6-311	General Operations	Y	
6-401	Appearance of Emissions	Y	
BAAQMD Condition #16736			
Part 1	Throughput limit (basis: cumulative increase)	Y	
Part 6	Record keeping requirement (basis: cumulative increase)	Y	

IV. Source-specific Applicable Requirements

**Table IV - G
 Source-specific Applicable Requirements
 S104 - H1 BLENDING TANK T-1,
 S105 – H1 BLENDING TANK T-2,
 S106 – H1 BLENDING TANK T-3**

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
BAAQMD Regulation 6, Rule 1	Particulate Matter , General Requirements (12/5/2007)		
6-1-301	Ringelmann 1 Limitation	N	
6-1-305	Visible Particles	N	
6-1-310	Particle Weight Limitation	N	
6-1-311	General Operations	N	
6-1-401	Appearance of Emissions	N	
SIP Regulation 6	Particulate Matter and Visible Emissions (9/4/98)		
6-301	Ringelmann 1 Limitation	Y	
6-305	Visible Particles	Y	
6-310	Particle Weight Limitation	Y	
6-311	General Operations	Y	
6-401	Appearance of Emissions	Y	
BAAQMD Condition #9984			
Part 1	Visible emissions limit requirement (basis: Regulation 1-301, 6-1-301, SIP Regulation 6-301)	Y	
Part 2	A49 Baghouse air flow rate and exhaust grain loading requirement (basis: cumulative increase)	Y	
Part 3	Abatement requirement, and device failure warning requirement (basis: Regulation 6-1-301, 6-1-310, 6-1-311; SIP Regulation 6-301, 6-310, 6-311, cumulative increase)	Y	

IV. Source-specific Applicable Requirements

**Table IV - H
 Source-specific Applicable Requirements
 S107 - H1 LIQUID/SOLID BLENDER**

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
BAAQMD Regulation 6, Rule 1	Particulate Matter , General Requirements (12/5/2007)		
6-1-301	Ringelmann 1 Limitation	N	
6-1-305	Visible Particles	N	
6-1-310	Particle Weight Limitation	N	
6-1-311	General Operations	N	
6-1-401	Appearance of Emissions	N	
SIP Regulation 6	Particulate Matter and Visible Emissions (9/4/98)		
6-301	Ringelmann 1 Limitation	Y	
6-305	Visible Particles	Y	
6-310	Particle Weight Limitation	Y	
6-311	General Operations	Y	
6-401	Appearance of Emissions	Y	

**Table IV - I
 Source-specific Applicable Requirements**

**S111 – O4 CALCINED PRODUCT ELEVATOR,
 S112 – O4 CALCINED PRODUCT SCREENER,
 S113 – CALCINED PRODUCT PACKAGING, S114 – O4 KILN HOPPER**

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
BAAQMD Regulation 6, Rule 1	Particulate Matter , General Requirements (12/5/2007)		
6-1-301	Ringelmann 1 Limitation	N	
6-1-305	Visible Particles	N	
6-1-310	Particle Weight Limitation	N	
6-1-311	General Operations	N	
6-1-401	Appearance of Emissions	N	

IV. Source-specific Applicable Requirements

**Table IV - I
 Source-specific Applicable Requirements**

**S111 – O4 CALCINED PRODUCT ELEVATOR,
 S112 – O4 CALCINED PRODUCT SCREENER,
 S113 – CALCINED PRODUCT PACKAGING, S114 – O4 KILN HOPPER**

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
SIP Regulation 6	Particulate Matter and Visible Emissions (9/4/98)		
6-301	Ringelmann 1 Limitation	Y	
6-305	Visible Particles	Y	
6-310	Particle Weight Limitation	Y	
6-311	General Operations	Y	
6-401	Appearance of Emissions	Y	
BAAQMD Condition #13138			
Part 1	Visible emissions limit requirement (basis: Regulation 1-301, 6-1-301, SIP Regulation 6-301)	Y	
Part 2	A14 Baghouse particulate emission rate, and exhaust grain loading requirement (basis: cumulative increase)	Y	
Part 3	Abatement requirement, and device failure warning requirement (basis: Regulation 6-1-301, 6-1-310; SIP Regulation 6-301, 6-310, cumulative increase)	Y	

**Table IV - J
 Source-specific Applicable Requirements
 S303 - ALUMINA RECEIVING FLUIDSTAT STATION,
 S309 – ALUMINA RECIRCULATION FLUIDSTAT STATION,
 S310 – ALUMINA MEASURING FLUIDSTAT STATION**

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
BAAQMD Regulation 6, Rule 1	Particulate Matter , General Requirements (12/5/2007)		
6-1-301	Ringelmann 1 Limitation	N	

IV. Source-specific Applicable Requirements

Table IV - J
Source-specific Applicable Requirements
S303 - ALUMINA RECEIVING FLUIDSTAT STATION,
S309 – ALUMINA RECIRCULATION FLUIDSTAT STATION,
S310 – ALUMINA MEASURING FLUIDSTAT STATION

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
6-1-305	Visible Particles	N	
6-1-310	Particle Weight Limitation	N	
6-1-311	General Operations	N	
6-1-401	Appearance of Emissions	N	
SIP Regulation 6	Particulate Matter and Visible Emissions (9/4/98)		
6-301	Ringelmann 1 Limitation	Y	
6-305	Visible Particles	Y	
6-310	Particle Weight Limitation	Y	
6-311	General Operations	Y	
6-401	Appearance of Emissions	Y	

Table IV - K
Source-specific Applicable Requirements
S304 - ALUMINA SILO 1
S305 – ALUMINA SILO 2, S306 – ALUMINA SILO 3
S307 – ALUMINA SILO 4, S308 – ALUMINA SILO 5

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
BAAQMD Regulation 6, Rule 1	Particulate Matter , General Requirements (12/5/2007)		
6-1-301	Ringelmann 1 Limitation	N	
6-1-305	Visible Particles	N	
6-1-310	Particle Weight Limitation	N	
6-1-311	General Operations	N	
6-1-401	Appearance of Emissions	N	
SIP Regulation 6	Particulate Matter and Visible Emissions (9/4/98)		
6-301	Ringelmann 1 Limitation	Y	
6-305	Visible Particles	Y	

IV. Source-specific Applicable Requirements

**Table IV - K
 Source-specific Applicable Requirements
 S304 - ALUMINA SILO 1
 S305 – ALUMINA SILO 2, S306 – ALUMINA SILO 3
 S307 – ALUMINA SILO 4, S308 – ALUMINA SILO 5**

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
6-310	Particle Weight Limitation	Y	
6-311	General Operations	Y	
6-401	Appearance of Emissions	Y	

**Table IV - L
 Source-specific Applicable Requirements
 S311 - ALUMINA BULK BAG UNLOADER,
 S312 – ALUMINA REPACKAGING STATION,
 S313 – FINES GRINDER FEED HOPPER SYSTEM
 S-323 – FINES GRINDER FEED HOPPER SYSTEM (SECONDARY)**

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
BAAQMD Regulation 6, Rule 1	Particulate Matter , General Requirements (12/5/2007)		
6-1-301	Ringelmann 1 Limitation	N	
6-1-305	Visible Particles	N	
6-1-310	Particle Weight Limitation	N	
6-1-311	General Operations	N	
6-1-401	Appearance of Emissions	N	
SIP Regulation 6	Particulate Matter and Visible Emissions (9/4/98)		
6-301	Ringelmann 1 Limitation	Y	
6-305	Visible Particles	Y	
6-310	Particle Weight Limitation	Y	
6-311	General Operations	Y	
6-401	Appearance of Emissions	Y	
BAAQMD Condition #3344			

IV. Source-specific Applicable Requirements

Table IV - L
Source-specific Applicable Requirements
S311 - ALUMINA BULK BAG UNLOADER,
S312 – ALUMINA REPACKAGING STATION,
S313 – FINES GRINDER FEED HOPPER SYSTEM
S-323 – FINES GRINDER FEED HOPPER SYSTEM (SECONDARY)

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
Part 1	Visible emission limit requirement (basis: Regulation 1-301, 6-1-301, SIP Regulation 6-301)	Y	
Part 2	S311 and S312 throughput limit (basis: cumulative increase)	Y	
Part 3	S313 and S323 catalyst throughput limit (basis: cumulative increase)	Y	
Part 4	Abatement requirement (basis: Regulation 6-1-301, 6-1-310, 6-1-311, SIP Regulation 6-301, 6-310, 6-311)	Y	
Part 5	A40 Baghouse good operating condition requirement, and device failure warning requirement (basis: Regulation 6-1-301, 6-1-310, 6-1-311, SIP Regulation 6-301, 6-310, 6-311)	Y	
Part 6	A40 Baghouse air flow rate and exhaust grain loading limits requirement (basis: cumulative increase)	Y	
Part 7	Nickel content limit in the material processed at S313 and S323 (basis: toxic risk screen)	Y	
Part 8	Record keeping requirement (basis: Regulation 2-6-501; cumulative increase)	Y	

Table IV - M
Source-specific Applicable Requirements
S314 - REGROUND FINES STORAGE SILO TK-70112,
S315 - REGROUND FINES STORAGE SILO TK-70113,
S316 - REGROUND FINES STORAGE SILO TK-70114,
S317 - REGROUND FINES STORAGE SILO TK-70115,
S318 – FINES WEIGH HOPPER BLOW POT,
S319 – FINES BAGOUT STATION No.1 & No.2,
S320 – FINES GRINDER
S322 – FINES TANKER TRUCK DELIVERY SYSTEM

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
-------------------------------	---	------------------------------------	------------------------------

IV. Source-specific Applicable Requirements

Table IV - M
Source-specific Applicable Requirements
S314 - REGROUND FINES STORAGE SILO TK-70112,
S315 - REGROUND FINES STORAGE SILO TK-70113,
S316 - REGROUND FINES STORAGE SILO TK-70114,
S317 - REGROUND FINES STORAGE SILO TK-70115,
S318 – FINES WEIGH HOPPER BLOW POT,
S319 – FINES BAGOUT STATION No.1 & No.2,
S320 – FINES GRINDER
S322 – FINES TANKER TRUCK DELIVERY SYSTEM

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
BAAQMD Regulation 6, Rule 1	Particulate Matter , General Requirements (12/5/2007)		
6-1-301	Ringelmann 1 Limitation	N	
6-1-305	Visible Particles	N	
6-1-310	Particle Weight Limitation	N	
6-1-311	General Operations	N	
6-1-401	Appearance of Emissions	N	
SIP Regulation 6	Particulate Matter and Visible Emissions (9/4/98)		
6-301	Ringelmann 1 Limitation	Y	
6-305	Visible Particles	Y	
6-310	Particle Weight Limitation	Y	
6-311	General Operations	Y	
6-401	Appearance of Emissions	Y	
BAAQMD Condition #8468			
Part 1	Visible emission limit requirement (basis: Regulation 1-301, 6-1-301, SIP Regulation 6-301)	Y	
Part 2	Catalyst throughput limit (basis: cumulative increase)	Y	
Part 3	One silo loading at one time requirement (basis: cumulative increase)	Y	
Part 4	Abatement requirement (basis: Regulation 6-1-301, 6-1-310, 6-1-311; SIP Regulation 6-301, 6-310, 6-311, cumulative increase)	Y	
Part 5	A44 through A47 Baghouses good operating condition requirement, and device failure warning requirement (basis: Regulation 6-1-301, 6-1-310, 6-1-311; SIP Regulation 6-301, 6-310, 6-311, cumulative increase)	Y	
Part 6	A44 through A47 Baghouses air flow rate, and exhaust grain loading	Y	

IV. Source-specific Applicable Requirements

Table IV - M
Source-specific Applicable Requirements
S314 - REGROUND FINES STORAGE SILO TK-70112,
S315 - REGROUND FINES STORAGE SILO TK-70113,
S316 - REGROUND FINES STORAGE SILO TK-70114,
S317 - REGROUND FINES STORAGE SILO TK-70115,
S318 – FINES WEIGH HOPPER BLOW POT,
S319 – FINES BAGOUT STATION No.1 & No.2,
S320 – FINES GRINDER
S322 – FINES TANKER TRUCK DELIVERY SYSTEM

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
	limits requirement (basis: cumulative increase)		
Part 7	Nickel content limit in the material processed (basis: toxic risk screen)	Y	
Part 8	Record keeping requirement (basis: Regulation 2-6-501; cumulative increase)	Y	

Table IV - N
Source-specific Applicable Requirements
S321 - ALUMINA STORAGE SILO

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
BAAQMD Regulation 6, Rule 1	Particulate Matter , General Requirements (12/5/2007)		
6-1-301	Ringelmann 1 Limitation	N	
6-1-305	Visible Particles	N	
6-1-310	Particle Weight Limitation	N	
6-1-311	General Operations	N	
6-1-401	Appearance of Emissions	N	
SIP Regulation 6	Particulate Matter and Visible Emissions (9/4/98)		
6-301	Ringelmann 1 Limitation	Y	
6-305	Visible Particles	Y	
6-310	Particle Weight Limitation	Y	
6-311	General Operations	Y	

IV. Source-specific Applicable Requirements

**Table IV - N
 Source-specific Applicable Requirements
 S321 - ALUMINA STORAGE SILO**

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
6-401	Appearance of Emissions	Y	
BAAQMD Condition #13092			
Part 1	Visible emission limit requirement (basis: Regulation 1-301, 6-1-301, SIP Regulation 6-301)	Y	
Part 2	Throughput limit requirement (basis: cumulative increase)	Y	
Part 3	Abatement requirement; A50 Baghouse good operating condition and device failure warning requirement (basis: Regulation 6-1-301, 6-1-310, 6-1-311; SIP Regulation 6-301, 6-310, 6-311, cumulative increase)	Y	
Part 4	A50 Baghouse air flow rate, and exhaust grain loading limits requirement (basis: cumulative increase)	Y	
Part 5	Record keeping requirement (basis: Regulation 2-6-501; cumulative increase)	Y	

IV. Source-specific Applicable Requirements

**Table IV - O
 Source-specific Applicable Requirements
 S401 - X2 MULLER**

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
BAAQMD Regulation 6, Rule 1	Particulate Matter , General Requirements (12/5/2007)		
6-1-301	Ringelmann 1 Limitation	N	
6-1-305	Visible Particles	N	
6-1-310	Particle Weight Limitation	N	
6-1-311	General Operations	N	
6-1-401	Appearance of Emissions	N	
SIP Regulation 6	Particulate Matter and Visible Emissions (9/4/98)		
6-301	Ringelmann 1 Limitation	Y	
6-305	Visible Particles	Y	
6-310	Particle Weight Limitation	Y	
6-311	General Operations	Y	
6-401	Appearance of Emissions	Y	
BAAQMD Condition #8445			
Part 1	Visible emissions limit requirement (basis: Regulation 1-301, 6-1-301, SIP Regulation 6-301)	Y	
Part 2	A48 Baghouse air flow rate, and exhaust grain loading requirement (basis: cumulative increase)	Y	
Part 3	Abatement requirement, and device failure warning requirement (basis: Regulation 6-1-301, 6-1-310, 6-1-311; SIP Regulation 6-301, 6-310, 6-311, cumulative increase)	Y	

IV. Source-specific Applicable Requirements

Table IV - P
Source-specific Applicable Requirements
S408 - X2 DRIED PRODUCT ELEVATOR,
S409 – X2 DRIED PRODUCT SCREENER,
S410 – X2 LONGS BREAKER,
S412 – X2 KILN FEED CONVEYOR,
S414 – X2 CALCINED PRODUCT ELEVATOR,
S415 – X2 CALCINED PRODUCT SCREENER,
S416 – X2 CALCINED PRODUCT PACKAGING

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
BAAQMD Regulation 6, Rule 1	Particulate Matter , General Requirements (12/5/2007)		
6-1-301	Ringelmann 1 Limitation	N	
6-1-305	Visible Particles	N	
6-1-310	Particle Weight Limitation	N	
6-1-311	General Operations	N	
6-1-401	Appearance of Emissions	N	
SIP Regulation 6	Particulate Matter and Visible Emissions (9/4/98)		
6-301	Ringelmann 1 Limitation	Y	
6-305	Visible Particles	Y	
6-310	Particle Weight Limitation	Y	
6-311	General Operations	Y	
6-401	Appearance of Emissions	Y	

IV. Source-specific Applicable Requirements

Table IV - Q
Source-specific Applicable Requirements
S417 - X2 CALCINED PRODUCT CONVEYOR,
S418 – X2 RECYCLE STATION,
S515 – H2 SOLID ADDITIVE HOPPER A,
S516 – H2 SOLID ADDITIVE HOPPER B,
S517 – H2 PRODUCT RECYCLE SYSTEM,
S518 – H2 CALCINED FEED SYSTEM,
S519 – H2 SPHERICAL HOPPER SYSTEM,
S520 – H2 CALCINED FEED BAGOUT STATION

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
BAAQMD Regulation 6, Rule 1	Particulate Matter , General Requirements (12/5/2007)		
6-1-301	Ringelmann 1 Limitation	N	
6-1-305	Visible Particles	N	
6-1-310	Particle Weight Limitation	N	
6-1-311	General Operations	N	
6-1-401	Appearance of Emissions	N	
SIP Regulation 6	Particulate Matter and Visible Emissions (9/4/98)		
6-301	Ringelmann 1 Limitation	Y	
6-305	Visible Particles	Y	
6-310	Particle Weight Limitation	Y	
6-311	General Operations	Y	
6-401	Appearance of Emissions	Y	
BAAQMD Condition #16736			
Part 1	Throughput limit (basis: cumulative increase)	Y	
Part 5	Visible emissions limit requirement (basis: Regulation 6-1-301, SIP Regulation 6-301)	Y	
Part 6	Record keeping requirement (basis: cumulative increase)	Y	

IV. Source-specific Applicable Requirements

**Table IV - R
 Source-specific Applicable Requirements
 S420 - COLD CLEANER**

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
BAAQMD Regulation 8, Rule 16	Organic Compounds - Solvent Cleaning Operations (10/16/2002)		
8-16-118	Limited Exemption, compound with low volatility	Y	
8-16-118.2	Cold cleaner		
8-16-121	Limited Exemption, Single cold cleaner	Y	
8-16-122	Limited Exemption, Permitted cold cleaner	Y	
8-16-303	Cold Cleaner Requirements	Y	
8-16-303.1	General Operating Requirements	Y	
8-16-303.1.1	Proper Operation and Maintenance	Y	
8-16-303.1.2	Leak Repair Requirement	Y	
8-16-303.1.3	Prevention of Evaporation of Solvent	Y	
8-16-303.1.4	Waste Solvent	Y	
8-16-303.1.4.a	Waste Solvent - Covered Containers	Y	
8-16-303.1.4.b	Waste Solvent Treatment	Y	
8-16-303.1.5	Solvent Covers/Remote Reservoirs	Y	
8-16-303.1.6	Solvent Spray	Y	
8-16-303.2	Cold Cleaner Operating Requirements	Y	
8-16-303.2.1	Solvent Draining	Y	
8-16-303.2.2	Solvent Agitation	Y	
8-16-303.2.3	Porous and Absorbent Materials	Y	
8-16-303.3	Cold Cleaner General Equipment Requirements	Y	
8-16-303.3.1	Container	Y	
8-16-303.3.2	Cover/Apparatus to Reduce Evaporation	Y	
8-16-303.3.3	Draining Clean Parts	Y	
8-16-303.3.4	Label	Y	
8-16-304	Halogenated solvent Limitation	Y	
8-16-501	Solvent Records	Y	

IV. Source-specific Applicable Requirements

**Table IV - S
 Source-specific Applicable Requirements
 S502 - NICKEL SOLUTION TANK**

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
BAAQMD Regulation 2 Rule 1	Permits, General Requirements (7/19/2006)		
2-1-316.1	Toxic compound emission limit and risk screening analysis	N	
SIP Regulation 2 Rule 1	Permits, General Requirements (11/1/89)		
2-1-316.1	Toxic compound emission limit and risk screening analysis	Y	

**Table IV – T
 Source-specific Applicable Requirements
 S504 - H2 BLENDING TANK T-1, S505 – H2 BLENDING TANK T-2,
 S506 – H2 BLENDING TANK T-3, S507 – H2 LIQUID/SOLIDS BLENDER,
 S509 – HSA KILN FEED CONVEYOR, S510 – H2 KILN, S514 – H2 KILN
 BYPASS CHUTE & HOPPER W/DUSTHOOD**

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
BAAQMD Regulation 6, Rule 1	Particulate Matter , General Requirements (12/5/2007)		
6-1-301	Ringelmann 1 Limitation	N	
6-1-305	Visible Particles	N	
6-1-310	Particle Weight Limitation	N	
6-1-311	General Operations	N	
6-1-401	Appearance of Emissions	N	
SIP Regulation 6	Particulate Matter and Visible Emissions (9/4/98)		
6-301	Ringelmann 1 Limitation	Y	
6-305	Visible Particles	Y	
6-310	Particle Weight Limitation	Y	
6-311	General Operations	Y	
6-401	Appearance of Emissions	Y	

IV. Source-specific Applicable Requirements

Table IV – T
Source-specific Applicable Requirements
S504 - H2 BLENDING TANK T-1, S505 – H2 BLENDING TANK T-2,
S506 – H2 BLENDING TANK T-3, S507 – H2 LIQUID/SOLIDS BLENDER,
S509 – HSA KILN FEED CONVEYOR, S510 – H2 KILN, S514 – H2 KILN
BYPASS CHUTE & HOPPER W/DUSTHOOD

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
BAAQMD Regulation 7	Odorous Substances (3/17/82)		
7-301	General limit	N	
7-302	Limit at or beyond property line	N	
7-303	Limit	N	
7-401	Collection of Samples	N	
7-402	Analysis of Samples	N	
7-403	Evaluation apparatus	N	
7-404	Evaluation Procedure	N	
7-405	Evaluation Analysis	N	
7-601	Collection of Samples	N	
7-602	Sampling Equipment and Techniques for Collection	N	
BAAQMD Condition #9315			
Part 1	Nickel and Nickel compounds limit in the materials to be processed (basis: toxic risk screening analysis)	Y	
Part 2	Material throughput limit at S510 & S514 (basis: cumulative increase)	Y	
Part 3	A54 Baghouse Visible emissions limit requirement (basis: Regulation 1-301, 6-1-301, SIP Regulation 6-301)	Y	
Part 4	A54 Baghouse air flow rate, and exhaust grain loading requirement (basis: cumulative increase)	Y	
Part 5	Abatement requirement, and device failure warning requirement (basis: Regulation 6-1-301, 6-1-310, 6-1-311; SIP Regulation 6-301, 6-310, 6-311, cumulative increase)	Y	
Part 6	A56 Afterburner good operating condition requirement (basis: cumulative increase)	Y	
Part 7	Natural gas fuel only, and temperature monitor requirement (basis: cumulative increase)	Y	
Part 8	A56 Afterburner CO emissions limit requirement (basis: cumulative increase)	Y	
Part 9	A56 Afterburner operating temperature and residence time requirements (basis: cumulative increase)	Y	

IV. Source-specific Applicable Requirements

Table IV – T
Source-specific Applicable Requirements
S504 - H2 BLENDING TANK T-1, S505 – H2 BLENDING TANK T-2,
S506 – H2 BLENDING TANK T-3, S507 – H2 LIQUID/SOLIDS BLENDER,
S509 – HSA KILN FEED CONVEYOR, S510 – H2 KILN, S514 – H2 KILN
BYPASS CHUTE & HOPPER W/DUSTHOOD

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
Part 10	NOx and NH3 daily emission limits (basis: cumulative increase)	Y	
Part 11	A56 Afterburner operating option linked with NH3 daily emissions (basis: cumulative increase)	Y	
Part 12	A56 Afterburner visible emissions limit requirement (basis: Regulation 1-301, 6-1-301, SIP Regulation 6-301)	Y	
Part 13	Annual source test requirement (basis: cumulative increase)	Y	
Part 14	Record keeping (basis: Regulation 2-6-501; cumulative increase)	Y	

Table IV - U
Source-specific Applicable Requirements
S511 - HSA PRODUCT CONVEYOR,
S512 – HSA PRODUCT SCREENER,
S513 – HSA PRODUCT PACKAGING

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
BAAQMD Regulation 6, Rule 1	Particulate Matter , General Requirements (12/5/2007)		
6-1-301	Ringelmann 1 Limitation	N	
6-1-305	Visible Particles	N	
6-1-310	Particle Weight Limitation	N	
6-1-311	General Operations	N	
6-1-401	Appearance of Emissions	N	
SIP Regulation 6	Particulate Matter and Visible Emissions (9/4/98)		
6-301	Ringelmann 1 Limitation	Y	
6-305	Visible Particles	Y	
6-310	Particle Weight Limitation	Y	
6-311	General Operations	Y	
6-401	Appearance of Emissions	Y	

IV. Source-specific Applicable Requirements

**Table IV - V
 Source-specific Applicable Requirements
 S600 - X3 DRIED EXTRUDER, SCREENER, CONVEYORS**

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
BAAQMD Regulation 6, Rule 1	Particulate Matter , General Requirements (12/5/2007)		
6-1-301	Ringelmann 1 Limitation	N	
6-1-305	Visible Particles	N	
6-1-310	Particle Weight Limitation	N	
6-1-311	General Operations	N	
6-1-401	Appearance of Emissions	N	
SIP Regulation 6	Particulate Matter and Visible Emissions (9/4/98)		
6-301	Ringelmann 1 Limitation	Y	
6-305	Visible Particles	Y	
6-310	Particle Weight Limitation	Y	
6-311	General Operations	Y	
6-401	Appearance of Emissions	Y	
BAAQMD Condition #13093			
Part 1	Nickel & Nickel compounds limit in the material to be processed (basis: toxic risk screening analysis)	Y	
Part 2	Visible emissions limit requirement (basis: Regulation 1-301, 6-1-301, SIP Regulation 6-301)	Y	
Part 3	Abatement requirements (basis: TBACT, cumulative increase, permit condition ID# 13097, part 4)	Y	
Part 4	Material throughput limit (basis: cumulative increase)	Y	
Part 5	Record keeping (basis: cumulative increase)	Y	

IV. Source-specific Applicable Requirements

**Table IV - W
 Source-specific Applicable Requirements
 S601 - X3 FINES SURGE HOPPER**

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
BAAQMD Regulation 6, Rule 1	Particulate Matter , General Requirements (12/5/2007)		
6-1-301	Ringelmann 1 Limitation	N	
6-1-305	Visible Particles	N	
6-1-310	Particle Weight Limitation	N	
6-1-311	General Operations	N	
6-1-401	Appearance of Emissions	N	
SIP Regulation 6	Particulate Matter and Visible Emissions (9/4/98)		
6-301	Ringelmann 1 Limitation	Y	
6-305	Visible Particles	Y	
6-310	Particle Weight Limitation	Y	
6-311	General Operations	Y	
6-401	Appearance of Emissions	Y	
BAAQMD Condition #13094			
Part 1	Visible emission limit requirement (basis: Regulation 1-301, 6-1-301, SIP Regulation 6-301)	Y	
Part 2	Throughput limit requirement (basis: cumulative increase)	Y	
Part 3	Abatement requirement; A601 Baghouse good operating condition and device failure warning requirement (basis: Regulation 6-1-301, 6-1-310, 6-1-311; SIP Regulation 6-301, 6-310, 6-311, cumulative increase)	Y	
Part 4	A601 Baghouse air flow rate, and exhaust grain loading limits requirement (basis: cumulative increase)	Y	
Part 5	Record keeping requirement (basis: Regulation 2-6-501; cumulative increase)	Y	

IV. Source-specific Applicable Requirements

**Table IV - X
 Source-specific Applicable Requirements
 S602 - X3 ALUMINA SURGE HOPPER**

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
BAAQMD Regulation 6, Rule 1	Particulate Matter , General Requirements (12/5/2007)		
6-1-301	Ringelmann 1 Limitation	N	
6-1-305	Visible Particles	N	
6-1-310	Particle Weight Limitation	N	
6-1-311	General Operations	N	
6-1-401	Appearance of Emissions	N	
SIP Regulation 6	Particulate Matter and Visible Emissions (9/4/98)		
6-301	Ringelmann 1 Limitation	Y	
6-305	Visible Particles	Y	
6-310	Particle Weight Limitation	Y	
6-311	General Operations	Y	
6-401	Appearance of Emissions	Y	
BAAQMD Condition #13095			
Part 1	Visible emission limit requirement (basis: Regulation 1-301, 6-1-301, SIP Regulation 6-301)	Y	
Part 2	Throughput limit requirement (basis: cumulative increase)	Y	
Part 3	Abatement requirement; A602 Baghouse good operating condition and device failure warning requirement (basis: Regulation 6-1-301, 6-1-310, 6-1-311; SIP Regulation 6-301, 6-310, 6-311, cumulative increase)	Y	
Part 4	A602 Baghouse air flow rate, and exhaust grain loading limits requirement (basis: cumulative increase)	Y	
Part 5	Record keeping requirement (basis: Regulation 2-6-501; cumulative increase)	Y	

IV. Source-specific Applicable Requirements

**Table IV - Y
 Source-specific Applicable Requirements
 S603 - X3 EXTRUDER**

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
BAAQMD Regulation 6, Rule 1	Particulate Matter , General Requirements (12/5/2007)		
6-1-301	Ringelmann 1 Limitation	N	
6-1-305	Visible Particles	N	
6-1-310	Particle Weight Limitation	N	
6-1-311	General Operations	N	
6-1-401	Appearance of Emissions	N	
SIP Regulation 6	Particulate Matter and Visible Emissions (9/4/98)		
6-301	Ringelmann 1 Limitation	Y	
6-305	Visible Particles	Y	
6-310	Particle Weight Limitation	Y	
6-311	General Operations	Y	
6-401	Appearance of Emissions	Y	
BAAQMD Regulation 7	Odorous Substances (3/17/82)		
7-301	General limit	N	
7-302	Limit at or beyond property line	N	
7-303	Limit	N	
7-401	Collection of Samples	N	
7-402	Analysis of Samples	N	
7-403	Evaluation apparatus	N	
7-404	Evaluation Procedure	N	
7-405	Evaluation Analysis	N	
7-601	Collection of Samples	N	
7-602	Sampling Equipment and Techniques for Collection	N	
BAAQMD Condition #13096			
Part 1	Visible emission limit requirement (basis: Regulation 1-301, 6-1-301, SIP Regulation 6-301)	Y	
Part 2	Throughput limit requirement (basis: cumulative increase)	Y	

IV. Source-specific Applicable Requirements

**Table IV - Y
 Source-specific Applicable Requirements
 S603 - X3 EXTRUDER**

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
Part 3	Record keeping requirement (basis: Regulation 2-6-501; cumulative increase)	Y	
BAAQMD Condition #15672			
Part 5	NH3 daily and annual emission limits (basis: cumulative increase)	Y	
Part 11	Annual source test requirement (basis: BACT)	Y	

**Table IV - Z
 Source-specific Applicable Requirements
 S604 - X3 DRYER**

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
BAAQMD Regulation 6, Rule 1	Particulate Matter , General Requirements (12/5/2007)		
6-1-301	Ringelmann 1 Limitation	N	
6-1-305	Visible Particles	N	
6-1-310	Particle Weight Limitation	N	
6-1-311	General Operations	N	
6-1-401	Appearance of Emissions	N	
SIP Regulation 6	Particulate Matter and Visible Emissions (9/4/98)		
6-301	Ringelmann 1 Limitation	Y	
6-305	Visible Particles	Y	
6-310	Particle Weight Limitation	Y	
6-311	General Operations	Y	
6-401	Appearance of Emissions	Y	
BAAQMD Regulation 7	Odorous Substances (3/17/82)		
7-301	General limit	N	
7-302	Limit at or beyond property line	N	

IV. Source-specific Applicable Requirements

**Table IV - Z
 Source-specific Applicable Requirements
 S604 - X3 DRYER**

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
7-303	Limit	N	
7-401	Collection of Samples	N	
7-402	Analysis of Samples	N	
7-403	Evaluation apparatus	N	
7-404	Evaluation Procedure	N	
7-405	Evaluation Analysis	N	
7-601	Collection of Samples	N	
7-602	Sampling Equipment and Techniques for Collection	N	
BAAQMD Regulation 9, Rule 1	Inorganic Gaseous Pollutants, Sulfur Dioxide (3/15/95)		
9-1-301	Limitations on ground level concentrations	Y	
9-1-311	Emission Limitations for Catalyst Manufacturing Plants	Y	
9-1-311.2	SO2 Emission Limit	Y	
SIP Regulation 9, Rule 1	Inorganic Gaseous Pollutants, Sulfur Dioxide (6/8/99)		
9-1-301	Limitations on ground level concentrations	Y	
9-1-311	Emission Limitations for Catalyst Manufacturing Plants	Y	
9-1-311.2	SO2 Emission Limit	Y	
BAAQMD Condition #13097			
Part 1	Visible emission limit requirement (basis: Regulation 1-301, 6-1-301, SIP Regulation 6-301)	Y	
Part 2	Abatement requirement (basis: Regulation 6-1-301, 6-1-310, 6-1-311, SIP Regulation 6-301, 6-310, 6-311)	Y	
Part 3	A603 Baghouse good operating condition and pressure drop monitoring requirement (basis: Regulation 6-1-301, 6-1-310, 6-1-311, 2-1-403, SIP Regulation 6-301, 6-310, 6-311)	Y	
Part 4	A603 Baghouse air flow rate, and exhaust grain loading limits requirement (basis: cumulative increase)	Y	
Part 5	Natural gas fuel only, and usage limit (basis: cumulative increase)	Y	
Part 6	Fuel metering device requirement (basis: cumulative increase)	Y	
Part 7	Record keeping requirement (basis: Regulation 2-6-501; cumulative increase)	Y	

IV. Source-specific Applicable Requirements

**Table IV - Z
 Source-specific Applicable Requirements
 S604 - X3 DRYER**

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
BAAQMD Condition #15672			
Part 5	NH3 daily and annual emission limits (basis: cumulative increase)	Y	
Part 11	Annual source test requirement (basis: BACT)	Y	

**Table IV - AA
 Source-specific Applicable Requirements
 S606 - X3 CALCINER**

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
BAAQMD Regulation 6, Rule 1	Particulate Matter , General Requirements (12/5/2007)		
6-1-301	Ringelmann 1 Limitation	N	
6-1-305	Visible Particles	N	
6-1-310	Particle Weight Limitation	N	
6-1-311	General Operations	N	
6-1-401	Appearance of Emissions	N	
SIP Regulation 6	Particulate Matter and Visible Emissions (9/4/98)		
6-301	Ringelmann 1 Limitation	Y	
6-305	Visible Particles	Y	
6-310	Particle Weight Limitation	Y	
6-311	General Operations	Y	
6-401	Appearance of Emissions	Y	
BAAQMD Regulation 7	Odorous Substances (3/17/82)		
7-301	General limit	N	
7-302	Limit at or beyond property line	N	
7-303	Limit	N	
7-401	Collection of Samples	N	

IV. Source-specific Applicable Requirements

**Table IV - AA
 Source-specific Applicable Requirements
 S606 - X3 CALCINER**

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
7-402	Analysis of Samples	N	
7-403	Evaluation apparatus	N	
7-404	Evaluation Procedure	N	
7-405	Evaluation Analysis	N	
7-601	Collection of Samples	N	
7-602	Sampling Equipment and Techniques for Collection	N	
BAAQMD Regulation 9, Rule 1	Inorganic Gaseous Pollutants, Sulfur Dioxide (3/15/95)		
9-1-301	Limitations on ground level concentrations	Y	
9-1-311	Emission Limitations for Catalyst Manufacturing Plants	Y	
9-1-311.2	Hourly SO2 limit	Y	
SIP Regulation 9, Rule 1	Inorganic Gaseous Pollutants, Sulfur Dioxide (6/8/99)		
9-1-301	Limitations on ground level concentrations	Y	
9-1-311	Emission Limitations for Catalyst Manufacturing Plants	Y	
9-1-311.2	SO2 Emission Limit	Y	
BAAQMD Condition #15672			
Part 1	Visible emissions limit requirement (basis: Regulation 1-301, 6-1-301, SIP Regulation 6-301)	Y	
Part 2	Abatement requirement, and device failure warning requirement (basis: BACT)	Y	
Part 3	A604 Baghouse air flow rate and exhaust grain loading requirement (basis: BACT; cumulative increase)	Y	
Part 4	Fuel and fuel usage limits (basis: cumulative increase)	Y	
Part 5	NH3 daily and annual emission limits (basis: cumulative increase)	Y	
Part 6	NOx daily and annual emission limits (basis: cumulative increase)	Y	
Part 7	CO abatement requirement (basis: BACT)	Y	
Part 8	CO abatement efficiency requirement (basis: BACT; cumulative increase)	Y	
Part 9	CO annual emission limit (basis: BACT; cumulative increase)	Y	
Part 10	Nickel content limit in the material processed (basis: toxic risk screen;	Y	

IV. Source-specific Applicable Requirements

Table IV - AA
Source-specific Applicable Requirements
S606 - X3 CALCINER

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
	cumulative increase)		
Part 11	Annual source test requirement (basis: BACT)	Y	
Part 12	NOx and CO continuous emission monitoring (CEM) requirement (basis: BACT; cumulative increase)	Y	
Part 13	Fuel meter requirement (basis: cumulative increase)	Y	
Part 14	Fuel usage and nickel content record keeping requirement (basis: Regulation 2-6-501; cumulative increase)	Y	

V. SCHEDULE OF COMPLIANCE

The permit holder shall comply with all applicable requirements cited in this permit. The permit holder shall also comply with applicable requirements that become effective during the term of this permit on a timely basis.

VI. PERMIT CONDITIONS

Any condition that is preceded by an asterisk is not federally enforceable.

Condition # 3344

For S311, Alumina bulk bag unloader,
S312, Alumina repackaging station,
S313, Fines grinder feed hopper system, and
S323, Fines grinder feed hopper system (secondary)

1. The owner/operator shall ensure visible particulate emissions from each source, S311, S312, S313, and S323 shall not exceed Ringelmann 1.0 for more than 3 consecutive minutes in any hour or result in fallout on adjacent property in such quantities as to cause a public nuisance per Regulation 1-301. (basis: Regulation 1-301, 6-1-301, SIP Regulation 6-301)
2. The owner/operator shall not exceed the combined bulk throughput at source S311, Bulk Bag Unloader, and S312, Repackaging Station, of 12,480 tons during any consecutive twelve-month period. (basis: cumulative increase)
3. The owner/operator shall not exceed a total catalyst throughput at sources S313 and S323 of 4,380 tons during any consecutive twelve-month period. (basis: cumulative increase)
4. The owner/operator shall route all particulate emissions from S311 through S313, and S323 under negative pressure to specified Dust Collector A40. (basis: Regulation 6-1-301, 6-1-310, 6-1-311, SIP Regulation 6-301, 6-310, 6-311)
5. The owner/operator shall abate emissions from sources S311, S312, S313, and S323 by the properly maintained Dust Collector A40 at all times that S311, S312, S313, and S323 are in operation. A District approved bag failure warning device shall be installed and maintained on A40 (Dust Collector). (basis: Regulation 6-1-301, 6-1-310, 6-1-311, SIP Regulation 6-301, 6-310, 6-311)

VI. Permit Conditions

6. The outlet loading for Dust Collector A40 shall not exceed 0.005 grain/dscf. The airflow rate from A40 shall not exceed 2,900 scfm. (basis: cumulative increase)
7. The nickel content of the material processed in the grinder feed hoppers (S313 and S323) shall not exceed 7% by weight in any 24-hour averaging period. (basis: toxic risk screen)
8. In order to demonstrate compliance with the above conditions, the owner/operator shall maintain the following records on site, and made available for District inspection for a period of five years from the date on which a record was made.
 - a. The daily throughput of product at source S 311, S312, S313, and S323 summarized on a monthly basis.
 - b. Nickel content of materials processed at sources S313 and S323.
 - c. Total daily hours of operation, summarized on a monthly basis. (basis: Regulation 2-6-501; cumulative increase)

Condition # 8444

For S1, X1 Muller:

1. Visible particulate emissions from the area dust collector A4 shall not exceed Ringelmann 1.0 for more than 3 consecutive minutes in any hour or result in fallout on adjacent property in such quantities as to cause a public nuisance per Regulation 1-301. (basis: Regulation 1-301, 6-1-301, SIP Regulation 6-301)
2. The airflow rate from A4, dust collector, shall not exceed 1,116 SCFM. The outlet loading of the dust collector A4 shall not exceed 0.006 grains/dscf. (basis: cumulative increase)
3. Emission from source S1 shall be abated by the properly maintained Dust Collector A4 at all times that S1 is in operation. A district approved bag failure warning device must be in operation at all such times. (basis: Regulation 6-1-301, 6-1-310, 6-1-311; SIP Regulation 6-301, 6-310, 6-311, cumulative increase)

Condition # 8445

For S401, X2 Muller:

1. Visible particulate emissions from the area dust collector A48 shall not exceed Ringelmann 1.0 for more than 3 consecutive minutes in any hour or result in fallout

VI. Permit Conditions

on adjacent property in such quantities as to cause a public nuisance per Regulation 1-301. (basis: Regulation 1-301, 6-1-301, SIP Regulation 6-301)

2. The air flow rate from A48, dust collector, shall not exceed 1,116 SCFM. The outlet loading of the dust collector A48 shall not exceed 0.006 grains/dscf. (basis: cumulative increase)
3. Emission from source S401 shall be abated by the properly maintained Dust Collector A48 at all times that S401 is in operation. A district approved bag failure warning device must be in operation at all such times. (basis: Regulation 6-1-301, 6-1-310, 6-1-311; SIP Regulation 6-301, 6-310, 6-311, cumulative increase)

Condition # 8468

For S314 through S317, Reground fines storage silos,

S318, Fines weigh hopper blow pot,
S319, Fines bagout stations,
S320, Fines grinder, and
S322, Fines tanker truck delivery system

1. The owner/operator shall ensure visible particulate emissions from each source S314 through S320, and S322 shall not exceed Ringelmann 1.0 for more than 3 consecutive minutes in any hour or result in fallout on adjacent property in such quantities as to cause a public nuisance per Regulation 1-301. (basis: Regulation 1-301, 6-1-301, SIP Regulation 6-301)
2. The owner/operator shall not exceed the following material/catalyst throughput limits during any consecutive twelve month period.

S314 through S317: 4,380 tons,
S318: 4,380 tons,
S319: 4,380 tons,
S320 & S322: 4,380 tons
(basis: cumulative increase)
3. Only one silo among sources S314 through S317 shall be in active loading operation from source S313 at any one time. (basis: cumulative increase)
4. The owner/operator shall route all particulate emissions from sources S314 through S320, and S322 under negative pressure to specified Dust Collector A44, A45, A46, or A47. (basis: Regulation 6-1-301, 6-1-310, 6-1-311; SIP Regulation 6-301, 6-310, 6-311, cumulative increase, TBACT, toxic risk screen)

VI. Permit Conditions

5. The owner/operator shall abate emissions from sources S314 through S320, and S322 by the properly maintained Dust Collector A44, A45, A46 or A47 at all times that S314 through S320, and S322 are in operation. A District approved bag failure warning device shall be installed and maintained on A40 (Dust Collector). (basis: Regulation 6-1-301, 6-1-310, 6-1-311; SIP Regulation 6-301, 6-310, 6-311, cumulative increase, TBACT, toxic risk screen)
6. The outlet loading for Dust Collector A44, A45, A46 and A47 shall not exceed 0.005 grain/dscf. The air flow rate from A44, A45, A46 and A47 shall not exceed 3,000 scfm from each unit. (basis: cumulative increase, TBACT, toxic risk screen)
7. The nickel content of the materials processed by the handling and grinding equipment (S314 through S320, and S322) shall not exceed 7% by weight in any hour.
(basis: toxic risk screen)
8. In order to demonstrate compliance with the above conditions, the owner/operator shall maintain the following records on site and made available for District inspection for a period of five years from the date on which a record was made.
 - a. The daily throughput of product at sources S 318, S319, S320, and S322 summarized on a monthly basis.
 - b. Total daily hours of operation, summarized on a monthly basis.
(basis: Regulation 2-6-501; cumulative increase)

Condition # 9315

For S504 through S506, H2 Blending tanks,
S507, H2 Liquid/solids blender,
S509, HSA kiln feed conveyor,
S510, H2 Kiln, and
S514, H2 Kiln Bypass Chute & Hopper w/dusthood:

1. The owner/operator shall not process or handle materials, which contain more than 10% of nickel or nickel compounds by weight averaged over any consecutive 12-month period. (basis: Toxic risk screening analysis)
2. The owner/operator shall not exceed a combined total material throughput limit of 52 ton per day at S510 and S514. (basis: cumulative increase)
3. The owner/operator shall not exceed visible particulate emissions from the area dust collector A54 of Ringelmann 1.0 for a period or periods aggregating more than three minutes in any hour, or result in fallout on adjacent property in such quantities as to cause a public nuisance per Regulation 1-301. (basis: Regulation 1-301, 6-1-301, SIP Regulation 6-301)

VI. Permit Conditions

4. The owner/operator shall not exceed the air flow rate from A54, dust collector of 7,500 SCFM. The outlet loading of the dust collector A54 shall not exceed 0.006 grain/dscf. (basis: TBACT; cumulative increase)
5. The owner/operator shall abate emissions from sources S504 through S507, S509, S510, and S514 by the properly maintained dust collector, A54, at all times that any of the sources S504 through S507, S509, S510, and S514 is in operation. A District approved bag failure warning device must be in operation at all such times. (basis: Regulation 6-1-301, 6-1-310, 6-1-311; SIP Regulation 6-301, 6-310, 6-311, cumulative increase)
6. The owner/operator of afterburner, A56, shall maintain the afterburner in proper operating condition, including a dedicated fuel meter. (basis: cumulative increase)
7. The owner/operator of afterburner, A56, shall burn only natural gas, and shall have a District approved temperature monitor. (basis: cumulative increase)
8. The CO contribution from A56 shall not exceed 400 ppmv dry at 3% oxygen. (basis: cumulative increase)
9. When the afterburner, A56, is being used to abate emissions from S504 through S507, S509, S510, and S514, the owner/operator shall operate the afterburner, A56, at a minimum operating temperature of 1400 degree Fahrenheit and a minimum residence time of 0.4 second. (basis: cumulative increase)
10. The owner/operator shall operate S504 through S507, S509, S510, and S514 so that the following emission limits are not exceeded:
 - a. NO_x 120 lb/day
 - b. NH₃ 2,200 lb/day

Whenever the total ammonia input, calculated as equivalent NH₃, to sources S504, through S507, S509, S510, and S514 exceeds 2,200 lb/day, the owner/operator shall abate sources S 504, through S507, S509, S510, and S514 by the afterburner, A56. When the afterburner A56 is in operation, the emissions from A56 shall not exceed the following limits:

NO_x = 120 lb/day

NH₃ = 200 lb/day

A day shall be defined as an operating day of 24 hours from midnight to midnight. A year shall be defined as any consecutive 12 month period. (basis: cumulative increase)

11. Notwithstanding the terms of part 10, the operation of the afterburner A56 may be

VI. Permit Conditions

waived for a particular catalyst product and ammonia input if the owner/operator demonstrates through a District approved source test(s) representative of that catalyst product and ammonia input, that the ammonia emissions from sources S504 through S507, S509, S510, and S514 do not exceed 2,200 lb/day. (basis: cumulative increase)

12. The owner/operator shall not exceed visible particulate emissions from A56 of Ringelmann 1.0 for a period or periods aggregating more than three minutes in any hour, or result in fallout on adjacent property in such quantities as to cause public nuisance per Regulation 1-301. (basis: Regulation 6-1-301, 1-301, SIP Regulation 6-301)
13. The owner/operator of A56 shall conduct a District approved source test annually with the after burner abatement device in operation and not in operation to demonstrate a net reduction of NH₃ emissions from uncontrolled levels per operating day, and to demonstrate compliance with parts 8, 10, and 11. At a minimum, the following emissions will be measured (ppm, lb/hr, lb/day): NO_x, NH₃, O₂, CO, and non-methane hydrocarbons.

The source tests shall be conducted on representative materials processed at S504 through S507, S509, S510, and S514 with representatively high NH₃ emissions and representatively high NO_x emissions to demonstrate compliance with parts 8, 10, and 11. The test results shall be reported to the District within 30 days of completion of the test.

The owner/operator of A56 shall conduct the source tests annually with no more than 12 months between tests. Furthermore, the District may require at its discretion the owner/operator to conduct up to an additional two source tests annually to demonstrate continuing compliance with parts 8, 10, and 11. (basis: cumulative increase)

VI. Permit Conditions

14. To demonstrate compliance with the above parts, the owner/operator shall maintain the following records in a District approved log and made available for District inspection for at least five years from the date on which a record was made.
 - a. The natural gas usage of A56, totaled on a monthly basis
 - b. The days of operation and type of material processed, daily throughput of each material and daily input of ammonia, calculated as equivalent NH₃ at the Calciner Oven, S510, totaled on a monthly basis, as necessary to verify compliance with the emission limits of parts 10 and 11 using the emission factors generated in the source tests of part 13.
 - c. All source tests results conducted for compliance with parts 8, 10, and 11. (basis: cumulative increase)

Condition # 9984

For sources S104, S105 and S106, Mixing Tanks:

1. Visible particulate emissions from the H-1 Baghouse, A49, shall not reach nor exceed Ringelmann 1.0 for a period or periods aggregating more than three consecutive minutes in any hour, or result in fallout on adjacent property in such quantities as to cause a public nuisance per Regulation 1-301. (basis: Regulation 6-1-301, 1-301, SIP Regulation 6-301)
2. The air flow rate from A49, H-1 Baghouse, shall not exceed 3,500 SCFM. The outlet loading of the dust collector A49 shall not exceed 0.006 grains/dscf. (basis: cumulative increase)
3. Emissions from sources S104, S105 and S106 shall be abated by the properly maintained H-1 Baghouse, A49, at all times that S104, S105 and/or S106, respectively, are in operation. A district approved bag failure warning device must be in operation at all such times. (basis: Regulation 6-1-301, 6-1-310, 6-1-311; SIP Regulation 6-301, 6-310, 6-311, cumulative increase)

VI. Permit Conditions

Condition # 13092

For source S321, Alumina Storage Silo abated by A50 baghouse (A/N 14899):

1. Visible particulate emissions from source S321 shall not exceed Ringelmann 1.0 for more than 3 consecutive minutes in any hour or result in fallout on adjacent property in such quantities as to cause a public nuisance per Regulation 1-301. (basis: Regulation 6-1-301, 1-301, SIP Regulation 6-301)
2. The Alumina through put at source S321 shall not exceed 9,636 tons (dry basis) during any consecutive twelve month period. (basis: cumulative increase)
3. Emissions from source S321 shall be abated by the properly maintained baghouse A50 at all times that S321 is in operation. A District approved bag failure warning device shall be installed and maintained on A50. (basis: Regulation 6-1-301, 6-1-310, 6-1-311; SIP Regulation 6-301, 6-310, 6-311, cumulative increase)
4. The outlet loading for baghouse A50 shall not exceed 0.006 grain/dscf. The air flow rate from A50 shall not exceed 150 dscfm. (basis: cumulative increase)
5. In order to demonstrate compliance with the above conditions, the following records shall be kept on site and made available for District inspection for a period of five years from the date on which a record was made.
 - a. The daily throughput of Alumina at source S 321, summarized on a monthly basis.
 - b. Total daily hours of operation, summarized on a monthly basis. (basis: Regulation 2-6-501; cumulative increase)

Condition # 13093

For source S600, X-3 Extrudate Screener, Conveyors, and Fugitive emissions (A/N 14899):

(Revisions: A# 7774; A# 17565)

1. The owner/operator shall not process or handle materials which contain more than 0.84% of nickel or nickel compounds by weight averaged over any consecutive 12-month period. (basis: Toxic risk screening analysis)
2. The owner/operator shall not exceed visible particulate emissions from source S-600 of Ringelmann 1.0 for more than 3 consecutive minutes in any hour or result in fallout on adjacent property in such quantities as to cause a public nuisance per Regulation 6-1-301. (basis: Regulation 6-1-301, SIP Regulation 6-301)
3. The owner/operator shall abate particulate emissions from S-600 by the dust collector,

VI. Permit Conditions

A-607, at all times of operation. The exhaust from A-607 shall always be routed to the baghouse, A-603, via the calciner, S-606 (shell side) and the dryer, S-604. The particulate loading of the exhaust from the baghouse, A-603, shall not exceed 0.006 gr/dscf. The exhaust flow rate from A-603 shall not exceed 12,000 dscfm. (basis: TBACT; cumulative increase; permit condition ID # 13097, part 4).

4. The owner/operator shall not exceed a total material throughput limit of 36 ton per day. (basis: cumulative increase)
5. The owner/operator shall maintain records of daily material throughput, and calculations for nickel/nickel compounds concentration to demonstrate compliance with conditions 1 & 4 in a District approved logbook. These records shall be kept on site for a period of five years from the date of data entry and be made available to the District staff for inspection. (basis: cumulative increase)

Condition # 13094

For source S601, X-3 Fines Surge Hopper abated by A601 baghouse (A/N 14899):

1. Visible particulate emissions from source S601 shall not exceed Ringelmann 1.0 for more than 3 consecutive minutes in any hour or result in fallout on adjacent property in such quantities as to cause a public nuisance per Regulation 1-301. (basis: Regulation 6-1-301, 1-301, SIP Regulation 6-301)
2. The catalyst throughput at source S601 shall not exceed 1,400 tons (dry basis) during any consecutive twelve month period. (basis: cumulative increase)
3. Emissions from source S601 shall be abated by the properly maintained baghouse A601 at all times that S601 is in operation. A District approved bag failure warning device shall be installed and maintained on A601. (basis: Regulation 6-1-301, 6-1-310, 6-1-311; SIP Regulation 6-301, 6-310, 6-311, cumulative increase)
4. The outlet loading for baghouse A601 shall not exceed 0.006 grain/dscf. The air flow rate from A601 shall not exceed 100 dscfm. (basis: cumulative increase)
5. In order to demonstrate compliance with the above conditions, the following records shall be kept on site and made available for District inspection for a period of five years from the date on which a record was made.
 - a. The daily throughput of product at source S 601, summarized on a monthly basis.
 - b. Total daily hours of operation, summarized on a monthly basis. (basis: Regulation 2-6-501; cumulative increase)

VI. Permit Conditions

Condition # 13095

For source S602, X-3 Alumina Surge
Hopper abated by A602 dust collector (A/N 14899):

1. Visible particulate emissions from source S602 shall not exceed Ringelmann 1.0 for more than 3 consecutive minutes in any hour or result in fallout on adjacent property in such quantities as to cause a public nuisance per Regulation 1-301. (basis: Regulation 1-301, 6-1-301, SIP Regulation 6-301)
2. The Alumina through put at source S602 shall not exceed 9636 tons (dry basis) during any consecutive twelve month period. (basis: cumulative increase)
3. Emissions from source S602 shall be abated by the properly maintained baghouse A602 at all times that S602 is in operation. A District approved bag failure warning device shall be installed and maintained on A602. (basis: Regulation 6-1-301, 6-1-310, 6-1-311; SIP Regulation 6-301, 6-310, 6-311, cumulative increase)
4. The outlet loading for baghouse A602 shall not exceed 0.006 grain/dscf. The air flow rate from A602 shall not exceed 200 dscfm. (basis: cumulative increase)
5. In order to demonstrate compliance with the above conditions, the following records shall be kept on site and made available for District inspection for a period of five years from the date on which a record was made.
 - a. The daily throughput of Alumina at source S 602, summarized on a monthly basis.
 - b. Total daily hours of operation, summarized on a monthly basis. (basis: Regulation 2-6-501; cumulative increase)

Condition # 13096

For source S603, X-3 Extruder (A/N 14899):

1. Visible particulate emissions from source S603 shall not reach nor exceed Ringelmann 1.0 for more than 3 consecutive minutes in any hour or result in fallout on adjacent property in such quantities as to cause a public nuisance per Regulation 1-301. (basis: Regulation 1-301, 6-1-301, SIP Regulation 6-301)
2. The combined throughput at source S603 shall not exceed 31,665 tons (wet basis) during any consecutive twelve month period. (basis: cumulative increase)
3. In order to demonstrate compliance with the above conditions, the following records shall be kept on site and made available for District inspection for a period of five years from the date on which a record was made.

VI. Permit Conditions

- a. The daily throughput of product at source S 603, summarized on a monthly basis.
- b. Total daily hours of operation, summarized on a monthly basis. (basis: Regulation 2-6-501; cumulative increase)

Condition # 13097

For source S604, X-3 Dryer abated by A603 baghouse (A/N 14899):

1. Visible particulate emissions from source S604 shall not exceed Ringelmann 1.0 for more than 3 consecutive minutes in any hour or result in fallout on adjacent property in such quantities as to cause a public nuisance per Regulation 1-301. (basis: Regulation 1-301, 6-1-301, SIP Regulation 6-301)
2. All particulate matter emissions from this source (S604) shall be routed to the Baghouse (A 603). (basis: Regulation 6-1-301, 6-1-310, 6-1-311, SIP Regulation 6-301, 6-310, 6-311)
3. Baghouse (A603) shall be properly maintained and kept in good operating condition at all times. Baghouse (A603) shall be equipped with a device for measuring the pressure drop across the baghouse. (basis: Regulation 6-1-301, 6-1-310, 6-1-311, 2-1-403, SIP Regulation 6-301, 6-310, 6-311)
4. The outlet loading for baghouse A603 shall not exceed 0.006 grain/dscf. The air flow rate from A603 shall not exceed 12,000 dscfm. (basis: Cumulative Increase)
5. The total combined fuel usage at source S604 shall not exceed 534,360 therms in any consecutive 12 month period. Only natural gas shall be burned at S604. (basis: Cumulative Increase)
6. The owner/operator shall install and maintain a non-resettable totalizing fuel meter for natural gas, unless the owner/operator applies for and receives written approval from the District to use an alternate method for measuring the cumulative annual fuel usage. (basis: Cumulative Increase)
7. In order to demonstrate compliance with the above conditions, the owner/operator shall keep records of the natural gas usage of S604, totaled on a monthly basis. Records shall be kept on site and made available for District inspection for a period of five years from the date on which a record was made. (basis: Regulation 2-6-501; Cumulative Increase)

VI. Permit Conditions

Condition # 13099

For sources S2 (X-1) and S407 (X-2)

Dryers, abated by A6 and A57 baghouses, respectively
(A/N 14899):

1. Visible particulate emissions from each source, S2 or S407, shall not exceed Ringelmann 1.0 for more than 3 consecutive minutes in any hour or result in fallout on adjacent property in such quantities as to cause a public nuisance per Regulation 1-301. (basis: Regulation 1-301, 6-1-301, SIP Regulation 6-301)
2. Emissions from source S2 or S407, shall be abated by the properly maintained baghouses A-6 or A-57, respectively, at all times that S2 or S407 are in operation. A District approved bag failure warning device shall be installed and maintained on A-6 and A-57 baghouses. (basis: Regulation 6-1-301, 6-1-310, 6-1-311; SIP Regulation 6-301, 6-310, 6-311, cumulative increase)
3. The outlet loading for baghouses A-6 or A-57 shall not exceed 0.006 grain/dscf each. The air flow rate from A-6 or A-57 shall not exceed 8,000 dscfm each. (basis: cumulative increase)

Condition # 13100

Permit conditions for Sources S7 (X-1 Kiln) and S413(X-2 Kiln) abated by A-2 and A-43 baghouses, respectively. S7 and S413 are also abated by A-58 Selective Catalyst Reduction System (A/N 14899):

1. Visible particulate emissions from each source S7 or S413 shall not exceed Ringelmann 1.0 for more than 3 consecutive minutes in any hour or result in fallout on adjacent property in such quantities as to cause a public nuisance per Regulation 1-301. (basis: Regulation 1-301, 6-1-301, SIP Regulation 6-301)
2. Emissions from source S7 or S413 shall be abated by the properly maintained baghouse A-2 and A-43, respectively, and SCR A-58 at all times that S7 or S413 is in operation. A District approved bag failure warning device shall be installed and maintained on A-2 and A-43 baghouses. (basis: Regulation 6-1-301, 6-1-310, 6-1-311, SIP Regulation 6-301, 6-310, 6-311)
3. The outlet loading for baghouse A-2 and/or A-43 shall not exceed 0.006 grain/dscf each. The air flow rate from A-2 and A-43 shall not exceed 8,000 dscfm, combined. (basis: cumulative increase)

VI. Permit Conditions

4. The total combined fuel usage at source S7 shall not exceed 700,000 therms in any consecutive 12 month period. Only natural gas shall be burned at S7. (basis: cumulative increase)
5. The total combined fuel usage at source S413 shall not exceed 700,000 therms in any consecutive 12 month period. Only natural gas shall be burned at S413. (basis: cumulative increase)
6. The NO_x emissions from sources S7 and S413 through P-43 shall not exceed: 58 lb/day or 21,000 lb/yr. A day shall be defined as an operating day of 24 hours from midnight to midnight. A year shall be defined as any consecutive 12 month period. (basis: cumulative increase)
7. The plant shall conduct a District approved source test on the dust collector to demonstrate compliance with the 0.006 grain/dscf or less outlet grain loading, as specified in part 3. The source test shall be conducted with source S7 and/or S413, X-1 and/or X-2 Kilns operating at or near their full rated capacity of 1,680 lb/hr. (basis: cumulative increase)
8. To demonstrate compliance with parts 6 and 7, the owner/operator of S7, S413, A-2, A-43 and A-58 shall install and maintain a District approved continuous emission monitor (CEM) for NO_x. (basis: cumulative increase)
9. The owner/operator of S7 and S413 shall install and maintain non-resettable totalizing fuel meters for natural gas for each source, unless the owner/operator applies for and receives written approval from the District to use an alternate method for measuring the cumulative annual fuel usage. (basis: cumulative increase)
10. In order to demonstrate compliance with the above conditions, the following records shall be kept on site and made available for District inspection for a period of five years from the date on which a record was made.
 - a. The natural gas usage of S7 and S413, totaled on a monthly basis (basis: Regulation 2-6-501, cumulative increase)

Condition # 13138

For S111 through S114, Product Packaging Operation
(A/N 25609):

1. Visible particulate emissions from the Baghouse, A-14, shall not exceed Ringelmann 1.0 for more than 3 consecutive minutes in any hour, or result in fallout on adjacent property in such quantities as to cause a public nuisance per Regulation 1-301. (basis: Regulation 1-301, 6-1-301, SIP Regulation 6-301)

VI. Permit Conditions

2. The outlet loading of the dust collector A-14 shall not exceed 0.006 grains/dscf and the total particulate emissions from the collector shall not exceed 0.390 pounds per hour. (basis: cumulative increase)
3. Emissions from sources S111, S112, S113 and S114 shall be abated by the properly maintained Baghouse, A-14, at all times that S111 through S114 are in operation. A district approved bag failure warning device must be in operation at all such times. (basis: Regulation 6-1-301, 6-1-310; , SIP Regulation 6-301, 6-310, cumulative increase)

Condition # 15672

For Source S606 (X-3 Calciner)
abated by A-604 baghouse, A-605 Selective Catalyst
Reduction System, And A-606 CO Catalyst A/N 18507:
(Revision: A# 17565, 22820, 22844)

1. The owner/operator shall not exceed visible particulate emissions from source S606 of Ringelmann 1.0 for more than 3 consecutive minutes in any hour or result in fallout on adjacent property in such quantities as to cause a public nuisance per Regulation 1-301. (basis: Regulation 1-301, 6-1-301, SIP Regulation 6-301)
2. The owner/operator shall abate emissions from source S606 by the properly maintained baghouse A-604 and SCR A-605 at all times that S606 is in operation. A District approved bag failure warning device shall be installed and maintained on A-604 baghouse.(basis: BACT)
3. The owner/operator shall ensure that the particulate loading of the exhaust from the baghouse A-604 shall not exceed 0.006 grain/dscf. The air flow rate from A-604 shall not exceed 1,736 dscfm. (basis: BACT; cumulative increase)
4. The owner/operator shall not exceed a total combined fuel usage at source S606 of 700,000 therms in any consecutive 12 month period. Only natural gas shall be burned at S606. (basis: Cumulative Increase)
5. The owner/operator shall not exceed the following ammonia emission limits from sources S603, S604 and S606 through P-603:

NH₃ = 490 lb/day or 48,000 lb/yr.

A day shall be defined as an operating day of 24 hours from midnight to midnight. A year shall be defined as any consecutive 12 month period. (basis: Cumulative Increase)

VI. Permit Conditions

6. The owner/operator shall not exceed the following NO_x emission limits from S606 (Calciner) :

NO_x = 51 lb/day or 18,500 lb/yr.

A day shall be defined as an operating day of 24 hours from midnight to midnight. A year shall be defined as any consecutive 12 month period. (basis: Cumulative Increase)

7. The owner/operator shall abate CO emissions from the X3 Calciner S606, with the CO Catalytic Oxidizer, A606, at all times the Calciner, S606, is in operation. (basis: BACT)

8. The owner/operator shall maintain the percent CO abatement efficiency of the CO Catalyst Oxidizer, A-606, of at least 90% on a mass basis, whenever the CO concentration at the A606 outlet is greater than 40 ppmv. Any indicated excess will be considered to have occurred if the average abatement efficiency over any continuous 8-hour average (15 - minutes interval readings) falls below 90% on a mass basis and the CO concentration exceeds 40 ppmv (15 – minutes interval readings).

(basis: BACT; cumulative increase)

8. The owner/operator shall not exceed the following CO emission limit from S606 (Calciner):

CO = 19,524 lb/yr.
(basis: Cumulative Increase; BACT)

10. The owner/operator shall not exceed the nickel content of an average of 0.84% by weight in the materials processed in S603, S604 and S606 during any consecutive twelvemonth period. (basis: toxic risk screen; Cumulative Increase)

11. The owner/operator of S603 through S606 shall conduct source tests annually with baghouses A-603, A-604 and SCR A-605 in operation to determine compliance with part 5, with no more than 12 months between tests. Furthermore, at the District's discretion, the District may require the owner/operator to conduct up to an additional two source tests annually to determine continuing compliance with part 5. (basis: BACT)

12. To demonstrate compliance with parts 6, 8 and 9, the owner/operator of S606 shall install and maintain District approved continuous emission monitors (CEM) for NO_x and CO. An alternative to a continuous emission monitor for CO may be used to demonstrate compliance with Condition 8 and 9, upon written approval by the District. (basis: Cumulative Increase; BACT)

VI. Permit Conditions

13. The owner/operator shall install and maintain a non-re settable totalizing fuel meter for natural gas, unless the owner/operator applies for and receives written approval from the District to use an alternate method for measuring the cumulative annual fuel usage. (basis: Cumulative Increase)
14. In order to demonstrate compliance with the above conditions, the following records shall be kept onsite and made available for District inspection for a period of five years from the date on which are cord was made.
 - a. The natural gas usage of S606, totaled on a monthly basis
 - b. The nickel weight percent of each material processed in S603, S604 and S606. The weight average shall be calculated on a monthly basis.
(basis: Regulation 2-6-501; Cumulative Increase)

Condition # 16736

For S11, S19, S417, S418, S515,
S516, S517, S518, S519, and S520:

1. The material throughput at these sources shall not exceed the following limits per consecutive 365 day period.
 - S11 : 11,000 tons;
 - S19 : 3,667 tons;
 - S417 : 12,000 tons;
 - S418 : 12,000 tons;
 - S515 : 1,700 tons;
 - S516 : 3,300 tons;
 - S517 : 16,000 tons;
 - S518 : 16,000 tons;
 - S519 : 16,000 tons.
 - S520 : 16,000 tons(basis: cumulative increase)
2. The total particulate grain loading of exhaust from the baghouse, A-23, shall not exceed 0.01 gr/dscf. This limit will be revised after reviewing the source test results as required per condition #4 below. (basis: TBACT; Toxic risk screen)
3. Visible particulate emissions from the baghouses, A-3, A-22, A-23, A-42, A-52, A-53, and A-55 shall not exceed Ringelmann 1.0 for more than 3 consecutive minutes in any hour or result in fallout on adjacent property in such quantities as to cause public nuisance. (basis: Regulation 1-301, 6-1-301, SIP Regulation 6-301)
4. In order to demonstrate compliance with part #1, the owner/operator of these sources shall keep daily records of material throughput in a District approved logbook. The

VI. Permit Conditions

records shall be kept on-site for at least five years from the date of data entry, and shall be made available to the District staff for inspection. (basis: cumulative increase)

VII. APPLICABLE LIMITS & COMPLIANCE MONITORING REQUIREMENTS

This section has been included only to summarize the applicable emission limits contained in Section IV, Source-Specific Applicable Requirements, of this permit. The following tables show the relationship between each emission limit and the associated compliance monitoring provisions, if any. The monitoring frequency column indicates whether periodic (P) or continuous (C) monitoring is required. For periodic monitoring, the frequency of the monitoring has also been shown, using the following codes: annual (A), quarterly (Q), monthly (M), weekly (W), daily (D), or on an event basis (E). No monitoring (N) has been required if the current applicable rule or regulation does not require monitoring, and the operation is unlikely to deviate from the applicable emission limit based upon the nature of the operation.

This section is only a summary of the limits and monitoring requirements. In the case of a conflict with any requirement in Sections I-VI, the preceding sections take precedence over Section VII.

Table VII - A
Applicable Limits and Compliance Monitoring Requirements
S1 - X1 MULLER

Type of Limit	Citation of Limit	FE Y/N	Future Effective Date	Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
Opacity	BAAQMD 6-1-301	N		Ringelmann 1.0 for ≤ 3 minutes/hr	BAAQMD condition #8444, part 3	C	Bag failure warning device
Opacity	SIP 6-301	Y		Ringelmann 1.0 for ≤ 3 minutes/hr	BAAQMD condition #8444, part 3	C	Bag failure warning device
	BAAQMD condition #8444, part 1	Y		Ringelmann 0.5	BAAQMD condition #8444, part 3	C	Bag failure warning device
FP	BAAQMD 6-1-310	N		0.15 gr/dscf	BAAQMD condition #8444, part 3	C	Bag failure warning device
	BAAQMD 6-1-311	N		$4.10P^{0.67}$ lb/hr, where P is process weight, ton/hr		N	None

VII. Applicable Limits and Compliance Monitoring Requirements

**Table VII - A
 Applicable Limits and Compliance Monitoring Requirements
 S1 - X1 MULLER**

Type of Limit	Citation of Limit	FE Y/N	Future Effective Date	Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
FP	SIP 6-310	Y		0.15 gr/dscf	BAAQMD condition #8444, part 3	C	Bag failure warning device
	SIP 6-311	Y		4.10P ^{0.67} lb/hr, where P is process weight, ton/hr		N	None
	BAAQMD condition #8444, part 2	Y		0.006 gr/dscf	BAAQMD condition #8444, part 3	C	Bag failure warning device
Air flow rate	BAAQMD condition 8444, part 2	Y		1,116 scfm	None	N	None

**Table VII - B
 Applicable Limits and Compliance Monitoring Requirements
 S2 - X1 DRYER
 S407 – X2 DRYER**

Type of Limit	Citation of Limit	FE Y/N	Future Effective Date	Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
Opacity	BAAQMD 6-1-301	N		Ringelmann 1.0 for ≤ 3 minutes/hr	BAAQMD condition #13099, part 2	C	Bag failure warning device
Opacity	SIP 6-301	Y		Ringelmann 1.0 for ≤ 3 minutes/hr	BAAQMD condition #13099, part 2	C	Bag failure warning device
	BAAQMD condition #13099, part 1	Y		Ringelmann 0.5	BAAQMD condition #13099, part 2	C	Bag failure warning device

VII. Applicable Limits and Compliance Monitoring Requirements

**Table VII - B
 Applicable Limits and Compliance Monitoring Requirements
 S2 - X1 DRYER
 S407 – X2 DRYER**

Type of Limit	Citation of Limit	FE Y/N	Future Effective Date	Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
FP	BAAQMD 6-1-310	N		0.15 gr/dscf	BAAQMD condition #13099, part 2	C	Bag failure warning device
	BAAQMD 6-1-311	N		$4.10P^{0.67}$ lb/hr, where P is process weight, ton/hr		N	None
FP	SIP 6-310	Y		0.15 gr/dscf	BAAQMD condition #13099, part 2	C	Bag failure warning device
	SIP 6-311	Y		$4.10P^{0.67}$ lb/hr, where P is process weight, ton/hr		N	None
	BAAQMD condition #13099, part 3	Y		0.006 gr/dscf	BAAQMD condition #13099, part 2	C	Bag failure warning device
Air flow rate	BAAQMD condition 13099, part 3	Y		8,000 scfm	None	N	None
SO2	BAAQMD 9-1-301	N		GLC of 0.5 ppm for 3 min. or 0.25 ppm for 60 min. or 0.05 ppm for 24 hours	None	N	None
	BAAQMD 9-1-311.2	N		50 lbs/hr	None	N	None
SO2	SIP 9-1-301	Y		GLC of 0.5 ppm for 3 min. or 0.25 ppm for 60 min. or 0.05 ppm for 24 hours	None	N	None
	SIP 9-1-311.2	Y		50 lbs/hr	None	N	None

VII. Applicable Limits and Compliance Monitoring Requirements

Table VII - C
Applicable Limits and Compliance Monitoring Requirements
S3 - X1 DRIED PRODUCT ELEVATOR
S4 – X1 DRIED PRODUCT SCREENER
S5 – X1 LONG BREAKER
S6 – X1 KILN FEED CONVEYOR SYSTEM
S8 – X1 CALCINED PRODUCT ELEVATOR
S9 – X1 CALCINED PRODUCT SCREENER
S10 – X1 CALCINED PRODUCT PACKAGING

Type of Limit	Citation of Limit	FE Y/N	Future Effective Date	Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
Opacity	BAAQMD 6-1-301	N		Ringelmann 1.0 for ≤ 3 minutes/hr	None	N	None
Opacity	SIP 6-301	Y		Ringelmann 1.0 for ≤ 3 minutes/hr	None	N	None
FP	BAAQMD 6-1-310	N		0.15 gr/dscf	None	N	None
	BAAQMD 6-1-311	N		4.10P ^{0.67} lb/hr, where P is process weight, ton/hr	None	N	None
FP	SIP 6-310	Y		0.15 gr/dscf	None	N	None
	SIP 6-311	Y		4.10P ^{0.67} lb/hr, where P is process weight, ton/hr	None	N	None

Table VII - D
Applicable Limits and Compliance Monitoring Requirements
S7 - X1 KILN
S413 – X2 KILN

Type of Limit	Citation of Limit	FE Y/N	Future Effective Date	Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
Opacity	BAAQMD 6-1-301	N		Ringelmann 1.0 for ≤ 3 minutes/hr	BAAQMD condition #13100, part 2	C	Bag failure warning device

VII. Applicable Limits and Compliance Monitoring Requirements

**Table VII - D
 Applicable Limits and Compliance Monitoring Requirements
 S7 - X1 KILN
 S413 – X2 KILN**

Type of Limit	Citation of Limit	FE Y/N	Future Effective Date	Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
Opacity	SIP 6-301	Y		Ringelmann 1.0 for ≤ 3 minutes/hr	BAAQMD condition #13100, part 2	C	Bag failure warning device
FP	BAAQMD 6-1-310	Y		0.15 gr/dscf	BAAQMD condition #13100, part 2	C	Bag failure warning device
	BAAQMD 6-1-311	Y		4.10P ^{0.67} lb/hr, where P is process weight, ton/hr	None	N	None
FP	SIP 6-310	Y		0.15 gr/dscf	BAAQMD condition #13100, part 2	C	Bag failure warning device
	SIP 6-311	Y		4.10P ^{0.67} lb/hr, where P is process weight, ton/hr	None	N	None
FP	BAAQMD condition #13100, part 3	Y		0.006 gr/dscf	BAAQMD condition #13100, part 2	C	Bag failure warning device
Air flow rate	BAAQMD condition #13100, part 3	Y		8,000 scfm	None	N	None
NOx	BAAQMD condition #13100, part 6	Y		58 lb/day or 21,000 lb/yr	BAAQMD condition #13100, part 8	C	CEM
Natural gas	BAAQMD condition #13100, part 4	Y		700,000 therms at S7	BAAQMD condition #13100, part 9 & 10	C	Fuel meter, record keeping

VII. Applicable Limits and Compliance Monitoring Requirements

**Table VII - D
 Applicable Limits and Compliance Monitoring Requirements
 S7 - X1 KILN
 S413 – X2 KILN**

Type of Limit	Citation of Limit	FE Y/N	Future Effective Date	Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
	BAAQMD condition #13100, part 5	Y		700,000 therms at S413	BAAQMD condition #13100, part 9 & 10	C	Fuel meter, record keeping
SO2	BAAQMD 9-1-301	N		GLC of 0.5 ppm for 3 min. or 0.25 ppm for 60 min. or 0.05 ppm for 24 hours	None	N	None
	BAAQMD 9-1-311.2	N		50 lbs/hr	None	N	None
SO2	SIP 9-1-301	Y		GLC of 0.5 ppm for 3 min. or 0.25 ppm for 60 min. or 0.05 ppm for 24 hours	None	N	None
	SIP 9-1-311.2	Y		50 lbs/hr	None	N	None

**Table VII - E
 Applicable Limits and Compliance Monitoring Requirements
 S11 - X1 CALCINED PRODUCT CONVEYOR**

Type of Limit	Citation of Limit	FE Y/N	Future Effective Date	Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
Opacity	BAAQMD 6-1-301, Condition # 16736, part 5	N		Ringelmann 1.0 for ≤ 3 minutes/hr	None	N	None

VII. Applicable Limits and Compliance Monitoring Requirements

**Table VII - E
 Applicable Limits and Compliance Monitoring Requirements
 S11 - X1 CALCINED PRODUCT CONVEYOR**

Type of Limit	Citation of Limit	FE Y/N	Future Effective Date	Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
Opacity	BAAQMD 6-301, Condition # 16736, part 5	Y		Ringelmann 1.0 for ≤ 3 minutes/hr	None	N	None
FP	BAAQMD 6-1-310	N		0.15 gr/dscf	None	N	None
FP	BAAQMD 6-1-311	N		4.10P ^{0.67} lb/hr, where P is process weight, ton/hr	None	N	None
	SIP 6-310	Y		0.15 gr/dscf	None	N	None
	SIP 6-311	Y		4.10P ^{0.67} lb/hr, where P is process weight, ton/hr	None	N	None
Through-put	BAAQMD condition #16736, part 1	Y		11,000 tons/yr	BAAQMD condition #16736, part 6	P/D	Record keeping

**Table VII - F
 Applicable Limits and Compliance Monitoring Requirements
 S19 – X1 RECYCLE STATION**

Type of Limit	Citation of Limit	FE Y/N	Future Effective Date	Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
Opacity	BAAQMD 6-1-301	N		Ringelmann 1.0 for ≤ 3 minutes/hr	None	N	None
Opacity	SIP 6-301	Y		Ringelmann 1.0 for ≤ 3 minutes/hr	None	N	None
FP	BAAQMD 6-1-310	N		0.15 gr/dscf	None	N	None

VII. Applicable Limits and Compliance Monitoring Requirements

**Table VII - F
 Applicable Limits and Compliance Monitoring Requirements
 S19 – X1 RECYCLE STATION**

Type of Limit	Citation of Limit	FE Y/N	Future Effective Date	Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
	BAAQMD 6-1-311	N		4.10P ^{0.67} lb/hr, where P is process weight, ton/hr	None	N	None
FP	SIP 6-310	Y		0.15 gr/dscf	None	N	None
	SIP 6-311	Y		4.10P ^{0.67} lb/hr, where P is process weight, ton/hr	None	N	None
Through-put	BAAQMD condition #16736, part 1	Y		3,667 tons/yr	BAAQMD condition #16736, part 6	P/D	Record keeping

**Table VII – G
 Applicable Limits and Compliance Monitoring Requirements
 S104 - H1 BLENDING TANK T-1
 S105 – H1 BLENDING TANK T-2
 S106 – H1 BLENDING TANK T-3**

Type of Limit	Citation of Limit	FE Y/N	Future Effective Date	Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
Opacity	BAAQMD 6-1-301, Condition 9984, part 1	N		Ringelmann 1.0 for ≤ 3 minutes/hr	BAAQMD condition #9984, part 3	C	Bag failure warning device
Opacity	SIP 6-301, Condition 9984, part 1	Y		Ringelmann 1.0 for ≤ 3 minutes/hr	BAAQMD condition #9984, part 3	C	Bag failure warning device
FP	BAAQMD 6-1-310	N		0.15 gr/dscf	BAAQMD condition #9984, part 3	C	Bag failure warning device

VII. Applicable Limits and Compliance Monitoring Requirements

**Table VII – G
 Applicable Limits and Compliance Monitoring Requirements
 S104 - H1 BLENDING TANK T-1
 S105 – H1 BLENDING TANK T-2
 S106 – H1 BLENDING TANK T-3**

Type of Limit	Citation of Limit	FE Y/N	Future Effective Date	Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
	BAAQMD 6-1-311	N		4.10P ^{0.67} lb/hr, where P is process weight, ton/hr	None	N	None
FP	SIP 6-310	Y		0.15 gr/dscf	BAAQMD condition #9984, part 3	C	Bag failure warning device
	SIP 6-311	Y		4.10P ^{0.67} lb/hr, where P is process weight, ton/hr	None	N	None
	BAAQMD condition #9984, part 2	Y		0.006 gr/dscf	BAAQMD condition #9984, part 3	C	Bag failure warning device
Air flow rate	BAAQMD condition #9984, part 2	Y		3,500 scfm	None	N	None

**Table VII - H
 Applicable Limits and Compliance Monitoring Requirements
 S107 - H1 LIQUID/SOLID BLENDER**

Type of Limit	Citation of Limit	FE Y/N	Future Effective Date	Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
Opacity	BAAQMD 6-1-301	N		Ringelmann 1.0 for ≤ 3 minutes/hr	None	N	None
Opacity	SIP 6-301	Y		Ringelmann 1.0 for ≤ 3 minutes/hr	None	N	None

VII. Applicable Limits and Compliance Monitoring Requirements

**Table VII - I
 Applicable Limits and Compliance Monitoring Requirements**

**S111 – O4 CALCINED PRODUCT ELEVATOR
 S112 – O4 CALCINED PRODUCT SCREENER
 S113 – O4 CALCINED PRODUCT PACKAGING
 S114 – O4 KILN HOPPER**

Type of Limit	Citation of Limit	FE Y/N	Future Effective Date	Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
Opacity	BAAQMD 6-1-301, condition #13138 part 1	N		Ringelmann 1.0 for ≤ 3 minutes/hr	BAAQMD condition #13138, part 3	C	Bag failure warning device
Opacity	SIP 6-301, condition #13138 part 1	Y		Ringelmann 1.0 for ≤ 3 minutes/hr	BAAQMD condition #13138, part 3	C	Bag failure warning device
FP	BAAQMD 6-1-310	N		0.15 gr/dscf	BAAQMD condition #13138, part 3	C	Bag failure warning device
	BAAQMD 6-1-311	N		$4.10P^{0.67}$ lb/hr, where P is process weight, ton/hr	None	N	None
FP	SIP 6-310	Y		0.15 gr/dscf	BAAQMD condition #13138, part 3	C	Bag failure warning device
	SIP 6-311	Y		$4.10P^{0.67}$ lb/hr, where P is process weight, ton/hr	None	N	None
	BAAQMD condition #13138, part 2	Y		0.006 gr/dscf	BAAQMD condition #13138, part 3	C	Bag failure warning device
	BAAQMD condition #13138, part 2	Y		0.39 lb/hr	BAAQMD condition #13138, part 3	C	Bag failure warning device

VII. Applicable Limits and Compliance Monitoring Requirements

Table VII - J
Applicable Limits and Compliance Monitoring Requirements
S303 - ALUMINA RECEIVING FLUIDSTAT STATION
S309 – ALUMINA RECIRCULATION FLUIDSTAT STATION
S310 – ALUMINA MEASURING FLUIDSTAT STATION

Type of Limit	Citation of Limit	FE Y/N	Future Effective Date	Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
Opacity	BAAQMD 6-1-301	N		Ringelmann 1.0 for ≤ 3 minutes/hr	None	N	None
Opacity	SIP 6-301	Y		Ringelmann 1.0 for ≤ 3 minutes/hr	None	N	None
FP	BAAQMD 6-1-310	N		0.15 gr/dscf	None	N	None
	BAAQMD 6-1-311	N		4.10P ^{0.67} lb/hr, where P is process weight, ton/hr	None	N	None
FP	SIP 6-310	Y		0.15 gr/dscf	None	N	None
	SIP 6-311	Y		4.10P ^{0.67} lb/hr, where P is process weight, ton/hr	None	N	None

Table VII - K
Applicable Limits and Compliance Monitoring Requirements
S304 - ALUMINA SILO 1
S305 – ALUMINA SILO 2, S306 – ALUMINA SILO 3
S307 – ALUMINA SILO 4, S308 – ALUMINA SILO 5

Type of Limit	Citation of Limit	FE Y/N	Future Effective Date	Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
Opacity	BAAQMD 6-1-301	N		Ringelmann 1.0 for ≤ 3 minutes/hr	None	N	None
Opacity	SIP 6-301	Y		Ringelmann 1.0 for ≤ 3 minutes/hr	None	N	None
FP	BAAQMD 6-1-310	N		0.15 gr/dscf	None	N	None

VII. Applicable Limits and Compliance Monitoring Requirements

Table VII - K
Applicable Limits and Compliance Monitoring Requirements
S304 - ALUMINA SILO 1
S305 – ALUMINA SILO 2, S306 – ALUMINA SILO 3
S307 – ALUMINA SILO 4, S308 – ALUMINA SILO 5

Type of Limit	Citation of Limit	FE Y/N	Future Effective Date	Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
	BAAQMD 6-1-311	N		4.10P ^{0.67} lb/hr, where P is process weight, ton/hr	None	N	None
FP	SIP 6-310	Y		0.15 gr/dscf	None	N	None
	SIP 6-311	Y		4.10P ^{0.67} lb/hr, where P is process weight, ton/hr	None	N	None

Table VII - L
Applicable Limits and Compliance Monitoring Requirements
S311 - ALUMINA BULK BAG UNLOADER
S312 – ALUMINA REPACKAGING STATION
S313 – FINES GRINDER FEED HOPPER SYSTEM
S323 – FINES GRINDER FEED HOPPER SYSTEM (SECONDARY)

Type of Limit	Citation of Limit	FE Y/N	Future Effective Date	Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
Opacity	BAAQMD 6-1-301, condition #3344, part 1	N		Ringelmann 1.0 for ≤ 3 minutes/hr	BAAQMD condition #3344, part 5	C	Bag failure warning device
Opacity	SIP 6-301, condition #3344, part 1	Y		Ringelmann 1.0 for ≤ 3 minutes/hr	BAAQMD condition #3344, part 5	C	Bag failure warning device
FP	BAAQMD 6-1-310	N		0.15 gr/dscf	BAAQMD Condition #3344, part 5	C	Bag failure warning device

VII. Applicable Limits and Compliance Monitoring Requirements

**Table VII - L
 Applicable Limits and Compliance Monitoring Requirements
 S311 - ALUMINA BULK BAG UNLOADER
 S312 – ALUMINA REPACKAGING STATION
 S313 – FINES GRINDER FEED HOPPER SYSTEM
 S323 – FINES GRINDER FEED HOPPER SYSTEM (SECONDARY)**

Type of Limit	Citation of Limit	FE Y/N	Future Effective Date	Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
	BAAQMD 6-1-311	N		4.10P ^{0.67} lb/hr, where P is process weight, ton/hr	None	N	None
FP	SIP 6-310	Y		0.15 gr/dscf	BAAQMD Condition #3344, part 5	C	Bag failure warning device
	SIP 6-311	Y		4.10P ^{0.67} lb/hr, where P is process weight, ton/hr	None	N	None
	BAAQMD condition #3344, part 6	Y		0.005 gr/dscf	BAAQMD condition. #3344, part 5	C	Bag failure warning device
Nickel content	BAAQMD condition #3344, part 7	Y		7% by weight per hour at S313 and S323	BAAQMD condition #3344, part 8	P/H	Record keeping
Through-put (bulk)	BAAQMD condition #3344, part 2	Y		12,480 tons/yr for S311 and S312	BAAQMD condition #3344, part 8	P/D	Record keeping
Through-put (catalyst)	BAAQMD condition #3344, part 3	Y		4,380 tons/yr for S313 and S323	BAAQMD condition #3344, part 8	P/D	Record keeping
Air flow rate	BAAQMD condition #3344, part 6	Y		2,900 scfm	None	N	None

VII. Applicable Limits and Compliance Monitoring Requirements

Table VII – M
Applicable Limits and Compliance Monitoring Requirements
S314 - REGROUND FINES STORAGE SILO TK-70112
S315 – REGROUND FINES STORAGE SILO TK-70113
S316 – REGROUND FINES STORAGE SILO TK-70114
S317 – REGROUND FINES STORAGE SILO TK-70115
S318 – FINES WEIGH HOPPER BLOW POT
S319 – FINES BAGOUT STATION No.1 & No.2
S320 – FINES GRINDER
S322 – FINES TANKER TRUCK DELIVERY SYSTEM

Type of Limit	Citation of Limit	FE Y/N	Future Effective Date	Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
Opacity	BAAQMD 6-1-301	N		Ringelmann 1.0 for ≤ 3 minutes/hr	BAAQMD condition #8468, part 5	C	Bag failure warning device
Opacity	SIP 6-301	Y		Ringelmann 1.0 for ≤ 3 minutes/hr	BAAQMD condition #8468, part 5	C	Bag failure warning device
FP	BAAQMD 6-1-310	N		0.15 gr/dscf	BAAQMD condition #8468, part 5	C	Bag failure warning device
	BAAQMD 6-1-311	N		$4.10P^{0.67}$ lb/hr, where P is process weight, ton/hr	None	N	None
FP	SIP 6-310	Y		0.15 gr/dscf	BAAQMD condition #8468, part 5	C	Bag failure warning device
	SIP 6-311	Y		$4.10P^{0.67}$ lb/hr, where P is process weight, ton/hr	None	N	None
	BAAQMD condition #8468, part 6	Y		0.005 gr/dscf	BAAQMD condition. #8468, part 5	C	Bag failure warning device
Nickel content	BAAQMD condition #8468, part 7	Y		7% by weight per hour	BAAQMD condition #3344, part 8	P/H	Record keeping
Through- put (catalyst)	BAAQMD condition #8468, part 2	Y		4,380 tons/yr for each source	BAAQMD condition #8468, part 8	P/D	Record keeping

VII. Applicable Limits and Compliance Monitoring Requirements

Table VII – M
Applicable Limits and Compliance Monitoring Requirements
S314 - REGROUND FINES STORAGE SILO TK-70112
S315 – REGROUND FINES STORAGE SILO TK-70113
S316 – REGROUND FINES STORAGE SILO TK-70114
S317 – REGROUND FINES STORAGE SILO TK-70115
S318 – FINES WEIGH HOPPER BLOW POT
S319 – FINES BAGOUT STATION No.1 & No.2
S320 – FINES GRINDER
S322 – FINES TANKER TRUCK DELIVERY SYSTEM

Type of Limit	Citation of Limit	FE Y/N	Future Effective Date	Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
Air flow rate	BAAQMD condition #8468, part 6	Y		3,000 scfm from each source	None	N	None

Table VII - N
Applicable Limits and Compliance Monitoring Requirements
S321 - ALUMINA STORAGE SILO

Type of Limit	Citation of Limit	FE Y/N	Future Effective Date	Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
Opacity	BAAQMD 6-1-301	N		Ringelmann 1.0 for ≤ 3 minutes/hr	BAAQMD Condition #13092, part 3	C	Bag failure warning device
Opacity	SIP 6-301	Y		Ringelmann 1.0 for ≤ 3 minutes/hr	BAAQMD Condition #13092, part 3	C	Bag failure warning device
FP	BAAQMD 6-1-310	N		0.15 gr/dscf	BAAQMD condition #13092, part 3	C	Bag failure warning device
	BAAQMD 6-1-311	N		4.10P ^{0.67} lb/hr, where P is process weight, ton/hr	None	N	None
FP	SIP 6-310	Y		0.15 gr/dscf	BAAQMD condition #13092, part 3	C	Bag failure warning device

VII. Applicable Limits and Compliance Monitoring Requirements

**Table VII - N
 Applicable Limits and Compliance Monitoring Requirements
 S321 - ALUMINA STORAGE SILO**

Type of Limit	Citation of Limit	FE Y/N	Future Effective Date	Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
	SIP 6-311	Y		4.10P ^{0.67} lb/hr, where P is process weight, ton/hr	None	N	None
	BAAQMD condition #13092, part 4	Y		0.005 gr/dscf	BAAQMD condition. #13092, part 3	C	Bag failure warning device
Through-put (Alumina)	BAAQMD condition #13092, part 2	Y		9,636 tons/yr	BAAQMD condition #13092, part 5	P/D	Record keeping
Air flow rate	BAAQMD condition #13092, part 4	Y		150 scfm	None	N	None

**Table VII - O
 Applicable Limits and Compliance Monitoring Requirements
 S401 - X2 MULLER**

Type of Limit	Citation of Limit	FE Y/N	Future Effective Date	Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
Opacity	BAAQMD 6-1-301	N		Ringelmann 1.0 for ≤ 3 minutes/hr	BAAQMD condition #8445, part 3	C	Bag failure warning device
Opacity	SIP 6-301	Y		Ringelmann 1.0 for ≤ 3 minutes/hr	BAAQMD condition #8445, part 3	C	Bag failure warning device
FP	BAAQMD 6-1-310	N		0.15 gr/dscf	BAAQMD condition #8445, part 3	C	Bag failure warning device

VII. Applicable Limits and Compliance Monitoring Requirements

**Table VII - O
 Applicable Limits and Compliance Monitoring Requirements
 S401 - X2 MULLER**

Type of Limit	Citation of Limit	FE Y/N	Future Effective Date	Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
	BAAQMD 6-1-311	N		4.10P ^{0.67} lb/hr, where P is process weight, ton/hr	None	N	None
FP	SIP 6-310	Y		0.15 gr/dscf	BAAQMD condition #8445, part 3	C	Bag failure warning device
	SIP 6-311	Y		4.10P ^{0.67} lb/hr, where P is process weight, ton/hr	None	N	None
	BAAQMD condition #8445, part 2	Y		0.006 gr/dscf	BAAQMD condition. #8445, part 3	C	Bag failure warning device
Air flow rate	BAAQMD condition #8445, part 2	Y		1,116 scfm	None	N	None

VII. Applicable Limits and Compliance Monitoring Requirements

**Table VII - P
 Applicable Limits and Compliance Monitoring Requirements
 S408 - X2 DRIED PRODUCT ELEVATOR
 S409 – X2 DRIED PRODUCT SCREENER
 S410 – X2 LONG BREAKER, S412 – X2 KILN FEED CONVEYOR
 S414 – X2 CALCINED PRODUCT ELEVATOR
 S415 – X2 CALCINED PRODUCT SCREENER
 S416 – X2 CALCINED PRODUCT PACKAGING**

Type of Limit	Citation of Limit	FE Y/N	Future Effective Date	Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
Opacity	BAAQMD 6-1-301	N		Ringelmann 1.0 for ≤ 3 minutes/hr	None	N	None
Opacity	SIP 6-301	Y		Ringelmann 1.0 for ≤ 3 minutes/hr	None	N	None
FP	BAAQMD 6-1-310	N		0.15 gr/dscf	None	N	None
FP	BAAQMD 6-1-311	N		4.10P ^{0.67} lb/hr, where P is process weight, ton/hr	None	N	None
FP	SIP 6-310	Y		0.15 gr/dscf	None	N	None
FP	SIP 6-311	Y		4.10P ^{0.67} lb/hr, where P is process weight, ton/hr	None	N	None

VII. Applicable Limits and Compliance Monitoring Requirements

Table VII - Q
Applicable Limits and Compliance Monitoring Requirements
S417 - X2 CALCINED PRODUCT CONVEYOR
S418 – X2 RECYCLE STATION
S515 – H2 SOLID ADDITIVE HOPPER A
S516 – H2 SOLID ADDITIVE HOPPER B
S517 – H2 PRODUCT RECYCLE SYSTEM
S518 – H2 CALCINED FEED SYSTEM
S519 – H2 SPHERICAL HOPPER SYSTEM
S520 – H2 CALCINED FEED BAGOUT STATION

Type of Limit	Citation of Limit	FE Y/N	Future Effective Date	Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
Opacity	BAAQMD 6-1-301, condition #16736, part 5	N		Ringelmann 1.0 for ≤ 3 minutes/hr	None	N	None
Opacity	SIP 6-301, condition #16736, part 5	Y		Ringelmann 1.0 for ≤ 3 minutes/hr	None	N	None
FP	BAAQMD 6-1-310	N		0.15 gr/dscf	None	N	None
	BAAQMD 6-1-311	N		4.10P ^{0.67} lb/hr, where P is process weight, ton/hr	None	N	None
FP	SIP 6-310	Y		0.15 gr/dscf	None	N	None
	SIP 6-311	Y		4.10P ^{0.67} lb/hr, where P is process weight, ton/hr	None	N	None
Through-put	BAAQMD condition #16736, part 1	Y		S417: 12,000 tons/yr S418: 12,000 tons/yr S515: 1,700 tons/yr S516: 3,300 tons/yr S517: 16,000 tons/yr S518: 16,000 tons/yr S519: 16,000 tons/yr S520: 16,000 tons/yr	BAAQMD condition #16736, part 6	P/D	Record keeping

VII. Applicable Limits and Compliance Monitoring Requirements

**Table VII - R
 Applicable Limits and Compliance Monitoring Requirements
 S420 - COLD CLEANER**

Type of Limit	Citation of Limit	FE Y/N	Future Effective Date	Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
Through put	BAAQMD 8-16-121	Y		20 gallons/yr	BAAQMD 8-16-501.2, 8-16-501.6	P/Annual	Record keeping

**Table VII – S
 Applicable Limits and Compliance Monitoring Requirements
 S502 - NICKEL SOLUTION TANK**

Type of Limit	Citation of Limit	FE Y/N	Future Effective Date	Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
Ni	BAAQMD Regulation 2-1, Table 2-1-316	Y		0.73 lb/yr	BAAQMD 2-1-316.1	P/Annual	Record keeping

VII. Applicable Limits and Compliance Monitoring Requirements

Table VII – T
Applicable Limits and Compliance Monitoring Requirements
S504 - H2 BLENDING TANK T-1
S505 – H2 BLENDING TANK T-2
S506 – H2 BLENDING TANK T-3
S507 – H2 LIQUID/SOLID BLENDER
S509 – H2 KILN FEED CONVEYOR
S510 – H2 Kiln
S514 – H2 Kiln Bypass Chute & Hopper w/dusthood

Type of Limit	Citation of Limit	FE Y/N	Future Effective Date	Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
Opacity	BAAQMD 6-1-301	N		Ringelmann 1.0 for ≤ 3 minutes/hr	BAAQMD condition #9315, part 5	C	Bag failure warning device
Opacity	SIP 6-301	Y		Ringelmann 1.0 for ≤ 3 minutes/hr	BAAQMD condition #9315, part 5	C	Bag failure warning device
FP	BAAQMD 6-1-310	N		0.15 gr/dscf	BAAQMD condition #9315, part 5	C	Bag failure warning device
	BAAQMD 6-1-311	N		$4.10P^{0.67}$ lb/hr, where P is process weight, ton/hr	None	N	None
FP	SIP 6-310	Y		0.15 gr/dscf	BAAQMD condition #9315, part 5	C	Bag failure warning device
	SIP 6-311	Y		$4.10P^{0.67}$ lb/hr, where P is process weight, ton/hr	None	N	None
	BAAQMD condition #9315, part 4	Y		0.006 gr/dscf	BAAQMD condition #9315, part 5	C	Bag failure warning device
Air flow rate	BAAQMD condition #9315, part 4	Y		7,500 scfm	None	N	None
NOx	BAAQMD condition #9315, part 10	Y		120 lb/day	BAAQMD condition #9315, part 13 & 14	P/A and D	Source test (A), Record keeping (D)

VII. Applicable Limits and Compliance Monitoring Requirements

Table VII – T
Applicable Limits and Compliance Monitoring Requirements
S504 - H2 BLENDING TANK T-1
S505 – H2 BLENDING TANK T-2
S506 – H2 BLENDING TANK T-3
S507 – H2 LIQUID/SOLID BLENDER
S509 – H2 KILN FEED CONVEYOR
S510 – H2 Kiln
S514 – H2 Kiln Bypass Chute & Hopper w/dusthood

Type of Limit	Citation of Limit	FE Y/N	Future Effective Date	Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
NH3	BAAQMD condition #9315, part 10	Y		2,200 lb/day, and 200 lb/day (when A-56 in operation)	BAAQMD condition #9315, part 13	P/A and D	Source test (A), Record keeping (D)
CO	BAAQMD condition #9315, part 8	Y		400 ppmv dry @ 3% Oxygen	BAAQMD condition #9315, part 13	P/A	Source test
Temperature (A-56)	BAAQMD condition #9315, part 9	Y		1400 degree F	BAAQMD condition #9315, part 7	C	Temperature Monitor
Residence time (A-56)	BAAQMD condition #9315, part 9	Y		0.4 second	BAAQMD condition #9315, part 13	P/A	Source test

VII. Applicable Limits and Compliance Monitoring Requirements

Table VII - U
Applicable Limits and Compliance Monitoring Requirements
S511 – H2 PRODUCT CONVEYOR
S512 – H2 PRODUCT SCREENER
S513 – H2 PRODUCT PACKAGING

Type of Limit	Citation of Limit	FE Y/N	Future Effective Date	Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
Opacity	BAAQMD 6-1-301	N		Ringelmann 1.0 for ≤ 3 minutes/hr	None	N	None
Opacity	SIP 6-301	Y		Ringelmann 1.0 for ≤ 3 minutes/hr	None	N	None
FP	BAAQMD 6-1-310	N		0.15 gr/dscf	None	N	None
	BAAQMD 6-1-311	N		4.10P ^{0.67} lb/hr, where P is process weight, ton/hr	None	N	None
FP	SIP 6-310	Y		0.15 gr/dscf	None	N	None
	SIP 6-311	Y		4.10P ^{0.67} lb/hr, where P is process weight, ton/hr	None	N	None

Table VII – V
Applicable Limits and Compliance Monitoring Requirements
S600 - X3 DRIED EXTRUDER, SCREENER, CONVEYOR

Type of Limit	Citation of Limit	FE Y/N	Future Effective Date	Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
Opacity	BAAQMD 6-1-301, condition #13093, part 2	N		Ringelmann 1.0 for ≤ 3 minutes/hr	None	N	None
Opacity	SIP 6-301, condition #13093, part 2	Y		Ringelmann 1.0 for ≤ 3 minutes/hr	None	N	None

VII. Applicable Limits and Compliance Monitoring Requirements

**Table VII – V
 Applicable Limits and Compliance Monitoring Requirements
 S600 - X3 DRIED EXTRUDER, SCREENER, CONVEYOR**

Type of Limit	Citation of Limit	FE Y/N	Future Effective Date	Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
FP	BAAQMD 6-1-310	N		0.15 gr/dscf	BAAQMD condition # 15672, part 2	C	Bag failure warning device
	BAAQMD 6-1-311	N		4.10P ^{0.67} lb/hr, where P is process weight, ton/hr	None	N	None
FP	SIP 6-310	Y		0.15 gr/dscf	BAAQMD condition # 15672, part 2	C	Bag failure warning device
	SIP 6-311	Y		4.10P ^{0.67} lb/hr, where P is process weight, ton/hr	None	N	None
	BAAQMD condition # 13093, part 3	Y		0.006 gr/dscf	BAAQMD condition # 13097, part 4	C	Bag failure warning device
Air flow rate	BAAQMD condition # 13093, part 3	Y		12,000 cfm	None	N	None
Through-put	BAAQMD condition #13093, part 4	Y		36 tons/day	BAAQMD condition #13093, part 6	P/D	Record keeping
Nickel & Nickel compounds content	BAAQMD condition #13093, part 1	Y		0.84% by weight per year	BAAQMD condition #13093, part 6	P/D	Record keeping

VII. Applicable Limits and Compliance Monitoring Requirements

**Table VII - W
 Applicable Limits and Compliance Monitoring Requirements
 S601 - X3 FINES SURGE HOPPER**

Type of Limit	Citation of Limit	FE Y/N	Future Effective Date	Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
Opacity	BAAQMD 6-1-301, condition #13094, part 1	N		Ringelmann 1.0 for \leq 3 minutes/hr	BAAQMD Condition #13094, part 3	C	Bag failure warning device
Opacity	SIP 6-301, condition #13094, part 1	Y		Ringelmann 1.0 for \leq 3 minutes/hr	BAAQMD Condition #13094, part 3	C	Bag failure warning device
FP	BAAQMD 6-1-310	N		0.15 gr/dscf	BAAQMD Condition #13094, part 3	C	Bag failure warning device
	BAAQMD 6-1-311	N		$4.10P^{0.67}$ lb/hr, where P is process weight, ton/hr	None	N	None
FP	SIP 6-310	Y		0.15 gr/dscf	BAAQMD Condition #13094, part 3	C	Bag failure warning device
	SIP 6-311	Y		$4.10P^{0.67}$ lb/hr, where P is process weight, ton/hr	None	N	None
	BAAQMD condition #13094, part 4	Y		0.006 gr/dscf	BAAQMD Condition #13094, part 3	C	Bag failure warning device
Air flow rate	BAAQMD condition #13094, part 4	Y		100 scfm	None	N	None
Through-put (catalyst)	BAAQMD condition #13094, part 2	Y		1,400 tons/yr	BAAQMD condition #13094, part 5	P/D	Record keeping

VII. Applicable Limits and Compliance Monitoring Requirements

**Table VII - X
 Applicable Limits and Compliance Monitoring Requirements
 S602 - X3 ALUMINA SURGE HOPPER**

Type of Limit	Citation of Limit	FE Y/N	Future Effective Date	Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
Opacity	BAAQMD 6-1-301, condition #13095, part 1	N		Ringelmann 1.0 for ≤ 3 minutes/hr	BAAQMD Condition #13095, part 3	C	Bag failure warning device
Opacity	SIP 6-301, condition #13095, part 1	Y		Ringelmann 1.0 for ≤ 3 minutes/hr	BAAQMD Condition #13095, part 3	C	Bag failure warning device
FP	BAAQMD 6-1-310	N		0.15 gr/dscf	BAAQMD Condition #13095, part 3	C	Bag failure warning device
	BAAQMD 6-1-311	N		$4.10P^{0.67}$ lb/hr, where P is process weight, ton/hr	None	N	None
FP	SIP 6-310	Y		0.15 gr/dscf	BAAQMD Condition #13095, part 3	C	Bag failure warning device
	SIP 6-311	Y		$4.10P^{0.67}$ lb/hr, where P is process weight, ton/hr	None	N	None
	BAAQMD condition #13095, part 4	Y		0.006 gr/dscf	BAAQMD Condition #13095, part 3	C	Bag failure warning device
Air flow rate	BAAQMD condition #13095, part 4	Y		200 scfm	BAAQMD condition #13095, part 4	N	None
Through-put (Alumina)	BAAQMD condition #13095, part 2	Y		9,636 tons/yr	BAAQMD condition #13095, part 5	P/D	Record keeping

VII. Applicable Limits and Compliance Monitoring Requirements

**Table VII - Y
 Applicable Limits and Compliance Monitoring Requirements
 S603 - X3 EXTRUDER**

Type of Limit	Citation of Limit	FE Y/N	Future Effective Date	Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
Opacity	BAAQMD 6-1-301, condition #13096, part 1	N		Ringelmann 1.0 for \leq 3 minutes/hr	None	N	None
Opacity	SIP 6-301, condition #13096, part 1	Y		Ringelmann 1.0 for \leq 3 minutes/hr	None	N	None
FP	BAAQMD 6-1-310	N		0.15 gr/dscf	None	N	None
	BAAQMD 6-1-311	N		$4.10P^{0.67}$ lb/hr, where P is process weight, ton/hr	None	N	None
FP	SIP 6-310	Y		0.15 gr/dscf	None	N	None
	SIP 6-311	Y		$4.10P^{0.67}$ lb/hr, where P is process weight, ton/hr	None	N	None
NH3	BAAQMD #15672, part 5	Y		490 lb/day or 48,000 lb/yr	BAAQMD condition #15672, part 11	P/A	Source test
Through-put	BAAQMD condition #13096, part 2	Y		31,665 tons/yr	BAAQMD condition #13096, part 3	P/D	Record keeping
Nickel content	BAAQMD condition #15672, part 10	Y		0.84% by weight per year	BAAQMD condition #15672, part 14	P/M	Record keeping

VII. Applicable Limits and Compliance Monitoring Requirements

**Table VII - Z
 Applicable Limits and Compliance Monitoring Requirements
 S604 - X3 DRYER**

Type of Limit	Citation of Limit	FE Y/N	Future Effective Date	Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
Opacity	BAAQMD 6-1-301, condition #13097, part 1	N		Ringelmann 1.0 for \leq 3 minutes/hr	BAAQMD Condition #13097, part 3	C	Pressure drop monitoring device
Opacity	SIP 6-301, condition #13097, part 1	Y		Ringelmann 1.0 for \leq 3 minutes/hr	BAAQMD Condition #13097, part 3	C	Pressure drop monitoring device
FP	BAAQMD 6-1-310	N		0.15 gr/dscf	BAAQMD Condition #13097, part 3	C	Pressure drop monitoring device
	BAAQMD 6-1-311	N		$4.10P^{0.67}$ lb/hr, where P is process weight, ton/hr	None	N	None
FP	SIP 6-310	Y		0.15 gr/dscf	BAAQMD Condition #13097, part 3	C	Pressure drop monitoring device
	SIP 6-311	Y		$4.10P^{0.67}$ lb/hr, where P is process weight, ton/hr	None	N	None
	BAAQMD condition #13097, part 4	Y		0.006 gr/dscf	BAAQMD Condition #13097, part 3	C	Pressure drop monitoring device
NH3	BAAQMD #15672, part 5	Y		490 lb/day or 48,000 lb/yr	BAAQMD condition #15672, part 11	P/A	Source test
Nickel content	BAAQMD condition #15672, part 10	Y		0.84% by weight per year	BAAQMD condition #15672, part 14	P/M	Record keeping

VII. Applicable Limits and Compliance Monitoring Requirements

**Table VII - Z
 Applicable Limits and Compliance Monitoring Requirements
 S604 - X3 DRYER**

Type of Limit	Citation of Limit	FE Y/N	Future Effective Date	Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
Air flow rate	BAAQMD condition #13097, part 4	Y		12,000 scfm	None	N	None
Natural gas	BAAQMD condition #13097, part 5	Y		534,360 therms/yr	BAAQMD condition #13097, part 6 and 7	C/M	Fuel meter and Record keeping

**Table VII - AA
 Applicable Limits and Compliance Monitoring Requirements
 S606 - X3 CALCINER**

Type of Limit	Citation of Limit	FE Y/N	Future Effective Date	Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
Opacity	BAAQMD 6-1-301, condition #15672, part 1	N		Ringelmann 1.0 for ≤ 3 minutes/hr	BAAQMD condition #15672, part 2	C	Bag failure warning device
Opacity	SIP 6-301, condition #15672, part 1	Y		Ringelmann 1.0 for ≤ 3 minutes/hr	BAAQMD condition #15672, part 2	C	Bag failure warning device
FP	BAAQMD 6-1-310	N		0.15 gr/dscf	BAAQMD condition #15672, part 2	C	Bag failure warning device
	BAAQMD 6-1-311	N		4.10P ^{0.67} lb/hr, where P is process weight, ton/hr	None	N	None

VII. Applicable Limits and Compliance Monitoring Requirements

**Table VII - AA
 Applicable Limits and Compliance Monitoring Requirements
 S606 - X3 CALCINER**

Type of Limit	Citation of Limit	FE Y/N	Future Effective Date	Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
FP	SIP 6-310	Y		0.15 gr/dscf	BAAQMD condition #15672, part 2	C	Bag failure warning device
	SIP 6-311	Y		4.10P ^{0.67} lb/hr, where P is process weight, ton/hr	None	N	None
	BAAQMD condition #15672, part 3	Y		0.006 gr/dscf	BAAQMD condition #15672, part 2	C	Bag failure warning device
NOx	BAAQMD condition #15672, part 6	Y		51 lb/day or 18,500 lb/yr	BAAQMD condition #15672, part 12	C	CEM
CO	BAAQMD condition #15672, part 9	Y		19,524 lb/yr	BAAQMD condition #15672, part 12	C	CEM
	BAAQMD condition #15672, part 8	Y		40 ppmv	BAAQMD condition #15672, part 12	C	CEM
CO abatement efficiency	BAAQMD condition #15672, part 8	Y		90% mass basis	BAAQMD condition #15672, part 12	C	CEM
NH3	BAAQMD #15672, part 5	Y		490 lb/day or 48,000 lb/yr	BAAQMD condition #15672, part 11	P/A	Source test
SO2	BAAQMD 9-1-301	N		GLC of 0.5 ppm for 3 min. or 0.25 ppm for 60 min. or 0.05 ppm for 24 hours	None	N	None

VII. Applicable Limits and Compliance Monitoring Requirements

**Table VII - AA
 Applicable Limits and Compliance Monitoring Requirements
 S606 - X3 CALCINER**

Type of Limit	Citation of Limit	FE Y/N	Future Effective Date	Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
	BAAQMD 9-1-311.2	N		50 lbs/hr	None	N	None
SO2	SIP 9-1-301	Y		GLC of 0.5 ppm for 3 min. or 0.25 ppm for 60 min. or 0.05 ppm for 24 hours	None	N	None
	SIP 9-1-311.2	Y		50 lbs/hr	None	N	None
Nickel content	BAAQMD condition #15672, part 10	Y		0.84% by weight per year	BAAQMD condition #15672, part 14	P/M	Record keeping
Air flow rate	BAAQMD condition #15672, part 3	Y		1,736 scfm	None	N	None
Natural gas	BAAQMD condition #15672, part 4	Y		700,000 therms	BAAQMD condition #15672, part 13 & 14	P/C/M	Fuel meter, Record keeping

VIII. TEST METHODS

The test methods associated with the emission limit of a District regulation are generally referenced in Section 600 et seq. of the regulation. The following table indicates only the test methods associated with the emission limits referenced in Section VII, Applicable Emission Limits & Compliance Monitoring Requirements, of this permit.

**Table VIII
 Test Methods**

Applicable Requirement	Description of Requirement	Acceptable Test Methods
BAAQMD 6-1-301	Ringelmann No. 1 Limitation	Manual of Procedures, Volume I, Evaluation of Visible Emissions
BAAQMD 6-1-310	Particulate Weight Limitation	Manual of Procedures, Volume IV, ST-15, Particulates Sampling or USEPA Method 5, Determination of Particulate Matter Emissions from Stationary Sources
BAAQMD 6-1-311	General Operations	Manual of Procedures, Volume IV, ST-15, Particulates Sampling or USEPA Method 5, Determination of Particulate Matter Emissions from Stationary Sources
SIP 6-301	Ringelmann No. 1 Limitation	Manual of Procedures, Volume I, Evaluation of Visible Emissions
SIP 6-310	Particulate Weight Limitation	Manual of Procedures, Volume IV, ST-15, Particulates Sampling or USEPA Method 5, Determination of Particulate Matter Emissions from Stationary Sources
SIP 6-311	General Operations	Manual of Procedures, Volume IV, ST-15, Particulates Sampling or USEPA Method 5, Determination of Particulate Matter Emissions from Stationary Sources
BAAQMD 8-16-601	VOC emissions	Manual of Procedures, Volume IV, ST-7, or EPA Method 25 or 25A
BAAQMD 8-16-602	VOC content	Manual of Procedures, Volume III, Methods 21 or 22, 31
BAAQMD 9-1-301	Ground Level Concentrations, SO ₂	Manual of Procedures, Volume VI, Section 1.

VIII. Test Methods

**Table VIII
 Test Methods**

Applicable Requirement	Description of Requirement	Acceptable Test Methods
BAAQMD 9-1-302	General Emission Limitation	Manual of Procedures, Volume IV, ST-19A, Sulfur Dioxide, Continuous Sampling, or ST-19B, Total Sulfur Oxides Integrated Sample
BAAQMD 9-1-304	Fuel Burning (Liquid and Solid Fuels)	Manual of Procedures, Volume III, Method 10, Determination of Sulfur in Fuel Oils.
BAAQMD 9-1-311.2	Emission Limitations, SO ₂	Manual of Procedures, Volume IV, ST-19A or B.
SIP 9-1-301	Ground Level Concentrations, SO ₂	Manual of Procedures, Volume VI, Section 1.
SIP 9-1-302	General Emission Limitation	Manual of Procedures, Volume IV, ST-19A, Sulfur Dioxide, Continuous Sampling, or ST-19B, Total Sulfur Oxides Integrated Sample
SIP 9-1-304	Fuel Burning (Liquid and Solid Fuels)	Manual of Procedures, Volume III, Method 10, Determination of Sulfur in Fuel Oils.
SIP 9-1-311.2	Emission Limitations, SO ₂	Manual of Procedures, Volume IV, ST-19A or B.
BAAQMD conditions #9315, #13100, #15672,	Emission Limit, NO _x	Manual of Procedures, Volume IV, ST-13A, Oxides of Nitrogen, Continuous Sampling or EPA Method 7E, 40 CFR Part 60 Appendix A
BAAQMD condition #9315, #15672,	Emission Limit, CO	Manual of Procedures, Volume IV, ST-6, Carbon Monoxide
BAAQMD condition #9315	Stack-gas Oxygen	Manual of Procedures, Volume IV, ST-14, Oxygen
BAAQMD condition #9315, #15672	Emission Limit, NH ₃	Manual of Procedures, Volume IV, ST-1B, Ammonia
BAAQMD condition #3344, #8468, #15672	Ni content	Atomic Absorption Spectro-photometry
BAAQMD condition #16736	Hexavalent Chromium	Manual of Procedures, Volume III, Method 34

IX. PERMIT SHIELD

Not applicable

X. REVISION HISTORY

Final Title V Permit (Application 18172)	November 30, 2001
Minor Revision (Application 6134): Capacity for S-321, Silo, changed from operating rate to volume	January 7, 2003
Renewal (Application 14581)	December 15, 2008
Administrative Amendment (Application 23611): Sources S109, S110, S201, S205, S206, S207, S208, S210, S211, S216, S220, S221, S222 thru S231, and Abatement Devices A12, A15, A21 thru A26 deleted because they were dismantled and removed from operation.	September 1, 2011
Minor Revision (Application 23296): New sources S322 and S323 added. Permit conditions for S322, S323, and S606 revised.	February 14, 2012

XI. GLOSSARY

ACT

Federal Clean Air Act

BAAQMD

Bay Area Air Quality Management District

BACT

Best Available Control Technology

CAA

The federal Clean Air Act

CAAQS

California Ambient Air Quality Standards

CEQA

California Environmental Quality Act

CFR

The Code of Federal Regulations. 40 CFR contains the implementing regulations for federal environmental statutes such as the Clean Air Act. Parts 50-99 of 40 CFR contain the requirements for air pollution programs.

CO

Carbon Monoxide

Cumulative Increase

The sum of permitted emissions from each new or modified source since a specified date pursuant to BAAQMD Rule 2-1-403, Permit Conditions (as amended by the District Board on 7/17/91) and SIP Rule 2-1-403, Permit Conditions (as approved by EPA on 6/23/95). Used to determine whether threshold-based requirements are triggered.

District

The Bay Area Air Quality Management District

EPA

The federal Environmental Protection Agency.

Excluded

Not subject to any District regulations.

Federally Enforceable, FE

All limitations and conditions which are enforceable by the Administrator of the EPA including those requirements developed pursuant to 40 CFR Part 51, subpart I (NSR), Part 52.21 (PSD), Part 60, (NSPS), Part 61, (NESHAPs), Part 63 (HAP), and Part 72 (Permits Regulation, Acid Rain), including limitations and conditions contained in operating permits issued under an EPA-approved program that has been incorporated into the SIP.

XI. Glossary

FP

Filterable Particulate as measured by BAAQMD Method ST-15, Particulate.

HAP

Hazardous Air Pollutant. Any pollutant listed pursuant to Section 112(b) of the Act. Also refers to the program mandated by Title I, Section 112, of the Act and implemented by 40 CFR Part 63.

Major Facility

A facility with potential emissions of: (1) at least 100 tons per year of regulated air pollutants, (2) at least 10 tons per year of any single hazardous air pollutant, and/or (3) at least 25 tons per year of any combination of hazardous air pollutants, or such lesser quantity of hazardous air pollutants as determined by the EPA administrator.

MFR

Major Facility Review. The District's term for the federal operating permit program mandated by Title V of the Federal Clean Air Act and implemented by District Regulation 2, Rule 6.

MOP

The District's Manual of Procedures.

NAAQS

National Ambient Air Quality Standards

NESHAPS

National Emission Standards for Hazardous Air Pollutants. See in 40 CFR Parts 61 and 63

NMHC

Non-methane Hydrocarbons

NO_x

Oxides of nitrogen.

NSPS

Standards of Performance for New Stationary Sources. Federal standards for emissions from new stationary sources. Mandated by Title I, Section 111 of the Federal Clean Air Act, and implemented by 40 CFR Part 60 and District Regulation 10.

NSR

New Source Review. A federal program for pre-construction review and permitting of new and modified sources of pollutants for which criteria have been established in accordance with Section 108 of the Federal Clean Air Act. Mandated by Title I of the Federal Clean Air Act and implemented by 40 CFR Parts 51 and 52 and District Regulation 2, Rule 2. (Note: There are additional NSR requirements mandated by the California Clean Air Act.)

XI. Glossary

Offset Requirement

A New Source Review requirement to provide federally enforceable emission offsets for the emissions from a new or modified source. Applies to emissions of POC, NO_x, PM₁₀, and SO₂.

Phase II Acid Rain Facility

A facility that generates electricity for sale through fossil-fuel combustion and is not exempted by 40 CFR 72 from Titles IV and V of the Clean Air Act.

POC

Precursor Organic Compounds

PM

Particulate Matter

PM₁₀

Particulate matter with aerodynamic equivalent diameter of less than or equal to 10 microns

PSD

Prevention of Significant Deterioration. A federal program for permitting new and modified sources of those air pollutants for which the District is classified "attainment" of the National Air Ambient Quality Standards. Mandated by Title I of the Act and implemented by both 40 CFR Part 52 and District Regulation 2, Rule 2.

SIP

State Implementation Plan. State and District programs and regulations approved by EPA and developed in order to attain the National Air Ambient Quality Standards. Mandated by Title I of the Act.

SO₂

Sulfur dioxide

Title V

Title V of the federal Clean Air Act. Requires a federally enforceable operating permit program for major and certain other facilities.

TRMP

Toxic Risk Management Plan

TSP

Total Suspended Particulate

VOC

Volatile Organic Compounds

XI. Glossary

Units of Measure:

bhp	=	brake-horsepower
btu	=	British Thermal Unit
g	=	grams
gal	=	gallon
hp	=	horsepower
hr	=	hour
lb	=	pound
in	=	inches
max	=	maximum
m ²	=	square meter
min	=	minute
mm	=	million
ppmv	=	parts per million, by volume
ppmw	=	parts per million, by weight
psia	=	pounds per square inch, absolute
psig	=	pounds per square inch, gauge
scfm	=	standard cubic feet per minute
yr	=	year