

Bay Area Air Quality Management District

939 Ellis Street
San Francisco, CA 94109
(415) 771-6000

Final

MAJOR FACILITY REVIEW PERMIT

Issued To:

**New United Motor Manufacturing Inc.
Facility # A1438**

Facility Address:

45500 Fremont Boulevard
Fremont, CA 94538

Mailing Address:

45500 Fremont Boulevard
Fremont, CA 94538

Responsible Official

Ernesto Gonzalez-Beltran
Vice President Manufacturing Operations
510-498-5554

Facility Contact

Edward Moore
Environmental Engineer
(510) 498-5795

Type of Facility: Automotive Manufacturing
Primary SIC: 3711
Product: Automobiles

BAAQMD Permit Division Contact:
Sanjeev Kamboj

ISSUED BY THE BAY AREA AIR QUALITY MANAGEMENT DISTRICT

Signed by Jeff McKay for Jack P. Broadbent _____ October 24, 2007
Jack P. Broadbent, Executive Officer/Air Pollution Control Officer Date

TABLE OF CONTENTS

I.	STANDARD CONDITIONS	3
II.	EQUIPMENT	7
III.	GENERALLY APPLICABLE REQUIREMENTS.....	22
IV.	SOURCE-SPECIFIC APPLICABLE REQUIREMENTS	25
V.	SCHEDULE OF COMPLIANCE.....	133
VI.	PERMIT CONDITIONS	134
VII.	APPLICABLE LIMITS & COMPLIANCE MONITORING REQUIREMENTS.....	195
VIII.	TEST METHODS.....	308
IX.	PERMIT SHIELD.....	311
X.	REVISION HISTORY.....	312
XI.	GLOSSARY	313
XII.	APPLICABLE STATE IMPLEMENTATION PLAN.....	317

I. STANDARD CONDITIONS

A. Administrative Requirements

The permit holder shall comply with all applicable requirements in the following regulations:

- BAAQMD Regulation 1 - General Provisions and Definitions
(as amended by the District Board on 5/2/01);
- SIP Regulation 1 - General Provisions and Definitions
(as approved by EPA through 6/28/99);
- BAAQMD Regulation 2, Rule 1 - Permits, General Requirements
(as amended by the District Board on 8/1/01);
- SIP Regulation 2, Rule 1 - Permits, General Requirements
(as approved by EPA through 1/26/99);
- BAAQMD Regulation 2, Rule 2 - Permits, New Source Review
(as amended by the District Board on 5/17/00);
- SIP Regulation 2, Rule 2 - Permits, New Source Review and Prevention of Significant Deterioration
(as approved by EPA through 1/26/99);
- BAAQMD Regulation 2, Rule 4 - Permits, Emissions Banking
(as amended by the District Board on 5/17/00);
- SIP Regulation 2, Rule 4 - Permits, Emissions Banking
(as approved by EPA through 1/26/99); and
- BAAQMD Regulation 2, Rule 6 - Permits, Major Facility Review
(as amended by the District Board on 4/16/03).

B. Conditions to Implement Regulation 2, Rule 6, Major Facility Review

1. This Major Facility Review Permit was issued on December 18, 2002, and expires on November 30, 2007. The permit holder shall submit a complete application for renewal of this Major Facility Review Permit no later than May 31, 2007, and no earlier than November 30, 2006. **If a complete application for renewal has not been submitted in accordance with this deadline, the facility may not operate after November 30, 2007.** If the permit renewal has not been issued by December 13, 2004, but a complete application for renewal has been submitted in accordance with the above deadlines, the existing permit will continue in force until the District takes final action on the renewal application. (Regulation 2-6-307, 404.2, 407, & 409.6; MOP Volume II, Part 3, §4.2)
2. The permit holder shall comply with all conditions of this permit. The permit consists of this document and all appendices. Any non-compliance with the terms and conditions of this permit will constitute a violation of the law and will be grounds for enforcement action; permit termination, revocation and re-issuance, or modification; or denial of a permit renewal application. (Regulation 2-6-307; MOP Volume II, Part 3, §4.11)
3. In the event any enforcement action is brought as a result of a violation of any term or condition of this permit, the fact that it would have been necessary for the

I. Standard Conditions

- permittee to halt or reduce the permitted activity in order to maintain compliance with such term or condition shall not be a defense to such enforcement action. (MOP Volume II, Part 3, §4.11)
4. This permit may be modified, revoked, reopened and reissued, or terminated for cause. (Regulation 2-6-307, 409.8, 415; MOP Volume II, Part 3, §4.11)
 5. The filing of a request by the facility for a permit modification, revocation and re-issuance, or termination, or the filing of a notification of planned changes or anticipated non-compliance does not stay the applicability of any permit condition. (Regulation 2-6-409.7; MOP Volume II, Part 3, §4.11)
 6. This permit does not convey any property rights of any sort, or any exclusive privilege. (Regulation 2-6-409.7; MOP Volume II, Part 3, §4.11)
 7. The permit holder shall supply within 30 days any information that the District requests in writing to determine whether cause exists for modifying, revoking and reissuing, or terminating the permit or to determine compliance with the permit. (Regulation 1-441, Regulation 2-6-409.4 & 501; MOP Volume II, Part 3, §4.11)
 8. Any records required to be maintained pursuant to this permit which the permittee considers to contain proprietary or trade secret information shall be prominently designated as such. Copies of any such proprietary or trade secret information which are provided to the District shall be maintained by the District in a locked confidential file, provided, however, that requests from the public for the review of any such information shall be handled in accordance with the District's procedures set forth in Section 11 of the District's Administrative Code. (Regulation 2-6-419; MOP Volume II, Part 3, §4.11)
 9. Proprietary or trade secret information provided to EPA will be subject to the requirements of 40 CFR Part 2, Subpart B - Public Information, Confidentiality of Business Information. (40 CFR Part 2)
 10. The emissions inventory submitted with the application for this Major Facility Review Permit is an estimate of actual emissions for the time period stated and is included only as one means of determining applicable requirements for emission sources. It does not establish, or constitute a basis for establishing, any new emission limitations. (MOP Volume II, Part 3, §4.11)
 11. The responsible official shall certify all documents submitted by the facility pursuant to the major facility review permit. The certification shall state that based on information and belief formed after reasonable inquiry, the statements and information in the document are true, accurate, and complete. The certifications shall be signed by a responsible official for the facility. (MOP Volume II, Part 3, §4.11)

C. Requirement to Pay Fees

The permit holder shall pay annual fees in accordance with District Regulation 3, including Schedule P. (Regulation 2-6-402 & 409.13, Regulation 3; MOP Volume II, Part 3, §4.12)

D. Inspection and Entry

Access to Facility: The permit holder shall provide reasonable access to the facility and equipment which is subject to this permit to the APCO and/or to his or her designee.

I. Standard Conditions

(Regulation 1-440, Regulation 2-6-409.3; MOP Volume II, Part 3, §4.14)

E. Records

1. The permit holder must provide any information, records, and reports requested or specified by the APCO. (Regulation 1-441, Regulation 2-6-409.4)
2. Notwithstanding the specific wording in any requirement, all records for federally enforceable requirements shall be maintained for at least five years from the date of entry. (Regulation 2-6-501, Regulation 3; MOP Volume II, Part 3, §4.7)

F. Monitoring Reports

Reports of all required monitoring must be submitted to the District at least once every six months, except where an applicable requirement specifies more frequent reporting. The first reporting period for this permit shall be December 18, 2002, to May 31, 2003. The report shall be submitted by June 30, 2003. Subsequent reports shall be for the following periods: June 1st through November 30th and December 1st through May 31st, and are due on the last day of the month after the end of the reporting period. All instances of non-compliance shall be clearly identified in these reports. The reports shall be certified by the responsible official as true, accurate, and complete. In addition, all instances of non-compliance with the permit shall be reported in writing to the District's Compliance and Enforcement Division within 10 calendar days of the discovery of the incident. Within 30 calendar days of the discovery of any incident of non-compliance, the facility shall submit a written report including the probable cause of non-compliance and any corrective or preventative actions. The reports shall be sent to the following address:

Director of Compliance and Enforcement
Bay Area Air Quality Management District
939 Ellis Street
San Francisco, CA 94109
Attn: Title V Reports

(Regulation 2-6-502, Regulation 3; MOP Volume II, Part 3, §4.7)

G. Compliance Certification

Compliance certifications shall be submitted annually by the responsible official of this facility to the Bay Area Air Quality Management District and to the Environmental Protection Agency. The certification period will be December 1st to November 30th. The certification shall be submitted by December 31st of each year. The certification must list each applicable requirement, the compliance status, whether compliance was continuous or intermittent, the method used to determine compliance, and any other specific information required by the permit. The permit holder may satisfy this requirement through submittal of District-generated Compliance Certification forms. The certification should be directed to the District's Compliance and Enforcement Division at the address above, and a copy of the certification should be sent to the Environmental Protection Agency at the following address:

I. Standard Conditions

Director of the Air Division
USEPA, Region IX
75 Hawthorne Street
San Francisco, CA 94105
Attention: Air-3

(MOP Volume II, Part 3, §4.5 and 4.15)

H. Emergency Provisions

1. The permit holder may seek relief from enforcement action in the event of a breakdown, as defined by Regulation 1-208 of the District's Rules and Regulations, by following the procedures contained in Regulations 1-431 and 1-432. The District will thereafter determine whether breakdown relief will be granted in accordance with Regulation 1-433. (MOP Volume II, Part 3, §4.8)
2. The permit holder may seek relief from enforcement action for a violation of any of the terms and conditions of this permit by applying to the District's Hearing Board for a variance pursuant to Health and Safety Code Section 42350. The Hearing Board will determine after notice and hearing whether variance relief should be granted in accordance with the procedures and standards set forth in Health and Safety Code Section 42350 et seq. (MOP Volume II, Part 3, §4.8)
3. Notwithstanding the foregoing, the granting by the District of breakdown relief or the issuance by the Hearing Board of a variance will not provide relief from federal enforcement. (MOP Volume II, Part 3, §4.8)

I. Severability

In the event that any provision of this permit is invalidated by a court or tribunal of competent jurisdiction, or by the Administrator of the EPA, all remaining portions of the permit shall remain in full force and effect. (Regulation 2-6-409.5; MOP Volume II, Part 3, §4.10)

J. Miscellaneous Conditions

1. The maximum capacity for each source as shown in Table II-A is the maximum allowable capacity. Exceedance of the maximum allowable capacity for any source is a violation of Regulation 2, Rule 1, Section 301. (Regulation 2-1-301)

K. Accidental Release

This facility is subject to 40 CFR Part 68, Chemical Accident Prevention Provisions. The permit holder shall submit a risk management plan (RMP) by the date specified in §68.10. The permit holder shall also certify compliance with the requirements of Part 68 as part of the annual compliance certification, as required by Regulation 2, Rule 6. (40 CFR Part 68, Regulation 2, Rule 6)

II. EQUIPMENT

Table II A - Permitted Sources

Each of the following sources has been issued a permit to operate pursuant to the requirements of BAAQMD Regulation 2, Permits. The capacities in this table are the maximum allowable capacities for each source, pursuant to Standard Condition I.J and Regulation 2-1-301. All combustion sources burn natural gas only.

S #	Description*	Make or Type	Model	Capacity
2	Passenger Body Elpo Dip Tank	Custom Made	N/A	N/A
3	Passenger Body Elpo Oven	Custom Made	N/A	27 MMBTU/hr
41	Passenger Body Phosphate Washer	Custom Made	N/A	18 MMBTU/hr
57	Bumper Topcoat Booth	Custom Made	N/A	4.68 MMBTU/hr
58	Bumper Topcoat Oven	Custom Made	N/A	9.87 MMBTU/hr
59	Bumpers Prime Booth	Custom Made	N/A	17.2 MMBTU/hr
60	Passenger Undercoating Booth	Custom Made	N/A	1.55 MMBTU/hr
61	Passenger Blackout Chassis Booth	Custom Made	N/A	N/A
62	Passenger Gas Tank Paint Booth	Custom Made	N/A	N/A
63	Passenger Gas Tank Oven	Custom Made	N/A	1.2 MMBTU/hr
65	Bumper Prime Oven	Custom Made	N/A	4 MMBTU/hr
71	Passenger Cavity Wax Booth	Custom Made	N/A	N/A
72	Passenger PVC Exterior, Underbody & Engine Wax Booth	Custom Made	N/A	N/A
73	Passenger Exterior Wax Hot Air Dryer	Custom Made	N/A	3 MMBTU/hr
101	Spare Parts ELPO Dip Tank	Custom Made	N/A	N/A
102	Spare Parts ELPO Oven	Custom Made	N/A	10 MMBTU/hr
405	Waste Water Storage Tank	Custom Made	N/A	12,000 Gallon
406	Windshield Washer Fluid Above Ground Storage Tank	Custom Made	N/A	12,000 Gallon
408	Purge Thinner Above Ground Storage Tank	Custom Made	N/A	12,000 Gallon
412	Waste Water Storage Tank	Custom Made	N/A	12,000 Gallon
414	Waste Water Storage Tank	Custom Made	N/A	12,000 Gallon
415	Paint Stripper Tank	Custom Made	N/A	12,000 Gallon

II. Equipment

Table II A - Permitted Sources

Each of the following sources has been issued a permit to operate pursuant to the requirements of BAAQMD Regulation 2, Permits. The capacities in this table are the maximum allowable capacities for each source, pursuant to Standard Condition I.J and Regulation 2-1-301. All combustion sources burn natural gas only.

S #	Description*	Make or Type	Model	Capacity
416	Purge Thinner Storage Tank	Custom Made	N/A	12,000 Gallon
420	ELPO Waste Paint Above Ground Storage Tank	Custom Made	N/A	10,000 Gallon
421	Elpo Paint Pigment Storage	Custom Made	N/A	10,000 Gallon
422	Elpo Paint Resin Above Ground Storage Tank	Custom Made	N/A	10,000 Gallon
437	CPI Separator Storage Tank (water)	Custom Made	N/A	10,000 Gallon
781	Cold Cleaner	Custom Made	N/A	4 Gallon
782	Cold Cleaner	Custom Made	N/A	6 Gallon
786	Cold Cleaner	Graymills	N/A	9 Gallon
787	Cold Cleaner	Graymills	PL-422-A	12 Gallon
794	Cold Cleaner	Custom Made	N/A	8 Gallon
801	Stamping Plant Fugitive Solvent Emissions	Custom Made	N/A	N/A
802	Stamping Plant Fugitive Machining Emissions	Custom Made	N/A	N/A
803	Passenger Sealer Deck Line (Fugitive)	Custom Made	N/A	N/A
804	Passenger Fugitive Repair Priming	Custom Made	N/A	N/A
805	Body Shop Assembly Areas	Custom Made	N/A	N/A
806	GDF #6340, 7 Gasoline Nozzles	Custom Made	N/A	N/A
807	Passenger Anti-Chip Wheelhouse Booth	Custom Made	N/A	N/A
808	Passenger Sealer-Antichip Oven	Custom Made	N/A	N/A
813	Passenger Fugitive Trial Application Area - Bead Sealer	Custom Made	N/A	N/A
826	Passenger BAYCO Parts Cleaning Oven	Custom Made	N/A	2 MMBTU/hr
900	Lime Slurry Tank	Custom Made	N/A	N/A
960	Plastic Plant Booth and General Cleaning	Custom Made	N/A	N/A

II. Equipment

Table II A - Permitted Sources

Each of the following sources has been issued a permit to operate pursuant to the requirements of BAAQMD Regulation 2, Permits. The capacities in this table are the maximum allowable capacities for each source, pursuant to Standard Condition I.J and Regulation 2-1-301. All combustion sources burn natural gas only.

S #	Description*	Make or Type	Model	Capacity
961	Plastic Plant Booth and General Cleaning	Custom Made	N/A	N/A
964	Cold Cleaner	Protecto Seal	N/A	40 Gallon
965	Plastic Plant Storage Thinner Tank	Custom Made	N/A	300 Gallon
992	Plastic Plant Storage Thinner Tank	Custom Made	N/A	300 Gallon
1001	Truck Ed Bath	Custom Made	N/A	N/A
1002	Truck Ed Oven	Custom Made	N/A	8 MMBTU/hr
1003	Truck ED Dry Sand Booth	Custom Made	N/A	3.2 MMBTU/hr
1004	Truck Metal Repair Booth	Custom Made	N/A	N/A
1005	Truck PVC Undercoat Area	Custom Made	N/A	6.4 MMBTU/hr
1006	Truck Antichip Booth	Custom Made	N/A	6.7 MMBTU/hr
1007	Truck Sealer Oven	Custom Made	N/A	N/A
1008	Truck Primer Booth	Custom Made	N/A	26 MMBTU/hr
1009	Truck Prime Oven	Custom Made	N/A	4 MMBTU/hr
1010	Truck Off-line Repair	Custom Made	N/A	N/A
1011	Truck Dry Sand Booth	Custom Made	N/A	3.2 MMBTU/hr
1012	Truck Touch Up Booth	Custom Made	N/A	4 MMBTU/hr
1014	Truck Topcoat Booth	Custom Made	N/A	29.5 MMBTU/hr
1015	Truck Topcoat Oven	Custom Made	N/A	4 MMBTU/hr
1017	Truck Touch Up Booth	Custom Made	N/A	N/A
1018	Truck Blackout Booth	Custom Made	N/A	5.2 MMBTU/hr
1019	Truck Cavity Wax Booth	Custom Made	N/A	N/A
1020	OFF-Line Assembly Paint Hospital (Truck)	Custom Made	N/A	N/A
1021	Truck Underbody, Engine & Exterior Wax Booth	Custom Made	N/A	N/A
1050	Truck Fuel Tank Coating Booth	Custom Made	N/A	5.9 MMBTU/hr
1051	Truck Fuel Tank - Heater Box	Custom Made	N/A	2 MMBTU/hr
1053	Truck Wax Dry Off Booth (Electric)	Custom Made	N/A	N/A
1056	Truck ASH, Boiler #1	Custom Made	N/A	25.1 MMBTU/hr

II. Equipment

Table II A - Permitted Sources

Each of the following sources has been issued a permit to operate pursuant to the requirements of BAAQMD Regulation 2, Permits. The capacities in this table are the maximum allowable capacities for each source, pursuant to Standard Condition I.J and Regulation 2-1-301. All combustion sources burn natural gas only.

S #	Description*	Make or Type	Model	Capacity
1057	Truck ASH, Boiler #2	Custom Made	N/A	25.1 MMBTU/hr
1061	Truck Axle Coating Booth	Custom Made	N/A	N/A
1062	Truck Axle Oven	Custom Made	N/A	N/A
1063	General Truck Axle Booth and Area Cleaning	Custom Made	N/A	N/A
1070	Instrument Panel Booth	Custom Made	N/A	N/A
1071	Instrument Panel Oven	Custom Made	N/A	4 MMBTU/hr
1072	General Cleaning & Paint Cleaning	Custom Made	N/A	N/A
1504	Cold Cleaning Tank	Protecto Seal	N/A	37 Gallon
1509	Protectoseal Cleaning Tank, 40 Gallons	Protecto Seal	N/A	40 Gallon
1510	Cold Cleaner	Protecto Seal	N/A	40 Gallon
1511	Truck Elpo Resin Storage Tank	Custom Made	N/A	10,400 Gallon
1512	Truck Elpo Pigment Storage Tank	Custom Made	N/A	5,200 Gallon
1803	Truck Sealer Deck (Fugitive)	Custom Made	N/A	N/A
1809	Stamping Body & Assembly	Custom Made	N/A	N/A
1810	Cleaning Materials	Custom Made	N/A	N/A
1900	Plastic Parts Adhesion Operation	Custom Made	N/A	N/A
2007	Cold Cleaner	Protecto Seal	27A	18 Gallon
2826	Plastic Plant Bayco Part Cleaning Oven	Custom Made	N/A	2 MMBTU/hr
3007	NPS Dry Off Oven	Custom Made	N/A	5.6 MMBTU/hr
3008	NPS Prime Booth	Custom Made	N/A	44.8 MMBTU/hr
3009	NPS Prime Oven	Custom Made	N/A	19 MMBTU/hr
3014	NPS Topcoat Booth #1	Custom Made	N/A	40 MMBTU/hr
3015	NPS Topcoat Oven #1	Custom Made	N/A	13.3 MMBTU/hr
3016	NPS Topcoat Booth #2	Custom Made	N/A	30.6 MMBTU/hr
3017	NPS Topcoat Oven #2	Custom Made	N/A	13.3 MMBTU/hr
3500	Cold Cleaner	Custom Made	N/A	40 Gallon
3501	Cold Cleaner	Custom Made	N/A	40 Gallon

II. Equipment

Table II A - Permitted Sources

Each of the following sources has been issued a permit to operate pursuant to the requirements of BAAQMD Regulation 2, Permits. The capacities in this table are the maximum allowable capacities for each source, pursuant to Standard Condition I.J and Regulation 2-1-301. All combustion sources burn natural gas only.

S #	Description*	Make or Type	Model	Capacity
3502	Cold Cleaner	Custom Made	N/A	40 Gallon
3503	NPS Purge Thinner Tank	Custom Made	N/A	300 Gallon
3505	NPS Waste Solvent Tank	Custom Made	N/A	300 Gallon
30960	General Cleaning and Painting Cleaning	Custom Made	N/A	N/A

*Note: All combustion sources are fired by natural gas only.

II. Equipment

Table II B – Abatement Devices

A#	Description	Source(s) Controlled	Applicable Requirement	Operating Parameters	Limit or Efficiency
4	Passenger Body Elpo Oven Thermal Oxidizer	S3	BAAQMD Condition # 4281 Part 3	temperature shall be \geq 1200 °F	Destruction Efficiency \geq 90 wt%
102	Spare Parts ELPO Oxidizer	S102	BAAQMD Condition # 207 Part 3(A)(1)	temperature shall be \geq 800 °F	Destruction Efficiency \geq 60 wt%
571	Plastic Plant Thermal Oxidizer	S1070, S1071, S58, S65	BAAQMD Condition # 10320 Part 19	temperature shall be \geq 1400 °F	A571 Destruction Efficiency \geq 98.5%, if inlet concentration of VOC \geq 500 ppmv, as methane; or A571 Destruction Efficiency \geq 95%, if inlet concentration of VOC \leq 500 ppmv, as methane
592	Plastic Plant VOC Concentrator	S59	None	None	None

II. Equipment

Table II B – Abatement Devices

A#	Description	Source(s) Controlled	Applicable Requirement	Operating Parameters	Limit or Efficiency
809	Passenger Line Antichip/Sealer Oven Thermal Oxidizers	S808, S1051, S63	BAAQMD Condition # 207 Part 3(B)(1)	temperature shall be \geq 1400 °F	A808 Destruction Efficiency \geq 98.5%, if inlet concentration of VOC \geq 500 ppmv, as methane; or A808 Destruction Efficiency \geq 95%, if inlet concentration of VOC \leq 500 ppmv, as methane
900	Lime Dust Collector	S900	Regulation 6-301	pressure drop shall be \geq 1 inch water column and \leq 5 inches of water column	Ringelmann 1 for < 3 minutes/hr
900	Lime Dust Collector	S900	Regulation 6-310	pressure drop shall be \geq 1 inch water column and \leq 5 inches of water column	0.15 gr/dscf
900	Lime Dust Collector	S900	Regulation 6-311	pressure drop shall be \geq 1 inch water column and \leq 5 inches of water column	$4.10P^{0.67}$ lb/hr, where P is process weight, ton/hr

II. Equipment

Table II B – Abatement Devices

A#	Description	Source(s) Controlled	Applicable Requirement	Operating Parameters	Limit or Efficiency
1007	Truck Sealer Oven Thermal Oxidizer	S1007	BAAQMD Condition # 9158 Part 2 b & c	temperature shall be \geq 1400 °F	Destruction Efficiency \geq 98%, if VOC concentration \geq 1200 ppm as C1; or Destruction Efficiency > 95-98%, if VOC concentration \geq 500 ppm and \leq 1200 ppm (linearly); or Total Non-methane Organic Hydrocarbon Outlet Concentration \leq 10 ppmv

II. Equipment

Table II B – Abatement Devices

A#	Description	Source(s) Controlled	Applicable Requirement	Operating Parameters	Limit or Efficiency
1008	Truck Prime Booth Thermal Oxidizer	S1008	BAAQMD Condition # 9163 Part 11 b & c	temperature shall be \geq 1400 °F	Destruction Efficiency \geq 98%, if VOC concentration \geq 1200 ppm as C1; or Destruction Efficiency > 95-98%, if VOC concentration \geq 500 ppm and \leq 1200 ppm (linearly); or Total Non- methane Organic Hydrocarbon Outlet Concentration \leq 10 ppmv

II. Equipment

Table II B – Abatement Devices

A#	Description	Source(s) Controlled	Applicable Requirement	Operating Parameters	Limit or Efficiency
1009	Truck Prime Oven Thermal Oxidizer	S1009	BAAQMD Condition # 9158 Part 2 b & c	temperature shall be \geq 1400 °F	Destruction Efficiency \geq 98%, if VOC concentration \geq 1200 ppm as C1; or Destruction Efficiency > 95-98%, if VOC concentration \geq 500 ppm and \leq 1200 ppm (linearly); or Total Non- methane Organic Hydrocarbon Outlet Concentration \leq 10 ppmv

II. Equipment

Table II B – Abatement Devices

A#	Description	Source(s) Controlled	Applicable Requirement	Operating Parameters	Limit or Efficiency
1015	Truck Topcoat Oven Thermal Oxidizer	S1015	BAAQMD Condition # 9158 Part 2 b & c	temperature shall be \geq 1400 °F	Destruction Efficiency \geq 98%, if VOC concentration \geq 1200 ppm as C1; or Destruction Efficiency > 95-98%, if VOC concentration \geq 500 ppm and \leq 1200 ppm (linearly); or Total Non- methane Organic Hydrocarbon Outlet Concentration \leq 10 ppmv
3008	NPS Prime Booth Thermal Oxidizer	S3008	BAAQMD Condition # 14206 Part 11	temperature shall be \geq 1400 °F	Destruction Efficiency \geq 98%, if VOC concentration \geq 1200 ppm as C1; or Destruction Efficiency > 95-98%, if VOC concentration \geq 500 ppm and \leq 1200 ppm (linearly)

II. Equipment

Table II B – Abatement Devices

A#	Description	Source(s) Controlled	Applicable Requirement	Operating Parameters	Limit or Efficiency
3014	NPS Topcoat # 1 Thermal Oxidizer	S3014	BAAQMD Condition # 14207 Part 11	temperature shall be \geq 1400 °F	Destruction Efficiency \geq 98%, if VOC concentration \geq 1200 ppm as C1; or Destruction Efficiency > 95-98%, if VOC concentration \geq 500 ppm and \leq 1200 ppm (linearly)
3016	NPS Topcoat # 2 Thermal Oxidizer	S3016	BAAQMD Condition # 14207 Part 11	temperature shall be \geq 1400 °F	Destruction Efficiency \geq 98%, if VOC concentration \geq 1200 ppm as C1; or Destruction Efficiency > 95-98%, if VOC concentration \geq 500 ppm and \leq 1200 ppm (linearly)

II. Equipment

Table II B – Abatement Devices

A#	Description	Source(s) Controlled	Applicable Requirement	Operating Parameters	Limit or Efficiency
10022	Truck ED-Oven Thermal Oxidizer	S1002	BAAQMD Condition # 9158 Part 2	temperature shall be \geq 1400 °F	Destruction Efficiency \geq 98%, if VOC concentration \geq 1200 ppm as C1; or Destruction Efficiency > 95-98%, if VOC concentration \geq 500 ppm and \leq 1200 ppm (linearly); or Total Non- methane Organic Hydrocarbon Outlet Concentration \leq 10 ppmv
10082	Truck Prime Booth Carbon Concentrator	S1008	None	None	None

II. Equipment

Table II B – Abatement Devices

A#	Description	Source(s) Controlled	Applicable Requirement	Operating Parameters	Limit or Efficiency
10142	Truck Topcoat (Clearcoat) Booth Thermal Oxidizer	S1014	BAAQMD Condition # 9164 Part 2 b & c	temperature shall be \geq 1400 °F	Destruction Efficiency \geq 98%, if VOC concentration \geq 1200 ppm as C1; or Destruction Efficiency > 95-98%, if VOC concentration \geq 500 ppm and \leq 1200 ppm (linearly); or Total Non-methane Organic Hydrocarbon Outlet Concentration \leq 10 ppmv
10144	Topcoat Booth (Basecoat) Carbon Concentrator	S1014	BAAQMD Condition # 9164 Part 4	None	Reduction Efficiency \geq 90 wt%
10612	Truck Axle Particulate Water Scrubber	S1061	Regulation 6-301	None	Ringelmann 1 for < 3 minutes/hr
10612	Truck Axle Particulate Water Scrubber	S1061	Regulation 6-310	None	0.15 gr/dscf
10612	Truck Axle Particulate Water Scrubber	S1061	Regulation 6-311	None	$4.10P^{0.67}$ lb/hr, where P is process weight, ton/hr
10704	IP Booth Water Contact Scrubber	S1070	Regulation 6-301	None	None

II. Equipment

Table II B – Abatement Devices

A#	Description	Source(s) Controlled	Applicable Requirement	Operating Parameters	Limit or Efficiency
10704	IP Booth Water Contact Scrubber	S1070	Regulation 6-310	None	None
10704	IP Booth Water Contact Scrubber	S1070	Regulation 6-311	None	None

Table II C – Significant Sources

Each of the following sources are exempt pursuant to the requirements of BAAQMD Regulation 2, Rule 1. However, they are significant because estimated emissions exceed 2 TPY.

S #	Description*	Make or Type	Model	Capacity
48	Bumper Molding Operation	Custom Made	N/A	N/A

III. GENERALLY APPLICABLE REQUIREMENTS

The permit holder shall comply with all applicable requirements, including those specified in the BAAQMD and SIP Rules and Regulations and other federal requirements cited below. These requirements apply in a general manner to the facility and/or to sources exempt from the requirement to obtain a District Permit to Operate. The District has determined that these requirements will not be violated under normal, routine operations, and that no additional periodic monitoring or reporting to demonstrate compliance is warranted. In cases where a requirement, in addition to being generally applicable, is also specifically applicable to one or more sources, the requirement and the source are also included in Section IV, Source-Specific Applicable Requirements, of this permit. This section also contains provisions that may apply to temporary sources.

The dates in parentheses in the Title column identify the versions of the regulations being cited and are, as applicable:

1. BAAQMD regulation(s): The date(s) of adoption or most recent amendment of the regulation by the District Board of Directors
2. Any federal requirement, including a version of a District regulation that has been approved into the SIP: The most recent date of EPA approval of any portion of the rule, encompassing all actions on the rule through that date

The full language of SIP requirements is on EPA Region 9's website. The address is included at the end of this permit.

NOTE:

There are differences between the current BAAQMD rules and the version of the rules in the SIP. All sources must comply with both versions of the rule until US EPA has reviewed and approved the District's revision of the regulation.

**Table III
 Generally Applicable Requirements**

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)
BAAQMD Regulation 1	General Provisions and Definitions (5/1/01)	N
SIP Regulation 1	General Provisions and Definitions (6/28/99)	Y
BAAQMD Regulation 2, Rule 1	General Requirements (8/1/01)	N
BAAQMD 2-1-429	Federal Emissions Statement (6/7/95)	N
SIP Regulation 2, Rule 1	General Requirements (1/26/99)	Y
BAAQMD Regulation 4	Air Pollution Episode Plan (3/20/91)	N
SIP Regulation 4	Air Pollution Episode Plan (8/06/90)	Y

III. Generally Applicable Requirements

Table III
Generally Applicable Requirements

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)
BAAQMD Regulation 5	Open Burning (3/6/02)	N
SIP Regulation 5	Open Burning (9/4/98)	Y
BAAQMD Regulation 6	Particulate Matter and Visible Emissions (12/19/90)	Y
BAAQMD Regulation 7	Odorous Substances (3/17/82)	N
BAAQMD Regulation 8, Rule 1	Organic Compounds - General Provisions (6/15/94)	Y
BAAQMD Regulation 8, Rule 2	Organic Compounds – Miscellaneous Operations (6/15/94)	Y
BAAQMD Regulation 8, Rule 3	Organic Compounds - Architectural Coatings (11/21/01)	N
SIP Regulation 8, Rule 3	Organic Compounds - Architectural Coatings (02/18/98)	Y
BAAQMD Regulation 8, Rule 4	Organic Compounds – General Solvent and Surface Coating Operations (10/16/02)	N
SIP Regulation 8, Rule 4	Organic Compounds – General Solvent and Surface Coating Operations (12/23/97)	Y
BAAQMD Regulation 8, Rule 15	Organic Compounds – Emulsified and Liquid Asphalts (6/1/94)	Y
BAAQMD Regulation 8, Rule 16	Organic Compounds – Solvent Cleaning Operation (10/17/02)	Y
BAAQMD Regulation 8, Rule 40	Organic Compounds – Aeration of Contaminated Soil and Removal of Underground Storage Tanks (12/5/99)	Y
BAAQMD Regulation 8, Rule 47	Organic Compounds – Air Stripping and Soil Vapor Extractions Operations (6/15/94)	Y
BAAQMD Regulation 8, Rule 49	Organic Compounds - Aerosol Paint Products (12/20/95)	N
SIP Regulation 8, Rule 49	Organic Compounds - Aerosol Paint Products (3/22/95)	Y
BAAQMD Regulation 8, Rule 51	Organic Compounds - Adhesive and Sealant Products (07/17/02)	N
SIP Regulation 8, Rule 51	Organic Compounds – Adhesive and Sealant Products (2/26/02)	Y
BAAQMD Regulation 9, Rule 1	Inorganic Gaseous Pollutants, Sulfur Dioxide (3/15/95)	N
SIP Regulation 9, Rule 1	Inorganic Gaseous Pollutants, Sulfur Dioxide (6/8/99)	Y
BAAQMD Regulation 11, Rule 2	Hazardous Pollutants - Asbestos Demolition, Renovation and Manufacturing (10/7/98)	Y
BAAQMD Regulation 12, Rule 4	Miscellaneous Standards of Performance - Sandblasting (7/11/90)	N

III. Generally Applicable Requirements

Table III
Generally Applicable Requirements

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)
SIP Regulation 12, Rule 4	Miscellaneous Standards of Performance - Sandblasting (9/2/81)	Y
California Health and Safety Code Section 41750 et seq.	Portable Equipment	N
California Health and Safety Code Section 44300 et seq.	Air Toxics "Hot Spots" Information and Assessment Act of 1987	N
40 CFR Part 61, Subpart M	National Emission Standards for Hazardous Air Pollutants – National Emission Standard for Asbestos (6/19/95)	Y

IV. SOURCE-SPECIFIC APPLICABLE REQUIREMENTS

The permit holder shall comply with all applicable requirements, including those specified in the BAAQMD and SIP Rules and Regulations and other federal requirements cited below. The requirements cited in the following tables apply in a specific manner to the indicated source(s).

The dates in parentheses in the Title column identify the versions of the regulations being cited and are, as applicable:

1. BAAQMD regulation(s): The date(s) of adoption or most recent amendment of the regulation by the District Board of Directors.
2. Any federal requirement, including a version of a District regulation that has been approved into the SIP: The most recent date of EPA approval of any portion of the rule, encompassing all actions on the rule through that date

The full text of each permit condition cited is included in Section VI, Permit Conditions, of this permit. The full language of SIP requirements is on EPA Region 9's website. The address is included at the end of this permit. All other text may be found in the regulations themselves.

Table IV - A
Source-specific Applicable Requirements
S2 - PASSENGER BODY ELPO DIP TANK

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
BAAQMD Regulation 6	Particulate Matter and Visible Emissions (12/19/90)		
6-301	Ringelmann No. 1 Limitation	Y	
6-305	Visible Particles	Y	
6-310	Particulate Weight Limitation	Y	
6-311	General Operations	Y	
6-401	Appearance of Emissions	Y	
BAAQMD Regulation 8, Rule 13	Light and Medium Duty Motor Vehicle Assembly Plants (12/20/95)		
8-13-306	Limits, Electrophoretic Primer	Y	
8-13-503	Usage Records, Electrophoretic Primer	Y	

IV. Source-specific Applicable Requirements

Table IV - A
Source-specific Applicable Requirements
S2 - PASSENGER BODY ELPO DIP TANK

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
8-13-504	Air Pollution Abatement Equipment, Recordkeeping Requirements	Y	
BAAQMD Condition # 207			
Part 1.a	Emissions Limitation (basis: Cumulative Increase)	Y	
Part 1.c	Emissions Limitation -- Calculations Procedure (basis: Cumulative Increase)	Y	
Part 1.d	Emissions Limitation -- Calculated or Controlled Emissions (basis: Cumulative Increase)	Y	
Part 2.a	Material Usage Limitations -- VOC Material Content and Use Table (basis: Cumulative Increase)	Y	
Part 2.b	Material Usage Limitations -- Alternative Usage and/or VOC Limitation Petition (basis: Cumulative Increase)	Y	
Part 2.c	Material Usage Limitations -- Applicable Requirements (basis: Regulation 1-102)	Y	
Part 5.a	Recordkeeping and Reporting -- All Records (basis: Cumulative Increase)	Y	
Part 5.b	Recordkeeping and Reporting -- Monthly Report (basis: Cumulative Increase)	Y	
Part 6	Sampling (basis: Regulation 1-441)	Y	
Part 7	Enforcement (basis: Regulation 1-401)	Y	
Part 8.a	Miscellaneous -- Good Working Order and Operation (basis: Cumulative Increase)	Y	
Part 8.b	Miscellaneous -- Definition of "NUMMI" (basis: Regulation 1-241)	N	
Part 8.c	Miscellaneous -- Audit of Records (basis: Regulation 1-441)	Y	
Part 8.d	Miscellaneous -- Plant Access (basis: Regulation 1-440)	Y	
Part 8.e	Miscellaneous -- No Violations (basis: Regulation 1-103)	Y	
Part 9	Severability (basis: Regulation 1-109)	Y	
Part 10	Corrective Action Plan (basis: Cumulative Increase)	Y	
Part 10.a	Notification and Corrective Action Plan (basis: Cumulative Increase)	Y	
Part 10.b	Corrective Action Plan Commitment (basis: Cumulative Increase)	Y	
Part 10.c	Time Periods Effective (basis: Cumulative Increase)	Y	
Part 10.d	Annual Total Limit Requirement (basis: Cumulative Increase)	Y	
Part 10.e	Total Emission Limit Requirement (basis: Cumulative Increase)	Y	
Part 10.f	Correcting An Exceedance (basis: Cumulative Increase)	Y	

IV. Source-specific Applicable Requirements

Table IV - B
Source-specific Applicable Requirements
S3 - PASSENGER BODY ELPO OVEN

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
BAAQMD Regulation 1	General Provisions and Definitions (5/2/01)		
1-523	Parametric Monitoring and Recordkeeping Procedures	N	
1-523.1	Parametric monitor periods of inoperation	Y	
1-523.2	Limits on periods of inoperation	Y	
1-523.3	Reports of Violations	N	
1-523.4	Records	Y	
1-523.5	Maintenance and calibration	N	
SIP Regulation 1	General Provisions and Definitions (6/28/99)		
1-523	Parametric Monitoring and Recordkeeping Procedures	Y ¹	
1-523.3	Reports of Violations	Y ¹	
BAAQMD Regulation 6	Particulate Matter and Visible Emissions (12/19/90)		
6-301	Ringelmann No. 1 Limitation	Y	
6-305	Visible Particles	Y	
6-310	Particulate Weight Limitation	Y	
6-311	General Operations	Y	
6-401	Appearance of Emissions	Y	
BAAQMD Regulation 8, Rule 13	Light and Medium Duty Motor Vehicle Assembly Plants (12/20/95)		
8-13-306	Limits, Electrophoretic Primer	Y	
8-13-503	Usage Records, Electrophoretic Primer	Y	
8-13-504	Air Pollution Abatement Equipment, Recordkeeping Requirements	Y	
BAAQMD Condition # 207			
Part 1.a	Emissions Limitation (basis: Cumulative Increase)	Y	
Part 1.c	Emissions Limitation -- Calculations Procedure (basis: Cumulative Increase)	Y	

IV. Source-specific Applicable Requirements

Table IV - B
Source-specific Applicable Requirements
S3 - PASSENGER BODY ELPO OVEN

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
Part 1.d	Emissions Limitation – Calculated or Controlled Emissions (basis: Cumulative Increase)	Y	
Part 2.a	Material Usage Limitations -- VOC Material Content and Use Table (basis: Cumulative Increase)	Y	
Part 2.b	Material Usage Limitations – Alternative Usage and/or VOC Limitation Petition (basis: Cumulative Increase)	Y	
Part 2.c	Material Usage Limitations – Applicable Requirements (basis: Regulation 1-102)	Y	
Part 4.b	Allowable Temperature Excursion (basis: Cumulative Increase)	Y	
Part 4.c	Recording of Allowable Temperature Excursions (basis: Cumulative Increase)	Y	
Part 4.d	Revision of Allowable Temperature Excursions (basis: Cumulative Increase)	Y	
Part 5.a	Recordkeeping and Reporting – All Records (basis: Cumulative Increase)	Y	
Part 5.b	Recordkeeping and Reporting -- Monthly Report (basis: Cumulative Increase)	Y	
Part 5.c	Recordkeeping and Reporting -- Temperature Records (basis: Regulation 1-523)	N	
Part 6	Sampling (basis: Regulation 1-441)	Y	
Part 7	Enforcement (basis: Regulation 1-401)	Y	
Part 8.a	Miscellaneous -- Good Working Order and Operation (basis: Cumulative Increase)	Y	
Part 8.b	Miscellaneous -- Definition of “NUMMI” (basis: Regulation 1-241)	N	
Part 8.c	Miscellaneous -- Audit of Records (basis: Regulation 1-441)	Y	
Part 8.d	Miscellaneous -- Plant Access (basis: Regulation 1-440)	Y	
Part 8.e	Miscellaneous -- No Violations (basis: Regulation 1-103)	Y	
Part 9	Severability (basis: Regulation 1-109)	Y	
Part 10	Corrective Action Plan (basis: Cumulative Increase)	Y	
Part 10.a	Notification and Corrective Action Plan (basis: Cumulative Increase)	Y	
Part 10.b	Corrective Action Plan Commitment (basis: Cumulative Increase)	Y	
Part 10.c	Time Periods Effective (basis: Cumulative Increase)	Y	
Part 10.d	Annual Total Limit Requirement (basis: Cumulative Increase)	Y	
Part 10.e	Total Emission Limit Requirement (basis: Cumulative Increase)	Y	
Part 10.f	Correcting An Exceedance (basis: Cumulative Increase)	Y	

IV. Source-specific Applicable Requirements

Table IV - B
Source-specific Applicable Requirements
S3 - PASSENGER BODY ELPO OVEN

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
BAAQMD Condition # 4281			
Part 1	Abatement Operating Requirements (basis: BACT)	Y	
Part 2	A4 Operating Requirement (basis: Cumulative Increase)	Y	
Part 3	Destruction Efficiency Requirement for A4 (basis: Cumulative Increase)	Y	
Part 4	Temperature Monitoring (basis: BACT, Regulation 1-523)	Y	
Part 5	Destruction Efficiency Source Test Requirement (basis: Cumulative Increase)	Y	
Part 6	Destruction Efficiency Source Test Requirement (basis: Cumulative Increase)	Y	
Part 8	Source Test Requirement (basis: Cumulative Increase)	Y	
Part 9	Records Retention (basis: Cumulative Increase)	Y	

Table IV - C
Source-specific Applicable Requirements
S41 – PASSENGER BODY PHOSPHATE WASHER

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
BAAQMD Regulation 6	Particulate Matter and Visible Emissions (12/19/90)		
6-301	Ringelmann No. 1 Limitation	Y	
6-305	Visible Particles	Y	
6-310	Particulate Weight Limitation	Y	
6-311	General Operations	Y	
6-401	Appearance of Emissions	Y	
BAAQMD Regulation 9, Rule 1	Inorganic Gaseous Pollutants - Sulfur Dioxide (3/15/95)		
9-1-301	Limitations on Ground Level Concentrations	Y	
9-1-302	General Emission Limitations	Y	

IV. Source-specific Applicable Requirements

Table IV - C
Source-specific Applicable Requirements
S41 – PASSENGER BODY PHOSPHATE WASHER

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
BAAQMD Condition # 17797			
Part 3	Limitation on Fuel Usage (basis: Regulation 2-6-409.2)	Y	

Table IV - D
Source-specific Applicable Requirements
S57 – BUMPER TOPCOAT BOOTH
S58 – BUMPER TOPCOAT OVEN
S59 – BUMPERS PRIME BOOTH
S65 – BUMPER PRIME OVEN

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
BAAQMD Regulation 1	General Provisions and Definitions (5/2/01)		
1-523	Parametric Monitoring and Recordkeeping Procedures	N	
1-523.1	Parametric monitor periods of inoperation	Y	
1-523.2	Limits on periods of inoperation	Y	
1-523.3	Reports of Violations	N	
1-523.4	Records	Y	
1-523.5	Maintenance and calibration	N	
SIP Regulation 1	General Provisions and Definitions (6/28/99)		
1-523	Parametric Monitoring and Recordkeeping Procedures	Y ¹	
1-523.3	Reports of Violations	Y ¹	
BAAQMD Regulation 6	Particulate Matter and Visible Emissions (12/19/90)		
6-301	Ringelmann No. 1 Limitation	Y	
6-305	Visible Particles	Y	
6-310	Particulate Weight Limitation	Y	

IV. Source-specific Applicable Requirements

Table IV - D
Source-specific Applicable Requirements
S57 – BUMPER TOPCOAT BOOTH
S58 – BUMPER TOPCOAT OVEN
S59 – BUMPERS PRIME BOOTH
S65 – BUMPER PRIME OVEN

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
6-311	General Operations	Y	
6-401	Appearance of Emissions	Y	
BAAQMD Regulation 8, Rule 13	Light and Medium Duty Motor Vehicle Assembly Plants (12/20/95)		
8-13-307	Limits, Flexible Parts Coating	Y	
8-13-406	Compliance Verification	Y	
8-13-503	Usage Records, Coatings	Y	
8-13-504	Air Pollution Abatement Equipment, Recordkeeping Requirements	Y	
BAAQMD Condition # 10320			
Part 1	All Conditions Are In Effect (basis: Cumulative Increase)	Y	
Part 2	Natural Gas Usage Limit (basis: Cumulative Increase)	Y	
Part 3	Fuel Requirements (basis: Cumulative Increase)	Y	
Part 4	NOx Limit (basis: Cumulative Increase)	Y	
Part 5	CO Limit (basis: Cumulative Increase)	Y	
Part 6	Toxics Limitations (basis: Toxics)	N	
Part 7	Records (basis: Cumulative Increase)	Y	
Part 8	Abatement Requirement (basis: BACT)	Y	
Part 9	POC Emissions Limit (basis: Cumulative Increase)	Y	
Part 10	Coatings Usage Limit (basis: Cumulative Increase; MOP Volume II, Part 3, Section 4.7)	Y	
Part 11	Adhesion Promoter (basis: Cumulative Increase)	Y	
Part 12	Transfer Efficiency Requirement (basis: BACT)	Y	
Part 13	Minimization of Solvent (basis: BACT)	Y	
Part 14	Records (basis: Cumulative Increase)	Y	
Part 15	Particulate Abatement Requirements (basis: BACT, Cumulative Increase)	Y	
Part 16	Abatement Requirement (basis: BACT, Cumulative Increase)	Y	
Part 17	Abatement Requirement (basis: BACT, Cumulative Increase)	Y	
Part 18	Net Mass Emissions (basis: BACT, Cumulative Increase)	Y	

IV. Source-specific Applicable Requirements

Table IV - D
Source-specific Applicable Requirements
S57 – BUMPER TOPCOAT BOOTH
S58 – BUMPER TOPCOAT OVEN
S59 – BUMPERS PRIME BOOTH
S65 – BUMPER PRIME OVEN

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
Part 19	Thermal Oxidizer Temperature Requirements (basis: BACT, Cumulative Increase)	Y	
Part 20	Destruction Efficiency Requirements (basis: BACT, Cumulative Increase)	Y	
Part 21	NOx Limit for Thermal Oxidizers (basis: Cumulative Increase)	Y	
Part 22	Continuous Temperature Recording (basis: BACT, Cumulative Increase)	Y	
Part 23	Annual Source Test Requirement (basis: BACT, Cumulative Increase)	Y	
Part 24	Source Test Report (basis: Cumulative Increase; MOP Volume II, Part 3, Section 4.7)	Y	
Part 26	Allowable Temperature Excursion (basis: Cumulative Increase)	Y	
Part 27	Recording of Allowable Temperature Excursions (basis: Cumulative Increase)	Y	
Part 28	Revision of Allowable Temperature Excursions (basis: Cumulative Increase)	Y	
Part 47	Source Test of A592 (basis: BACT)	Y	

IV. Source-specific Applicable Requirements

Table IV - E
Source-specific Applicable Requirements
S60 – PASSENGER UNDERCOATING BOOTH
S61 – PASSENGER BLACKOUT CHASSIS BOOTH
S803 – PASSENGER SEALER DECK LINE (FUGITIVE)
S804 – PASSENGER FUGITIVE REPAIR PRIMING
S807 – PASSENGER ANTI-CHIP WHEELHOUSE BOOTH
S813 – PASSENGER FUGITIVE TRIAL APPLICATION AREA – BEAD SEALER

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
BAAQMD Regulation 6	Particulate Matter and Visible Emissions (12/19/90)		
6-301	Ringelmann No. 1 Limitation	Y	
6-305	Visible Particles	Y	
6-310	Particulate Weight Limitation	Y	
6-311	General Operations	Y	
6-401	Appearance of Emissions	Y	
BAAQMD Regulation 8, Rule 13	Light and Medium Duty Motor Vehicle Assembly Plants (12/20/95)		
8-13-302	Final Limits, Topcoat, Spray Primer, Primer Surfacer	Y	
8-13-406	Compliance Verification	Y	
8-13-503	Usage Records, Coatings	Y	
BAAQMD Condition # 207			
Part 1.a	Emissions Limitation (basis: Cumulative Increase)	Y	
Part 1.c	Emissions Limitation -- Calculations Procedure (basis: Cumulative Increase)	Y	
Part 1.d	Emissions Limitation – Calculated or Controlled Emissions (basis: Cumulative Increase)	Y	
Part 2.a	Material Usage Limitations -- VOC Material Content and Use Table (basis: Cumulative Increase)	Y	
Part 2.b	Material Usage Limitations – Alternative Usage and/or VOC Limitation Petition (basis: Cumulative Increase)	Y	
Part 2.c	Material Usage Limitations – Applicable Requirements (basis: Regulation 1-102)	Y	
Part 5.a	Recordkeeping and Reporting – All Records (basis: Cumulative Increase)	Y	

IV. Source-specific Applicable Requirements

Table IV - E
Source-specific Applicable Requirements
S60 – PASSENGER UNDERCOATING BOOTH
S61 – PASSENGER BLACKOUT CHASSIS BOOTH
S803 – PASSENGER SEALER DECK LINE (FUGITIVE)
S804 – PASSENGER FUGITIVE REPAIR PRIMING
S807 – PASSENGER ANTI-CHIP WHEELHOUSE BOOTH
S813 – PASSENGER FUGITIVE TRIAL APPLICATION AREA – BEAD SEALER

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
Part 5.b	Recordkeeping and Reporting -- Monthly Report (basis: Cumulative Increase)	Y	
Part 5.c	Recordkeeping and Reporting -- Temperature Records (basis: Regulation 1-523)	N	
Part 6	Sampling (basis: Regulation 1-441)	Y	
Part 7	Enforcement (basis: Regulation 1-401)	Y	
Part 8.a	Miscellaneous -- Good Working Order and Operation (basis: Cumulative Increase)	Y	
Part 8.b	Miscellaneous -- Definition of "NUMMI" (basis: Regulation 1-241)	N	
Part 8.c	Miscellaneous -- Audit of Records (basis: Regulation 1-441)	Y	
Part 8.d	Miscellaneous -- Plant Access (basis: Regulation 1-440)	Y	
Part 8.e	Miscellaneous -- No Violations (basis: Regulation 1-103)	Y	
Part 9	Severability (basis: Regulation 1-109)	Y	
Part 10	Corrective Action Plan (basis: Cumulative Increase)	Y	
Part 10.a	Notification and Corrective Action Plan (basis: Cumulative Increase)	Y	
Part 10.b	Corrective Action Plan Commitment (basis: Cumulative Increase)	Y	
Part 10.c	Time Periods Effective (basis: Cumulative Increase)	Y	
Part 10.d	Annual Total Limit Requirement (basis: Cumulative Increase)	Y	
Part 10.e	Total Emission Limit Requirement (basis: Cumulative Increase)	Y	
Part 10.f	Correcting An Exceedance (basis: Cumulative Increase)	Y	

IV. Source-specific Applicable Requirements

Table IV - F
Source-specific Applicable Requirements
S62 – PASSENGER GAS TANK PAINT BOOTH
S63 – PASSENGER GAS TANK OVEN

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
BAAQMD Regulation 1	General Provisions and Definitions (5/2/01)		
1-523	Parametric Monitoring and Recordkeeping Procedures	N	
1-523.1	Parametric monitor periods of inoperation	Y	
1-523.2	Limits on periods of inoperation	Y	
1-523.3	Reports of Violations	N	
1-523.4	Records	Y	
1-523.5	Maintenance and calibration	N	
SIP Regulation 1	General Provisions and Definitions (6/28/99)		
1-523	Parametric Monitoring and Recordkeeping Procedures	Y ¹	
1-523.3	Reports of Violations	Y ¹	
BAAQMD Regulation 6	Particulate Matter and Visible Emissions (12/19/90)		
6-301	Ringelmann No. 1 Limitation	Y	
6-305	Visible Particles	Y	
6-310	Particulate Weight Limitation	Y	
6-311	General Operations	Y	
6-401	Appearance of Emissions	Y	
BAAQMD Regulation 8, Rule 13	Light and Medium Duty Motor Vehicle Assembly Plants (12/20/95)		
8-13-308	Limits, Off-Line Coating	Y	
8-13-406	Compliance Verification	Y	
8-13-503	Usage Records, Coatings	Y	
BAAQMD Condition # 207			
Part 1.a	Emissions Limitation (basis: Cumulative Increase)	Y	
Part 1.c	Emissions Limitation -- Calculations Procedure (basis: Cumulative Increase)	Y	

IV. Source-specific Applicable Requirements

Table IV - F
Source-specific Applicable Requirements
S62 – PASSENGER GAS TANK PAINT BOOTH
S63 – PASSENGER GAS TANK OVEN

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
Part 1.d	Emissions Limitation – Calculated or Controlled Emissions (basis: Cumulative Increase)	Y	
Part 2.a	Material Usage Limitations -- VOC Material Content and Use Table (basis: Cumulative Increase)	Y	
Part 2.b	Material Usage Limitations – Alternative Usage and/or VOC Limitation Petition (basis: Cumulative Increase)	Y	
Part 2.c	Material Usage Limitations – Applicable Requirements (basis: Regulation 1-102)	Y	
Part 5.a	Recordkeeping and Reporting – All Records (basis: Cumulative Increase)	Y	
Part 5.b	Recordkeeping and Reporting -- Monthly Report (basis: Cumulative Increase)	Y	
Part 5.c	Recordkeeping and Reporting -- Temperature Records (basis: Regulation 1-523)	N	
Part 6	Sampling (basis: Regulation 1-441)	Y	
Part 7	Enforcement (basis: Regulation 1-401)	Y	
Part 8.a	Miscellaneous -- Good Working Order and Operation (basis: Cumulative Increase)	Y	
Part 8.b	Miscellaneous -- Definition of “NUMMI” (basis: Regulation 1-241)	N	
Part 8.c	Miscellaneous -- Audit of Records (basis: Regulation 1-441)	Y	
Part 8.d	Miscellaneous -- Plant Access (basis: Regulation 1-440)	Y	
Part 8.e	Miscellaneous -- No Violations (basis: Regulation 1-103)	Y	
Part 9	Severability (basis: Regulation 1-109)	Y	
Part 10	Corrective Action Plan (basis: Cumulative Increase)	Y	
Part 10.a	Notification and Corrective Action Plan (basis: Cumulative Increase)	Y	
Part 10.b	Corrective Action Plan Commitment (basis: Cumulative Increase)	Y	
Part 10.c	Time Periods Effective (basis: Cumulative Increase)	Y	
Part 10.d	Annual Total Limit Requirement (basis: Cumulative Increase)	Y	
Part 10.e	Total Emission Limit Requirement (basis: Cumulative Increase)	Y	
Part 10.f	Correcting An Exceedance (basis: Cumulative Increase)	Y	

IV. Source-specific Applicable Requirements

Table IV - G
Source-specific Applicable Requirements
S71 – PASSENGER CAVITY WAX BOOTH
S72 – PASSENGER PVC EXTERIOR, UNDERBODY & ENGINE WAX BOOTH
S73 – PASSENGER EXTERIOR WAX HOT AIR DRYER

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
BAAQMD Regulation 6	Particulate Matter and Visible Emissions (12/19/90)		
6-301	Ringelmann No. 1 Limitation	Y	
6-305	Visible Particles	Y	
6-310	Particulate Weight Limitation	Y	
6-311	General Operations	Y	
6-401	Appearance of Emissions	Y	
BAAQMD Regulation 8, Rule 13	Light and Medium Duty Motor Vehicle Assembly Plants (12/20/95)		
8-13-302	Final Limits, Topcoat, Spray Primer, Primer Surfacer	Y	
8-13-406	Compliance Verification	Y	
8-13-503	Usage Records, Coatings	Y	
BAAQMD Condition # 207			
Part 1.a	Emissions Limitation (basis: Cumulative Increase)	Y	
Part 1.c	Emissions Limitation -- Calculations Procedure (basis: Cumulative Increase)	Y	
Part 1.d	Emissions Limitation – Calculated or Controlled Emissions (basis: Cumulative Increase)	Y	
Part 1.e	Emissions Limitation – VOC Emissions Limit for Wax Booth & Oven (basis: Cumulative Increase)	Y	
Part 2.a	Material Usage Limitations -- VOC Material Content and Use Table (basis: Cumulative Increase)	Y	
Part 2.b	Material Usage Limitations – Alternative Usage and/or VOC Limitation Petition (basis: Cumulative Increase)	Y	
Part 2.c	Material Usage Limitations – Applicable Requirements (basis: Regulation 1-102)	Y	
Part 5.a	Recordkeeping and Reporting – All Records (basis: Cumulative Increase)	Y	
Part 5.b	Recordkeeping and Reporting -- Monthly Report (basis: Cumulative Increase)	Y	

IV. Source-specific Applicable Requirements

Table IV - G
Source-specific Applicable Requirements
S71 – PASSENGER CAVITY WAX BOOTH
S72 – PASSENGER PVC EXTERIOR, UNDERBODY & ENGINE WAX BOOTH
S73 – PASSENGER EXTERIOR WAX HOT AIR DRYER

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
Part 5.c	Recordkeeping and Reporting -- Temperature Records (basis: Regulation 1-523)	N	
Part 6	Sampling (basis: Regulation 1-441)	Y	
Part 7	Enforcement (basis: Regulation 1-401)	Y	
Part 8.a	Miscellaneous -- Good Working Order and Operation (basis: Cumulative Increase)	Y	
Part 8.b	Miscellaneous -- Definition of "NUMMI" (basis: Regulation 1-241)	N	
Part 8.c	Miscellaneous -- Audit of Records (basis: Regulation 1-441)	Y	
Part 8.d	Miscellaneous -- Plant Access (basis: Regulation 1-440)	Y	
Part 8.e	Miscellaneous -- No Violations (basis: Regulation 1-103)	Y	
Part 9	Severability (basis: Regulation 1-109)	Y	
Part 10	Corrective Action Plan (basis: Cumulative Increase)	Y	
Part 10.a	Notification and Corrective Action Plan (basis: Cumulative Increase)	Y	
Part 10.b	Corrective Action Plan Commitment (basis: Cumulative Increase)	Y	
Part 10.c	Time Periods Effective (basis: Cumulative Increase)	Y	
Part 10.d	Annual Total Limit Requirement (basis: Cumulative Increase)	Y	
Part 10.e	Total Emission Limit Requirement (basis: Cumulative Increase)	Y	
Part 10.f	Correcting An Exceedance (basis: Cumulative Increase)	Y	

Table IV - H
Source-specific Applicable Requirements
S101 – SPARE PARTS ELPO DIP TANK
S102 – SPARE PARTS ELPO OVEN

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
BAAQMD Regulation 1	General Provisions and Definitions (5/2/01)		
1-523	Parametric Monitoring and Recordkeeping Procedures	N	
1-523.1	Parametric monitor periods of inoperation	Y	

IV. Source-specific Applicable Requirements

Table IV - H
Source-specific Applicable Requirements
S101 – SPARE PARTS ELPO DIP TANK
S102 – SPARE PARTS ELPO OVEN

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
1-523.2	Limits on periods of inoperation	Y	
1-523.3	Reports of Violations	N	
1-523.4	Records	Y	
1-523.5	Maintenance and calibration	N	
SIP Regulation 1	General Provisions and Definitions (6/28/99)		
1-523	Parametric Monitoring and Recordkeeping Procedures	Y ¹	
1-523.3	Reports of Violations	Y ¹	
BAAQMD Regulation 6	Particulate Matter and Visible Emissions (12/19/90)		
6-301	Ringelmann No. 1 Limitation	Y	
6-305	Visible Particles	Y	
6-310	Particulate Weight Limitation	Y	
6-311	General Operations	Y	
6-401	Appearance of Emissions	Y	
BAAQMD Regulation 8, Rule 13	Light and Medium Duty Motor Vehicle Assembly Plants (12/20/95)		
8-13-306	Limits, Electrophoretic Primer	Y	
8-13-503	Usage Records, Electrophoretic Primer	Y	
8-13-504	Air Pollution Abatement Equipment, Recordkeeping Requirements	Y	
BAAQMD Condition # 207			
Part 1.a	Emissions Limitation (basis: Cumulative Increase)	Y	
Part 1.c	Emissions Limitation -- Calculations Procedure (basis: Cumulative Increase)	Y	
Part 1.d	Emissions Limitation – Calculated or Controlled Emissions (basis: Cumulative Increase)	Y	
Part 2.a	Material Usage Limitations -- VOC Material Content and Use Table (basis: Cumulative Increase)	Y	
Part 2.b	Material Usage Limitations – Alternative Usage and/or VOC Limitation Petition (basis: Cumulative Increase)	Y	

IV. Source-specific Applicable Requirements

Table IV - H
Source-specific Applicable Requirements
S101 – SPARE PARTS ELPO DIP TANK
S102 – SPARE PARTS ELPO OVEN

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
Part 2.c	Material Usage Limitations – Applicable Requirements (basis: Regulation 1-102)	Y	
Part 3	Emission Control Equipment (basis: BACT)	Y	
Part 3.a.1	Emission Control Equipment – Destruction Efficiency Requirement for Spare Parts Elpo Oven Catalytic Thermal Oxidizer (basis: Cumulative Increase)	Y	
Part 3.a.2	Emission Control Equipment -- Source Test Requirement for Spare Parts Elpo Oven Catalytic Thermal Oxidizer (basis: Cumulative Increase)	Y	
Part 3.a.3	Emission Control Equipment – Source Test Report for Spare Parts Elpo Oven Catalytic Thermal Oxidizer (basis: Cumulative Increase, Regulation 2-6-501, MOP Volume II, Part 3, Section 4.7)	Y	
Part 4.a.1	Allowable Temperature Excursion(s) – A102 (basis: BACT)	Y	
Part 4.a.2	Allowable Temperature Excursion(s) – A102 (basis: BACT)		
Part 4.b	Allowable Temperature Excursion(s) – Definition (basis: Cumulative Increase)	Y	
Part 4.c	Allowable Temperature Excursion(s) – Recording of Allowable Temperature Excursions (basis: Cumulative Increase)	Y	
Part 4.d	Allowable Temperature Excursion(s) – Revision of Allowable Temperature Excursions (basis: Cumulative Increase)	Y	
Part 5.a	Recordkeeping and Reporting – All Records (basis: Cumulative Increase)	Y	
Part 5.b	Recordkeeping and Reporting -- Monthly Report (basis: Cumulative Increase)	Y	
Part 5.c	Recordkeeping and Reporting -- Temperature Records (basis: Regulation 1-523)	N	
Part 6	Sampling (basis: Regulation 1-441)	Y	
Part 7	Enforcement (basis: Regulation 1-401)	Y	
Part 8.a	Miscellaneous -- Good Working Order and Operation (basis: Cumulative Increase)	Y	
Part 8.b	Miscellaneous -- Definition of “NUMMI” (basis: Regulation 1-241)	N	
Part 8.c	Miscellaneous -- Audit of Records (basis: Regulation 1-441)	Y	
Part 8.d	Miscellaneous -- Plant Access (basis: Regulation 1-440)	Y	
Part 8.e	Miscellaneous -- No Violations (basis: Regulation 1-103)	Y	
Part 9	Severability (basis: Regulation 1-109)	Y	
Part 10	Corrective Action Plan (basis: Cumulative Increase)	Y	

IV. Source-specific Applicable Requirements

Table IV - H
Source-specific Applicable Requirements
S101 – SPARE PARTS ELPO DIP TANK
S102 – SPARE PARTS ELPO OVEN

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
Part 10.a	Notification and Corrective Action Plan (basis: Cumulative Increase)	Y	
Part 10.b	Corrective Action Plan Commitment (basis: Cumulative Increase)	Y	
Part 10.c	Time Periods Effective (basis: Cumulative Increase)	Y	
Part 10.d	Annual Total Limit Requirement (basis: Cumulative Increase)	Y	
Part 10.e	Total Emission Limit Requirement (basis: Cumulative Increase)	Y	
Part 10.f	Correcting An Exceedance (basis: Cumulative Increase)	Y	

Table IV - I
Source-specific Applicable Requirements
S781 - COLD CLEANER, S782 - COLD CLEANER ,
S786 - COLD CLEANER, S787 - COLD CLEANER,
S794 - COLD CLEANER,

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
BAAQMD Regulation 8, Rule 16	Organic Compounds – Solvent Cleaning Operations (10/16/2002)		
8-16-303	Cold Cleaner Requirements	Y	
8-16-303.1	General Operating Requirements	Y	
8-16-303.1.1	Maintain equipment in good working order.	Y	
8-16-303.1.2	Leak Repair Requirement	Y	
8-16-303.1.3	Solvent Storage or Disposal – Evaporation Prevention	Y	
8-16-303.1.4	Waste Solvent Disposal	Y	
8-16-303.1.4(a)	Covered Containers for Waste Solvent Awaiting Pick-up	Y	
8-16-303.1.4(b)	On-site Waste Treatment	Y	
8-16-303.1.5	Solvent Evaporation Minimization Devices shall not be Removed	Y	
8-16-303.1.6	Solvent Spray Requirements	Y	
8-16-303.2	Cold Cleaner Operating Requirements	Y	

IV. Source-specific Applicable Requirements

Table IV - I
Source-specific Applicable Requirements
S781 - COLD CLEANER, S782 - COLD CLEANER ,
S786 - COLD CLEANER, S787 - COLD CLEANER,
S794 - COLD CLEANER,

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
8-16-303.2.1	Solvent shall be Drained from Cleaned Parts	Y	
8-16-303.2.2	Solvent Agitation	Y	
8-16-303.2.3	Solvent Cleaning of Porous or Absorbent Materials is Prohibited	Y	
8-16-303.3	Cold Cleaner General Equipment Requirements	Y	
8-16-303.3.1	Container	Y	
8-16-303.3.2	Solvent Evaporation Reduction for Idle Equipment	Y	
8-16-303.3.3	Used Solvent Returned to Container	Y	
8-16-303.3.4	Label Stating Operating Requirements	Y	
8-16-303.4	Control Device (one of the following)	Y	
8-16-303.4.1	Freeboard Ratio ≥ 0.75	Y	
8-16-303.5	VOC content < 0.42 pounds per gallon or comply with 8-16-303.4.1 and <u>other options</u>	Y	
8-16-501	Solvent Records	Y	
8-16-501.2	Facility-wide Monthly Solvent Usage Records	Y	
8-16-501.3	Annual Records of Type and Amount of Solvent Used for Wipe Cleaning	Y	
8-16-501.5	Records Retained	Y	

IV. Source-specific Applicable Requirements

Table IV - J
Source-specific Applicable Requirements
S405 – WASTE WATER STORAGE TANK
S408 – PURGE THINNER ABOVE GROUND STORAGE TANK
S414 – WASTE WATER STORAGE TANK

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
BAAQMD Regulation 8, Rule 5	Storage of Organic Liquids (12/15/99)		
8-5-301	Storage Tank Smaller than 150 m ³	Y	
8-5-302	Above Ground Gasoline Storage Tank Smaller than 75 m ³	Y	
8-5-303	Above Ground Storage Tank Larger than 37.5 m ³ and Smaller than 75 m ³	Y	
8-5-501	Records	Y	

Table IV - K
Source-specific Applicable Requirements
S406 – WINDSHIELD WASHER FLUID ABOVE GROUND STORAGE TANK

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
BAAQMD Regulation 8, Rule 5	Storage of Organic Liquids (12/15/99)		
8-5-301	Storage Tank Smaller than 150 m ³	Y	
8-5-302	Above Ground Gasoline Storage Tank Smaller than 75 m ³	Y	
8-5-303	Above Ground Storage Tank Larger than 37.5 m ³ and Smaller than 75 m ³	Y	
8-5-501	Records	Y	
BAAQMD Condition # 10709			
Part 1	Throughput Limit (basis: Cumulative Increase)	Y	
Part 2	Type of Material Storage Limit (basis: Cumulative Increase)	Y	
Part 3	Records (basis: Cumulative Increase)	Y	

IV. Source-specific Applicable Requirements

Table IV - L
Source-specific Applicable Requirements
S412 – WASTE WATER STORAGE TANK
S415 – PAINT STRIPPER TANK
S416 – PURGE THINNER STORAGE TANK
S420– ELPO WASTE PAINT ABOVE GROUND STORAGE TANK
S421 – ELPO PAINT PIGMENT STORAGE
S422 – ELPO PAINT RESIN ABOVE GROUND STORAGE TANK
S437 – CPI SEPARATOR STORAGE TANK

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
BAAQMD Regulation 8, Rule 5	Storage of Organic Liquids (12/15/99)		
8-5-117	Exemption, Low Vapor Pressure	Y	

Table IV - N
Source-specific Applicable Requirements
S801 – STAMPING PLANT FUGITIVE SOLVENT EMISSIONS

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
BAAQMD Regulation 8, Rule 2	Miscellaneous Operation (6/15/94)		
8-2-301	Miscellaneous Operations	Y	
BAAQMD Condition # 207			
Part 1.a	Emissions Limitation (basis: Cumulative Increase)	Y	
Part 1.b	Fugitive Emissions Limitations (basis: Cumulative Increase)	Y	
Part 1.c	Emissions Limitation -- Calculations Procedure (basis: Cumulative Increase)	Y	
Part 1.d	Emissions Limitation – Calculated or Controlled Emissions (basis: Cumulative Increase)	Y	
Part 2.a	Material Usage Limitations -- VOC Material Content and Use Table (basis: Cumulative Increase)	Y	

IV. Source-specific Applicable Requirements

Table IV - N
Source-specific Applicable Requirements
S801 – STAMPING PLANT FUGITIVE SOLVENT EMISSIONS

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
Part 2.b	Material Usage Limitations – Alternative Usage and/or VOC Limitation Petition (basis: Cumulative Increase)	Y	
Part 2.c	Material Usage Limitations – Applicable Requirements (basis: Regulation 1-102)	Y	
Part 5.a	Recordkeeping and Reporting – All Records (basis: Cumulative Increase)	Y	
Part 5.b	Recordkeeping and Reporting -- Monthly Report (basis: Cumulative Increase)	Y	
Part 5.c	Recordkeeping and Reporting -- Temperature Records (basis: Regulation 1-523)	N	
Part 6	Sampling (basis: Regulation 1-441)	Y	
Part 7	Enforcement (basis: Regulation 1-401)	Y	
Part 8.a	Miscellaneous -- Good Working Order and Operation (basis: Cumulative Increase)	Y	
Part 8.b	Miscellaneous -- Definition of “NUMMI” (basis: Regulation 1-241)	N	
Part 8.c	Miscellaneous -- Audit of Records (basis: Regulation 1-441)	Y	
Part 8.d	Miscellaneous -- Plant Access (basis: Regulation 1-440)	Y	
Part 8.e	Miscellaneous -- No Violations (basis: Regulation 1-103)	Y	
Part 9	Severability (basis: Regulation 1-109)	Y	
Part 10	Corrective Action Plan (basis: Cumulative Increase)	Y	
Part 10.a	Notification and Corrective Action Plan (basis: Cumulative Increase)	Y	
Part 10.b	Corrective Action Plan Commitment (basis: Cumulative Increase)	Y	
Part 10.c	Time Periods Effective (basis: Cumulative Increase)	Y	
Part 10.d	Annual Total Limit Requirement (basis: Cumulative Increase)	Y	
Part 10.e	Total Emission Limit Requirement (basis: Cumulative Increase)	Y	
Part 10.f	Correcting An Exceedance (basis: Cumulative Increase)	Y	

IV. Source-specific Applicable Requirements

Table IV – O
Source-specific Applicable Requirements
S802 – STAMPING PLANT FUGITIVE MACHINING EMISSIONS

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
BAAQMD Regulation 6	Particulate Matter and Visible Emissions (12/19/90)		
6-301	Ringelmann No. 1 Limitation	Y	
6-305	Visible Particles	Y	
6-310	Particulate Weight Limitation	Y	
6-311	General Operations	Y	
6-401	Appearance of Emissions	Y	

IV. Source-specific Applicable Requirements

Table IV - P
Source-specific Applicable Requirements
S805 – BODY SHOP ASSEMBLY AREAS

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
BAAQMD Regulation 6	Particulate Matter and Visible Emissions (12/19/90)		
6-301	Ringelmann No. 1 Limitation	Y	
6-305	Visible Particles	Y	
6-310	Particulate Weight Limitation	Y	
6-311	General Operations	Y	
6-401	Appearance of Emissions	Y	
BAAQMD Regulation 8, Rule 13	Light and Medium Duty Motor Vehicle Assembly Plants (12/20/95)		
8-13-302	Final Limits, Topcoat, Spray Primer, Primer Surfacer	Y	
8-13-302.1	Final Limits, Spray Primer	Y	
8-13-406	Compliance Verification	Y	
8-13-503	Usage Records, Coatings	Y	
BAAQMD Condition # 207			
Part 1.a	Emissions Limitation (basis: Cumulative Increase)	Y	
Part 1.b	Emissions Limitation – Fugitive Emissions (basis: Cumulative Increase)	Y	
Part 1.c	Emissions Limitation -- Calculations Procedure (basis: Cumulative Increase)	Y	
Part 1.d	Emissions Limitation – Calculated or Controlled Emissions (basis: Cumulative Increase)	Y	
Part 1.e	Emissions Limitation – VOC Emissions Limit for Wax Booth & Oven (basis: Cumulative Increase)	Y	
Part 2.a	Material Usage Limitations -- VOC Material Content and Use Table (basis: Cumulative Increase)	Y	
Part 2.b	Material Usage Limitations – Alternative Usage and/or VOC Limitation Petition (basis: Cumulative Increase)	Y	
Part 2.c	Material Usage Limitations – Applicable Requirements (basis: Regulation 1-102)	Y	
Part 5.a	Recordkeeping and Reporting – All Records (basis: Cumulative Increase)	Y	
Part 5.b	Recordkeeping and Reporting -- Monthly Report (basis: Cumulative Increase)	Y	

IV. Source-specific Applicable Requirements

Table IV - P
Source-specific Applicable Requirements
S805 – BODY SHOP ASSEMBLY AREAS

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
Part 5.c	Recordkeeping and Reporting -- Temperature Records (basis: Regulation 1-523)	N	
Part 6	Sampling (basis: Regulation 1-441)	Y	
Part 7	Enforcement (basis: Regulation 1-401)	Y	
Part 8.a	Miscellaneous -- Good Working Order and Operation (basis: Cumulative Increase)	Y	
Part 8.b	Miscellaneous -- Definition of "NUMMI" (basis: Regulation 1-241)	N	
Part 8.c	Miscellaneous -- Audit of Records (basis: Regulation 1-441)	Y	
Part 8.d	Miscellaneous -- Plant Access (basis: Regulation 1-440)	Y	
Part 8.e	Miscellaneous -- No Violations (basis: Regulation 1-103)	Y	
Part 9	Severability (basis: Regulation 1-109)	Y	
Part 10	Corrective Action Plan (basis: Cumulative Increase)	Y	
Part 10.a	Notification and Corrective Action Plan (basis: Cumulative Increase)	Y	
Part 10.b	Corrective Action Plan Commitment (basis: Cumulative Increase)	Y	
Part 10.c	Time Periods Effective (basis: Cumulative Increase)	Y	
Part 10.d	Annual Total Limit Requirement (basis: Cumulative Increase)	Y	
Part 10.e	Total Emission Limit Requirement (basis: Cumulative Increase)	Y	
Part 10.f	Correcting An Exceedance (basis: Cumulative Increase)	Y	
Part 10.e	Total Emission Limit Requirement (basis: Cumulative Increase)	Y	
Part 10.f	Correcting An Exceedance (basis: Cumulative Increase)	Y	

IV. Source-specific Applicable Requirements

Table IV - Q
Source-specific Applicable Requirements
S806 – GDF # 6340

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
BAAQMD Regulation 8, Rule 7	Organic Compounds - Gasoline Dispensing Facilities (11/17/99)		
8-7-301	Phase I Requirements	Y	
8-7-301.1	Requirement for CARB Phase I System	Y	
8-7-301.2	Installation of Phase I Equipment per CARB Requirements	Y	
8-7-301.3	Submerged Fill Pipes	Y	
8-7-301.5	Maintenance of Phase I Equipment per Manufacturers Guidelines	Y	
8-7-301.6	Leak-Free, Vapor-Tight	Y	
8-7-301.7	Poppeted Drybreaks	Y	
8-7-301.8	No Coaxial Phase 1	Y	
8-7-301.9	CARB-Certified Anti-Rotational Coupler or Swivel Adapter	Y	
8-7-301.10	System Vapor Recovery Rate	Y	
8-7-301.11	CARB-Certified Spill Box	Y	
8-7-301.12	Drain Valve Permanently Plugged	Y	
8-7-302	Phase II Requirements	Y	
8-7-302.1	Requirement for CARB Certified Phase II System	Y	
8-7-302.2	Maintenance of Phase II System per CARB Requirements	Y	
8-7-302.3	Maintenance of All Equipment as Specified by Manufacturer	Y	
8-7-302.4	Repair of Defective Parts Within 7 Days	Y	
8-7-302.5	Leak-Free, Vapor-Tight	Y	
8-7-302.6	Insertion Interlocks	Y	
8-7-302.7	Built-In Vapor Check Valve	Y	
8-7-302.8	Minimum Liquid Removal Rate	Y	
8-7-302.9	Coaxial Hose	Y	
8-7-302.10	Galvanized Piping or Flexible Tubing	Y	
8-7-302.11	ORVR Compatible	Y	
8-7-302.12	Liquid Retainment Limit	Y	
8-7-302.13	Spitting Limit	Y	
8-7-303	Topping Off	Y	
8-7-304	Certification Requirements	Y	

IV. Source-specific Applicable Requirements

Table IV - Q
Source-specific Applicable Requirements
S806 – GDF # 6340

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
8-7-306	Prohibition of Use	Y	
8-7-307	Posting of Operating Instructions	Y	
8-7-308	Operating Practices	Y	
8-7-309	Contingent Vapor Recovery Requirements	Y	
8-7-311	Exempt Tank Requirements	Y	
8-7-313	Requirements for New or Modified Phase II Installations	Y	
8-7-315	Pressure Vacuum Valve Requirement, Underground Storage Tank	Y	
8-7-316	Pressure Vacuum Valve Requirement, Aboveground Storage Tanks and Vaulted Below-Grade Storage Tanks	Y	
8-7-406	Testing Requirements, New and Modified Installations	Y	
8-7-501	Burden of Proof	Y	
8-7-502	Right of Access	Y	
8-7-503	Record Keeping Requirements	Y	
SIP Regulation 8, Rule 7	Organic Compounds - Gasoline Dispensing Facilities (6/1/94)		
8-7-401	Certification of New Installations	Y	
BAAQMD Condition # 7799			
Part 1	Toxics Limit (basis: Cumulative Increase)	N	

IV. Source-specific Applicable Requirements

Table IV – R
Source-specific Applicable Requirements
S808 – PASSENGER ANTICHIP OVEN

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
BAAQMD Regulation 1	General Provisions and Definitions (5/2/01)		
1-523	Parametric Monitoring and Recordkeeping Procedures	N	
1-523.1	Parametric monitor periods of inoperation	Y	
1-523.2	Limits on periods of inoperation	Y	
1-523.3	Reports of Violations	N	
1-523.4	Records	Y	
1-523.5	Maintenance and calibration	N	
SIP Regulation 1	General Provisions and Definitions (6/28/99)		
1-523	Parametric Monitoring and Recordkeeping Procedures	Y ¹	
1-523.3	Reports of Violations	Y ¹	
BAAQMD Regulation 6	Particulate Matter and Visible Emissions (12/19/90)		
6-301	Ringelmann No. 1 Limitation	Y	
6-305	Visible Particles	Y	
6-310	Particulate Weight Limitation	Y	
6-311	General Operations	Y	
6-401	Appearance of Emissions	Y	
BAAQMD Regulation 8, Rule 13	Light and Medium Duty Motor Vehicle Assembly Plants (12/20/95)		
8-13-302	Final Limits, Topcoat, Spray Primer, Primer Surfacer	Y	
8-13-302.1	Final Limits, Spray Primer	Y	
8-13-406	Compliance Verification	Y	
8-13-503	Usage Records, Coatings	Y	
8-13-504	Air Pollution Abatement Equipment, Recordkeeping Requirements	Y	
BAAQMD Condition # 207			
Part 1.a	Emissions Limitation (basis: Cumulative Increase)	Y	
Part 1.c	Emissions Limitation -- Calculations Procedure (basis: Cumulative Increase)	Y	

IV. Source-specific Applicable Requirements

Table IV – R
Source-specific Applicable Requirements
S808 – PASSENGER ANTICHIP OVEN

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
Part 1.d	Emissions Limitation – Calculated or Controlled Emissions (basis: Cumulative Increase)	Y	
Part 2.a	Material Usage Limitations -- VOC Material Content and Use Table (basis: Cumulative Increase)	Y	
Part 2.b	Material Usage Limitations – Alternative Usage and/or VOC Limitation Petition (basis: Cumulative Increase)	Y	
Part 2.c	Material Usage Limitations – Applicable Requirements (basis: Regulation 1-102)	Y	
Part 3.b.	Thermal Oxidizer Annual Source Testing Requirement (basis: BACT)	Y	
Part 4	Allowable Temperature Excursions (basis: BACT)	Y	
Part 5.a	Recordkeeping and Reporting – All Records (basis: Cumulative Increase)	Y	
Part 5.b	Recordkeeping and Reporting -- Monthly Report (basis: Cumulative Increase)	Y	
Part 5.c	Recordkeeping and Reporting -- Temperature Records (basis: Regulation 1-523)	N	
Part 6	Sampling (basis: Regulation 1-441)	Y	
Part 7	Enforcement (basis: Regulation 1-401)	Y	
Part 8.a	Miscellaneous -- Good Working Order and Operation (basis: Cumulative Increase)	Y	
Part 8.b	Miscellaneous -- Definition of “NUMMI” (basis: Regulation 1-241)	N	
Part 8.c	Miscellaneous -- Audit of Records (basis: Regulation 1-441)	Y	
Part 8.d	Miscellaneous -- Plant Access (basis: Regulation 1-440)	Y	
Part 8.e	Miscellaneous -- No Violations (basis: Regulation 1-103)	Y	
Part 9	Severability (basis: Regulation 1-109)	Y	
Part 10	Corrective Action Plan (basis: Cumulative Increase)	Y	
Part 10.a	Notification and Corrective Action Plan (basis: Cumulative Increase)	Y	
Part 10.b	Corrective Action Plan Commitment (basis: Cumulative Increase)	Y	
Part 10.c	Time Periods Effective (basis: Cumulative Increase)	Y	
Part 10.d	Annual Total Limit Requirement (basis: Cumulative Increase)	Y	
Part 10.e	Total Emission Limit Requirement (basis: Cumulative Increase)	Y	
Part 10.f	Correcting An Exceedance (basis: Cumulative Increase)	Y	
Part 10.e	Total Emission Limit Requirement (basis: Cumulative Increase)	Y	
Part 10.f	Correcting An Exceedance (basis: Cumulative Increase)	Y	

IV. Source-specific Applicable Requirements

Table IV - T
Source-specific Applicable Requirements
S1504 - COLD CLEANING TANK, S2007 - COLD CLEANER,

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
BAAQMD Regulation 8, Rule 16	Organic Compounds – Solvent Cleaning Operations (10/16/2002)		
8-16-303	Cold Cleaner Requirements	Y	
8-16-303.1	General Operating Requirements	Y	
8-16-303.1.1	Maintain equipment in good working order.	Y	
8-16-303.1.2	Leak Repair Requirement	Y	
8-16-303.1.3	Solvent Storage or Disposal – Evaporation Prevention	Y	
8-16-303.1.4	Waste Solvent Disposal	Y	
8-16-303.1.4(a)	Covered Containers for Waste Solvent Awaiting Pick-up	Y	
8-16-303.1.4(b)	On-site Waste Treatment	Y	
8-16-303.1.5	Solvent Evaporation Minimization Devices shall not be Removed	Y	
8-16-303.1.6	Solvent Spray Requirements	Y	
8-16-303.2	Cold Cleaner Operating Requirements	Y	
8-16-303.2.1	Solvent shall be Drained from Cleaned Parts	Y	
8-16-303.2.2	Solvent Agitation	Y	
8-16-303.2.3	Solvent Cleaning of Porous or Absorbent Materials is Prohibited	Y	
8-16-303.3	Cold Cleaner General Equipment Requirements	Y	
8-16-303.3.1	Container	Y	
8-16-303.3.2	Solvent Evaporation Reduction for Idle Equipment	Y	
8-16-303.3.3	Used Solvent Returned to Container	Y	
8-16-303.3.4	Label Stating Operating Requirements	Y	
8-16-303.4	Control Device (one of the following)	Y	
8-16-303.4.1	Freeboard Ratio ≥ 0.75	Y	
8-16-303.5	VOC content < 0.42 pounds per gallon or comply with 8-16-303.4.1 and <u>other options</u>	Y	
8-16-501	Solvent Records	Y	
8-16-501.2	Facility-wide Monthly Solvent Usage Records	Y	
8-16-501.3	Annual Records of Type and Amount of Solvent Used for Wipe Cleaning	Y	
8-16-501.5	Records Retained	Y	

IV. Source-specific Applicable Requirements

Table IV - T
Source-specific Applicable Requirements
S1504 - COLD CLEANING TANK, S2007 - COLD CLEANER,

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
BAAQMD Condition # 16780			
Part 1	POC Emissions Limit (basis: Cumulative Increase)	Y	
Part 2	Usage Limit & Monthly Recordkeeping (basis: Cumulative Increase)	Y	
Part 3	Records (basis: Cumulative Increase)	Y	

IV. Source-specific Applicable Requirements

Table IV - U
Source-specific Applicable Requirements
S826 – PASSENGER BAYCO PARTS CLEANING OVEN

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
BAAQMD Regulation 6	Particulate Matter and Visible Emissions (12/19/90)		
6-301	Ringelmann No. 1 Limitation	Y	
6-305	Visible Particles	Y	
6-310	Particulate Weight Limitation	Y	
6-311	General Operations	Y	
6-401	Appearance of Emissions	Y	
BAAQMD Regulation 9, Rule 1	Inorganic Gaseous Pollutants - Sulfur Dioxide (3/15/95)		
9-1-301	Limitations on Ground Level Concentrations	Y	
9-1-302	General Emission Limitations	Y	

Table IV - V
Source-specific Applicable Requirements
S900 – LIME SLURRY TANK

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
BAAQMD Regulation 6	Particulate Matter and Visible Emissions (12/19/90)		
6-301	Ringelmann No. 1 Limitation	Y	
6-305	Visible Particles	Y	
6-310	Particulate Weight Limitation	Y	
6-311	General Operations	Y	
6-401	Appearance of Emissions	Y	
BAAQMD Condition # 4159		Y	
Part 1	Dust Collector Requirement (basis: Cumulative Increase)	Y	

IV. Source-specific Applicable Requirements

Table IV - V
Source-specific Applicable Requirements
S900 – LIME SLURRY TANK

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
Part 2	Pressure Drop Requirements (basis: Regulation 2-6-409.2)	Y	
Part 3	Records (basis: Regulation 2-6-409.2)	Y	

Table IV - W
Source-specific Applicable Requirements
S960 – PLASTIC PLANT BOOTH AND GENERAL CLEANING S961 – BUMPER RELEASE CLEANING & POLISH

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
BAAQMD Regulation 1	General Provisions and Definitions (5/2/01)		
1-523	Parametric Monitoring and Recordkeeping Procedures	N	
1-523.1	Parametric monitor periods of inoperation	Y	
1-523.2	Limits on periods of inoperation	Y	
1-523.3	Reports of Violations	N	
1-523.4	Records	Y	
1-523.5	Maintenance and calibration	N	
SIP Regulation 1	General Provisions and Definitions (6/28/99)		
1-523	Parametric Monitoring and Recordkeeping Procedures	Y ¹	
1-523.3	Reports of Violations	Y ¹	
BAAQMD Regulation 8, Rule 13	Light and Medium Duty Motor Vehicle Assembly Plants (12/20/95)		
8-13-309	Surface Preparation and Cleanup Solvent	Y	
8-13-503	Usage Records, Coatings	Y	
BAAQMD Condition # 10320			
Part 1	All Conditions Are In Effect (basis: Cumulative Increase)	Y	

IV. Source-specific Applicable Requirements

Table IV - W
Source-specific Applicable Requirements
S960 – PLASTIC PLANT BOOTH AND GENERAL CLEANING S961 – BUMPER RELEASE
CLEANING & POLISH

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
Part 6	Toxics Limitations (basis: Toxics)	N	
Part 31	POC Emissions Limit (basis: Cumulative Increase)	Y	
Part 32	Collected & Recovery Requirement (basis: BACT)	Y	
Part 33	Enclosed Collection System (basis: BACT)	Y	
Part 34	Records (basis: Regulation 2-6-409.2)	Y	

Table IV - X
Source-specific Applicable Requirements

S964 - COLD CLEANER

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
BAAQMD Regulation 8, Rule 16	Organic Compounds – Solvent Cleaning Operations (10/16/2002)		
8-16-303	Cold Cleaner Requirements	Y	
8-16-303.1	General Operating Requirements	Y	
8-16-303.1.1	Maintain equipment in good working order.	Y	
8-16-303.1.2	Leak Repair Requirement	Y	
8-16-303.1.3	Solvent Storage or Disposal – Evaporation Prevention	Y	
8-16-303.1.4	Waste Solvent Disposal	Y	
8-16-303.1.4(a)	Covered Containers for Waste Solvent Awaiting Pick-up	Y	
8-16-303.1.4(b)	On-site Waste Treatment	Y	
8-16-303.1.5	Solvent Evaporation Minimization Devices shall not be Removed	Y	
8-16-303.1.6	Solvent Spray Requirements	Y	
8-16-303.2	Cold Cleaner Operating Requirements	Y	
8-16-303.2.1	Solvent shall be Drained from Cleaned Parts	Y	

IV. Source-specific Applicable Requirements

Table IV - X
Source-specific Applicable Requirements

S964 - COLD CLEANER

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
8-16-303.2.2	Solvent Agitation	Y	
8-16-303.2.3	Solvent Cleaning of Porous or Absorbent Materials is Prohibited	Y	
8-16-303.3	Cold Cleaner General Equipment Requirements	Y	
8-16-303.3.1	Container	Y	
8-16-303.3.2	Solvent Evaporation Reduction for Idle Equipment	Y	
8-16-303.3.3	Used Solvent Returned to Container	Y	
8-16-303.3.4	Label Stating Operating Requirements	Y	
8-16-303.4	Control Device (one of the following)	Y	
8-16-303.4.1	Freeboard Ratio ≥ 0.75	Y	
8-16-303.5	VOC content ≤ 0.42 pounds per gallon or comply with 8-16-303.4.1 and other options	Y	
8-16-501	Solvent Records	Y	
8-16-501.2	Facility-wide Monthly Solvent Usage Records	Y	
8-16-501.3	Annual Records of Type and Amount of Solvent Used for Wipe Cleaning	Y	
8-16-501.5	Records Retained	Y	
BAAQMD Condition # 10320			
Part 1	All Conditions Are In Effect (basis: Cumulative Increase)	Y	
Part 6	Toxics Limitations (basis: Toxics)	N	
Part 31	POC Emissions Limit (basis: Cumulative Increase)	Y	
Part 32	Collected & Recovery Requirement (basis: BACT)	Y	
Part 33	Enclosed Collection System (basis: BACT)	Y	
Part 34	Records (basis: Regulation 2-6-409.2)	Y	

IV. Source-specific Applicable Requirements

Table IV - Y
Source-specific Applicable Requirements
S965 – PLASTIC PLANT THINNER STORAGE TANK
S992 – PLASTIC PLANT THINNER STORAGE TANK

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
BAAQMD Regulation 8, Rule 5	Storage of Organic Liquids (12/15/99)		
8-5-301	Storage Tank Smaller than 150 m ³	Y	
8-5-303	Above Ground Storage Tank Larger than 37.5 m ³ and Smaller than 75 m ³	Y	
8-5-501	Records	Y	
BAAQMD Condition # 10320			
Part 1	All Conditions Are In Effect (basis: Cumulative Increase)	Y	
Part 6	Toxics Limitations (basis: Toxics)	N	
Part 35	Material Storage Limitations (basis: Cumulative Increase)	Y	
Part 36	Submerged Fill Pipe (basis: Regulation 8-5-301)	Y	

IV. Source-specific Applicable Requirements

Table IV - AA
Source-specific Applicable Requirements
S1001 – TRUCK ED BATH

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
BAAQMD Regulation 6	Particulate Matter and Visible Emissions (12/19/90)		
6-301	Ringelmann No. 1 Limitation	Y	
6-305	Visible Particles	Y	
6-310	Particulate Weight Limitation	Y	
6-311	General Operations	Y	
6-401	Appearance of Emissions	Y	
BAAQMD Regulation 8, Rule 13	Light and Medium Duty Motor Vehicle Assembly Plants (12/20/95)		
8-13-306	Limits, Electrophoretic Primer	Y	
8-13-503	Usage Records, Electrophoretic Primer	Y	
8-13-504	Air Pollution Abatement Equipment, Recordkeeping Requirements	Y	
40 CFR 60 Subpart A	General Provisions (7/1/2000)		
60.1	Applicability.	Y	
60.2	Definitions.	Y	
60.3	Units and abbreviations.	Y	
60.4	Address.	Y	
60.5	Determination of construction or modification.	Y	
60.6	Review of plans.	Y	
60.7	Notification and record keeping.	Y	
60.8	Performance tests.	Y	
60.9	Availability of information.	Y	
60.10	State authority.	Y	
60.11	Compliance with standards and maintenance requirements.	Y	
60.12	Circumvention.	Y	
60.13	Monitoring requirements.	Y	
60.14	Modification.	Y	
60.15	Reconstruction.	Y	
60.16	Priority list.	Y	
60.17	Incorporations by reference.	Y	
60.18	General control device requirements.	Y	

IV. Source-specific Applicable Requirements

Table IV - AA
Source-specific Applicable Requirements
S1001 – TRUCK ED BATH

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
60.19	General notification and reporting requirements.	Y	
40 CFR 60 Subpart MM	Standards of Performance for Automobile and Light Duty Truck Surface Coating Operations (12/24/80)		
60.392	Standards for Volatile Organic Compounds	Y	
60.392(a)	Prime Coat Operation	Y	
60.392(b)	Guide Coat Operation	Y	
60.392(c)	Topcoat Operation	Y	
60.393	Performance Test and Compliance Provisions	Y	
60.394	Monitoring of Emissions and Operations	Y	
60.395	Reporting and Recordkeeping Requirements	Y	
60.396	Reference Methods and Procedures	Y	
60.397	Modifications	Y	
BAAQMD Condition # 9156			
Part 1	Offset Baseline (basis: Regulation 2-2-302)	Y	
Part 2	Testing of Abatement Equipment (basis: Cumulative Increase)	Y	
Part 3	Toxics Limitations (basis: Toxics)	N	
Part 4	Monthly Reports (basis: Cumulative Increase)	Y	
Part 5	VOC Emission Limit (basis: Cumulative Increase)	Y	
Part 6	Toxics Limits (basis: Toxics)	N	
Part 7	Source Obligation, Relaxation of Enforceable Conditions (basis: Regulation 2-2-412)	Y	
Part 8	Natural Gas Usage Limits (basis: Cumulative Increase)	Y	
Part 9	Definition of Year and Month (basis: Cumulative Increase)	Y	
BAAQMD Condition # 9257			
Part 1	VOC Content Limitation (basis: BACT, Cumulative Increase)	Y	
Part 2	Usage Limit (basis: Cumulative Increase)	Y	
Part 3	Monthly Records (basis: Cumulative Increase)	Y	
Part 5	VOC Emission Limit (basis: Cumulative Increase)	Y	

IV. Source-specific Applicable Requirements

Table IV - AB
Source-specific Applicable Requirements
S1002 – TRUCK ED OVEN

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
BAAQMD Regulation 1	General Provisions and Definitions (5/2/01)		
1-523	Parametric Monitoring and Recordkeeping Procedures	N	
1-523.1	Parametric monitor periods of inoperation	Y	
1-523.2	Limits on periods of inoperation	Y	
1-523.3	Reports of Violations	N	
1-523.4	Records	Y	
1-523.5	Maintenance and calibration	N	
SIP Regulation 1	General Provisions and Definitions (6/28/99)		
1-523	Parametric Monitoring and Recordkeeping Procedures	Y ¹	
1-523.3	Reports of Violations	Y ¹	
BAAQMD Regulation 6	Particulate Matter and Visible Emissions (12/19/90)		
6-301	Ringelmann No. 1 Limitation	Y	
6-305	Visible Particles	Y	
6-310	Particulate Weight Limitation	Y	
6-311	General Operations	Y	
6-401	Appearance of Emissions	Y	
BAAQMD Regulation 8, Rule 13	Light and Medium Duty Motor Vehicle Assembly Plants (12/20/95)		
8-13-306	Limits, Electrophoretic Primer	Y	
8-13-503	Usage Records, Electrophoretic Primer	Y	
8-13-504	Air Pollution Abatement Equipment, Recordkeeping Requirements	Y	
40 CFR 60 Subpart A	General Provisions (7/1/2000)		
60.1	Applicability.	Y	
60.2	Definitions.	Y	
60.3	Units and abbreviations.	Y	
60.4	Address.	Y	
60.5	Determination of construction or modification.	Y	
60.6	Review of plans.	Y	
60.7	Notification and record keeping.	Y	
60.8	Performance tests.	Y	

IV. Source-specific Applicable Requirements

Table IV - AB
Source-specific Applicable Requirements
S1002 – TRUCK ED OVEN

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
60.9	Availability of information.	Y	
60.10	State authority.	Y	
60.11	Compliance with standards and maintenance requirements.	Y	
60.12	Circumvention.	Y	
60.13	Monitoring requirements.	Y	
60.14	Modification.	Y	
60.15	Reconstruction.	Y	
60.16	Priority list.	Y	
60.17	Incorporations by reference.	Y	
60.18	General control device requirements.	Y	
60.19	General notification and reporting requirements.	Y	
40 CFR 60 Subpart MM	Standards of Performance for Automobile and Light Duty Truck Surface Coating Operations (12/24/80)		
60.392	Standards for Volatile Organic Compounds	Y	
60.392(a)	Prime Coat Operation	Y	
60.392(b)	Guide Coat Operation	Y	
60.392(c)	Topcoat Operation	Y	
60.393	Performance Test and Compliance Provisions	Y	
60.394	Monitoring of Emissions and Operations	Y	
60.395	Reporting and Recordkeeping Requirements	Y	
60.396	Reference Methods and Procedures	Y	
60.397	Modifications	Y	
BAAQMD Condition # 9156			
Part 1	Offset Baseline (basis: Regulation 2-2-302)	Y	
Part 2	Testing of Abatement Equipment (basis: Cumulative Increase)	Y	
Part 3	Toxics Limitations (basis: Toxics)	N	
Part 4	Monthly Reports (basis: Cumulative Increase)	Y	
Part 5	VOC Emission Limit (basis: Cumulative Increase)	Y	
Part 6	Toxics Limits (basis: Toxics)	N	
Part 7	Source Obligation, Relaxation of Enforceable Conditions (basis: Regulation 2-2-412)	Y	
Part 8	Natural Gas Usage Limits (basis: Cumulative Increase)	Y	
Part 9	Definition of Year and Month (basis: Cumulative Increase)	Y	

IV. Source-specific Applicable Requirements

Table IV - AB
Source-specific Applicable Requirements
S1002 – TRUCK ED OVEN

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
BAAQMD Condition # 9158			
Part 1	Abatement Requirement (basis: BACT)	Y	
Part 2	Destruction Efficiency or Total Non-methane Organic Hydrocarbon Concentration Requirement (basis: BACT)	Y	
Part 3	Continuous Temperature Monitor (basis: BACT)	Y	
Part 4	Annual Source Test Requirement (basis: BACT)	Y	
Part 5	Records (basis: BACT)	Y	
Part 6	Fuel Limitations (basis: Cumulative Increase)	Y	
Part 7	NOx Limit (basis: Cumulative Increase)	Y	
Part 8	VOC Emission Limit (basis: Cumulative Increase)	Y	
Part 9	Allowable Temperature Excursion (basis: Cumulative Increase)	Y	
Part 10	Recording of Allowable Temperature Excursions (basis: Cumulative Increase)	Y	
Part 11	Revision of Allowable Temperature Excursions (basis: Cumulative Increase)	Y	
Part 12	Abatement Equipment Operation Requirement (basis: Cumulative Increase)	Y	

Table IV - AC
Source-specific Applicable Requirements
S1003 – TRUCK ED DRY SAND BOOTH
S1004 – TRUCK METAL REPAIR BOOTH
S1011 – TRUCK DRY SAND BOOTH

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
BAAQMD Regulation 6	Particulate Matter and Visible Emissions (12/19/90)		
6-301	Ringelmann No. 1 Limitation	Y	
6-305	Visible Particles	Y	
6-310	Particulate Weight Limitation	Y	

IV. Source-specific Applicable Requirements

Table IV - AC
Source-specific Applicable Requirements
S1003 – TRUCK ED DRY SAND BOOTH
S1004 – TRUCK METAL REPAIR BOOTH
S1011 – TRUCK DRY SAND BOOTH

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
6-311	General Operations	Y	
6-401	Appearance of Emissions	Y	
BAAQMD Condition # 9156			
Part 1	Offset Baseline (basis: Regulation 2-2-302)	Y	
Part 2	Testing of Abatement Equipment (basis: Cumulative Increase)	Y	
Part 3	Toxics Limitations (basis: Toxics)	N	
Part 4	Monthly Reports (basis: Cumulative Increase)	Y	
Part 5	VOC Emission Limit (basis: Cumulative Increase)	Y	
Part 6	Toxics Limits (basis: Toxics)	N	
Part 7	Source Obligation, Relaxation of Enforceable Conditions (basis: Regulation 2-2-412)	Y	
Part 8	Natural Gas Usage Limits (basis: Cumulative Increase)	Y	
Part 9	Definition of Year and Month (basis: Cumulative Increase)	Y	

Table IV - AD
Source-specific Applicable Requirements
S1005 – TRUCK PVC UNDERCOAT AREA

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
BAAQMD Regulation 6	Particulate Matter and Visible Emissions (12/19/90)		
6-301	Ringelmann No. 1 Limitation	Y	
6-305	Visible Particles	Y	
6-310	Particulate Weight Limitation	Y	
6-311	General Operations	Y	
6-401	Appearance of Emissions	Y	

IV. Source-specific Applicable Requirements

Table IV - AD
Source-specific Applicable Requirements
S1005 – TRUCK PVC UNDERCOAT AREA

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
BAAQMD Regulation 8, Rule 13	Light and Medium Duty Motor Vehicle Assembly Plants (12/20/95)		
8-13-302	Final Limits, Topcoat, Spray Primer, Primer Surfacer	Y	
8-13-302.1	Final Limits, Spray Primer	Y	
8-13-406	Compliance Verification	Y	
8-13-503	Usage Records, Coatings	Y	
8-13-504	Air Pollution Abatement Equipment, Recordkeeping Requirements	Y	
40 CFR 60 Subpart A	General Provisions (7/1/2000)		
60.1	Applicability.	Y	
60.2	Definitions.	Y	
60.3	Units and abbreviations.	Y	
60.4	Address.	Y	
60.5	Determination of construction or modification.	Y	
60.6	Review of plans.	Y	
60.7	Notification and record keeping.	Y	
60.8	Performance tests.	Y	
60.9	Availability of information.	Y	
60.10	State authority.	Y	
60.11	Compliance with standards and maintenance requirements.	Y	
60.12	Circumvention.	Y	
60.13	Monitoring requirements.	Y	
60.14	Modification.	Y	
60.15	Reconstruction.	Y	
60.16	Priority list.	Y	
60.17	Incorporations by reference.	Y	
60.18	General control device requirements.	Y	
60.19	General notification and reporting requirements.	Y	
40 CFR 60 Subpart MM	Standards of Performance for Automobile and Light Duty Truck Surface Coating Operations (12/24/80)		
60.392	Standards for Volatile Organic Compounds	Y	
60.392(a)	Prime Coat Operation	Y	
60.392(b)	Guide Coat Operation	Y	

IV. Source-specific Applicable Requirements

Table IV - AD
Source-specific Applicable Requirements
S1005 – TRUCK PVC UNDERCOAT AREA

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
60.392(c)	Topcoat Operation	Y	
60.393	Performance Test and Compliance Provisions	Y	
60.394	Monitoring of Emissions and Operations	Y	
60.395	Reporting and Recordkeeping Requirements	Y	
60.396	Reference Methods and Procedures	Y	
60.397	Modifications	Y	
BAAQMD Condition # 9156			
Part 1	Offset Baseline (basis: Regulation 2-2-302)	Y	
Part 2	Testing of Abatement Equipment (basis: Cumulative Increase)	Y	
Part 3	Toxics Limitations (basis: Toxics)	N	
Part 4	Monthly Reports (basis: Cumulative Increase)	Y	
Part 5	VOC Emission Limit (basis: Cumulative Increase)	Y	
Part 6	Toxics Limits (basis: Toxics)	N	
Part 7	Source Obligation, Relaxation of Enforceable Conditions (basis: Regulation 2-2-412)	Y	
Part 8	Natural Gas Usage Limits (basis: Cumulative Increase)	Y	
Part 9	Definition of Year and Month (basis: Cumulative Increase)	Y	
BAAQMD Condition # 9159			
Part 1	VOC Content Limitation (basis: BACT, Cumulative Increase)	Y	
Part 2	Usage Limit (basis: Cumulative Increase)	Y	
Part 3	Monthly Records (basis: Cumulative Increase)	Y	
Part 4	Spray Equipment Limitations (basis: BACT)	Y	
Part 5	VOC Emission Limit (basis: Cumulative Increase)	Y	
Part 6	Fuel Limitations (basis: Cumulative Increase)	Y	
Part 7	NOx Limit (basis: Cumulative Increase)	Y	
Part 8	Particulate Abatement Requirement (basis: Cumulative Increase)	Y	
Part 9	Solvent Minimization (basis: BACT)	Y	

IV. Source-specific Applicable Requirements

Table IV - AE
Source-specific Applicable Requirements
S1006 – TRUCK ANTI CHIP BOOTH

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
BAAQMD Regulation 6	Particulate Matter and Visible Emissions (12/19/90)		
6-301	Ringelmann No. 1 Limitation	Y	
6-305	Visible Particles	Y	
6-310	Particulate Weight Limitation	Y	
6-311	General Operations	Y	
6-401	Appearance of Emissions	Y	
BAAQMD Regulation 8, Rule 13	Light and Medium Duty Motor Vehicle Assembly Plants (12/20/95)		
8-13-302	Final Limits, Topcoat, Spray Primer, Primer Surfacer	Y	
8-13-302.1	Final Limits, Spray Primer	Y	
8-13-406	Compliance Verification	Y	
8-13-503	Usage Records, Coatings	Y	
8-13-504	Air Pollution Abatement Equipment, Recordkeeping Requirements	Y	
40 CFR 60 Subpart A	General Provisions (7/1/2000)		
60.1	Applicability.	Y	
60.2	Definitions.	Y	
60.3	Units and abbreviations.	Y	
60.4	Address.	Y	
60.5	Determination of construction or modification.	Y	
60.6	Review of plans.	Y	
60.7	Notification and record keeping.	Y	
60.8	Performance tests.	Y	
60.9	Availability of information.	Y	
60.10	State authority.	Y	
60.11	Compliance with standards and maintenance requirements.	Y	
60.12	Circumvention.	Y	
60.13	Monitoring requirements.	Y	
60.14	Modification.	Y	
60.15	Reconstruction.	Y	
60.16	Priority list.	Y	

IV. Source-specific Applicable Requirements

Table IV - AE
Source-specific Applicable Requirements
S1006 – TRUCK ANTI CHIP BOOTH

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
60.17	Incorporations by reference.	Y	
60.18	General control device requirements.	Y	
60.19	General notification and reporting requirements.	Y	
40 CFR 60 Subpart MM	Standards of Performance for Automobile and Light Duty Truck Surface Coating Operations (12/24/80)		
60.392	Standards for Volatile Organic Compounds	Y	
60.392(a)	Prime Coat Operation	Y	
60.392(b)	Guide Coat Operation	Y	
60.392(c)	Topcoat Operation	Y	
60.393	Performance Test and Compliance Provisions	Y	
60.394	Monitoring of Emissions and Operations	Y	
60.395	Reporting and Recordkeeping Requirements	Y	
60.396	Reference Methods and Procedures	Y	
60.397	Modifications	Y	
BAAQMD Condition # 9156			
Part 1	Offset Baseline (basis: Regulation 2-2-302)	Y	
Part 2	Testing of Abatement Equipment (basis: Cumulative Increase)	Y	
Part 3	Toxics Limitations (basis: Toxics)	N	
Part 4	Monthly Reports (basis: Cumulative Increase)	Y	
Part 5	VOC Emission Limit (basis: Cumulative Increase)	Y	
Part 6	Toxics Limits (basis: Toxics)	N	
Part 7	Source Obligation, Relaxation of Enforceable Conditions (basis: Regulation 2-2-412)	Y	
Part 8	Natural Gas Usage Limits (basis: Cumulative Increase)	Y	
Part 9	Definition of Year and Month (basis: Cumulative Increase)	Y	
BAAQMD Condition # 9161			
Part 1	VOC Content Limitation (basis: BACT, Cumulative Increase)	Y	
Part 2	Usage Limit (basis: Cumulative Increase)	Y	
Part 3	Monthly Records (basis: Cumulative Increase)	Y	
Part 4	Spray Equipment Limitations (basis: BACT)	Y	

IV. Source-specific Applicable Requirements

Table IV - AE
Source-specific Applicable Requirements
S1006 – TRUCK ANTI CHIP BOOTH

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
Part 5	VOC Emission Limit (basis: Cumulative Increase)	Y	

Table IV – AF
Source-specific Applicable Requirements
S1007 – TRUCK SEALER OVEN

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
BAAQMD Regulation 1	General Provisions and Definitions (5/2/01)		
1-523	Parametric Monitoring and Recordkeeping Procedures	N	
1-523.1	Parametric monitor periods of inoperation	Y	
1-523.2	Limits on periods of inoperation	Y	
1-523.3	Reports of Violations	N	
1-523.4	Records	Y	
1-523.5	Maintenance and calibration	N	
SIP Regulation 1	General Provisions and Definitions (6/28/99)		
1-523	Parametric Monitoring and Recordkeeping Procedures	Y ¹	
1-523.3	Reports of Violations	Y ¹	
BAAQMD Regulation 6	Particulate Matter and Visible Emissions (12/19/90)		
6-301	Ringelmann No. 1 Limitation	Y	
6-305	Visible Particles	Y	
6-310	Particulate Weight Limitation	Y	
6-311	General Operations	Y	
6-401	Appearance of Emissions	Y	
BAAQMD Regulation 8, Rule 13	Light and Medium Duty Motor Vehicle Assembly Plants (12/20/95)		
8-13-302	Final Limits, Topcoat, Spray Primer, Primer Surfacer	Y	

IV. Source-specific Applicable Requirements

Table IV – AF
Source-specific Applicable Requirements
S1007 – TRUCK SEALER OVEN

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
8-13-302.1	Final Limits, Spray Primer	Y	
8-13-406	Compliance Verification	Y	
8-13-503	Usage Records, Coatings	Y	
8-13-504	Air Pollution Abatement Equipment, Recordkeeping Requirements	Y	
40 CFR 60 Subpart A	General Provisions (7/1/2000)		
60.1	Applicability.	Y	
60.2	Definitions.	Y	
60.3	Units and abbreviations.	Y	
60.4	Address.	Y	
60.5	Determination of construction or modification.	Y	
60.6	Review of plans.	Y	
60.7	Notification and record keeping.	Y	
60.8	Performance tests.	Y	
60.9	Availability of information.	Y	
60.10	State authority.	Y	
60.11	Compliance with standards and maintenance requirements.	Y	
60.12	Circumvention.	Y	
60.13	Monitoring requirements.	Y	
60.14	Modification.	Y	
60.15	Reconstruction.	Y	
60.16	Priority list.	Y	
60.17	Incorporations by reference.	Y	
60.18	General control device requirements.	Y	
60.19	General notification and reporting requirements.	Y	
40 CFR 60 Subpart MM	Standards of Performance for Automobile and Light Duty Truck Surface Coating Operations (12/24/80)		
60.392	Standards for Volatile Organic Compounds	Y	
60.392(a)	Prime Coat Operation	Y	
60.392(b)	Guide Coat Operation	Y	
60.392(c)	Topcoat Operation	Y	
60.393	Performance Test and Compliance Provisions	Y	
60.394	Monitoring of Emissions and Operations	Y	
60.395	Reporting and Recordkeeping Requirements	Y	

IV. Source-specific Applicable Requirements

Table IV – AF
Source-specific Applicable Requirements
S1007 – TRUCK SEALER OVEN

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
60.396	Reference Methods and Procedures	Y	
60.397	Modifications	Y	
BAAQMD Condition # 9156			
Part 1	Offset Baseline (basis: Regulation 2-2-302)	Y	
Part 2	Testing of Abatement Equipment (basis: Cumulative Increase)	Y	
Part 3	Toxics Limitations (basis: Toxics)	N	
Part 4	Monthly Reports (basis: Cumulative Increase)	Y	
Part 5	VOC Emission Limit (basis: Cumulative Increase)	Y	
Part 6	Toxics Limits (basis: Toxics)	N	
Part 7	Source Obligation, Relaxation of Enforceable Conditions (basis: Regulation 2-2-412)	Y	
Part 8	Natural Gas Usage Limits (basis: Cumulative Increase)	Y	
Part 9	Definition of Year and Month (basis: Cumulative Increase)	Y	
BAAQMD Condition # 9158			
Part 1	Abatement Requirement (basis: BACT)	Y	
Part 2	Destruction Efficiency or Total Non-methane Organic Hydrocarbon Concentration Requirement (basis: BACT)	Y	
Part 3	Continuous Temperature Monitor (basis: BACT)	Y	
Part 4	Annual Source Test Requirement (basis: BACT)	Y	
Part 5	Records (basis: BACT)	Y	
Part 6	Fuel Limitations (basis: Cumulative Increase)	Y	
Part 7	NOx Limit (basis: Cumulative Increase)	Y	
Part 8	VOC Emission Limit (basis: Cumulative Increase)	Y	
Part 9	Allowable Temperature Excursion (basis: Cumulative Increase)	Y	
Part 10	Recording of Allowable Temperature Excursions (basis: Cumulative Increase)	Y	
Part 11	Revision of Allowable Temperature Excursions (basis: Cumulative Increase)	Y	
Part 12	Abatement Equipment Operation Requirement (basis: Cumulative Increase)	Y	

IV. Source-specific Applicable Requirements

Table IV - AG
Source-specific Applicable Requirements
S1008 – TRUCK PRIME BOOTH

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
BAAQMD Regulation 1	General Provisions and Definitions (5/2/01)		
1-523	Parametric Monitoring and Recordkeeping Procedures	N	
1-523.1	Parametric monitor periods of inoperation	Y	
1-523.2	Limits on periods of inoperation	Y	
1-523.3	Reports of Violations	N	
1-523.4	Records	Y	
1-523.5	Maintenance and calibration	N	
SIP Regulation 1	General Provisions and Definitions (6/28/99)		
1-523	Parametric Monitoring and Recordkeeping Procedures	Y ¹	
1-523.3	Reports of Violations	Y ¹	
BAAQMD Regulation 6	Particulate Matter and Visible Emissions (12/19/90)		
6-301	Ringelmann No. 1 Limitation	Y	
6-305	Visible Particles	Y	
6-310	Particulate Weight Limitation	Y	
6-311	General Operations	Y	
6-401	Appearance of Emissions	Y	
BAAQMD Regulation 8, Rule 13	Light and Medium Duty Motor Vehicle Assembly Plants (12/20/95)		
8-13-302	Final Limits, Topcoat, Spray Primer, Primer Surfacer	Y	
8-13-302.2	Final Limits, Primer Surfacer	Y	
8-13-406	Compliance Verification	Y	
8-13-503	Usage Records, Coatings	Y	
8-13-504	Air Pollution Abatement Equipment, Recordkeeping Requirements	Y	
40 CFR 60 Subpart A	General Provisions (7/1/2000)		
60.1	Applicability.	Y	
60.2	Definitions.	Y	
60.3	Units and abbreviations.	Y	
60.4	Address.	Y	
60.5	Determination of construction or modification.	Y	

IV. Source-specific Applicable Requirements

Table IV - AG
Source-specific Applicable Requirements
S1008 – TRUCK PRIME BOOTH

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
60.6	Review of plans.	Y	
60.7	Notification and record keeping.	Y	
60.8	Performance tests.	Y	
60.9	Availability of information.	Y	
60.10	State authority.	Y	
60.11	Compliance with standards and maintenance requirements.	Y	
60.12	Circumvention.	Y	
60.13	Monitoring requirements.	Y	
60.14	Modification.	Y	
60.15	Reconstruction.	Y	
60.16	Priority list.	Y	
60.17	Incorporations by reference.	Y	
60.18	General control device requirements.	Y	
60.19	General notification and reporting requirements.	Y	
40 CFR 60 Subpart MM	Standards of Performance for Automobile and Light Duty Truck Surface Coating Operations (12/24/80)		
60.392	Standards for Volatile Organic Compounds	Y	
60.392(a)	Prime Coat Operation	Y	
60.392(b)	Guide Coat Operation	Y	
60.392(c)	Topcoat Operation	Y	
60.393	Performance Test and Compliance Provisions	Y	
60.394	Monitoring of Emissions and Operations	Y	
60.395	Reporting and Recordkeeping Requirements	Y	
60.396	Reference Methods and Procedures	Y	
60.397	Modifications	Y	
BAAQMD Condition # 9156			
Part 1	Offset Baseline (basis: Regulation 2-2-302)	Y	
Part 2	Testing of Abatement Equipment (basis: Cumulative Increase)	Y	
Part 3	Toxics Limitations (basis: Toxics)	N	
Part 4	Monthly Reports (basis: Cumulative Increase)	Y	
Part 5	VOC Emission Limit (basis: Cumulative Increase)	Y	
Part 6	Toxics Limits (basis: Toxics)	N	

IV. Source-specific Applicable Requirements

Table IV - AG
Source-specific Applicable Requirements
S1008 – TRUCK PRIME BOOTH

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
Part 7	Source Obligation, Relaxation of Enforceable Conditions (basis: Regulation 2-2-412)	Y	
Part 8	Natural Gas Usage Limits (basis: Cumulative Increase)	Y	
Part 9	Definition of Year and Month (basis: Cumulative Increase)	Y	
BAAQMD Condition # 9163			
Part 1	VOC Content Limitation (basis: BACT, Cumulative Increase)	Y	
Part 2	Usage Limit (basis: Cumulative Increase)	Y	
Part 3	Monthly Records (basis: Cumulative Increase)	Y	
Part 4	Spray Equipment Limitations (basis: BACT)	Y	
Part 5	VOC Emission Limit (basis: Cumulative Increase)	Y	
Part 6	Fuel Limitations (basis: Cumulative Increase)	Y	
Part 7	NOx Limit (basis: Cumulative Increase)	Y	
Part 8	Particulate Abatement Requirement (basis: Cumulative Increase)	Y	
Part 9	Abatement Requirement (basis: BACT)	Y	
Part 10	Destruction Efficiency or Total Non-methane Organic Hydrocarbon Concentration Requirement (basis: BACT)	Y	
Part 11	Continuous Temperature Monitoring (basis: BACT, Regulation 1-523)	Y	
Part 12	Activated Carbon System Requirements (basis: BACT)	Y	
Part 13	Annual Source Testing Requirement (basis: BACT)	Y	
Part 14	Maintenance of Abatement Equipment (basis: Cumulative Increase)	Y	
Part 15	Records (basis: Cumulative Increase)	Y	
Part 16	Minimization of Solvents (basis: BACT)	Y	
Part 17	Allowable Temperature Excursion (basis: Cumulative Increase)	Y	
Part 18	Recording of Allowable Temperature Excursions (basis: Cumulative Increase)	Y	
Part 19	Revision of Allowable Temperature Excursions (basis: Cumulative Increase)	Y	
Part 22	Abatement Operating Requirements (basis: BACT)	Y	

IV. Source-specific Applicable Requirements

Table IV - AH
Source-specific Applicable Requirements
S1009 – TRUCK PRIMER OVEN

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
BAAQMD Regulation 1	General Provisions and Definitions (5/2/01)		
1-523	Parametric Monitoring and Recordkeeping Procedures	N	
1-523.1	Parametric monitor periods of inoperation	Y	
1-523.2	Limits on periods of inoperation	Y	
1-523.3	Reports of Violations	N	
1-523.4	Records	Y	
1-523.5	Maintenance and calibration	N	
SIP Regulation 1	General Provisions and Definitions (6/28/99)		
1-523	Parametric Monitoring and Recordkeeping Procedures	Y ¹	
1-523.3	Reports of Violations	Y ¹	
BAAQMD Regulation 6	Particulate Matter and Visible Emissions (12/19/90)		
6-301	Ringelmann No. 1 Limitation	Y	
6-305	Visible Particles	Y	
6-310	Particulate Weight Limitation	Y	
6-311	General Operations	Y	
6-401	Appearance of Emissions	Y	
BAAQMD Regulation 8, Rule 13	Light and Medium Duty Motor Vehicle Assembly Plants (12/20/95)		
8-13-302	Final Limits, Topcoat, Spray Primer, Primer Surfacer	Y	
8-13-302.2	Final Limits, Primer Surfacer	Y	
8-13-406	Compliance Verification	Y	
8-13-503	Usage Records, Coatings	Y	
8-13-504	Air Pollution Abatement Equipment, Recordkeeping Requirements	Y	
40 CFR 60 Subpart A	General Provisions (7/1/2000)		
60.1	Applicability.	Y	
60.2	Definitions.	Y	
60.3	Units and abbreviations.	Y	
60.4	Address.	Y	
60.5	Determination of construction or modification.	Y	
60.6	Review of plans.	Y	

IV. Source-specific Applicable Requirements

Table IV - AH
Source-specific Applicable Requirements
S1009 – TRUCK PRIMER OVEN

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
60.7	Notification and record keeping.	Y	
60.8	Performance tests.	Y	
60.9	Availability of information.	Y	
60.10	State authority.	Y	
60.11	Compliance with standards and maintenance requirements.	Y	
60.12	Circumvention.	Y	
60.13	Monitoring requirements.	Y	
60.14	Modification.	Y	
60.15	Reconstruction.	Y	
60.16	Priority list.	Y	
60.17	Incorporations by reference.	Y	
60.18	General control device requirements.	Y	
60.19	General notification and reporting requirements.	Y	
40 CFR 60 Subpart MM	Standards of Performance for Automobile and Light Duty Truck Surface Coating Operations (12/24/80)		
60.392	Standards for Volatile Organic Compounds	Y	
60.392(a)	Prime Coat Operation	Y	
60.392(b)	Guide Coat Operation	Y	
60.392(c)	Topcoat Operation	Y	
60.393	Performance Test and Compliance Provisions	Y	
60.394	Monitoring of Emissions and Operations	Y	
60.395	Reporting and Recordkeeping Requirements	Y	
60.396	Reference Methods and Procedures	Y	
60.397	Modifications	Y	
BAAQMD Condition # 9156			
Part 1	Offset Baseline (basis: Regulation 2-2-302)	Y	
Part 2	Testing of Abatement Equipment (basis: Cumulative Increase)	Y	
Part 3	Toxics Limitations (basis: Toxics)	N	
Part 4	Monthly Reports (basis: Cumulative Increase)	Y	
Part 5	VOC Emission Limit (basis: Cumulative Increase)	Y	
Part 6	Toxics Limits (basis: Toxics)	N	

IV. Source-specific Applicable Requirements

Table IV - AH
Source-specific Applicable Requirements
S1009 – TRUCK PRIMER OVEN

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
Part 7	Source Obligation, Relaxation of Enforceable Conditions (basis: Regulation 2-2-412)	Y	
Part 8	Natural Gas Usage Limits (basis: Cumulative Increase)	Y	
Part 9	Definition of Year and Month (basis: Cumulative Increase)	Y	
BAAQMD Condition # 9158			
Part 1	Abatement Requirement (basis: BACT)	Y	
Part 2	Destruction Efficiency or Total Non-methane Organic Hydrocarbon Concentration Requirement (basis: BACT)	Y	
Part 3	Continuous Temperature Monitor (basis: BACT)	Y	
Part 4	Annual Source Test Requirement (basis: BACT)	Y	
Part 5	Records (basis: BACT)	Y	
Part 6	Fuel Limitations (basis: Cumulative Increase)	Y	
Part 7	NOx Limit (basis: Cumulative Increase)	Y	
Part 8	VOC Emission Limit (basis: Cumulative Increase)	Y	
Part 9	Allowable Temperature Excursion (basis: Cumulative Increase)	Y	
Part 10	Recording of Allowable Temperature Excursions (basis: Cumulative Increase)	Y	
Part 11	Revision of Allowable Temperature Excursions (basis: Cumulative Increase)	Y	
Part 12	Abatement Equipment Operation Requirement (basis: Cumulative Increase)	Y	

Table IV - AI
Source-specific Applicable Requirements
S1010 – TRUCK OFF-LINE REPAIR
S1017 – TRUCK TOUCH UP BOOTH

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
BAAQMD Regulation 1	General Provisions and Definitions (5/2/01)		

IV. Source-specific Applicable Requirements

Table IV - AI
Source-specific Applicable Requirements
S1010 – TRUCK OFF-LINE REPAIR
S1017 – TRUCK TOUCH UP BOOTH

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
1-523	Parametric Monitoring and Recordkeeping Procedures	N	
1-523.1	Parametric monitor periods of inoperation	Y	
1-523.2	Limits on periods of inoperation	Y	
1-523.3	Reports of Violations	N	
1-523.4	Records	Y	
1-523.5	Maintenance and calibration	N	
SIP Regulation 1	General Provisions and Definitions (6/28/99)		
1-523	Parametric Monitoring and Recordkeeping Procedures	Y ¹	
1-523.3	Reports of Violations	Y ¹	
BAAQMD Regulation 6	Particulate Matter and Visible Emissions (12/19/90)		
6-301	Ringelmann No. 1 Limitation	Y	
6-305	Visible Particles	Y	
6-310	Particulate Weight Limitation	Y	
6-311	General Operations	Y	
6-401	Appearance of Emissions	Y	
BAAQMD Regulation 8, Rule 13	Light and Medium Duty Motor Vehicle Assembly Plants (12/20/95)		
8-13-302	Final Limits, Topcoat, Spray Primer, Primer Surfacer	Y	
8-13-406	Compliance Verification	Y	
8-13-503	Usage Records, Coatings	Y	
8-13-504	Air Pollution Abatement Equipment, Recordkeeping Requirements	Y	
40 CFR 60 Subpart A	General Provisions (7/1/2000)		
60.1	Applicability.	Y	
60.2	Definitions.	Y	
60.3	Units and abbreviations.	Y	
60.4	Address.	Y	
60.5	Determination of construction or modification.	Y	
60.6	Review of plans.	Y	
60.7	Notification and record keeping.	Y	

IV. Source-specific Applicable Requirements

Table IV - AI
Source-specific Applicable Requirements
S1010 – TRUCK OFF-LINE REPAIR
S1017 – TRUCK TOUCH UP BOOTH

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
60.8	Performance tests.	Y	
60.9	Availability of information.	Y	
60.10	State authority.	Y	
60.11	Compliance with standards and maintenance requirements.	Y	
60.12	Circumvention.	Y	
60.13	Monitoring requirements.	Y	
60.14	Modification.	Y	
60.15	Reconstruction.	Y	
60.16	Priority list.	Y	
60.17	Incorporations by reference.	Y	
60.18	General control device requirements.	Y	
60.19	General notification and reporting requirements.	Y	
40 CFR 60 Subpart MM	Standards of Performance for Automobile and Light Duty Truck Surface Coating Operations (12/24/80)		
60.392	Standards for Volatile Organic Compounds	Y	
60.392(a)	Prime Coat Operation	Y	
60.392(b)	Guide Coat Operation	Y	
60.392(c)	Topcoat Operation	Y	
60.393	Performance Test and Compliance Provisions	Y	
60.394	Monitoring of Emissions and Operations	Y	
60.395	Reporting and Recordkeeping Requirements	Y	
60.396	Reference Methods and Procedures	Y	
60.397	Modifications	Y	
BAAQMD Condition # 9156			
Part 1	Offset Baseline (basis: Regulation 2-2-302)	Y	
Part 2	Testing of Abatement Equipment (basis: Cumulative Increase)	Y	
Part 3	Toxics Limitations (basis: Toxics)	N	
Part 4	Monthly Reports (basis: Cumulative Increase)	Y	
Part 5	VOC Emission Limit (basis: Cumulative Increase)	Y	
Part 6	Toxics Limits (basis: Toxics)	N	

IV. Source-specific Applicable Requirements

Table IV - AI
Source-specific Applicable Requirements
S1010 – TRUCK OFF-LINE REPAIR
S1017 – TRUCK TOUCH UP BOOTH

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
Part 7	Source Obligation, Relaxation of Enforceable Conditions (basis: Regulation 2-2-412)	Y	
Part 8	Natural Gas Usage Limits (basis: Cumulative Increase)	Y	
Part 9	Definition of Year and Month (basis: Cumulative Increase)	Y	
BAAQMD Condition # 10011			
Part 1	VOC Content Limitation (basis: BACT, Cumulative Increase)	Y	
Part 2	Usage Limit (basis: Cumulative Increase)	Y	
Part 3	Monthly Records (basis: Cumulative Increase)	Y	
Part 4	Equipment Requirement (basis: Cumulative Increase)	Y	
Part 5	VOC Emission Limit (basis: Cumulative Increase)	Y	

IV. Source-specific Applicable Requirements

Table IV - AJ
Source-specific Applicable Requirements
S1012 – TRUCK TOUCH UP BOOTH

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
BAAQMD Regulation 6	Particulate Matter and Visible Emissions (12/19/90)		
6-301	Ringelmann No. 1 Limitation	Y	
6-305	Visible Particles	Y	
6-310	Particulate Weight Limitation	Y	
6-311	General Operations	Y	
6-401	Appearance of Emissions	Y	
BAAQMD Condition # 9156			
Part 1	Offset Baseline (basis: Regulation 2-2-302)	Y	
Part 2	Testing of Abatement Equipment (basis: Cumulative Increase)	Y	
Part 3	Toxics Limitations (basis: Toxics)	N	
Part 4	Monthly Reports (basis: Cumulative Increase)	Y	
Part 5	VOC Emission Limit (basis: Cumulative Increase)	Y	
Part 6	Toxics Limits (basis: Toxics)	N	
Part 7	Source Obligation, Relaxation of Enforceable Conditions (basis: Regulation 2-2-412)	Y	
Part 8	Natural Gas Usage Limits (basis: Cumulative Increase)	Y	
Part 9	Definition of Year and Month (basis: Cumulative Increase)	Y	
BAAQMD Condition # 9166			
Part 1	Coating Usage Limit (basis: Cumulative Increase)	Y	
Part 2	Emission Limit (basis: Cumulative Increase)	Y	
Part 3	Records (basis: Cumulative Increase)	Y	

IV. Source-specific Applicable Requirements

Table IV - AK
Source-specific Applicable Requirements
S1014 – TRUCK TOPCOAT BOOTH

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
BAAQMD Regulation 1	General Provisions and Definitions (5/2/01)		
1-523	Parametric Monitoring and Recordkeeping Procedures	N	
1-523.1	Parametric monitor periods of inoperation	Y	
1-523.2	Limits on periods of inoperation	Y	
1-523.3	Reports of Violations	N	
1-523.4	Records	Y	
1-523.5	Maintenance and calibration	N	
SIP Regulation 1	General Provisions and Definitions (6/28/99)		
1-523	Parametric Monitoring and Recordkeeping Procedures	Y ¹	
1-523.3	Reports of Violations	Y ¹	
BAAQMD Regulation 6	Particulate Matter and Visible Emissions (12/19/90)		
6-301	Ringelmann No. 1 Limitation	Y	
6-305	Visible Particles	Y	
6-310	Particulate Weight Limitation	Y	
6-311	General Operations	Y	
6-401	Appearance of Emissions	Y	
BAAQMD Regulation 8, Rule 13	Light and Medium Duty Motor Vehicle Assembly Plants (12/20/95)		
8-13-302	Final Limits, Topcoat, Spray Primer, Primer Surfacer	Y	
8-13-302.2	Final Limits, Primer Surfacer	Y	
8-13-302.3	Final Limits, Topcoat	Y	
8-13-503	Usage Records, Coatings	Y	
8-13-504	Air Pollution Abatement Equipment, Recordkeeping Requirements	Y	
40 CFR 60 Subpart A	General Provisions (7/1/2000)		
60.1	Applicability.	Y	
60.2	Definitions.	Y	
60.3	Units and abbreviations.	Y	
60.4	Address.	Y	
60.5	Determination of construction or modification.	Y	

IV. Source-specific Applicable Requirements

Table IV - AK
Source-specific Applicable Requirements
S1014 – TRUCK TOPCOAT BOOTH

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
60.6	Review of plans.	Y	
60.7	Notification and record keeping.	Y	
60.8	Performance tests.	Y	
60.9	Availability of information.	Y	
60.10	State authority.	Y	
60.11	Compliance with standards and maintenance requirements.	Y	
60.12	Circumvention.	Y	
60.13	Monitoring requirements.	Y	
60.14	Modification.	Y	
60.15	Reconstruction.	Y	
60.16	Priority list.	Y	
60.17	Incorporations by reference.	Y	
60.18	General control device requirements.	Y	
60.19	General notification and reporting requirements.	Y	
40 CFR 60 Subpart MM	Standards of Performance for Automobile and Light Duty Truck Surface Coating Operations (12/24/80)		
60.392	Standards for Volatile Organic Compounds	Y	
60.392(a)	Prime Coat Operation	Y	
60.392(b)	Guide Coat Operation	Y	
60.392(c)	Topcoat Operation	Y	
60.393	Performance Test and Compliance Provisions	Y	
60.394	Monitoring of Emissions and Operations	Y	
60.395	Reporting and Recordkeeping Requirements	Y	
60.396	Reference Methods and Procedures	Y	
60.397	Modifications	Y	
BAAQMD Condition # 9156			
Part 1	Offset Baseline (basis: Regulation 2-2-302)	Y	
Part 2	Testing of Abatement Equipment (basis: Cumulative Increase)	Y	
Part 3	Toxics Limitations (basis: Toxics)	N	
Part 4	Monthly Reports (basis: Cumulative Increase)	Y	
Part 5	VOC Emission Limit (basis: Cumulative Increase)	Y	
Part 6	Toxics Limits (basis: Toxics)	N	

IV. Source-specific Applicable Requirements

Table IV - AK
Source-specific Applicable Requirements
S1014 – TRUCK TOPCOAT BOOTH

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
Part 7	Source Obligation, Relaxation of Enforceable Conditions (basis: Regulation 2-2-412)	Y	
Part 8	Natural Gas Usage Limits (basis: Cumulative Increase)	Y	
Part 9	Definition of Year and Month (basis: Cumulative Increase)	Y	
BAAQMD Condition # 9164			
Part 1	Abatement Requirement (basis: BACT)	Y	
Part 2	Destruction Efficiency or Total Non-methane Organic Hydrocarbon Concentration Requirement (basis: BACT)	Y	
Part 3	Continuous Temperature Monitor (basis: BACT)	Y	
Part 4	VOC Reduction Efficiency Requirement (basis: BACT)	Y	
Part 5	Annual Source Test Requirement (basis: BACT)	Y	
Part 6	Proper Maintenance (basis: Cumulative Increase)	Y	
Part 7	Records (basis: BACT)	Y	
Part 8	Fuel Limitations (basis: Cumulative Increase)	Y	
Part 9	NOx Emissions Limit (basis: Cumulative Increase)	Y	
Part 10	Minimization of Clean-up Solvent (basis: BACT)	Y	
Part 11	Minimization of Purge Solvent (basis: BACT)	Y	
Part 12	Allowable Temperature Excursion (basis: Cumulative Increase)	Y	
Part 13	Recording of Allowable Temperature Excursions (basis: Cumulative Increase)	Y	
Part 14	Abatement During Production and Cleanup (basis: BACT)	Y	
Part 15	VOC Content Limitation (basis: BACT, Cumulative Increase)	Y	
Part 16	Usage Limit (basis: Cumulative Increase)	Y	
Part 17	Monthly Records (basis: Cumulative Increase)	Y	
Part 18	Spray Equipment Limitations (basis: BACT)	Y	
Part 19	VOC Emission Limit (basis: Cumulative Increase)	Y	
Part 20	Particulate Abatement Requirement (basis: Cumulative Increase)	Y	

IV. Source-specific Applicable Requirements

Table IV - AL
Source-specific Applicable Requirements
S1015 – TRUCK TOPCOAT OVEN

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
BAAQMD Regulation 1	General Provisions and Definitions (5/2/01)		
1-523	Parametric Monitoring and Recordkeeping Procedures	N	
1-523.1	Parametric monitor periods of inoperation	Y	
1-523.2	Limits on periods of inoperation	Y	
1-523.3	Reports of Violations	N	
1-523.4	Records	Y	
1-523.5	Maintenance and calibration	N	
SIP Regulation 1	General Provisions and Definitions (6/28/99)		
1-523	Parametric Monitoring and Recordkeeping Procedures	Y ¹	
1-523.3	Reports of Violations	Y ¹	
BAAQMD Regulation 6	Particulate Matter and Visible Emissions (12/19/90)		
6-301	Ringelmann No. 1 Limitation	Y	
6-305	Visible Particles	Y	
6-310	Particulate Weight Limitation	Y	
6-311	General Operations	Y	
6-401	Appearance of Emissions	Y	
BAAQMD Regulation 8, Rule 13	Light and Medium Duty Motor Vehicle Assembly Plants (12/20/95)		
8-13-302	Final Limits, Topcoat, Spray Primer, Primer Surfacer	Y	
8-13-302.2	Final Limits, Primer Surfacer	Y	
8-13-302.3	Final Limits, Topcoat	Y	
8-13-406	Compliance Verification	Y	
8-13-503	Usage Records, Coatings	Y	
8-13-504	Air Pollution Abatement Equipment, Recordkeeping Requirements	Y	
40 CFR 60 Subpart A	General Provisions (7/1/2000)		
60.1	Applicability.	Y	
60.2	Definitions.	Y	
60.3	Units and abbreviations.	Y	
60.4	Address.	Y	

IV. Source-specific Applicable Requirements

Table IV - AL
Source-specific Applicable Requirements
S1015 – TRUCK TOPCOAT OVEN

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
60.5	Determination of construction or modification.	Y	
60.6	Review of plans.	Y	
60.7	Notification and record keeping.	Y	
60.8	Performance tests.	Y	
60.9	Availability of information.	Y	
60.10	State authority.	Y	
60.11	Compliance with standards and maintenance requirements.	Y	
60.12	Circumvention.	Y	
60.13	Monitoring requirements.	Y	
60.14	Modification.	Y	
60.15	Reconstruction.	Y	
60.16	Priority list.	Y	
60.17	Incorporations by reference.	Y	
60.18	General control device requirements.	Y	
60.19	General notification and reporting requirements.	Y	
40 CFR 60 Subpart MM	Standards of Performance for Automobile and Light Duty Truck Surface Coating Operations (12/24/80)		
60.392	Standards for Volatile Organic Compounds	Y	
60.392(a)	Prime Coat Operation	Y	
60.392(b)	Guide Coat Operation	Y	
60.392(c)	Topcoat Operation	Y	
60.393	Performance Test and Compliance Provisions	Y	
60.394	Monitoring of Emissions and Operations	Y	
60.395	Reporting and Recordkeeping Requirements	Y	
60.396	Reference Methods and Procedures	Y	
60.397	Modifications	Y	
BAAQMD Condition # 9156			
Part 1	Offset Baseline (basis: Regulation 2-2-302)	Y	
Part 2	Testing of Abatement Equipment (basis: Cumulative Increase)	Y	
Part 3	Toxics Limitations (basis: Toxics)	N	
Part 4	Monthly Reports (basis: Cumulative Increase)	Y	
Part 5	VOC Emission Limit (basis: Cumulative Increase)	Y	

IV. Source-specific Applicable Requirements

Table IV - AL
Source-specific Applicable Requirements
S1015 – TRUCK TOPCOAT OVEN

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
Part 6	Toxics Limits (basis: Toxics)	N	
Part 7	Source Obligation, Relaxation of Enforceable Conditions (basis: Regulation 2-2-412)	Y	
Part 8	Natural Gas Usage Limits (basis: Cumulative Increase)	Y	
Part 9	Definition of Year and Month (basis: Cumulative Increase)	Y	
BAAQMD Condition # 9158			
Part 1	Abatement Requirement (basis: BACT)	Y	
Part 2	Destruction Efficiency or Total Non-methane Organic Hydrocarbon Concentration Requirement (basis: BACT)	Y	
Part 3	Continuous Temperature Monitor (basis: BACT)	Y	
Part 4	Annual Source Test Requirement (basis: BACT)	Y	
Part 5	Records (basis: BACT)	Y	
Part 6	Fuel Limitations (basis: Cumulative Increase)	Y	
Part 7	NOx Limit (basis: Cumulative Increase)	Y	
Part 8	VOC Emission Limit (basis: Cumulative Increase)	Y	
Part 9	Allowable Temperature Excursion (basis: Cumulative Increase)	Y	
Part 10	Recording of Allowable Temperature Excursions (basis: Cumulative Increase)	Y	
Part 11	Revision of Allowable Temperature Excursions (basis: Cumulative Increase)	Y	
Part 12	Abatement Equipment Operation Requirement (basis: Cumulative Increase)	Y	

IV. Source-specific Applicable Requirements

Table IV - AN
Source-specific Applicable Requirements
S1018 – TRUCK BLACKOUT BOOTH

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
BAAQMD Regulation 6	Particulate Matter and Visible Emissions (12/19/90)		
6-301	Ringelmann No. 1 Limitation	Y	
6-305	Visible Particles	Y	
6-310	Particulate Weight Limitation	Y	
6-311	General Operations	Y	
6-401	Appearance of Emissions	Y	
BAAQMD Regulation 8, Rule 13	Light and Medium Duty Motor Vehicle Assembly Plants (12/20/95)		
8-13-302	Final Limits, Topcoat, Spray Primer, Primer Surfacer	Y	
8-13-302.3	Final Limits, Topcoat	Y	
8-13-503	Usage Records, Coatings	Y	
8-13-504	Air Pollution Abatement Equipment, Recordkeeping Requirements	Y	
40 CFR 60 Subpart A	General Provisions (7/1/2000)		
60.1	Applicability.	Y	
60.2	Definitions.	Y	
60.3	Units and abbreviations.	Y	
60.4	Address.	Y	
60.5	Determination of construction or modification.	Y	
60.6	Review of plans.	Y	
60.7	Notification and record keeping.	Y	
60.8	Performance tests.	Y	
60.9	Availability of information.	Y	
60.10	State authority.	Y	
60.11	Compliance with standards and maintenance requirements.	Y	
60.12	Circumvention.	Y	
60.13	Monitoring requirements.	Y	
60.14	Modification.	Y	
60.15	Reconstruction.	Y	
60.16	Priority list.	Y	
60.17	Incorporations by reference.	Y	

IV. Source-specific Applicable Requirements

Table IV - AN
Source-specific Applicable Requirements
S1018 – TRUCK BLACKOUT BOOTH

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
60.18	General control device requirements.	Y	
60.19	General notification and reporting requirements.	Y	
40 CFR 60 Subpart MM	Standards of Performance for Automobile and Light Duty Truck Surface Coating Operations (12/24/80)		
60.392	Standards for Volatile Organic Compounds	Y	
60.392(a)	Prime Coat Operation	Y	
60.392(b)	Guide Coat Operation	Y	
60.392(c)	Topcoat Operation	Y	
60.393	Performance Test and Compliance Provisions	Y	
60.394	Monitoring of Emissions and Operations	Y	
60.395	Reporting and Recordkeeping Requirements	Y	
60.396	Reference Methods and Procedures	Y	
60.397	Modifications	Y	
BAAQMD Condition # 9156			
Part 1	Offset Baseline (basis: Regulation 2-2-302)	Y	
Part 2	Testing of Abatement Equipment (basis: Cumulative Increase)	Y	
Part 3	Toxics Limitations (basis: Toxics)	N	
Part 4	Monthly Reports (basis: Cumulative Increase)	Y	
Part 5	VOC Emission Limit (basis: Cumulative Increase)	Y	
Part 6	Toxics Limits (basis: Toxics)	N	
Part 7	Source Obligation, Relaxation of Enforceable Conditions (basis: Regulation 2-2-412)	Y	
Part 8	Natural Gas Usage Limits (basis: Cumulative Increase)	Y	
Part 9	Definition of Year and Month (basis: Cumulative Increase)	Y	
BAAQMD Condition # 9170			
Part 1	VOC Content Limitation (basis: BACT, Cumulative Increase)	Y	
Part 2	Usage Limit (basis: Cumulative Increase)	Y	
Part 3	Monthly Records (basis: Cumulative Increase)	Y	
Part 4	VOC Emission Limit (basis: Cumulative Increase)	Y	

IV. Source-specific Applicable Requirements

**Table IV – AO
 Source-specific Applicable Requirements
 S1019 – TRUCK CAVITY WAX BOOTH**

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
BAAQMD Regulation 6	Particulate Matter and Visible Emissions (12/19/90)		
6-301	Ringelmann No. 1 Limitation	Y	
6-305	Visible Particles	Y	
6-310	Particulate Weight Limitation	Y	
6-311	General Operations	Y	
6-401	Appearance of Emissions	Y	
BAAQMD Regulation 8, Rule 13	Light and Medium Duty Motor Vehicle Assembly Plants (12/20/95)		
8-13-302	Final Limits, Topcoat, Spray Primer, Primer Surfacer	Y	
8-13-302.1	Final Limits, Spray Primer	Y	
8-13-503	Usage Records, Coatings	Y	
8-13-504	Air Pollution Abatement Equipment, Recordkeeping Requirements	Y	
40 CFR 60 Subpart A	General Provisions (7/1/2000)		
60.1	Applicability.	Y	
60.2	Definitions.	Y	
60.3	Units and abbreviations.	Y	
60.4	Address.	Y	
60.5	Determination of construction or modification.	Y	
60.6	Review of plans.	Y	
60.7	Notification and record keeping.	Y	
60.8	Performance tests.	Y	
60.9	Availability of information.	Y	
60.10	State authority.	Y	
60.11	Compliance with standards and maintenance requirements.	Y	
60.12	Circumvention.	Y	
60.13	Monitoring requirements.	Y	
60.14	Modification.	Y	
60.15	Reconstruction.	Y	
60.16	Priority list.	Y	
60.17	Incorporations by reference.	Y	

IV. Source-specific Applicable Requirements

**Table IV – AO
 Source-specific Applicable Requirements
 S1019 – TRUCK CAVITY WAX BOOTH**

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
60.18	General control device requirements.	Y	
60.19	General notification and reporting requirements.	Y	
40 CFR 60 Subpart MM	Standards of Performance for Automobile and Light Duty Truck Surface Coating Operations (12/24/80)		
60.392	Standards for Volatile Organic Compounds	Y	
60.392(a)	Prime Coat Operation	Y	
60.392(b)	Guide Coat Operation	Y	
60.392(c)	Topcoat Operation	Y	
60.393	Performance Test and Compliance Provisions	Y	
60.394	Monitoring of Emissions and Operations	Y	
60.395	Reporting and Recordkeeping Requirements	Y	
60.396	Reference Methods and Procedures	Y	
60.397	Modifications	Y	
BAAQMD Condition # 9156			
Part 1	Offset Baseline (basis: Regulation 2-2-302)	Y	
Part 2	Testing of Abatement Equipment (basis: Cumulative Increase)	Y	
Part 3	Toxics Limitations (basis: Toxics)	N	
Part 4	Monthly Reports (basis: Cumulative Increase)	Y	
Part 5	VOC Emission Limit (basis: Cumulative Increase)	Y	
Part 6	Toxics Limits (basis: Toxics)	N	
Part 7	Source Obligation, Relaxation of Enforceable Conditions (basis: Regulation 2-2-412)	Y	
Part 8	Natural Gas Usage Limits (basis: Cumulative Increase)	Y	
Part 9	Definition of Year and Month (basis: Cumulative Increase)	Y	
BAAQMD Condition # 9171			
Part 1	VOC Content Limitation (basis: BACT, Cumulative Increase)	Y	
Part 2	Usage Limit (basis: Cumulative Increase)	Y	
Part 3	Monthly Records (basis: Cumulative Increase)	Y	
Part 4	Spray Equipment Limitations (basis: BACT)	Y	
Part 5	VOC Emission Limit (basis: Cumulative Increase)	Y	

IV. Source-specific Applicable Requirements

Table IV - AP
Source-specific Applicable Requirements
S1020 – OFF-LINE ASSEMBLY PAINT HOSPITAL (TRUCK)

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
BAAQMD Regulation 6	Particulate Matter and Visible Emissions (12/19/90)		
6-301	Ringelmann No. 1 Limitation	Y	
6-305	Visible Particles	Y	
6-310	Particulate Weight Limitation	Y	
6-311	General Operations	Y	
6-401	Appearance of Emissions	Y	
BAAQMD Regulation 8, Rule 13	Light and Medium Duty Motor Vehicle Assembly Plants (12/20/95)		
8-13-302	Final Limits, Topcoat, Spray Primer, Primer Surfacer	Y	
8-13-302.3	Final Limits, Topcoat	Y	
8-13-503	Usage Records, Coatings	Y	
40 CFR 60 Subpart MM	Standards of Performance for Automobile and Light Duty Truck Surface Coating Operations (12/24/80)		
60.392	Standards for Volatile Organic Compounds	Y	
60.392(a)	Prime Coat Operation	Y	
60.392(b)	Guide Coat Operation	Y	
60.392(c)	Topcoat Operation	Y	
60.393	Performance Test and Compliance Provisions	Y	
60.394	Monitoring of Emissions and Operations	Y	
60.395	Reporting and Recordkeeping Requirements	Y	
60.396	Reference Methods and Procedures	Y	
60.397	Modifications	Y	
BAAQMD Condition # 9156			
Part 1	Offset Baseline (basis: Regulation 2-2-302)	Y	
Part 2	Testing of Abatement Equipment (basis: Cumulative Increase)	Y	
Part 3	Toxics Limitations (basis: Toxics)	N	
Part 4	Monthly Reports (basis: Cumulative Increase)	Y	
Part 5	VOC Emission Limit (basis: Cumulative Increase)	Y	
Part 6	Toxics Limits (basis: Toxics)	N	

IV. Source-specific Applicable Requirements

Table IV - AP
Source-specific Applicable Requirements
S1020 – OFF-LINE ASSEMBLY PAINT HOSPITAL (TRUCK)

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
Part 7	Source Obligation, Relaxation of Enforceable Conditions (basis: Regulation 2-2-412)	Y	
Part 8	Natural Gas Usage Limits (basis: Cumulative Increase)	Y	
Part 9	Definition of Year and Month (basis: Cumulative Increase)	Y	
BAAQMD Condition # 9172			
Part 1	VOC Content Limitation (basis: BACT, Cumulative Increase)	Y	
Part 2	Usage Limit (basis: Cumulative Increase)	Y	
Part 3	Monthly Records (basis: Cumulative Increase)	Y	
Part 4	Equipment Requirement (basis: Cumulative Increase)	Y	
Part 5	VOC Emission Limit (basis: Cumulative Increase)	Y	

Table IV - AQ
Source-specific Applicable Requirements
S1021 – TRUCK UNDERBODY, ENGINE & EXTERIOR WAX BOOTH

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
BAAQMD Regulation 6	Particulate Matter and Visible Emissions (12/19/90)		
6-301	Ringelmann No. 1 Limitation	Y	
6-305	Visible Particles	Y	
6-310	Particulate Weight Limitation	Y	
6-311	General Operations	Y	
6-401	Appearance of Emissions	Y	
BAAQMD Regulation 8, Rule 13	Light and Medium Duty Motor Vehicle Assembly Plants (12/20/95)		
8-13-302	Final Limits, Topcoat, Spray Primer, Primer Surfacer	Y	
8-13-302.3	Final Limits, Topcoat	Y	

IV. Source-specific Applicable Requirements

Table IV - AQ
Source-specific Applicable Requirements
S1021 – TRUCK UNDERBODY, ENGINE & EXTERIOR WAX BOOTH

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
8-13-503	Usage Records, Coatings	Y	
40 CFR 60 Subpart A	General Provisions (7/1/2000)		
60.1	Applicability.	Y	
60.2	Definitions.	Y	
60.3	Units and abbreviations.	Y	
60.4	Address.	Y	
60.5	Determination of construction or modification.	Y	
60.6	Review of plans.	Y	
60.7	Notification and record keeping.	Y	
60.8	Performance tests.	Y	
60.9	Availability of information.	Y	
60.10	State authority.	Y	
60.11	Compliance with standards and maintenance requirements.	Y	
60.12	Circumvention.	Y	
60.13	Monitoring requirements.	Y	
60.14	Modification.	Y	
60.15	Reconstruction.	Y	
60.16	Priority list.	Y	
60.17	Incorporations by reference.	Y	
60.18	General control device requirements.	Y	
60.19	General notification and reporting requirements.	Y	
40 CFR 60 Subpart MM	Standards of Performance for Automobile and Light Duty Truck Surface Coating Operations (12/24/80)		
60.392	Standards for Volatile Organic Compounds	Y	
60.392(a)	Prime Coat Operation	Y	
60.392(b)	Guide Coat Operation	Y	
60.392(c)	Topcoat Operation	Y	
60.393	Performance Test and Compliance Provisions	Y	
60.394	Monitoring of Emissions and Operations	Y	
60.395	Reporting and Recordkeeping Requirements	Y	
60.396	Reference Methods and Procedures	Y	
60.397	Modifications	Y	

IV. Source-specific Applicable Requirements

Table IV - AQ
Source-specific Applicable Requirements
S1021 – TRUCK UNDERBODY, ENGINE & EXTERIOR WAX BOOTH

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
BAAQMD Condition # 7364			
Part 1	VOC Content Limitation (basis: BACT, Cumulative Increase)	Y	
Part 2	Usage Limit (basis: Cumulative Increase)	Y	
Part 3	Monthly Records (basis: Cumulative Increase)	Y	
Part 4	Spray Equipment Limitations (basis: BACT)	Y	
Part 5	VOC Emission Limit (basis: Cumulative Increase)	Y	
BAAQMD Condition # 9156			
Part 1	Offset Baseline (basis: Regulation 2-2-302)	Y	
Part 2	Testing of Abatement Equipment (basis: Cumulative Increase)	Y	
Part 3	Toxics Limitations (basis: Toxics)	N	
Part 4	Monthly Reports (basis: Cumulative Increase)	Y	
Part 5	VOC Emission Limit (basis: Cumulative Increase)	Y	
Part 6	Toxics Limits (basis: Toxics)	N	
Part 7	Source Obligation, Relaxation of Enforceable Conditions (basis: Regulation 2-2-412)	Y	
Part 9	Definition of Year and Month (basis: Cumulative Increase)	Y	

IV. Source-specific Applicable Requirements

Table IV - AR
Source-specific Applicable Requirements
S1050 – TRUCK FUEL TANK COATING BOOTH
S1051 – TRUCK FUEL TANK – HEATER BOX

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
BAAQMD Regulation 1	General Provisions and Definitions (5/2/01)		
1-523	Parametric Monitoring and Recordkeeping Procedures	N	
1-523.1	Parametric monitor periods of inoperation	Y	
1-523.2	Limits on periods of inoperation	Y	
1-523.3	Reports of Violations	N	
1-523.4	Records	Y	
1-523.5	Maintenance and calibration	N	
SIP Regulation 1	General Provisions and Definitions (6/28/99)		
1-523	Parametric Monitoring and Recordkeeping Procedures	Y ¹	
1-523.3	Reports of Violations	Y ¹	
BAAQMD Regulation 6	Particulate Matter and Visible Emissions (12/19/90)		
6-301	Ringelmann No. 1 Limitation	Y	
6-305	Visible Particles	Y	
6-310	Particulate Weight Limitation	Y	
6-311	General Operations	Y	
6-401	Appearance of Emissions	Y	
BAAQMD Regulation 8, Rule 13	Light and Medium Duty Motor Vehicle Assembly Plants (12/20/95)		
8-13-308	Limits, Off-Line Coatings	Y	
8-13-503	Usage Records, Coatings	Y	
8-13-504	Air Pollution Abatement Equipment, Recordkeeping Requirements	Y	
40 CFR 60 Subpart A	General Provisions (7/1/2000)		
60.1	Applicability.	Y	
60.2	Definitions.	Y	
60.3	Units and abbreviations.	Y	
60.4	Address.	Y	
60.5	Determination of construction or modification.	Y	
60.6	Review of plans.	Y	

IV. Source-specific Applicable Requirements

Table IV - AR
Source-specific Applicable Requirements
S1050 – TRUCK FUEL TANK COATING BOOTH
S1051 – TRUCK FUEL TANK – HEATER BOX

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
60.7	Notification and record keeping.	Y	
60.8	Performance tests.	Y	
60.9	Availability of information.	Y	
60.10	State authority.	Y	
60.11	Compliance with standards and maintenance requirements.	Y	
60.12	Circumvention.	Y	
60.13	Monitoring requirements.	Y	
60.14	Modification.	Y	
60.15	Reconstruction.	Y	
60.16	Priority list.	Y	
60.17	Incorporations by reference.	Y	
60.18	General control device requirements.	Y	
60.19	General notification and reporting requirements.	Y	
BAAQMD Condition # 10578			
Part 1	POC Emissions Limit (basis: Cumulative Increase)	Y	
Part 2	Coating Usage Limit (basis: Cumulative Increase)	Y	
Part 3	Spray Equipment Limitations (basis: BACT)	Y	
Part 4	Records (basis: Cumulative Increase)	Y	
Part 5	Particulate Abatement Requirement (basis: Cumulative Increase)	Y	
Part 6	Abatement Requirement (basis: BACT)	Y	
Part 7	Minimum Temperature Requirement (basis: BACT)	Y	
Part 8	VOC Destruction Efficiency (basis: BACT)	Y	
Part 9	Continuous Temperature Requirement (basis: BACT)	Y	
Part 10	Annual Source Test Requirement (basis: BACT)	Y	
Part 11	Source Test Reporting (basis: BACT; MOP Volume II, Part 3, Section 4.7)	Y	
Part 12	Low NOx Burner Requirement (basis: BACT)	Y	
Part 13	Allowable Temperature Excursion (basis: Cumulative Increase)	Y	
Part 14	Recording of Allowable Temperature Excursions (basis: Cumulative Increase)	Y	
Part 15	Revision of Allowable Temperature Excursions (basis: Cumulative Increase)	Y	

IV. Source-specific Applicable Requirements

Table IV - AR
Source-specific Applicable Requirements
S1050 – TRUCK FUEL TANK COATING BOOTH
S1051 – TRUCK FUEL TANK – HEATER BOX

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
Part 16	Definition of Year (basis: Cumulative Increase)	Y	
Part 17	Toxics Requirement (basis: Toxics)	N	
Part 18	Maximum Natural Gas Usage (basis: Cumulative Increase)	Y	
Part 19	Testing of Abatement Equipment (basis: Cumulative Increase)	Y	

IV. Source-specific Applicable Requirements

Table IV - AS
Source-specific Applicable Requirements
S1053 – TRUCK WAX DRY OFF BOOTH (ELECTRIC)

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
BAAQMD Regulation 6	Particulate Matter and Visible Emissions (12/19/90)		
6-301	Ringelmann No. 1 Limitation	Y	
6-305	Visible Particles	Y	
6-310	Particulate Weight Limitation	Y	
6-311	General Operations	Y	
6-401	Appearance of Emissions	Y	
BAAQMD Regulation 8, Rule 13	Light and Medium Duty Motor Vehicle Assembly Plants (12/20/95)		
8-13-302	Final Limits, Topcoat, Spray Primer, Primer Surfacer	Y	
8-13-302.3	Final Limits, Topcoat	Y	
8-13-503	Usage Records, Coatings	Y	
40 CFR 60 Subpart MM	Standards of Performance for Automobile and Light Duty Truck Surface Coating Operations (12/24/80)		
60.392	Standards for Volatile Organic Compounds	Y	
60.392(a)	Prime Coat Operation	Y	
60.392(b)	Guide Coat Operation	Y	
60.392(c)	Topcoat Operation	Y	
60.393	Performance Test and Compliance Provisions	Y	
60.394	Monitoring of Emissions and Operations	Y	
60.395	Reporting and Recordkeeping Requirements	Y	
60.396	Reference Methods and Procedures	Y	
60.397	Modifications	Y	
BAAQMD Condition # 9156			
Part 1	Offset Baseline (basis: Regulation 2-2-302)	Y	
Part 3	Toxics Limitations (basis: Toxics)	N	
Part 4	Monthly Reports (basis: Cumulative Increase)	Y	
Part 5	VOC Emission Limit (basis: Cumulative Increase)	Y	
Part 6	Toxics Limits (basis: Toxics)	N	
Part 7	Source Obligation, Relaxation of Enforceable Conditions (basis: Regulation 2-2-412)	Y	

IV. Source-specific Applicable Requirements

Table IV - AS
Source-specific Applicable Requirements
S1053 – TRUCK WAX DRY OFF BOOTH (ELECTRIC)

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
Part 9	Definition of Year and Month (basis: Cumulative Increase)	Y	
BAAQMD Condition # 9167			
Part 1	VOC Emission Limit (basis: Cumulative Increase)	Y	

Table IV - AT
Source-specific Applicable Requirements
S1056 TRUCK ASH, BOILER #1
S1057 TRUCK ASH, BOILER #2

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
BAAQMD Regulation 6	Particulate Matter and Visible Emissions (12/19/90)		
6-301	Ringelmann No. 1 Limitation	Y	
6-305	Visible Particles	Y	
6-310	Particulate Weight Limitation	Y	
6-311	General Operations	Y	
6-401	Appearance of Emissions	Y	
BAAQMD Regulation 9, Rule 1	Inorganic Gaseous Pollutants - Sulfur Dioxide (3/15/95)		
9-1-301	Limitations on Ground Level Concentrations	Y	
9-1-302	General Emission Limitations	Y	
BAAQMD Regulation 9, Rule 7	Inorganic Gaseous Pollutants - Nitrogen Oxides and Carbon Monoxide from Industrial, Institutional, and Commercial Boilers, Steam Generators, and Process Heaters (9/15/93)		
9-7-301	Emission Limits-Gaseous Fuel	Y	
9-7-301.1	Emission Limits-NOx	Y	
9-7-301.2	Emission Limits-CO	Y	

IV. Source-specific Applicable Requirements

Table IV - AT
Source-specific Applicable Requirements
S1056 TRUCK ASH, BOILER #1
S1057 TRUCK ASH, BOILER #2

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
9-7-503	Records	Y	
9-7-503.4	Source test records	Y	
9-7-603	Compliance Determination	Y	
BAAQMD Condition # 9156			
Part 1	Offset Baseline (basis: Regulation 2-2-302)	Y	
Part 7	Source Obligation, Relaxation of Enforceable Conditions (basis: Regulation 2-2-412)	Y	
Part 8	Natural Gas Usage Limits (basis: Cumulative Increase)	Y	
Part 9	Definition of Year and Month (basis: Cumulative Increase)	Y	
BAAQMD Condition #9174			
Part 1	Fuel Limitations (basis: Cumulative Increase)	Y	
Part 2	NOx Limit (basis: BACT, Cumulative Increase)	Y	
Part 3	Proper Maintenance (basis: Cumulative Increase)	Y	
Part 4	Records (BACT, Cumulative Increase)	Y	
Part 5	Source Test Requirement (basis: Regulation 2-6-409.2)	Y	

IV. Source-specific Applicable Requirements

Table IV - AU
Source-specific Applicable Requirements
S1061 – TRUCK AXLE COATING BOOTH
S1062 – TRUCK AXLE OVEN

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
BAAQMD Regulation 1	General Provisions and Definitions (5/2/01)		
1-523	Parametric Monitoring and Recordkeeping Procedures	N	
1-523.1	Parametric monitor periods of inoperation	Y	
1-523.2	Limits on periods of inoperation	Y	
1-523.3	Reports of Violations	N	
1-523.4	Records	Y	
1-523.5	Maintenance and calibration	N	
SIP Regulation 1	General Provisions and Definitions (6/28/99)		
1-523	Parametric Monitoring and Recordkeeping Procedures	Y ¹	
1-523.3	Reports of Violations	Y ¹	
BAAQMD Regulation 6	Particulate Matter and Visible Emissions (12/19/90)		
6-301	Ringelmann No. 1 Limitation	Y	
6-305	Visible Particles	Y	
6-310	Particulate Weight Limitation	Y	
6-311	General Operations	Y	
6-401	Appearance of Emissions	Y	
BAAQMD Regulation 8, Rule 13	Light and Medium Duty Motor Vehicle Assembly Plants (12/20/95)		
8-13-308	Limits, Off-Line Coatings	Y	
8-13-503	Usage Records, Coatings	Y	
8-13-504	Air Pollution Abatement Equipment, Recordkeeping Requirements	Y	
40 CFR 60 Subpart A	General Provisions (7/1/2000)		
60.1	Applicability.	Y	
60.2	Definitions.	Y	
60.3	Units and abbreviations.	Y	
60.4	Address.	Y	
60.5	Determination of construction or modification.	Y	
60.6	Review of plans.	Y	

IV. Source-specific Applicable Requirements

Table IV - AU
Source-specific Applicable Requirements
S1061 – TRUCK AXLE COATING BOOTH
S1062 – TRUCK AXLE OVEN

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
60.7	Notification and record keeping.	Y	
60.8	Performance tests.	Y	
60.9	Availability of information.	Y	
60.10	State authority.	Y	
60.11	Compliance with standards and maintenance requirements.	Y	
60.12	Circumvention.	Y	
60.13	Monitoring requirements.	Y	
60.14	Modification.	Y	
60.15	Reconstruction.	Y	
60.16	Priority list.	Y	
60.17	Incorporations by reference.	Y	
60.18	General control device requirements.	Y	
60.19	General notification and reporting requirements.	Y	
40 CFR 60 Subpart MM	Standards of Performance for Automobile and Light Duty Truck Surface Coating Operations (12/24/80)		
60.392	Standards for Volatile Organic Compounds	Y	
60.392(a)	Prime Coat Operation	Y	
60.392(b)	Guide Coat Operation	Y	
60.392(c)	Topcoat Operation	Y	
60.393	Performance Test and Compliance Provisions	Y	
60.394	Monitoring of Emissions and Operations	Y	
60.395	Reporting and Recordkeeping Requirements	Y	
60.396	Reference Methods and Procedures	Y	
60.397	Modifications	Y	
BAAQMD Condition # 10481			
Part 1	Definition of Year (basis: Cumulative Increase)	Y	
Part 2	Maximum Natural Gas Usage (basis: Cumulative Increase)	Y	
Part 3	Fuel Limitations (basis: Cumulative Increase)	Y	
Part 4	NOx Limit (basis: Cumulative Increase)	Y	
Part 5	CO Limit (basis: Cumulative Increase)	Y	
Part 6	Toxics Requirement (basis: Toxics)	N	

IV. Source-specific Applicable Requirements

Table IV - AU
Source-specific Applicable Requirements
S1061 – TRUCK AXLE COATING BOOTH
S1062 – TRUCK AXLE OVEN

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
Part 7	Quarterly Emissions Report (basis: Cumulative Increase)	Y	
Part 8	Abatement Operating Requirements (basis: BACT)	Y	
Part 11	Records Retention (basis: Cumulative Increase)	Y	
BAAQMD Condition # 10484			
Part 1	POC Emissions Limit (basis: Cumulative Increase)	Y	
Part 2	Coating Usage Limit (basis: Cumulative Increase)	Y	
Part 3	Spray Equipment Limitations (basis: BACT)	Y	
Part 4	VOC Content Limit (basis: BACT)	Y	
Part 5	No Purge Solvent Usage (basis: BACT)	Y	
Part 6	Lb/Axle Emissions Limit (basis: BACT)	Y	
Part 7	Records (basis: BACT, Cumulative Increase)	Y	
Part 8	Particulate Abatement Requirement (basis: BACT)	Y	

Table IV - AV
Source-specific Applicable Requirements
S1063 – GENERAL TRUCK AXLE BOOTH AND AREA CLEANING

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
BAAQMD Regulation 8, Rule 13	Light and Medium Duty Motor Vehicle Assembly Plants (12/20/95)		
8-13-309	Surface Preparation and Cleanup Solvent	Y	
8-13-503	Usage Records, Coatings	Y	
BAAQMD Condition # 10481			
Part 1	Definition of Year (basis: Cumulative Increase)	Y	
Part 6	Toxics Requirement (basis: Toxics)	N	
Part 7	Quarterly Emissions Report (basis: Cumulative Increase)	Y	
Part 8	Abatement Operating Requirements (basis: BACT)	Y	

IV. Source-specific Applicable Requirements

Table IV - AV
Source-specific Applicable Requirements
S1063 – GENERAL TRUCK AXLE BOOTH AND AREA CLEANING

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
Part 9	Clean-up Emissions Limit (basis: Cumulative Increase)	Y	
Part 10	Records (basis: Cumulative Increase)	Y	
Part 11	Records Retention (basis: Cumulative Increase)	Y	

Table IV - AW
Source-specific Applicable Requirements
S1070 – INSTRUMENT PANEL BOOTH, S1071 – INSTRUMENT PANEL OVEN

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
BAAQMD Regulation 1	General Provisions and Definitions (5/2/01)		
1-523	Parametric Monitoring and Recordkeeping Procedures	N	
1-523.1	Parametric monitor periods of inoperation	Y	
1-523.2	Limits on periods of inoperation	Y	
1-523.3	Reports of Violations	N	
1-523.4	Records	Y	
1-523.5	Maintenance and calibration	N	
SIP Regulation 1	General Provisions and Definitions (6/28/99)		
1-523	Parametric Monitoring and Recordkeeping Procedures	Y ¹	
1-523.3	Reports of Violations	Y ¹	
BAAQMD Regulation 6	Particulate Matter and Visible Emissions (12/19/90)		
6-301	Ringelmann No. 1 Limitation	Y	
6-305	Visible Particles	Y	
6-310	Particulate Weight Limitation	Y	
6-311	General Operations	Y	
6-401	Appearance of Emissions	Y	
BAAQMD Regulation 8, Rule 13	Light and Medium Duty Motor Vehicle Assembly Plants (12/20/95)		
8-13-308	Limits, Off-Line Coatings	Y	
8-13-503	Usage Records, Coatings	Y	

IV. Source-specific Applicable Requirements

Table IV - AW
Source-specific Applicable Requirements
S1070 – INSTRUMENT PANEL BOOTH, S1071 – INSTRUMENT PANEL OVEN

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
8-13-504	Air Pollution Abatement Equipment, Recordkeeping Requirements	Y	
BAAQMD Condition # 10320			
Part 1	All Conditions Are In Effect (basis: Cumulative Increase)	Y	
Part 2	Natural Gas Usage Limit (basis: Cumulative Increase)	Y	
Part 3	Fuel Requirements (basis: Cumulative Increase)	Y	
Part 4	NOx Limit (basis: Cumulative Increase)	Y	
Part 5	CO Limit (basis: Cumulative Increase)	Y	
Part 6	Toxics Limitations (basis: Toxics)	N	
Part 7	Records (basis: Cumulative Increase)	Y	
Part 8	Abatement Requirement (basis: BACT)	Y	
Part 9	POC Emissions Limit (basis: Cumulative Increase)	Y	
Part 10	Coatings Usage Limit (basis: Cumulative Increase; MOP Volume II, Part 3, Section 4.7)	Y	
Part 11	Adhesion Promoter (basis: Cumulative Increase)	Y	
Part 12	Transfer Efficiency Requirement (basis: BACT)	Y	
Part 13	Minimization of Solvent (basis: BACT)	Y	
Part 14	Records (basis: Cumulative Increase)	Y	
Part 15	Particulate Abatement Requirements (basis: BACT, Cumulative Increase)	Y	
Part 16	Abatement Requirement (basis: BACT, Cumulative Increase)	Y	
Part 17	Abatement Requirement (basis: BACT, Cumulative Increase)	Y	
Part 18	Net Mass Emissions (basis: BACT, Cumulative Increase)	Y	
Part 19	Thermal Oxidizer Temperature Requirements (basis: BACT, Cumulative Increase)	Y	
Part 20	Destruction Efficiency Requirements (basis: BACT, Cumulative Increase)	Y	
Part 21	NOx Limit for Thermal Oxidizers (basis: Cumulative Increase)	Y	
Part 22	Continuous Temperature Recording (basis: BACT, Cumulative Increase)	Y	
Part 23	Annual Source Test Requirement (basis: BACT, Cumulative Increase)	Y	
Part 24	Source Test Report (basis: Cumulative Increase; MOP Volume II, Part 3, Section 4.7)	Y	
Part 26	Allowable Temperature Excursion (basis: Cumulative Increase)	Y	
Part 27	Recording of Allowable Temperature Excursions (basis: Cumulative Increase)	Y	

IV. Source-specific Applicable Requirements

Table IV - AW
Source-specific Applicable Requirements
S1070 – INSTRUMENT PANEL BOOTH, S1071 – INSTRUMENT PANEL OVEN

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
Part 28	Revision of Allowable Temperature Excursions (basis: Cumulative Increase)	Y	
Part 41	POC Emissions Limit (basis: Cumulative Increase)	Y	
Part 42	Coating Usage Limit (basis: Cumulative Increase)	Y	
Part 43	Low NOx Burner Requirement (basis: BACT)	Y	
Part 44	Particulate Abatement Requirement (basis: Cumulative Increase)	Y	
Part 47	A592 Abatement Efficiency Requirement (basis: BACT)	Y	

IV. Source-specific Applicable Requirements

Table IV - AX
Source-specific Applicable Requirements
S1072 – GENERAL CLEANING & PAINT CLEANING

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
BAAQMD Regulation 8, Rule 13	Light and Medium Duty Motor Vehicle Assembly Plants (12/20/95)		
8-13-309	Surface Preparation and Cleanup Solvent	Y	
8-13-503	Usage Records, Coatings	Y	
BAAQMD Condition # 10320			
Part 1	All Conditions Are In Effect (basis: Cumulative Increase)	Y	
Part 6	Toxics Limitations (basis: Toxics)	N	
Part 7	Records (basis: Cumulative Increase)	Y	
Part 8	Abatement Operating Requirements (basis: BACT)	Y	
Part 31	POC Emissions Limit (basis: Cumulative Increase)	Y	
Part 32	Collected & Recovery Requirement (basis: BACT)	Y	
Part 33	Enclosed Collection System (basis: BACT)	Y	
Part 34	Records (basis: Regulation 2-6-409.2)	Y	

Table IV - AY
Source-specific Applicable Requirements
S1509 – PROTECTOSEAL CLEANING TANK, 40 GALLONS

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
BAAQMD Regulation 8, Rule 16	Organic Compounds – Solvent Cleaning Operations (10/16/2002)		
8-16-303	Cold Cleaner Requirements	Y	
8-16-303.1	General Operating Requirements	Y	
8-16-303.1.1	Maintain equipment in good working order.	Y	
8-16-303.1.2	Leak Repair Requirement	Y	

IV. Source-specific Applicable Requirements

Table IV - AY
Source-specific Applicable Requirements
S1509 – PROTECTOSEAL CLEANING TANK, 40 GALLONS

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
8-16-303.1.3	Solvent Storage or Disposal – Evaporation Prevention	Y	
8-16-303.1.4	Waste Solvent Disposal	Y	
8-16-303.1.4(a)	Covered Containers for Waste Solvent Awaiting Pick-up	Y	
8-16-303.1.4(b)	On-site Waste Treatment	Y	
8-16-303.1.5	Solvent Evaporation Minimization Devices shall not be Removed	Y	
8-16-303.1.6	Solvent Spray Requirements	Y	
8-16-303.2	Cold Cleaner Operating Requirements	Y	
8-16-303.2.1	Solvent shall be Drained from Cleaned Parts	Y	
8-16-303.2.2	Solvent Agitation	Y	
8-16-303.2.3	Solvent Cleaning of Porous or Absorbent Materials is Prohibited	Y	
8-16-303.3	Cold Cleaner General Equipment Requirements	Y	
8-16-303.3.1	Container	Y	
8-16-303.3.2	Solvent Evaporation Reduction for Idle Equipment	Y	
8-16-303.3.3	Used Solvent Returned to Container	Y	
8-16-303.3.4	Label Stating Operating Requirements	Y	
8-16-303.4	Control Device (one of the following)	Y	
8-16-303.4.1	Freeboard Ratio ≥ 0.75	Y	
8-16-303.5	VOC content ≤ 0.42 pounds per gallon or comply with 8-16-303.4.1 and other options	Y	
8-16-501	Solvent Records	Y	
8-16-501.2	Facility-wide Monthly Solvent Usage Records	Y	
8-16-501.3	Annual Records of Type and Amount of Solvent Used for Wipe Cleaning	Y	
8-16-501.5	Records Retained	Y	
BAAQMD Condition # 10320			
Part 1	All Conditions Are In Effect (basis: Cumulative Increase)	Y	
Part 6	Toxics Limitations (basis: Toxics)	N	
Part 31	POC Emissions Limit (basis: Cumulative Increase)	Y	
Part 32	Collected & Recovery Requirement (basis: BACT)	Y	
Part 33	Enclosed Collection System (basis: BACT)	Y	
Part 34	Records (basis: Regulation 2-6-409.2)	Y	

IV. Source-specific Applicable Requirements

Table IV - AZ
Source-specific Applicable Requirements
S1510 – COLD CLEANER

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y ¹ /N)	Future Effective Date
BAAQMD Regulation 8, Rule 16	Organic Compounds – Solvent Cleaning Operations (10/16/2002)		
8-16-303	Cold Cleaner Requirements	Y	
8-16-303.1	General Operating Requirements	Y	
8-16-303.1.1	Maintain equipment in good working order.	Y	
8-16-303.1.2	Leak Repair Requirement	Y	
8-16-303.1.3	Solvent Storage or Disposal – Evaporation Prevention	Y	
8-16-303.1.4	Waste Solvent Disposal	Y	
8-16-303.1.4(a)	Covered Containers for Waste Solvent Awaiting Pick-up	Y	
8-16-303.1.4(b)	On-site Waste Treatment	Y	
8-16-303.1.5	Solvent Evaporation Minimization Devices shall not be Removed	Y	
8-16-303.1.6	Solvent Spray Requirements	Y	
8-16-303.2	Cold Cleaner Operating Requirements	Y	
8-16-303.2.1	Solvent shall be Drained from Cleaned Parts	Y	
8-16-303.2.2	Solvent Agitation	Y	
8-16-303.2.3	Solvent Cleaning of Porous or Absorbent Materials is Prohibited	Y	
8-16-303.3	Cold Cleaner General Equipment Requirements	Y	
8-16-303.3.1	Container	Y	
8-16-303.3.2	Solvent Evaporation Reduction for Idle Equipment	Y	
8-16-303.3.3	Used Solvent Returned to Container	Y	
8-16-303.3.4	Label Stating Operating Requirements	Y	
8-16-303.4	Control Device (one of the following)	Y	
8-16-303.4.1	Freeboard Ratio ≥ 0.75	Y	
8-16-303.5	VOC content < 0.42 pounds per gallon or comply with 8-16-303.4.1 and other options	Y	
8-16-501	Solvent Records	Y	
8-16-501.2	Facility-wide Monthly Solvent Usage Records	Y	
8-16-501.3	Annual Records of Type and Amount of Solvent Used for Wipe Cleaning	Y	

IV. Source-specific Applicable Requirements

Table IV - AZ
Source-specific Applicable Requirements
S1510 – COLD CLEANER

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y ¹ /N)	Future Effective Date
8-16-501.5	Records Retained	Y	
BAAQMD Condition # 10481			
Part 1	Definition of Year (basis: Cumulative Increase)	Y	
Part 6	Toxics Requirement (basis: Toxics)	N	
Part 7	Quarterly Emissions Report (basis: Cumulative Increase)	Y	
Part 8	Abatement Operating Requirements (basis: BACT)	Y	
Part 9	Clean-up Emissions Limit (basis: Cumulative Increase)	Y	
Part 10	Records (basis: Cumulative Increase)	Y	
Part 11	Records Retention (basis: Cumulative Increase)	Y	

Table IV – BA
Source-specific Applicable Requirements
S1511 – TRUCK ELPO RESIN STORAGE TANK

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
BAAQMD Regulation 8, Rule 5	Storage of Organic Liquids (12/15/99)		
8-5-117	Exemption, Low Vapor Pressure	Y	
BAAQMD Condition # 13984			
Part 1	Throughput Limitation (basis: Cumulative Increase)	Y	
Part 2	Vapor Pressure Limitation (basis: Cumulative Increase)	Y	
Part 3	Records (basis: Cumulative Increase)	Y	

IV. Source-specific Applicable Requirements

Table IV - BB
Source-specific Applicable Requirements
S1512 – TRUCK ELPO PIGMENT STORAGE TANK

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
BAAQMD Regulation 8, Rule 5	Storage of Organic Liquids (12/15/99)		
8-5-117	Exemption, Low Vapor Pressure	Y	
BAAQMD Condition # 13985			
Part 1	Throughput Limitation (basis: Cumulative Increase)	Y	
Part 2	Vapor Pressure Limitation (basis: Cumulative Increase)	Y	
Part 3	Records (basis: Cumulative Increase)	Y	

Table IV - BC
Source-specific Applicable Requirements
S1803 – TRUCK SEALER DECK (FUGITIVE)

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
BAAQMD Regulation 8, Rule 13	Light and Medium Duty Motor Vehicle Assembly Plants (12/20/95)		
8-13-302	Final Limits, Topcoat, Spray Primer, Primer Surfacer	Y	
8-13-302.1	Final Limits, Spray Primer	Y	
8-13-406	Compliance Verification	Y	
8-13-503	Usage Records, Coatings	Y	
40 CFR 60 Subpart A	General Provisions (7/1/2000)		
60.1	Applicability.	Y	
60.2	Definitions.	Y	
60.3	Units and abbreviations.	Y	
60.4	Address.	Y	
60.5	Determination of construction or modification.	Y	

IV. Source-specific Applicable Requirements

Table IV - BC
Source-specific Applicable Requirements
S1803 – TRUCK SEALER DECK (FUGITIVE)

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
60.6	Review of plans.	Y	
60.7	Notification and record keeping.	Y	
60.8	Performance tests.	Y	
60.9	Availability of information.	Y	
60.10	State authority.	Y	
60.11	Compliance with standards and maintenance requirements.	Y	
60.12	Circumvention.	Y	
60.13	Monitoring requirements.	Y	
60.14	Modification.	Y	
60.15	Reconstruction.	Y	
60.16	Priority list.	Y	
60.17	Incorporations by reference.	Y	
60.18	General control device requirements.	Y	
60.19	General notification and reporting requirements.	Y	
40 CFR 60 Subpart MM	Standards of Performance for Automobile and Light Duty Truck Surface Coating Operations (12/24/80)		
60.392	Standards for Volatile Organic Compounds	Y	
60.392(a)	Prime Coat Operation	Y	
60.392(b)	Guide Coat Operation	Y	
60.392(c)	Topcoat Operation	Y	
60.393	Performance Test and Compliance Provisions	Y	
60.394	Monitoring of Emissions and Operations	Y	
60.395	Reporting and Recordkeeping Requirements	Y	
60.396	Reference Methods and Procedures	Y	
60.397	Modifications	Y	
BAAQMD Condition # 9175			
Part 1	VOC Content Limitation (basis: BACT, Cumulative Increase)	Y	
Part 2	Usage Limit (basis: Cumulative Increase)	Y	
Part 3	Monthly Records (basis: Cumulative Increase)	Y	
Part 4	Spray Equipment Limitations (basis: BACT)	Y	
Part 5	VOC Emission Limit (basis: Cumulative Increase)	Y	

IV. Source-specific Applicable Requirements

Table IV - BD
Source-specific Applicable Requirements
S1809 – STAMPING BODY & ASSEMBLY

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
BAAQMD Regulation 6	Particulate Matter and Visible Emissions (12/19/90)		
6-301	Ringelmann No. 1 Limitation	Y	
6-305	Visible Particles	Y	
6-310	Particulate Weight Limitation	Y	
6-311	General Operations	Y	
6-401	Appearance of Emissions	Y	
BAAQMD Regulation 8, Rule 51	Adhesive and Sealant Products (07/17/2002)		
8-51-301	Adhesive Product, Application Limits	N	
8-51-301.3	Adhesive Primers	N	
8-51-302	Adhesive Products, Substrate Limits	N	
8-51-304	Sealant Product Limits	N	
8-51-320	Solvent Evaporative Loss Minimization	Y	
8-51-501	Stationary Source, Recordkeeping Requirements	Y	
SIP Regulation 8, Rule 51	Adhesive and Sealant Products (2/26/02)		
8-51-301	Adhesive Product, Application Limits (refers to definition in SIP Regulation 8-51-226)	Y	
8-51-301.3	Adhesive Primers (refers to definition in SIP Regulation 8-51-226)	Y	
8-51-302	Adhesive Products, Substrate Limits (refers to definition in SIP Regulation 8-51-226)	Y	
8-51-304	Sealant Product Limits (refers to definition in SIP Regulation 8-51-226)	Y	
BAAQMD Condition # 7343			
Part 1	Usage Limit (basis: Cumulative Increase)	Y	
Part 2	Records (basis: Cumulative Increase)	Y	
Part 3	Emissions Limit (basis: Cumulative Increase)	Y	

IV. Source-specific Applicable Requirements

Table IV - BE
Source-specific Applicable Requirements
S1810 – CLEANING MATERIALS

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
BAAQMD Regulation 8, Rule 13	Light and Medium Duty Motor Vehicle Assembly Plants (12/20/95)		
8-13-309	Surface Preparation and Cleanup Solvent	Y	
8-13-503	Usage Records, Coatings	Y	
BAAQMD Condition # 9877			
Part 1	Usage Limit (basis: Cumulative Increase)	Y	
Part 2	Monthly Records (basis: Cumulative Increase)	Y	
Part 3	VOC Emissions Limit (basis: Cumulative Increase)	Y	
Part 4	Minimum Solvent Recovery Requirement (basis: BACT)	Y	

IV. Source-specific Applicable Requirements

Table IV - E
Source-specific Applicable Requirements
S1900 – PLASTIC PARTS ADHESION OPERATION

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
BAAQMD Condition # 18533			
Part 1	Material Usage Limit (basis: Cumulative Increase, Toxics)	Y	
Part 2	Emissions Limit (basis: Cumulative Increase; Toxics)	Y	
Part 3	Recordkeeping (basis: Cumulative Increase, Toxics)	Y	

Table IV - BF
Source-specific Applicable Requirements
S2826 – PLASTIC PLANT BAYCO PART CLEANING OVEN

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
BAAQMD Regulation 6	Particulate Matter and Visible Emissions (12/19/90)		
6-301	Ringelmann No. 1 Limitation	Y	
6-305	Visible Particles	Y	
6-310	Particulate Weight Limitation	Y	
6-311	General Operations	Y	
6-401	Appearance of Emissions	Y	
BAAQMD Regulation 9, Rule 1	Inorganic Gaseous Pollutants - Sulfur Dioxide (3/15/95)		
9-1-301	Limitations on Ground Level Concentrations	Y	
9-1-302	General Emission Limitations	Y	
BAAQMD Condition # 15149			
Part 1	Ringelmann 0.5 Limit (basis: BACT)	Y	
Part 2	Visible Emissions Check (basis: Regulation 2-6-409.2)	Y	
Part 3	Records (basis: Regulation 2-6-409.2)	Y	

IV. Source-specific Applicable Requirements

Table IV - BG
Source-specific Applicable Requirements
S3007 – NPS DRY OFF OVEN

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
BAAQMD Regulation 1	General Provisions and Definitions (5/2/01)		
1-523	Parametric Monitoring and Recordkeeping Procedures	N	
1-523.1	Parametric monitor periods of inoperation	Y	
1-523.2	Limits on periods of inoperation	Y	
1-523.3	Reports of Violations	N	
1-523.4	Records	Y	
1-523.5	Maintenance and calibration	N	
SIP Regulation 1	General Provisions and Definitions (6/28/99)		
1-523	Parametric Monitoring and Recordkeeping Procedures	Y ¹	
1-523.3	Reports of Violations	Y ¹	
BAAQMD Regulation 8, Rule 13	Light and Medium Duty Motor Vehicle Assembly Plants (12/20/95)		
8-13-306	Limits, Electrophoretic Primer	Y	
8-13-503	Usage Records, Coatings	Y	
8-13-504	Air Pollution Abatement Equipment, Recordkeeping Requirements	Y	
40 CFR 60 Subpart A	General Provisions (7/1/2000)		
60.1	Applicability.	Y	
60.2	Definitions.	Y	
60.3	Units and abbreviations.	Y	
60.4	Address.	Y	
60.5	Determination of construction or modification.	Y	
60.6	Review of plans.	Y	
60.7	Notification and record keeping.	Y	
60.8	Performance tests.	Y	
60.9	Availability of information.	Y	
60.10	State authority.	Y	
60.11	Compliance with standards and maintenance requirements.	Y	
60.12	Circumvention.	Y	

IV. Source-specific Applicable Requirements

Table IV - BG
Source-specific Applicable Requirements
S3007 – NPS DRY OFF OVEN

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
60.13	Monitoring requirements.	Y	
60.14	Modification.	Y	
60.15	Reconstruction.	Y	
60.16	Priority list.	Y	
60.17	Incorporations by reference.	Y	
60.18	General control device requirements.	Y	
60.19	General notification and reporting requirements.	Y	
40 CFR 60 Subpart MM	Standards of Performance for Automobile and Light Duty Truck Surface Coating Operations (12/24/80)		
60.392	Standards for Volatile Organic Compounds	Y	
60.392(a)	Prime Coat Operation	Y	
60.393	Performance Test and Compliance Provisions	Y	
60.394	Monitoring of Emissions and Operations	Y	
60.395	Reporting and Recordkeeping Requirements	Y	
60.396	Reference Methods and Procedures	Y	
60.397	Modifications	Y	
BAAQMD Condition #14205			
Part 1	Definition of Year (basis: Cumulative Increase)	Y	
Part 2	Allowable Temperature Excursion (basis: Cumulative Increase)	Y	
Part 3	Recording of Allowable Temperature Excursions (basis: Cumulative Increase)	Y	
Part 4	Revision of Allowable Temperature Excursions (basis: Cumulative Increase)	Y	
Part 5	POC Emissions Limit (basis: Cumulative Increase)	Y	
Part 6	Natural Gas Usage Limits (basis: Cumulative Increase)	Y	
Part 7	Fuel Usage Limitations (basis: Cumulative Increase)	Y	
Part 8	Coating Usage Limits (basis: Toxics)	N	
Part 9	NOx Emissions Limit (basis: Cumulative Increase)	Y	
Part 10	CO Emissions Limit (basis: Cumulative Increase)	Y	
Part 11	Records (basis: Cumulative Increase)	Y	
Part 12	Quarterly Emissions Records (basis: Cumulative Increase)	Y	
Part 13	Abatement Operating Requirements (basis: BACT)	Y	

IV. Source-specific Applicable Requirements

Table IV - BH
Source-specific Applicable Requirements
S3008 – NPS PRIME BOOTH

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
BAAQMD Regulation 1	General Provisions and Definitions (5/2/01)		
1-523	Parametric Monitoring and Recordkeeping Procedures	N	
1-523.1	Parametric monitor periods of inoperation	Y	
1-523.2	Limits on periods of inoperation	Y	
1-523.3	Reports of Violations	N	
1-523.4	Records	Y	
1-523.5	Maintenance and calibration	N	
SIP Regulation 1	General Provisions and Definitions (6/28/99)		
1-523	Parametric Monitoring and Recordkeeping Procedures	Y ¹	
1-523.3	Reports of Violations	Y ¹	
BAAQMD Regulation 6	Particulate Matter and Visible Emissions (12/19/90)		
6-301	Ringelmann No. 1 Limitation	Y	
6-305	Visible Particles	Y	
6-310	Particulate Weight Limitation	Y	
6-311	General Operations	Y	
6-401	Appearance of Emissions	Y	
BAAQMD Regulation 8, Rule 13	Light and Medium Duty Motor Vehicle Assembly Plants (12/20/95)		
8-13-302	Final Limits, Topcoat, Spray Primer, Primer Surfacer	Y	
8-13-503	Usage Records, Coatings	Y	
8-13-504	Air Pollution Abatement Equipment, Recordkeeping Requirements	Y	
40 CFR 60 Subpart A	General Provisions (7/1/2000)		
60.1	Applicability.	Y	
60.2	Definitions.	Y	
60.3	Units and abbreviations.	Y	
60.4	Address.	Y	
60.5	Determination of construction or modification.	Y	
60.6	Review of plans.	Y	

IV. Source-specific Applicable Requirements

Table IV - BH
Source-specific Applicable Requirements
S3008 – NPS PRIME BOOTH

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
60.7	Notification and record keeping.	Y	
60.8	Performance tests.	Y	
60.9	Availability of information.	Y	
60.10	State authority.	Y	
60.11	Compliance with standards and maintenance requirements.	Y	
60.12	Circumvention.	Y	
60.13	Monitoring requirements.	Y	
60.14	Modification.	Y	
60.15	Reconstruction.	Y	
60.16	Priority list.	Y	
60.17	Incorporations by reference.	Y	
60.18	General control device requirements.	Y	
60.19	General notification and reporting requirements.	Y	
40 CFR 60 Subpart MM	Standards of Performance for Automobile and Light Duty Truck Surface Coating Operations (12/24/80)		
60.392	Standards for Volatile Organic Compounds	Y	
60.392(a)	Prime Coat Operation	Y	
60.393	Performance Test and Compliance Provisions	Y	
60.394	Monitoring of Emissions and Operations	Y	
60.395	Reporting and Recordkeeping Requirements	Y	
60.396	Reference Methods and Procedures	Y	
60.397	Modifications	Y	
BAAQMD Condition #14205			
Part 1	Definition of Year (basis: Cumulative Increase)	Y	
Part 2	Allowable Temperature Excursion (basis: Cumulative Increase)	Y	
Part 3	Recording of Allowable Temperature Excursions (basis: Cumulative Increase)	Y	
Part 4	Revision of Allowable Temperature Excursions (basis: Cumulative Increase)	Y	
Part 5	POC Emissions Limit (basis: Cumulative Increase)	Y	
Part 6	Natural Gas Usage Limits (basis: Cumulative Increase)	Y	
Part 7	Fuel Usage Limitations (basis: Cumulative Increase)	Y	
Part 8	Coating Usage Limits (basis: Toxics)	N	

IV. Source-specific Applicable Requirements

**Table IV - BH
 Source-specific Applicable Requirements
 S3008 – NPS PRIME BOOTH**

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
Part 9	NOx Emissions Limit (basis: Cumulative Increase)	Y	
Part 10	CO Emissions Limit (basis: Cumulative Increase)	Y	
Part 11	Records (basis: Cumulative Increase)	Y	
Part 12	Quarterly Emissions Records (basis: Cumulative Increase)	Y	
Part 13	Abatement Operating Requirements (basis: BACT)	Y	
BAAQMD Condition #14206			
Part 1	POC Emissions Limit (basis: Cumulative Increase)	Y	
Part 2	Coating Usage Limit (basis: Cumulative Increase)	Y	
Part 4	Spray Equipment Limitations (basis: BACT)	Y	
Part 5	Thermal Oxidizer Usage During Clean-Up Operation (basis: BACT)	Y	
Part 6	Minimization of Solvent Usage (basis: BACT)	Y	
Part 7	Particulate Abatement Requirement (basis: Cumulative Increase)	Y	
Part 8	Abatement Requirement (basis: BACT)	Y	
Part 9	Abatement Requirement (basis: BACT)	Y	
Part 10	Minimum Temperature Requirement (basis: BACT)	Y	
Part 11	Destruction Efficiency Requirement (basis: BACT)	Y	
Part 12	Continuous Temperature Measurement (basis: BACT)	Y	
Part 13	Source Test Requirement (basis: BACT)	Y	
Part 14	Source Test Report (basis: BACT; MOP Volume II, Part 3, Section 4.7)	Y	
Part 18	Source Test of A30082 (basis: BACT)	Y	

**Table IV - BI
 Source-specific Applicable Requirements
 S3009 – NPS PRIME OVEN**

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
BAAQMD Regulation 6	Particulate Matter and Visible Emissions (12/19/90)		
6-301	Ringelmann No. 1 Limitation	Y	

IV. Source-specific Applicable Requirements

Table IV - BI
Source-specific Applicable Requirements
S3009 – NPS PRIME OVEN

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
6-305	Visible Particles	Y	
6-310	Particulate Weight Limitation	Y	
6-311	General Operations	Y	
6-401	Appearance of Emissions	Y	
BAAQMD Regulation 8, Rule 13	Light and Medium Duty Motor Vehicle Assembly Plants (12/20/95)		
8-13-302	Final Limits, Topcoat, Spray Primer, Primer Surfacer	Y	
8-13-503	Usage Records, Coatings	Y	
8-13-504	Air Pollution Abatement Equipment, Recordkeeping Requirements	Y	
40 CFR 60 Subpart A	General Provisions (7/1/2000)		
60.1	Applicability.	Y	
60.2	Definitions.	Y	
60.3	Units and abbreviations.	Y	
60.4	Address.	Y	
60.5	Determination of construction or modification.	Y	
60.6	Review of plans.	Y	
60.7	Notification and record keeping.	Y	
60.8	Performance tests.	Y	
60.9	Availability of information.	Y	
60.10	State authority.	Y	
60.11	Compliance with standards and maintenance requirements.	Y	
60.12	Circumvention.	Y	
60.13	Monitoring requirements.	Y	
60.14	Modification.	Y	
60.15	Reconstruction.	Y	
60.16	Priority list.	Y	
60.17	Incorporations by reference.	Y	
60.18	General control device requirements.	Y	
60.19	General notification and reporting requirements.	Y	
40 CFR 60 Subpart MM	Standards of Performance for Automobile and Light Duty Truck Surface Coating Operations (12/24/80)		
60.392	Standards for Volatile Organic Compounds	Y	

IV. Source-specific Applicable Requirements

Table IV - BI
Source-specific Applicable Requirements
S3009 – NPS PRIME OVEN

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
60.392(a)	Prime Coat Operation	Y	
60.393	Performance Test and Compliance Provisions	Y	
60.394	Monitoring of Emissions and Operations	Y	
60.395	Reporting and Recordkeeping Requirements	Y	
60.396	Reference Methods and Procedures	Y	
60.397	Modifications	Y	
BAAQMD Condition #14205			
Part 1	Definition of Year (basis: Cumulative Increase)	Y	
Part 2	Allowable Temperature Excursion (basis: Cumulative Increase)	Y	
Part 3	Recording of Allowable Temperature Excursions (basis: Cumulative Increase)	Y	
Part 4	Revision of Allowable Temperature Excursions (basis: Cumulative Increase)	Y	
Part 5	POC Emissions Limit (basis: Cumulative Increase)	Y	
Part 6	Natural Gas Usage Limits (basis: Cumulative Increase)	Y	
Part 7	Fuel Usage Limitations (basis: Cumulative Increase)	Y	
Part 8	Coating Usage Limits (basis: Toxics)	N	
Part 9	NOx Emissions Limit (basis: Cumulative Increase)	Y	
Part 10	CO Emissions Limit (basis: Cumulative Increase)	Y	
Part 11	Records (basis: Cumulative Increase)	Y	
Part 12	Quarterly Emissions Records (basis: Cumulative Increase)	Y	
Part 13	Abatement Operating Requirements (basis: BACT)	Y	
BAAQMD Condition #14206			
Part 1	POC Emissions Limit (basis: Cumulative Increase)	Y	
Part 2	Coating Usage Limit (basis: Cumulative Increase)	Y	
Part 3	NOx Emission Limit (basis: Cumulative Increase)	Y	
Part 4	Spray Equipment Limitations (basis: BACT)	Y	
Part 5	Thermal Oxidizer Usage During Clean-Up Operation (basis: BACT)	Y	
Part 6	Minimization of Solvent Usage (basis: BACT)	Y	
Part 7	Particulate Abatement Requirement (basis: Cumulative Increase)	Y	
Part 8	Abatement Requirement (basis: BACT)	Y	

IV. Source-specific Applicable Requirements

Table IV - BI
Source-specific Applicable Requirements
S3009 – NPS PRIME OVEN

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
Part 9	Abatement Requirement (basis: BACT)	Y	
Part 10	Minimum Temperature Requirement (basis: BACT)	Y	
Part 11	Destruction Efficiency Requirement (basis: BACT)	Y	
Part 12	Continuous Temperature Measurement (basis: BACT)	Y	
Part 13	Source Test Requirement (basis: BACT)	Y	
Part 14	Source Test Report (basis: BACT)	Y	
Part 17	Source Test for Heater Boxes (basis: Regulation 2-6-409.2)	Y	

IV. Source-specific Applicable Requirements

Table IV - BJ
Source-specific Applicable Requirements
S3014 – NPS TOP COAT BOOTH #1 S3015 – NPS TOP COAT OVEN #1
S3016 – NPS TOPCOAT BOOTH #2
S3017 – NPS TOPCOAT OVEN #2

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
BAAQMD Regulation 1	General Provisions and Definitions (5/2/01)		
1-523	Parametric Monitoring and Recordkeeping Procedures	N	
1-523.1	Parametric monitor periods of inoperation	Y	
1-523.2	Limits on periods of inoperation	Y	
1-523.3	Reports of Violations	N	
1-523.4	Records	Y	
1-523.5	Maintenance and calibration	N	
SIP Regulation 1	General Provisions and Definitions (6/28/99)		
1-523	Parametric Monitoring and Recordkeeping Procedures	Y ¹	
1-523.3	Reports of Violations	Y ¹	
BAAQMD Regulation 6	Particulate Matter and Visible Emissions (12/19/90)		
6-301	Ringelmann No. 1 Limitation	Y	
6-305	Visible Particles	Y	
6-310	Particulate Weight Limitation	Y	
6-311	General Operations	Y	
6-401	Appearance of Emissions	Y	
BAAQMD Regulation 8, Rule 13	Light and Medium Duty Motor Vehicle Assembly Plants (12/20/95)		
8-13-302	Final Limits, Topcoat, Spray Primer, Primer Surfacer	Y	
8-13-503	Usage Records, Coatings	Y	
8-13-504	Air Pollution Abatement Equipment, Recordkeeping Requirements	Y	
40 CFR 60 Subpart A	General Provisions (7/1/2000)		
60.1	Applicability.	Y	
60.2	Definitions.	Y	
60.3	Units and abbreviations.	Y	
60.4	Address.	Y	
60.5	Determination of construction or modification.	Y	

IV. Source-specific Applicable Requirements

Table IV - BJ
Source-specific Applicable Requirements
S3014 – NPS TOP COAT BOOTH #1 S3015 – NPS TOP COAT OVEN #1
S3016 – NPS TOPCOAT BOOTH #2
S3017 – NPS TOPCOAT OVEN #2

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
60.6	Review of plans.	Y	
60.7	Notification and record keeping.	Y	
60.8	Performance tests.	Y	
60.9	Availability of information.	Y	
60.10	State authority.	Y	
60.11	Compliance with standards and maintenance requirements.	Y	
60.12	Circumvention.	Y	
60.13	Monitoring requirements.	Y	
60.14	Modification.	Y	
60.15	Reconstruction.	Y	
60.16	Priority list.	Y	
60.17	Incorporations by reference.	Y	
60.18	General control device requirements.	Y	
60.19	General notification and reporting requirements.	Y	
40 CFR 60 Subpart MM	Standards of Performance for Automobile and Light Duty Truck Surface Coating Operations (12/24/80)		
60.392	Standards for Volatile Organic Compounds	Y	
60.392(a)	Prime Coat Operation	Y	
60.392(b)	Guide Coat Operation	Y	
60.392(c)	Topcoat Operation	Y	
60.393	Performance Test and Compliance Provisions	Y	
60.394	Monitoring of Emissions and Operations	Y	
60.395	Reporting and Recordkeeping Requirements	Y	
60.396	Reference Methods and Procedures	Y	
60.397	Modifications	Y	
BAAQMD Condition #14205			
Part 1	Definition of Year (basis: Cumulative Increase)	Y	
Part 2	Allowable Temperature Excursion (basis: Cumulative Increase)	Y	
Part 3	Recording of Allowable Temperature Excursions (basis: Cumulative Increase)	Y	

IV. Source-specific Applicable Requirements

Table IV - BJ
Source-specific Applicable Requirements
S3014 – NPS TOP COAT BOOTH #1 S3015 – NPS TOP COAT OVEN #1
S3016 – NPS TOPCOAT BOOTH #2
S3017 – NPS TOPCOAT OVEN #2

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
Part 4	Revision of Allowable Temperature Excursions (basis: Cumulative Increase)	Y	
Part 5	POC Emissions Limit (basis: Cumulative Increase)	Y	
Part 6	Natural Gas Usage Limits (basis: Cumulative Increase)	Y	
Part 7	Fuel Usage Limitations (basis: Cumulative Increase)	Y	
Part 8	Coating Usage Limits (basis: Toxics)	N	
Part 9	NOx Emissions Limit (basis: Cumulative Increase)	Y	
Part 10	CO Emissions Limit (basis: Cumulative Increase)	Y	
Part 11	Records (basis: Cumulative Increase)	Y	
Part 12	Quarterly Emissions Records (basis: Cumulative Increase)	Y	
Part 13	Abatement Operating Requirements (basis: BACT)	Y	
BAAQMD Condition #14207			
Part 1	POC Emissions Limit (basis: Cumulative Increase)	Y	
Part 2	Coating Usage Limit (basis: Cumulative Increase)	Y	
Part 3	NOx Emission Limit (basis: Cumulative Increase)	Y	
Part 4	Spray Equipment Limitations (basis: BACT)	Y	
Part 5	Thermal Oxidizer Usage During Clean-Up Operation (basis: BACT)	Y	
Part 6	Minimization of Solvent Usage (basis: BACT)	Y	
Part 7	Particulate Abatement Requirement (basis: Cumulative Increase)	Y	
Part 8	Abatement Requirement (basis: BACT)	Y	
Part 9	Abatement Requirement (basis: BACT)	Y	
Part 10	Minimum Temperature Requirement (basis: BACT)	Y	
Part 11	VOC Destruction Efficiency (basis: BACT)	Y	
Part 12	Continuous Temperature Monitor (basis: BACT)	Y	
Part 13	Annual Source Test (basis: BACT)	Y	
Part 14	Source Test Report (basis: BACT)	Y	
Part 17	Source Test for Heater Boxes (basis: Regulation 2-6-409.2)	Y	

IV. Source-specific Applicable Requirements

Table IV – BM
Source-specific Applicable Requirements
S3500 – COLD CLEANER, S3501 – COLD CLEANER, S3502 – COLD CLEANER

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
BAAQMD Regulation 8, Rule 16	Organic Compounds – Solvent Cleaning Operations (10/16/2002)		
8-16-303	Cold Cleaner Requirements	Y	
8-16-303.1	General Operating Requirements	Y	
8-16-303.1.1	Maintain equipment in good working order.	Y	
8-16-303.1.2	Leak Repair Requirement	Y	
8-16-303.1.3	Solvent Storage or Disposal – Evaporation Prevention	Y	
8-16-303.1.4	Waste Solvent Disposal	Y	
8-16-303.1.4(a)	Covered Containers for Waste Solvent Awaiting Pick-up	Y	
8-16-303.1.4(b)	On-site Waste Treatment	Y	
8-16-303.1.5	Solvent Evaporation Minimization Devices shall not be Removed	Y	
8-16-303.1.6	Solvent Spray Requirements	Y	
8-16-303.2	Cold Cleaner Operating Requirements	Y	
8-16-303.2.1	Solvent shall be Drained from Cleaned Parts	Y	
8-16-303.2.2	Solvent Agitation	Y	
8-16-303.2.3	Solvent Cleaning of Porous or Absorbent Materials is Prohibited	Y	
8-16-303.3	Cold Cleaner General Equipment Requirements	Y	
8-16-303.3.1	Container	Y	
8-16-303.3.2	Solvent Evaporation Reduction for Idle Equipment	Y	
8-16-303.3.3	Used Solvent Returned to Container	Y	
8-16-303.3.4	Label Stating Operating Requirements	Y	
8-16-303.4	Control Device (one of the following)	Y	
8-16-303.4.1	Freeboard Ratio ≥ 0.75	Y	
8-16-303.5	VOC content ≤ 0.42 pounds per gallon or comply with 8-16-303.4.1 and other options	Y	
8-16-501	Solvent Records	Y	
8-16-501.2	Facility-wide Monthly Solvent Usage Records	Y	
8-16-501.3	Annual Records of Type and Amount of Solvent Used for Wipe Cleaning	Y	
8-16-501.5	Records Retained	Y	

IV. Source-specific Applicable Requirements

**Table IV – BM
 Source-specific Applicable Requirements
 S3500 – COLD CLEANER, S3501 – COLD CLEANER, S3502 – COLD CLEANER**

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
BAAQMD Condition #14205			
Part 1	Definition of Year (basis: Cumulative Increase)	Y	
Part 5	POC Emissions Limit (basis: Cumulative Increase)	Y	
Part 11	Records (basis: Cumulative Increase)	Y	
Part 12	Quarterly Emissions Records (basis: Cumulative Increase)	Y	
BAAQMD Condition #14210			
Part 1	POC Emissions Limit (basis: Cumulative Increase)	Y	
Part 2	Solvent Collection & Recovery Requirement (basis: BACT)	Y	
Part 3	Enclosed Collection System (basis: Cumulative Increase)	Y	

**Table IV - BN
 Source-specific Applicable Requirements
 S3503 – NPS PURGE THINNER TANK
 S3505 – NPS WASTE SOLVENT TANK**

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
BAAQMD Regulation 8, Rule 5	Storage of Organic Liquids (12/15/99)		
8-5-301	Storage Tank Smaller than 150 m ³	Y	
8-5-303	Above Ground Storage Tank Larger than 37.5 m ³ and Smaller than 75 m ³	Y	
8-5-501	Records	Y	
BAAQMD Condition #14205			
Part 1	Definition of Year (basis: Cumulative Increase)	Y	
Part 5	POC Emissions Limit (basis: Cumulative Increase)	Y	
Part 11	Records (basis: Cumulative Increase)	Y	

IV. Source-specific Applicable Requirements

Table IV - BN
Source-specific Applicable Requirements
S3503 – NPS PURGE THINNER TANK
S3505 – NPS WASTE SOLVENT TANK

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
Part 12	Quarterly Emissions Records (basis: Cumulative Increase)	Y	
BAAQMD Condition #14211			
Part 1	Usage Restriction (basis: Cumulative Increase)	Y	
Part 2	Submerged Fill Pipe (basis: Regulation 8-5-301.1)	Y	

Table IV – BR
Source-specific Applicable Requirements
S30960 – GENERAL CLEANING AND PAINTING CLEANING

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
BAAQMD Regulation 8, Rule 13	Light and Medium Duty Motor Vehicle Assembly Plants (12/20/95)		
8-13-309	Surface Preparation and Cleanup Solvent	Y	
8-13-503	Usage Records, Coatings	Y	
BAAQMD Condition #14205			
Part 1	Definition of Year (basis: Cumulative Increase)	Y	
Part 5	POC Emissions Limit (basis: Cumulative Increase)	Y	
Part 11	Records (basis: Cumulative Increase)	Y	
Part 12	Quarterly Emissions Records (basis: Cumulative Increase)	Y	
Part 13	Abatement Operating Requirements (basis: BACT)	Y	
BAAQMD Condition #14210			
Part 1	POC Emissions Limit (basis: Cumulative Increase)	Y	
Part 2	Solvent Collection & Recovery Requirement (basis: BACT)	Y	

IV. Source-specific Applicable Requirements

**Table IV – BR
 Source-specific Applicable Requirements
 S30960 – GENERAL CLEANING AND PAINTING CLEANING**

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
Part 3	Enclosed Collection System (basis: Cumulative Increase)	Y	

**Table IV – BS
 Source-specific Applicable Requirements
 FACILITY**

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
40 CFR 63 Subpart A	National Emission Standards for Hazardous Air Pollutants for Source Categories: General Provisions; and Requirements for Control Technology Determinations for Major Sources in Accordance with Clean Air Act Sections, Section 112(g) and 112(j); Final Rule – General Provisions		
63.52	Approved process for new and existing affected sources.	Y	
63.52(a)	Sources subject to section 112(j) as of the section 112(j) deadline	Y	
63.52(a)(1)	Submit an application for Title V permit revision	Y	
63.52(a)(2)	Submit an application for a Title V permit revision within 30 days after being notified by permitting authority	Y	
63.52(e)	Permit application review	Y	
63.52(e)(1)	Submit a Part 2 MACT application meeting the requirements of 63.53(b)	Y	
63.52(h)	Enhanced monitoring	Y	
63.52(h)(i)	MACT emission limitations	Y	
63.52(h)(i)(1)	Compliance with all requirements applicable to affected sources, including compliance date for affected sources	Y	
63.53	Application content for case-by-case MACT determination	Y	
63.53(a)	Part 1 MACT application	Y	
63.53(b)	Part 2 MACT application	Y	

V. SCHEDULE OF COMPLIANCE

The permit holder shall comply with all applicable requirements cited in this permit. The permit holder shall also comply with applicable requirements that become effective during the term of this permit on a timely basis.

VI. Permit Conditions

VI. PERMIT CONDITIONS

Any condition that is preceded by an asterisk is not federally enforceable.

Note: All italics lettering contains explanatory material for the permit proposal and will be deleted in the final permit.

Condition # 207

For S2, PASSENGER BODY ELPO DIP TANK,
S3, PASSENGER BODY ELPO OVEN
S60, PASSENGER UNDERCOATING BOOTH
S61, PASSENGER BLACKOUT CHASSIS BOOTH
S62, PASSENGER FUEL TANK BOOTH
S63, PASSENGER PROTECTIVE GAS TANK OVEN
S71, PASSENGER CAVITY WAX BOOTH
S72, PASSENGER PVC EXTERIOR, UNDERBODY & ENGINE WAX BOOTH
S73, PASSENGER EXTERIOR WAX HOT AIR DRYER
S101, SPARE PARTS ELPO DIP TANK
S102, SPARE PARTS ELPO OVEN
S801, STAMPING PLANT FUGITIVE SOLVENT EMISSION
S802, STAMPING PLANT FUGITIVE MACHINING
S803, PASSENGER SEALER DECK LINE (FUGITIVE)
S804, PASSENGER FUGITIVE REPAIR PRIMING
S805, BODY SHOP ASSEMBLY AREAS
S807, PASSENGER ANTI-CHIP WHEELHOUSE BOOTH
S808, PASSENGER SEALER-ANTICHIP OVEN
S813, PASSENGER FUGITIVE TRIAL APPLICATION AREA – BEAD SEALER

1. EMISSIONS LIMITATION

- a. Total emissions for the sources listed for Condition 207, not including any reduction due to abatement devices and activities, shall not exceed 459.2 tons of VOC during any consecutive 12-month period. Total emissions of organic compounds, including reductions due to abatement measures, shall not exceed 250.5 tons of VOC per year. (basis: Cumulative Increase)
- b. Fugitive emissions for S801, S802, S803, S804, S805, and S813 shall be calculated based upon materials used and the materials' VOC content. Total fugitive emissions from S801, S802, S803, S804, S805, and S813, shall not exceed 69 tons during any consecutive 12-month period or 6.8 tons per month. (basis: Cumulative Increase)
- c. Compliance with emission limitations shall be demonstrated by calculation, utilizing material usage rates and VOC content, unless other methods are specified or approved in writing by the APCO. (basis: Cumulative Increase)

VI. Permit Conditions

- d. Calculated or Controlled emissions for the listed materials shall not exceed those listed in the Emissions Limitation Table for these sources:

Emission Limitation Table

Primer	Material	Calculated Emissions (Tons/yr.)	Controlled Emissions (Tons/Yr)
	Passenger Body Elpo	133.9	66.4
	Spare Parts Elpo	17.2	6.9
	Anti Chip II	31.4	7.2
	Anti Chip IB	28.0	22.0
	Blackout Chassis	18.1	Not Applicable
	Undercoating	93.8	14.5
	Final Repair ^(*)	2.0	Not applicable
	Protective Gas Tank	19.1	9.3

Fugitive	Paint Shop Sealant	17.0	5.4
	Repair Primer ^(*)	5.1	Not applicable
	Cavity Wax	2.5	Not applicable
	Underbody Wax	5.3	Not applicable
	Hinge	4.9	Not applicable
	Engine Wax	0.5	Not applicable
	Exterior Wax	5.9	Not applicable
	All Materials Used In Body & Assembly Areas	69.0	Not applicable
	Underbody Black (S801+S802+S803+ S804+S805+S813) out	5.5	Not applicable

Totals (Tons/Year)

459.2

250.5

(*) The final Repair and Repair Primer sections include prime and color touch-up coatings.

- e. The total VOC emissions due to operation of the wax booths and oven (S-71, S-72 and S-73) shall not exceed 19 tons/year and 150 pounds/day. (basis: Cumulative Increase)

2. MATERIAL USAGE LIMITATIONS

- a. Material usage for these sources cannot exceed the values listed this VOC Material

VI. Permit Conditions

Content and Use Table (Table 1). (basis: Cumulative Increase)

Coating	Material Type	Lbs. VOC/Gal	Annual Limits (Gal)	Monthly Limit (Gal) (*)	Condition 207 Source No.(s)
	Passenger Body ELPO	1.21	221,334	21,725	2, 3
	Spare Parts ELPO	1.21	28,400	3,156	101, 102
	Anti-Chip II	2.09	30,009	2,946	807
	Anti-Chip IB	4.06	13,786	1,353	807
	Blackout Chassis	3.02	11,990	1,177	61
	Undercoating	0.57	328,967	32,290	60, 803
	Final Repair	6.41	637	63	805
	Protective Fuel Tank	0.95	40,124	3,497	62, 63

Fugitive	Paint Shop Sealant	0.39	87,129	10,753	805
	Repair Primer	5.83	1,750	172	805
	Cavity Wax	0.94	5,236	523	71
	Underbody Wax	1.04	10,096	991	805, 807
	Hinge Wax	5.01	1,962	193	71
	Engine Wax	0.59	1,538	151	72
	Exterior Wax	1.50	7,900	776	73
	All materials used in Body & Assembly Areas	NA	NA	NA	801, 802, 803, 804, 805, 813
	Underbody Black (S801+S802+S803+S804+S805+S813)	3.02	3,642	357	801, 802, 803, 804, 805, 813

(*) All material usage and VOC content are expressed excluding water.

- b. NUMMI may petition the APCO to accept alternative usage and/or VOC content limits equivalent to the specified values in VOC Material Content and Use Table, Table 1. (basis: Cumulative Increase)
- c. If any District regulation, specifies more stringent requirements that those listed in the VOC Material Content and Use Table, Table 1, or other parts of these conditions, then the more stringent requirement shall apply. (basis: Regulation 1-102)

VI. Permit Conditions

3. EMISSION CONTROL EQUIPMENT

Abatement equipment must be operating during periods of passenger vehicle or passenger spare/small parts production and during subsequent clean-up operations. Abatement equipment is not required to operate during periods when there are no VOC emissions. (basis: BACT)

- a. SPARE PARTS ELPO OVEN CATALYTIC THERMAL OXIDIZER (A102)
 1. Catalytic thermal oxidizer (A102) shall be maintained and operated continuously for S102, Spare Parts ELPO Oven, with a minimum destruction efficiency of 60% or an outlet concentration of 10 ppm by volume or less. The minimum destruction/operating temperature shall be 800 °F. The destruction temperature shall be continuously recorded using chart or digital recorders. (basis: Cumulative Increase)
 2. NUMMI shall conduct a source test for this abatement system (A102), once per calendar year. The source test shall measure both the inlet and outlet concentrations of the non-methane hydrocarbons abated by the system. (basis: Cumulative Increase)
 3. Within 60 days of the source test, a report shall be provided to the District. This 60-day period may be extended to 90 days, if NUMMI can demonstrate to the satisfaction of the APCO that the additional time is required. If the source testing indicates any violation of the permit conditions for Condition 207, NUMMI shall report such violation to the Director of Enforcement within 10 days of discovery pursuant to Standard Condition 1.F. (basis: Cumulative Increase, Regulation 2-6-501, MOP Volume II, Part 3, Section 4.7)
- b. PASSENGER SEALER OVEN THERMAL OXIDIZER
 1. All volatile organic compound (VOC) emissions from S808, Passenger Sealer-Antichip Oven, shall be abated by thermal incineration (A809). The thermal oxidizer (A809) shall be source tested as required in Part 3 of Condition # 207 to determine net mass emissions of POC as described in the following procedure:
 - a. The net mass emissions of POC shall be determined for the sources listed above with their respective coating sources combined. To determine the net mass emissions, the following shall be calculated and/or measured:
 - b. POC emissions on a pounds per unit basis [A] shall be determined by multiplying the annual coating usage with the POC content and dividing by the annual production rate.
 - c. POC emissions to each booth and oven Thermal Oxidizer (averaged, using the data obtained from at least 3 current source tests) shall be determined using District approved source testing methods [B].

VI. Permit Conditions

- d. POC emissions from each booth and oven Thermal Oxidizer (averaged, using the data obtained from at least 3 current source tests) shall be determined using District approved source testing methods [C].
 - e. [B] and [C] shall each be divided by the production rate measured during the source test yielding a pounds per unit basis. [B] and [C] shall be each multiplied by the annualized units per hour and divided by the source test measured units per hour rate.
 - f. The net mass emissions shall be calculated by subtracting the measured POC emissions from the inlet from the calculated POC emissions and adding the measured POC emissions from the outlet [A-B+C].
 - g. The determined value [A-B+C] shall be multiplied by the actual annual production rate.
 - h. Within 60 days of the source test, a report shall be provided to the District. This 60-day period may be extended to 90 days, if NUMMI can demonstrate to the satisfaction of the APCO that the additional time is required. If the source testing indicates any violation of the permit conditions (total mass emission greater than emission limits for coating line (booth(s) and oven(s) combined)), NUMMI shall report such violation to the Director of Enforcement within 10 days of discovery pursuant to Standard Condition 1.F. (basis: Cumulative Increase, Regulation 2-6-501, MOP Volume II, Part 3, Section 4.7)
2. S808 Passenger Sealer-Antichip Oven, cooling tunnel and setting zone emissions shall be controlled by thermal incineration with the following parameters.
 - a. 1400°F minimum destruction temperature unless NUMMI can demonstrate to the satisfaction of the APCO that the permit conditions can be met with the Thermal Oxidizer (A809) operating at a lower temperature.
 - b. VOC destruction efficiency of 98.5% by weight whenever the inlet concentration of VOC to the Thermal Oxidizer (A 808) is equal to or greater than 500 ppmv, measured as methane. Below a concentration of 500 ppmv, either the precursor organic destruction efficiency shall be a minimum of 95% by weight or total non-methane organic carbon emissions from the outlet of the Thermal Oxidizer (A809) shall be 10 ppm by volume or less.
 - c. The destruction temperature shall be recorded using chart or digital recorders. (basis: Cumulative Increase; BACT)
 3. The thermal oxidizer shall be source tested once per calendar year, unless a different schedule is approved by the APCO, and maintained on a regular basis. Records of the source test results and completed maintenance activities shall be kept for a minimum of 5 years from the date of the source test report and the date of the maintenance activity. (basis: BACT)

VI. Permit Conditions

4. ALLOWABLE TEMPERATURE EXCURSION(S)

- a.
 1. NUMMI may operate the Thermal Oxidizer (A809) below 1400 degrees F only in compliance with the temperature excursion parameters set forth in Parts 4b and 4c of Condition 207. (basis: BACT)
 2. NUMMI may operate the Thermal Oxidizer (A102) below 800 degrees F only in compliance with the temperature excursion parameters set forth in Parts 4b and 4c of Condition 207. (basis: BACT)
- b. The minimum temperature and abatement efficiency requirements for Thermal Oxidizers located at NUMMI shall not apply during an "Allowable Temperature Excursion", provided that the controller set temperature is at or above the minimum temperature requirement. An Allowable Temperature Excursion is one of the following:
 1. A temperature excursion not exceeding 20 degrees F below the minimum; or
 2. A temperature excursion period or period(s) aggregating 15 minutes or less in any hour or less; or
 3. A temperature excursion greater than 15 minutes but less than 3 hours in duration, provided that all of the following are satisfied:
 - a. There are no more than 2 excursions per facility (Plant No. A1438) per calendar day;
 - b. There are no more than 2 excursions per abatement device per month; and
 - c. There are no more than 5 excursions per facility (Plant No. A1438) per month.(basis: Cumulative Increase)
- c. NUMMI shall keep records to demonstrate that it meets all qualifying criteria for Allowable Temperature Excursions are met, including but not limited to the following:
 1. Starting date and time; and the duration of each Allowable Temperature Excursion;
 2. Minimum temperature during each Allowable Temperature Excursion;
 3. Number of Allowable Temperature Excursions (>15 minutes) per abatement device per month;
 4. Total number of Allowable Temperature Excursions (> 15 minutes) for the facility per month. A summary of these records shall be included in NUMMI's monthly report to the District. To satisfy the NSPS requirement of 40 CFR 60, Subpart MM, a declaration is also required in NUMMI's monthly report if there are no temperature excursions.(basis: Cumulative Increase)
- d. The District may revise or revoke the allowable temperature excursion(s) section of Condition 207, if source operations change significantly such that the basis for granting this condition is no longer valid. (basis: Cumulative Increase)

VI. Permit Conditions

5 RECORD KEEPING AND REPORTING

- a. All records required by Condition 207 shall be kept and made available for District inspection for a period of 5 years following the date of entry. (basis: Cumulative Increase)
- b. For all paints, primers, sealants, coatings, solvents and miscellaneous cleaning materials used for the sources listed for Condition 207, monthly records of material usage must be kept for five years. A monthly report including material usage and a summary of total actual organic emissions from all sources applicable to Condition 207 shall be submitted to the District within 30 days after the end of each month. If the total organic emissions for any month exceeds 41.6 tons, the District shall be notified in writing within 30 days of the report as to what steps will be taken to assure that the limit of 459.2 tons per year will not be exceeded. (basis: Cumulative Increase)
- c. The temperature chart or digital recorder is subject to the parametric monitoring and recordkeeping requirements of Regulation 1-523. (basis: Regulation 1-523)

6. SAMPLING

Samples of coating materials shall be made available to the District upon request by the APCO. (basis: Regulation 1-441)

7. ENFORCEMENT

Violation by NUMMI of any of the conditions set forth in this permit shall subject NUMMI to enforcement action under Chapter 4 of Part 4 of Division 26 of the California Health and Safety Code. (basis: Regulation 1-401)

8. MISCELLANEOUS

- a. All equipment, facilities, and systems installed or used to achieve compliance with the terms and conditions of this Permit to Operate shall at all times be maintained in good working order. (basis: Cumulative Increase)
- *b. For the purpose of these conditions, any reference to "NUMMI" shall be deemed to also refer to the NUMMI's agents, contractors, subcontractors, assignees, or joint venture partners, as well as to any party brought in to operate the proposed facility, as appropriate. (basis: Regulation 1-241)
- c. The APCO shall have the right to inspect and audit all records required to be maintained by Section 5 of Condition 207, and any other records in the NUMMI's possession which may indicate the nature or quantity of emissions from the facility. (basis: Regulation 1-441)

VI. Permit Conditions

- d. The APCO shall have access to any portion of the plant to conduct source tests or inspections. (basis: Regulation 1-440)
- e. Nothing in these conditions shall be construed to allow the violation of any law or of any rule or regulation of the Bay Area Air Quality Management District, the State of California or the United States Environmental Protection Agency. (basis: Regulation 1-103)

9. SEVERABILITY

The provisions of these conditions are intended to be severable, and, if any individual condition or provision hereof is held to be invalid by order of the Hearing Board of the Bay Area Air Quality Management District, by order of any court competent jurisdiction, or for any other reason, the remainder of these conditions shall not be affected. (basis: Regulation 1-109)

10. CORRECTIVE PLAN

The corrective plan is a means for NUMMI to correct occasional exceedances, to stay within the yearly limits and thus to remain in compliance with District Regulations. If any of the annual or monthly material usage limits are exceeded, NUMMI shall implement abatement measures to prevent the recurrence of the type of incident which caused the excess. This plan is intended to provide a mechanism for bringing NUMMI back into compliance should a temporary exceedance occur. This plan does not constitute an alternative means of compliance. (basis: Cumulative Increase)

- a. If an exceedance of either usage or emission limits specified in Sections 1 and 2 of Condition 207, from the applicable sources covered by Condition 207 becomes apparent, NUMMI shall notify the District and will include a Corrective Plan with the next monthly report for the month after the exceedance is reported. (basis: Cumulative Increase)
- b. The corrective Plan will include a method to make up the exceedance within the three-months following the exceedance. For these purposes the exceedance will be calculated on a plant-wide basis, and an excess in one parameter can be balanced by an equivalent reduction in another. (basis: Cumulative Increase)
- c. The plan to reduce emissions pursuant to part 10.b will indicate the time periods during which each step will be taken. (basis: Cumulative Increase)
- d. If a second or subsequent monthly exceedance occurs in any 12 month consecutive period for the same usage or emission limit, after the month following the first exceedance, the annual limit will be reduced for only the following year by one-half the

VI. Permit Conditions

amount of the second or subsequent exceedance. (basis: Cumulative Increase)

- e. If, during any consecutive 12-month period, the annual emission limit is exceeded, the annual limit for only the following year will be reduced by an amount of one-half the exceedance. (basis: Cumulative Increase)
- f. Correcting an exceedance may be accomplished by the following methods:
 - 1. reducing the production rate,
 - 2. altering the paint composition,
 - 3. improvement of transfer efficiencies,
 - 4. installation of abatement devices,
 - 5. any other method approved by the APCO.(basis: Cumulative Increase)

Condition # 4159

For S900, LIME SLURRY TANK

- 1. New United Motor Manufacturing Inc. shall maintain the Lime Dust Collector Baghouse (A900) in good working condition. The baghouse shall operate five minutes before, during, and five minutes after dry lime is added to the Lime Slurry Tanks (S900). (basis: Cumulative Increase)
- 2. The pressure drop across the baghouse (A900) shall be a minimum of 1 inch of water and a maximum of 5 inches of water. (basis: Regulation 2-6-409.2)
- 3. A record of pressure drop readings for each use of the baghouse (A900) shall be maintained. In addition to pressure drop notations, the record shall contain time, date, and the name or initials of the individual taking the readings. Records shall be retained for a period of at least 5 years from the date of entry and made available to District staff upon request. (basis: Regulation 2-6-409.2)

Condition # 4281

For S3, Passenger Body Elpo Oven:

- 1. Abatement equipment must be operating during passenger vehicle production and during subsequent clean-up operations. Abatement equipment is not required to operate during periods when there are no VOC emissions. (basis: BACT)
- 2. VOC emissions from S3 Passenger Body Elpo Oven shall be abated by A4 Thermal Oxidizer. (basis: Cumulative Increase)

VI. Permit Conditions

3. The Thermal Oxidizer (A4) shall be maintained at a minimum destruction efficiency of 90% and a minimum afterburner temperature of 1200°F, except under conditions set forth in Parts 4b, 4c, and 4d of Condition 207, Allowable Temperature Excursion(s). (basis: Cumulative Increase)
4. Daily records of continuous temperature measurements for the Thermal Oxidizer (A4) shall be made and made available to District inspection for a period of 5 years from the date the record was made. The temperature chart or digital recorder is subject to the parametric monitoring and recordkeeping requirements of Regulation 1-523. (basis: BACT, Regulation 1-523)
5. NUMMI shall perform a District approved source test on A4 Thermal Oxidizer to determine destruction efficiency at least once per calendar year. (basis: Cumulative Increase)
6. NUMMI shall receive approval from the District's Source Test Manager for installation of new testing ports, platforms and source testing procedures. NUMMI shall notify the Source Test Manager at least two weeks prior to any source test. Complete reports demonstrating compliance with Part 3 of Condition 4281 shall be submitted to the District's Source Test Section within sixty (60) days of completion of the source test. This period may be extended to 90 days, if NUMMI demonstrates to the satisfaction of the APCO that additional time is required. (basis: Cumulative Increase)
7. deleted [date of Title V permit].
8. NUMMI shall conduct a source test of the Thermal Oxidizer (A4) once per calendar year. The thermal oxidizer (A4) shall be source tested to determine net mass emissions of POC as described in the following procedure:
 - a. The net mass emissions of POC shall be determined for the sources listed above with their respective coating sources combined. To determine the net mass emissions, the following shall be calculated and/or measured:
 - b. POC emissions on a pounds per unit basis [A] shall be determined by multiplying the annual coating usage with the POC content and dividing by the annual production rate.
 - c. Measured POC emissions to the Thermal Oxidizer (averaged, using the data obtained from at least 3 current source tests) shall be determined using District approved source testing methods [B].
 - d. Measured POC emissions from the Thermal Oxidizer (averaged, using the data obtained from at least 3 current source tests) shall be determined using District

VI. Permit Conditions

- approved source testing methods [C].
- e. [B] and [C] shall each be divided by the production rate measured during the source test yielding a pounds per unit basis. [B] and [C] shall be each multiplied by the annual units per hour and divided by the source test measured units per hour rate.
 - f. The net mass emissions shall be calculated by subtracting the measured POC emissions from the inlet from the calculated POC emissions and adding the measured POC emissions from the outlet [A-B+C].
 - g. The determined value [A-B+C] shall be multiplied by the actual; annual production rate.
 - h. Annual emissions shall not exceed the limit specified in Part 1(d) of Condition 207.
 - i. Within 60 days of the source test, a report shall be provided to the District. This 60-day period may be extended to 90 days, if NUMMI can demonstrate to the satisfaction of the APCO that the additional time is required. If the source test indicates any violation of the permit conditions (total mass emission greater than emission limits for coating line (booth(s) and oven(s) combined), NUMMI shall report such violation to the Director of Enforcement within 10 days of determining that a violation has occurred. basis: Cumulative Increase, Manual of Procedures, Volume II, Part 3, Section 4.7)
9. All source test records for the Thermal Oxidizer (A4) shall be maintained and made available for District inspection for a period of 5 years from the date the record was made. (basis: Cumulative Increase)

Condition # 7343

For S1809, STAMPING BODY & ASSEMBLY:

1. The coating usage rate for this source shall not exceed the following limits:

Coating	gal/yr	gal/mo
Sealant	17,875	1,859
Adhesive	8,500	884
Various	117,166	12,185

One or more of these usages may increase above the specified limits if there is a corresponding usage decrease for one or more of the coatings, based on controlled emissions, so that the allowable emissions limit for this source is not exceeded.

VI. Permit Conditions

(basis: Cumulative Increase)

- Records for each of the coatings shall be kept on a quarterly basis. These records shall be used to determine whether the monthly usage limit is exceeded based on a three-month average. For coatings that are common to more than one production line, the aggregate monthly reported usages for the lines shall be verified by comparison with the usage records of that material. The records shall be kept and made available for District inspection for a period of five years from the date of entry.
(basis: Cumulative Increase)
- The VOC emissions from this source shall not exceed 74.66 tons per year. (basis: Cumulative Increase)

Condition # 7364

For S1021, UNDERBODY, ENGINE & EXTERIOR WAX BOOTH:

- The VOC content of each coating shall not exceed the following:

Coating	lbs VOC/gal
Underbody Wax	0.73
Engine Wax	0.54
Exterior Wax	1.50
Hinge Wax	6.92

(basis: BACT, Cumulative Increase)

- The coating usage rate for this booth shall not exceed any of the following:

Coating	gal/yr	gal/mo
Underbody Wax	31,772	3,304
Engine Wax	1,954	203
Exterior Wax	24,635	2,562
Hinge Wax	2,566	267

One or more of these limits may increase above the specified limits if there is a corresponding decrease for other coatings, based on controlled emissions, so that total emissions for this source do not exceed the limit specified in Part 5 of Condition # 7364. (basis: Cumulative Increase)

- Monthly usage records for each of the coatings shall be kept. The records shall be kept and made available for District inspection for a period of five years from the date of entry. (basis: Cumulative Increase)
- Wax shall be applied using a “squirt gun” or brush. No air-atomized spray gun

VI. Permit Conditions

shall be used. (basis: BACT)

5. The VOC emissions from this source shall not exceed either of the following:

2.46 tons/month
23.69 tons/year

(basis: Cumulative Increase)

Condition # 7799

For S806, GASOLINE DISPENSING FACILITY:

- *1. Pursuant to BAAQMD Toxics Section Policy, this facility's gasoline throughput shall not exceed 1.1 million gallons in any consecutive 12-month period. (basis: Cumulative Increase)

Condition # 9156

For S1001, TRUCK ED BATH

S1002, TRUCK ED OVEN

S1003, TRUCK ED DRY SAND BOOTH

S1004, TRUCK METAL REPAIR BOOTH

S1005, TRUCK PVC UNDERCOAT AREA

S1006, TRUCK ANTI CHIP BOOTH

S1007, TRUCK SEALER OVEN

S1008, TRUCK PRIME BOOTH

S1009, TRUCK PRIME OVEN

S1010, TRUCK OFF-LINE REPAIR

S1011, TRUCK DRY SAND BOOTH

S1012, TRUCK TOUCH UP BOOTH

S1014, TRUCK TOPCOAT BOOTH I

S1015, TRUCK TOPCOAT OVEN

S1017, TRUCK TOUCH UP BOOTH

S1018, TRUCK BLACKOUT BOOTH

S1019, TRUCK CAVITY WAX BOOTH

S1020, OFF-LINE ASSEMBLY PAINT HOSPITAL (TRUCK)

S1021, TRUCK UNDERBODY, ENGINE & EXTERIOR WAX BOOTH

S1053, TRUCK WAX DRY OFF BOOTH (ELECTRIC)

S1056 TRUCK ASH, BOILER #1

S1057 TRUCK ASH, BOILER #2:

Conditions Common to All Sources for the Truck Vehicle Line (Excluding Storage Tanks, Cold Cleaners, Air Supply Houses, Door Air Heaters, Boilers, and Standby Generators):

VI. Permit Conditions

1. The permitted emission levels for the truck line were fully offset in Application 3611. (basis: Regulation 2-2-302)
2. NUMMI shall not substitute any materials for those specified in the Health Risk Assessment (HRA), without prior notification and approval of the District, if such substitution would result in:
 - a) an increase in the quantity of permitted air toxic compounds emitted,
 - b) the addition of air toxic compounds which were not listed in the HRA, or
 - c) an increase in the permitted VOC content or air toxic compound content for each coating category contained in the HRA.(basis: Toxics)
4. Monthly compliance reports showing coating and clean-up usage and calculated emissions shall be submitted to the District. (basis: Cumulative Increase)
5. The VOC emissions from non-combustion operations for the truck vehicle line shall not exceed 779.17 tons per year. (basis: Cumulative Increase)
- *6. Total emissions of the following compounds from non-combustion operations on the second vehicle line shall not exceed the following:

Carcinogen	lbs/year
Benzene	157.0
1,4 Dioxane	141.0
Formaldehyde	3342
Methylene Chloride	684.8
Perchloroethylene	1341.9
Vinyl chloride	2.8

NUMMI shall demonstrate annual compliance with these limits. (basis: Toxics)
7. In accordance with Section 2-2-412, Source Obligation, Relaxation of Enforceable Conditions: If any requirement of Regulation 2-2 would be triggered by an existing source solely because of a relaxation of any limitation on the emission of a pollutant, the requirements of Regulation 2-2 shall apply to the source in the same way as to a new or modified source or stationary source otherwise subject to this Rule. (basis: Regulation 2-2-412)
8. The combined total natural gas usage for all truck line combustion sources shall not exceed 8.6 million therms per year. Monthly records of natural gas usage shall be maintained for 5 years from date of entry and shall be made available to District personnel upon request. (basis: Cumulative Increase)
9. For determining compliance with emissions and/or usage limits, a year is any consecutive twelve month period; a month is a calendar month. (basis: Cumulative Increase)

VI. Permit Conditions

Condition # 9158

For S1002, TRUCK ED OVEN
S1007, TRUCK SEALER OVEN,
S1009, TRUCK PRIME OVEN, AND
S1015, TRUCK TOPCOAT OVEN:

1. VOC emissions from the oven and cooling tunnel shall be abated by thermal oxidation (A10022, A1007, A1009, A1015).
 - a. The net mass emissions of POC shall be determined for the sources listed above with their respective coating sources combined. To determine the net mass emissions, the following shall be calculated and/or measured:
 - b. POC emissions on a pounds per unit basis [A] shall be determined by multiplying the annual coating usage with the POC content and dividing by the annual production rate.
 - c. Measured POC emissions to each Thermal Oxidizer (averaged, using the data obtained from the 3 most recent source tests) shall be determined using District approved source testing methods [B].
 - d. Measured POC emissions from each oven Thermal Oxidizer (averaged, using the data obtained from the 3 most recent source tests) shall be determined using District approved source testing methods[C].
 - e. [B] and [C] shall each be divided by the production rate measured during the source test to yield a pounds per unit basis. [B] and [C] shall be each multiplied by the annualized units per hour and divided by the source test measured units per hour rate.
 - f. The net mass emissions shall be calculated by subtracting the measured POC emissions from the inlet from the calculated POC emissions and adding the measured POC emissions from the outlet [A-B+C].
 - g. The determined value [A-B+C] shall be multiplied by the actual annual reduction rate.
 - h. Within 60 days of the source test, a report shall be provided to the District. This 60-day period may be extended to 90 days, if NUMMI can demonstrate to the satisfaction of the APCO that the additional time is required. If the source test indicates any violation of the permit conditions (total mass emission greater than emission limits for coating line (booth(s) and oven(s) combined), NUMMI shall

VI. Permit Conditions

report such violation to the Director of Enforcement within 10 days of determining that a violation has occurred .(basis: BACT; Manual of Procedures, Volume II, Part 3, Section 4.7)

2. The thermal oxidizers (A10022, A1007, A1009, A1015) shall achieve the following:
 - a. The minimum oxidizer operating temperature shall be 1400 degree F, regardless of inlet concentration.
 - b. At oxidizer inlet, VOC concentrations greater 1200 ppm as C1, the minimum oxidizer destruction efficiency shall be 98% by weight or total non-methane organic hydrocarbon emissions from the outlet of the thermal oxidizer shall be 10 ppm or less by volume.
 - c. At oxidizer inlet VOC concentrations from 500 ppm to 1200 ppm as C1, the minimum oxidizer destruction efficiency shall vary linearly with VOC concentration from 95 to 98% by weight or total non-methane organic hydrocarbon emissions from the outlet of the thermal oxidizer shall be 10 ppm or less by volume. (basis: BACT)
3. The thermal oxidizer firebox shall be equipped with APCO approved continuous temperature measuring and recording instrument. The temperature measuring and recording instrument shall be installed, calibrated and maintained according to the manufacturer's specifications. The temperature chart or digital recorder is subject to the parametric monitoring and recordkeeping requirements of Regulation 1-523.
4. The thermal oxidizers (A10022, A1007, A1009, A1015) shall be source tested once per calendar year to verify compliance with Parts 1 and 2 of Condition 9158 and maintained according to manufacturer's specifications. Records of the source test results shall be kept for a period of five years following the date of entry. (basis: Cumulative Increase)
 - a. Each of the Truck Line Oven thermal oxidizers (A10022, A1007, A1009, A1015) shall be source tested for NOx and CO emissions once per calendar year, after notification to the APCO. If the total carbon monoxide (CO) emissions from all the thermal oxidizers of the Truck Line exceed the PSD Modeling threshold dictated in Regulation 2-2-305 (dated June 7, 1994), NUMMI shall submit a PSD Modeling Protocol to the APCO for review before implementation of the PSD Air Quality Analysis, as specified in Regulation 2-2-414 (dated June 7, 1995). The PSD Modeling Protocol shall be submitted to the District within 90 days of the source test report date. To calculate CO emissions, NUMMI shall use the most recent source test derived emission factors for thermal oxidizer burner warm-up and normal operations. NUMMI shall use an 1,200 hours per year for the thermal oxidizer burner warm-up and 5,400 hours per year for normal burner operations to estimate combustion emissions, unless NUMMI can demonstrate a more accurate method. (basis: Cumulative Increase)

VI. Permit Conditions

5. All records required in Parts 3 and 4 of Condition 9158 shall be kept and made available for District Inspection for a period of five years following the date of entry. (basis: Cumulative Increase)
6. Only natural gas, propane, LPG, or butane shall be used as a fuel for these sources. (basis: Cumulative Increase)
7. Except during periods of thermal oxidizer start-up and burner warm-up operations (when oxidizer temperature is at or below 1200 degrees F), emissions of oxides of nitrogen, measured as NO₂, from this source shall not exceed 0.1 lb NO_x per million BTU. (basis: Cumulative Increase)
8. The VOC emissions from these sources shall not exceed any of the:

Source		tons/month	tons/year
S1002	Truck ED Oven	0.33	3.21
S1007	Truck Sealer Oven	1.31	12.56
S1009	Truck Prime Oven	0.53	5.09
S1015	Topcoat Oven	0.69	6.59

(basis: Cumulative Increase)

9. The minimum temperature and abatement efficiency requirements for Thermal Oxidizers located at NUMMI shall not apply during an "Allowable Temperature Excursion" below the minimum temperature requirement, provided that the controller set temperature is at or above the minimum temperature requirement. An Allowable Temperature Excursion is one of the following:
 - a. A temperature excursion no more than 20 degrees F below the requirement; or
 - b. A temperature excursion period(s) aggregating 15 minutes or less in any hour; or
 - c. A temperature excursion longer than 15 minutes but shorter than 3 hours in duration, provided that all of the following are satisfied:
 - i. There are no more than 2 excursions per facility (Plant No. A1438) per calendar day;
 - ii. There are no more than 2 excursions per abatement device per month; and
 - iii. There are no more than 5 excursions per facility (Plant No. A1438) per month. (basis: Cumulative Increase)
10. NUMMI shall keep records to demonstrate that all qualifying criteria for Allowable Temperature Excursions are met, including the following:
 - a. Starting date and time and the duration of each Allowable Temperature Excursion;

VI. Permit Conditions

- b. Minimum temperature during each Allowable Temperature Excursion;
- c. Number of Allowable Temperature Excursions (>15 minutes) per abatement device per month;
- d. Total number of Allowable Temperature Excursions (>15 minutes) for the entire facility per month.

A summary of these records shall be included in NUMMI's monthly report to the APCO. To satisfy the NSPS requirement of 40 CFR 60, Subpart MM, a negative declaration is also required in NUMMI's monthly report if there are no temperature excursions. (basis: Cumulative Increase)

11. The District may revise or revoke Parts 9 and 10 of Condition 9158 if source operations change significantly such that the basis for granting this condition is no longer valid. (basis: Cumulative Increase)
12. Abatement equipment must be operating during periods of truck line production and during clean-up operations following production. Abatement equipment is not required to operate during periods when there are no VOC emissions. (basis: BACT)

Condition # 9159

For S1005, TRUCK UNDERCOAT AREA

1. The VOC content of each coating shall not exceed the following:

Coating	lbs VOC/gal
PVC Undercoat	0.6

(basis: BACT, Cumulative Increase)
2. The coating usage rate for this booth shall not exceed either of the following limits:

Coating	gal/yr	gal/mo
PVC Undercoat	291,757	30,343

unless NUMMI can demonstrate that the emissions do not exceed the limit specified in Part 5 of Condition # 9159. (basis: Cumulative Increase)
3. Monthly usage records for each of the coatings shall be kept. The records shall be kept and made available for District inspection for a period of five years from the date of entry. (basis: Cumulative Increase)
4. Only High-Volume-Low Pressure (HVLP), electrostatic, and/or APCO approved paint equipment with equivalent or higher transfer efficiency shall be used to apply coatings. Air-atomized spray equipment may be used to apply Repair, Blackout, and Soft-Chip coatings. (basis: BACT)
5. The VOC emissions from this source shall not exceed either of the following:

VI. Permit Conditions

2.73 tons/month
26.3 tons/year
(basis: BACT, Cumulative Increase)

6. deleted [date of Title V permit].
7. deleted [date of Title V permit].
8. Particulate emissions from this source shall be abated by 99%. (basis: BACT)
9. To minimize the amount of clean-up solvent used in the Undercoat Booth, NUMMI shall cover all robots, where practical. (basis: BACT)

Condition # 9161

For S1006, TRUCK ANTI CHIP BOOTH:

1. The VOC content of each coating shall not exceed the following:

Coating	lbs VOC/gal
Anti-Chip I	4.06
Anti-Chip II	1.42
Repair Primer	4.63

(basis: BACT, Cumulative Increase)

2. The coating usage rate for this booth shall not exceed any of the following:

Coating	gal/yr	gal/mon
Anti-Chip I	11,628	1,209
Anti-Chip II	29,413	3,059
Repair Primer	233	24

One or more of these usages may increase above the specified limits provided there is a corresponding usage decrease for one or more of the coatings, based on controlled emissions, so that total emissions for this source do not exceed the emissions limit specified in Part 5 of Condition # 9161. (basis: Cumulative Increase)

3. Monthly usage records for each of the coatings shall be kept. Monthly records shall be totaled for each consecutive 12-month period. The records shall be kept and made available for District inspection for a period of five years from the date of entry. (basis: BACT)
4. Only High-Volume-Low Pressure (HVLP), electrostatic, and/or APCO approved

VI. Permit Conditions

application equipment with equivalent or higher transfer efficiency shall be used to apply coatings. Air-atomized spray equipment may be used to apply Repair, Blackout, and Soft-Chip coatings. (basis: BACT)

5. The VOC emissions from this source shall not exceed either of the following:

3.20 tons/month

30.76 tons/year

(basis: Cumulative Increase)

VI. Permit Conditions

Condition # 9163

For S1008, TRUCK PRIME BOOTH:

1. The VOC content of each coating shall not exceed the following:

Coating	lbs VOC/gal
Primer	4.08
Int. Color	4.46
Others-Repair	4.63
Soft-Chip	7.09

(basis: BACT, Cumulative Increase)

2. The coating usage rate for this booth shall not exceed any of the following limits:

Coating	gal/yr	gal/mo
Primer	62,129	6,461
Int. Color	26,973	2,805
Others-Repair	233	24
Soft-Chip	9,908	1,030

One or more of these usages may increase above the specified limits if there is a corresponding usage decrease for one or more of the coatings, based on controlled emissions, so that total emissions for this source do not exceed the limit specified in Part 5 of Condition # 9163. (basis: Cumulative Increase)

3. Monthly usage records for each of the coatings shall be kept. Monthly records shall be totaled for each consecutive 12-month period. The records shall be kept and made available for District inspection for a period of five years from the date of entry. (basis: Cumulative Increase)

4. Only High-Volume-Low Pressure (HVLP), electrostatic, and/or APCO approved application equipment with equivalent or higher transfer efficiency shall be used to apply coatings. Air-atomized spray equipment may be used to apply Repair, Blackout, and Soft-Chip coatings. (basis: BACT)

5. The VOC emissions from this source shall not exceed either of the following:

11.01	tons/month
105.9	tons/year

(basis: Cumulative Increase)

- *6. Only natural gas, propane, LPG, or butane shall be used as a fuel for this source.

(basis: Regulation 2-1-103)

7. Except during periods of thermal oxidizer start-up and burner warm-up operations

VI. Permit Conditions

(when oxidizer temperatures is at or below 1200 degrees F), emissions of oxides of nitrogen, measured as NO₂, from this source shall not exceed 0.1 lb NO_x per million BTU. (basis: Cumulative Increase)

8. Particulate emissions from this source shall be abated by 98%. (basis: BACT)
9. All VOC emissions from the soft-chip, automatic, flash off and setting zones in the booth shall be controlled by the activated carbon system (A10082) and the thermal oxidizer (A1008) required for the booth (S1008). This includes VOC emissions from clean-up and wet-down operations occurring during the normal hours of operation. (basis: BACT)
10. The thermal oxidizer shall achieve the following level of control:
 - a. The minimum oxidizer operating temperature shall be 1400 degrees F, regardless of inlet concentration.
 - b. When oxidizer inlet VOC concentrations are greater than 1200 ppm as C₁, the minimum allowable oxidizer destruction efficiency shall be 98.5% by weight or total non-methane organic hydrocarbon emissions from the outlet of the thermal oxidizer shall be 10 ppm or less by volume.
 - c. When oxidizer inlet VOC concentrations from 500 ppm to 1200 ppm as C₁, the minimum allowable oxidizer destruction efficiency shall vary linearly with VOC concentration from 95 to 98.5% by weight or total non-methane organic hydrocarbon emissions from the outlet of the thermal oxidizer shall be 10 ppm or less by volume.
(basis: BACT)
11. The thermal oxidizer (A1008) firebox shall be equipped with APCO approved continuous temperature measuring and recording instrument. The temperature measuring and recording instrument shall be installed, calibrated and maintained according to the manufacturer's specifications. The temperature chart or digital recorder is subject to the parametric monitoring and recordkeeping requirements of Regulation 1-523. (basis: BACT, Regulation 1-523)
12. The VOC reduction efficiency of the activated carbon system (A10082) shall be at least 90% by weight. (basis: BACT)
13. The activated carbon system (A10082) and the thermal oxidizer (A1008) shall be source tested once per calendar year to verify compliance with Parts 10 and 12 of Condition 9163. Each of the Truck Line thermal oxidizers shall be source tested for NO_x and CO emissions once per calendar year, after notification to the APCO. If the total carbon monoxide (CO) emissions from all the thermal oxidizers of the Truck

VI. Permit Conditions

Line exceed the PSD Modeling threshold in Regulation 2-2-305 (dated June 7, 1994), NUMMI shall submit a PSD Modeling Protocol to the APCO for review before implementation of the PSD Air Quality Analysis, as specified in Regulation 2-2-414 (dated June 7, 1995). The PSD Modeling Protocol shall be submitted to the APCO within 90 days of the source test report date. To calculate CO emissions, NUMMI shall use the most recent source test derived emission factors for thermal oxidizer burner warm-up and normal operations. NUMMI shall use 1,200 hours per year for the thermal oxidizer burner warm-up and 5,400 hours per year for normal burner operations to estimate combustion emissions, unless NUMMI can demonstrate a more accurate method. (basis: BACT)

14. The activated carbon system (A10082) and the thermal oxidizer (A1008) shall be maintained according to the manufacturer's specifications. (basis: Cumulative Increase)
15. All records required in Parts 11 and 13 of Condition 9161 shall be kept and made available for District Inspection for a period of five years following the date of entry. (basis: Cumulative Increase)
16. To minimize the amount of clean-up solvent used in the booth, NUMMI shall:
 - a. Provide a paper, plastic lining, or protective removable coating for the walls and fixtures of the booth, except over doors and windows.
 - b. Cover all robots, where practical.
 - c. Replace the paper/plastic lining, or protective removable coating on an as needed basis. (basis: BACT)
17. The minimum temperature and abatement efficiency requirements for Thermal Oxidizers located at NUMMI shall not apply during an "Allowable Temperature Excursion" below the minimum temperature requirement, provided that the controller set temperature is at or above the minimum temperature requirement. An Allowable Temperature Excursion is one of the following:
 - a. A temperature excursion not exceeding 20 degrees F below the requirement; or
 - b. A temperature excursion period(s) aggregating 15 minutes or less in any hour; or
 - c. A temperature excursion greater than 15 minutes but less than 3 hours in duration, provided that all of the following are satisfied:
 - i. There are no more than 2 excursions per facility (Plant No. A1438) per calendar day;
 - ii. There are no more than 2 excursions per abatement device per month; and
 - iii. There are no more than 5 excursions per facility (Plant No. A1438) per month.

VI. Permit Conditions

(basis: Cumulative Increase)

18. NUMMI shall keep records to demonstrate that all qualifying criteria for Allowable Temperature Excursions are met including but not limited to the following:
- Starting date and time and the duration of each Allowable Temperature Excursion;
 - Minimum temperature during each Allowable Temperature Excursion;
 - Number of Allowable Temperature Excursions (>15 minutes) per abatement device per month;
 - Total number of Allowable Temperature Excursions (> 15 minutes) for the entire facility per month.

A summary of these records shall be included in NUMMI's monthly report to the APCO. To satisfy the NSPS requirement of 40 CFR 60, Subpart MM, a negative declaration is also required in NUMMI's monthly report if there are no temperature excursions. (basis: Cumulative Increase)

19. The District may revise or revoke Parts 17 and 18 of Condition 9161 if source operations change significantly such that the basis for granting this condition is no longer valid. (basis: Cumulative Increase)
20. Abatement equipment must be operated during periods of truck line production and during cleanup operations following production. Abatement equipment is not required to operate during periods when there are no VOC emissions. (basis: BACT)

Condition # 9164

For S1014, TRUCK TOPCOAT BOOTH I:

- All VOC emissions from the automatic, flash off and setting zones of the booth shall be controlled by the activated carbon system (A10144) and the thermal oxidizer (A10142) required for the Truck Topcoat Booth (S1014). This includes VOC emissions from clean-up and wet-down operations occurring during the normal hours of operation. (basis: BACT)
- The thermal oxidizer shall achieve the following level of control:
 - The minimum thermal oxidizer operating temperature shall be 1400 degrees F, regardless of inlet concentration.
 - At thermal oxidizer inlet VOC concentrations greater 1200 ppm as C1, the minimum allowable oxidizer destruction efficiency shall be 98% by weight or total non-methane organic hydrocarbon emissions from the outlet of the thermal oxidizer shall be 10 ppm or less by volume.
 - At thermal oxidizer inlet VOC concentrations from 500 ppm to 1200 ppm as C1,

VI. Permit Conditions

the minimum allowable oxidizer destruction efficiency shall vary linearly with VOC concentration from 95 to 98% by weight or total non-methane organic hydrocarbon emissions from the outlet of the thermal oxidizer shall be 10 ppm or less by volume. (basis: BACT)

3. The thermal oxidizer firebox shall be equipped with APCO approved continuous temperature measuring and recording instrument. The temperature measuring and recording instrument shall be installed, calibrated and maintained according to the manufacturer's specifications.
 - a. The temperature chart or digital recorder is subject to the parametric monitoring and recordkeeping requirements of Regulation 1-523. (basis: BACT, Regulation 1-523)
4. The VOC reduction efficiency of the rotary drum carbon beds shall be at least 90% by weight. (basis: BACT, Cumulative Increase)
5. The activated carbon system (A10144) and the thermal oxidizer (A10142) shall be source tested once per calendar year to verify compliance with Parts 1, 2 and 4 of Condition 9164. Records of the source test results and maintenance schedule shall be kept for a period of five years following the date of entry.
 - a. Each of the Truck Line thermal oxidizers shall be source tested for NO_x and CO emissions once per calendar year, after notification to the APCO. If the total carbon monoxide (CO) emissions from all the thermal oxidizers of the Truck Line exceed the PSD Modeling threshold dictated in Regulation 2-2-305 (dated June 7, 1994), NUMMI shall submit a PSD Modeling Protocol to the APCO for review before implementation of the PSD Air Quality Analysis, as specified in Regulation 2-2-414 (dated June 7, 1995). The PSD Modeling Protocol shall be submitted to the APCO within 90 days of the source test report date. To calculate CO emissions, NUMMI shall use the most recent source test derived emission factors for thermal oxidizer burner warm-up and normal operations. NUMMI shall use an 1,200 hours per year for the thermal oxidizer burner warm-up and 5,400 hours per year for normal burner operations to estimate combustion emissions, unless NUMMI can demonstrate a more accurate representation. (basis: BACT)
6. The activated carbon system (A10144) and the thermal oxidizer (A10142) shall be maintained in accordance with manufacturer's specifications. (basis: Cumulative Increase)
7. All records required in Parts 3 and 5 of Condition 9164 shall be kept and made available for District Inspection for a period of five years following the date of entry. (basis: BACT)

VI. Permit Conditions

8. Only natural gas, propane or butane shall be used as a fuel for this source. (basis: Cumulative Increase)
9. Except during periods of thermal oxidizer start-up and burner warm-up operations (when oxidizer temperature is at or below 1200 degrees F), emissions of oxides of nitrogen, measured as NO₂, from this source shall not exceed 0.1 lb NO_x per million BTU. (basis: Cumulative Increase)
10. To minimize the amount of clean-up solvent used in the booth, NUMMI shall:
 - a. Provide a paper, plastic lining, or a protective removable coating for the walls and fixtures of the booth, except over doors and windows.
 - b. Cover all robots, where practical.
 - c. replace the paper/plastic lining, or protective removable coating on an as needed basis. (basis: BACT)
11. To minimize the amount of purge solvent used in S1014 Topcoat Booths I, NUMMI shall coat at least 2 vehicles between purge cycles for the two most popular colors. (basis: BACT)
12. The minimum temperature and abatement efficiency requirements for Thermal Oxidizers located at NUMMI shall not apply during an "Allowable Temperature Excursion" below the minimum temperature requirement, provided that the controller set temperature is at or above the minimum temperature requirement. An Allowable Temperature Excursion is one of the following:
 - a. A temperature excursion not exceeding 20 degrees F below the requirement; or
 - b. A temperature excursion period(s) aggregating 15 minutes or less in any hour; or
 - c. A temperature excursion greater than 15 minutes but less than 3 hours in duration, provided that all of the following are satisfied:
 - i. There are no more than 2 excursions per facility (Plant No. A1438) per calendar day;
 - ii. There are no more than 2 excursions per abatement device per ~~calendar~~ month; and
 - iii. There are no more than 5 excursions per facility (Plant No. A1438) per month. (basis: Cumulative Increase)
13. NUMMI shall keep records to demonstrate that all qualifying criteria for Allowable Temperature Excursions are met including but not limited to the following:
 - a. Starting date and time, and the duration of each Allowable Temperature Excursion;
 - b. Minimum temperature during each Allowable Temperature Excursion;
 - c. Number of Allowable Temperature Excursions (>15 minutes) per abatement device per month;
 - d. Total number of Allowable Temperature Excursions (>15 minutes) for the entire facility per month. A summary of these records shall be included in NUMMI's

VI. Permit Conditions

monthly report to the APCO. To satisfy the NSPS requirement of 40 CFR 60, Subpart MM, a negative declaration is also required in NUMMI's monthly report if there are no temperature excursions.

(basis: Cumulative Increase)

14. Abatement equipment must be operating during periods of truck line production and during clean-up operations following production. Abatement equipment is not required to operate during periods when there are no VOC emissions. (basis: BACT)

15. The VOC content of each coating shall not exceed the following:

Coating	lbs VOC/gal
Solids	3.54
Base Coat	4.79
Clear Coat	4.12
Other-Repair	4.63

(basis: Cumulative Increase)

16. The coating usage rate for this booth shall not exceed any of the following limits:

Coating	gal/yr	gal/mon
Solids	26,927	2,800
Base Coat	53,211	5,534
Clear Coat	70,094	7,290
Others-Repair	349	36

One or more of these coating usages may increase above the specified usage limit provided there is a corresponding decrease for one or more of the coatings, based on controlled emissions so that total emissions for this source are not exceeded. (basis: Cumulative Increase)

17. Monthly usage records for each of the coatings shall be kept. The records shall be kept and made available for District inspection for a period of five years from the date of entry. (basis: Cumulative Increase)

18. Only High-Volume-Low Pressure (HVLV), electrostatic, and/or APCO approved application equipment with equivalent or higher transfer efficiency shall be used to apply coatings. Air-atomized spray equipment may be used to apply Repair, Blackout, and Soft-Chip coatings. (basis: Cumulative Increase)

19. The VOC emissions from this source shall not exceed either of the following:

13.60	tons/month
130.76	tons/year

(basis: Cumulative Increase)

VI. Permit Conditions

20. Particulate emissions from this source shall be abated by 98%. (basis: BACT)

Condition # 9166

For S1012, TOUCH UP BOOTH:

1. The owner/operator of S1012 Touch Up Booth shall not exceed 417 gallons per year of touch up coating during any consecutive twelve-month period:
(basis: Cumulative Increase)
2. The owner/operator may use coatings specified in Condition 9166 in excess of that limit specified in Part 1 of Permit Condition 9166, provided that the owner/operator can demonstrate that all of the following are satisfied:
 - a. Total POC emissions from S-1012 do not exceed 2002 pounds in any consecutive twelve month period;
 - b. The use of these materials does not increase toxic emissions above any risk screening trigger level.
(basis: Cumulative Increase)
3. To determine compliance with the above conditions, the owner/operator shall maintain the following records and provide all of the data necessary to evaluate compliance with the above conditions, including the following information:
 - a. Quantities of each type of coating used at this source on a monthly basis.
 - b. If a material other than those specified in Part 1 of Permit Condition 9166 is used, POC and toxic component contents of each material used; and mass emission calculations to demonstrate compliance with Condition 2, on a monthly basis;
 - c. Monthly usage and/or emission calculations shall be totaled for each consecutive twelve-month period.

All records shall be retained on-site for five years, from the date of entry, and made available for inspection by District staff upon request. These recordkeeping requirements shall not replace the recordkeeping requirements contained in any applicable District Regulations. (basis: Cumulative Increase)

Condition # 9167

For S1053, TRUCK WAX DRY OFF BOOTH (ELECTRIC):

1. The VOC emissions from this source shall not exceed either of the following emission limits:

Source	tons/mo	tons/year
--------	---------	-----------

VI. Permit Conditions

S1053 Truck Wax Dry Off Booth 1.64 15.79
(basis: Cumulative Increase)

Condition # 9170

For S1018, BLACKOUT BOOTH:

1. The VOC content of the coating shall not exceed the following limit:

Coating	lbs VOC/gal	
Blackout	2.95	

(basis: BACT, Cumulative Increase)
2. The coating usage rate for this booth shall not exceed either of the following:

Coating	gal/yr	gal/mo
Blackout	12,317	1,281

(basis: Cumulative Increase)
3. Monthly usage records for each of the coatings shall be kept. Monthly records shall be totaled for each consecutive 12-month period. The records shall be kept and made available for District inspection for a period of five years from the date of entry.
(basis: Cumulative Increase)
4. The VOC emissions from this source shall not exceed either of the following:

1.89	tons/month
18.17	tons/year

(basis: Cumulative Increase)

Condition # 9171

For S1019, TRUCK CAVITY WAX BOOTH:

1. The VOC content of each coating shall not exceed the following:

Coating	lbs VOC/gal	
Cavity Wax	0.73	

(basis: BACT, Cumulative Increase)
2. The coating usage rate for this booth shall not exceed either of the following:

Coating	gal/yr	gal/mon
Cavity Wax	15,406	1,602

(basis: Cumulative Increase)
3. Monthly usage records for each of the coatings shall be kept. Monthly records shall be totaled for each consecutive 12-month period. The records shall be kept and made

VI. Permit Conditions

available for District inspection for a period of five years from the date of entry.
 (basis: Cumulative Increase)

4. Only High-Volume-Low Pressure (HVLV), electrostatic, and/or APCO approved application equipment with equivalent or higher transfer efficiency shall be used to apply coatings. (basis: BACT)
5. The VOC emissions from this source shall not exceed either of the following:

0.58	tons/month
5.62	tons/yr

 (basis: Cumulative Increase)

Condition # 9172

For S1020, OFF-LINE ASSEMBLY PAINT HOSPITAL (TRUCK):

1. The VOC content of each coating shall not exceed the following:

Coating	lbs VOC/gal
Solids	3.54
Base Color	4.79
Clear Coat	4.12
Lacquer	6.61

(basis: BACT, Cumulative Increase)

2. The coating usage rate for this booth shall not exceed any of the following:

Coating	gal/yr	gal/mon
Solids	629	65
Base Color	893	93
Clear Coat	1,734	180
Lacquer	279	29

One or more of these usages may increase above specified limits if there is a corresponding usage decrease for one or more of the coatings, based on controlled emissions, so that total emissions for this source are not exceeded. (basis: Cumulative Increase)

3. Monthly usage records for each of the coatings shall be kept. Monthly records shall be totaled for each consecutive 12-month period. The records shall be kept and made available for District inspection for a period of five years from the date of entry.
 (basis: Cumulative Increase)
4. Only cup guns and brushes shall be used in this area. [basis: Cumulative Increase]

VI. Permit Conditions

5. The VOC emissions from this source shall not exceed either of the following:
- | | |
|------|------------|
| 0.81 | tons/month |
| 7.75 | tons/year |
- (basis: Cumulative Increase)

Condition # 9174

For S1056, TRUCK ASH BOILER # 1, AND
S1057, TRUCK ASH BOILER # 2:

1. Only natural gas, propane, LPG, or butane shall be used as a fuel at this source for this source. (basis: Cumulative Increase)
2. Emissions of oxides of nitrogen shall not exceed 30 ppm at 3 percent oxygen, dry basis, averaged over any one-hour period. (basis: BACT, Cumulative Increase)
3. This boiler shall be operated and maintained according to the manufacturer's specifications. (basis: Cumulative Increase)
4. All source test records and preventative maintenance records shall be kept and made available for District Inspection for a period of five years following the date of entry. (basis: Cumulative Increase)
5. To demonstrate compliance with Part 2, S1056 and S1057 shall be source tested once per calendar year for NO_x and CO, unless a different schedule is approved. A minimum of two weeks notification shall be given to the District's Source Test Manager, prior to NUMMI initiating any source test for these boilers. Source testing shall be performed to determine the NO_x and CO emissions of the sources, in accordance with the District's Manual of Procedures. Stack sampling ports and platform(s) shall be provided for these sources exhaust stacks. Records of the source test results shall be kept. All records shall be kept and made available for District inspection for a period of five years following the date of entry (basis: Regulation 2-6-409.2)

Condition # 9175

For S1803, TRUCK SEALER DECK (FUGITIVE)

1. The VOC content of the coating shall not exceed the following limit:

Coating	lbs VOC/gal
Bead Sealer	0.25

(basis: BACT, Cumulative Increase)

VI. Permit Conditions

2. The coating usage rate shall not exceed any of the following:

Coating	gal/yr	gal/mon
Bead Sealer	110,236	11,465

unless NUMMI can demonstrate that emissions from the source does not exceed the limit specified in Part 5 of Condition # 9175. (basis: BACT, Cumulative Increase)
3. Monthly usage records for each of the coatings shall be kept. Monthly records shall be totaled for each consecutive 12-month period. The records shall be kept and made available for District inspection for a period of five years from the date of entry. (basis: Cumulative Increase)
4. Only High-Volume-Low Pressure (HVLP), electrostatic, and/or APCO approved application equipment with equivalent or higher transfer efficiency shall be used to apply coatings. Air-atomized spray equipment may be used to apply Repair, Blackout, and Soft-Chip coatings. (basis: BACT)
5. The VOC emissions from this source shall not exceed either of the following:

0.29 tons/month
2.76 tons/year

(basis: Cumulative Increase)

Condition # 9257

For S1001, TRUCK ED BATH:

1. The VOC content of the coating shall not exceed any of the following limit:

Coating	lbs VOC/gal
ELPO Primer	0.59

(basis: BACT, Cumulative Increase)
2. The coating usage rate for this booth shall not exceed any of the following limits:

Coating	gal/yr	gal/mon
ELPO Primer	107,371	11,167

Unless NUMMI can demonstrate that emissions are below the limit specified in Part 5 of Condition # 9257. (basis: Cumulative Increase)
3. Monthly usage records for each of the coatings shall be kept. Monthly records shall be totaled for each consecutive 12-month period. The records shall be kept and made available for District inspection for a period of five years from the date of entry. (basis: Cumulative Increase)
4. Deleted.
5. The VOC emissions from this source shall not exceed either of the following:

0.99 tons/month	9.5 tons/year
-----------------	---------------

(basis: Cumulative Increase)

VI. Permit Conditions

Condition # 9877

For S1810, Cleaning Materials:

- The solvent usage rate shall not exceed the following:

Operation	gals/yr	gal/mo
Wipe & Clean-up	17,616	1,832
Cleaning Solvent	164,050	17,061

One or more of these usages may increase above the specified limit if there is a corresponding usage decrease for one or more of the solvents, based on controlled emissions so that total allowable emissions for this source are not exceeded. (basis: Cumulative Increase)

- Usage records for each of the solvent operations shall be kept on a monthly basis. (basis: Cumulative Increase)
- The VOC emissions from this source shall not exceed either of the following:

28.3	tons/month
272	tons/year

(basis: Cumulative Increase)
- NUMMI shall recover at least 65% of all cleaning solvent. Records of the amounts of solvent recovered shall be kept on a monthly basis. Monthly excursions below the percent recovery limit are allowed as long as the annual VOC emission limit for clean up solvent is not exceeded. (basis: BACT)

Condition # 10011

For S1010, TRUCK OFF-LINE REPAIR, AND
S1017, TRUCK TOUCH UP BOOTH:

- The VOC content of each coating shall not exceed the following:

Coating	lbs VOC/gal
Repair Primer	4.63
Solids (repair)	3.54
Base Coat (repair)	4.79
Clear Coat (repair)	4.12
Solids (lacq. repair)	6.32
Base Coat (lacq. repair)	6.41
Clear Coat (lacq. repair)	6.30
Adhesion Promoter	6.61
Anti-Chip I	4.06
Anti-Chip II	1.42

(basis: BACT, Cumulative Increase)

VI. Permit Conditions

2. The coating usage rate for this booth shall not exceed any of the following:

Coating	gal/yr	gal/mo
Repair Primer	837	87
Solids (repair)	606	63
Base Coat (repair)	857	89
Clear Coat (repair)	1,665	173
Solids (lacq. repair)	691	72
Base Coat (lacq. repair)	963	100
Clear Coat (lacq. repair)	1,576	164
Adhesion Promoter	1,238	128
Anti-Chip I	38	4
Anti-Chip II	10	1

One or more of these usages may increase above the specified limit if there is a corresponding usage decrease for one or more of the coatings, based on controlled emissions, so that total emissions for this source are not exceeded. (basis: Cumulative Increase)

3. Monthly usage records for each of the coatings shall be kept. Monthly records shall be totaled for each consecutive 12-month period. The records shall be kept and made available for District inspection for a period of five years from the date of entry. (basis: Cumulative Increase)
4. Only cup guns and brushes shall be used in this area. [basis: Cumulative Increase]
5. The VOC emissions from the sources shall not exceed either of the following:
2.38 tons/month
22.91 tons/year
(basis: Cumulative Increase)

VI. Permit Conditions

Condition # 10320

For S57, BUMPER TOPCOAT BOOTH,
S58, BUMPER TOPCOAT OVEN,
S59, BUMPER PRIME BOOTH,
S65, BUMPER PRIME OVEN,
S960, PLASTIC PLANT BOOTH AND GENERAL CLEANING
S961, BUMPER RELEASE CLEANING & POLISH

S964, COLD CLEANER
S965, PLASTIC PLANT THINNER STORAGE TANK
S992, PLASTIC PLANT THINNER STORAGE TANK
S1070, INSTRUMENT PANEL BOOTH,
S1071 INSTRUMENT PANEL OVEN, AND
S1072, GENERAL CLEANING & PAINT CLEANING
S1509, PROTECTOSEAL CLEANING TANK:

1. All conditions shall be in effect at all times during equipment operation, including period of equipment start-up. For the purposes of determining compliance with emissions and/or usage limits, a year is defined as a twelve month consecutive period; a month is defined as a calendar month. (basis: Cumulative Increase)
2. The combined total natural gas usage for all bumper and Instrument Panel line combustion sources shall not exceed 3.16 Million (MM) Therms per year. Records of natural gas usage shall be maintained for five (5) years from the date of entry and shall be made available to District personnel upon request. (basis: Cumulative Increase)
3. Only natural gas, propane, butane, and LPG shall be used as a fuel for any heater boxes used for sources S58, S65, and S1071. (basis: Cumulative Increase)
4. The total NO_x emissions from the combustion equipment for the sources listed for Condition 10320 shall not exceed 26.16 tons per year. (basis: Cumulative Increase)
5. The total CO emissions from the combustion equipment for the sources listed for Condition 10320 shall not exceed 46.48 tons per year. (basis: Cumulative Increase)
- *6. NUMMI shall not substitute any materials for those described in this permit application's Health Risk Assessment (HRA), which would trigger a toxics review, and which would result in:
 - a) an increase in the quantity of permitted air toxic compounds emitted,
 - b) The addition of unpermitted air toxic compounds emitted, which were not listed in the permit application HRA, or
 - c) an increase in the permitted VOC content or air toxic compound content for each coating category as specified in the permit application Health Risk Assessment

VI. Permit Conditions

without prior notification and approval of the APCO. (basis: Toxics)

7. In order to demonstrate compliance with Parts 4 and 5 of Condition 10320, NUMMI shall calculate the NOx and CO mass emission rates quarterly, using natural gas usage records and District approved NOx and CO emission factors. The NOx and CO emission factors for the thermal oxidizer (A571) for S57, S58, S59, S65, S1070 and S1071 shall be obtained from the results of the source tests, required by the District in Part 23 of Condition 10320. (basis: Cumulative Increase)
8. Abatement equipment (A571) must be operated during periods of instrument panel and/or bumper line production (sources S57, S58, S59, S65, S1070 and S1071) and during cleanup operations following production. Abatement equipment is not required to operate during periods when there are no VOC emissions. For S1070, if waterborne coating is used exclusively, abatement by A571 is not required. (basis: BACT)
9. In no event shall the total combined, annual coating emissions from sources S57, S58, S59, and S-65 combined exceed 173 tons per year of POC. (basis: Cumulative Increase)
10. The total coating usage for sources S57, S58, S59, and S65 shall not exceed the following specified limits unless NUMMI can demonstrate to the satisfaction of the APCO that a change in coating limits and/or composition will not result in emissions exceeding those in Part 9 of Condition 10320:

Primer	61,606 gallons per year
Non-Metallic	
High Solids	32,586 gallons per year
Base Coat	37,127 gallons per year
Clear Coat	48,350 gallons per year

One or more of the usages may increase above the specified limit if there is a corresponding usage decrease for one or more of the other coatings, so that total emissions do not exceed the emission limit, specified in Part 9 of Condition 10320. NUMMI shall provide documentation to demonstrate compliance with Part 9 of Condition 10320 within 10 days of the exceedance of any of the coating limits. The total controlled emission limit for these spray booths (S57 and S59) and the associated ovens (S58 and S65) must be maintained at all times. (basis: Cumulative Increase; MOP Volume II, Part 3, Section 4.7)

11. Adhesion promoting material may be used at sources S57, S58, S59, and S65 provided the total emissions for the sources do not exceed the limitations specified in Part 9 of Condition 10320. (basis: Cumulative Increase)
12. Only High-Volume-Low-Pressure (HVLP), electrostatic, and/or APCO approved

VI. Permit Conditions

application equipment with equivalent or higher transfer efficiency shall be used to apply coatings in sources S57, S59, and S1070. (basis: BACT)

13. To minimize the amount of clean-up solvent used in the booths, NUMMI shall:
 - a. Provide a paper or plastic lining, or protective removable coating for the walls and fixtures of the booth, except over doors and windows.
 - b. Cover all robots, where practical.
 - c. Replace the paper/plastic lining, or protective removable coating on an as needed basis. (basis: BACT)

14. NUMMI shall maintain the following data:
 - a) deleted 12/13/2004.
 - b) Amount and type of coating applied.
 - c) Amount of clean-up solvent used.
 - d) Amount of coating and solvents purchased.
 - e) Monthly compliance reports showing coating and clean-up usage and calculated emissions shall be submitted to the District Director of Enforcement.
 - f) Records shall be available for District inspection for a period of at least 5 years following the date of entry. (basis: Cumulative Increase)

15. Primary method for removal of particulate matter from S57 and S59 shall be a water contact scrubbing system. The overall control efficiency of the system shall be 98%. Any downtime of the water contact scrubber system shall be recorded. Such records shall be made available for inspection upon request and kept for a minimum of 5 years from the date of record.(basis: BACT, Cumulative Increase)

16. All VOC emissions from the automatic, flash off and setting zones of the Bumper Booths (S57 and S59) and the manual zone of Bumper Booth #2 (S59) shall be abated by the thermal oxidizer (A 571). This includes VOC emissions from clean-up and wet-down operations occurring during normal operating hours. (basis: BACT, Cumulative Increase)

17. The VOC emissions from sources S57, S58, S59, S65, S1070 and S1071 shall be abated by the thermal oxidizer (A571). This shall not apply to S-1070 during periods when waterborne coating is used exclusively. (basis: BACT, Cumulative Increase)
 - a. The net mass emissions of POC shall be determined for the sources listed in Condition 10320 with their respective coating sources combined. To determine the net mass emissions, the following shall be calculated and/or measured:

 - b. POC emissions on a pounds per unit basis [A] shall be determined by multiplying the annual coating usage with the POC content and dividing by the annual production rate.

VI. Permit Conditions

- c. Measured POC emissions to each booth and oven Thermal Oxidizer (averaged, using the data obtained from at least 3 current source tests) shall be determined using District approved source testing methods [B].
 - d. Measured POC emissions from each booth and oven Thermal Oxidizer and carbon concentrator (averaged, using the data obtained from at least 3 current source tests) shall be determined using District approved source testing methods [C].
 - e. [B] and [C] shall each be divided by the production rate measured during the source test yielding a pounds per unit basis. [B] and [C] shall each be multiplied by the annual units per hour and divided by the source test measured units per hour rate.
 - f. The net mass emissions shall be calculated by subtracting the measured POC emissions from the inlet from the calculated POC emissions and adding the measured POC emissions from the outlet [A-B+C].
 - g. The determined value [A-B+C] shall be multiplied by the actual; annual production rate.
 - h. Within 60 days of the source test, a report shall be provided to the District. This 60-day period may be extended to 90 days, if NUMMI can demonstrate to the satisfaction of the APCO that the additional time is required. If the source test indicates any violation of the permit conditions (total mass emission greater than emission limits for coating line (booth(s) and oven(s) combined), NUMMI shall report such violation to the Director of Enforcement within 10 days of determining that a violation has occurred .(basis: BACT; Manual of Procedures, Volume II, Part 3, Section 4.7)
(basis: BACT, Cumulative Increase)
19. The operating temperature for the Thermal Oxidizer (A571) may fall below 1400 degrees F if the source complies with the temperature excursion parameters set forth in Parts 26 and 27 of this condition. (basis: BACT, Cumulative Increase)
 20. The minimum destruction efficiency of the Thermal Oxidizer (A571) shall be 98.5% by weight, whenever the VOC inlet concentration is greater than or equal to 500 ppmv, measured as methane. Below a concentration of 500 ppmv, the minimum destruction efficiency shall be 95% by weight or total non-methane organic carbon emissions from the outlet of the thermal oxidizer shall be 10 ppm by volume or less. (basis: BACT, Cumulative Increase)
 21. The NO_x emissions from the burners of the thermal oxidizer (A571) shall not exceed 1.72 tons per month. (basis: Cumulative Increase)

VI. Permit Conditions

22. The combustion chamber for the thermal oxidizer (A571) shall be equipped with District approved continuous temperature measuring and recording instrument. The temperature measuring and recording instrument shall be installed, calibrated and maintained according to the manufacturer's specifications.
 - a. The temperature chart or digital recorder is subject to the parametric monitoring and recordkeeping requirements of Regulation 1-523. (basis: BACT, Regulation 1-523)
23. The thermal oxidizer (A571) shall be source tested once per calendar year. After prior notification to the District's Source Test Manager, source testing shall be performed to determine the VOC control efficiency of the abatement devices and the nitrogen oxide and carbon monoxide emissions, in accordance with the District's Manual of Procedures. Records of the source test results shall be kept and made available for District inspection for a period of five years following the date the report was completed. (basis: BACT, Cumulative Increase)
24. Within 60 days of the completion of any source testing, a report documenting the results shall be provided to the District. This 60-day period may be extended to 90 days, if NUMMI can demonstrate to the satisfaction of the APCO that the additional time is required. If source testing indicates any violation of the permit conditions, NUMMI shall report such violation to the Director of Enforcement within 10 days of determining that a violation has occurred and also within the final report. (basis: Cumulative Increase; MOP Volume II, Part 3, Section 4.7)
26. The minimum temperature and abatement efficiency requirements for Thermal Oxidizers located at NUMMI shall not apply during an "Allowable Temperature Excursion" below the minimum temperature requirement, provided that the controller set temperature is at or above the minimum temperature requirement. An Allowable Temperature Excursion is one of the following:
 - a. A temperature excursion not exceeding 20 degrees F below the requirement; or
 - b. A temperature excursion period(s) aggregating less than or equal to 15 minutes in any hour; or
 - c. A temperature excursion greater than 15 minutes but less than 3 hours in duration, provided that all of the following are satisfied:
 - i. There are no more than 2 excursions per facility (Plant No. A1438) per day;
 - ii. There are no more than 2 excursions per abatement device per month; and
 - iii. There are no more than 5 excursions per facility (Plant No. A1438) per month. (basis: Cumulative Increase)
27. NUMMI shall keep records to demonstrate that all qualifying criteria for Allowable

VI. Permit Conditions

Temperature Excursions are met including but not limited to the following:

- a. Starting date and time, and the duration of each Allowable Temperature Excursion;
- b. Minimum temperature during each Allowable Temperature Excursion;
- c. Number of Allowable Temperature Excursions (> 15 minutes) per abatement device per month;
- d. Total number of Allowable Temperature Excursions (> 15 minutes) for the entire facility per month.

A summary of these records shall be included in NUMMI's monthly report to the District. To satisfy the NSPS requirement of 40 CFR 60, Subpart MM, a negative declaration is also required in NUMMI's monthly report if there are no temperature excursions. (basis: Cumulative Increase)

28. The District may revise or revoke Parts 26 and 27 of Condition 10320 if source operations change significantly such that the basis for granting this condition is no longer valid. (basis: Cumulative Increase)
31. In no event shall the total annual emissions from the combination of S960, S961, S964, S1072 and S1509 exceed 134.51 tons per year of POC. (basis: Cumulative Increase)
32. Clean-up solvent usage for sources S960, S961, S964, S1072, and S1509 shall be collected and recovered at 77% or greater. Monthly excursions below the percent recovery limit are allowed as long as the annual VOC emission limit for clean up is not exceeded. (basis: BACT)
33. Paint and solvent from sources S960, S961, S964, S1072, and S1509 shall be recovered in an enclosed collection system and shipped to either a solvent recycler or proper disposal facility. (basis: BACT)
34. For the following sources, S960, S961, S1072, S964, and S1509, NUMMI shall record the amount of clean-up solvent used monthly. To verify compliance, monthly reports showing clean-up usage and calculated emissions shall be submitted to the Director of Enforcement. Records shall be available for District inspection for a period of at least 5 years following the date on which such data or reports are recorded or made. (basis: Cumulative Increase)
41. In no event shall the total combined, annual coating emissions from sources S1070 and S1071 exceed 21.49 tons per year of POC. (basis: Cumulative Increase)

VI. Permit Conditions

42. The total coating usage at sources S1070 and S1071 shall not exceed the following specified limits unless NUMMI can demonstrate to the satisfaction of the APCO that a change in coating limits and/or composition will not result in emissions exceeding those in Part 41 of Condition 10320:

Top Coat (Solventborne)	36,865 gal/year
Top Coat (Waterborne)	16,189 gal/year (less water)

(basis: Cumulative Increase)

43. The natural gas heater boxes for the IP Oven (S1071) shall utilize low-NO_x burners.
(basis: BACT)

44. The owner/operator shall abate S1070 with a water contact scrubbing system with an overall control efficiency of 90%. Any downtime of the water contact scrubber system shall be recorded. Such records shall be made available for inspection upon request and kept for a minimum of 5 years from the date of record. (basis: Cumulative Increase)

47. The permit holder shall operate the zeolite concentrator (A592) to abate the organic emissions from source S59 Bumper Prime Booth with a minimum destruction efficiency of 90%. To verify compliance with this requirement, the permit holder shall conduct a District approved source test once per calendar year, unless a different schedule is approved. After prior notification to and approval from the District's Source Test Manager, source testing shall be performed to determine the VOC control efficiency of the abatement devices, in accordance with the District's Manual of Procedures. Records of the source test results shall be kept. All records shall be kept and made available for District inspection for a period of five years following the date of entry.
(basis: BACT).

Condition # 10481

For S1061, TRUCK AXLE BOOTH S1062, TRUCK AXLE OVEN, AND
S1063, GENERAL TRUCK AXLE BOOTH AND AREA CLEANING, AND
S1510, COLD CLEANER:

Conditions Common to All Sources of the Axle Line:

1. All conditions shall be in effect at all times during equipment operation, including period of equipment start-up. For the purposes of determining compliance with emissions and/or usage limit, a year is any twelve-month consecutive period; a month is defined as a calendar month. (basis: Cumulative Increase)
2. The combined total natural gas usage for all Axle Line combustion sources shall not exceed 1.2 Million (MM) Therms per year. Monthly records of natural gas usage shall be maintained for five years from the date of entry and shall be maintained

VI. Permit Conditions

available for District personnel upon request. (basis: BACT)

3. Only natural gas, propane, butane, and LPG shall be used as a fuel for the heater boxes of these sources. (basis: Cumulative Increase)
4. The total NOx emissions from the combustion equipment of the Axle Line shall not exceed 6.06 tons per year. (basis: Cumulative Increase)
5. The total CO emissions from the combustion equipment of the Axle Line shall not exceed 2.52 tons per year. (basis: Cumulative Increase)
- *6. NUMMI shall not substitute any materials for those described in this permit application's Health Risk Assessment (HRA), which would trigger a toxics review, and which would result in:
 - a) an increase in the quantity of permitted air toxic compounds emitted,
 - b) the addition of unpermitted air toxic compounds emitted, which were not listed in the permit application HRA, or
 - c) an increase in the permitted VOC content or air toxic compound content for each coating category as specified in the permit application Health Risk Assessment.

without prior notification and approval of the APCO. (basis: Toxics)

7. In order to demonstrate compliance with Parts 4 and 5 of Condition 10481, NUMMI shall calculate the NOx and CO mass emission rates quarterly, using natural gas usage records and District approved NOx and CO emission factors. The NOx and CO emission factors for the Axle Booth (S1061) and Axle Oven (S1062) shall be obtained from the results of the source tests. The owner/operator of S1061 and S1062 shall perform a District approved source test one per Title V permit term for NOx and CO emissions to verify the emissions of Part 4 and 5 of Condition 10481 (basis: Cumulative Increase)
8. Abatement equipment must be operated during periods of axle production and during cleanup operations following production. Abatement equipment is not required to operate during periods when there are no VOC emissions. (basis: BACT)
9. In no event shall the total annual emissions from the combination of S1063 and S1510 exceed 22.32 tons per year of POC. (basis: Cumulative Increase)
10. NUMMI shall maintain records of the following data for S1063 (General Truck Axle Booth and Area Cleaning) and S1510 (Cold Cleaner):
 - a. Amount of clean-up solvent used.
 - b. To verify compliance, monthly reports showing clean-up usage and calculated

VI. Permit Conditions

emissions shall be submitted to the Director of Enforcement.
(basis: Cumulative Increase)

11. Records required for Condition No. 10481 shall be made available for District inspection for a period of 5 years from the date such data was recorded or reports made. (basis: Cumulative Increase)

Condition # 10484

For S1061, TRUCK AXLE COATING BOOTH, AND
S1062, TRUCK AXLE OVEN:

1. In no event shall the total annual coating emissions from Axle Booth (S1061) and Axle Oven (S1062) combined exceed 12.22 tons per year of POC. (basis: Cumulative Increase)
2. The total coating usage for the sources listed in Condition 10484 shall not exceed the following specified limit unless NUMMI can demonstrate to the satisfaction of the APCO that a change in coating usage and/or composition will not result in emissions exceeding those in Part 1 of Condition 10484:

Off-Line Coating 11,108 gallons per year
(basis: Cumulative Increase)
3. Only High-Volume-Low-Pressure (HVLV), electrostatic, and/or APCO approved application equipment with equivalent or higher transfer efficiency shall be used to apply coatings. (basis: BACT)
4. NUMMI shall not apply off-line coating in S-1061 and S-1062 having a VOC content in excess of 2.2 lbs/gal. [basis: BACT]
5. NUMMI shall use no solvent for purge cleaning of the paint lines. (basis: BACT)
6. The VOC emissions per axle shall not exceed 0.087 lb per axle coated. (basis: BACT)
7. NUMMI shall maintain the following data:
 - a) Deleted 12/13/2004.
 - b) Amount and type of coating applied.
 - c) Amount of clean-up solvent used.
 - d) Deleted 12/13/2004.
 - e) To verify compliance, monthly compliance reports showing coating and clean-up usage and total calculated emissions and averaged-monthly emissions per axle shall be submitted to the District Director of Enforcement. The format and content of the compliance reports must be submitted to the

VI. Permit Conditions

APCO for prior approval.

All records required for Condition 10484 shall be available for District inspection for a period of at least 5 years following the date of entry. (basis: Cumulative Increase)

8. The owner/operator shall abate S1061 with a water contact scrubbing system with an overall control efficiency of 90%. Any downtime of the water contact scrubber system shall be recorded. Such records shall be made available for inspection upon request and kept for a minimum of 5 years from the date of record.(basis: BACT)

Condition # 10578

For S1050, TRUCK FUEL TANK COATING BOOTH, AND
S1051, TRUCK FUEL TANK – HEATER BOX:

1. In no event shall the total annual coating emissions from Truck Fuel Tank Booth (S1050) and Truck Fuel Tank Oven (S1051) combined exceed 11.68 tons per year of POC. (basis: Cumulative Increase)
2. The total coating usage for the sources specified in Condition 10578 shall not exceed the following specified usages limits unless NUMMI can demonstrate to the satisfaction of the APCO that a change in coating limits and/or composition will not result in emissions exceeding those in Part 1 of Condition 10578:

Tank Body	24,598 gallons per year
Fastener	9,048 gallons per year

One or more of these coating limits may increase above the specified limits if there is a corresponding usage decrease for one or more of the coatings, based on controlled emissions, so that total emissions, as specified in Part 1 of Condition 10578, for this source are not exceeded. (basis: Cumulative Increase)

3. Only High-Volume-Low-Pressure (HVLP), electrostatic, and/or APCO approved application equipment with equivalent transfer efficiency (at least 55% Transfer Efficiency for Tank Body coating) shall be used to apply coatings. (basis: BACT)
4. NUMMI shall maintain the following data:
 - a) Deleted 12/13/2004.
 - b) Amount and type of coating applied.
 - c) Amount of clean-up solvent used.
 - d) Monthly compliance reports showing coating and clean-up usage and calculated emissions shall be submitted to the District Director of Enforcement.

VI. Permit Conditions

- Records shall be available for District inspection for a period of at least 5 years following the date of entry. (basis: Cumulative Increase)
5. Any particulate matter exhausted from the booth (S1050) shall be vented to the Thermal Oxidizer (A809). (basis: Cumulative Increase)
 6. The POC emissions from the Truck Fuel Tank Oven (S1051) shall be abated by a Thermal Oxidizer (A809). The Thermal Oxidizer (A809) shall be source tested as required in Part 10 of Condition # 10578 to determine net mass emissions, using the following procedure:
 - a. The net mass emissions of POC shall be determined for the booth (S1050) and oven (S1051) combined. To determine the net mass emissions, the following shall be calculated and/or measured:
 - b. POC emissions shall be determined by coating usage and POC content [A].
 - c. Measured POC emissions to A809 Thermal Oxidizer (averaged, using the data obtained from at least 3 current source tests) shall be determined using District approved source testing methods [B].
 - d. Measured POC emissions from A809 Thermal Oxidizer (averaged, using the data obtained from at least 3 current source tests) shall be determined using District approved source testing methods [C].
 - e. The net mass emissions shall be calculated by subtracting the measured POC emissions from the inlet from the calculated POC emissions and adding the measured POC emissions from the outlet [A-B+C].
 - f. The determined value [A-B+C] shall be prorated for production and annualized for the hours of operation. (basis: Cumulative Increase)
 - g. Within 60 days of the source test, a report shall be provided to the District. This 60-day period may be extended to 90 days, if NUMMI can demonstrate to the satisfaction of the APCO that the additional time is required. If the source test indicates any violation of the permit conditions (total mass emission greater than emission limits for coating line (booth(s) and oven(s) combined), NUMMI shall report such violation to the Director of Enforcement within 10 days of determining that a violation has occurred. (basis: BACT; Manual of Procedures, Volume II, Part 3, Section 4.7)
 7. The minimum operating temperature for the Thermal Oxidizer (A809) shall be 1400 degrees F. The Thermal Oxidizer (A809) may operate below 1400 degrees F if the source complies with the temperature excursion parameters set forth in Parts 13 and 14 of this condition. (basis: BACT)
 8. The minimum destruction efficiency of the Thermal Oxidizer (A809) shall be 98.5% by weight, whenever the VOC inlet concentration is greater than or equal to 500 ppmv, measured as methane. Below a concentration of 500 ppmv, the minimum destruction efficiency shall be 95% by weight or total non-methane organic carbon emissions from the outlet of the Thermal Oxidizer (A809) shall be 10 ppmv or less.

VI. Permit Conditions

(basis: BACT, Cumulative Increase)

9. The combustion chamber of the Thermal Oxidizer (A809) shall be equipped with District approved continuous temperature measuring and recording instrument. The temperature measuring and recording instrument shall be installed, calibrated and maintained according to the manufacture's specifications. (basis: Cumulative Increase)
10. The Thermal Oxidizer (A809) shall be source tested once per calendar year, unless a different schedule is approved. After prior notification to and approval from the District's Source Test Manager, source testing shall be performed to determine the VOC control efficiency of the abatement devices, in accordance with the District's Manual of Procedures. Stack sampling ports and platform(s) shall be provided at the booth exhaust stacks, the oven exhaust stacks, the inlet and outlet of the Thermal Oxidizer (A809). Records of the source test results shall be kept. All records shall be kept and made available for District inspection for a period of five years following the date the report was completed. (basis: BACT)
11. Within 60 days of the source testing, a report shall be provided to the District. If the source testing indicates any violation of the permit conditions, NUMMI shall report such violation to the Director of Enforcement within within 10 days of determining that a violation has occurred and also within the report. (basis: BACT; MOP Volume II, Part 3, Section 4.7)
12. Low-NOx burners shall be used in the Truck Line Gas Tank Oven (S1051). (basis: BACT)
13. The minimum temperature and abatement efficiency requirements for Thermal Oxidizers located at NUMMI shall not apply during an "Allowable Temperature Excursion" below the minimum temperature requirement, provided that the controller set temperature is at or above the minimum temperature requirement. An Allowable Temperature Excursion is one of the following:
 - a. A temperature excursion not exceeding 20 degrees F below the requirement; or
 - b. A temperature excursion period(s) aggregating 15 minutes or less in any hour; or
 - c. A temperature excursion greater than 15 minutes but less than 3 hours in duration, provided that all of the following are satisfied:
 - i. There are no more than 2 excursions per facility (Plant No. A1438) per calendar day;
 - ii. There are no more than 2 excursions per abatement device per month; and
 - iii. There are no more than 5 excursions per facility (Plant No. A1438) per month. (basis: Cumulative Increase)
14. NUMMI shall keep records to demonstrate that all qualifying criteria for Allowable Temperature Excursions are met including but not limited to the following:

VI. Permit Conditions

- a. Starting date and time, and the duration of each Allowable Temperature Excursion;
- b. Minimum temperature during each Allowable Temperature Excursion;
- c. Number of Allowable Temperature Excursions (> 15 minutes) per abatement device per month;
- d. Total number of Allowable Temperature Excursions (> 15 minutes) for the entire facility per month.

A summary of these records shall be included in NUMMI's monthly report to the District. To satisfy the NSPS requirement of 40 CFR 60, Subpart MM, a negative declaration is also required in NUMMI's monthly report if there are no temperature excursions. (basis: Cumulative Increase)

15. The District may revise or revoke parts 13 and 14 of Condition 10578 if source operations change significantly such that the basis for granting this condition is no longer valid. (basis: Cumulative Increase)
16. All conditions shall be in effect at all times during equipment operation, including period of equipment start-up. For the purposes of determining compliance with emissions and/or usage limits, a year is defined as a twelve month consecutive month period ; a month is defined as a calendar month. (basis: Cumulative Increase)
17. NUMMI shall not substitute any materials for those described in this permit application's Health Risk Assessment (HRA), which would trigger a toxics review, and which would result in:
 - a) an increase in the quantity of permitted air toxic compounds emitted,
 - b) the addition of unpermitted air toxic compounds emitted, which were not listed in the permit application HRA, or
 - c) an increase in the permitted VOC content or air toxic compound content for each coating category as specified in the permit application Health Risk Assessment without prior notification and approval of the District. (basis: Toxics)
18. The combined total natural gas usage for S1050 and S1051 shall not exceed 0.13 million therms per year. Monthly records of natural gas usage shall be maintained for five years and shall be made available to District personnel upon request. (basis: Cumulative Increase)
19. Abatement equipment must be operating during periods of fuel tank production and during cleanup operations following production. Abatement equipment is not required to operate during periods periods when there are no VOC emissions. (basis: BACT)

Condition # 10709

For S406, WINDSHIELD WASHER FLUID ABOVE GROUND STORAGE TANK:

VI. Permit Conditions

1. The total liquid throughput for Storage Tank S406 shall not exceed 530,170 gallons during any consecutive twelve (12) month period. (basis: Cumulative Increase)
2. Only windshield washer fluid shall be stored in tank S406. (basis: Cumulative Increase)
3. The following records shall be kept on site and made available for District inspection for a period of 5 years from the date of entry:
 - a. The type and amount of all materials stored in the tank and the dates and amounts when materials are added or removed. (basis: Cumulative Increase)

Condition # 13984

For S1511, TRUCK ELPO RESIN STORAGE TANK:

1. The liquid throughput for Storage Tank S1511 shall not exceed 283,000 gallons during any consecutive 12-month period. (basis: Cumulative Increase)
2. Only ELPO Resin materials with a vapor pressure less than 0.5 psia shall be stored in tank S1511. (basis: Cumulative Increase)
1. The following records shall be kept on site and made available for District inspection for a period of 5 years of entry:
 - a. The type and throughput of materials stored in tank S1511 summarized on a monthly basis. (basis: Cumulative Increase)

Condition # 13985

For S1512, TRUCK ELPO PIGMENT STORAGE TANK

1. The total liquid throughput for Storage Tank S1512 shall not exceed 27,900 gallons during any consecutive 12-month period. (basis: Cumulative Increase)
2. Only ELPO Pigment materials with a vapor pressure less than 0.5 psia shall be stored in tank S1512. (basis: Cumulative Increase)
3. The following records shall be kept on site and made available for District inspection for a period of 5 years of entry:
 - a. The type and throughput of materials stored in tank, S1512, summarized on a monthly basis. basis: Cumulative Increase)

VI. Permit Conditions

Condition # 14205

For S3007, NPS Dry Off Oven
S3008, NPS PRIME BOOTH
S3009, NPS PRIME OVEN,
S3014, NPS TOP COAT BOOTH #1
S3015, NPS TOPCOAT OVEN #1,
S3016, NPS TOPCOAT BOOTH #2,
S3017, NPS TOPCOAT OVEN #2,

Conditions Common to All Sources of the Passenger Paint Shop:

1. All conditions shall be in effect at all times during equipment operation, including period of equipment start-up, unless otherwise indicated.

For the purposes of determining compliance with emissions and/or usage limits, a year is defined as any twelve month consecutive period; a month is defined as a calendar month. (basis: Cumulative Increase)

2. The minimum temperature and abatement efficiency requirements for Thermal Oxidizers located at NUMMI shall not apply during an "Allowable Temperature Excursion" below the minimum temperature requirement, provided that the controller set temperature is at or above the minimum temperature requirement. An Allowable Temperature Excursion is one of the following:
 - a. A temperature excursion not exceeding 20 degrees F below the requirement; or
 - b. A temperature excursion period(s) aggregating less than or equal to 15 minutes in any hour; or
 - c. A temperature excursion greater than 15 minutes but less than 3 hours in duration, provided that all of the following are satisfied:
 - i. There are no more than 2 excursions per facility (Plant No. A1438) per day;
 - ii. There are no more than 2 excursions per abatement device per month; and
 - iii. There are no more than 5 excursions per facility (Plant No. A1438) per month.(basis: Cumulative Increase)
3. NUMMI shall keep records to demonstrate that all qualifying criteria for Allowable Temperature Excursions are met including but not limited to the following:
 - a. Starting date and time, and the duration of each Allowable Temperature Excursion;
 - b. Minimum temperature during each Allowable Temperature Excursion;

VI. Permit Conditions

- c. Number of Allowable Temperature Excursions (> 15 minutes) per abatement device per month;
- d. Total number of Allowable Temperature Excursions (> 15 minutes) for the entire facility per month.

A summary of these records shall be included in NUMMI's monthly report to the District. To satisfy the NSPS requirement of 40 CFR 60, Subpart MM, a negative declaration is also required in NUMMI's monthly report if there are no temperature excursions. (basis: Cumulative Increase)

4. The District may revise or revoke parts 2 and 3 of Condition 14205 if source operations change significantly such that the basis for granting this condition is no longer valid. (basis: Cumulative Increase)
5. Total emissions of organic compounds from the North Passenger Paint Shop sources, calculated on the basis of coating and solvent usage and including any reductions due to abatement, shall not exceed 719.23 tons per year (TPY) of POC. (basis: Cumulative Increase)
6. The combined total natural gas usage for all North Passenger Paint Shop combustion sources shall not exceed 9.63 Million (MM) Therms per year. Monthly records of natural gas usage shall be maintained for five years from the date of entry and shall be maintained available for District personnel upon request. NUMMI shall only use a District-approved gas meter. (basis: Cumulative Increase)
7. Only natural gas, propane, butane, and LPG shall be used as a fuel for combustion equipment for sources S3009, S3015, and S3017. (basis: Cumulative Increase)
8. Manual touch-up or repair operations may be performed in the North Passenger Paint Shop booth and oven sources. The total usage of coating for manual touch-up or repair shall not exceed 6,906 gallons per year, or result in POC emissions exceeding 19.91 tons per year. (basis: Cumulative Increase)
9. The total NO_x emissions from the combustion equipment (including Booth Air Supply Houses, Oven Heater Boxes, Thermal Oxidizers, and Boiler) of the North Passenger Paint Shop sources shall not exceed 40.54 tons per year. (basis: Cumulative Increase)
10. The total CO emissions from the combustion equipment (including Booth Air Supply Houses, Oven Heater Boxes, Thermal Oxidizers, and Boiler) of the North Passenger Paint Shop sources shall not exceed 50.46 tons per year. (basis: Cumulative Increase)
11. NUMMI shall maintain the following data:
 - a) Usage records of each coating shall be kept on a monthly basis.
 - b) Amount of clean-up solvent used shall be kept on a monthly basis.
 - c) d. Monthly reports showing coating and clean-up usage and calculated

VI. Permit Conditions

emissions shall be submitted to the Director of Enforcement. If an exceedance is calculated, NUMMI shall submit a written report with this monthly report to the District to demonstrate that the overall North Passenger Paint Shop sources will not exceed the overall emissions limit specified in Part 5 of Condition 14205.

Records shall be available for District inspection for a period of at least five years following the date of entry. (basis: Cumulative Increase)

12. In order to demonstrate compliance with Parts 9 and 10 of Condition 14205, NUMMI shall calculate quarterly the NOx and CO mass emission rates, using natural gas usage records and District approved NOx and CO emission factors. The NOx and CO emission factors for the Thermal Oxidizers (A3008, A3014, and A3016), Booths (S3008, S3014, S3016) and Ovens (S3009, S3015, and S3017) shall be based on the results of the most recent source tests, required by the District. The owner/operator shall perform District approved source test of nitrogen oxide and carbon monoxide emissions from the combustion equipment of the axle line once per Title V permit term to verify compliance with Part 9 and 10 of Condition 14205. (basis: Cumulative Increase)
13. Abatement equipment must be operated during periods of passenger vehicle production and during cleanup operations following production. Abatement equipment is not required to operate during periods periods when there are no VOC emissions. (basis: BACT)

Condition # 14206

For S3008, PRIME BOOTH, AND
S3009, PRIME OVEN:

1. In no event shall the annual coating emissions (not including manual touch-up or repair) from these two sources (S3008 and S3009) combined exceed 130.94 tons per year or 16.36 tons per month of POC, unless NUMMI notifies the District within 30 calendar days of such an exceedance and submits a written report with the scheduled, monthly report to demonstrate that the overall North Passenger Paint Shop sources will not exceed the overall emissions limit specified in Part 5 of Condition 14205. (basis: Cumulative Increase)
2. The total coating usage limits (not including manual touch-up or repair) for these two sources (S3008 and S3009) shall not exceed the following specified limits unless NUMMI can demonstrate to the satisfaction of the APCO that a change in coating usage and/or composition will not result in emissions exceeding those in Part 1 of Condition 14206:

Coating	Gallons/Year	Gallons/Month
Primer	60,869	7,608

VI. Permit Conditions

Interior Color	32,435	4,054
Black Out	8,105	1,013
Soft-Chip	8,225	1,028

One or more of these usages may increase above the specified limit if there is a corresponding usage decrease for one or more of the other coatings, which is based on controlled emissions, so that total emissions do not exceed the limit, specified in Part 1 of Condition 14206. NUMMI shall provide documentation to demonstrate compliance with Part 1 of Condition 14206 within 30 days of the exceedance of any of the coating limits. (basis: Cumulative Increase)

3. The natural gas heater boxes for the Primer Oven (S3009) shall utilize low-NOx burners or equivalent. Low-NOx burners in heater boxes are typically estimated to emit 0.1 pound per million BTU. If source tests indicate that emissions are higher than 0.1 pound per million BTU, then NUMMI shall provide a detailed explanation and/or other documentation to verify that low-NOx burners are indeed being used correctly. (basis: Cumulative Increase)
4. Only High-Volume-Low-Pressure (HVLP), electrostatic, and/or APCO approved application equipment with equivalent or higher transfer efficiency shall be used to apply coatings. Air-atomized spray equipment may be used to apply Repair, Blackout, and Soft-Chip coatings. (basis: BACT)
5. The Thermal Oxidizer (A3008) shall remain in operation during clean-up operations for at least thirty minutes after production. (basis: BACT)
6. To minimize the amount of clean-up solvent used in the booth, NUMMI shall:
 - a. Provide a paper or plastic lining, or protective removable coating for the walls and fixtures of the booth, except over doors and windows.
 - b. Cover all robots, where practical.
 - c. Replace the paper/plastic lining, or protective removable coating on an as needed basis.(basis: BACT)
7. NUMMI shall abate particulate emissions from S3008 with a water contact scrubber system with an overall control efficiency of 98%. Any downtime of the water contact scrubber system shall be recorded. Such records shall be made available for inspection upon request and kept for a minimum of 5 years from the date of record.(basis: BACT)
8. POC emissions from the Primer Booth (S3008) autozone shall be controlled a Thermal Oxidizer (A3008), with the option of being concentrated first by an Activated Carbon Adsorber (A30082). This includes POC emissions from clean-up

VI. Permit Conditions

and wet-down operations occurring during the normal hours of operation. (basis: BACT)

9. The POC emissions from the Primer Oven (S3009) shall be abated by a Thermal Oxidizer (A3008). (basis: BACT)
10. The minimum operating temperature for the Thermal Oxidizer (A3008) shall be 1400 degrees F. The Thermal Oxidizer (A3008) may operate below 1400 degrees F if the source complies with the temperature excursion parameters set forth in Parts 2 and 3 of Condition 14205. (basis: BACT)
11. The VOC destruction efficiency of the Thermal Oxidizer (A3008) shall be maintained at a minimum of 98.5% by weight, whenever the inlet concentration of VOC to the Thermal Oxidizer (A3008) is equal to or greater than 500 ppmv, as measured as methane. Below a concentration of 500 ppmv, the precursor organic destruction efficiency shall be kept at a minimum of 95% by weight or total non-methane organic carbon emissions from the outlet of the Thermal Oxidizer (A3008) shall be 10 ppm by volume or less. (basis: BACT)
12. The combustion chamber of the Thermal Oxidizer (A3008) shall be equipped with District approved continuous temperature measuring and recording instrument (analog or digital). The temperature measuring and recording instrument shall be installed, calibrated and maintained according to the manufacture's specifications.

The temperature chart or digital recorder is subject to the parametric monitoring and recordkeeping requirements of Regulation 1-523. (basis: BACT, Regulation 1-523)
13. The Thermal Oxidizer (A3008) shall be source tested once per calendar year, unless a different schedule is approved. After prior notification to the District's Source Test Manager, source testing shall be performed to determine the VOC control efficiency of the abatement devices, in accordance with the District's Manual of Procedures. Records of the source test results shall be kept. All records shall be kept and made available for District inspection for a period of five years following the date of entry. (basis: BACT)
14. Within 60 days of the completing any source testing, a report shall be provided to the District. This 60 day period may be extended to 90 days, if NUMMI can demonstrate to the satisfaction of the APCO that the additional time is required. If the source testing indicates any violation of the permit conditions, NUMMI shall report such violation to the Director of Enforcement ~~in~~ within within 10 days of determining that a violation has occurred and also within the report. (basis: BACT; MOP Volume II, Part 3, Section 4.7)

VI. Permit Conditions

17. To demonstrate compliance with Part 3 of Condition 14206, the heater boxes of NPS Prime Oven (S3009) shall be source tested once per calendar year to determine the NO_x emission rate (lb/MMBTU). After prior notification to the District's Source Test Manager, source testing shall be performed in accordance with the District's Manual of Procedures. Results of the source test shall be submitted to the District for review and approval within 60 days of the source test. Records of the source test results shall be kept and made available for District inspection for a period of five years following the date of entry. (basis: Regulation 2-6-409.2)
18. The permit holder shall operate the carbon concentrator (A30082) to abate the organic emissions from source S3008 NPS Booth will a minimum destruction efficiency of 90%. To verify compliance with this requirement, the permit holder shall conduct a District approved source test once per calendar year, unless a different schedule is approved. After prior notification to and approval from the District's Source Test Manager, source testing shall be performed to determine the VOC control efficiency of the abatement devices, in accordance with the District's Manual of Procedures. Records of the source test results and shall be kept. All records shall be kept and made available for District inspection for a period of five years following the date of entry. (basis: BACT).

Condition # 14207

For S3014, NPS TOP COAT BOOTH #1,
S3015, NPS TOPCOAT OVEN #1,
S3016, NPS TOPCOAT BOOTH #2, AND
S3017, NPS TOPCOAT OVEN #2:

1. In no event shall the annual coating emissions (not including manual touch-up or repair) from the Topcoat Booths and Ovens (S3014, S3015, S3016, and S3017) combined exceed 250.5 tons per year or 31.3 tons per month of POC, unless NUMMI notifies the Director of Enforcement within 30 calendar days of such an exceedance and submits a written report with the scheduled, monthly report to demonstrate that the overall North Passenger Paint Shop sources will not exceed the overall emissions limit specified in Part 5 of Condition 14205. (basis: Cumulative Increase)
2. The total coating usage (not including manual touch-up or repair) for the sources, S3014, S3015, S3016, and S3017, shall not exceed the following specified limits unless NUMMI can demonstrate to the satisfaction of the APCO that a change in coating limits and/or composition will not result in emissions exceeding those Part 1 of Condition 14207:

Coating	Gallons/Yr	Gallons/Mon
Base Coat	123,552	15,444
Clear Coat	91,289	11,411

VI. Permit Conditions

Non-Met High-Solids 52,452 6,557

One or more of these coatings limits may increase above the specified limit if there is a corresponding usage decrease for one or more of the other coatings, such that total emissions do not exceed the limit, specified in Part 1 of Condition 14207. NUMMI shall provide documentation to demonstrate compliance with Part 1 of Condition 14207 within 30 days of the exceedance of any of the coating limits. (basis: Cumulative Increase)

3. The natural gas heater boxes for the Topcoat #1 and #2 Ovens (S3015 and S3017) shall utilize low-NOx burners or equivalent. Low- NOx burners in heater boxes are typically estimated to emit 0.1 pound per million BTU. If source tests indicate that emissions are higher than 0.1 pound per million BTU, NUMMI shall provide a detailed explanation and/or other documentation to verify that low-NOx burners are indeed being used correctly. (basis: Cumulative Increase)
4. Only High-Volume-Low-Pressure (HVLV), electrostatic, and/or APCO approved application equipment with equivalent or higher transfer efficiency shall be used to apply coatings. Air-atomized spray equipment may be used to apply Repair, and Blackout coatings. (basis: BACT)
5. The Thermal Oxidizers (A3014 and A3016) shall remain in operation during clean-up operations for at least thirty minutes after production. (basis: BACT)
6. To minimize the amount of clean-up solvent used in the booth, NUMMI shall:
 - a. Provide a paper or plastic lining, or a protective removable coating for the walls and fixtures of the booth, except over doors and windows.
 - b. Cover all robots, where practical.
 - c. Replace the paper/plastic lining, or protective removable coating on an as needed basis. (basis: BACT)
7. Primary method for removal of particulate matter from S3014 and S3016 shall be a water contact scrubbing system (A30141). The overall control efficiency of the system shall be 98%. Any downtime of the water contact scrubber system shall be recorded. Such records shall be made available for inspection upon request and kept for a minimum of 5 years from the date of record. (basis: BACT)
8. POC emissions from each Topcoat #1 and 2 Booth (S3014 and S3016) autozone shall be controlled by a Thermal Oxidizer (A3014 abating S3014 and A3016 abating S3016) with the option of being concentrated by Activated Carbon Adsorbers (A30142 and A30162). This includes POC emissions from clean-up and wet- down operations occurring during the normal hours of operation. (basis: BACT)
9. The POC emissions from the Topcoat #1 and #2 Ovens (S3015 and S3017) shall be abated by a Thermal Oxidizer (A3014 and A3016, respectively). (basis: BACT)

VI. Permit Conditions

10. The minimum operating temperature for the Thermal Oxidizers (A3014 and A3016) shall be 1400 degrees F. The Thermal Oxidizers (A3014 and A3016) may operate below 1400 degrees F if the source complies with the temperature excursion parameters set forth in Parts 2 and 3 of Condition 14205. (basis: BACT)
11. The minimum destruction efficiency of the Thermal Oxidizer (A3014 and A3016) shall be 98.5% by weight, whenever the POC inlet concentration is greater than or equal to 500 ppmv, measured as methane. Below a concentration of 500 ppmv, the minimum destruction efficiency shall be 95% by weight or total non-methane organic carbon emissions from the outlet of the Thermal Oxidizers (A3014 and A3016) shall be 10 ppmv or less. (basis: BACT)
12. The combustion chamber of the Thermal Oxidizers (A3014 and A3016) shall be equipped with District approved continuous temperature measuring and recording instrument (analog or digital). The temperature measuring and recording instrument shall be installed, calibrated and maintained in accordance with the manufacture's specifications.

The temperature chart or digital recorder is subject to the parametric monitoring and recordkeeping requirements of Regulation 1-523. (basis: BACT, 1-523)

13. The Thermal Oxidizers (A3014 and A3016) shall be source tested once per calendar year, unless a different schedule is approved. After prior notification to and approval from the District's Source Test Manager, source testing shall be performed to determine the VOC control efficiency of the abatement devices, in accordance with the District's Manual of Procedures. Records of the source test results and shall be kept. All records shall be kept and made available for District inspection for a period of five years following the date of entry. (basis: BACT)
14. Within 60 days of the above described source testing, a report shall be provided to the District. This 60 day period may be extended to 90 days, if NUMMI can demonstrate to the satisfaction of the APCO that the additional time is required. If source testing indicates any violation of the permit conditions, NUMMI shall report such violation to the Director of Enforcement in the report. (basis: BACT)
17. To demonstrate compliance with Part 3 of Condition 14207, the heater boxes of Topcoat Ovens #1 and #2 shall be source tested once per calendar year to determine the NOx emission rate (lb/MMBTU). After prior notification to the District's Source Test Manager, source testing shall be performed in accordance with the District's Manual of Procedures. Results of the source test shall be submitted to the District for review and approval within 60 days of the source test. Records of the source test results shall be kept and made available for District inspection for a period of five years following the date of entry. (basis: Regulation 2-6-409.2)

VI. Permit Conditions

Condition # 14210

For S3500, COLD CLEANER,
S3501, COLD CLEANER,
S3502, COLD CLEANER, AND
S30960, GENERAL CLEANING AND PAINT CLEANING:

1. In no event shall the total annual emissions from the combination of S3500 through S3502 Cold Cleaners and S30960 Fugitive Cleanup exceed 321.03 tons per year or 40.13 tons per month of POC, unless NUMMI notifies the Director of Enforcement within 30 calendar days of such an exceedance and submits a written report with the scheduled, monthly report to demonstrate that the overall North Passenger Paint Shop sources will not exceed the overall emissions limit specified in Part 5 of Condition 14205. (basis: Cumulative Increase)
2. Clean-up solvent usage shall be collected and recovered at 65% or greater (overall), as demonstrated by comparing gross solvent usage records to throughput of solvent recovery tank and/or disposal records. Monthly excursions below the percent recovery limit are allowed as long as the annual VOC emission clean up is not exceeded. (basis: BACT)
3. Purged paint and solvent shall be recovered in an enclosed collection system and shipped to a solvent recycler or proper disposal site. (basis: BACT)

Condition # 14211

For S3503, NPS PURGE THINNER TANK, AND
S3505, NPS WASTE SOLVENT TANK:

1. This source shall be used to store materials for the passenger line coating operation. (basis: Cumulative Increase)
2. This source shall be equipped with a submerged fill pipe. (basis: Regulation 8-5-301.1)

Condition # 15149

For S2826, PLASTIC PLANT BAYCO PART Cleaning Oven

1. Visible emissions from this source shall not exceed Ringelmann 0.5. (basis: BACT)
2. Source S2826 shall be checked for visible emissions monthly during daylight hours,

VI. Permit Conditions

while the equipment is operating. If any visible emissions are detected, the operator shall take corrective action within one week, and check for visible emissions after corrective action is taken. If no visible emissions are detected, the operator shall continue to check for visible emissions at the same frequency. (basis: Regulation 2-6-409.2)

- 3 Records of all visible emissions checks shall be kept, noting the person performing the check, and all corrective action taken at Source S2826. The records shall be retained for five (5) years from the date of entry and shall be made available to District personnel upon request. (basis: Regulation 2-6-409.2)

VI. Permit Conditions

Condition # 16780

For

S1504, COLD CLEANER TANK

AND

S2007 , COLD CLEANERS:

1. In no event shall the combined annual emissions from the operation of S1504S2007, exceed 5,068 pounds of precursor organic compounds during any consecutive twelve-month period. (basis: Cumulative Increase)
2. Unless NUMMI can demonstrate to the satisfaction of the APCO, through monthly record keeping and VOC calculations, that an alternative type or amount of material usage will not result in VOC emissions exceeding those limits set in Part 1 of Condition 16780 or increase toxics emissions above any risk screening trigger level, the following usage limits shall not be exceeded while operating the sources covered by Condition 16780:
 - a. Combined, net usage of Safety Kleen 105 shall not exceed 160 gallons during any consecutive twelve- month period.
 - b. Combined, net usage of System One Ashland Solvent shall not exceed 60 gallons during any consecutive twelve-month period.
 - c. Combined, net usage of NUMMI Solvent IV shall not exceed 500 gallons during any consecutive twelve- month period. (basis: Cumulative Increase)
3. In order to verify compliance with the above conditions, the following records shall be maintained in a District approved log and kept on site and made available for District inspection for a period of 5 years from the date on which a record is made:
 - a. The type and net amount of solvent used monthly.
 - b. The monthly quantities shall be totaled on a consecutive 12-month basis. (basis: Cumulative Increase)

Condition # 17797

For S41, PASSENGER BODY PHOSPHATE WASHER

1. Only use natural gas as a fuel for this source (basis: Regulation 9-1-304).

Condition # 18533

For S1900, PLASTIC PARTS ADHESION OPERATION

1. Usage of adhesion promoter at S-1900 shall not exceed 50 gallons in any consecutive twelve month period, unless otherwise allowed in part 2 of this condition. (basis:

VI. Permit Conditions

Cumulative Increase, Toxics)

2. Material usage in excess of that specified in part 1 of this condition, may be used at S-1900 provided NUMMI can demonstrate that both of the following are satisfied:
 - a. Total POC emissions from S-1900 do not exceed 81 pounds in any consecutive twelve month period; and
 - b. The use of these materials does not increase toxic emissions above any risk screening trigger level listed in Table 2-1-316 of Regulation 2-1.
(basis: Cumulative Increase or Toxic Risk Screen)

3. To demonstrate compliance with parts 1 and 2 of this condition, NUMMI shall maintain the following records and provide all of the data necessary to evaluate compliance with the stipulations of this condition, including, but not necessarily limited to, the following information:
 - a. Monthly usage of all POC containing materials used;
 - b. If a material other than that specified in part 1 is used or a material specified in part 1 is used in excess of the limit specified in part 1 and/or 2a, POC and toxic component contents of each material used; and mass emission calculations to demonstrate compliance with parts 1 and 2a, on a monthly basis;
 - c. Monthly usage and/or emission calculations shall be totaled for each consecutive twelve month period.

All records shall be recorded in a District-approved log. All records shall be retained on-site for 5 years, from the date of entry, and made available for inspection by District staff upon request. These recordkeeping requirements shall not replace the recordkeeping requirements contained in any applicable District Regulations.
(basis: Cumulative Increase, Toxic Risk Screen)

Condition # 19492

For S1901, OFFLINE EXPORT FINAL REPAIR AREA/BOOTH

- 1a. Usage of final repair coating at S-1901 shall not exceed 425 gallons in any consecutive twelve month period, unless otherwise allowed in part 2 of this condition.

- 1b. Usage of cleanup solvent (i.e., Isopropanol) at S-1901 shall not exceed 5 gallons in any consecutive twelve month period, unless otherwise allowed in part 2 of this condition. (basis: Cumulative Increase)

2. Material usage in excess of that specified in part 1 of this condition, may be used at S-1901 provided NUMMI can demonstrate that both of the following are satisfied:
 - a. Total POC emissions from S-1901 do not exceed 2,073 pounds in any consecutive

VI. Permit Conditions

twelve month period; and

- b. The use of these materials does not increase toxic emissions above any risk screening trigger level listed in Table 2-1-316 of Regulation 2-1.
(basis: Cumulative Increase or Toxic Risk Screen)

3. To demonstrate compliance with parts 1 and 2 of this condition, NUMMI shall maintain the following records and provide all of the data necessary to evaluate compliance with the stipulations of this condition, including, but not necessarily limited to, the following information:
 - a. Monthly usage of all POC containing materials used;
 - b. If a material other than that specified in part 1 is used or a material specified in part 1 is used in excess of the limit specified in part 1 and/or 2a, POC and toxic component contents of each material used; and mass emission calculations to demonstrate compliance with parts 1 and 2a, on a monthly basis;
 - c. Monthly usage and/or emission calculations shall be totaled for each consecutive twelve-month period.

All records shall be recorded in a District-approved log. All records shall be retained on-site for years, from the date of entry, and made available for inspection by District staff upon request. These recordkeeping requirements shall not replace the recordkeeping requirements contained in any applicable District Regulations.
(basis: Cumulative Increase, Toxic Risk Screen)

VII. APPLICABLE LIMITS & COMPLIANCE MONITORING REQUIREMENTS

This section has been included only to summarize the applicable emission limits contained in Section IV, Source-Specific Applicable Requirements, of this permit. The following tables show the relationship between each emission limit and the associated compliance monitoring provisions, if any. The monitoring frequency indicates whether periodic (P) or continuous (C) monitoring is required. For periodic monitoring, the frequency of the monitoring has also been shown, using the following codes: annual (A), quarterly (Q), monthly (M), weekly (W), daily (D), or on an event basis (E). No monitoring (N) has been required if the current applicable rule or regulation does not require monitoring, and the operation is unlikely to deviate from the applicable emission limit based upon the nature of the operation.

Note that emission limits indicated in each table are combined emission limits for sources identified in table, unless otherwise specified in individual emission limits.

Table VII - A
Applicable Limits and Compliance Monitoring Requirements
S2 – PASSENGER BODY ELPO DIP TANK

Type of Limit	Citation of Limit	FE Y/N	Future Effective Date	Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
VOC	BAAQMD 8-13-306	Y		Electrophoretic Primer VOC ≤ 145 g/l (1.2 lb/gal)	BAAQMD 8-13-503	P/M	Records
	BAAQMD Condition # 207 Part 1(a)			Total* Emissions ≤ 459.2 TPY (before abatement) or 250.5 TPY (after abatement)	BAAQMD Condition # 207 Part 5(b)	P/M	Records
	BAAQMD Condition # 207 Part 1(d)			Passenger Body Elpo (S2 + S3) Emissions ≤ 133.9 TPY (before abatement) or 66.4 TPY (after abatement)	BAAQMD Condition # 207 Part 5(b)	P/M	Records
	BAAQMD Condition # 207 Part 2(a)			Passenger Body Elpo VOC ≤ 1.21 lb/gal	BAAQMD Condition # 207 Part 5(b)	P/M	Records

VII. Applicable Limits and Compliance Monitoring Requirements

Table VII - A
Applicable Limits and Compliance Monitoring Requirements
S2 – PASSENGER BODY ELPO DIP TANK

Type of Limit	Citation of Limit	FE Y/N	Future Effective Date	Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
VOC	BAAQMD Condition # 207 Part 2(a)	Y		Passenger Body Elpo (S2+S3) Usage ≤ 221,334 gal/yr, and 21,725 gal/mon	BAAQMD Condition # 207 Part 5(b)	P/M	Records
Opacity	BAAQMD 6-301	Y		Ringelmann 1 for < 3 minutes in any hour	None	N	None
FP	BAAQMD 6-310	Y		0.15 gr/dscf	None	N	None
FP	BAAQMD 6-311	Y		4.10P0.67 lb/hr, where P is process weight, ton/hr	None	N	None

Total* includes all the following sources:

- S2, Passenger Body Elpo Dip Tank,
- S3, Passenger Body Elpo Oven
- S60, Passenger Undercoating Booth
- S61, Passenger Blackout Chassis Booth
- S62, Passenger Fuel Tank Booth
- S63, Passenger Protective Gas tank Oven
- S71, Passenger Cavity Wax Booth
- S72, Passenger PVC Exterior, Underbody & Engine Wax Booth
- S73, Passenger Exterior Wax Hot Air Dryer

- S101, Spare Parts ELPO Dip Tank
- S102, Spare Parts ELPO Oven
- S801, Stamping Plant Fugitive Solvent Emission
- S803, Passenger Sealer Deck Line (Fugitive)
- S804, Passenger Fugitive Repair Priming
- S805, Body Shop Assembly Areas
- S807, Passenger Anti-Chip Wheelhouse Booth
- S808, Passenger Sealer-Antichip Oven
- S813, Passenger Fugitive Trial Application Area – Bead Sealer

Table VII - B
Applicable Limits and Compliance Monitoring Requirements
S3 - PASSENGER BODY ELPO OVEN

Type of Limit	Citation of Limit	FE Y/N	Future Effective Date	Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
VOC	BAAQMD 8-13-306	Y		Electrophoretic Primer VOC ≤ 145 g/l (1.2 lb/gal)	BAAQMD 8-13-503	P/M	Records
	BAAQMD Condition # 207 Part 1(a)			Total* Emissions ≤ 459.2 TPY (before abatement) or 250.5 TPY (after abatement)	BAAQMD Condition # 207 Part 5(b)	P/M	Records

VII. Applicable Limits and Compliance Monitoring Requirements

Table VII - B
Applicable Limits and Compliance Monitoring Requirements
S3 - PASSENGER BODY ELPO OVEN

Type of Limit	Citation of Limit	FE Y/N	Future Effective Date	Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
VOC	BAAQMD Condition # 207 Part 1(d)			Passenger Body Elpo (S2+S3) Emissions \leq 133.9 TPY (before abatement) or 66.4 TPY (after abatement)	BAAQMD Condition # 207 Part 5(b)	P/M	Records
	BAAQMD Condition # 207 Part 2(a)			Passenger Body Elpo VOC \leq 1.21 lb/gal	BAAQMD Condition # 207 Part 5(b)	P/M	Records
	BAAQMD Condition # 207 Part 2(a)	Y		Passenger Body Elpo (S2+S3) Usage \leq 221,334 gal/yr, and 21,725 gal/mon	BAAQMD Condition # 207 Part 5(b)	P/M	Records
	BAAQMD Condition # 4281 Part 2	Y		A4 Destruction Efficiency \geq 90 wt%	BAAQMD Condition # 4281 Part 5	P/A	Source Test
	BAAQMD Condition # 4281 Part 2	Y		Temperature \geq 1200 °F	BAAQMD Condition # 4281 Part 4	P/C	Temperature
Opacity	BAAQMD 6-301	Y		Ringelmann 1 for < 3 minutes in any hour		N	
FP	BAAQMD 6-310	Y		0.15 gr/dscf		N	
FP	BAAQMD 6-311	Y		4.10P0.67 lb/hr, where P is process weight, ton/hr		N	

Total* includes all the following sources:

S2, Passenger Body Elpo Dip Tank,
 S3, Passenger Body Elpo Oven
 S60, Passenger Undercoating Booth
 S61, Passenger Blackout Chassis Booth
 S62, Passenger Fuel Tank Booth
 S63, Passenger Protective Gas tank Oven
 S71, Passenger Cavity Wax Booth
 S72, Passenger PVC Exterior, Underbody & Engine Wax Booth
 S73, Passenger Exterior Wax Hot Air Dryer

S101, Spare Parts ELPO Dip Tank
 S102, Spare Parts ELPO Oven
 S801, Stamping Plant Fugitive Solvent Emission
 S803, Passenger Sealer Deck Line (Fugitive)
 S804, Passenger Fugitive Repair Priming
 S805, Body Shop Assembly Areas
 S807, Passenger Anti-Chip Wheelhouse Booth
 S808, Passenger Sealer-Antichip Oven
 S813, Passenger Fugitive Trial Application Area – Bead Sealer

VII. Applicable Limits and Compliance Monitoring Requirements

Table VII - C
Applicable Limits and Compliance Monitoring Requirements
S41 – PASSENGER BODY PHOSPHATE WASHER

Type of Limit	Citation of Limit	FE Y/N	Future Effective Date	Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
Opacity	BAAQMD 6-301	Y		Ringelmann 1 for < 3 minutes in any hour		N	
FP	BAAQMD 6-310	Y		0.15 gr/dscf		N	
FP	BAAQMD 6-312	Y		4.10P0.67 lb/hr, where P is process weight, ton/hr		N	
SO2	BAAQMD 9-1-301	Y		GLC ¹ of 0.5 ppm for 3 min or 0.25 ppm for 60 min or 0.05 ppm for 24 hours		N	
	BAAQMD 9-1-302	Y		SO2 shall not exceed 300 ppm (dry)		N	

¹ Ground Level Concentration

VII. Applicable Limits and Compliance Monitoring Requirements

Table VII - D
Applicable Limits and Compliance Monitoring Requirements
S57 – BUMPER TOPCOAT BOOTH
S58 – BUMPER TOPCOAT OVEN
S59 – BUMPERS PRIME BOOTH
S65 – BUMPER PRIME OVEN

Type of Limit	Citation of Limit	FE Y/N	Future Effective Date	Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
VOC	BAAQMD 8-13-307.1	Y		Flexible Parts Primer VOC ≤ 490 g/l (4.1 lb/gal)	BAAQMD 8-13-503	P/M	Records
	BAAQMD 8-13-307.2	Y		Color Topcoat VOC ≤ 450 g/l (3.8 lb/gal)	BAAQMD 8-13-503	P/M	Records
VOC	BAAQMD 8-13-307.3	Y		Basecoat/Clearcoat VOC ≤ 540 g/l (4.5 lb/gal)	BAAQMD 8-13-503	P/M	Records
POC	BAAQMD Condition # 10320 Part 9	Y		Emissions ≤ 173 TPY	BAAQMD Condition # 10320 Part 14	P/M	Records
	BAAQMD Condition # 10320 Part 10	Y		Primer Usage ≤ 57,994 gal/yr, Non-Metallic High Solids Usage ≤ 32,586 gal/yr, Base Coat Usage ≤ 37,127 gal/yr, Clear Coat Usage ≤ 48,350 gal/yr; or compliance with Condition # 10320 Part 9	BAAQMD Condition # 10320 Part 14	P/M	Records
	BAAQMD Condition # 10320 Part 19	Y		A571 Temperature ≥ 1400 °F	BAAQMD Condition # 10320 Part 22	P/C	Temperature
POC	BAAQMD Condition # 10320 Part 20	Y		A571 Destruction Efficiency ≥ 98.5%, if inlet concentration of VOC ≥ 500 ppmv, as methane; or A571 Destruction Efficiency ≥ 95%, if inlet concentration of VOC < 500 ppmv, as methane	BAAQMD Condition # 10320 Part 23	P/A	Source Test

VII. Applicable Limits and Compliance Monitoring Requirements

Table VII - D
Applicable Limits and Compliance Monitoring Requirements
S57 – BUMPER TOPCOAT BOOTH
S58 – BUMPER TOPCOAT OVEN
S59 – BUMPERS PRIME BOOTH
S65 – BUMPER PRIME OVEN

Type of Limit	Citation of Limit	FE Y/N	Future Effective Date	Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
POC	BAAQMD Condition # 10320 Part 47	Y		Control Efficiency $\geq 90\%$	BAAQMD Condition # 10320 Part 47	P/A	Source Test
NOx	BAAQMD Condition # 10320 Part 4			S57+S58+S59+S65+S1070 +S1071 Emissions ≤ 26.16 TPY	BAAQMD Condition # 10320 Part 7	P/M	Records
NOx	BAAQMD Condition # 10320 Part 21			NOx from A571 ≤ 1.72 tons/month	BAAQMD Condition # 10320 Part 25	P/M	Records
CO	BAAQMD Condition # 10320 Part 5	Y		S57+S58+S59+S65+S1070 +S1071 Emissions ≤ 46.48 TPY	BAAQMD Condition # 10320 Part 7	P/M	Records
PM10	BAAQMD Condition # 10320 Part 15	Y		Capture/Control Efficiency of A593 $\geq 98\%$	BAAQMD Condition # 10320 Part 15	P/E	Records of scrubber system downtime
Opacity	BAAQMD 6-301	Y		Ringelmann 1 for < 3 minutes in any hour	BAAQMD Condition # 10320 Part 30	P/W	Records of scrubber system downtime
FP	BAAQMD 6-310	Y		0.15 gr/dscf	BAAQMD Condition # 10320 Part 30	P/W	Records of scrubber system downtime

VII. Applicable Limits and Compliance Monitoring Requirements

Table VII - D
Applicable Limits and Compliance Monitoring Requirements
S57 – BUMPER TOPCOAT BOOTH
S58 – BUMPER TOPCOAT OVEN
S59 – BUMPERS PRIME BOOTH
S65 – BUMPER PRIME OVEN

Type of Limit	Citation of Limit	FE Y/N	Future Effective Date	Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
FP	BAAQMD 6-311	Y		4.10P0.67 lb/hr, where P is process weight, ton/hr	BAAQMD Condition # 10320 Part 30	P/W	Records of scrubber system downtime
Fuel Usage	BAAQMD Condition # 10320 Part 2			S57+S58+S59+S65+S1070 +S1071 Natural Gas Usage ≤ 3.16 MM Therms/Yr	BAAQMD Condition # 10320 Part 2	P/M	Records

Table VII - E
Applicable Limits and Compliance Monitoring Requirements
S60 – PASSENGER UNDERCOATING BOOTH

Type of Limit	Citation of Limit	FE Y/N	Future Effective Date	Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
VOC	BAAQMD 8-13-302.1	Y		Spray Primer VOC ≤ 1.80 kg/l (15.0 lb VOC/gal of applied solids)	BAAQMD 8-13-503	P/M	Records
	BAAQMD 8-13-302.2	Y		Primer Surfacer VOC ≤ 1.80 kg/l (15.0 lb VOC/gal of applied solids)	BAAQMD 8-13-503	P/M	Records
	BAAQMD 8-13-302.3	Y		Topcoat VOC ≤ 1.80 kg/l (15.0 lb VOC/gal of applied solids)	BAAQMD 8-13-503	P/M	Records
VOC	BAAQMD Condition # 207 Part 1(a)			Total* Emissions ≤ 459.2 TPY (before abatement) or 250.5 TPY (after abatement)	BAAQMD Condition # 207 Part 5(b)	P/M	Records

VII. Applicable Limits and Compliance Monitoring Requirements

Table VII - E
Applicable Limits and Compliance Monitoring Requirements
S60 – PASSENGER UNDERCOATING BOOTH

Type of Limit	Citation of Limit	FE Y/N	Future Effective Date	Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
	BAAQMD Condition # 207 Part 1(d)			Undercoating (S60+S803) Emissions \leq 93.8 TPY (before abatement) or 14.5 TPY (after abatement)	BAAQMD Condition # 207 Part 5(b)	P/M	Records
	BAAQMD Condition # 207 Part 2(a)			Undercoating VOC \leq 0.75 lb/gal	BAAQMD Condition # 207 Part 5(b)	P/M	Records
	BAAQMD Condition # 207 Part 2(a)			Undercoating (S60+S803) Usage \leq 328,967 gal/yr, 32,290 gal/mon	BAAQMD Condition # 207 Part 5(b)	P/M	Records
Opacity	BAAQMD 6-301	Y		Ringelmann 1 for < 3 minutes in any hour	None	N	None
FP	BAAQMD 6-310	Y		0.15 gr/dscf	None	N	None
FP	BAAQMD 6-311	Y		4.10P0.67 lb/hr, where P is process weight, ton/hr	None	N	None

Total* includes all the following sources:

S2, Passenger Body Elpo Dip Tank,
 S3, Passenger Body Elpo Oven
 S60, Passenger Undercoating Booth
 S61, Passenger Blackout Chassis Booth
 S62, Passenger Fuel Tank Booth
 S63, Passenger Protective Gas tank Oven
 S71, Passenger Cavity Wax Booth
 S72, Passenger PVC Exterior, Underbody & Engine Wax
 Booth
 S73, Passenger Exterior Wax Hot Air Dryer

S101, Spare Parts ELPO Dip Tank
 S102, Spare Parts ELPO Oven
 S801, Stamping Plant Fugitive Solvent Emission
 S803, Passenger Sealer Deck Line (Fugitive)
 S804, Passenger Fugitive Repair Priming
 S805, Body Shop Assembly Areas
 S807, Passenger Anti-Chip Wheelhouse Booth
 S808, Passenger Sealer-Antichip Oven
 S813, Passenger Fugitive Trial Application Area – Bead
 Sealer

VII. Applicable Limits and Compliance Monitoring Requirements

Table VII - F
Applicable Limits and Compliance Monitoring Requirements
S61 – PASSENGER BLACKOUT CHASSIS BOOTH

Type of Limit	Citation of Limit	FE Y/N	Future Effective Date	Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
VOC	BAAQMD 8-13-302.1	Y		Spray Primer VOC \leq 1.80 kg/l (15.0 lb VOC/gal of applied solids)	BAAQMD 8-13-503	P/M	Records
	BAAQMD 8-13-302.2	Y		Primer Surfacer VOC \leq 1.80 kg/l (15.0 lb VOC/gal of applied solids)	BAAQMD 8-13-503	P/M	Records
	BAAQMD 8-13-302.3	Y		Topcoat VOC \leq 1.80 kg/l (15.0 lb VOC/gal of applied solids)	BAAQMD 8-13-503	P/M	Records
	BAAQMD Condition # 207 Part 1(a)			Total* Emissions \leq 459.2 TPY (before abatement) or 250.5 TPY (after abatement)	BAAQMD Condition # 207 Part 5(b)	P/M	Records
	BAAQMD Condition # 207 Part 1(d)			Blackout Chassis Emissions \leq 18.1 TPY	BAAQMD Condition # 207 Part 5(b)	P/M	Records
	BAAQMD Condition # 207 Part 2(a)			Blackout Chassis VOC \leq 3.02 lb/gal	BAAQMD Condition # 207 Part 5(b)	P/M	Records
	BAAQMD Condition # 207 Part 2(a)			Blackout Chassis Usage \leq 11,990 gal/yr, 1,177 gal/mon	BAAQMD Condition # 207 Part 5(b)	P/M	Records
Opacity	BAAQMD 6-301	Y		Ringelmann 1 for < 3 minutes in any hour	None	N	None

VII. Applicable Limits and Compliance Monitoring Requirements

Table VII - F
Applicable Limits and Compliance Monitoring Requirements
S61 – PASSENGER BLACKOUT CHASSIS BOOTH

Type of Limit	Citation of Limit	FE Y/N	Future Effective Date	Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
FP	BAAQMD 6-310	Y		0.15 gr/dscf	None	N	None
FP	BAAQMD 6-311	Y		4.10P0.67 lb/hr, where P is process weight, ton/hr	None	N	None

Total* includes all the following sources:

S2, Passenger Body Elpo Dip Tank,
 S3, Passenger Body Elpo Oven
 S60, Passenger Undercoating Booth
 S61, Passenger Blackout Chassis Booth
 S62, Passenger Fuel Tank Booth
 S63, Passenger Protective Gas tank Oven
 S71, Passenger Cavity Wax Booth
 S72, Passenger PVC Exterior, Underbody & Engine Wax Booth
 S73, Passenger Exterior Wax Hot Air Dryer

S101, Spare Parts ELPO Dip Tank
 S102, Spare Parts ELPO Oven
 S801, Stamping Plant Fugitive Solvent Emission
 S803, Passenger Sealer Deck Line (Fugitive)
 S804, Passenger Fugitive Repair Priming
 S805, Body Shop Assembly Areas
 S807, Passenger Anti-Chip Wheelhouse Booth
 S808, Passenger Sealer-Antichip Oven
 S813, Passenger Fugitive Trial Application Area – Bead Sealer

Table VII - G
Applicable Limits and Compliance Monitoring Requirements
S62 – PASSENGER GAS TANK PAINT BOOTH
S63 – PASSENGER GAS TANK PAINT OVEN

Type of Limit	Citation of Limit	FE Y/N	Future Effective Date	Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
VOC	BAAQMD 8-13-308	Y		Off-Line VOC \leq 340 g/l (2.8 lb/gal)	BAAQMD 8-13-503	P/M	Records
	BAAQMD Condition # 207 Part 1(a)			Total* Emissions \leq 459.2 TPY (before abatement) or 250.5 TPY (after abatement)	BAAQMD Condition # 207 Part 5(b)	P/M	Records
	BAAQMD Condition # 207 Part 1(d)			Protective Fuel Tank \leq 19.1 TPY (before abatement) or 9.3 TPY (after abatement)	BAAQMD Condition # 207 Part 5(b)	P/M	Records

VII. Applicable Limits and Compliance Monitoring Requirements

Table VII - G
Applicable Limits and Compliance Monitoring Requirements
S62 – PASSENGER GAS TANK PAINT BOOTH
S63 – PASSENGER GAS TANK PAINT OVEN

Type of Limit	Citation of Limit	FE Y/N	Future Effective Date	Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
	BAAQMD Condition # 207 Part 2(a)			Protective Fuel Tank VOC ≤ 0.95 lb/gal	BAAQMD Condition # 207 Part 5(b)	P/M	Records
	BAAQMD Condition # 207 Part 2(a)			Protective Fuel Tank Usage ≤ 40,124 gal/yr, 3,497 gal/mon	BAAQMD Condition # 207 Part 5(b)	P/M	Records

Total* includes all the following sources:

S2, Passenger Body Elpo Dip Tank,
 S3, Passenger Body Elpo Oven
 S60, Passenger Undercoating Booth
 S61, Passenger Blackout Chassis Booth
 S62, Passenger Fuel Tank Booth
 S63, Passenger Protective Gas tank Oven
 S71, Passenger Cavity Wax Booth
 S72, Passenger PVC Exterior, Underbody & Engine Wax Booth
 S73, Passenger Exterior Wax Hot Air Dryer

S101, Spare Parts ELPO Dip Tank
 S102, Spare Parts ELPO Oven
 S801, Stamping Plant Fugitive Solvent Emission
 S803, Passenger Sealer Deck Line (Fugitive)
 S804, Passenger Fugitive Repair Priming
 S805, Body Shop Assembly Areas
 S807, Passenger Anti-Chip Wheelhouse Booth
 S808, Passenger Sealer-Antichip Oven
 S813, Passenger Fugitive Trial Application Area – Bead Sealer

VII. Applicable Limits and Compliance Monitoring Requirements

**Table VII – G1
 Applicable Limits and Compliance Monitoring Requirements
 S62 – PASSENGER GAS TANK PAINT BOOTH**

Type of Limit	Citation of Limit	FE Y/N	Future Effective Date	Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
Opacity	BAAQMD 6-301	Y		Ringelmann 1 for < 3 minutes in any hour	None	N	None
FP	BAAQMD 6-310	Y		0.15 gr/dscf	None	N	None
FP	BAAQMD 6-311	Y		4.10P0.67 lb/hr, where P is process weight, ton/hr	None	N	None

**Table VII – G2
 Applicable Limits and Compliance Monitoring Requirements
 S63 – PASSENGER GAS TANK PAINT OVEN**

Type of Limit	Citation of Limit	FE Y/N	Future Effective Date	Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
Opacity	BAAQMD 6-301	Y		Ringelmann 1 for < 3 minutes in any hour		N	
FP	BAAQMD 6-310	Y		0.15 gr/dscf		N	
FP	BAAQMD 6-311	Y		4.10P0.67 lb/hr, where P is process weight, ton/hr		N	

VII. Applicable Limits and Compliance Monitoring Requirements

Table VII - H
Applicable Limits and Compliance Monitoring Requirements
S71 – PASSENGER CAVITY WAX BOOTH

Type of Limit	Citation of Limit	FE Y/N	Future Effective Date	Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
VOC	BAAQMD 8-13-302.1	Y		Spray Primer VOC \leq 1.80 kg/l (15.0 lb VOC/gal of applied solids)	BAAQMD 8-13-503	P/M	Records
	BAAQMD 8-13-302.2	Y		Primer Surfacer VOC \leq 1.80 kg/l (15.0 lb VOC/gal of applied solids)	BAAQMD 8-13-503	P/M	Records
	BAAQMD 8-13-302.3	Y		Topcoat VOC \leq 1.80 kg/l (15.0 lb VOC/gal of applied solids)	BAAQMD 8-13-503	P/M	Records
	BAAQMD Condition # 207 Part 1(a)			Total* Emissions \leq 459.2 TPY (before abatement) or 250.5 TPY (after abatement)	BAAQMD Condition # 207 Part 5(b)	P/M	Records
	BAAQMD Condition # 207 Part 1(d)			Cavity Wax Emissions \leq 2.5 TPY	BAAQMD Condition # 207 Part 5(b)	P/M	Records
	BAAQMD Condition # 207 Part 1(d)			Hinge Wax Emissions \leq 4.9 TPY	BAAQMD Condition # 207 Part 5(b)	P/M	Records
	BAAQMD Condition # 207 Part 2(a)			Cavity Wax VOC \leq 0.94 lb/gal	BAAQMD Condition # 207 Part 5(b)	P/M	Records
	BAAQMD Condition # 207 Part 2(a)			Hinge Wax VOC \leq 5.01 lb/gal	BAAQMD Condition # 207 Part 5(b)	P/M	Records
	BAAQMD Condition # 207 Part 2(a)			Cavity Wax Usage \leq 5,326 gal/yr, 523 gal/mon	BAAQMD Condition # 207 Part 5(b)	P/M	Records

VII. Applicable Limits and Compliance Monitoring Requirements

Table VII - H
Applicable Limits and Compliance Monitoring Requirements
S71 – PASSENGER CAVITY WAX BOOTH

Type of Limit	Citation of Limit	FE Y/N	Future Effective Date	Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
	BAAQMD Condition # 207 Part 2(a)			Hinge Wax Usage \leq 1,962 gal/yr, 193 gal/mon	BAAQMD Condition # 207 Part 5(b)	P/M	Records
Opacity	BAAQMD 6-301	Y		Ringelmann 1 for < 3 minutes in any hour	None	N	None
FP	BAAQMD 6-310	Y		0.15 gr/dscf	None	N	None
FP	BAAQMD 6-311	Y		4.10P0.67 lb/hr, where P is process weight, ton/hr	None	N	None

Total* includes all the following sources:

S2, Passenger Body Elpo Dip Tank,
 S3, Passenger Body Elpo Oven
 S60, Passenger Undercoating Booth
 S61, Passenger Blackout Chassis Booth
 S62, Passenger Fuel Tank Booth
 S63, Passenger Protective Gas tank Oven
 S71, Passenger Cavity Wax Booth
 S72, Passenger PVC Exterior, Underbody & Engine Wax Booth
 S73, Passenger Exterior Wax Hot Air Dryer

S101, Spare Parts ELPO Dip Tank
 S102, Spare Parts ELPO Oven
 S801, Stamping Plant Fugitive Solvent Emission
 S803, Passenger Sealer Deck Line (Fugitive)
 S804, Passenger Fugitive Repair Priming
 S805, Body Shop Assembly Areas
 S807, Passenger Anti-Chip Wheelhouse Booth
 S808, Passenger Sealer-Antichip Oven
 S813, Passenger Fugitive Trial Application Area – Bead Sealer

Table VII - I
Applicable Limits and Compliance Monitoring Requirements
S72 – PASSENGER PVC EXTERIOR, UNDERBODY & ENGINE WAX BOOTH

Type of Limit	Citation of Limit	FE Y/N	Future Effective Date	Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
VOC	BAAQMD 8-13-302.1	Y		Spray Primer VOC \leq 1.80 kg/l (15.0 lb VOC/gal of applied solids)	BAAQMD 8-13-503	P/M	Records
	BAAQMD 8-13-302.2	Y		Primer Surfacer VOC \leq 1.80 kg/l (15.0 lb VOC/gal of applied solids)	BAAQMD 8-13-503	P/M	Records

VII. Applicable Limits and Compliance Monitoring Requirements

Table VII - I
Applicable Limits and Compliance Monitoring Requirements
S72 – PASSENGER PVC EXTERIOR, UNDERBODY & ENGINE WAX BOOTH

Type of Limit	Citation of Limit	FE Y/N	Future Effective Date	Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
	BAAQMD 8-13-302.3	Y		Topcoat VOC \leq 1.80 kg/l (15.0 lb VOC/gal of applied solids)	BAAQMD 8-13-503	P/M	Records
VOC	BAAQMD Condition # 207 Part 1(a)			Total* Emissions \leq 459.2 TPY (before abatement) or 250.5 TPY (after abatement)	BAAQMD Condition # 207 Part 5(b)	P/M	Records
	BAAQMD Condition # 207 Part 1(d)			Engine Wax Emissions \leq 0.5 TPY	BAAQMD Condition # 207 Part 5(b)	P/M	Records
	BAAQMD Condition # 207 Part 2(a)			Engine Wax VOC \leq 0.59 lb/gal	BAAQMD Condition # 207 Part 5(b)	P/M	Records
	BAAQMD Condition # 207 Part 2(a)			Engine Wax Usage \leq 1,538 gal/yr, 151 gal/mon	BAAQMD Condition # 207 Part 5(b)	P/M	Records
Opacity	BAAQMD 6-301	Y		Ringelmann 1 for < 3 minutes in any hour	None	N	None
FP	BAAQMD 6-310	Y		0.15 gr/dscf	None	N	None
FP	BAAQMD 6-311	Y		4.10P0.67 lb/hr, where P is process weight, ton/hr	None	N	None

Total* includes all the following sources:
 S2, Passenger Body Elpo Dip Tank,
 S3, Passenger Body Elpo Oven
 S60, Passenger Undercoating Booth
 S61, Passenger Blackout Chassis Booth
 S62, Passenger Fuel Tank Booth
 S63, Passenger Protective Gas tank Oven
 S71, Passenger Cavity Wax Booth
 S72, Passenger PVC Exterior, Underbody & Engine Wax
 Booth
 S73, Passenger Exterior Wax Hot Air Dryer

S101, Spare Parts ELPO Dip Tank
 S102, Spare Parts ELPO Oven
 S801, Stamping Plant Fugitive Solvent Emission
 S803, Passenger Sealer Deck Line (Fugitive)
 S804, Passenger Fugitive Repair Priming
 S805, Body Shop Assembly Areas
 S807, Passenger Anti-Chip Wheelhouse Booth
 S808, Passenger Sealer-Antichip Oven
 S813, Passenger Fugitive Trial Application Area – Bead
 Sealer

VII. Applicable Limits and Compliance Monitoring Requirements

Table VII - J
Applicable Limits and Compliance Monitoring Requirements
S73 – PASSENGER EXTERIOR WAX HOT AIR DRYER

Type of Limit	Citation of Limit	FE Y/N	Future Effective Date	Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
VOC	BAAQMD 8-13-302.1	Y		Spray Primer VOC \leq 1.80 kg/l (15.0 lb VOC/gal of applied solids)	BAAQMD 8-13-503	P/M	Records
	BAAQMD 8-13-302.2	Y		Primer Surfacer VOC \leq 1.80 kg/l (15.0 lb VOC/gal of applied solids)	BAAQMD 8-13-503	P/M	Records
	BAAQMD 8-13-302.3	Y		Topcoat VOC \leq 1.80 kg/l (15.0 lb VOC/gal of applied solids)	BAAQMD 8-13-503	P/M	Records
	BAAQMD Condition # 207 Part 1(a)			Total* Emissions \leq 459.2 TPY (before abatement) or 250.5 TPY (after abatement)	BAAQMD Condition # 207 Part 5(b)	P/M	Records
	BAAQMD Condition # 207 Part 1(d)			Exterior Wax VOC \leq 5.9 TPY	BAAQMD Condition # 207 Part 5(b)	P/M	Records
	BAAQMD Condition # 207 Part 2(a)			Exterior Wax VOC \leq 1.50 lb/gal	BAAQMD Condition # 207 Part 5(b)	P/M	Records
	BAAQMD Condition # 207 Part 2(a)			Exterior Wax Usage \leq 7,900 gal/yr, 776 gal/mon	BAAQMD Condition # 207 Part 5(b)	P/M	Records
Opacity	BAAQMD 6-301	Y		Ringelmann 1 for < 3 minutes in any hour		N	
FP	BAAQMD 6-310	Y		0.15 gr/dscf		N	

Total* includes all the following sources:

S2, Passenger Body Elpo Dip Tank,
 S3, Passenger Body Elpo Oven
 S60, Passenger Undercoating Booth
 S61, Passenger Blackout Chassis Booth
 S62, Passenger Fuel Tank Booth
 S63, Passenger Protective Gas tank Oven
 S71, Passenger Cavity Wax Booth
 S72, Passenger PVC Exterior, Underbody & Engine Wax Booth
 S73, Passenger Exterior Wax Hot Air Dryer

S101, Spare Parts ELPO Dip Tank
 S102, Spare Parts ELPO Oven
 S801, Stamping Plant Fugitive Solvent Emission
 S803, Passenger Sealer Deck Line (Fugitive)
 S804, Passenger Fugitive Repair Priming
 S805, Body Shop Assembly Areas
 S807, Passenger Anti-Chip Wheelhouse Booth
 S808, Passenger Sealer-Antichip Oven
 S813, Passenger Fugitive Trial Application Area – Bead Sealer

VII. Applicable Limits and Compliance Monitoring Requirements

Table VII – K
Applicable Limits and Compliance Monitoring Requirements
S101 – SPARE PARTS ELPO DIP TANK, S102 – SPARE PARTS ELPO OVEN

Type of Limit	Citation of Limit	FE Y/N	Future Effective Date	Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
VOC	BAAQMD 8-13-306	Y		Electrophoretic Primer VOC ≤ 145 g/l (1.2 lb/gal)	BAAQMD 8-13-503	P/M	Records
	BAAQMD Condition # 207 Part 1(a)			Total* Emissions ≤ 459.2 TPY (before abatement) or 250.5 TPY (after abatement)	BAAQMD Condition # 207 Part 5(b)	P/M	Records
	BAAQMD Condition # 207 Part 1(d)			Spare Parts ELPO Emissions ≤ 17.2 TPY (before abatement) or 6.9 TPY (after abatement)	BAAQMD Condition # 207 Part 5(b)	P/M	Records
	BAAQMD Condition # 207 Part 2(a)			Spare Parts Elpo VOC ≤ 1.21 lb/gal	BAAQMD Condition # 207 Part 5(b)	P/M	Records
	BAAQMD Condition # 207 Part 2(a)	Y		Spare Parts Elpo Usage ≤ 28,400 gal/yr, 3,156 gal/mon	BAAQMD Condition # 207 Part 5(b)	P/M	Records
	BAAQMD Condition # 207 Part 3(A)(1)	Y		Spare Parts Elpo Oven Destruction Efficiency ≥ 60 wt%	BAAQMD Condition # 207 Part 3(A)(2)	P/A	Source Test
	BAAMQD Condition # 207 Part 3(A)(1)			Temperature ≥ 800 °F	BAAQMD Condition # 207 Part 3(A)(1)	P/C	Temperature

Total* includes all the following sources:

S2, Passenger Body Elpo Dip Tank,
 S3, Passenger Body Elpo Oven
 S60, Passenger Undercoating Booth
 S61, Passenger Blackout Chassis Booth
 S62, Passenger Fuel Tank Booth
 S63, Passenger Protective Gas tank Oven
 S71, Passenger Cavity Wax Booth
 S72, Passenger PVC Exterior, Underbody & Engine Wax
 Booth
 S73, Passenger Exterior Wax Hot Air Dryer

S101, Spare Parts ELPO Dip Tank
 S102, Spare Parts ELPO Oven
 S801, Stamping Plant Fugitive Solvent Emission
 S803, Passenger Sealer Deck Line (Fugitive)
 S804, Passenger Fugitive Repair Priming
 S805, Body Shop Assembly Areas
 S807, Passenger Anti-Chip Wheelhouse Booth
 S808, Passenger Sealer-Antichip Oven
 S813, Passenger Fugitive Trial Application Area – Bead
 Sealer

VII. Applicable Limits and Compliance Monitoring Requirements

**Table VII – K1
 Applicable Limits and Compliance Monitoring Requirements
 S101 – SPARE PARTS ELPO DIP TANK**

Type of Limit	Citation of Limit	FE Y/N	Future Effective Date	Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
Opacity	BAAQMD 6-301	Y		Ringelmann 1 for < 3 minutes in any hour	None	N	None
FP	BAAQMD 6-310	Y		0.15 gr/dscf	None	N	None
FP	BAAQMD 6-311	Y		4.10P0.67 lb/hr, where P is process weight, ton/hr	None	N	None

**Table VII – K2
 Applicable Limits and Compliance Monitoring Requirements
 S102 – SPARE PARTS ELPO OVEN**

Type of Limit	Citation of Limit	FE Y/N	Future Effective Date	Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
Opacity	BAAQMD 6-301	Y		Ringelmann 1 for < 3 minutes in any hour		N	
FP	BAAQMD 6-310	Y		0.15 gr/dscf		N	
FP	BAAQMD 6-311	Y		4.10P0.67 lb/hr, where P is process weight, ton/hr		N	

VII. Applicable Limits and Compliance Monitoring Requirements

**Table VII – L
 Applicable Limits and Compliance Monitoring Requirements
 S405 – WASTE WATER STORAGE TANK
 S408 – PURGE THINNER ABOVE GROUND STORAGE TANK
 S414 – WASTE WATER STORAGE TANK**

Type of Limit	Citation of Limit	FE Y/N	Future Effective Date	Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
VOC	None	Y		None	Regulation 8-5-501	P/E	Records

**Table VII – M
 Applicable Limits and Compliance Monitoring Requirements
 S406 – WINDSHIELD WASHER FLUID ABOVE GROUND STORAGE TANK**

Type of Limit	Citation of Limit	FE Y/N	Future Effective Date	Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
VOC	None	Y		None	Regulation 8-5-501	P/E	Records
	BAAQMD Condition # 10709 Part 1	Y		Throughput \leq 530,170 gals/yr	BAAQMD Condition # 10709 Part 3	P/E	Records

VII. Applicable Limits and Compliance Monitoring Requirements

Table VII - O
Applicable Limits and Compliance Monitoring Requirements
S801 – STAMPING PLANT FUGITIVE SOLVENT EMISSIONS

Type of Limit	Citation of Limit	FE Y/N	Future Effective Date	Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
VOC	BAAQMD Regulation 8-2-301	Y		Emissions \leq 15 lb/day or \leq 300 ppmv		N	
	BAAQMD Condition # 207 Part 1(b)			Fugitive Emissions from Body & Assembly (S801+S802+S803+S804+S805+S813) \leq 69 TPY and 6.8 ton/mon	BAAQMD Condition # 207 Part 5(b)	P/M	Records

Table VII - P
Applicable Limits and Compliance Monitoring Requirements
S802 – STAMPING PLANT FUGITIVE MACHINING EMISSIONS

Type of Limit	Citation of Limit	FE Y/N	Future Effective Date	Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
VOC	BAAQMD Condition # 207 Part 1(b)			Fugitive Emissions from Body & Assembly (S801+S802+S803+S804+S805+S813) \leq 69 TPY and 6.8 ton/mon	BAAQMD Condition # 207 Part 5(b)	P/M	Records
Opacity	BAAQMD 6-301	Y		Ringelmann 1 for < 3 minutes in any hour	None	N	None
FP	BAAQMD 6-310	Y		0.15 gr/dscf	None	N	None

VII. Applicable Limits and Compliance Monitoring Requirements

Table VII - P
Applicable Limits and Compliance Monitoring Requirements
S802 – STAMPING PLANT FUGITIVE MACHINING EMISSIONS

Type of Limit	Citation of Limit	FE Y/N	Future Effective Date	Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
FP	BAAQMD 6-310	Y		4.10P0.67 lb/hr, where P is process weight, ton/hr	None	N	None

VII. Applicable Limits and Compliance Monitoring Requirements

Table VII – Q
Applicable Limits and Compliance Monitoring Requirements
S803 – PASSENGER SEALER DECK LINE (FUGITIVE)

Type of Limit	Citation of Limit	FE Y/N	Future Effective Date	Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
VOC	BAAQMD 8-13-302.1	Y		Spray Primer VOC \leq 1.80 kg/l (15.0 lb VOC/gal of applied solids)	BAAQMD 8-13-503	P/M	Records
	BAAQMD 8-13-302.2	Y		Primer Surfacer VOC \leq 1.80 kg/l (15.0 lb VOC/gal of applied solids)	BAAQMD 8-13-503	P/M	Records
	BAAQMD 8-13-302.3	Y		Topcoat VOC \leq 1.80 kg/l (15.0 lb VOC/gal of applied solids)	BAAQMD 8-13-503	P/M	Records
	BAAQMD Condition # 207 Part 1(a)			Total* Emissions \leq 459.2 TPY (before abatement) or 250.5 TPY (after abatement)	BAAQMD Condition # 207 Part 5(b)	P/M	Records
	BAAQMD Condition # 207 Part 1(d)			Undercoating (S60+S803) Emissions \leq 93.8 TPY (before abatement) or 14.5 TPY (after abatement)	BAAQMD Condition # 207 Part 5(b)	P/M	Records
	BAAQMD Condition # 207 Part 1(d)			Underbody Black (S801+S802+S803+S804+S805+S813) Emissions \leq 5.5 TPY	BAAQMD Condition # 207 Part 5(b)	P/M	Records
	BAAQMD Condition # 207 Part 2(a)			Undercoating VOC \leq 0.75 lb/gal	BAAQMD Condition # 207 Part 5(b)	P/M	Records
	BAAQMD Condition # 207 Part 2(a)			Underbody Black VOC \leq 3.02 lb/gal	BAAQMD Condition # 207 Part 5(b)	P/M	Records
	BAAQMD Condition # 207 Part 2(a)			Undercoating (S60+S803) Usage \leq 328,967 gal/yr, 32,290 gal/mon	BAAQMD Condition # 207 Part 5(b)	P/M	Records

VII. Applicable Limits and Compliance Monitoring Requirements

Table VII – Q
Applicable Limits and Compliance Monitoring Requirements
S803 – PASSENGER SEALER DECK LINE (FUGITIVE)

Type of Limit	Citation of Limit	FE Y/N	Future Effective Date	Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
VOC	BAAQMD Condition # 207 Part 2(a)			Underbody Black (S801+S802+S803+S804+S805+S813) Usage ≤ 3,642 gal/yr, 357 gal/mon	BAAQMD Condition # 207 Part 5(b)	P/M	Records
Opacity	BAAQMD 6-301	Y		Ringelmann 1 for < 3 minutes in any hour	None	N	None
FP	BAAQMD 6-310	Y		0.15 gr/dscf	None	N	None
FP	BAAQMD 6-310	Y		4.10P0.67 lb/hr, where P is process weight, ton/hr	None	N	None

Total* includes all the following sources:

S2, Passenger Body Elpo Dip Tank,
 S3, Passenger Body Elpo Oven
 S60, Passenger Undercoating Booth
 S61, Passenger Blackout Chassis Booth
 S62, Passenger Fuel Tank Booth
 S63, Passenger Protective Gas tank Oven
 S71, Passenger Cavity Wax Booth
 S72, Passenger PVC Exterior, Underbody & Engine Wax Booth
 S73, Passenger Exterior Wax Hot Air Dryer

S101, Spare Parts ELPO Dip Tank
 S102, Spare Parts ELPO Oven
 S801, Stamping Plant Fugitive Solvent Emission
 S803, Passenger Sealer Deck Line (Fugitive)
 S804, Passenger Fugitive Repair Priming
 S805, Body Shop Assembly Areas
 S807, Passenger Anti-Chip Wheelhouse Booth
 S808, Passenger Sealer-Antichip Oven
 S813, Passenger Fugitive Trial Application Area – Bead Sealer

VII. Applicable Limits and Compliance Monitoring Requirements

Table VII - R
Applicable Limits and Compliance Monitoring Requirements
S804 – PASSENGER FUGITIVE REPAIR PRIMING
S813 – PASSENGER FUGITIVE TRIAL APPLICATION AREA – BEAD SEALER

Type of Limit	Citation of Limit	FE Y/N	Future Effective Date	Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
VOC	BAAQMD 8-13-302.1	Y		Spray Primer VOC \leq 1.80 kg/l (15.0 lb VOC/gal of applied solids)	BAAQMD 8-13-503	P/M	Records
	BAAQMD 8-13-302.2	Y		Primer Surfacer VOC \leq 1.80 kg/l (15.0 lb VOC/gal of applied solids)	BAAQMD 8-13-503	P/M	Records
VOC	BAAQMD 8-13-302.3	Y		Topcoat VOC \leq 1.80 kg/l (15.0 lb VOC/gal of applied solids)	BAAQMD 8-13-503	P/M	Records
	BAAQMD Condition # 207 Part 1(a)			Total* Emissions \leq 459.2 TPY (before abatement) or 250.5 TPY (after abatement)	BAAQMD Condition # 207 Part 5(b)	P/M	Records
	BAAQMD Condition # 207 Part 1(b)			Fugitive Emissions from Body & Assembly (S801+S802+S803+S804+S805+S813) \leq 69 TPY and 6.8 ton/mon	BAAQMD Condition # 207 Part 5(b)	P/M	Records
	BAAQMD Condition # 207 Part 1(d)			Underbody Black (S801+S802+S803+S804+S805+S813) Emissions \leq 5.5 TPY	BAAQMD Condition # 207 Part 5(b)	P/M	Records
	BAAQMD Condition # 207 Part 2(a)			Underbody Black VOC \leq 3.02 lb/gal	BAAQMD Condition # 207 Part 5(b)	P/M	Records

VII. Applicable Limits and Compliance Monitoring Requirements

Table VII - R
Applicable Limits and Compliance Monitoring Requirements
S804 – PASSENGER FUGITIVE REPAIR PRIMING
S813 – PASSENGER FUGITIVE TRIAL APPLICATION AREA – BEAD SEALER

Type of Limit	Citation of Limit	FE Y/N	Future Effective Date	Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
	BAAQMD Condition # 207 Part 2(a)			Underbody Black (S801+S802+S803+S804+S805+S813) Usage ≤ 3,642 gal/yr, 357 gal/mon	BAAQMD Condition # 207 Part 5(b)	P/M	Records
Opacity	BAAQMD 6-301	Y		Ringelmann 1 for < 3 minutes in any hour	None	N	None
FP	BAAQMD 6-310	Y		0.15 gr/dscf	None	N	None
FP	BAAQMD 6-310	Y		4.10P0.67 lb/hr, where P is process weight, ton/hr	None	N	None

Total* includes all the following sources:
 S2, Passenger Body Elpo Dip Tank,
 S3, Passenger Body Elpo Oven
 S60, Passenger Undercoating Booth
 S61, Passenger Blackout Chassis Booth
 S62, Passenger Fuel Tank Booth
 S63, Passenger Protective Gas tank Oven
 S71, Passenger Cavity Wax Booth
 S72, Passenger PVC Exterior, Underbody & Engine Wax Booth
 S73, Passenger Exterior Wax Hot Air Dryer
 S101, Spare Parts ELPO Dip Tank
 S102, Spare Parts ELPO Oven
 S801, Stamping Plant Fugitive Solvent Emission
 S803, Passenger Sealer Deck Line (Fugitive)
 S804, Passenger Fugitive Repair Priming
 S805, Body Shop Assembly Areas
 S807, Passenger Anti-Chip Wheelhouse Booth
 S808, Passenger Sealer-Antichip Oven
 S813, Passenger Fugitive Trial Application Area – Bead Sealer

VII. Applicable Limits and Compliance Monitoring Requirements

Table VII – S
Applicable Limits and Compliance Monitoring Requirements
S805 – BODY SHOP ASSEMBLY AREAS

Type of Limit	Citation of Limit	FE Y/N	Future Effective Date	Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
VOC	BAAQMD 8-13-302.1	Y		Spray Primer VOC \leq 1.80 kg/1 (15.0 lb VOC/gal of applied solids)	BAAQMD 8-13-503	P/M	Records
	BAAQMD Condition # 207 Part 1(a)			Total* Emissions \leq 459.2 TPY (before abatement) or 250.5 TPY (after abatement)	BAAQMD Condition # 207 Part 5(b)	P/M	Records
	BAAQMD Condition # 207 Part 1(b)			Fugitive Emissions from Body & Assembly (S801+S802+S803+S804+S805+S813) \leq 69 TPY and 6.8 ton/mon	BAAQMD Condition # 207 Part 5(b)	P/M	Records
	BAAQMD Condition # 207 Part 1(d)			Final Repair Emissions \leq 2.0 TPY	BAAQMD Condition # 207 Part 5(b)	P/M	Records
	BAAQMD Condition # 207 Part 1(d)			Paint Shop Sealant Emissions \leq 17.0 TPY (before abatement) or 5.4 TPY (after abatement)	BAAQMD Condition # 207 Part 5(b)	P/M	Records
	BAAQMD Condition # 207 Part 1(d)			Repair Primer Emissions \leq 5.1 TPY	BAAQMD Condition # 207 Part 5(b)	P/M	Records
	BAAQMD Condition # 207 Part 1(d)			Underbody Wax (S805+S807) Emissions \leq 5.3 TPY	BAAQMD Condition # 207 Part 5(b)	P/M	Records
	BAAQMD Condition # 207 Part 1(d)			Underbody Black (S801+S802+S803+S804+S805+S813) Emissions \leq 5.5 TPY	BAAQMD Condition # 207 Part 5(b)	P/M	Records

VII. Applicable Limits and Compliance Monitoring Requirements

Table VII – S
Applicable Limits and Compliance Monitoring Requirements
S805 – BODY SHOP ASSEMBLY AREAS

Type of Limit	Citation of Limit	FE Y/N	Future Effective Date	Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
	BAAQMD Condition # 207 Part 2(a)			Final Repair VOC \leq 6.41 lb/gal	BAAQMD Condition # 207 Part 5(b)	P/M	Records
	BAAQMD Condition # 207 Part 2(a)			Final Repair Usage \leq 637 gal/yr, 63 gal/mon	BAAQMD Condition # 207 Part 5(b)	P/M	Records
	BAAQMD Condition # 207 Part 2(a)			Paint Shop Sealant VOC \leq 0.39 lb/gal	BAAQMD Condition # 207 Part 5(b)	P/M	Records
	BAAQMD Condition # 207 Part 2(a)			Paint Shop Sealant Usage \leq 87,129 gal/yr, 10,753 gal/mon	BAAQMD Condition # 207 Part 5(b)	P/M	Records
	BAAQMD Condition # 207 Part 2(a)			Repair Primer VOC \leq 5.83 lb/gal	BAAQMD Condition # 207 Part 5(b)	P/M	Records
	BAAQMD Condition # 207 Part 2(a)			Repair Primer Usage \leq 1,750 gal/yr, 172 gal/mon	BAAQMD Condition # 207 Part 5(b)	P/M	Records
	BAAQMD Condition # 207 Part 2(a)			Underbody Wax (S805+S807) VOC \leq 1.04 lb/gal	BAAQMD Condition # 207 Part 5(b)	P/M	Records
	BAAQMD Condition # 207 Part 2(a)			Underbody Wax (S805+S807) Usage \leq 10,096 gal/yr, 991 gal/mon	BAAQMD Condition # 207 Part 5(b)	P/M	Records

VII. Applicable Limits and Compliance Monitoring Requirements

Table VII – S
Applicable Limits and Compliance Monitoring Requirements
S805 – BODY SHOP ASSEMBLY AREAS

Type of Limit	Citation of Limit	FE Y/N	Future Effective Date	Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
	BAAQMD Condition # 207 Part 2(a)			Underbody Black VOC ≤ 3.02 lb/gal	BAAQMD Condition # 207 Part 5(b)	P/M	Records
	BAAQMD Condition # 207 Part 2(a)			Underbody Black (S801+S802+S803+S804+ S805+S813) Usage ≤ 3,642 gal/yr, 357 gal/mon	BAAQMD Condition # 207 Part 5(b)	P/M	Records
Opacity	BAAQMD 6-301	Y		Ringelmann 1 for < 3 minutes in any hour	None	N	None
FP	BAAQMD 6-310	Y		0.15 gr/dscf	None	N	None
FP	BAAQMD 6-310	Y		4.10P0.67 lb/hr, where P is process weight, ton/hr	None	N	None

Total* includes all the following sources:

S2, Passenger Body Elpo Dip Tank,
 S3, Passenger Body Elpo Oven
 S60, Passenger Undercoating Booth
 S61, Passenger Blackout Chassis Booth
 S62, Passenger Fuel Tank Booth
 S63, Passenger Protective Gas tank Oven
 S71, Passenger Cavity Wax Booth
 S72, Passenger PVC Exterior, Underbody & Engine Wax
 Booth
 S73, Passenger Exterior Wax Hot Air Dryer

S101, Spare Parts ELPO Dip Tank
 S102, Spare Parts ELPO Oven
 S801, Stamping Plant Fugitive Solvent Emission
 S803, Passenger Sealer Deck Line (Fugitive)
 S804, Passenger Fugitive Repair Priming
 S805, Body Shop Assembly Areas
 S807, Passenger Anti-Chip Wheelhouse Booth
 S808, Passenger Sealer-Antichip Oven
 S813, Passenger Fugitive Trial Application Area – Bead
 Sealer

VII. Applicable Limits and Compliance Monitoring Requirements

Table VII – T
Applicable Limits and Compliance Monitoring Requirements
S807 – PASSENGER ANTI-CHIP WHEELHOUSE BOOTH
S808 – PASSENGER ANTI-CHIP OVEN (THERMAL OXIDIZER ZONES 1, 2, 3, 4, 5)

Type of Limit	Citation of Limit	FE Y/N	Future Effective Date	Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
VOC	BAAQMD 8-13-302.1	Y		Spray Primer VOC \leq 1.80 kg/l (15.0 lb VOC/gal of applied solids)	BAAQMD 8-13-503	P/M	Records
	BAAQMD Condition # 207 Part 1(a)			Total* Emissions \leq 459.2 TPY (before abatement) or 250.5 TPY (after abatement)	BAAQMD Condition # 207 Part 5(b)	P/M	Records
	BAAQMD Condition # 207 Part 1(d)	Y		Anti-Chip II (S807+S818) Emissions \leq 31.4 TPY (before abatement) or 7.2 TPY (after abatement)	BAAQMD Condition # 207 Part 5(b)	P/M	Records
VOC	BAAQMD Condition # 207 Part 1(d)	Y		Anti-Chip II (S807+S817) Emissions \leq 28.0 TPY (before abatement) or 22.0 TPY (after abatement)	BAAQMD Condition # 207 Part 5(b)	P/M	Records
	BAAQMD Condition # 207 Part 1(d)	Y		Underbody Wax (S805+S807) Emissions \leq 5.3 TPY	BAAQMD Condition # 207 Part 5(b)	P/M	Records
	BAAQMD Condition # 207 Part 2(a)			Anti-Chip II VOC \leq 2.09 lb/gal	BAAQMD Condition # 207 Part 5(b)	P/M	Records
	BAAQMD Condition # 207 Part 2(a)			Anti-Chip IB VOC \leq 4.06 lb/gal	BAAQMD Condition # 207 Part 5(b)	P/M	Records
	BAAQMD Condition # 207 Part 2(a)			Underbody Wax VOC \leq 1.04 lb/gal	BAAQMD Condition # 207 Part 5(b)	P/M	Records

VII. Applicable Limits and Compliance Monitoring Requirements

Table VII – T
Applicable Limits and Compliance Monitoring Requirements
S807 – PASSENGER ANTI-CHIP WHEELHOUSE BOOTH
S808 – PASSENGER ANTI-CHIP OVEN (THERMAL OXIDIZER ZONES 1, 2, 3, 4, 5)

Type of Limit	Citation of Limit	FE Y/N	Future Effective Date	Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
	BAAQMD Condition # 207 Part 2(a)	Y		Anti-Chip II (S807+S818) Usage ≤ 30,009 gal/yr, 2,946 gal/mon	BAAQMD Condition # 207 Part 5(b)	P/M	Records
	BAAQMD Condition # 207 Part 2(a)	Y		Anti-Chip IB (S807+S817) Usage ≤ 13,786 gal/yr, 1,353 gal/mon	BAAQMD Condition # 207 Part 5(b)	P/M	Records
	BAAQMD Condition # 207 Part 2(a)			Underbody Wax (S805+S807) Usage ≤ 10,096 gal/yr, 991 gal/mon	BAAQMD Condition # 207 Part 5(b)	P/M	Records
	BAAQMD Condition # 207 Part 3(B)(2)			A808 Temperature > 1400 °F	BAAQMD Condition # 207 Part 3(B)(2)	P/C	Temperature
	BAAQMD Condition # 207 Part 3(B)(2)			A808 Destruction Efficiency ≥ 98.5%, if inlet concentration of VOC ≥ 500 ppmv, as methane; or A808 Destruction Efficiency ≥ 95%, if inlet concentration of VOC ≤ 500 ppmv, as methane	BAAQMD Condition # 207 Part 3(B)(3)	P/A	Source Test

Total* includes all the following sources:

S2, Passenger Body Elpo Dip Tank,
 S3, Passenger Body Elpo Oven
 S60, Passenger Undercoating Booth
 S61, Passenger Blackout Chassis Booth
 S62, Passenger Fuel Tank Booth
 S63, Passenger Protective Gas tank Oven
 S71, Passenger Cavity Wax Booth
 S72, Passenger PVC Exterior, Underbody & Engine Wax Booth
 S73, Passenger Exterior Wax Hot Air Dryer

S101, Spare Parts ELPO Dip Tank
 S102, Spare Parts ELPO Oven
 S801, Stamping Plant Fugitive Solvent Emission
 S803, Passenger Sealer Deck Line (Fugitive)
 S804, Passenger Fugitive Repair Priming
 S805, Body Shop Assembly Areas
 S807, Passenger Anti-Chip Wheelhouse Booth
 S808, Passenger Sealer-AntiChip Oven
 S813, Passenger Fugitive Trial Application Area – Bead Sealer

VII. Applicable Limits and Compliance Monitoring Requirements

Table VII – T1
Applicable Limits and Compliance Monitoring Requirements
S807 – PASSENGER ANTI-CHIP WHEELHOUSE BOOTH

Type of Limit	Citation of Limit	FE Y/N	Future Effective Date	Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
Opacity	BAAQMD 6-301	Y		Ringelmann 1 for < 3 minutes in any hour	None	N	None
FP	BAAQMD 6-310	Y		0.15 gr/dscf	None	N	None
FP	BAAQMD 6-310	Y		4.10P0.67 lb/hr, where P is process weight, ton/hr	None	N	None

Table VII – T2
Applicable Limits and Compliance Monitoring Requirements
S808 – PASSENGER ANTICHIP OVEN (THERMAL OXIDIZER ZONES 1, 2, 3, 4, 5)

Type of Limit	Citation of Limit	FE Y/N	Future Effective Date	Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
Opacity	BAAQMD 6-301	Y		Ringelmann 1 for < 3 minutes in any hour		N	
FP	BAAQMD 6-310	Y		0.15 gr/dscf		N	
FP	BAAQMD 6-310	Y		4.10P0.67 lb/hr, where P is process weight, ton/hr		N	

VII. Applicable Limits and Compliance Monitoring Requirements

**Table VII - U
 Applicable Limits and Compliance Monitoring Requirements
 S806 – GDF**

Type of Limit	Citation of Limit	FE Y/N	Future Effective Date	Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
VOC	BAAQMD Condition # 7799	N		Throughput $\leq 1.1 \text{ E}6$ gals/yr	BAAQMD 8-7-503	P/M	Records

**Table VII – V
 Applicable Limits and Compliance Monitoring Requirements
 S1504– COLD CLEANING TANK,
 S2007– COLD CLEANER,**

Type of Limit	Citation of Limit	FE Y/N	Future Effective Date	Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
POC	BAAQMD Condition # 16780 Part 1 & Part 2	N		Emissions $\leq 5,068$ lbs/yr, or Usage ≤ 160 gal/yr Safety Kleen 105, and ≤ 60 gal/yr SystemOne Ashland Solvent, and ≤ 500 gal/yr NUMMI Solvent IV	BAAQMD Condition # 16780 Part 3	P/M	Records

VII. Applicable Limits and Compliance Monitoring Requirements

Table VII - W
Applicable Limits and Compliance Monitoring Requirements
S826 – PASSENGER BAYCO PARTS CLEANING OVEN

Type of Limit	Citation of Limit	FE Y/N	Future Effective Date	Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
Opacity	BAAQMD 6-301	Y		Ringelmann No. 1		N	
FP	BAAQMD 6-310	Y		0.15 grains/dscf		N	
FP	BAAQMD 6-311	Y		4.10P0.67 lb/hr, where P is process weight, ton/hr		N	
SO2	BAAQMD 9-1-301	Y		GLC ¹ of 0.5 ppm for 3 min or 0.25 ppm for 60 min or 0.05 ppm for 24 hours		N	
	BAAQMD 9-1-302	Y		SO2 shall not exceed 300 ppm (dry)		N	

Table VI – X
Applicable Limits and Compliance Monitoring Requirements
S900 – LIME SLURRY TANK

Type of Limit	Citation of Limit	FE Y/N	Future Effective Date	Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
Opacity	BAAQMD 6-301	Y		Ringelmann 1 for < 3 minutes in any hour	BAAQMD Condition # 4159 Part 3	P/W	Pressure Drop
FP	BAAQMD 6-310	Y		0.15 gr/dscf	BAAQMD Condition # 4159 Part 3	P/W	Pressure Drop
FP	BAAQMD 6-311	Y		4.10P0.67 lb/hr, where P is process weight, ton/hr	BAAQMD Condition # 4159 Part 3	P/W	Pressure Drop

VII. Applicable Limits and Compliance Monitoring Requirements

Table VII - Y
Applicable Limits and Compliance Monitoring Requirements
S960 – PLASTIC PLANT BOOTH AND GENERAL CLEANING S961 – BUMPER RELEASE
CLEANING & POLISH

S964 – COLD CLEANER, S1072 – GENERAL CLEANING & PAINT CLEANING
S1509 – PROTECTOSEAL CLEANING TANK

Type of Limit	Citation of Limit	FE Y/N	Future Effective Date	Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
POC	BAAQMD Condition # 10320 Part 31	Y		Emissions \leq 134.59 TPY	BAAQMD Condition # 10320 Part 34	P/M	Records
	BAAQMD Condition # 10320 Part 32	Y		Cleanup Solvent Collected/Recovered \geq 77%, or compliance with Condition # 10320 Part 31	BAAQMD Condition # 10320 Part 34	P/M	Records

Table VII - Z
Applicable Limits and Compliance Monitoring Requirements
S965 – PLASTIC PLANT THINNER STORAGE TANK
S992 – PLASTIC PLANT THINNER STORAGE TANK

Type of Limit	Citation of Limit	FE Y/N	Future Effective Date	Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
VOC	None	Y		None	Regulation 8-5-501	P/E	Records

VII. Applicable Limits and Compliance Monitoring Requirements

Table VII - AB
Applicable Limits and Compliance Monitoring Requirements
S1001 – TRUCK ED BATH

Type of Limit	Citation of Limit	FE Y/N	Future Effective Date	Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
VOC	BAAQMD Regulation 8-13-306	Y		Electrophoretic Primer VOC ≤ 145 g/l (1.2 lb/gal)	8-13-503	P/M	Records
	40 CFR 60 Subpart MM Section 60.392 (a)(1)	Y		Prime Coat Operation VOC ≤ 0.17 kg/l of applied coating solids, when Solids Turnover Ratio (R_T) ≥ 0.16	40 CFR 60 Subpart MM Section 60.393	P/M	Records
	40 CFR 60 Subpart MM Section 60.392 (a)(2)	Y		Prime Coat Operation VOC $\leq 0.17 \times 350^{(0.16-R_T)}$ kg/l of applied coating solids, when Solids Turnover Ratio (R_T) ≥ 0.04 and ≤ 0.16	40 CFR 60 Subpart MM Section 60.393	P/M	Records
	40 CFR 60 Subpart MM Section 60.392 (a)(3)	Y		Prime Coat Operation VOC ≤ 0.17 kg/l of applied coating solids, when Solids Turnover Ratio (R_T) ≤ 0.04	40 CFR 60 Subpart MM Section 60.393	P/M	Records
	BAAQMD Condition # 9156 Part 5	Y		Truck Vehicle Line* Emissions from non-combustion operations ≤ 779.17 TPY	BAAQMD Condition # 9156 Part 4	P/M	Records
	BAAQMD Condition # 9257 Part 1	Y		Elpo Primer VOC ≤ 0.59 lb/gal	BAAQMD Regulation 8-13-503	P/M	Records
	BAAQMD Condition # 9257 Part 2	Y		Elpo Primer Usage $\leq 107,371$ gal/yr; $\leq 11,167$ gal/mon; or compliance with Condition # 9257 Part 5	BAAQMD Condition # 9257 Part 3	P/M	Records

VII. Applicable Limits and Compliance Monitoring Requirements

Table VII - AB
Applicable Limits and Compliance Monitoring Requirements
S1001 – TRUCK ED BATH

Type of Limit	Citation of Limit	FE Y/N	Future Effective Date	Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
	BAAQMD Condition # 9257 Part 5	Y		Emissions \leq 0.99 ton/mon; \leq 9.5 ton/yr	BAAQMD Condition # 9156 Part 3	P/M	Records
Opacity	BAAQMD 6-301	Y		Ringelmann 1 for < 3 minutes in any hour	None	N	None
FP	BAAQMD 6-310	Y		0.15 gr/dscf	None	N	None
FP	BAAQMD 6-311	Y		4.10P0.67 lb/hr, where P is process weight, ton/hr	None	N	None
Fuel Usage	BAAQMD Condition # 9156 Part 8	Y		Truck Vehicle Line* Natural Gas Usage \leq 8,600,000 therm/yr	BAAQMD Condition # 9156 Part 8	P/M	Records
Toxics	BAAQMD Condition # 9156 Part 6	N		(for Truck Vehicle Line*) Benzene < 157 lb/yr 1,4 Dioxane < 141.0 lb/yr Formaldehyde < 3342 lb/yr Methylene Chloride < 684.8 lb/yr Perchloroethylene < 1341.9 lb/yr Vinyl chloride < 2.8 lb/yr	BAAQMD Condition # 9156 Part 6	P/A	Records

Truck Vehicle Line* sources include all of the following:

S1001, Truck Ed Bath
 S1002, Truck Ed Oven
 S1003, Truck Ed Dry Sand Booth
 S1004, Truck Metal Repair Booth
 S1005, Truck PVC Undercoat Area
 S1006, Truck Anti Chip Booth
 S1007, Truck Sealer Oven
 S1008, Truck Prime Booth
 S1009, Truck Prime Oven
 S1010, Truck Off-Line Repair

S1011, Truck Dry Sand Booth
 S1012, Truck Touch Up Booth
 S1014, Truck Topcoat Booth I
 S1015, Truck Topcoat Oven
 S1017, Truck Touch UP Booth
 S1018, Truck Blackout Booth
 S1019, Truck Cavity Wax Booth
 S1020, OFF-Line Assembly Paint Hospital
 S1021, Truck Underbody, Engine & Exterior Wax Booth
 S1056 Truck ASH, Boiler #1
 S1057 Truck ASH, Boiler #2

Table VII - AC
Applicable Limits and Compliance Monitoring Requirements
S1002 – TRUCK ED OVEN

Type of Limit	Citation of Limit	FE Y/N	Future Effective Date	Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
VOC	BAAQMD Regulation 8-13-306	Y		Electrophoretic Primer VOC ≤ 145 g/l (1.2 lb/gal)	8-13-503	P/M	Records
	40 CFR 60 Subpart MM Section 60.392 (a)(1)	Y		Prime Coat Operation VOC ≤ 0.17 kg/l of applied coating solids, when Solids Turnover Ratio (R_T) ≥ 0.16	40 CFR 60 Subpart MM Section 60.393	P/M	Records
	40 CFR 60 Subpart MM Section 60.392 (a)(2)	Y		Prime Coat Operation VOC $\leq 0.17 \times 350^{(0.16-R_T)}$ kg/l of applied coating solids, when Solids Turnover Ratio (R_T) ≥ 0.04 and ≤ 0.16	40 CFR 60 Subpart MM Section 60.393	P/M	Records
	40 CFR 60 Subpart MM Section 60.392 (a)(3)	Y		Prime Coat Operation VOC ≤ 0.17 kg/l of applied coating solids, when Solids Turnover Ratio (R_T) ≤ 0.04	40 CFR 60 Subpart MM Section 60.393	P/M	Records
	BAAQMD Condition # 9156 Part 5	Y		Truck Vehicle Line Emissions ≤ 779.17 TPY	BAAQMD Condition # 9156 Part 4	P/M	Records
	BAAQMD Condition # 9158 Part 2 a	Y		Temperature ≥ 1400 °F, or compliance with Condition # 9158 Parts 9 & 10	BAAQMD Condition # 9158 Part 3	P/C	Temperature

VII. Applicable Limits and Compliance Monitoring Requirements

Table VII - AC
Applicable Limits and Compliance Monitoring Requirements
S1002 – TRUCK ED OVEN

Type of Limit	Citation of Limit	FE Y/N	Future Effective Date	Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
	BAAQMD Condition # 9158 Part 2 b and c	Y		Destruction Efficiency \geq 98%, if VOC concentration \geq 1200 ppm as C1; or Destruction Efficiency $>$ 95-98%, if VOC concentration \geq 500 ppm and \leq 1200 ppm (linearly); or Total Non-methane Organic Hydrocarbon Outlet Concentration \leq 10 ppmv	BAAQMD Condition # 9158 Part 4	P/A	Source Test
	BAAQMD Condition # 9158 Part 8	Y		Emissions \leq 0.33 ton/mon; \leq 3.21 ton/yr	BAAQMD Condition # 9156 Part 4	P/M	Records
NOx	BAAQMD Condition # 9158 Part 7	Y		Emissions \leq 0.1 lb/MMBTU	BAAQMD Condition # 9158 Part 4a	P/A	Source Test
Opacity	BAAQMD 6-301	Y		Ringelmann 1 for $<$ 3 minutes in any hour		N	
FP	BAAQMD 6-310	Y		0.15 gr/dscf		N	
FP	BAAQMD 6-311	Y		4.10P0.67 lb/hr, where P is process weight, ton/hr		N	
Fuel Usage	BAAQMD Condition # 9156 Part 8	Y		Truck Vehicle Line* Natural Gas Usage \leq 8,600,000 therm/yr	BAAQMD Condition # 9156 Part 8	P/M	Records
Toxics	BAAQMD Condition # 9156 Part 6	N		(for Truck Vehicle Line*) Benzene $<$ 157 lb/yr 1,4 Dioxane $<$ 141.0 lb/yr Formaldehyde $<$ 3342 lb/yr Methylene Chloride $<$ 684.8 lb/yr Perchloroethylene $<$ 1341.9 lb/yr Vinyl chloride $<$ 2.8 lb/yr	BAAQMD Condition # 9156 Part 6	P/A	Records

Truck Vehicle Line* sources include all of the following:

- S1001, Truck Ed Bath
- S1002, Truck Ed Oven
- S1003, Truck Ed Dry Sand Booth
- S1004, Truck Metal Repair Booth
- S1005, Truck PVC Undercoat Area
- S1006, Truck Anti Chip Booth
- S1007, Truck Sealer Oven
- S1008, Truck Prime Booth
- S1009, Truck Prime Oven
- S1010, Truck Off-Line Repair

- S1011, Truck Dry Sand Booth
- S1012, Truck Touch Up Booth
- S1014, Truck Topcoat Booth I
- S1015, Truck Topcoat Oven
- S1017, Truck Touch UP Booth
- S1018, Truck Blackout Booth S1019, Truck Cavity Wax Booth
- S1020, OFF-Line Assembly Paint Hospital
- S1021, Truck Underbody, Engine & Exterior Wax Booth
- S1056 Truck ASH, Boiler #1
- S1057 Truck ASH, Boiler #2

Table VII - AD
Applicable Limits and Compliance Monitoring Requirements
S1003 – ED DRY SAND BOOTH
S1004 – METAL REPAIR BOOTH
S1011 – DRY SAND BOOTH

Type of Limit	Citation of Limit	FE Y/N	Future Effective Date	Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
VOC	BAAQMD Condition # 9156 Part 5	Y		Truck Vehicle Line Emissions ≤ 779.17 TPY	BAAQMD Condition # 9156 Part 4	P/M	Records
Fuel Usage	BAAQMD Condition # 9156 Part 8	Y		Truck Vehicle Line* Natural Gas Usage ≤ 8,600,000 therm/yr	BAAQMD Condition # 9156 Part 8	P/M	Records
Opacity	BAAQMD 6-301	Y		Ringelmann 1 for < 3 minutes in any hour	None	N	None
FP	BAAQMD 6-310	Y		0.15 gr/dscf	None	N	None
FP	BAAQMD 6-311	Y		4.10P0.67 lb/hr, where P is process weight, ton/hr	None	N	None
Toxics	BAAQMD Condition # 9156 Part 6	N		(for Truck Vehicle Line*) Benzene < 157 lb/yr 1,4 Dioxane < 141.0 lb/yr Formaldehyde < 3342 lb/yr Methylene Chloride < 684.8 lb/yr Perchloroethylene < 1341.9 lb/yr Vinyl chloride < 2.8 lb/yr	BAAQMD Condition # 9156 Part 6	P/A	Records

Truck Vehicle Line* sources include all of the following:

- S1001, Truck Ed Bath
- S1002, Truck Ed Oven

- S1003, Truck Ed Dry Sand Booth
- S1004, Truck Metal Repair Booth
- S1005, Truck PVC Undercoat Area

VII. Applicable Limits and Compliance Monitoring Requirements

S1006, Truck Anti Chip Booth
 S1007, Truck Sealer Oven
 S1008, Truck Prime Booth
 S1009, Truck Prime Oven
 S1010, Truck Off-Line Repair
 S1011, Truck Dry Sand Booth
 S1012, Truck Touch Up Booth
 S1014, Truck Topcoat Booth I

S1015, Truck Topcoat Oven
 S1017, Truck Touch UP Booth
 S1018, Truck Blackout Booth
 S1019, Truck Cavity Wax Booth
 S1020, OFF-Line Assembly Paint Hospital
 S1021, Truck Underbody, Engine & Exterior Wax Booth
 S1056 Truck ASH, Boiler #1
 S1057 Truck ASH, Boiler #2

Table VII - AE
Applicable Limits and Compliance Monitoring Requirements
S1005 – TRUCK PVC UNDERCOAT AREA

Type of Limit	Citation of Limit	FE Y/N	Future Effective Date	Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
VOC	BAAQMD Regulation 8-13-302.1	Y		Spray Primer VOC ≤ 1.8 kg/l (15.0 lb/gal) applied coating solids	8-13-503	P/M	Records
	40 CFR 60 Subpart MM Section 60.392 (a)(1)	Y		Prime Coat Operation VOC ≤ 0.17 kg/l of applied coating solids, when Solids Turnover Ratio (R_T) ≥ 0.16	40 CFR 60 Subpart MM Section 60.393	P/M	Records
	40 CFR 60 Subpart MM Section 60.392 (a)(2)	Y		Prime Coat Operation VOC $\leq 0.17 \times 350^{(0.16-R_T)}$ kg/l of applied coating solids, when Solids Turnover Ratio (R_T) ≥ 0.04 and ≤ 0.16	40 CFR 60 Subpart MM Section 60.393	P/M	Records
	40 CFR 60 Subpart MM Section 60.392 (a)(3)	Y		Prime Coat Operation VOC ≤ 0.17 kg/l of applied coating solids, when Solids Turnover Ratio (R_T) ≤ 0.04	40 CFR 60 Subpart MM Section 60.393	P/M	Records
	40 CFR 60 Subpart MM Section 60.392 (b)	Y		Guide Coat VOC ≤ 1.40 kg/l of applied coating solids	40 CFR 60 Subpart MM Section 60.393	P/M	Records

VII. Applicable Limits and Compliance Monitoring Requirements

Table VII - AE
Applicable Limits and Compliance Monitoring Requirements
S1005 – TRUCK PVC UNDERCOAT AREA

Type of Limit	Citation of Limit	FE Y/N	Future Effective Date	Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
	40 CFR 60 Subpart MM Section 60.392 (c)	Y		Topcoat Operation VOC \leq 1.47 kg/l of applied coating solids	40 CFR 60 Subpart MM Section 60.393	P/M	Records
VOC	BAAQMD Condition # 9156 Part 5	Y		Truck Vehicle Line Emissions \leq 779.17 TPY	BAAQMD Condition # 9156 Part 4	P/M	Records
	BAAQMD Condition # 9159 Part 1	Y		PVC Undercoat VOC \leq 0.6 lb/gal	8-13-503	P/M	Records
	BAAQMD Condition # 9159 Part 2	Y		PVC Undercoat Usage \leq 291,757 gal/yr; \leq 30,343 gal/mon; or compliance with Condition # 9159 Part 5	BAAQMD Condition # 9159 Part 3	P/M	Records
	BAAQMD Condition # 9159 Part 5	Y		Emissions \leq 2.73 ton/mon; \leq 26.3 ton/yr	BAAQMD Condition # 9156 Part 4	P/M	Records
Opacity	BAAQMD 6-301	Y		Ringelmann 1 for < 3 minutes in any hour	None	N	None
FP	BAAQMD 6-310	Y		0.15 gr/dscf	None	N	None
FP	BAAQMD 6-311	Y		4.10P0.67 lb/hr, where P is process weight, ton/hr	None	N	None
Fuel Usage	BAAQMD Condition # 9156 Part 8	Y		Truck Vehicle Line* Natural Gas Usage \leq 8,600,000 therm/yr	BAAQMD Condition # 9156 Part 8	P/M	Records

VII. Applicable Limits and Compliance Monitoring Requirements

Table VII - AE
Applicable Limits and Compliance Monitoring Requirements
S1005 – TRUCK PVC UNDERCOAT AREA

Type of Limit	Citation of Limit	FE Y/N	Future Effective Date	Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
NOx	BAAQMD Condition # 9159 Part 7	Y		Emissions \leq 0.1 lb/MMBTU		N	
PM ₁₀	BAAQMD Condition # 9159 Part 8	Y		Capture/Control Efficiency \leq 99%	None	N	None
Toxics	BAAQMD Condition # 9156 Part 6	N		(for Truck Vehicle Line*) Benzene < 157 lb/yr 1,4 Dioxane < 141.0 lb/yr Formaldehyde < 3342 lb/yr Methylene Chloride < 684.8 lb/yr Perchloroethylene < 1341.9 lb/yr Vinyl chloride < 2.8 lb/yr	BAAQMD Condition # 9156 Part 6	P/A	Records

Truck Vehicle Line* sources include all of the following:

S1001, Truck Ed Bath
 S1002, Truck Ed Oven
 S1003, Truck Ed Dry Sand Booth
 S1004, Truck Metal Repair Booth
 S1005, Truck PVC Undercoat Area
 S1006, Truck Anti Chip Booth
 S1007, Truck Sealer Oven
 S1008, Truck Prime Booth
 S1009, Truck Prime Oven
 S1010, Truck Off-Line Repair

S1011, Truck Dry Sand Booth
 S1012, Truck Touch Up Booth
 S1014, Truck Topcoat Booth I
 S1015, Truck Topcoat Oven
 S1017, Truck Touch UP Booth
 S1018, Truck Blackout Booth w/POS
 S1019, Truck Cavity Wax Booth
 S1020, OFF-Line Assembly Paint Hospital
 S1021, Truck Underbody, Engine & Exterior Wax Booth
 S1056 Truck ASH, Boiler #1
 S1057 Truck ASH, Boiler #2

VII. Applicable Limits and Compliance Monitoring Requirements

Table VII - AF
Applicable Limits and Compliance Monitoring Requirements
S1006 – TRUCK ANTICHIP BOOTH

Type of Limit	Citation of Limit	FE Y/N	Future Effective Date	Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
VOC	BAAQMD Regulation 8-13-302.1	Y		Spray Primer VOC ≤ 1.8 kg/l (15.0 lb/gal) applied coating solids	8-13-503	P/M	Records
VOC	40 CFR 60 Subpart MM Section 60.392 (a)(1)	Y		Prime Coat Operation VOC ≤ 0.17 kg/l of applied coating solids, when Solids Turnover Ratio (R_T) ≥ 0.16	40 CFR 60 Subpart MM Section 60.393	P/M	Records
	40 CFR 60 Subpart MM Section 60.392 (a)(2)	Y		Prime Coat Operation VOC $\leq 0.17 \times 350^{(0.16-R_T)}$ kg/l of applied coating solids, when Solids Turnover Ratio (R_T) ≥ 0.04 and ≤ 0.16	40 CFR 60 Subpart MM Section 60.393	P/M	Records
	40 CFR 60 Subpart MM Section 60.392 (a)(3)	Y		Prime Coat Operation VOC ≤ 0.17 kg/l of applied coating solids, when Solids Turnover Ratio (R_T) ≤ 0.04	40 CFR 60 Subpart MM Section 60.393	P/M	Records
	40 CFR 60 Subpart MM Section 60.392 (b)	Y		Guide Coat VOC ≤ 1.40 kg/l of applied coating solids	40 CFR 60 Subpart MM Section 60.393	P/M	Records
	40 CFR 60 Subpart MM Section 60.392 (c)	Y		Topcoat Operation VOC ≤ 1.47 kg/l of applied coating solids	40 CFR 60 Subpart MM Section 60.393	P/M	Records

VII. Applicable Limits and Compliance Monitoring Requirements

Table VII - AF
Applicable Limits and Compliance Monitoring Requirements
S1006 – TRUCK ANTICHIP BOOTH

Type of Limit	Citation of Limit	FE Y/N	Future Effective Date	Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
	BAAQMD Condition # 9156 Part 5	Y		Truck Vehicle Line Sources ≤ 779.17 TPY	BAAQMD Condition # 9156 Part 4	P/M	Records
	BAAQMD Condition # 9161 Part 1	Y		Anti-Chip I VOC ≤ 4.06 lb/gal; Anti-Chip II ≤ 1.42 lb/gal; Repair Primer VOC ≤ 4.63 lb/gal	BAAQMD Regulation 8-13-503	P/M	Records
	BAAQMD Condition # 9161 Part 2	Y		Anti-Chip I Usage ≤ 11,628 gal/yr, 1,209 gal/mon Anti-Chip II Usage ≤ 29,413 gal/yr, 3,059 gal/mon Repair Primer Usage ≤ 233 gal/yr, 24 gal/mon; or compliance with Condition # 9161 Part 5	BAAQMD Condition # 9161 Part 3	P/M	Records
	BAAQMD Condition # 9161 Part 5	Y		Emissions ≤ 3.20 ton/mon or ≤ 30.76 TPY	BAAQMD Condition # 9156 Part 4	P/M	Records
Fuel Usage	BAAQMD Condition # 9156 Part 8	Y		Truck Vehicle Line* Natural Gas Usage ≤ 8,600,000 therm/yr	BAAQMD Condition # 9156 Part 8	P/M	Records
PM10	BAAQMD Condition # 9161 Part 6	Y		Capture/Control Efficiency ≤ 98%	None	N	None
Opacity	BAAQMD 6-301	Y		Ringelmann 1 for < 3 minutes in any hour	None	N	None
FP	BAAQMD 6-310	Y		0.15 gr/dscf	None	N	None

VII. Applicable Limits and Compliance Monitoring Requirements

Table VII - AF
Applicable Limits and Compliance Monitoring Requirements
S1006 – TRUCK ANTICHIP BOOTH

Type of Limit	Citation of Limit	FE Y/N	Future Effective Date	Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
FP	BAAQMD 6-311	Y		4.10P0.67 lb/hr, where P is process weight, ton/hr	None	N	None
Toxics	BAAQMD Condition # 9156 Part 6	N		(for Truck Vehicle Line*) Benzene < 157 lb/yr 1,4 Dioxane < 141.0 lb/yr Formaldehyde < 3342 lb/yr Methylene Chloride < 684.8 lb/yr Perchloroethylene < 1341.9 lb/yr Vinyl chloride < 2.8 lb/yr	BAAQMD Condition # 9156 Part 6	P/A	Records

Truck Vehicle Line* sources include all of the following:

- S1001, Truck Ed Bath
- S1002, Truck Ed Oven
- S1003, Truck Ed Dry Sand Booth
- S1004, Truck Metal Repair Booth
- S1005, Truck PVC Undercoat Area
- S1006, Truck Anti Chip Booth
- S1007, Truck Sealer Oven
- S1008, Truck Prime Booth w/POS
- S1009, Truck Prime Oven
- S1010, Truck Off-Line Repair

- S1011, Truck Dry Sand Booth
- S1012, Truck Touch Up Booth
- S1014, Truck Topcoat Booth I
- S1015, Truck Topcoat Oven
- S1017, Truck Touch UP Booth
- S1018, Truck Blackout Booth
- S1019, Truck Cavity Wax Booth
- S1020, OFF-Line Assembly Paint Hospital
- S1021, Truck Underbody, Engine & Exterior Wax Booth
- S1056 Truck ASH, Boiler #1
- S1057 Truck ASH, Boiler #2

VII. Applicable Limits and Compliance Monitoring Requirements

Table VII - AG
Applicable Limits and Compliance Monitoring Requirements
S1007 – TRUCK SEALER OVEN

Type of Limit	Citation of Limit	FE Y/N	Future Effective Date	Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
VOC	BAAQMD Regulation 8-13-302.1	Y		Spray Primer VOC ≤ 1.8 kg/l (15.0 lb/gal) applied coating solids	8-13-503	P/M	Records
	40 CFR 60 Subpart MM Section 60.392 (a)(1)	Y		Prime Coat Operation VOC ≤ 0.17 kg/l of applied coating solids, when Solids Turnover Ratio (R_T) ≥ 0.16	40 CFR 60 Subpart MM Section 60.393	P/M	Records
	40 CFR 60 Subpart MM Section 60.392 (a)(2)	Y		Prime Coat Operation VOC $\leq 0.17 \times 350^{(0.16-R_T)}$ kg/l of applied coating solids, when Solids Turnover Ratio (R_T) ≥ 0.04 and ≤ 0.16	40 CFR 60 Subpart MM Section 60.393	P/M	Records
	40 CFR 60 Subpart MM Section 60.392 (a)(3)	Y		Prime Coat Operation VOC ≤ 0.17 kg/l of applied coating solids, when Solids Turnover Ratio (R_T) ≤ 0.04	40 CFR 60 Subpart MM Section 60.393	P/M	Records
	40 CFR 60 Subpart MM Section 60.392 (b)	Y		Guide Coat VOC ≤ 1.40 kg/l of applied coating solids	40 CFR 60 Subpart MM Section 60.393	P/M	Records
	40 CFR 60 Subpart MM Section 60.392 (c)	Y		Topcoat Operation VOC ≤ 1.47 kg/l of applied coating solids	40 CFR 60 Subpart MM Section 60.393	P/M	Records

VII. Applicable Limits and Compliance Monitoring Requirements

Table VII - AG
Applicable Limits and Compliance Monitoring Requirements
S1007 – TRUCK SEALER OVEN

Type of Limit	Citation of Limit	FE Y/N	Future Effective Date	Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
	BAAQMD Condition # 9156 Part 5	Y		Truck Vehicle Line Sources ≤ 779.17 TPY	BAAQMD Condition # 9156 Part 4	P/M	Records
	BAAQMD Condition # 9158 Part 2a	Y		Temperature > 1400 °F, or compliance with Condition # 9158 Part 9 & 10	BAAQMD Condition # 9158 Part 3	P/A	Temperature
	BAAQMD Condition # 9158 Part 2 b & c	Y		Destruction Efficiency ≥ 98%, if VOC concentration ≥ 1200 ppm as C1; or Destruction Efficiency > 95-98%, if VOC concentration ≥ 500 ppm and ≤ 1200 ppm (linearly); or Total Non-methane Organic Hydrocarbon Outlet Concentration ≤ 10 ppmv	BAAQMD Condition # 9158 Part 4	P/A	Source Test
	BAAQMD Condition # 9158 Part 8	Y		Emissions ≤ 1.31 ton/mon; ≤ 12.56 TPY	BAAQMD Condition # 9156 Part 4	P/M	Records
NOx	BAAQMD Condition # 9158 Part 7	Y		Emissions ≤ 0.1 lb/MMBTU	BAAQMD Condition # 9158 Part 4a	P/A	Source Test
Opacity	BAAQMD 6-301	Y		Ringelmann 1 for < 3 minutes in any hour		N	
FP	BAAQMD 6-310	Y		0.15 gr/dscf		N	
FP	BAAQMD 6-311	Y		4.10P0.67 lb/hr, where P is process weight, ton/hr		N	

VII. Applicable Limits and Compliance Monitoring Requirements

Table VII - AG
Applicable Limits and Compliance Monitoring Requirements
S1007 – TRUCK SEALER OVEN

Type of Limit	Citation of Limit	FE Y/N	Future Effective Date	Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
Fuel Usage	BAAQMD Condition # 9156 Part 8	Y		Truck Vehicle Line* Natural Gas Usage \leq 8,600,000 therm/yr	BAAQMD Condition # 9156 Part 8	P/M	Records
Toxics	BAAQMD Condition # 9156 Part 6	N		(for Truck Vehicle Line*) Benzene < 157 lb/yr 1,4 Dioxane < 141.0 lb/yr Formaldehyde < 3342 lb/yr Methylene Chloride < 684.8 lb/yr Perchloroethylene < 1341.9 lb/yr Vinyl chloride < 2.8 lb/yr	BAAQMD Condition # 9156 Part 6	P/A	Records

Truck Vehicle Line* sources include all of the following:

S1001, Truck Ed Bath
 S1002, Truck Ed Oven
 S1003, Truck Ed Dry Sand Booth
 S1004, Truck Metal Repair Booth
 S1005, Truck PVC Undercoat Area
 S1006, Truck Anti Chip Booth
 S1007, Truck Sealer Oven
 S1008, Truck Prime Booth
 S1009, Truck Prime Oven
 S1010, Truck Off-Line Repair

S1011, Truck Dry Sand Booth
 S1012, Truck Touch Up Booth
 S1014, Truck Topcoat Booth I
 S1015, Truck Topcoat Oven
 S1017, Truck Touch UP Booth
 S1018, Truck Blackout Booth
 S1019, Truck Cavity Wax Booth
 S1020, OFF-Line Assembly Paint Hospital
 S1021, Truck Underbody, Engine & Exterior Wax Booth
 S1056 Truck ASH, Boiler #1
 S1057 Truck ASH, Boiler #2

Table VII - AH
Applicable Limits and Compliance Monitoring Requirements
S1008 – TRUCK PRIME BOOTH

Type of Limit	Citation of Limit	FE Y/N	Future Effective Date	Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
VOC	BAAQMD Regulation 8-13-302.2	Y		Spray Primer VOC \leq 1.8 kg/l (15.0 lb/gal) applied coating solids	8-13-503	P/M	Records

VII. Applicable Limits and Compliance Monitoring Requirements

Table VII - AH
Applicable Limits and Compliance Monitoring Requirements
S1008 – TRUCK PRIME BOOTH

Type of Limit	Citation of Limit	FE Y/N	Future Effective Date	Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
VOC	40 CFR 60 Subpart MM Section 60.392 (a)(1)	Y		Prime Coat Operation VOC ≤ 0.17 kg/l of applied coating solids, when Solids Turnover Ratio (R_T) ≥ 0.16	40 CFR 60 Subpart MM Section 60.393	P/M	Records
	40 CFR 60 Subpart MM Section 60.392 (a)(2)	Y		Prime Coat Operation VOC $\leq 0.17 \times 350^{(0.16-R_T)}$ kg/l of applied coating solids, when Solids Turnover Ratio (R_T) ≥ 0.04 and ≤ 0.16	40 CFR 60 Subpart MM Section 60.393	P/M	Records
	40 CFR 60 Subpart MM Section 60.392 (a)(3)	Y		Prime Coat Operation VOC ≤ 0.17 kg/l of applied coating solids, when Solids Turnover Ratio (R_T) ≤ 0.04	40 CFR 60 Subpart MM Section 60.393	P/M	Records
	40 CFR 60 Subpart MM Section 60.392 (b)	Y		Guide Coat VOC ≤ 1.40 kg/l of applied coating solids	40 CFR 60 Subpart MM Section 60.393	P/M	Records
	40 CFR 60 Subpart MM Section 60.392 (c)	Y		Topcoat Operation VOC ≤ 1.47 kg/l of applied coating solids	40 CFR 60 Subpart MM Section 60.393	P/M	Records
	BAAQMD Condition # 9156 Part 5	Y		Truck Vehicle Line Emissions ≤ 779.17 TPY	BAAQMD Condition # 9156 Part 4	P/M	Records

VII. Applicable Limits and Compliance Monitoring Requirements

Table VII - AH
Applicable Limits and Compliance Monitoring Requirements
S1008 – TRUCK PRIME BOOTH

Type of Limit	Citation of Limit	FE Y/N	Future Effective Date	Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
VOC	BAAQMD Condition # 9163 Part 1	Y		Primer VOC \leq 4.08 lb/gal Int. Color VOC \leq 4.46 lb/gal Others-Repair \leq 4.63 lb/gal Soft-Chip \leq 7.09 lb/gal	8-13-503	P/M	Records
	BAAQMD Condition # 9163 Part 2	Y		Primer Usage \leq 62,129 gal/mon, 6,461 gal/mon Int. Color Usage \leq 26,973 gal/yr, 2,805 gal/mon Others-Repair Usage \leq 233 gal/yr, 24 gal/mon Soft-Chip Usage \leq 9,908 gal/yr, 1,030 gal/mon; or compliance with Condition # 9163 Part 5	BAAQMD Condition # 9163 Part 3	P/M	Records
	BAAQMD Condition # 9163 Part 5	Y		Emissions \leq 11.01 ton/mon; \leq 105.9 TPY	BAAQMD Condition # 9156 Part 4	P/M	Records
	BAAQMD Condition # 9163 Part 10a	Y		Temperature \geq 1400 °F, or compliance with Condition 9163 Part 17 and 18	BAAQMD Condition # 9163 Part 11	P/C	Temperature

VII. Applicable Limits and Compliance Monitoring Requirements

Table VII - AH
Applicable Limits and Compliance Monitoring Requirements
S1008 – TRUCK PRIME BOOTH

Type of Limit	Citation of Limit	FE Y/N	Future Effective Date	Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
	BAAQMD Condition # 9163 Part 10 b & c	Y		Destruction Efficiency of Thermal Oxidizers \geq 98.5%, if VOC concentration \geq 1200 ppm as C1; or Destruction Efficiency $>$ 95-98.5%, if VOC concentration \geq 500 ppm and \leq 1200 ppm (linearly); or Total Non-methane Organic Hydrocarbon Outlet Concentration \leq 10 ppmv	BAAQMD Condition # 9163 Part 14	P/A	Source Test
VOC	BAAQMD Condition # 9163 Part 12	Y		VOC Reduction Efficiency of Activated Carbon System (A10082) \geq 90% wt	BAAQMD Condition # 9163 Part 13	P/A	Source Test
Fuel Usage	BAAQMD Condition # 9156 Part 8	Y		Truck Vehicle Line* Natural Gas Usage \leq 8,600,000 therm/yr	BAAQMD Condition # 9156 Part 8	P/M	Records
PM10	BAAQMD Condition # 9163 Part 8	Y		Capture/Control Efficiency \leq 98%		N	None
Toxics	BAAQMD Condition # 9156 Part 6	N		(for Truck Vehicle Line*) Benzene $<$ 157 lb/yr 1,4 Dioxane $<$ 141.0 lb/yr Formaldehyde $<$ 3342 lb/yr Methylene Chloride $<$ 684.8 lb/yr Perchloroethylene $<$ 1341.9 lb/yr Vinyl chloride $<$ 2.8 lb/yr	BAAQMD Condition # 9156 Part 6	P/A	Records

Truck Vehicle Line* sources include all of the following:

S1001, Truck Ed Bath
 S1002, Truck Ed Oven
 S1003, Truck Ed Dry Sand Booth
 S1004, Truck Metal Repair Booth

S1005, Truck PVC Undercoat Area
 S1006, Truck Anti Chip Booth
 S1007, Truck Sealer Oven
 S1008, Truck Prime Booth
 S1009, Truck Prime Oven

VII. Applicable Limits and Compliance Monitoring Requirements

S1010, Truck Off-Line Repair
S1011, Truck Dry Sand Booth
S1012, Truck Touch Up Booth
S1014, Truck Topcoat Booth I
S1015, Truck Topcoat Oven
S1017, Truck Touch UP Booth

S1018, Truck Blackout Booth
S1019, Truck Cavity Wax Booth
S1020, OFF-Line Assembly Paint Hospital
S1021, Truck Underbody, Engine & Exterior Wax Booth
S1056 Truck ASH, Boiler #1
S1057 Truck ASH, Boiler #2

VII. Applicable Limits and Compliance Monitoring Requirements

Table VII – AI
Applicable Limits and Compliance Monitoring Requirements
S1009 – TRUCK PRIME OVEN

Type of Limit	Citation of Limit	FE Y/N	Future Effective Date	Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
VOC	BAAQMD Regulation 8-13-302.2	Y		Primer Surfacer VOC ≤ 1.8 kg/l (15.0 lb/gal) applied coating solids	8-13-503	P/M	Records
	40 CFR 60 Subpart MM Section 60.392 (a)(1)	Y		Prime Coat Operation VOC ≤ 0.17 kg/l of applied coating solids, when Solids Turnover Ratio (R_T) ≥ 0.16	40 CFR 60 Subpart MM Section 60.393	P/M	Records
	40 CFR 60 Subpart MM Section 60.392 (a)(2)	Y		Prime Coat Operation VOC $\leq 0.17 \times 350^{(0.16-R_T)}$ kg/l of applied coating solids, when Solids Turnover Ratio (R_T) ≥ 0.04 and ≤ 0.16	40 CFR 60 Subpart MM Section 60.393	P/M	Records
	40 CFR 60 Subpart MM Section 60.392 (a)(3)	Y		Prime Coat Operation VOC ≤ 0.17 kg/l of applied coating solids, when Solids Turnover Ratio (R_T) ≤ 0.04	40 CFR 60 Subpart MM Section 60.393	P/M	Records
	40 CFR 60 Subpart MM Section 60.392 (b)	Y		Guide Coat VOC ≤ 1.40 kg/l of applied coating solids	40 CFR 60 Subpart MM Section 60.393	P/M	Records
	40 CFR 60 Subpart MM Section 60.392 (c)	Y		Topcoat Operation VOC ≤ 1.47 kg/l of applied coating solids	40 CFR 60 Subpart MM Section 60.393	P/M	Records

VII. Applicable Limits and Compliance Monitoring Requirements

Table VII – AI
Applicable Limits and Compliance Monitoring Requirements
S1009 – TRUCK PRIME OVEN

Type of Limit	Citation of Limit	FE Y/N	Future Effective Date	Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
	BAAQMD Condition # 9156 Part 5	Y		Truck Vehicle Line Emissions \leq 779.17 TPY	BAAQMD Condition # 9156 Part 4	P/M	Records
	BAAQMD Condition # 9158 Part 2 a	Y		Temperature \geq 1400 °F, or compliance with Condition # 9158 Parts 9 & 10	BAAQMD Condition # 9158 Part 3	P/C	Temperature
	BAAQMD Condition # 9158 Part 2 b and c	Y		Destruction Efficiency \geq 98% wt, if inlet VOC \geq 1200 ppm as C1; or Destruction Efficiency \geq 95-98% wt, if inlet VOC \geq 500-1200 ppm as C1; or Total Non-methane Organic Hydrocarbon Outlet Concentration \leq 10 ppmv	BAAQMD Condition # 9158 Part 4	P/A	Source Test
	BAAQMD Condition # 9158 Part 8	Y		Emissions \leq 0.53 ton/mon; \leq 5.09 TPY	BAAQMD Condition # 9156 Part 4	P/M	Records
Opacity	BAAQMD 6-301	Y		Ringelmann 1 for < 3 minutes in any hour		N	
FP	BAAQMD 6-310	Y		0.15 gr/dscf		N	
FP	BAAQMD 6-311	Y		4.10P0.67 lb/hr, where P is process weight, ton/hr		N	
Fuel Usage	BAAQMD Condition # 9156 Part 8	Y		Truck Vehicle Line* Natural Gas Usage \leq 8,600,000 therm/yr	BAAQMD Condition # 9156 Part 8	P/M	Records
NOx	BAAQMD Condition # 9158 Part 7	Y		Emissions \leq 0.1 lb/MMBTU	BAAQMD Condition # 9158 Part 4a	P/A	Source Test

VII. Applicable Limits and Compliance Monitoring Requirements

Table VII – AI
Applicable Limits and Compliance Monitoring Requirements
S1009 – TRUCK PRIME OVEN

Type of Limit	Citation of Limit	FE Y/N	Future Effective Date	Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
Toxics	BAAQMD Condition # 9156 Part 6	N		(for Truck Vehicle Line*) Benzene < 157 lb/yr 1,4 Dioxane < 141.0 lb/yr Formaldehyde < 3342 lb/yr Methylene Chloride < 684.8 lb/yr Perchloroethylene < 1341.9 lb/yr Vinyl chloride < 2.8 lb/yr	BAAQMD Condition # 9156 Part 6	P/A	Records

Truck Vehicle Line* sources include all of the following:

- S1001, Truck Ed Bath
- S1002, Truck Ed Oven
- S1003, Truck Ed Dry Sand Booth
- S1004, Truck Metal Repair Booth
- S1005, Truck PVC Undercoat Area
- S1006, Truck Anti Chip Booth
- S1007, Truck Sealer Oven
- S1008, Truck Prime Booth
- S1009, Truck Prime Oven
- S1010, Truck Off-Line Repair
- S1011, Truck Dry Sand Booth

- S1012, Truck Touch Up Booth
- S1014, Truck Topcoat Booth I
- S1015, Truck Topcoat Oven
- S1017, Truck Touch UP Booth
- S1018, Truck Blackout Booth
- S1019, Truck Cavity Wax Booth
- S1020, OFF-Line Assembly Paint Hospital
- S1021, Truck Underbody, Engine & Exterior Wax Booth
- S1056 Truck ASH, Boiler #1
- S1057 Truck ASH, Boiler #2

VII. Applicable Limits and Compliance Monitoring Requirements

Table VII - AJ
Applicable Limits and Compliance Monitoring Requirements
S1010 – TRUCK OFF-LINE REPAIR
S1017 – TRUCK TOUCH UP BOOTH

Type of Limit	Citation of Limit	FE Y/N	Future Effective Date	Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
VOC	BAAQMD 8-13-302.1	Y		Spray Primer VOC \leq 1.80 kg/l (15.0 lb VOC/gal of applied solids)	BAAQMD 8-13-503	P/M	Records
VOC	BAAQMD 8-13-302.2	Y		Primer Surfacer VOC \leq 1.80 kg/l (15.0 lb VOC/gal of applied solids)	BAAQMD 8-13-503	P/M	Records
	BAAQMD 8-13-302.3	Y		Topcoat VOC \leq 1.80 kg/l (15.0 lb VOC/gal of applied solids)	BAAQMD 8-13-503	P/M	Records
	40 CFR 60 Subpart MM Section 60.392 (a)(1)	Y		Prime Coat Operation VOC \leq 0.17 kg/l of applied coating solids, when Solids Turnover Ratio (R_T) \geq 0.16	40 CFR 60 Subpart MM Section 60.393	P/M	Records
	40 CFR 60 Subpart MM Section 60.392 (a)(2)	Y		Prime Coat Operation VOC \leq 0.17 x 350 ($^{0.16-R_T}$) kg/l of applied coating solids, when Solids Turnover Ratio (R_T) \geq 0.04 and \leq 0.16	40 CFR 60 Subpart MM Section 60.393	P/M	Records
	40 CFR 60 Subpart MM Section 60.392 (a)(3)	Y		Prime Coat Operation VOC \leq 0.17 kg/l of applied coating solids, when Solids Turnover Ratio (R_T) \leq 0.04	40 CFR 60 Subpart MM Section 60.393	P/M	Records
	40 CFR 60 Subpart MM Section 60.392 (b)	Y		Guide Coat VOC \leq 1.40 kg/l of applied coating solids	40 CFR 60 Subpart MM Section 60.393	P/M	Records

VII. Applicable Limits and Compliance Monitoring Requirements

Table VII - AJ
Applicable Limits and Compliance Monitoring Requirements
S1010 – TRUCK OFF-LINE REPAIR
S1017 – TRUCK TOUCH UP BOOTH

Type of Limit	Citation of Limit	FE Y/N	Future Effective Date	Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
	40 CFR 60 Subpart MM Section 60.392 (c)	Y		Topcoat Operation VOC \leq 1.47 kg/l of applied coating solids	40 CFR 60 Subpart MM Section 60.393	P/M	Records
	BAAQMD Condition # 9156 Part 5	Y		Truck Vehicle Line Emissions \leq 779.17 TPY	BAAQMD Condition # 9156 Part 4	P/M	Records
	BAAQMD Condition # 10011 Part 1	Y		Repair Primer VOC \leq 4.63 lb/gal Solids (repair) VOC \leq 3.54 lb/gal Base Coat (repair) VOC \leq 4.79 lb/gal Clear Coat (repair) VOC \leq 4.12 lb/gal Solids (lacq. Repair) VOC \leq 6.32 lb/gal Base Coat (lacq. repair) VOC \leq 6.41 lb/gal Clear Coat (lacq. Repair) VOC \leq 6.30 lb/gal Adhesion Promoter VOC \leq 6.61 lb/gal Anti-Chip I VOC \leq 4.06 lb/gal Anti-Chip II VOC \leq 1.42 lb/gal	8-13-503	P/M	Records

VII. Applicable Limits and Compliance Monitoring Requirements

Table VII - AJ
Applicable Limits and Compliance Monitoring Requirements
S1010 – TRUCK OFF-LINE REPAIR
S1017 – TRUCK TOUCH UP BOOTH

Type of Limit	Citation of Limit	FE Y/N	Future Effective Date	Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
VOC	BAAQMD Condition # 10011 Part 2	Y		Repair Primer Usage ≤ 837 gal/yr, 87 gal/mon Solids (repair) Usage ≤ 606 gal/yr, 63 gal/mon Base Coat (repair) Usage ≤ 857 gal/yr, 89 gal/mon Clear Coat (repair) Usage ≤ 1,665 gal/yr, 173 gal/mon Solids (lacq. Repair) Usage ≤ 691 gal/yr, 72 gal/mon Base Coat (lacq. repair) Usage ≤ 963 gal/yr, 100 gal/mon Clear Coat (lacq. Repair) Usage ≤ 1,576 gal/yr, 164 gal/mon Adhesion Promoter Usage ≤ 1,238 gal/yr, 128 gal/mon Anti-Chip I Usage ≤ 38 gal/yr, 4 gal/mon Anti-Chip II Usage ≤ 10 gal/yr, 1 gal/mon; or compliance with Condition # 10011 Part 4	BAAQMD Condition # 10011 Part 3	P/M	Records
	BAAQMD Condition # 10011 Part 4	Y		Emissions ≤ 2.38 ton/mon; ≤ 22.91 TPY	BAAQMD Condition # 9156 Part 6	P/M	Records
Fuel Usage	BAAQMD Condition # 9156 Part 8	Y		Truck Vehicle Line* Natural Gas Usage ≤ 8,600,000 therm/yr	BAAQMD Condition # 9156 Part 8	P/M	Records
Opacity	BAAQMD 6-301	Y		Ringelmann 1 for < 3 minutes in any hour	None	N	None

VII. Applicable Limits and Compliance Monitoring Requirements

Table VII - AJ
Applicable Limits and Compliance Monitoring Requirements
S1010 – TRUCK OFF-LINE REPAIR
S1017 – TRUCK TOUCH UP BOOTH

Type of Limit	Citation of Limit	FE Y/N	Future Effective Date	Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
FP	BAAQMD 6-310	Y		0.15 gr/dscf	None	N	None
FP	BAAQMD 6-311	Y		4.10P0.67 lb/hr, where P is process weight, ton/hr	None	N	None
Toxics	BAAQMD Condition # 9156 Part 6	N		(for Truck Vehicle Line*) Benzene < 157 lb/yr 1,4 Dioxane < 141.0 lb/yr Formaldehyde < 3342 lb/yr Methylene Chloride < 684.8 lb/yr Perchloroethylene < 1341.9 lb/yr Vinyl chloride < 2.8 lb/yr	BAAQMD Condition # 9156 Part 6	P/A	Records

Truck Vehicle Line* sources include all of the following:

- S1001, Truck Ed Bath
- S1002, Truck Ed Oven
- S1003, Truck Ed Dry Sand Booth
- S1004, Truck Metal Repair Booth
- S1005, Truck PVC Undercoat Area
- S1006, Truck Anti Chip Booth
- S1007, Truck Sealer Oven
- S1008, Truck Prime Booth
- S1009, Truck Prime Oven
- S1010, Truck Off-Line Repair
- S1011, Truck Dry Sand Booth

- S1012, Truck Touch Up Booth
- S1014, Truck Topcoat Booth I
- S1015, Truck Topcoat Oven
- S1017, Truck Touch UP Booth
- S1018, Truck Blackout Booth w/POS
- S1019, Truck Cavity Wax Booth
- S1020, OFF-Line Assembly Paint Hospital
- S1021, Truck Underbody, Engine & Exterior Wax Booth
- S1056 Truck ASH, Boiler #1
- S1057 Truck ASH, Boiler #2

Table VII - AK
Applicable Limits and Compliance Monitoring Requirements
S1012 – TRUCK TOUCH UP BOOTH

Type of Limit	Citation of Limit	FE Y/N	Future Effective Date	Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
VOC	BAAQMD 8-13-302.2	Y		Topcoat VOC ≤ 1.80 kg/l (15.0 lb VOC/gal of applied solids)	BAAQMD 8-13-503	P/M	Records

VII. Applicable Limits and Compliance Monitoring Requirements

Table VII - AK
Applicable Limits and Compliance Monitoring Requirements
S1012 – TRUCK TOUCH UP BOOTH

Type of Limit	Citation of Limit	FE Y/N	Future Effective Date	Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
	40 CFR 60 Subpart MM Section 60.392 (a)(1)	Y		Prime Coat Operation VOC ≤ 0.17 kg/l of applied coating solids, when Solids Turnover Ratio (R_T) ≥ 0.16	40 CFR 60 Subpart MM Section 60.393	P/M	Records
	40 CFR 60 Subpart MM Section 60.392 (a)(2)	Y		Prime Coat Operation VOC $\leq 0.17 \times 350^{(0.16-R_T)}$ kg/l of applied coating solids, when Solids Turnover Ratio (R_T) ≥ 0.04 and ≤ 0.16	40 CFR 60 Subpart MM Section 60.393	P/M	Records
	40 CFR 60 Subpart MM Section 60.392 (a)(3)	Y		Prime Coat Operation VOC ≤ 0.17 kg/l of applied coating solids, when Solids Turnover Ratio (R_T) ≤ 0.04	40 CFR 60 Subpart MM Section 60.393	P/M	Records
	40 CFR 60 Subpart MM Section 60.392 (b)	Y		Guide Coat VOC ≤ 1.40 kg/l of applied coating solids	40 CFR 60 Subpart MM Section 60.393	P/M	Records
	40 CFR 60 Subpart MM Section 60.392 (c)	Y		Topcoat Operation VOC ≤ 1.47 kg/l of applied coating solids	40 CFR 60 Subpart MM Section 60.393	P/M	Records
VOC	BAAQMD Condition # 9156 Part 5	Y		Truck Vehicle Line Emissions ≤ 779.17 TPY	BAAQMD Condition # 9156 Part 4	P/M	Records

VII. Applicable Limits and Compliance Monitoring Requirements

Table VII - AK
Applicable Limits and Compliance Monitoring Requirements
S1012 – TRUCK TOUCH UP BOOTH

Type of Limit	Citation of Limit	FE Y/N	Future Effective Date	Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
	BAAQMD Condition # 9166 Part 1	Y		Coating < 417 gallons/yr; or compliance with Condition 9166, Part 2	BAAQMD Condition # 9166 Part 3	P/M	Records
Opacity	BAAQMD 6-301	Y		Ringelmann 1 for < 3 minutes in any hour	None	N	None
FP	BAAQMD 6-310	Y		0.15 gr/dscf	None	N	None
FP	BAAQMD 6-310	Y		4.10P0.67 lb/hr, where P is process weight, ton/hr	None	N	None
Fuel Usage	BAAQMD Condition # 9156 Part 8	Y		Natural Gas Usage ≤ 8,600,000 therm/yr	BAAQMD Condition # 9156 Part 8	P/M	Records
Toxics	BAAQMD Condition # 9156 Part 6	N		(for Truck Vehicle Line*) Benzene < 157 lb/yr 1,4 Dioxane < 141.0 lb/yr Formaldehyde < 3342 lb/yr Methylene Chloride < 684.8 lb/yr Perchloroethylene < 1341.9 lb/yr Vinyl chloride < 2.8 lb/yr	BAAQMD Condition # 9156 Part 6	P/A	Records

Truck Vehicle Line* sources include all of the following:

- S1001, Truck Ed Bath
- S1002, Truck Ed Oven
- S1003, Truck Ed Dry Sand Booth
- S1004, Truck Metal Repair Booth
- S1005, Truck PVC Undercoat Area
- S1006, Truck Anti Chip Booth S1007, Truck Sealer Oven
- S1008, Truck Prime Booth
- S1009, Truck PrimeOven
- S1010, Truck Off-Line Repair
- S1011, Truck Dry Sand Booth

- S1012, Truck Touch Up Booth
- S1014, Truck Topcoat Booth I
- S1015, Truck Topcoat Oven
- S1017, Truck Touch UP Booth
- S1018, Truck Blackout Booth
- S1019, Truck Cavity Wax Booth
- S1020, OFF-Line Assembly Paint Hospital
- S1021, Truck Underbody, Engine & Exterior Wax Booth
- S1056 Truck ASH, Boiler #1
- S1057 Truck ASH, Boiler #2

VII. Applicable Limits and Compliance Monitoring Requirements

Table VII - AL
Applicable Limits and Compliance Monitoring Requirements
S1014 – TRUCK TOPCOAT BOOTH

Type of Limit	Citation of Limit	FE Y/N	Future Effective Date	Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
	BAAQMD 8-13-302.2	Y		Primer Surfacer VOC \leq 1.80 kg/l (15.0 lb VOC/gal of applied solids)	BAAQMD 8-13-503	P/M	Records
	BAAQMD 8-13-302.3	Y		Topcoat VOC \leq 1.80 kg/l (15.0 lb VOC/gal of applied solids)	BAAQMD 8-13-503	P/M	Records
	40 CFR 60 Subpart MM Section 60.392 (a)(1)	Y		Prime Coat Operation VOC \leq 0.17 kg/l of applied coating solids, when Solids Turnover Ratio (R_T) \geq 0.16	40 CFR 60 Subpart MM Section 60.393	P/M	Records
	40 CFR 60 Subpart MM Section 60.392 (a)(2)	Y		Prime Coat Operation VOC \leq 0.17 x 350 ($^{0.16-R_T}$) kg/l of applied coating solids, when Solids Turnover Ratio (R_T) \geq 0.04 and \leq 0.16	40 CFR 60 Subpart MM Section 60.393	P/M	Records
	40 CFR 60 Subpart MM Section 60.392 (a)(3)	Y		Prime Coat Operation VOC \leq 0.17 kg/l of applied coating solids, when Solids Turnover Ratio (R_T) \leq 0.04	40 CFR 60 Subpart MM Section 60.393	P/M	Records
	40 CFR 60 Subpart MM Section 60.392 (b)	Y		Guide Coat VOC \leq 1.40 kg/l of applied coating solids	40 CFR 60 Subpart MM Section 60.393	P/M	Records

VII. Applicable Limits and Compliance Monitoring Requirements

Table VII - AL
Applicable Limits and Compliance Monitoring Requirements
S1014 – TRUCK TOPCOAT BOOTH

Type of Limit	Citation of Limit	FE Y/N	Future Effective Date	Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
	40 CFR 60 Subpart MM Section 60.392 (c)	Y		Topcoat Operation VOC \leq 1.47 kg/l of applied coating solids	40 CFR 60 Subpart MM Section 60.393	P/M	Records
	BAAQMD Condition # 9156 Part 5	Y		Truck Vehicle Line Emissions \leq 779.17 TPY	BAAQMD Condition # 9156 Part 4	P/M	Records
	BAAQMD Condition # 9164 Part 2a	Y		Temperature \geq 1400 °F; Or compliance with Condition # 9165 Parts 12 & 13	BAAQMD Condition # 9164 Part 3	P/C	Temperature
	BAAQMD Condition # 9164 Part 2 b & c	Y		Destruction Efficiency \geq 98% wt, if inlet VOC \geq 1200 ppm as C1; or Destruction Efficiency \geq 95-98% wt, if inlet VOC \geq 500-1200 ppm as C1; or Total Non-methane Organic Hydrocarbon Outlet Concentration \leq 10 ppmv	BAAQMD Condition # 9164 Part 5	P/A	Source Test
	BAAQMD Condition # 9164 Part 4	Y		VOC Reduction Efficiency of Activated Carbon System \geq 90% wt	BAAQMD Condition # 9164 Part 5	P/A	Source Test
	BAAQMD Condition # 9164 Part 15	Y		Solids VOC \leq 3.54 lb/gal Base Coat VOC \leq 4.79 lb/gal Clear Coat VOC \leq 4.12 lb/gal Other-Repair VOC \leq 4.63 lb/gal	BAAQMD 8-13-503	P/M	Records

VII. Applicable Limits and Compliance Monitoring Requirements

Table VII - AL
Applicable Limits and Compliance Monitoring Requirements
S1014 – TRUCK TOPCOAT BOOTH

Type of Limit	Citation of Limit	FE Y/N	Future Effective Date	Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
	BAAQMD Condition # 9164 Part 16	Y		Solids Usage \leq 26,927 gal/yr, 2,800 gal/mon; Base Coat Usage \leq 53,211 gal/yr, 5,534 gal/mon Clear Coat Usage \leq 70,094 gal/yr, 7,290 gal/mon Other-Repair Usage \leq 349 gal/yr, 36 gal/mon	BAAQMD Condition # 9164 Part 3	P/M	Records
	BAAQMD Condition # 9164 Part 19	Y		Emissions \leq 13.6 ton/mon; \leq 130.76 TPY	BAAQMD Condition # 9156 Part 4	P/M	Records
NOx	BAAQMD Condition # 9164 Part 9	Y		Emissions \leq 0.1 lb/MMBTU	BAAQMD Condition 9164 Part 5a	P/A	Source Test
PM10	BAAQMD Condition # 9164 Part 22	Y		Control Efficiency \geq 98% wt	None	None	None
Opacity	BAAQMD 6-301	Y		Ringelmann 1 for < 3 minutes in any hour			
FP	BAAQMD 6-310	Y		0.15 gr/dscf	None	N	None
FP	BAAQMD 6-310	Y		4.10P0.67 lb/hr, where P is process weight, ton/hr	None	N	None
Fuel Usage	BAAQMD Condition # 9156 Part 8	Y		Truck Vehicle Line* Natural Gas Usage \leq 8,600,000 therm/yr	BAAQMD Condition # 9156 Part 8	P/M	Records

VII. Applicable Limits and Compliance Monitoring Requirements

Table VII - AL
Applicable Limits and Compliance Monitoring Requirements
S1014 – TRUCK TOPCOAT BOOTH

Type of Limit	Citation of Limit	FE Y/N	Future Effective Date	Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
Toxics	BAAQMD Condition # 9156 Part 6	N		(for Truck Vehicle Line*) Benzene < 157 lb/yr 1,4 Dioxane < 141.0 lb/yr Formaldehyde < 3342 lb/yr Methylene Chloride < 684.8 lb/yr Perchloroethylene < 1341.9 lb/yr Vinyl chloride < 2.8 lb/yr	BAAQMD Condition # 9156 Part 6	P/A	Records

Truck Vehicle Line* sources include all of the following:

- S1001, Truck Ed Bath
- S1002, Truck Ed Oven
- S1003, Truck Ed Dry Sand Booth
- S1004, Truck Metal Repair Booth
- S1005, Truck PVC Undercoat Area
- S1006, Truck Anti Chip Booth
- S1007, Truck Sealer Oven
- S1008, Truck Prime Booth
- S1009, Truck PrimeOven
- S1010, Truck Off-Line Repair

- S1011, Truck Dry Sand Booth
- S1012, Truck Touch Up Booth
- S1014, Truck Topcoat Booth I
- S1015, Truck Topcoat Oven
- S1017, Truck Touch UP Booth
- S1018, Truck Blackout Booth
- S1019, Truck Cavity Wax Booth
- S1020, OFF-Line Assembly Paint Hospital
- S1021, Truck Underbody, Engine & Exterior Wax Booth
- S1056 Truck ASH, Boiler #1
- S1057 Truck ASH, Boiler #2

VII. Applicable Limits and Compliance Monitoring Requirements

Table VII – AM
Applicable Limits and Compliance Monitoring Requirements
S1015 – TRUCK TOPCOAT OVEN

Type of Limit	Citation of Limit	FE Y/N	Future Effective Date	Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
	BAAQMD 8-13-302.2	Y		Primer Surfacer VOC \leq 1.80 kg/l (15.0 lb VOC/gal of applied solids)	BAAQMD 8-13-503	P/M	Records
	BAAQMD 8-13-302.3	Y		Topcoat VOC \leq 1.80 kg/l (15.0 lb VOC/gal of applied solids)	BAAQMD 8-13-503	P/M	Records
	40 CFR 60 Subpart MM Section 60.392 (a)(1)	Y		Prime Coat Operation VOC \leq 0.17 kg/l of applied coating solids, when Solids Turnover Ratio (R_T) \geq 0.16	40 CFR 60 Subpart MM Section 60.393	P/M	Records
	40 CFR 60 Subpart MM Section 60.392 (a)(2)	Y		Prime Coat Operation VOC \leq 0.17 x 350 ($^{0.16-R_T}$) kg/l of applied coating solids, when Solids Turnover Ratio (R_T) \geq 0.04 and \leq 0.16	40 CFR 60 Subpart MM Section 60.393	P/M	Records
	40 CFR 60 Subpart MM Section 60.392 (a)(3)	Y		Prime Coat Operation VOC \leq 0.17 kg/l of applied coating solids, when Solids Turnover Ratio (R_T) \leq 0.04	40 CFR 60 Subpart MM Section 60.393	P/M	Records
	40 CFR 60 Subpart MM Section 60.392 (b)	Y		Guide Coat VOC \leq 1.40 kg/l of applied coating solids	40 CFR 60 Subpart MM Section 60.393	P/M	Records

VII. Applicable Limits and Compliance Monitoring Requirements

Table VII – AM
Applicable Limits and Compliance Monitoring Requirements
S1015 – TRUCK TOPCOAT OVEN

Type of Limit	Citation of Limit	FE Y/N	Future Effective Date	Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
	40 CFR 60 Subpart MM Section 60.392 (c)	Y		Topcoat Operation VOC \leq 1.47 kg/l of applied coating solids	40 CFR 60 Subpart MM Section 60.393	P/M	Records
	BAAQMD Condition # 9156 Part 5	Y		Truck Vehicle Line Emissions \leq 779.17 TPY	BAAQMD Condition # 9156 Part 4	P/M	Records
	BAAQMD Condition # 9158 Part 2a	Y		Temperature \geq 1400 °F, or compliance with Condition # 9158 Parts 9 & 10	BAAQMD Condition # 9158 Part 3	P/C	Temperature
	BAAQMD Condition # 9158 Part 2 b and c	Y		Destruction Efficiency \geq 98% wt, if inlet VOC \geq 1200 ppm as C1; or Destruction Efficiency \geq 95-98% wt, if inlet VOC \geq 500-1200 ppm as C1; or Total Non-methane Organic Hydrocarbon Outlet Concentration \leq 10 ppmv	BAAQMD Condition # 9158 Part 4	P/A	Source Test
	BAAQMD Condition # 9158 Part 8	Y		Emissions \leq 0.69 ton/mon; \leq 6.59 TPY	BAAQMD Condition # 9156 Part 4	P/M	Records
NOx	BAAQMD Condition # 9158 Part 7	Y		Emissions \leq 0.1 lb/MMBTU	BAAQMD Condition # 9158 Part 4a	P/A	Source Test
Fuel Usage	BAAQMD Condition # 9156 Part 8	Y		Truck Vehicle Line* Natural Gas Usage \leq 8,600,000 therm/yr	BAAQMD Condition # 9156 Part 8	P/M	Records

VII. Applicable Limits and Compliance Monitoring Requirements

Table VII – AM
Applicable Limits and Compliance Monitoring Requirements
S1015 – TRUCK TOPCOAT OVEN

Type of Limit	Citation of Limit	FE Y/N	Future Effective Date	Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
Opacity	BAAQMD 6-301	Y		Ringelmann 1 for < 3 minutes in any hour		N	
FP	BAAQMD 6-310	Y		0.15 gr/dscf		N	
FP	BAAQMD 6-311	Y		4.10P0.67 lb/hr, where P is process weight, ton/hr		N	
Toxics	BAAQMD Condition # 9156 Part 6	N		(for Truck Vehicle Line*) Benzene < 157 lb/yr 1,4 Dioxane < 141.0 lb/yr Formaldehyde < 3342 lb/yr Methylene Chloride < 684.8 lb/yr Perchloroethylene < 1341.9 lb/yr Vinyl chloride < 2.8 lb/yr	BAAQMD Condition # 9156 Part 6	P/A	Records

Truck Vehicle Line* sources include all of the following:

S1001, Truck Ed Bath
 S1002, Truck Ed Oven
 S1003, Truck Ed Dry Sand Booth
 S1004, Truck Metal Repair Booth
 S1005, Truck PVC Undercoat Area
 S1006, Truck Anti Chip Booth
 S1007, Truck Sealer Oven
 S1008, Truck Prime Booth
 S1009, Truck Prime Oven
 S1010, Truck Off-Line Repair

S1011, Truck Dry Sand Booth
 S1012, Truck Touch Up Booth
 S1014, Truck Topcoat Booth I
 S1015, Truck Topcoat Oven
 S1017, Truck Touch UP Booth
 S1018, Truck Blackout Booth
 S1019, Truck Cavity Wax Booth
 S1020, OFF-Line Assembly Paint Hospital
 S1021, Truck Underbody, Engine & Exterior Wax Booth
 S1056 Truck ASH, Boiler #1
 S1057 Truck ASH, Boiler #2

VII. Applicable Limits and Compliance Monitoring Requirements

Table VII – AN
Applicable Limits and Compliance Monitoring Requirements
S1018 – TRUCK BLACKOUT BOOTH

Type of Limit	Citation of Limit	FE Y/N	Future Effective Date	Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
VOC	BAAQMD 8-13-302.3	Y		Topcoat VOC ≤ 1.80 kg/l (15.0 lb VOC/gal of applied solids)	BAAQMD 8-13-503	P/M	Records
	40 CFR 60 Subpart MM Section 60.392 (a)(1)	Y		Prime Coat Operation VOC ≤ 0.17 kg/l of applied coating solids, when Solids Turnover Ratio (R_T) ≥ 0.16	40 CFR 60 Subpart MM Section 60.393	P/M	Records
	40 CFR 60 Subpart MM Section 60.392 (a)(2)	Y		Prime Coat Operation VOC $\leq 0.17 \times 350^{(0.16-R_T)}$ kg/l of applied coating solids, when Solids Turnover Ratio (R_T) ≥ 0.04 and ≤ 0.16	40 CFR 60 Subpart MM Section 60.393	P/M	Records
	40 CFR 60 Subpart MM Section 60.392 (a)(3)	Y		Prime Coat Operation VOC ≤ 0.17 kg/l of applied coating solids, when Solids Turnover Ratio (R_T) ≤ 0.04	40 CFR 60 Subpart MM Section 60.393	P/M	Records
	40 CFR 60 Subpart MM Section 60.392 (b)	Y		Guide Coat VOC ≤ 1.40 kg/l of applied coating solids	40 CFR 60 Subpart MM Section 60.393	P/M	Records
	40 CFR 60 Subpart MM Section 60.392 (c)	Y		Topcoat Operation VOC \leq 1.47 kg/l of applied coating solids	40 CFR 60 Subpart MM Section 60.393	P/M	Records

VII. Applicable Limits and Compliance Monitoring Requirements

Table VII – AN
Applicable Limits and Compliance Monitoring Requirements
S1018 – TRUCK BLACKOUT BOOTH

Type of Limit	Citation of Limit	FE Y/N	Future Effective Date	Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
VOC	BAAQMD Condition # 9156 Part 5	Y		Truck Vehicle Line Emissions \leq 779.17 TPY	BAAQMD Condition # 9156 Part 4	P/M	Records
	BAAQMD Condition # 9710 Part 1	Y		Blackout VOC \leq 2.95 lb/gal	BAAQMD 8-13-503	P/M	Records
	BAAQMD Condition # 9710 Part 2	Y		Blackout Usage \leq 12,317 gal/yr; 1,281 gal/mon	BAAQMD Condition # 9710 Part 3	P/M	Records
	BAAQMD Condition # 9710 Part 4	Y		Emissions \leq 1.89 ton/mon; \leq 18.17 TPY	BAAQMD Condition # 9156 Part 4	P/M	Records
Opacity	BAAQMD 6-301	Y		Ringelmann 1 for < 3 minutes in any hour	None	N	None
FP	BAAQMD 6-310	Y		0.15 gr/dscf	None	N	None
FP	BAAQMD 6-310	Y		4.10P0.67 lb/hr, where P is process weight, ton/hr	None	N	None
Fuel Usage	BAAQMD Condition # 9156 Part 8	Y		Truck Vehicle Line* Natural Gas Usage \leq 8,600,000 therm/yr	BAAQMD Condition # 9156 Part 8	P/M	Records
Toxics	BAAQMD Condition # 9156 Part 6	N		(for Truck Vehicle Line*) Benzene < 157 lb/yr 1,4 Dioxane < 141.0 lb/yr Formaldehyde < 3342 lb/yr Methylene Chloride < 684.8 lb/yr Perchloroethylene < 1341.9 lb/yr Vinyl chloride < 2.8 lb/yr	BAAQMD Condition # 9156 Part 6	P/A	Records

Truck Vehicle Line* sources include all of the following:

- S1001, Truck Ed Bath
- S1002, Truck Ed Oven
- S1003, Truck Ed Dry Sand Booth
- S1004, Truck Metal Repair Booth
- S1005, Truck PVC Undercoat Area
- S1006, Truck Anti Chip Booth
- S1007, Truck Sealer Oven
- S1008, Truck Prime Booth
- S1009, Truck PrimeOven
- S1010, Truck Off-Line Repair

- S1011, Truck Dry Sand Booth
- S1012, Truck Touch Up Booth
- S1014, Truck Topcoat Booth I
- S1015, Truck Topcoat Oven
- S1017, Truck Touch UP Booth
- S1018, Truck Blackout Booth
- S1019, Truck Cavity Wax Booth
- S1020, OFF-Line Assembly Paint Hospital
- S1021, Truck Underbody, Engine & Exterior Wax Booth
- S1056 Truck ASH, Boiler #1
- S1057 Truck ASH, Boiler #2

Table VII – AO
Applicable Limits and Compliance Monitoring Requirements
S1019 – TRUCK CAVITY WAX BOOTH

Type of Limit	Citation of Limit	FE Y/N	Future Effective Date	Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
VOC	BAAQMD 8-13-302.1	Y		Spray Primer VOC ≤ 1.80 kg/l (15.0 lb VOC/gal of applied solids)	BAAQMD 8-13-503	P/M	Records
	40 CFR 60 Subpart MM Section 60.392 (a)(1)	Y		Prime Coat Operation VOC ≤ 0.17 kg/l of applied coating solids, when Solids Turnover Ratio (R_T) ≥ 0.16	40 CFR 60 Subpart MM Section 60.393	P/M	Records
	40 CFR 60 Subpart MM Section 60.392 (a)(2)	Y		Prime Coat Operation VOC $\leq 0.17 \times 350^{(0.16-R_T)}$ kg/l of applied coating solids, when Solids Turnover Ratio (R_T) ≥ 0.04 and ≤ 0.16	40 CFR 60 Subpart MM Section 60.393	P/M	Records
	40 CFR 60 Subpart MM Section 60.392 (a)(3)	Y		Prime Coat Operation VOC ≤ 0.17 kg/l of applied coating solids, when Solids Turnover Ratio (R_T) ≤ 0.04	40 CFR 60 Subpart MM Section 60.393	P/M	Records
	40 CFR 60 Subpart MM Section 60.392 (b)	Y		Guide Coat VOC ≤ 1.40 kg/l of applied coating solids	40 CFR 60 Subpart MM Section 60.393	P/M	Records

VII. Applicable Limits and Compliance Monitoring Requirements

Table VII – AO
Applicable Limits and Compliance Monitoring Requirements
S1019 – TRUCK CAVITY WAX BOOTH

Type of Limit	Citation of Limit	FE Y/N	Future Effective Date	Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
	40 CFR 60 Subpart MM Section 60.392 (c)	Y		Topcoat Operation VOC \leq 1.47 kg/l of applied coating solids	40 CFR 60 Subpart MM Section 60.393	P/M	Records
	BAAQMD Condition # 9156 Part 5	Y		Truck Vehicle Line Emissions \leq 779.17 TPY	BAAQMD Condition # 9156 Part 4	P/M	Records
	BAAQMD Condition # 9171 Part 1	Y		Cavity Wax VOC \leq 0.73 lb/gal	BAAQMD 8-13-503	P/M	Records
	BAAQMD Condition # 9171 Part 2	Y		Cavity Wax Usage \leq 15,406 gal/yr; 1,602 gal/mon	BAAQMD Condition # 9711 Part 3	P/M	Records
	BAAQMD Condition # 9171 Part 5	Y		Emissions \leq 0.58 ton/mon; \leq 5.62 TPY	BAAQMD Condition # 9156 Part 4	P/M	Records
Opacity	BAAQMD 6-301	Y		Ringelmann 1 for < 3 minutes in any hour	None	N	None
FP	BAAQMD 6-310	Y		0.15 gr/dscf	None	N	None
FP	BAAQMD 6-311	Y		4.10P0.67 lb/hr, where P is process weight, ton/hr	None	N	None
Fuel Usage	BAAQMD Condition # 9156 Part 8	Y		Truck Vehicle Line* Natural Gas Usage \leq 8,600,000 therm/yr	BAAQMD Condition # 9156 Part 8	P/M	Records

VII. Applicable Limits and Compliance Monitoring Requirements

Table VII – AO
Applicable Limits and Compliance Monitoring Requirements
S1019 – TRUCK CAVITY WAX BOOTH

Type of Limit	Citation of Limit	FE Y/N	Future Effective Date	Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
Toxics	BAAQMD Condition # 9156 Part 6	N		(for Truck Vehicle Line*) Benzene < 157 lb/yr 1,4 Dioxane < 141.0 lb/yr Formaldehyde < 3342 lb/yr Methylene Chloride < 684.8 lb/yr Perchloroethylene < 1341.9 lb/yr Vinyl chloride < 2.8 lb/yr	BAAQMD Condition # 9156 Part 6	P/A	Records

Truck Vehicle Line* sources include all of the following:

- S1001, Truck Ed Bath
- S1002, Truck Ed Oven
- S1003, Truck Ed Dry Sand Booth
- S1004, Truck Metal Repair Booth
- S1005, Truck PVC Undercoat Area
- S1006, Truck Anti Chip Booth
- S1007, Truck Sealer Oven
- S1008, Truck Prime Booth
- S1009, Truck PrimeOven

- S1010, Truck Off-Line Repair
- S1011, Truck Dry Sand Booth
- S1012, Truck Touch Up Booth
- S1014, Truck Topcoat Booth I
- S1015, Truck Topcoat Oven
- S1017, Truck Touch UP Booth
- S1018, Truck Blackout Booth
- S1019, Truck Cavity Wax Booth
- S1020, OFF-Line Assembly Paint Hospital
- S1021, Truck Underbody, Engine & Exterior Wax Booth

VII. Applicable Limits and Compliance Monitoring Requirements

Table VII - AP
Applicable Limits and Compliance Monitoring Requirements
S1020 – OFF-LINE ASSEMBLY PAINT HOSPITAL

Type of Limit	Citation of Limit	FE Y/N	Future Effective Date	Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
	BAAQMD 8-13-302.3	Y		Topcoat VOC ≤ 1.80 kg/l (15.0 lb VOC/gal of applied solids)	BAAQMD 8-13-503	P/M	Records
	40 CFR 60 Subpart MM Section 60.392 (a)(1)	Y		Prime Coat Operation VOC ≤ 0.17 kg/l of applied coating solids, when Solids Turnover Ratio (R_T) ≥ 0.16	40 CFR 60 Subpart MM Section 60.393	P/M	Records
	40 CFR 60 Subpart MM Section 60.392 (a)(2)	Y		Prime Coat Operation VOC $\leq 0.17 \times 350^{(0.16-R_T)}$ kg/l of applied coating solids, when Solids Turnover Ratio (R_T) ≥ 0.04 and ≤ 0.16	40 CFR 60 Subpart MM Section 60.393	P/M	Records
	40 CFR 60 Subpart MM Section 60.392 (a)(3)	Y		Prime Coat Operation VOC ≤ 0.17 kg/l of applied coating solids, when Solids Turnover Ratio (R_T) ≤ 0.04	40 CFR 60 Subpart MM Section 60.393	P/M	Records
	40 CFR 60 Subpart MM Section 60.392 (b)	Y		Guide Coat VOC ≤ 1.40 kg/l of applied coating solids	40 CFR 60 Subpart MM Section 60.393	P/M	Records
	40 CFR 60 Subpart MM Section 60.392 (c)	Y		Topcoat Operation VOC ≤ 1.47 kg/l of applied coating solids	40 CFR 60 Subpart MM Section 60.393	P/M	Records

VII. Applicable Limits and Compliance Monitoring Requirements

Table VII - AP
Applicable Limits and Compliance Monitoring Requirements
S1020 – OFF-LINE ASSEMBLY PAINT HOSPITAL

Type of Limit	Citation of Limit	FE Y/N	Future Effective Date	Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
	BAAQMD Condition # 9156 Part 5	Y		Truck Vehicle Line Emissions \leq 779.17 TPY	BAAQMD Condition # 9156 Part 4	P/M	Records
	BAAQMD Condition # 9172 Part 1	Y		Solids VOC \leq 3.54 lb/gal Base Coat VOC \leq 4.79 lb/gal Clear Coat VOC \leq 4.12 lb/gal Lacquer VOC \leq 6.61 lb/gal	BAAQMD 8-13-503	P/M	Records
	BAAQMD Condition # 9172 Part 2	Y		Solids Usage \leq 629 gal/yr, 65 gal/mon Base Coat Usage \leq 893 gal/yr, 93 gal/mon Clear Coat Usage \leq 1,734 gal/yr, 180 gal/mon Lacquer Usage \leq 279 gal/yr, 29 gal/mon	BAAQMD Condition # 9172 Part 3	P/M	Records
	BAAQMD Condition # 9712 Part 4	Y		Emissions \leq 0.81 ton/mon; \leq 7.75 TPY	BAAQMD Condition # 9156 Part 4	P/M	Records
Opacity	BAAQMD 6-301	Y		Ringelmann 1 for < 3 minutes in any hour	None	N	None
FP	BAAQMD 6-310	Y		0.15 gr/dscf	None	N	None
FP	BAAQMD 6-311	Y		4.10P0.67 lb/hr, where P is process weight, ton/hr	None	N	None
Fuel Usage	BAAQMD Condition # 9156 Part 8	Y		Truck Vehicle Line* Natural Gas Usage \leq 8,600,000 therm/yr	BAAQMD Condition # 9156 Part 8	P/M	Records

VII. Applicable Limits and Compliance Monitoring Requirements

Table VII - AP
Applicable Limits and Compliance Monitoring Requirements
S1020 – OFF-LINE ASSEMBLY PAINT HOSPITAL

Type of Limit	Citation of Limit	FE Y/N	Future Effective Date	Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
Toxics	BAAQMD Condition # 9156 Part 6	N		(for Truck Vehicle Line*) Benzene < 157 lb/yr 1,4 Dioxane < 141.0 lb/yr Formaldehyde < 3342 lb/yr Methylene Chloride < 684.8 lb/yr Perchloroethylene < 1341.9 lb/yr Vinyl chloride < 2.8 lb/yr	BAAQMD Condition # 9156 Part 6	P/A	Records

Truck Vehicle Line* sources include all of the following:

S1001, Truck Ed Bath
 S1002, Truck Ed Oven
 S1003, Truck Ed Dry Sand Booth
 S1004, Truck Metal Repair Booth
 S1005, Truck PVC Undercoat Area
 S1006, Truck Anti Chip Booth
 S1007, Truck Sealer Oven
 S1008, Truck Prime Booth
 S1009, Truck Prime Oven
 S1010, Truck Off-Line Repair

S1011, Truck Dry Sand Booth
 S1012, Truck Touch Up Booth
 S1014, Truck Topcoat Booth I
 S1015, Truck Topcoat Oven
 S1017, Truck Touch UP Booth
 S1018, Truck Blackout Booth
 S1019, Truck Cavity Wax Booth
 S1020, OFF-Line Assembly Paint Hospital
 S1021, Truck Underbody, Engine & Exterior Wax Booth
 S1056 Truck ASH, Boiler #1
 S1057 Truck ASH, Boiler #2

Table VII - AQ
Applicable Limits and Compliance Monitoring Requirements
S1021 – TRUCK UNDERBODY, ENGINE & EXTERIOR WAX BOOTH

Type of Limit	Citation of Limit	FE Y/N	Future Effective Date	Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
VOC	BAAQMD 8-13-302.3	Y		Topcoat VOC \leq 1.80 kg/l (15.0 lb VOC/gal of applied solids)	BAAQMD 8-13-503	P/M	Records
VOC	40 CFR 60 Subpart MM Section 60.392 (a)(1)	Y		Prime Coat Operation VOC \leq 0.17 kg/l of applied coating solids, when Solids Turnover Ratio (R_T) \geq 0.16	40 CFR 60 Subpart MM Section 60.393	P/M	Records

VII. Applicable Limits and Compliance Monitoring Requirements

Table VII - AQ
Applicable Limits and Compliance Monitoring Requirements
S1021 – TRUCK UNDERBODY, ENGINE & EXTERIOR WAX BOOTH

Type of Limit	Citation of Limit	FE Y/N	Future Effective Date	Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
	40 CFR 60 Subpart MM Section 60.392 (a)(2)	Y		Prime Coat Operation VOC $\leq 0.17 \times 350^{(0.16-R_T)}$ kg/l of applied coating solids, when Solids Turnover Ratio $(R_T) \geq 0.04$ and ≤ 0.16	40 CFR 60 Subpart MM Section 60.393	P/M	Records
	40 CFR 60 Subpart MM Section 60.392 (a)(3)	Y		Prime Coat Operation VOC ≤ 0.17 kg/l of applied coating solids, when Solids Turnover Ratio $(R_T) \leq 0.04$	40 CFR 60 Subpart MM Section 60.393	P/M	Records
	40 CFR 60 Subpart MM Section 60.392 (b)	Y		Guide Coat VOC ≤ 1.40 kg/l of applied coating solids	40 CFR 60 Subpart MM Section 60.393	P/M	Records
	40 CFR 60 Subpart MM Section 60.392 (c)	Y		Topcoat Operation VOC ≤ 1.47 kg/l of applied coating solids	40 CFR 60 Subpart MM Section 60.393	P/M	Records
	BAAQMD Condition # 9156 Part 5	Y		Truck Vehicle Line Emissions ≤ 779.17 TPY	BAAQMD Condition # 9156 Part 4	P/M	Records

VII. Applicable Limits and Compliance Monitoring Requirements

Table VII - AQ
Applicable Limits and Compliance Monitoring Requirements
S1021 – TRUCK UNDERBODY, ENGINE & EXTERIOR WAX BOOTH

Type of Limit	Citation of Limit	FE Y/N	Future Effective Date	Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
	BAAQMD Condition # 7364 Part 1	Y		Underbody Wax VOC \leq 0.73 lb/gal Engine Wax VOC \leq 0.54 lb/gal Exterior Wax VOC \leq 1.50 lb/gal Hinge Wax VOC \leq 6.92 lb/gal	BAAQMD 8-13-503	P/M	Records
	BAAQMD Condition # 7364 Part 2	Y		Underbody Wax Usage \leq 31,772 gal/yr, 3,304 gal/mon; Engine Wax Usage \leq 1,954 gal/yr, 203 gal/mon; Exterior Wax Usage \leq 24,635 gal/yr, 2,562 gal/mon; Hinge Wax Usage \leq 2,566 gal/yr, 267 gal/mon; or compliance with Condition # 7364 Part 5	BAAQMD Condition # 7364 Part 3	P/M	Records
	BAAQMD Condition # 7364 Part 5	Y		Emissions \leq 2.46 ton/mon; \leq 23.69 TPY	BAAQMD Condition # 9156 Part 4	P/M	Records
Opacity	BAAQMD 6-301	Y		Ringelmann 1 for < 3 minutes in any hour	None	N	None
FP	BAAQMD 6-310	Y		0.15 gr/dscf	None	N	None
FP	BAAQMD 6-311	Y		4.10P0.67 lb/hr, where P is process weight, ton/hr	None	N	None

VII. Applicable Limits and Compliance Monitoring Requirements

Table VII - AQ
Applicable Limits and Compliance Monitoring Requirements
S1021 – TRUCK UNDERBODY, ENGINE & EXTERIOR WAX BOOTH

Type of Limit	Citation of Limit	FE Y/N	Future Effective Date	Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
Toxics	BAAQMD Condition # 9156 Part 6	N		(for Truck Vehicle Line*) Benzene < 157 lb/yr 1,4 Dioxane < 141.0 lb/yr Formaldehyde < 3342 lb/yr Methylene Chloride < 684.8 lb/yr Perchloroethylene < 1341.9 lb/yr Vinyl chloride < 2.8 lb/yr	BAAQMD Condition # 9156 Part 6	P/A	Records

Truck Vehicle Line* sources include all of the following:

S1001, Truck Ed Bath
 S1002, Truck Ed Oven
 S1003, Truck Ed Dry Sand Booth
 S1004, Truck Metal Repair Booth
 S1005, Truck PVC Undercoat Area
 S1006, Truck Anti Chip Booth
 S1007, Truck Sealer Oven
 S1008, Truck Prime Booth
 S1009, Truck Prime Oven
 S1010, Truck Off-Line Repair

S1011, Truck Dry Sand Booth
 S1012, Truck Touch Up Booth
 S1014, Truck Topcoat Booth I
 S1015, Truck Topcoat Oven
 S1017, Truck Touch UP Booth
 S1018, Truck Blackout Booth
 S1019, Truck Cavity Wax Booth
 S1020, OFF-Line Assembly Paint Hospital
 S1021, Truck Underbody, Engine & Exterior Wax Booth
 S1056 Truck ASH, Boiler #1
 S1057 Truck ASH, Boiler #2

Table VII - AR
Applicable Limits and Compliance Monitoring Requirements
S1050 – TRUCK FUEL TANK COATING BOOTH
S1051 – TRUCK FUEL TANK

Type of Limit	Citation of Limit	FE Y/N	Future Effective Date	Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
VOC	BAAQMD 8-13-308	Y		Off-Line VOC ≤ 340 g/l (2.8 lb/gal)	BAAQMD 8-13-503	P/M	Records
POC	BAAQMD Condition # 10578 Part 1	Y		Emissions ≤ 11.68 TPY	BAAQMD Condition # 10578 Part 4	P/M	Records

VII. Applicable Limits and Compliance Monitoring Requirements

Table VII - AR
Applicable Limits and Compliance Monitoring Requirements
S1050 – TRUCK FUEL TANK COATING BOOTH
S1051 – TRUCK FUEL TANK

Type of Limit	Citation of Limit	FE Y/N	Future Effective Date	Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
	BAAQMD Condition # 10578 Part 2	Y		Tank Body Coating Usage \leq 24,598 gal/yr, Fastener Coating Usage \leq 9,048 gal/yr; or compliance with Condition # 10578 Part 1	BAAQMD Condition # 10578 Part 4	P/M	Records
	BAAQMD Condition # 10578 Part 7	Y		Temperature \geq 1400 °F	BAAQMD Condition # 10578 Part 9	P/C	Temperature
	BAAQMD Condition # 10578 Part 8	Y		Destruction Efficiency \geq 98.5% wt, if inlet VOC \geq 500 ppm as C1; or Destruction Efficiency \geq 95% wt, if inlet VOC \leq 500 ppm as C1; or VOC Outlet Concentration \leq 10 ppmv	BAAQMD Condition # 10578 Part 10	P/A	Source Test
Fuel Usage	BAAQMD Condition # 10578 Part 18	Y		Natural Gas Usage \leq 130,000 therm/yr	BAAQMD Condition # 10578 Part 18	P/M	Records

VII. Applicable Limits and Compliance Monitoring Requirements

Table VII – AR1
Applicable Limits and Compliance Monitoring Requirements
S1050 – TRUCK FUEL TANK COATING BOOTH

Type of Limit	Citation of Limit	FE Y/N	Future Effective Date	Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
Opacity	BAAQMD 6-301	Y		Ringelmann 1 for < 3 minutes in any hour	None	N	None
FP	BAAQMD 6-310	Y		0.15 gr/dscf	None	N	None
FP	BAAQMD 6-311	Y		4.10P0.67 lb/hr, where P is process weight, ton/hr	None	N	None

VII. Applicable Limits and Compliance Monitoring Requirements

Table VII – AR2
Applicable Limits and Compliance Monitoring Requirements
S1051 – TRUCK FUEL TANK - HEATER BOX

Type of Limit	Citation of Limit	FE Y/N	Future Effective Date	Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
Opacity	BAAQMD 6-301	Y		Ringelmann 1 for < 3 minutes in any hour		N	
FP	BAAQMD 6-310	Y		0.15 gr/dscf		N	
FP	BAAQMD 6-311	Y		4.10P0.67 lb/hr, where P is process weight, ton/hr		N	

Table VII – AS
Applicable Limits and Compliance Monitoring Requirements
S1053 – TRUCK WAX DRY OFF BOOTH (ELECTRIC)

Type of Limit	Citation of Limit	FE Y/N	Future Effective Date	Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
VOC	BAAQMD 8-13-302.3	Y		Topcoat VOC ≤ 1.80 kg/l (15.0 lb VOC/gal of applied solids)	BAAQMD 8-13-503	P/M	Records
	40 CFR 60 Subpart MM Section 60.392 (a)(1)	Y		Prime Coat Operation VOC ≤ 0.17 kg/l of applied coating solids, when Solids Turnover Ratio (R_T) ≥ 0.16	40 CFR 60 Subpart MM Section 60.393	P/M	Records
	40 CFR 60 Subpart MM Section 60.392 (a)(2)	Y		Prime Coat Operation VOC $\leq 0.17 \times 350^{(0.16-R_T)}$ kg/l of applied coating solids, when Solids Turnover Ratio (R_T) ≥ 0.04 and ≤ 0.16	40 CFR 60 Subpart MM Section 60.393	P/M	Records

VII. Applicable Limits and Compliance Monitoring Requirements

Table VII – AS
Applicable Limits and Compliance Monitoring Requirements
S1053 – TRUCK WAX DRY OFF BOOTH (ELECTRIC)

Type of Limit	Citation of Limit	FE Y/N	Future Effective Date	Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
	40 CFR 60 Subpart MM Section 60.392 (a)(3)	Y		Prime Coat Operation VOC ≤ 0.17 kg/l of applied coating solids, when Solids Turnover Ratio (R_T) ≤ 0.04	40 CFR 60 Subpart MM Section 60.393	P/M	Records
	40 CFR 60 Subpart MM Section 60.392 (b)	Y		Guide Coat VOC ≤ 1.40 kg/l of applied coating solids	40 CFR 60 Subpart MM Section 60.393	P/M	Records
	40 CFR 60 Subpart MM Section 60.392 (c)	Y		Topcoat Operation VOC ≤ 1.47 kg/l of applied coating solids	40 CFR 60 Subpart MM Section 60.393	P/M	Records
	BAAQMD Condition # 9156 Part 5	Y		Truck Vehicle Line Emissions ≤ 779.17 TPY	BAAQMD Condition # 9156 Part 4	P/M	Records
	BAAQMD Condition # 9167 Part 1	Y		EMISSIONS < 1.64 ton/mon; ≤ 15.79 TPY	BAAQMD Condition # 9156 Part 4	P/M	Records
Opacity	BAAQMD 6-301	Y		Ringelmann 1 for < 3 minutes in any hour	None	N	None
FP	BAAQMD 6-310	Y		0.15 gr/dscf	None	N	None
FP	BAAQMD 6-311	Y		4.10P0.67 lb/hr, where P is process weight, ton/hr	None	N	None

VII. Applicable Limits and Compliance Monitoring Requirements

Table VII – AS
Applicable Limits and Compliance Monitoring Requirements
S1053 – TRUCK WAX DRY OFF BOOTH (ELECTRIC)

Type of Limit	Citation of Limit	FE Y/N	Future Effective Date	Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
Toxics	BAAQMD Condition # 9156 Part 6	N		(for Truck Vehicle Line*) Benzene < 157 lb/yr 1,4 Dioxane < 141.0 lb/yr Formaldehyde < 3342 lb/yr Methylene Chloride < 684.8 lb/yr Perchloroethylene < 1341.9 lb/yr Vinyl chloride < 2.8 lb/yr	BAAQMD Condition # 9156 Part 6	P/A	Records

Truck Vehicle Line* sources include all of the following:

S1001, Truck Ed Bath
 S1002, Truck Ed Oven
 S1003, Truck Ed Dry Sand Booth
 S1004, Truck Metal Repair Booth
 S1005, Truck PVC Undercoat Area
 S1006, Truck Anti Chip Booth
 S1007, Truck Sealer Oven
 S1008, Truck Prime Booth
 S1009, Truck Prime Oven
 S1010, Truck Off-Line Repair
 S1011, Truck Dry Sand Booth

S1012, Truck Touch Up Booth
 S1014, Truck Topcoat Booth I
 S1015, Truck Topcoat Oven
 S1017, Truck Touch UP Booth
 S1018, Truck Blackout Booth
 S1019, Truck Cavity Wax Booth
 S1020, OFF-Line Assembly Paint Hospital
 S1021, Truck Underbody, Engine & Exterior Wax Booth
 S1056 Truck ASH, Boiler #1
 S1057 Truck ASH, Boiler #2

VII. Applicable Limits and Compliance Monitoring Requirements

Table VI – AT
Applicable Limits and Compliance Monitoring Requirements
S1056 - TRUCK ASH, BOILER #1
S1057 – TRUCK ASH, BOILER #2

Type of Limit	Citation of Limit	FE Y/N	Future Effective Date	Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
Fuel Usage	BAAQMD Condition # 9156 Part 8	Y		Truck Vehicle Line* Natural Gas Usage ≤ 8,600,000 therm/yr	BAAQMD Condition # 9156 Part 8	P/M	Records
NOx	BAAQMD 9-7-301.1	Y		30 ppmv @3%O ₂ , dry, 1-hr average	BAAQMD Condition # 9174 Part 5	P/A	Annual source test
	BAAQMD Condition # 9174 Part 2	Y		30 ppmv @ 3%O ₂ , dry, 1-hr average	BAAQMD Condition # 9174 Part 5	P/A	Source Test
CO	BAAQMD 9-7-301.2	Y		400 ppmv @3%O ₂ , dry, 1-hr average	BAAQMD Condition # 9174 Part 5	P/A	Source Test
Opacity	BAAQMD 6-301	Y		Ringelmann 1 for < 3 minutes in any hour		N	
FP	BAAQMD 6-310	Y		0.15 gr/dscf		N	
FP	BAAQMD 6-311	Y		4.10P0.67 lb/hr, where P is process weight, ton/hr		N	
SO ₂	BAAQMD 9-1-301	Y		GLC ¹ of 0.5 ppm for 3 min or 0.25 ppm for 60 min or 0.05 ppm for 24 hours		N	
	BAAQMD 9-1-302	Y		SO ₂ shall not exceed 300 ppm (dry)		N	

¹ Ground Level Concentration

Truck Vehicle Line* sources include all of the following:

- S1001, Truck Ed Bath
- S1002, Truck Ed Oven
- S1003, Truck Ed Dry Sand Booth
- S1004, Truck Metal Repair Booth
- S1005, Truck PVC Undercoat Area
- S1006, Truck Anti Chip Booth
- S1007, Truck Sealer Oven
- S1008, Truck Prime Booth
- S1009, Truck PrimeOven

- S1010, Truck Off-Line Repair
- S1011, Truck Dry Sand Booth
- S1012, Truck Touch Up Booth
- S1014, Truck Topcoat Booth I
- S1015, Truck Topcoat Oven
- S1017, Truck Touch UP Booth
- S1018, Truck Blackout Booth
- S1019, Truck Cavity Wax Booth
- S1020, OFF-Line Assembly Paint Hospital

VII. Applicable Limits and Compliance Monitoring Requirements

S1021, Truck Underbody, Engine & Exterior Wax Booth
 S1056 Truck ASH, Boiler #1

S1057 Truck ASH, Boiler #2

Table VII - AU
Applicable Limits and Compliance Monitoring Requirements
S1061 – TRUCK AXLE BOOTH
S1062 – TRUCK AXLE OVEN

Type of Limit	Citation of Limit	FE Y/N	Future Effective Date	Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
VOC	BAAQMD 8-13-308	Y		Off-Line VOC ≤ 340 g/l (2.8 lb/gal)	BAAQMD 8-13-503	P/M	Records
	40 CFR 60 Subpart MM Section 60.392 (a)(1)	Y		Prime Coat Operation VOC ≤ 0.17 kg/l of applied coating solids, when Solids Turnover Ratio (R_T) ≥ 0.16	40 CFR 60 Subpart MM Section 60.393	P/M	Records
	40 CFR 60 Subpart MM Section 60.392 (a)(2)	Y		Prime Coat Operation VOC $\leq 0.17 \times 350^{(0.16-R_T)}$ kg/l of applied coating solids, when Solids Turnover Ratio (R_T) ≥ 0.04 and ≤ 0.16	40 CFR 60 Subpart MM Section 60.393	P/M	Records
	40 CFR 60 Subpart MM Section 60.392 (a)(3)	Y		Prime Coat Operation VOC ≤ 0.17 kg/l of applied coating solids, when Solids Turnover Ratio (R_T) ≤ 0.04	40 CFR 60 Subpart MM Section 60.393	P/M	Records
	40 CFR 60 Subpart MM Section 60.392 (b)	Y		Guide Coat VOC ≤ 1.40 kg/l of applied coating solids	40 CFR 60 Subpart MM Section 60.393	P/M	Records
	40 CFR 60 Subpart MM Section 60.392 (c)	Y		Topcoat Operation VOC \leq 1.47 kg/l of applied coating solids	40 CFR 60 Subpart MM Section 60.393	P/M	Records

VII. Applicable Limits and Compliance Monitoring Requirements

Table VII - AU
Applicable Limits and Compliance Monitoring Requirements
S1061 – TRUCK AXLE BOOTH
S1062 – TRUCK AXLE OVEN

Type of Limit	Citation of Limit	FE Y/N	Future Effective Date	Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
	BAAQMD Condition # 10484 Part 1	Y		Emissions \leq 12.22 TPY	BAAQMD Condition # 10484 Part 7	P/M	Records
	BAAQMD Condition # 10484 Part 2	Y		Off-Line Coating Usage \leq 11,108gal/yr, or compliance with Condition # 10484 Part 1	BAAQMD Condition # 10484 Part 7	P/M	Records
	BAAQMD Condition # 10484 Part 4	Y		Off-Line Coating VOC \leq 2.2 lb/gal	BAAQMD Condition # 10484 Part 7	P/M	Records
	BAAQMD Condition # 10484 Part 6	Y		VOC/axle \leq 0.087 lb/axle	BAAQMD Condition # 10484 Part 7	P/M	Records
NOx	BAAQMD Condition # 10481 Part 4	Y		Emissions \leq 6.06 TPY	BAAQMD Condition # 10481 Part 7	P/Q	Records
CO	BAAQMD Condition # 10481 Part 5	Y		Emissions \leq 2.52 TPY	BAAQMD Condition # 10481 Part 7	P/Q	Records
PM10	BAAQMD Condition # 10484 Part 8	Y		Control Efficiency \geq 90% wt	BAAQMD Condition # 10484 Part 8	P/E	Records of scrubber system downtime
Opacity	BAAQMD 6-301	Y		Ringelmann 1 for < 3 minutes in any hour	BAAQMD Condition # 10484 Part 8	P/E	Records of scrubber system downtime

VII. Applicable Limits and Compliance Monitoring Requirements

Table VII - AU
Applicable Limits and Compliance Monitoring Requirements
S1061 – TRUCK AXLE BOOTH
S1062 – TRUCK AXLE OVEN

Type of Limit	Citation of Limit	FE Y/N	Future Effective Date	Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
Fuel Usage	BAAQMD Condition # 10481 Part 2	Y		Natural Gas Usage \leq 1,200,000 therm/yr	BAAQMD Condition # 10481 Part 2	P/M	Records

Table VII – AV
Applicable Limits and Compliance Monitoring Requirements
S1063 – GENERAL TRUCK AXLE BOOTH AND AREA CLEANING
S1510– COLD CLEANER

Type of Limit	Citation of Limit	FE Y/N	Future Effective Date	Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
	BAAQMD Condition # 10481 Part 9	Y		POC \leq 22.32 TPY	BAAQMD Condition # 10481 Part 10	P/M	Records

VII. Applicable Limits and Compliance Monitoring Requirements

Table VII - AW
Applicable Limits and Compliance Monitoring Requirements
S1070 – INSTRUMENT PANEL BOOTH
S1071 – INSTRUMENT PANEL OVEN

Type of Limit	Citation of Limit	FE Y/N	Future Effective Date	Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
VOC	BAAQMD 8-13-308	Y		Off-Line VOC \leq 340 g/l (2.8 lb/gal)	BAAQMD 8-13-503	P/M	Records
	BAAQMD Condition # 10320 Part 41	Y		POC \leq 21.61 TPY	BAAQMD Condition # 10320 Part 14	P/M	Records
	BAAQMD Condition # 10320 Part 42	Y		Top Coat (Solventborne) \leq 37,071 gal/yr, Top Coat (Waterborne) \leq 16,279 gal/yr; or compliance with Condition # 10320 Part 41	BAAQMD Condition # 10320 Part 14	P/M	Records
	BAAQMD Condition # 10320 Part 19	Y		Temperature < 1400 °F, or compliance with Condition # 10320 Part 26 & 27	BAAQMD Condition # 10320 Part 22	P/C	Temperature
	BAAQMD Condition # 10320 Part 20	Y		Destruction Efficiency \geq 98.5% wt, if inlet VOC \geq 500 ppm as C1; or Destruction Efficiency \geq 95% wt, if inlet VOC \leq 500 ppm as C1; or VOC Outlet Concentration \leq 10 ppmv	BAAQMD Condition # 10320 Part 23	P/A	Source Test
NOx	BAAQMD Condition # 10320 Part 4			S57+S58+S59+S65+S1070 +S1071 Emissions \leq 26.16 TPY	BAAQMD Condition # 10320 Part 7	P/M	Records
CO	BAAQMD Condition # 10320 Part 5	Y		S57+S58+S59+S65+S1070 +S1071 Emissions \leq 46.48 TPY	BAAQMD Condition # 10320 Part 7	P/M	Records

VII. Applicable Limits and Compliance Monitoring Requirements

Table VII - AW
Applicable Limits and Compliance Monitoring Requirements
S1070 – INSTRUMENT PANEL BOOTH
S1071 – INSTRUMENT PANEL OVEN

Type of Limit	Citation of Limit	FE Y/N	Future Effective Date	Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
PM10	BAAQMD Condition # 10320 Part 44	Y		Control Efficiency \geq 90% wt	BAAQMD Condition # 10320 Part 44	P/E	Records of scrubber system downtime
Opacity	BAAQMD 6-301	Y		Ringelmann 1 for < 3 minutes in any hour	BAAQMD Condition # 10320 Part 44	P/E	Records of scrubber system downtime
FP	BAAQMD 6-310	Y		0.15 gr/dscf	BAAQMD Condition # 10320 Part 44	P/E	Records of scrubber system downtime
FP	BAAQMD 6-311	Y		4.10P0.67 lb/hr, where P is process weight, ton/hr	BAAQMD Condition # 10320 Part 44	P/E	Records of scrubber system downtime
Fuel Usage	BAAQMD Condition # 10320 Part 2	Y		S57+S58+S59+S65+S1070 +S1071 Natural Gas Usage \leq 3,160,000 therm/yr	BAAQMD Condition # 10320 Part 2	P/M	Records

VII. Applicable Limits and Compliance Monitoring Requirements

Table VII – AX
Applicable Limits and Compliance Monitoring Requirements
S1511 – TRUCK ELPO PIGMENT STORAGE TANK

Type of Limit	Citation of Limit	FE Y/N	Future Effective Date	Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
VOC	None	Y		None	Regulation 8-5-501	P/E	Records
	BAAQMD Condition # 13984 Part 1	Y		Throughput \leq 283,000 gal/yr	BAAQMD Condition # 13984 Part 3	P/M	Records

Table VII - AY
Applicable Limits and Compliance Monitoring Requirements
S1512 – TRUCK ELPO PIGMENT STORAGE TANK

Type of Limit	Emission Limit Citation	FE Y/N	Future Effective Date	Emission Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
VOC	None	Y		None	Regulation 8-5-501	P/E	Records
	BAAQMD Condition # 13985 Part 1	Y		Throughput \leq 27,900 gal/yr	BAAQMD Condition # 13985 Part 3	P/M	Records

VII. Applicable Limits and Compliance Monitoring Requirements

Table VII – AZ
Applicable Limits and Compliance Monitoring Requirements
S1803 – TRUCK SEALER DECK (FUGITIVE)

Type of Limit	Emission Limit Citation	FE Y/N	Future Effective Date	Emission Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
VOC	BAAQMD 8-13-302.1	Y		Spray Primer VOC ≤ 1.80 kg/l (15.0 lb VOC/gal of applied solids)	BAAQMD 8-13-503	P/M	Records
	40 CFR 60 Subpart MM Section 60.392 (a)(1)	Y		Prime Coat Operation VOC ≤ 0.17 kg/l of applied coating solids, when Solids Turnover Ratio (R_T) ≥ 0.16	40 CFR 60 Subpart MM Section 60.393	P/M	Records
	40 CFR 60 Subpart MM Section 60.392 (a)(2)	Y		Prime Coat Operation VOC $\leq 0.17 \times 350^{(0.16-R_T)}$ kg/l of applied coating solids, when Solids Turnover Ratio (R_T) ≥ 0.04 and ≤ 0.16	40 CFR 60 Subpart MM Section 60.393	P/M	Records
	40 CFR 60 Subpart MM Section 60.392 (a)(3)	Y		Prime Coat Operation VOC ≤ 0.17 kg/l of applied coating solids, when Solids Turnover Ratio (R_T) ≤ 0.04	40 CFR 60 Subpart MM Section 60.393	P/M	Records
	40 CFR 60 Subpart MM Section 60.392 (b)	Y		Guide Coat VOC ≤ 1.40 kg/l of applied coating solids	40 CFR 60 Subpart MM Section 60.393	P/M	Records
	40 CFR 60 Subpart MM Section 60.392 (c)	Y		Topcoat Operation VOC ≤ 1.47 kg/l of applied coating solids	40 CFR 60 Subpart MM Section 60.393	P/M	Records
	BAAQMD Condition # 9156 Part 5	Y		Truck Vehicle Line* Emissions ≤ 779.17 TPY	BAAQMD Condition # 9156 Part 4	P/M	Records

VII. Applicable Limits and Compliance Monitoring Requirements

Table VII – AZ
Applicable Limits and Compliance Monitoring Requirements
S1803 – TRUCK SEALER DECK (FUGITIVE)

Type of Limit	Emission Limit Citation	FE Y/N	Future Effective Date	Emission Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
	BAAQMD Condition # 9175 Part 1	Y		Bead Sealer VOC \leq 0.25 lb/gal	BAAQMD 8-13-503	P/M	Records
	BAAQMD Condition # 9175 Part 2	Y		Bead Sealer Usage \leq 110,236 gal/yr, 11,465 gal/mon, or compliance with Condition # 9175 Part 5	BAAQMD Condition # 9175 Part 3	P/M	Records
	BAAQMD Condition # 9175 Part 5	Y		Emissions \leq 0.29 ton/mon; \leq 2.76 TPY	BAAQMD Condition # 9156 Part 3	P/M	Records
Fuel Usage	BAAQMD Condition # 9156 Part 8	Y		Natural Gas Usage \leq 8,600,000 therm/yr	BAAQMD Condition # 9156 Part 8	P/M	Records
Toxics	BAAQMD Condition # 9156 Part 6	N		(for Truck Vehicle Line*) Benzene < 157 lb/yr 1,4 Dioxane < 141.0 lb/yr Formaldehyde < 3342 lb/yr Methylene Chloride < 684.8 lb/yr Perchloroethylene < 1341.9 lb/yr Vinyl chloride < 2.8 lb/yr	BAAQMD Condition # 9156 Part 6	P/A	Records

Truck Vehicle Line* sources include all of the following:

S1001, Truck Ed Bath
 S1002, Truck Ed Oven
 S1003, Truck Ed Dry Sand Booth
 S1004, Truck Metal Repair Booth
 S1005, Truck PVC Undercoat Area
 S1006, Truck Anti Chip Booth
 S1007, Truck Sealer Oven
 S1008, Truck Prime Booth S1009, Truck Prime Oven S1010,
 Truck Off-Line Repair
 S1011, Truck Dry Sand Booth

S1012, Truck Touch Up Booth
 S1014, Truck Topcoat Booth I
 S1015, Truck Topcoat Oven
 S1017, Truck Touch UP Booth
 S1018, Truck Blackout Booth
 S1019, Truck Cavity Wax Booth
 S1020, OFF-Line Assembly Paint Hospital
 S1021, Truck Underbody, Engine & Exterior Wax Booth
 S1056 Truck ASH, Boiler #1
 S1057 Truck ASH, Boiler #2

VII. Applicable Limits and Compliance Monitoring Requirements

Table VII - BA
Applicable Limits and Compliance Monitoring Requirements
S1809 – STAMPING BODY & ASSEMBLY

Type of Limit	Emission Limit Citation	FE Y/N	Future Effective Date	Emission Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
VOC	BAAQMD Regulation 8-51-301.3	Y		Automotive Glass Primer \leq 700 g/l; Other \leq 250 g/l	BAAQMD Regulation 8-51-501	P/M	Records
	BAAQMD Regulation 8-51-302	Y		Metal \leq 30 g/l; Porous Materials \leq 120 g/l; Wood \leq 120 g/l; Pre-formed Rubber Products \leq 250 g/l; All other substrates \leq 250 g/l	BAAQMD Regulation 8-51-501	P/M	Records
	BAAQMD Regulation 8-51-304	Y		Other Sealant \leq 420 g/l; Other Sealant Primer \leq 750 g/l	BAAQMD Regulation 8-51-501	P/M	Records
	BAAQMD Condition # 9156 Part 5	Y		Truck Vehicle Line Emissions \leq 779.17 TPY	BAAQMD Condition # 9156 Part 4	P/M	Records
	BAAQMD Condition # 7343 Part 1	Y		Sealant Usage \leq 17,875 gal/yr, 1,859 gal/mon; Adhesive Usage \leq 8,500 gal/yr, 884 gal/mon; Various Usage \leq 117,166 gal/yr, 12,185 gal/mon; or compliance with Condition # 7343 Part 3	BAAQMD Condition # 7343 Part 2	P/Q	Records
	BAAQMD Condition # 7343 Part 3	Y		Emissions \leq 74.66 TPY	BAAQMD Condition # 9156 Part 4	P/M	Records
Opacity	BAAQMD 6-301	Y		Ringelmann No. 1	None	N	None
FP	BAAQMD 6-310	Y		0.15 grains/dscf	None	N	None
FP	BAAQMD 6-311	Y		4.10P0.67 lb/hr, where P is process weight, ton/hr	None	N	None

VII. Applicable Limits and Compliance Monitoring Requirements

Table VII - BA
Applicable Limits and Compliance Monitoring Requirements
S1809 – STAMPING BODY & ASSEMBLY

Type of Limit	Emission Limit Citation	FE Y/N	Future Effective Date	Emission Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
Toxics	BAAQMD Condition # 9156 Part 6	N		(for Truck Vehicle Line*) Benzene < 157 lb/yr 1,4 Dioxane < 141.0 lb/yr Formaldehyde < 3342 lb/yr Methylene Chloride < 684.8 lb/yr Perchloroethylene < 1341.9 lb/yr Vinyl chloride < 2.8 lb/yr	BAAQMD Condition # 9156 Part 6	P/A	Records

Truck Vehicle Line* sources include all of the following:

S1001, Truck Ed Bath
 S1002, Truck Ed Oven
 S1003, Truck Ed Dry Sand Booth
 S1004, Truck Metal Repair Booth
 S1005, Truck PVC Undercoat Area
 S1006, Truck Anti Chip Booth
 S1007, Truck Sealer Oven
 S1008, Truck Prime Booth
 S1009, Truck Prime Oven
 S1010, Truck Off-Line Repair

S1011, Truck Dry Sand Booth
 S1012, Truck Touch Up Booth
 S1014, Truck Topcoat Booth I
 S1015, Truck Topcoat Oven
 S1017, Truck Touch UP Booth
 S1018, Truck Blackout Booth S1019, Truck Cavity Wax Booth
 S1020, OFF-Line Assembly Paint Hospital
 S1021, Truck Underbody, Engine & Exterior Wax Booth
 S1056 Truck ASH, Boiler #1
 S1057 Truck ASH, Boiler #2

VII. Applicable Limits and Compliance Monitoring Requirements

Table VII - BB
Applicable Limits and Compliance Monitoring Requirements
S1810 – CLEANING MATERIALS

Type of Limit	Emission Limit Citation	FE Y/N	Future Effective Date	Emission Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
	BAAQMD Condition # 9877 Part 1	Y		Wipe & Clean-up Usage < 17,616 gal/yr, 1,832 gal/mon; Cleaning Solvent Usage < 164,050 gal/yr, 17,061 gal/mon, or Compliance with Condition # 9877 Part 3	BAAQMD Condition # 9877 Part 2	P/M	Records
	BAAQMD Condition # 9877 Part 3	Y		Emissions ≤ 28.3 ton/month; 272 TPY	BAAQMD Condition # 9877 Part 4	P/M	Records
	BAAQMD Condition # 9877 Part 4	Y		Solvent Recovery ≥ 65%, or Compliance with Condition # 9877 Part 3	BAAQMD Condition # 9877 Part 4	P/M	Records
Toxics	BAAQMD Condition # 9156 Part 6	N		(for Truck Vehicle Line*) Benzene < 157 lb/yr 1,4 Dioxane < 141.0 lb/yr Formaldehyde < 3342 lb/yr Methylene Chloride < 684.8 lb/yr Perchloroethylene < 1341.9 lb/yr Vinyl chloride < 2.8 lb/yr	BAAQMD Condition # 9156 Part 6	P/A	Records

Truck Vehicle Line* sources include all of the following:

S1001, Truck Ed Bath
 S1002, Truck Ed Oven
 S1003, Truck Ed Dry Sand Booth
 S1004, Truck Metal Repair Booth
 S1005, Truck PVC Undercoat BoothArea
 S1006, Truck Anti Chip Booth
 S1007, Truck Sealer Oven
 S1008, Truck Prime Booth S1009, Truck Prime OvenS1010,
 Truck Off-Line Repair
 S1011, Truck Dry Sand Booth

S1012, Truck Touch Up Booth
 S1014, Truck Topcoat Booth I
 S1015, Truck Topcoat Oven
 S1017, Truck Touch UP Booth
 S1018, Truck Blackout Booth S1019, Truck Cavity Wax Booth
 S1020, OFF-Line Assembly Paint Hospital
 S1021, Truck Underbody, Engine & Exterior Wax Booth
 S1056 Truck ASH, Boiler #1
 S1057 Truck ASH, Boiler #2

VII. Applicable Limits and Compliance Monitoring Requirements

Table VII - BC
Applicable Limits and Compliance Monitoring Requirements
S1900 – PLASTIC PARTS ADHESION OPERATION

Type of Limit	Emission Limit Citation	FE Y/N	Future Effective Date	Emission Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
	BAAQMD Condition # 18533 Part 1	Y		Adhesive Usage < 13 gals/yr; or POC < 81 lbs/yr	BAAQMD Condition # 18533 Part 3	P/M	Records

Table VII - BD
Applicable Limits and Compliance Monitoring Requirements
S2826 – PLASTIC PLANT BAYCO PART CLEANING OVEN

Type of Limit	Emission Limit Citation	FE Y/N	Future Effective Date	Emission Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
Opacity	BAAQMD 6-301	Y		Ringelmann No. 1	BAAQMD Condition # 15149 Part 2	P/M	Visible Emissions check
FP	BAAQMD 6-310	Y		0.15 grains/dscf	BAAQMD Condition # 15149 Part 2	P/M	Visible Emissions check
FP	BAAQMD 6-311	Y		4.10P0.67 lb/hr, where P is process weight, ton/hr	BAAQMD Condition # 15149 Part 2	P/M	Visible Emissions check
SO2	BAAQMD 9-1-301	Y		GLC ¹ of 0.5 ppm for 3 min or 0.25 ppm for 60 min or 0.05 ppm for 24 hours		N	
	BAAQMD 9-1-302	Y		SO2 shall not exceed 300 ppm (dry)		N	

VII. Applicable Limits and Compliance Monitoring Requirements

Table VII - BE
Applicable Limits and Compliance Monitoring Requirements
S3007 – NPS DRY OFF OVEN

Type of Limit	Emission Limit Citation	FE Y/N	Future Effective Date	Emission Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
VOC	BAAQMD 8-13-306	Y		Electrophoretic Primer VOC ≤ 145 g/l (1.2 lb/gal)	BAAQMD 8-13-503	P/M	Records
	40 CFR 60 Subpart MM Section 60.392 (a)(1)	Y		Prime Coat Operation VOC ≤ 0.17 kg/l of applied coating solids, when Solids Turnover Ratio (R_T) ≥ 0.16	40 CFR 60 Subpart MM Section 60.393	P/M	Records
	40 CFR 60 Subpart MM Section 60.392 (a)(2)	Y		Prime Coat Operation VOC $\leq 0.17 \times 350^{(0.16-R_T)}$ kg/l of applied coating solids, when Solids Turnover Ratio (R_T) ≥ 0.04 and ≤ 0.16	40 CFR 60 Subpart MM Section 60.393	P/M	Records
	40 CFR 60 Subpart MM Section 60.392 (a)(3)	Y		Prime Coat Operation VOC ≤ 0.17 kg/l of applied coating solids, when Solids Turnover Ratio (R_T) ≤ 0.04	40 CFR 60 Subpart MM Section 60.393	P/M	Records
POC	BAAQMD Condition # 14205 Part 5	Y		North Passenger Paint Shop* Emissions ≤ 719.23 TPY	BAAQMD Condition # 14205 Part 11	P/M	Records
	BAAQMD Condition # 14205 Part 8	Y		North Passenger Paint Shop* Manual touch-up or repair operations Usage $\leq 6,906$ gal/yr or Emissions ≤ 19.91 TPY	BAAQMD Condition # 14205 Part 11	P/A	Records
NOx	BAAQMD Condition # 14205 Part 9	Y		S3007+S3008+S3009+S3014+S3015+S3016+S3017 Emissions ≤ 40.54 TPY	BAAQMD Condition # 14205 Part 12	P/Q	Records

VII. Applicable Limits and Compliance Monitoring Requirements

Table VII - BE
Applicable Limits and Compliance Monitoring Requirements
S3007 – NPS DRY OFF OVEN

Type of Limit	Emission Limit Citation	FE Y/N	Future Effective Date	Emission Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
CO	BAAQMD Condition # 14205 Part 10	Y		S3007+S3008+S3009+S3014+S3015+S3016+S3017 Emissions ≤ 50.46 TPY	BAAQMD Condition # 14205 Part 12	P/Q	Records
Opacity	BAAQMD 6-301	Y		Ringelmann No. 1		N	
FP	BAAQMD 6-310	Y		0.15 grains/dscf		N	
FP	BAAQMD 6-311	Y		4.10P0.67 lb/hr, where P is process weight, ton/hr		N	
Fuel Usage	BAAQMD Condition # 14205 Part 6	Y		S3007+S3008+S3009+S3014+S3015+S3016+S3017 Natural Gas Usage ≤ 9,630,000 therm/yr	BAAQMD Condition # 14205 Part 6	P/M	Records

North Passenger Paint Shop* sources include the following:
 S3007, NPS Dry Off Oven
 S3008, NPS Prime Booth,
 S3009, NPS Prime Oven,
 S3014, NPS Top Coat Booth #1,

S3015, NPS Topcoat Oven #1,
 S3016, NPS Topcoat Booth #2,
 S3017, NPS Topcoat Oven #2 Heater Boxes,

VII. Applicable Limits and Compliance Monitoring Requirements

Table VII - BF
Applicable Limits and Compliance Monitoring Requirements
S3008 – NPS PRIME BOOTH

Type of Limit	Emission Limit Citation	FE Y/N	Future Effective Date	Emission Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
VOC	BAAQMD 8-13-302.1	Y		Spray Primer VOC ≤ 1.80 kg/l (15.0 lb VOC/gal of applied solids)	BAAQMD 8-13-503	P/M	Records
	BAAQMD 8-13-302.2	Y		Primer Surfacer VOC ≤ 1.80 kg/l (15.0 lb VOC/gal of applied solids)	BAAQMD 8-13-503	P/M	Records
	40 CFR 60 Subpart MM Section 60.392 (a)(1)	Y		Prime Coat Operation VOC ≤ 0.17 kg/l of applied coating solids, when Solids Turnover Ratio (R_T) ≥ 0.16	40 CFR 60 Subpart MM Section 60.393	P/M	Records
	40 CFR 60 Subpart MM Section 60.392 (a)(2)	Y		Prime Coat Operation VOC $\leq 0.17 \times 350^{(0.16-R_T)}$ kg/l of applied coating solids, when Solids Turnover Ratio (R_T) ≥ 0.04 and ≤ 0.16	40 CFR 60 Subpart MM Section 60.393	P/M	Records
	40 CFR 60 Subpart MM Section 60.392 (a)(3)	Y		Prime Coat Operation VOC ≤ 0.17 kg/l of applied coating solids, when Solids Turnover Ratio (R_T) ≤ 0.04	40 CFR 60 Subpart MM Section 60.393	P/M	Records
POC	BAAQMD Condition # 14205 Part 5	Y		North Passenger Paint Shop* Emissions ≤ 719.23 TPY	BAAQMD Condition # 14205 Part 11	P/M	Records
	BAAQMD Condition # 14205 Part 8	Y		North Passenger Paint Shop* Manual touch-up or repair operations Usage $\leq 6,906$ gal/yr or Emissions ≤ 19.91 TPY	BAAQMD Condition # 14205 Part 11	P/A	Records

VII. Applicable Limits and Compliance Monitoring Requirements

Table VII - BF
Applicable Limits and Compliance Monitoring Requirements
S3008 – NPS PRIME BOOTH

Type of Limit	Emission Limit Citation	FE Y/N	Future Effective Date	Emission Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
	BAAQMD Condition # 14206 Part 1	Y		Emissions \leq 130.94 tons/yr; or 16.36 tons/mon, unless NUMMI notifies District	BAAQMD Condition # 14205 Part 11	P/M	Records
POC	BAAQMD Condition # 14206 Part 2	Y		Primer Usage \leq 60,869 gal/yr, 7,608 gal/mon; Interior Color Usage \leq 32,435 gal/yr, 4054 gal/mon; Black Out Usage \leq 8105 gal/yr, 1013 gal/mon; Soft-Chip Usage \leq 8225 gal/yr, 1028 gal/mon; or compliance with Part 1 of Condition # 14206	BAAQMD Condition # 14205 Part 11	P/M	Records
	BAAQMD Condition # 14206 Part 10	Y		Minimum Temperature $<$ 1400 °F, or compliance with Parts 2 and 3 of Condition # 14205	BAAQMD Condition 14206 Part 12	P/C	Temperature Monitor
	BAAQMD Condition # 14206 Part 11	Y		Destruction Efficiency \geq 98.5% wt, if inlet VOC \geq 500 ppm as C1; or Destruction Efficiency \geq 95% wt, if inlet VOC \leq 500 ppm as C1; or VOC Outlet Concentration \leq 10 ppmv	BAAQMD Condition # 14205 Part 13	P/A	Source Test
NOx	BAAQMD Condition # 14205 Part 9	Y		S3007+S3008+S3009+S3014+S3015+S3016+S3017 Emissions \leq 40.54 TPY	BAAQMD Condition # 14205 Part 12	P/Q	Records
CO	BAAQMD Condition # 14205 Part 10	Y		S3007+S3008+S3009+S3014+S3015+S3016+S3017 Emissions \leq 50.46 TPY	BAAQMD Condition # 14205 Part 12	P/Q	Records

VII. Applicable Limits and Compliance Monitoring Requirements

Table VII - BF
Applicable Limits and Compliance Monitoring Requirements
S3008 – NPS PRIME BOOTH

Type of Limit	Emission Limit Citation	FE Y/N	Future Effective Date	Emission Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
PM10	BAAQMD Condition # 14206 Part 7	Y		Control Efficiency \geq 98%	BAAQMD Condition # 14206 Part 7	P/E	Records of scrubber system downtime
Opacity	BAAQMD 6-301	Y		Ringelmann No. 1	BAAQMD Condition # 14206 Part 7	P/E	Records of scrubber system downtime
FP	BAAQMD 6-310	Y		0.15 grains/dscf	BAAQMD Condition # 14206 Part 7	P/E	Records of scrubber system downtime
FP	BAAQMD 6-311	Y		4.10P0.67 lb/hr, where P is process weight, ton/hr	BAAQMD Condition # 14206 Part 7	P/E	Records of scrubber system downtime
Fuel Usage	BAAQMD Condition # 14205 Part 6	Y		S3007+S3008+S3009+S3014+S3015+S3016+S3017 Natural Gas Usage \leq 9,630,000 therm/yr	BAAQMD Condition # 14205 Part 6	P/M	Records

North Passenger Paint Shop* sources include the following:
 S3007, NPS Dry Off Oven
 S3008, NPS Prime Booth,
 S3009, NPS Prime Oven,
 S3014, NPS Top Coat Booth #1,

S3015, NPS Topcoat Oven #1,
 S3016, NPS Topcoat Booth #2,
 S3017, NPS Topcoat Oven #2,
 & Blackout Booth

VII. Applicable Limits and Compliance Monitoring Requirements

Table VII - BG
Applicable Limits and Compliance Monitoring Requirements
S3009 – NPS PRIME OVEN

Type of Limit	Emission Limit Citation	FE Y/N	Future Effective Date	Emission Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
VOC	BAAQMD 8-13-302.1	Y		Spray Primer VOC ≤ 1.80 kg/l (15.0 lb VOC/gal of applied solids)	BAAQMD 8-13-503	P/M	Records
	BAAQMD 8-13-302.2	Y		Primer Surfacer VOC ≤ 1.80 kg/l (15.0 lb VOC/gal of applied solids)	BAAQMD 8-13-503	P/M	Records
	40 CFR 60 Subpart MM Section 60.392 (a)(1)	Y		Prime Coat Operation VOC ≤ 0.17 kg/l of applied coating solids, when Solids Turnover Ratio (R_T) ≥ 0.16	40 CFR 60 Subpart MM Section 60.393	P/M	Records
	40 CFR 60 Subpart MM Section 60.392 (a)(2)	Y		Prime Coat Operation VOC $\leq 0.17 \times 350^{(0.16-R_T)}$ kg/l of applied coating solids, when Solids Turnover Ratio (R_T) ≥ 0.04 and ≤ 0.16	40 CFR 60 Subpart MM Section 60.393	P/M	Records
	40 CFR 60 Subpart MM Section 60.392 (a)(3)	Y		Prime Coat Operation VOC ≤ 0.17 kg/l of applied coating solids, when Solids Turnover Ratio (R_T) ≤ 0.04	40 CFR 60 Subpart MM Section 60.393	P/M	Records
POC	BAAQMD Condition # 14205 Part 5	Y		North Passenger Paint Shop* Emissions ≤ 719.23 TPY	BAAQMD Condition # 14205 Part 11	P/M	Records
	BAAQMD Condition # 14205 Part 8	Y		North Passenger Paint Shop* Manual touch-up or repair operations Usage $\leq 6,906$ gal/yr or Emissions ≤ 19.91 TPY	BAAQMD Condition # 14205 Part 11	P/A	Records

VII. Applicable Limits and Compliance Monitoring Requirements

Table VII - BG
Applicable Limits and Compliance Monitoring Requirements
S3009 – NPS PRIME OVEN

Type of Limit	Emission Limit Citation	FE Y/N	Future Effective Date	Emission Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
	BAAQMD Condition # 14206 Part 1	Y		Emissions \leq 130.94 tons/yr; or 16.36 tons/mon, unless NUMMI notifies District	BAAQMD Condition # 14205 Part 11	P/M	Records
POC	BAAQMD Condition # 14206 Part 2	Y		Primer Usage \leq 60,869 gal/yr, 7,608 gal/mon; Interior Color Usage \leq 32,435 gal/yr, 4054 gal/mon; Black Out Usage \leq 8105 gal/yr, 1013 gal/mon; Soft-Chip Usage \leq 8225 gal/yr, 1028 gal/mon; or compliance with Part 1 of Condition # 14206	BAAQMD Condition # 14205 Part 11	P/M	Records
	BAAQMD Condition # 14206 Part 10	Y		Minimum Temperature < 1400 °F, or compliance with Parts 2 and 3 of Condition # 14205	BAAQMD Condition 14206 Part 12	P/C	Temperature Monitor
	BAAQMD Condition # 14206 Part 11	Y		Destruction Efficiency \geq 98.5% wt, if inlet VOC \geq 500 ppm as C1; or Destruction Efficiency \geq 95% wt, if inlet VOC \leq 500 ppm as C1; or VOC Outlet Concentration \leq 10 ppmv	BAAQMD Condition # 14205 Part 13	P/A	Source Test
NOx	BAAQMD Condition # 14205 Part 9	Y		S3007+S3008+S3009+S3014+S3015+S3016+S3017 Emissions \leq 40.54 TPY	BAAQMD Condition # 14205 Part 12	P/Q	Records
	BAAQMD Condition # 14206 Part 3	Y		Emissions \leq 0.1 lb/MMBTU	BAAQMD Condition # 14206 Part 17	P/A	Source Test

VII. Applicable Limits and Compliance Monitoring Requirements

Table VII - BG
Applicable Limits and Compliance Monitoring Requirements
S3009 – NPS PRIME OVEN

Type of Limit	Emission Limit Citation	FE Y/N	Future Effective Date	Emission Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
CO	BAAQMD Condition # 14205 Part 10	Y		S3007+S3008+S3009+S3014+S3015+S3016+S3017 Emissions ≤ 50.46 TPY	BAAQMD Condition # 14205 Part 12	P/Q	Records
PM10	BAAQMD Condition # 14206 Part 7	Y		Control Efficiency ≥ 98%	None	N	None
Opacity	BAAQMD 6-301	Y		Ringelmann No. 1	None	N	None
FP	BAAQMD 6-310	Y		0.15 grains/dscf	None	N	None
FP	BAAQMD 6-311	Y		4.10P0.67 lb/hr, where P is process weight, ton/hr	None	N	None
Fuel Usage	BAAQMD Condition # 14205 Part 6	Y		S3007+S3008+S3009+S3014+S3015+S3016+S3017 Natural Gas Usage ≤ 9,630,000 therm/yr	BAAQMD Condition # 14205 Part 6	P/M	Records

North Passenger Paint Shop* sources include the following:
 S3007, NPS Dry Off Oven
 S3008, NPS Prime Booth,
 S3009, NPS Prime Oven,

S3014, NPS Top Coat Booth #1,
 S3015, NPS Topcoat Oven #1,
 S3016, NPS Topcoat Booth #2 ,
 S3017, NPS Topcoat Oven #2 Heater Boxes,

Table VII - BH
Applicable Limits and Compliance Monitoring Requirements
S3014 – NPS TOPCOAT BOOTH # 1
S3016 – NPS TOPCOAT BOOTH # 2

Type of Limit	Emission Limit Citation	FE Y/N	Future Effective Date	Emission Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
VOC	BAAQMD 8-13-302.1	Y		Spray Primer VOC ≤ 1.80 kg/l (15.0 lb VOC/gal of applied solids)	BAAQMD 8-13-503	P/M	Records
	BAAQMD 8-13-302.2	Y		Primer Surfacer VOC ≤ 1.80 kg/l (15.0 lb VOC/gal of applied solids)	BAAQMD 8-13-503	P/M	Records

VII. Applicable Limits and Compliance Monitoring Requirements

Table VII - BH
Applicable Limits and Compliance Monitoring Requirements
S3014 – NPS TOPCOAT BOOTH # 1
S3016 – NPS TOPCOAT BOOTH # 2

Type of Limit	Emission Limit Citation	FE Y/N	Future Effective Date	Emission Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
	BAAQMD 8-13-302.3	Y		Topcoat VOC ≤ 1.80 kg/l (15.0 lb VOC/gal of applied solids)	BAAQMD 8-13-503	P/M	Records
	40 CFR 60 Subpart MM Section 60.392 (a)(1)	Y		Prime Coat Operation VOC ≤ 0.17 kg/l of applied coating solids, when Solids Turnover Ratio (R_T) ≥ 0.16	40 CFR 60 Subpart MM Section 60.393	P/M	Records
	40 CFR 60 Subpart MM Section 60.392 (a)(2)	Y		Prime Coat Operation VOC $\leq 0.17 \times 350^{(0.16-R_T)}$ kg/l of applied coating solids, when Solids Turnover Ratio (R_T) ≥ 0.04 and ≤ 0.16	40 CFR 60 Subpart MM Section 60.393	P/M	Records
	40 CFR 60 Subpart MM Section 60.392 (a)(3)	Y		Prime Coat Operation VOC ≤ 0.17 kg/l of applied coating solids, when Solids Turnover Ratio (R_T) ≤ 0.04	40 CFR 60 Subpart MM Section 60.393	P/M	Records
	40 CFR 60 Subpart MM Section 60.392 (b)	Y		Guide Coat VOC ≤ 1.40 kg/l of applied coating solids	40 CFR 60 Subpart MM Section 60.393	P/M	Records
VOC	40 CFR 60 Subpart MM Section 60.392 (c)	Y		Topcoat Operation VOC \leq 1.47 kg/l of applied coating solids	40 CFR 60 Subpart MM Section 60.393	P/M	Records
POC	BAAQMD Condition # 14205 Part 5	Y		North Passenger Paint Shop* Emissions ≤ 719.23 TPY	BAAQMD Condition # 14205 Part 11	P/M	Records
	BAAQMD Condition # 14205 Part 8	Y		North Passenger Paint Shop* Manual touch-up or repair operations Usage $\leq 6,906$ gal/yr or Emissions ≤ 19.91 TPY	BAAQMD Condition # 14205 Part 11	P/A	Records

VII. Applicable Limits and Compliance Monitoring Requirements

Table VII - BH
Applicable Limits and Compliance Monitoring Requirements
S3014 – NPS TOPCOAT BOOTH # 1
S3016 – NPS TOPCOAT BOOTH # 2

Type of Limit	Emission Limit Citation	FE Y/N	Future Effective Date	Emission Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
	BAAQMD Condition # 14207 Part 1	Y		POC \leq 250.5 TPY or 31.3 ton/mon, or compliance with Condition # 14205 Part 5	BAAQMD Condition # 14205 Part 11	P/M	Records
	BAAQMD Condition # 14207 Part 2	Y		Base Coat Usage \leq 123,552 gal/yr or 15,444 gal/mon; Clear Coat Usage \leq 91,289 gal/yr or 11,411 gal/mon; Non-Met High Solids Usage \leq 52,452 gal/yr or 6,557 gal/mon; or compliance with Condition # 14207 Part 1	BAAQMD Condition # 14205 Part 11	P/M	Records
	BAAQMD Condition # 14207 Part 10	Y		Minimum Temperature $<$ 1400 °F, or compliance with Parts 2 and 3 of Condition # 14205	BAAQMD Condition 14207 Part 12	P/C	Temperature Monitor
	BAAQMD Condition # 14207 Part 11	Y		Destruction Efficiency \geq 98.5% wt, if inlet VOC \geq 500 ppm as C1; or Destruction Efficiency \geq 95% wt, if inlet VOC \leq 500 ppm as C1; or VOC Outlet Concentration \leq 10 ppmv	BAAQMD Condition # 14207 Part 13	P/A	Source Test
NOx	BAAQMD Condition # 14205 Part 9	Y		S3007+S3008+S3009+S3014+S3015+S3016+S3017 Emissions \leq 40.54 TPY	BAAQMD Condition # 14205 Part 12	P/Q	Records
CO	BAAQMD Condition # 14205 Part 10	Y		S3007+S3008+S3009+S3014+S3015+S3016+S3017 Emissions \leq 50.46 TPY	BAAQMD Condition # 14205 Part 12	P/Q	Records

VII. Applicable Limits and Compliance Monitoring Requirements

Table VII - BH
Applicable Limits and Compliance Monitoring Requirements
S3014 – NPS TOPCOAT BOOTH # 1
S3016 – NPS TOPCOAT BOOTH # 2

Type of Limit	Emission Limit Citation	FE Y/N	Future Effective Date	Emission Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
PM10	BAAQMD Condition # 14207 Part 7	Y		Control Efficiency \geq 98%	None	N	None
Opacity	BAAQMD 6-301	Y		Ringelmann No. 1	None	N	None
FP	BAAQMD 6-310	Y		0.15 grains/dscf	None	N	None
FP	BAAQMD 6-311	Y		4.10P0.67 lb/hr, where P is process weight, ton/hr	None	N	None
Fuel Usage	BAAQMD Condition # 14205 Part 6	Y		S3007+S3008+S3009+S3014+S3015+S3016+S3017 Natural Gas Usage \leq 9,630,000 therm/yr	BAAQMD Condition # 14205 Part 6	P/M	Records

North Passenger Paint Shop* sources include the following:
 S3007, NPS Dry Off Oven
 S3008, NPS Prime Booth,
 S3009, NPS Prime Oven,

S3014, NPS Top Coat Booth #1,
 S3015, NPS Topcoat Oven #1,
 S3016, NPS Topcoat Booth #2,
 S3017, NPS Topcoat Oven #2 Heater Boxes,

Table VII - BI
Applicable Limits and Compliance Monitoring Requirements
S3015 – NPS TOPCOAT OVEN # 1
S3017 – NPS TOPCOAT OVEN # 2

Type of Limit	Emission Limit Citation	FE Y/N	Future Effective Date	Emission Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
VOC	BAAQMD 8-13-302.1	Y		Spray Primer VOC \leq 1.80 kg/l (15.0 lb VOC/gal of applied solids)	BAAQMD 8-13-503	P/M	Records
	BAAQMD 8-13-302.2	Y		Primer Surfacer VOC \leq 1.80 kg/l (15.0 lb VOC/gal of applied solids)	BAAQMD 8-13-503	P/M	Records

VII. Applicable Limits and Compliance Monitoring Requirements

Table VII - BI
Applicable Limits and Compliance Monitoring Requirements
S3015 – NPS TOPCOAT OVEN # 1
S3017 – NPS TOPCOAT OVEN # 2

Type of Limit	Emission Limit Citation	FE Y/N	Future Effective Date	Emission Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
	BAAQMD 8-13-302.3	Y		Topcoat VOC ≤ 1.80 kg/l (15.0 lb VOC/gal of applied solids)	BAAQMD 8-13-503	P/M	Records
	40 CFR 60 Subpart MM Section 60.392 (a)(1)	Y		Prime Coat Operation VOC ≤ 0.17 kg/l of applied coating solids, when Solids Turnover Ratio (R_T) ≥ 0.16	40 CFR 60 Subpart MM Section 60.393	P/M	Records
	40 CFR 60 Subpart MM Section 60.392 (a)(2)	Y		Prime Coat Operation VOC $\leq 0.17 \times 350^{(0.16-R_T)}$ kg/l of applied coating solids, when Solids Turnover Ratio (R_T) ≥ 0.04 and ≤ 0.16	40 CFR 60 Subpart MM Section 60.393	P/M	Records
	40 CFR 60 Subpart MM Section 60.392 (a)(3)	Y		Prime Coat Operation VOC ≤ 0.17 kg/l of applied coating solids, when Solids Turnover Ratio (R_T) ≤ 0.04	40 CFR 60 Subpart MM Section 60.393	P/M	Records
	40 CFR 60 Subpart MM Section 60.392 (b)	Y		Guide Coat VOC ≤ 1.40 kg/l of applied coating solids	40 CFR 60 Subpart MM Section 60.393	P/M	Records
VOC	40 CFR 60 Subpart MM Section 60.392 (c)	Y		Topcoat Operation VOC ≤ 1.47 kg/l of applied coating solids	40 CFR 60 Subpart MM Section 60.393	P/M	Records

VII. Applicable Limits and Compliance Monitoring Requirements

Table VII - BI
Applicable Limits and Compliance Monitoring Requirements
S3015 – NPS TOPCOAT OVEN # 1
S3017 – NPS TOPCOAT OVEN # 2

Type of Limit	Emission Limit Citation	FE Y/N	Future Effective Date	Emission Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
POC	BAAQMD Condition # 14205 Part 5	Y		North Passenger Paint Shop* Emissions \leq 719.23 TPY	BAAQMD Condition # 14205 Part 11	P/M	Records
	BAAQMD Condition # 14205 Part 8	Y		North Passenger Paint Shop* Manual touch-up or repair operations Usage \leq 6,906 gal/yr or Emissions \leq 19.91 TPY	BAAQMD Condition # 14205 Part 11	P/A	Records
	BAAQMD Condition # 14207 Part 1	Y		POC \leq 250.5 TPY or 31.3 ton/mon, or compliance with Condition # 14205 Part 5	BAAQMD Condition # 14205 Part 11	P/M	Records
	BAAQMD Condition # 14207 Part 2	Y		Base Coat Usage \leq 123,552 gal/yr or 15,444 gal/mon; Clear Coat Usage \leq 91,289 gal/yr or 11,411 gal/mon; Non-Met High Solids Usage \leq 52,452 gal/yr or 6,557 gal/mon; or compliance with Condition # 14207 Part 1	BAAQMD Condition # 14205 Part 11	P/M	Records
	BAAQMD Condition # 14207 Part 10	Y		Minimum Temperature \geq 1400 °F, or compliance with Parts 2 and 3 of Condition # 14205	BAAQMD Condition 14207 Part 12	P/C	Temperature Monitor

VII. Applicable Limits and Compliance Monitoring Requirements

Table VII - BI
Applicable Limits and Compliance Monitoring Requirements
S3015 – NPS TOPCOAT OVEN # 1
S3017 – NPS TOPCOAT OVEN # 2

Type of Limit	Emission Limit Citation	FE Y/N	Future Effective Date	Emission Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
	BAAQMD Condition # 14207 Part 11	Y		Destruction Efficiency \geq 98.5% wt, if inlet VOC \geq 500 ppm as C1; or Destruction Efficiency \geq 95% wt, if inlet VOC \leq 500 ppm as C1; or VOC Outlet Concentration \leq 10 ppmv	BAAQMD Condition # 14207 Part 13	P/A	Source Test
NOx	BAAQMD Condition # 14205 Part 9	Y		S3007+S3008+S3009+S3014+S3015+S3016+S3017 Emissions \leq 40.54 TPY	BAAQMD Condition # 14205 Part 12	P/Q	Records
	BAAQMD Condition # 14207 Part 3	Y		Emissions \leq 0.1 lb/MMBTU	BAAQMD Condition # 14207 Part 17	P/A	Source Test
CO	BAAQMD Condition # 14205 Part 10	Y		S3007+S3008+S3009+S3014+S3015+S3016+S3017 Emissions \leq 50.46 TPY	BAAQMD Condition # 14205 Part 12	P/Q	Records
PM10	BAAQMD Condition # 14207 Part 7	Y		Control Efficiency \geq 98%	None	N	None
Opacity	BAAQMD 6-301	Y		Ringelmann No. 1	None	N	None
FP	BAAQMD 6-310	Y		0.15 grains/dscf	None	N	None
FP	BAAQMD 6-311	Y		4.10P.0.67 lb/hr, where P is process weight, ton/hr	None	N	None

VII. Applicable Limits and Compliance Monitoring Requirements

Table VII - BI
Applicable Limits and Compliance Monitoring Requirements
S3015 – NPS TOPCOAT OVEN # 1
S3017 – NPS TOPCOAT OVEN # 2

Type of Limit	Emission Limit Citation	FE Y/N	Future Effective Date	Emission Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
Fuel Usage	BAAQMD Condition # 14205 Part 6	Y		S3007+S3008+S3009+S3014+S3015+S3016+S3017 Natural Gas Usage ≤ 9,630,000 therm/yr	BAAQMD Condition # 14205 Part 6	P/M	Records

North Passenger Paint Shop* sources include the following:
 S3007, NPS Dry Off Oven
 S3008, NPS Prime Booth,
 S3009, NPS Prime Oven,

S3014, NPS Top Coat Booth #1,
 S3015, NPS Topcoat Oven #1,
 S3016, NPS Topcoat Booth #2,
 S3017, NPS Topcoat Oven #2,

VII. Applicable Limits and Compliance Monitoring Requirements

Table VII – BL
Applicable Limits and Compliance Monitoring Requirements
S3500 – COLD CLEANER, S3501 – COLD CLEANER, S3502 – COLD CLEANER,
S30960 – GENERAL CLEANING AND PAINTING CLEANING

Type of Limit	Emission Limit Citation	FE Y/N	Future Effective Date	Emission Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
POC	BAAQMD Condition # 14205 Part 5	Y		North Passenger Paint Shop* Emissions \leq 719.23 TPY	BAAQMD Condition # 14205 Part 11	P/M	Records
	BAAQMD Condition # 14210 Part 1	Y		Emissions \leq 321.03 TPY or 40.13 ton/mon or compliance with Condition # 14205 Part 5	BAAQMD Condition # 14205 Part 11	P/M	Records
	BAAQMD Condition # 14210 Part 2	Y		Collection/ Recovery Efficiency \geq 65% of Cleanup Solvent or compliance with Condition # 14210 Part 1	BAAQMD Condition # 14205 Part 11	P/M	Records

North Passenger Paint Shop* sources include the following:
 S3007, NPS Dry Off Oven
 S3008, NPS Prime Booth,
 S3009, NPS Prime Oven,
 S3014, NPS Top Coat Booth #1,
 S3015, NPS Topcoat Oven #1,
 S3016, NPS Topcoat Booth #2,
 S3017, NPS Topcoat Oven #2,

VIII. TEST METHODS

The test methods associated with the emission limit of a District regulation are generally referenced in Section 600 of the regulation. The following table indicates only the test methods associated with the emission limits referenced in Section VII, Applicable Limits & Compliance Monitoring Requirements, of this permit.

Table VIII
Test Methods

Applicable Requirement	Description of Requirement	Acceptable Test Methods
BAAQMD 6-301	Ringelmann No. 1 Limitation	Manual of Procedures, Volume I, Evaluation of Visible Emissions
BAAQMD 6-304	Tube Cleaning	Manual of Procedures, Volume I, Evaluation of Visible Emissions
BAAQMD 6-310	Particulate Weight Limitation	Manual of Procedures, Volume IV, ST-15, Particulates Sampling
BAAQMD 8-2-301	Miscellaneous Operations	Manual of Procedures, Volume IV, ST-7, Non-Methane Organic Carbon Sampling; or EPA Method 25 or Determination of Total Gaseous Nonmethane Organic Emissions as Carbon, or EPA Method 25A, Determination of Total Gaseous Organic Concentration Using a Flame Ionization Analyzer
BAAQMD 8-3-302	Final Limits	Manual of Procedures, Volume II, Method 21.
BAAQMD 8-4-302	Limitation on Solvents and Surface Coatings (3/17/82)	Manual of Procedures, Volume IV, ST-7, Non-Methane Organic Carbon Sampling
BAAQMD 8-4-304	Alternate Compliance (3/17/82)	Manual of Procedures, Volume IV, ST-7, Non-Methane Organic Carbon Sampling
BAAQMD 8-5-117	Exemption, Low Vapor Pressure	Manual of Procedures, Volume III, Method 28, Determination of Vapor Pressure of Organic Liquids from Storage Tanks
BAAQMD 8-5-301	Storage Tanks Smaller than 150m ³ (eq. to SIP 8-5-301)	Manual of Procedures, Volume III, Method 28, Determination of Vapor Pressure of Organic Liquids from Storage Tanks
BAAQMD 8-5-302	Above Ground Gasoline Storage Tanks Smaller than 75 m ³ (equivalent to SIP 8-5-302)	Manual of Procedures, Volume III, Method 13, Determination of the Reid Vapor Pressure of Petroleum Products
BAAQMD 8-5-303	Above Ground Storage Tanks Larger than 37.5 m ³ and Smaller than 75 m ³	Manual of Procedures, Volume III, Method 28, Determination of Vapor Pressure of Organic Liquids from Storage Tanks
BAAQMD 8-5-304.1	Storage Tanks Larger than 75 m ³ , Vapor Pressure Greater than 1.5 psia	Manual of Procedures, Volume III, Method 28, Determination of Vapor Pressure of Organic Liquids from Storage Tanks

VIII. Test Methods

**Table VIII
 Test Methods**

Applicable Requirement	Description of Requirement	Acceptable Test Methods
BAAQMD 8-5-304.2	Storage Tanks Larger than 150 m ³ , Vapor Pressure Greater than 0.5 psia	Manual of Procedures, Volume III, Method 28, Determination of Vapor Pressure of Organic Liquids from Storage Tanks
BAAQMD 8-5-305	Storage Tanks Storing Organic Liquids with a True Vapor Pressure Greater than 11 psia:	Manual of Procedures, Volume III, Method 28, Determination of Vapor Pressure of Organic Liquids from Storage Tanks
BAAQMD 8-5-311.3	Vapor Loss Control Device Requirements:	Manual of Procedures, Volume IV, ST-4, Bulk Gasoline Distribution Facilities
BAAQMD 8-5-328.1	Tank Cleaning Requirements - Liquid Balancing	Manual of Procedures, Volume III, Method 28, Determination of Vapor Pressure of Organic Liquids from Storage Tanks
BAAQMD 8-5-328.2	Tank Cleaning Requirements - Approved Emission Control System	Manual of Procedures, Volume IV, ST-7, Non-Methane Organic Carbon Sampling
BAAQMD 8-5-320.3	Tank Fitting Requirements, Pressure-Vacuum Valves	EPA Reference Method 21 (40 CFR 60, Appendix A).
BAAQMD 8-5-501	Records	Manual of Procedures, Volume III, Method 28, Determination of Vapor Pressure of Organic Liquids from Storage Tanks
SIP 8-5-301	Storage Tanks Smaller than 150m ³	Manual of Procedures, Volume III, Method 28, Determination of Vapor Pressure of Organic Liquids from Storage Tanks
SIP 8-5-302	Above Ground Gasoline Storage Tanks Smaller than 75 m ³	Manual of Procedures, Volume III, Method 13, Determination of the Reid Vapor Pressure of Petroleum Products
BAAQMD 8-16-216	Compounds with Low Volatility	ASTM D-1078-78
BAAQMD 8-13-302	Final Limits, Topcoat, Spray Primer, Primer Surfacer	Manual of Procedures, Volume IV, ST-7, Non-Methane Organic Carbon Sampling; or EPA Method 25 or Determination of Total Gaseous Nonmethane Organic Emissions as Carbon, or EPA Method 25A, Determination of Total Gaseous Organic Concentration Using a Flame Ionization Analyzer
BAAQMD 9-1-302	General Emission Limitation	Manual of Procedures, Volume IV, ST-19A, Sulfur Dioxide, Continuous Sampling, or ST-19B, Total Sulfur Oxides Integrated Sample
BAAQMD 9-1-303	Emissions from ships	Manual of Procedures, Volume IV, ST-19A, Sulfur Dioxide, Continuous Sampling, or ST-19B, Total Sulfur Oxides Integrated Sample

VIII. Test Methods

**Table VIII
 Test Methods**

Applicable Requirement	Description of Requirement	Acceptable Test Methods
BAAQMD 9-7-301.1	Performance Standard, NOx, Gaseous Fuel	Manual of Procedures, Volume IV, ST-13A, Oxides of Nitrogen, Continuous Sampling and ST-14, Oxygen, Continuous Sampling
BAAQMD 9-7-301.2	Performance Standard, CO, Gaseous Fuel	Manual of Procedures, Volume IV, ST-6, Carbon Monoxide, Continuous Sampling and ST-14, Oxygen, Continuous Sampling
BAAQMD 9-7-302.1	Performance Standard, NOx, Non-Gaseous Fuel	Manual of Procedures, Volume IV, ST-13A, Oxides of Nitrogen, Continuous Sampling and ST-14, Oxygen, Continuous Sampling
BAAQMD 9-7-302.2	Performance Standard, CO, Non- Gaseous Fuel	Manual of Procedures, Volume IV, ST-6, Carbon Monoxide, Continuous Sampling and ST-14, Oxygen, Continuous Sampling
BAAQMD 9-7-303	Emission Limits - Gaseous and Non-Gaseous Fuel, NOx and CO	Manual of Procedures, Volume IV, ST-13A, Oxides of Nitrogen, Continuous Sampling and

IX. PERMIT SHIELD

Not Applicable.

X. REVISION HISTORY

Final Title V Permit (Application 16480): December 18, 2002

Significant Revision (Applications 6914, 7048, 7119, 7151, 8370, 8419, and 8493): December 13, 2004

- Change of responsible official;
- Renaming of permitted sources to clarify actual operational use;
- Deletion of permitted sources which have been removed;
- Replacement of permitted abatement devices which have been replaced;
- Removal of sources which have been determined exempt;
- Change of conditions for existing sources (incorporating District applications);
- Removal of particulate monitoring for dry filters, which has been determined to be unnecessary;
- Addition of particulate monitoring for scrubbers;
- Correction of erroneous information.

Minor Revision (Application 12215): October 24, 2007

- Modify permit condition numbers 9158, 9163 and 9164 to include the following: Total non-methane organic hydrocarbon emissions from the outlet of the thermal oxidizers shall be 10 ppm or less by volume. These changes specify that the thermal oxidizers used to abate emissions from NUMMI's truck line operations will be in compliance in the event the outlet emissions from the thermal oxidizers are less than or equal to 10 ppm by volume of non-methane hydrocarbons.

XI. GLOSSARY

ACT

Federal Clean Air Act

BAAQMD

Bay Area Air Quality Management District

BACT

Best Available Control Technology

CAA

The federal Clean Air Act

CAAQS

California Ambient Air Quality Standards

CEQA

California Environmental Quality Act

CFR

The Code of Federal Regulations. 40 CFR contains the implementing regulations for federal environmental statutes such as the Clean Air Act. Parts 50-99 of 40 CFR contain the requirements for air pollution programs.

CO

Carbon Monoxide

Cumulative Increase

The sum of permitted emissions from each new or modified source since a specified date pursuant to BAAQMD Rule 2-1-403, Permit Conditions (as amended by the District Board on 7/17/91) and SIP Rule 2-1-403, Permit Conditions (as approved by EPA on 6/23/95). Used to determine whether threshold-based requirements are triggered.

District

The Bay Area Air Quality Management District

EPA

The federal Environmental Protection Agency.

Excluded

Not subject to any District Regulations.

Federally Enforceable, FE

All limitations and conditions which are enforceable by the Administrator of the EPA including those requirements developed pursuant to 40 CFR Part 51, subpart I (NSR), Part

X. Glossary

52.21 (PSD), Part 60, (NSPS), Part 61, (NESHAPs), Part 63 (HAP), and Part 72 (Permits Regulation, Acid Rain), and also including limitations and conditions contained in operating permits issued under an EPA-approved program that has been incorporated into the SIP.

FP

Filterable Particulate as measured by BAAQMD Method ST-15, Particulate.

HAP

Hazardous Air Pollutant. Any pollutant listed pursuant to Section 112(b) of the Act. Also refers to the program mandated by Title I, Section 112, of the Act and implemented by both 40 CFR Part 63.

Major Facility

A facility with potential emissions of: (1) at least 100 tons per year of regulated air pollutants, (2) at least 10 tons per year of any single hazardous air pollutant, and/or (3) at least 25 tons per year of any combination of hazardous air pollutants, or such lesser quantity of hazardous air pollutants as determined by the EPA administrator.

MFR

Major Facility Review. The District's term for the federal operating permit program mandated by Title V of the Act and implemented by District Regulation 2, Rule 6.

MOP

The District's Manual of Procedures.

NAAQS

National Ambient Air Quality Standards

NESHAPs

National Emission Standards for Hazardous Air Pollutants. See in 40 CFR Part 61.

NMHC

Non-methane Hydrocarbons

NO_x

Oxides of nitrogen.

NSPS

Standards of Performance for New Stationary Sources. Federal standards for emissions from new stationary sources. Mandated by Title I, Section 111 of the Act, and implemented by 40 CFR Part 60 and District Regulation 10.

NSR

New Source Review. A federal program for pre-construction review and permitting of new and modified sources of air pollutants for which the District is classified "non-attainment". Mandated by Title I of the Clean Air Act and implemented by 40 CFR Parts 51 and 52 as well as District Regulation 2, Rule 2. (Note: There are additional NSR requirements mandated by the California Clean Air Act.)

X. Glossary

Offset Requirement

A New Source Review requirement to provide federally enforceable emission offsets at a specified ratio for the emissions from a new or modified source and any pre-existing cumulative increase minus any onsite contemporaneous emission reduction credits. Applies to emissions of POC, NO_x, PM₁₀, and SO₂.

Phase II Acid Rain Facility

A facility that generates electricity for sale through fossil-fuel combustion and is not exempted by 40 CFR 72 from Titles IV and V of the Clean Air Act.

POC

Precursor Organic Compounds

PM

Total Particulate Matter

PM₁₀

Particulate matter with aerodynamic equivalent diameter of less than or equal to 10 microns

PSD

Prevention of Significant Deterioration. A federal program for permitting new and modified sources of air pollutants for which the District is classified "attainment" of the National Air Ambient Quality Standards. Mandated by Title I of the Act and implemented by both 40 CFR Part 52 and District Regulation 2, Rule 2.

SIP

State Implementation Plan. State and District programs and regulations approved by EPA and developed in order to attain the National Air Ambient Quality Standards. Mandated by Title I of the Act.

SO₂

Sulfur dioxide

Title V

Title V of the federal Clean Air Act. Requires a federally enforceable operating permit program for major and certain other facilities.

TRMP

Toxic Risk Management Plan

TSP

Total Suspended Particulate

VOC

X. Glossary

Volatile Organic Compounds

Units of Measure:

bhp	=	brake-horsepower
btu	=	British Thermal Unit
g	=	grams
gal	=	gallon
hp	=	horsepower
hr	=	hour
lb	=	pound
in	=	inches
max	=	maximum
m ²	=	square meter
min	=	minute
mon	=	month
mm	=	million
ppmv	=	parts per million, by volume
ppmw	=	parts per million, by weight
psia	=	pounds per square inch, absolute
psig	=	pounds per square inch, gauge
scfm	=	standard cubic feet per minute
yr	=	year

XII. APPLICABLE STATE IMPLEMENTATION PLAN

The Bay Area Air Quality Management District's portion of the State Implementation Plan can be found at EPA Region 9's website. The address is:

<http://yosemite.epa.gov/r9/r9sips.nsf/Agency?ReadForm&count=500&state=California&cat=Bay+Area+Air+Quality+Management+District-Agency-Wide+Provisions>