

Bay Area Air Quality Management District

939 Ellis Street
San Francisco, CA 94109
(415) 771-6000

Proposed

MAJOR FACILITY REVIEW PERMIT

Issued To:
TriCities Waste Management
Facility #A2246

Facility Address:
7010 Auto Mall Parkway
Fremont, CA 94538

Mailing Address:
7010 Auto Mall Parkway
Fremont, CA 94538

Responsible Official
James Devlin
North Bay Market Area Manager
(510) 430-8509

Facility Contact
~~Brian Bowen~~ Colleen Cassidy
Environmental Protection ~~Manager~~ Specialist
(916) 448-4675 / (510) 624-5928

Type of Facility: Municipal Solid Waste Landfill BAAQMD Permit Division Contact:
Primary SIC: 4953 Ted Hull, Senior Air Quality Engineer
Product: Landfill Operations

ISSUED BY THE BAY AREA AIR QUALITY MANAGEMENT DISTRICT

Jack P. Broadbent, Executive Officer/Air Pollution Control Officer

Date

TABLE OF CONTENTS

I. STANDARD CONDITIONS	3
II. EQUIPMENT	8
III. GENERALLY APPLICABLE REQUIREMENTS.....	10
IV. SOURCE-SPECIFIC APPLICABLE REQUIREMENTS	13
V. SCHEDULE OF COMPLIANCE.....	39
VI. PERMIT CONDITIONS	40
VII. APPLICABLE LIMITS & COMPLIANCE MONITORING REQUIREMENTS.....	56
VIII. TEST METHODS.....	74
IX. PERMIT SHIELD.....	78
X. REVISION HISTORY.....	80
XI. GLOSSARY	82

I. STANDARD CONDITIONS

A. Administrative Requirements

The permit holder shall comply with all applicable requirements in the following regulations:

- BAAQMD Regulation 1 - General Provisions and Definitions
(as amended by the District Board on 5/2/01);
- SIP Regulation 1 - General Provisions and Definitions
(as approved by EPA through 6/28/99);
- BAAQMD Regulation 2, Rule 1 - Permits, General Requirements
(as amended by the District Board on ~~12/21/04~~6/15/05);
- SIP Regulation 2, Rule 1 - Permits, General Requirements
(as approved by EPA through 1/26/99);
- BAAQMD Regulation 2, Rule 2 - Permits, New Source Review
(as amended by the District Board on ~~12/21/04~~6/15/05);
- SIP Regulation 2, Rule 2 - Permits, New Source Review and Prevention of Significant Deterioration
(as approved by EPA through 1/26/99);
- BAAQMD Regulation 2, Rule 4 - Permits, Emissions Banking
(as amended by the District Board on 12/21/04);
- SIP Regulation 2, Rule 4 - Permits, Emissions Banking
(as approved by EPA through 1/26/99); and
- BAAQMD Regulation 2, Rule 6 - Permits, Major Facility Review
(as amended by the District Board on 4/16/03).

B. Conditions to Implement Regulation 2, Rule 6, Major Facility Review

1. This Major Facility Review Permit was issued on ~~November 28, 2001~~ and expires on ~~October 31, 2006~~. The permit holder shall submit a complete application for renewal of this Major Facility Review Permit no later than ~~April 30, 2006~~ and no earlier than ~~October 31, 2005~~. **If a complete application for renewal has not been submitted in accordance with this deadline, the facility may not operate after ~~October 31, 2006~~.** If the permit renewal has not been issued by ~~October 31, 2006~~, but a complete application for renewal has been submitted in accordance with the above deadlines, the existing permit will continue in force until the District takes final action on the renewal application. (Regulation 2-6-307, 404.2, 407, & 409.6; MOP Volume II, Part 3, §4.2)
2. The permit holder shall comply with all conditions of this permit. The permit consists of this document and all appendices. Any non-compliance with the terms and conditions of this permit will constitute a violation of the law and will be grounds for enforcement action; permit termination, revocation and re-issuance, or modification; or denial of a permit renewal application. (Regulation 2-6-307; MOP Volume II, Part 3, §4.11)
3. In the event any enforcement action is brought as a result of a violation of any term or condition of this permit, the fact that it would have been necessary for the permittee to halt or reduce the permitted activity in order to maintain compliance with such term or condition shall not be a defense to such enforcement action. (MOP

I. Standard Conditions

Volume II, Part 3, §4.11)

4. This permit may be modified, revoked, reopened and reissued, or terminated for cause. (Regulation 2-6-307, 409.8, 415; MOP Volume II, Part 3, §4.11)
5. The filing of a request by the facility for a permit modification, revocation and re-issuance, or termination, or the filing of a notification of planned changes or anticipated non-compliance does not stay the applicability of any permit condition. (Regulation 2-6-409.7; MOP Volume II, Part 3, §4.11)
6. This permit does not convey any property rights of any sort, or any exclusive privilege. (Regulation 2-6-409.7; MOP Volume II, Part 3, §4.11)
7. The permit holder shall supply within 30 days any information that the District requests in writing to determine whether cause exists for modifying, revoking and reissuing, or terminating the permit or to determine compliance with the permit. (Regulation 1-441, Regulation 2-6-409.4 & 501; MOP Volume II, Part 3, §4.11)
8. Any records required to be maintained pursuant to this permit which the permittee considers to contain proprietary or trade secret information shall be prominently designated as such. Copies of any such proprietary or trade secret information which are provided to the District shall be maintained by the District in a locked confidential file, provided, however, that requests from the public for the review of any such information shall be handled in accordance with the District's procedures set forth in Section 11 of the District's Administrative Code. (Regulation 2-6-419; MOP Volume II, Part 3, §4.11)
9. Proprietary or trade secret information provided to EPA will be subject to the requirements of 40 CFR Part 2, Subpart B - Public Information, Confidentiality of Business Information. (40 CFR Part 2)
10. The emissions inventory submitted with the application for this Major Facility Review Permit is an estimate of actual emissions for the time period stated and is included only as one means of determining applicable requirements for emission sources. It does not establish, or constitute a basis for establishing, any new emission limitations. (MOP Volume II, Part 3, §4.11)
11. The responsible official shall certify all documents submitted by the facility pursuant to the major facility review permit. The certification shall state that based on information and belief formed after reasonable inquiry, the statements and information in the document are true, accurate, and complete. The certifications shall be signed by a responsible official for the facility. (Regulation 2-6-409.20, MOP Volume II, Part 3, §4.11)
12. The permit holder is responsible for compliance, and certification of compliance, with all conditions of the permit, regardless whether it acts through employees, agents, contractors, or subcontractors. (Regulation 2-6-307)

C. Requirement to Pay Fees

The permit holder shall pay annual fees in accordance with District Regulation 3, including Schedule P. (Regulation 2-6-402 & 409.13, Regulation 3; MOP Volume II,

I. Standard Conditions

Part 3, §4.12)

D. Inspection and Entry

Access to Facility: The permit holder shall provide reasonable access to the facility and equipment which is subject to this permit to the APCO and/or to his or her designee. (Regulation 1-440, Regulation 2-6-409.3; MOP Volume II, Part 3, §4.14)

E. Records

1. The permit holder must provide any information, records, and reports requested or specified by the APCO. (Regulation 1-441, Regulation 2-6-409.4)
2. Notwithstanding the specific wording in any requirement, all records for federally enforceable requirements shall be maintained for at least five years from the date of creation of the record. (Regulation 2-6-501, Regulation 3; MOP Volume II, Part 3, §4.7)

F. Monitoring Reports

Reports of all required monitoring must be submitted to the District at least once every six months, except where an applicable requirement specifies more frequent reporting. ~~The first reporting period for this permit shall be November 28, 2001 to April 30, 2002. The report shall be submitted by May 31, 2002. Subsequent r~~Reports shall be for the following periods: May 1st through October 31st and November 1st through April 30th, and are due on the last day of the month after the end of the reporting period. All instances of non-compliance shall be clearly identified in these reports. The reports shall be certified by the responsible official as true, accurate, and complete. In addition, all instances of non-compliance with the permit shall be reported in writing to the District's Compliance and Enforcement Division within 10 calendar days of the discovery of the incident. Within 30 calendar days of the discovery of any incident of non-compliance, the facility shall submit a written report including the probable cause of non-compliance and any corrective or preventative actions. The reports shall be sent to the following address:

Director of Compliance and Enforcement
Bay Area Air Quality Management District
939 Ellis Street
San Francisco, CA 94109
Attn: Title V Reports

(Regulation 2-6-502, Regulation 3; MOP Volume II, Part 3, §4.7)

I. Standard Conditions

G. Compliance Certification

Compliance certifications shall be submitted annually by the responsible official of this facility to the Bay Area Air Quality Management District and to the Environmental Protection Agency. The certification period will be November 1st to October 31st. The certification shall be submitted by November 30th of each year. The certification must list each applicable requirement, the compliance status, whether compliance was continuous or intermittent, the method used to determine compliance, and any other specific information required by the permit. The permit holder may satisfy this requirement through submittal of District-generated Compliance Certification forms. The certification should be directed to the District's Compliance and Enforcement Division at the address above, and a copy of the certification should be sent to the Environmental Protection Agency at the following address:

Director of the Air Division
USEPA, Region IX
75 Hawthorne Street
San Francisco, CA 94105
Attention: Air-3

(MOP Volume II, Part 3, §4.5 and 4.15)

H. Emergency Provisions

1. The permit holder may seek relief from enforcement action in the event of a breakdown, as defined by Regulation 1-208 of the District's Rules and Regulations, by following the procedures contained in Regulations 1-431 and 1-432. The District will thereafter determine whether breakdown relief will be granted in accordance with Regulation 1-433. (MOP Volume II, Part 3, §4.8)
2. The permit holder may seek relief from enforcement action for a violation of any of the terms and conditions of this permit by applying to the District's Hearing Board for a variance pursuant to Health and Safety Code Section 42350. The Hearing Board will determine after notice and hearing whether variance relief should be granted in accordance with the procedures and standards set forth in Health and Safety Code Section 42350 et seq. (MOP Volume II, Part 3, §4.8)
3. The granting by the District of breakdown relief or the issuance by the Hearing Board of a variance will not provide relief from federal enforcement. (MOP Volume II, Part 3, §4.8)

I. Severability

In the event that any provision of this permit is invalidated by a court or tribunal of competent jurisdiction, or by the Administrator of the EPA, all remaining portions of the permit shall remain in full force and effect. (Regulation 2-6-409.5; MOP Volume II, Part 3, §4.10)

I. Standard Conditions

J. Miscellaneous Conditions

1. The maximum capacity for each source as shown in Table II-A is the maximum allowable capacity. Exceedance of the maximum allowable capacity for any source is a violation of Regulation 2, Rule 1, Section 301. (Regulation 2-1-301)

II. EQUIPMENT

Table II A - Permitted Sources

Each of the following sources has been issued a permit to operate pursuant to the requirements of BAAQMD Regulation 2, Permits. The capacities in this table are the maximum allowable capacities for each source, pursuant to Standard Condition I.J and Regulation 2-1-301.

S-#	Description	Make or Type	Model	Capacity
S-1	TriCities Landfill: (Active Solid Waste Disposal Site with Active Gas Collection System, <u>Up to 2538</u> Vertical Gas Collection Wells)	Municipal Solid Waste	N/A	Max. Design Capacity = 19.271 million cubic yards (14.735 million cubic meters) Max. Waste In Place = 13.5 million tons Max. Waste Acceptance Rate = 2,628 tons/day
S-5	Wood Waste Stockpiles	N/A	N/A	200 tons/day
S-9	Portable Diesel Engine	John Deere		70 hp
S-10	Parts Cleaner	Safety-Kleen		20 gallon capacity
S-14	Diesel IC Engine – Air Compressor (GE-1)	John Deere	4239D	80 BHP
S-15	Diesel IC Engine – Air Compressor (GE-2)	John Deere	4239D	80 BHP
S-16	Diesel IC Engine – Vacuum Truck	Cummins	6BTA5.9	177 BHP
S-17	Diesel IC Engine – Street Sweeper	John Deere	4239D	80 BHP
S-18*	IC Engine Generator Set #1, Landfill Gas Fired	Caterpillar	G3516LE	1,148 BHP, 10.5 MMBTU/hr
S-19*	IC Engine Generator Set #1, Landfill Gas Fired	Caterpillar	G3516LE	1,148 BHP, 10.5 MMBTU/hr
S-20*	IC Engine Generator Set #1, Landfill Gas Fired	Caterpillar	G3516LE	1,148 BHP, 10.5 MMBTU/hr

* Proposed Equipment. (See Authority to Construct #009222)

II. Equipment

Table II B – Abatement Devices

A-#	Description	Source(s) Controlled	Applicable Requirement	Operating Parameters	Limit or Efficiency
A-3	Landfill Gas Flare, burning propane (during start-up only) and landfill gas, 75 MM BTU/hour	S-1	BAAQMD Regulation 8-34-301.3 and BAAQMD Condition #8366, Part 6, see also Table IV-A	Minimum Flue Gas Temperature: 1450 degrees F (3-hour average), see also Table VII-A	Either NMOC destruction efficiency ≥98% (wt), or <30 ppm NMOC @ 3% O ₂ at flare outlet, see also Table VII-A
A-5	Water Truck	S-1	BAAQMD Regulation 6-301	None	Ringelmann No. 1

III. GENERALLY APPLICABLE REQUIREMENTS

The permit holder shall comply with all applicable requirements, including those specified in the BAAQMD and SIP Rules and Regulations and other federal requirements cited below. These requirements apply in a general manner to the facility and/or to sources exempt from the requirement to obtain a District Permit to Operate. The District has determined that these requirements will not be violated under normal, routine operations, and that no additional periodic monitoring or reporting to demonstrate compliance is warranted. In cases where a requirement, in addition to being generally applicable, is also specifically applicable to one or more sources, the requirement and the source are also included in Section IV, Source-Specific Applicable Requirements, of this permit. This section also contains provisions that may apply to temporary sources.

The dates in parentheses in the Title column identify the versions of the regulations being cited and are, as applicable:

1. BAAQMD regulation(s): The date(s) of adoption or most recent amendment of the regulation by the District Board of Directors.
2. Any federal requirement, including a version of a District regulation that has been approved into the SIP: The most recent date of EPA approval of any portion of the rule, encompassing all actions on the rule through that date

The full language of SIP requirements is on EPA Region 9’s website. The address is:
<http://yosemite.epa.gov/r9/r9sips.nsf/Agency?ReadForm&count=500&state=California&cat=Bay+Area+Air+Quality+Management+District-Agency-Wide+Provisions>

NOTE:

There are differences between the current BAAQMD rules and the version of the rules in the SIP. All sources must comply with both versions of the rule until US EPA has reviewed and approved the District’s revision of the regulation.

**Table III
 Generally Applicable Requirements**

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)
BAAQMD Regulation 1	General Provisions and Definitions (5/2/01)	N
SIP Regulation 1	General Provisions and Definitions (6/28/99)	Y ⁺
BAAQMD Regulation 2, Rule 1	General Requirements (4/21/04 6/15/05)	N
BAAQMD 2-1-429	Federal Emissions Statement (6/7/95)	Y
SIP Regulation 2, Rule 1	General Requirements (1/26/99)	Y ⁺
<u>BAAQMD Regulation 2, Rule 5</u>	<u>New Source Review of Toxic Air Contaminants (6/15/05)</u>	<u>N</u>
<u>BAAQMD Regulation 4</u>	<u>Air Pollution Episode Plan (3/20/91)</u>	<u>N</u>
<u>SIP Regulation 4</u>	<u>Air Pollution Episode Plan (8/6/90)</u>	<u>Y</u>

III. Generally Applicable Requirements

**Table III
 Generally Applicable Requirements**

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)
BAAQMD Regulation 5	Open Burning (3/6/02)	N
SIP Regulation 5	Open Burning (9/4/98)	Y ⁺
BAAQMD Regulation 6	Particulate Matter and Visible Emissions (12/19/90)	Y
BAAQMD Regulation 7	Odororous Substances (3/17/82)	N
BAAQMD Regulation 8, Rule 1	Organic Compounds - General Provisions (6/15/94)	Y
BAAQMD Regulation 8, Rule 2	Organic Compounds – Miscellaneous Operations (6/15/94 7/20/05)	Y N
<u>SIP Regulation 8, Rule 2</u>	<u>Organic Compounds – Miscellaneous Operations</u> (6/15/94)	<u>Y</u>
BAAQMD Regulation 8, Rule 3	Organic Compounds - Architectural Coatings (11/21/01)	N Y
BAAQMD Regulation 8, Rule 4	Organic Compounds - General Solvent and Surface Coating Operations (10/16/02)	Y
BAAQMD Regulation 8, Rule 15	Organic Compounds – Emulsified and Liquid Asphalts (6/1/94)	Y
BAAQMD Regulation 8, Rule 16	Organic Compounds - Solvent Cleaning Operations (10/16/02)	Y
BAAQMD Regulation 8, Rule 40	Organic Compounds – Aeration of Contaminated Soil and Removal of Underground Storage Tanks (12/15/99 6/15/05)	Y
BAAQMD 8-40-116	Exemption, Small Volume	Y
BAAQMD 8-40-117	Exemption, Accidental Spills	Y
BAAQMD Regulation 8, Rule 47	Organic Compounds – Air Stripping and Soil Vapor Extraction Operations (6/15/94 6/15/05)	Y
BAAQMD Regulation 8, Rule 49	Organic Compounds - Aerosol Paint Products (12/20/95)	N
SIP Regulation 8, Rule 49	Organic Compounds - Aerosol Paint Products (3/22/95)	Y ⁺
BAAQMD Regulation 8, Rule 51	Organic Compounds - Adhesive and Sealant Products (7/17/02)	N
SIP Regulation 8, Rule 51	Organic Compounds - Adhesive and Sealant Products (2/26/02)	Y ⁺
BAAQMD Regulation 9, Rule 1	Inorganic Gaseous Pollutants – Sulfur Dioxide (3/15/95)	N
SIP Regulation 9, Rule 1	Inorganic Gaseous Pollutants - Sulfur Dioxide (6/8/99)	Y ⁺
BAAQMD Regulation 11, Rule 1	Hazardous Pollutants - Lead (3/17/82)	N
SIP Regulation 11, Rule 1	Hazardous Pollutants – Lead (9/2/81)	Y ⁺

III. Generally Applicable Requirements

**Table III
 Generally Applicable Requirements**

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)
BAAQMD Regulation 11, Rule 2	Hazardous Pollutants - Asbestos Demolition, Renovation and Manufacturing (10/7/98)	N
BAAQMD Regulation 11, Rule 3	Hazardous Pollutants - Beryllium (3/17/82)	N
BAAQMD Regulation 11, Rule 14	Hazardous Pollutants - Asbestos Containing Serpentine (7/17/91)	N
BAAQMD Regulation 12, Rule 4	Miscellaneous Standards of Performance - Sandblasting (7/11/90)	N
SIP Regulation 12, Rule 4	Miscellaneous Standards of Performance - Sandblasting (9/2/81)	Y ⁺
<u>California Health and Safety Code Section 41750 et seq.</u>	<u>Portable Equipment</u>	<u>N</u>
California Code of Regulations Title 17, Section 93105	Asbestos Airborne Toxic Control Measure for Construction, Grading, Quarrying, and Surface Mining Operations (7/26/01)	N
California Code of Regulations Title 17, Section 93106	Asbestos Airborne Toxic Control Measure for Asbestos-Containing Serpentine (7/20/00)	N
California Health and Safety Code Section 44300 et seq.	Air Toxics "Hot Spots" Information and Assessment Act of 1987	N
<u>California Health and Safety Code Title 17, Section 93115</u>	<u>Airborne Toxic Control Measure for Stationary Compression Ignition Engines</u>	<u>N</u>
<u>California Health and Safety Code Title 17, Section 93116</u>	<u>Airborne Toxic Control Measure for Diesel Particulate Matter from Portable Engines Rated at 50 Horsepower and Greater</u>	<u>N</u>
40 CFR Part 61, Subpart A	National Emission Standards for Hazardous Air Pollutants – General Provisions (5/28/03)	Y
40 CFR Part 61, Subpart M	National Emission Standards for Hazardous Air Pollutants – National Emission Standard for Asbestos (6/19/95)	Y
<u>EPA Regulation 40 CFR 82 Subpart F, 40 CFR 82.156</u>	<u>Protection of Stratospheric Ozone (2/21/95)</u>	
<u>Subpart F, 40 CFR 82.156</u>	<u>Leak Repair</u>	<u>Y</u>
<u>Subpart F, 40 CFR 82.161</u>	<u>Certification of Technicians</u>	<u>Y</u>
<u>Subpart F, 40 CFR 82.166</u>	<u>Records of Refrigerant</u>	<u>Y</u>

1. ~~This section has been removed from BAAQMD Regulations because it has been superseded. Nevertheless, the source must comply with this regulation until US EPA has reviewed and approved (or disapproved) the District's revision of the regulation.~~

IV. SOURCE-SPECIFIC APPLICABLE REQUIREMENTS

The permit holder shall comply with all applicable requirements, including those specified in the BAAQMD and SIP Rules and Regulations and other federal requirements cited below. The requirements cited in the following tables apply in a specific manner to the indicated source(s).

The dates in parentheses in the Title column identify the versions of the regulations being cited and are, as applicable:

1. BAAQMD regulation(s): The date(s) of adoption or most recent amendment of the regulation by the District Board of Directors.
2. Any federal requirement, including a version of a District regulation that has been approved into the SIP: The most recent date of EPA approval of any portion of the rule, encompassing all actions on the rule through that date.

The full text of each permit condition cited is included in Section VI, Permit Conditions, of this permit. The full language of SIP requirements is on EPA Region 9’s website. The address is:

<http://yosemite.epa.gov/r9/r9sips.nsf/Agency?ReadForm&count=500&state=California&cat=Bay+Area+Air+Quality+Management+District-Agency-Wide+Provisions>. All other text may be found in the regulations themselves.

Table IV - A
Source-Specific Applicable Requirements
S-1: LANDFILL WITH GAS COLLECTION SYSTEM AND
A-3: LANDFILL GAS FLARE

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
BAAQMD Regulation 1	General Provisions and Definitions (5/2/01)		
1-523	Parametric Monitoring and Recordkeeping Procedures	N	
1-523.1	Reporting requirement for periods of inoperation > 24 hours	Y	
1-523.2	Limit on duration of inoperation	Y	
1-523.3	Reporting requirement for violations of any applicable limits	N	
1-523.4	Records of inoperation, tests, calibrations, adjustments, & maintenance	Y	
1-523.5	Maintenance and calibration	N	
SIP Regulation 1	General Provisions and Definitions (6/28/99)		
1-523	Parametric Monitoring and Recordkeeping Procedures	Y ¹	
1-523.3	Reports of Violations	Y ¹	

IV. Source-Specific Applicable Requirements

Table IV - A
Source-Specific Applicable Requirements
S-1: LANDFILL WITH GAS COLLECTION SYSTEM AND
A-3: LANDFILL GAS FLARE

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
BAAQMD Regulation 6	Particulate Matter and Visible Emissions (12/19/90)		
6-301	Ringelmann No. 1 Limitation	Y	
6-305	Visible Particles	Y	
6-310	Particle Weight Limitation (applies to flare only)	Y	
6-401	Appearance of Emissions	Y	
BAAQMD Regulation 8, Rule 2	Organic Compounds – Miscellaneous Operations (6/15/94)		
8-2-301	Miscellaneous Operations (applies to low VOC soil handling and disposal activities only)	Y	
BAAQMD Regulation 8, Rule 34	Organic Compounds – Solid Waste Disposal Sites (10/6/99)		
8-34-113	Limited Exemption, Inspection and Maintenance	Y	
8-34-113.1	Emission Minimization Requirement	Y	
8-34-113.2	Shutdown Time Limitation	Y	
8-34-113.3	Recordkeeping Requirement	Y	
8-34-116	Limited Exemption, Well Raising	Y	
8-34-116.1	New Fill	Y	
8-34-116.2	Limits on Number of Wells Shutdown	Y	
8-34-116.3	Shutdown Duration Limit	Y	
8-34-116.4	Capping Well Extensions	Y	
8-34-116.5	Well Disconnection Records	Y	
8-34-117	Limited Exemption, Gas Collection System Components	Y	
8-34-117.1	Necessity of Existing Component Repairs/Adjustments	Y	
8-34-117.2	New Components are Described in Collection and Control System Design Plan	Y	
8-34-117.3	Meets Section 8-34-118 Requirements	Y	
8-34-117.4	Limits on Number of Wells Shutdown	Y	
8-34-117.5	Shutdown Duration Limit	Y	
8-34-117.6	Well Disconnection Records	Y	
8-34-118	Limited Exemption, Construction Activities	Y	

IV. Source-Specific Applicable Requirements

Table IV - A
Source-Specific Applicable Requirements
S-1: LANDFILL WITH GAS COLLECTION SYSTEM AND
A-3: LANDFILL GAS FLARE

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
8-34-118.1	Construction Plan	Y	
8-34-118.2	Activity is Required to Maintain Compliance with this Rule	Y	
8-34-118.3	Required or Approved by Other Enforcement Agencies	Y	
8-34-118.4	Emission Minimization Requirement	Y	
8-34-118.5	Excavated Refuse Requirements	Y	
8-34-118.6	Covering Requirements for Exposed Refuse	Y	
8-34-118.7	Installation Time Limit	Y	
8-34-118.8	Capping Required for New Components	Y	
8-34-118.9	Construction Activity Records	Y	
8-34-301	Landfill Gas Collection and Emission Control System Requirements	Y	
8-34-301.1	Continuous Operation	Y	
8-34-301.2	Collection and Control Systems Leak Limitations	Y	
8-34-301.3	Destruction Efficiency Requirements for Flares	Y	
8-34-303	Landfill Surface Requirements	Y	
8-34-304	Gas Collection System Installation Requirements	Y	
8-34-304.1	Based on Waste Age For Inactive or Closed Areas	Y	
8-34-304.2	Based on Waste Age For Active Areas	Y	
8-34-304.3	Based on Amount of Decomposable Waste Accepted	Y	
8-34-304.4	Based on NMOC Emission Rate	Y	
8-34-305	Wellhead Requirements	Y	
8-34-305.1	Operate Under Vacuum	Y	
8-34-305.2	Temperature < 55 °C	Y	
8-34-305.3	Nitrogen < 20% or	Y	
8-34-305.4	Oxygen < 5%	Y	
8-34-405	Design Capacity Reports (If Design Capacity is Amended)	Y	
8-34-408	Collection and Control System Design Plans	Y	
8-34-408.2	Sites With Existing Collection and Control Systems	Y	
8-34-411	Annual Report	Y	
8-34-412	Compliance Demonstration Tests	Y	
8-34-413	Performance Test Report	Y	
8-34-414	Repair Schedule for Wellhead Excesses	Y	
8-34-414.1	Records of Excesses	Y	

IV. Source-Specific Applicable Requirements

Table IV - A
Source-Specific Applicable Requirements
S-1: LANDFILL WITH GAS COLLECTION SYSTEM AND
A-3: LANDFILL GAS FLARE

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
8-34-414.2	Corrective Action	Y	
8-34-414.3	Collection System Expansion	Y	
8-34-414.4	Operational Due Date for Expansion	Y	
8-34-415	Repair Schedule for Surface Leak Excesses	Y	
8-34-415.1	Records of Excesses	Y	
8-34-415.2	Corrective Action	Y	
8-34-415.3	Re-monitor Excess Location Within 10 Days	Y	
8-34-415.4	Re-monitor Excess Location Within 1 Month	Y	
8-34-415.5	If No More Excesses, No Further Re-Monitoring	Y	
8-34-415.6	Additional Corrective Action	Y	
8-34-415.7	Re-monitor Second Excess Within 10 days	Y	
8-34-415.8	Re-monitor Second Excess Within 1 Month	Y	
8-34-415.9	If No More Excesses, No Further Re-monitoring	Y	
8-34-415.10	Collection System Expansion for Third Excess in a Quarter	Y	
8-34-415.11	Operational Due Date for Expansion	Y	
8-34-416	Cover Repairs	Y	
8-34-501	Operating Records	Y	
8-34-501.1	Collection System Downtime	Y	
8-34-501.2	Emission Control System Downtime	Y	
8-34-501.3	Continuous Temperature Records for Enclosed Combustors	Y	
8-34-501.4	Testing	Y	
8-34-501.6	Leak Discovery and Repair Records	Y	
8-34-501.7	Waste Acceptance Records	Y	
8-34-501.8	Non-decomposable Waste Records	Y	
8-34-501.9	Wellhead Excesses and Repair Records	Y	
8-34-501.10	Gas Flow Rate Records for All Emission Control Systems	Y	
8-34-501.12	Records Retention for 5 Years	Y	
8-34-503	Landfill Gas Collection and Emission Control System Leak Testing	Y	
8-34-504	Portable Hydrocarbon Detector	Y	
8-34-505	Well Head Monitoring	Y	
8-34-506	Landfill Surface Monitoring	Y	
8-34-507	Continuous Temperature Monitor and Recorder	Y	

IV. Source-Specific Applicable Requirements

Table IV - A
Source-Specific Applicable Requirements
S-1: LANDFILL WITH GAS COLLECTION SYSTEM AND
A-3: LANDFILL GAS FLARE

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
8-34-508	Gas Flow Meter	Y	
8-34-510	Cover Integrity Monitoring	Y	
BAAQMD Regulation 8, Rule 40	Organic Compounds – Aeration of Contaminated Soil and Removal of Underground Storage Tanks (12/15/99)		
8-40-110	Exemption, Storage Pile	Y	
8-40-112	Exemption, Sampling	Y	
8-40-113	Exemption, Non-Volatile Hydrocarbons	Y	
8-40-118	Exemption, Aeration Projects of Limited Impact	Y	
8-40-301	Uncontrolled Contaminated Soil Aeration	Y	
8-40-304	Active Storage Piles	Y	
8-40-305	Inactive Storage Piles	Y	
BAAQMD Regulation 9, Rule 1	Inorganic Gaseous Pollutants – Sulfur Dioxide (3/15/95)		
9-1-301	Limitations on Ground Level Concentrations (applies to flare only)	Y	
9-1-302	General Emission Limitations (applies to flare only)	Y	
BAAQMD Regulation 9, Rule 2	Inorganic Gaseous Pollutants – Hydrogen Sulfide (10/6/99)		
9-2-301	Limitations on Hydrogen Sulfide	N	
40 CFR Part 60, Subpart A	Standards of Performance for New Stationary Sources – General Provisions (5/4/98)		
60.4(b)	Requires Submission of Requests, Reports, Applications, and Other Correspondence to the Administrator	Y	
60.7	Notification and Record Keeping	Y	
60.8	Performance Tests	Y	
60.11	Compliance with Standards and Maintenance Requirements	Y	
60.11(a)	Compliance determined by performance tests	Y	
60.11(d)	Good air pollution control practice	Y	
60.12	Circumvention	Y	
60.13	Monitoring Requirements	Y	

IV. Source-Specific Applicable Requirements

Table IV - A
Source-Specific Applicable Requirements
S-1: LANDFILL WITH GAS COLLECTION SYSTEM AND
A-3: LANDFILL GAS FLARE

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
60.13(a)	Applies to all continuous monitoring systems	Y	
60.13(b)	Monitors shall be installed and in operation before performing performance tests	Y	
60.13(e)	Continuous monitors shall operate continuously	Y	
60.13(f)	Monitors shall be installed in proper locations	Y	
60.13(g)	Multiple monitors are required for multiple stacks	Y	
60.14	Modification	Y	
60.15	Reconstruction	Y	
60.19	General Notification and Reporting Requirements	Y	
40 CFR Part 60, Subpart WWW	Standards of Performance for New Stationary Sources – Standards of Performance for Municipal Solid Waste Landfills (2/24/99)		
60.752	Standards for Air Emissions from Municipal Solid Waste Landfills	Y	
60.752(b)	Requirements for MSW Landfills with Design Capacity equal to or greater than 2.5 million Mg and 2.5 million m ³ (Large Designated Facilities)	Y	
60.752(b)(2)	Comply with all requirements in sections (b)(2)(i through iv)	Y	
60.752 (b)(2)(i)	Submit a Collection and Control System Design Plan	Y	
60.752 (b)(2)(i)(A)	The collection and control system in the Design Plan shall comply with 60.752(b)(2)(ii)	Y	
60.752 (b)(2)(i)(B)	Design Plan shall include all proposed alternatives to 60.753 through 60.758	Y	
60.752 (b)(2)(i)(C)	Design Plan shall conform to 60.759 (active collection system) or demonstrate sufficiency of proposed alternatives	Y	
60.752 (b)(2)(ii)	Install a collection and control system	Y	
60.752 (b)(2)(iii)	Route collected gases to a control system.	Y	

IV. Source-Specific Applicable Requirements

Table IV - A
Source-Specific Applicable Requirements
S-1: LANDFILL WITH GAS COLLECTION SYSTEM AND
A-3: LANDFILL GAS FLARE

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
60.752 (b)(2)(iii)(B)	Reduce NMOC emissions by 98% by weight or reduce NMOC outlet concentration to less than 20 ppmv as hexane at 3% O ₂ , dry basis, as demonstrated by initial performance test within 180 days of start-up.	Y	
60.752 (b)(2)(iv)	Operate in accordance with 60.753, 60.755, and 60.756	Y	
60.752(c)	Title V Operating Permit Requirements	Y	
60.752(c)(1)	Subject is June 10, 1996 for Landfills new or modified between May 30, 1991 and March 12, 1996	Y	
60.752(c)(2)	Subject date is 90 days after date of commenced construction or modification for newer landfills	Y	
60.753	Operational Standards for Collection and Control Systems	Y	
60.753(a)	Operate a Collection System in each area or cell in which:	Y	
60.753(a)(1)	Active Cell – solid waste in place for 5 years or more	Y	
60.753(a)(2)	Closed/Final Grade – solid waste in place for 2 years or more	Y	
60.753(b)	Operate each wellhead under negative pressure unless:	Y	
60.753(b)(1)	Fire or increased well temperature or to prevent fire	Y	
60.753(b)(2)	Use of geomembrane or synthetic cover (subject to alternative pressure limits)	Y	
60.753(b)(3)	Decommissioned well after approval received for shut-down	Y	
60.753(c)	Operate each wellhead at < 55 °C, and either < 20% N ₂ or < than 5% O ₂ (or other approved alternative levels)	Y	
60.753(c)(1)	N ₂ determined by Method 3C	Y	
60.753(c)(2)	O ₂ determined by 3A and as described in (2)(i-v)	Y	
60.753(d)	Surface Leak Limit is less than 500 ppm methane above background at landfill surface. This section also describes some surface monitoring procedures.	Y	
60.753(e)	Vent all collected gases to a control system complying with 60.752(b)(2)(iii). If collection or control system inoperable, shut down gas mover and close all vents within 1 hour	Y	
60.753(f)	Operate the control system at all times when collected gas is routed to the control system	Y	

IV. Source-Specific Applicable Requirements

Table IV - A
Source-Specific Applicable Requirements
S-1: LANDFILL WITH GAS COLLECTION SYSTEM AND
A-3: LANDFILL GAS FLARE

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
60.753(g)	If monitoring demonstrates that 60.753(b), (c), or (d) are not being met, corrective action must be taken	Y	
60.754	Test Methods and Procedures	Y	
60.754(a)	NMOC Calculation Procedures for NMOC Emission Rate Reports and Comparison to 50 Mg/Year Standard	Y	
60.654(a)(1)	Calculate NMOC Emission Rate using either or both of the equations in 60.754(a)(1)(i-ii) with the listed default values	Y	
60.754(a)(1)(i)	Equation for known year-to-year waste acceptance rate	Y	
60.754(a)(1)(ii)	Equation for unknown year-to-year waste acceptance rate	Y	
60.754(a)(2)	Tier 1 – compare calculated NMOC emission rate to 50 Mg/year	Y	
60.754(a)(2)(ii)	If NMOC Emission Rate \geq 50 Mg/year, comply with 60.752(b)(2) or determine a site specific NMOC concentration and follow 60.754(a)(3)	Y	
60.754(c)	For PSD, NMOC emissions shall be calculated using AP-42	Y	
60.754(d)	Test Methods for Performance Test (Method 18 or 25C)	Y	
60.755	Compliance Provisions	Y	
60.755(a)	For Gas Collection Systems	Y	
60.755(a)(1)	Calculation Procedures for Maximum Expected Gas Generation Flow Rate	Y	
60.755(a)(1)(i)	Equation for unknown year-to-year waste acceptance rate	Y	
60.755(a)(1)(ii)	Equation for known year-to-year waste acceptance rate	Y	
60.755(a)(1)(iii)	For closed or inactive and full sites with gas collection systems, actual flow rates may be used	Y	
60.755(a)(2)	Vertical wells and horizontal collectors shall be of sufficient density to meet all performance specifications	Y	
60.755(a)(3)	Measure wellhead pressure monthly. If pressure is positive, take corrective action (final corrective action = expand system within 120 days of initial positive pressure reading)	Y	

IV. Source-Specific Applicable Requirements

Table IV - A
Source-Specific Applicable Requirements
S-1: LANDFILL WITH GAS COLLECTION SYSTEM AND
A-3: LANDFILL GAS FLARE

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
60.755(a)(4)	Expansion not required during first 180 days after startup.	Y	
60.755(a)(5)	Monitor wellheads monthly for temperature and either nitrogen or oxygen. If readings exceed limits, take corrective action up to expanding system within 120 days of first excess.	Y	
60.755(b)	Wells shall be placed in cells as described in design plan and no later than 60 days after:	Y	
60.755(b)(1)	Five years after initial waste placement in cell, for active cells	Y	
60.755(b)(2)	Two years after initial waste placement in cell, for closed/final grade cells.	Y	
60.755(c)	Procedures for complying with surface methane standard	Y	
60.755(c)(1)	Quarterly monitoring of surface and perimeter	Y	
60.755(c)(2)	Procedure for determining background concentration	Y	
60.755(c)(3)	Method 21 except probe inlet placed 5-10 cm above ground	Y	
60.755(c)(4)	Excess is any reading of 500 ppmv or more. Take corrective action indicated below (i-v).	Y	
60.755 (c)(4)(i)	Mark and record location of excess	Y	
60.755 (c)(4)(ii)	Repair cover or adjust vacuum. Re-monitor within 10 calendar days.	Y	
60.755 (c)(4)(iii)	If still exceeding 500 ppmv, take additional corrective action. Re-monitor within 10 calendar days of 2 nd excess.	Y	
60.755 (c)(4)(iv)	Re-monitor within 1 month of initial excess.	Y	
60.755 (c)(4)(v)	For any location with 3 monitored excesses in a quarter, additional collectors (or other approved collection system repairs) shall be operational within 120 days of 1 st excess.	Y	
60.755(c)(5)	Monitor cover integrity monthly and repair as needed.	Y	
60.755(d)	Instrumentation and procedures for complying with 60.755(c).	Y	
60.755(d)(1)	Portable analyzer meeting Method 21	Y	
60.755(d)(2)	Calibrated with methane diluted to 500 ppmv in air	Y	
60.755(d)(3)	Use Method 21, Section 4.4 instrument evaluation procedures	Y	
60.755(d)(4)	Calibrate per Method 21, Section 4.2 immediately before monitoring.	Y	

IV. Source-Specific Applicable Requirements

Table IV - A
Source-Specific Applicable Requirements
S-1: LANDFILL WITH GAS COLLECTION SYSTEM AND
A-3: LANDFILL GAS FLARE

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
60.755(e)	Provisions apply at all times except during startup, shutdown, or malfunction, provided the duration of these shall not exceed 5 days for collection systems or 1 hour for control systems.	Y	
60.756	Monitoring of Operations	Y	
60.756(a)	For active collection systems, install wellhead sampling port	Y	
60.756(a)(1)	Measure gauge pressure in wellhead on a monthly basis	Y	
60.756(a)(2)	Measure nitrogen or oxygen concentration in wellhead gas on a monthly basis.	Y	
60.756(a)(3)	Measure temperature of wellhead gas on a monthly basis.	Y	
60.756(b)	Enclosed combustors shall comply with (b)(1) and (b)(2)	Y	
60.756(b)(1)	Temperature monitor and continuous recorder (not required for boilers and process heaters with capacity > 44 MW)	Y	
60.756(b)(2)	Device that records flow to or bypass of the control device (i or ii below)	Y	
60.756(b)(2)(i)	Install, calibrate, and maintain a device that records flow to the control device at least every 15 minutes	Y	
60.756(b)(2)(ii)	Secure a bypass valve in closed position with a lock-and-key configuration and inspect seal and lock monthly	Y	
60.756(e)	Procedures for requesting alternative monitoring parameters	Y	
60.756(f)	Monitor surface on a quarterly basis. Closed landfills with no monitored exceedences in 3 consecutive quarters may reduce monitoring frequency to an annual basis	Y	
60.757	Reporting Requirements	Y	
60.757(a)	Submit an Initial Design Capacity Report	Y	
60.757(a)(3)	Amended Design Capacity Report required within 90 days of receiving a permitted increase in design capacity or within 90 days of an annual density calculation that results in a design capacity over the thresholds	Y	
60.757(b)	Submit Initial and Annual NMOC Emission Rate Report	Y	
60.757(b)(3)	Sites with Collection and Control Systems operating in compliance with this subpart are exempt from (b)(1) and (b)(2)	Y	

IV. Source-Specific Applicable Requirements

Table IV - A
Source-Specific Applicable Requirements
S-1: LANDFILL WITH GAS COLLECTION SYSTEM AND
A-3: LANDFILL GAS FLARE

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
60.757(c)	Submit a Collection and Control System Design Plan within 1 year of first NMOC emission rate report showing NMOC > 50 MG/year, except as follows	Y	
60.757(f)	Submit Annual Reports containing information required by (f)(1) through (f)(6)	Y	
60.757(f)(1)	Value and length of time for exceedance of parameters monitored per 60.756(a), (b) or (d)	Y	
60.757(f)(2)	Description and duration of all periods when gas is diverted from the control device by a by-pass line	Y	
60.757(f)(3)	Description and duration of all periods when control device was not operating for more than 1 hour	Y	
60.757(f)(4)	All periods when collection system was not operating for more than 5 days.	Y	
60.757(f)(5)	Location of each surface emission excess and all re-monitoring dates and concentrations.	Y	
60.757(f)(6)	Location and installation dates for any wells or collectors added as a result of corrective action for a monitored excess.	Y	
60.757(g)	Initial Performance Test Report Requirements (g)(1-6)	Y	
60.757(g)(1)	Diagram of collection system showing positions of all existing collectors, proposed positions for future collectors, and areas to be excluded from control.	Y	
60.757(g)(2)	Basis for collector positioning to meet sufficient density req.	Y	
60.757(g)(3)	Documentation supporting percentage of asbestos or non-degradeable material claims for areas without a collection system.	Y	
60.757(g)(4)	For areas excluded from collection due to non-productivity, calculations and gas generation rates for each non-productive area and the sum for all nonproductive areas.	Y	
60.757(g)(5)	Provisions for increasing gas mover equipment if current system inadequate to handle maximum projected gas flow rate.	Y	
60.757(g)(6)	Provisions for control of off-site migration	Y	
60.758	Recordkeeping Requirements	Y	
60.758(a)	Design Capacity and Waste Acceptance Records (retain 5 years)	Y	

IV. Source-Specific Applicable Requirements

Table IV - A
Source-Specific Applicable Requirements
S-1: LANDFILL WITH GAS COLLECTION SYSTEM AND
A-3: LANDFILL GAS FLARE

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
60.758(b)	Collection and Control Equipment Records (retain for life of control equipment except 5 years for monitoring data)	Y	
60.758(b)(1)	Collection System Records	Y	
60.758(b)(1)(i)	Maximum expected gas generation flow rate	Y	
60.758(b)(1)(ii)	Density of wells and collectors	Y	
60.758(b)(2)	Control System Records - enclosed combustors other than boilers or process heaters with heat input > 44 MW	Y	
60.758(b)(2)(i)	Combustion temperature measured every 15 minutes and averaged over the same time period as the performance test	Y	
60.758(b)(2)(ii)	Percent NMOC reduction achieved by the control device	Y	
60.758(c)	Records of parameters monitored pursuant to 60.756 and periods of operation when boundaries are exceeded (retain for 5 years)	Y	
60.758(c)(1)	Exceedances subject to record keeping are	Y	
60.758(c)(1)(i)	All 3-hour periods when average combustion temperature was more than 28 C below the average combustion temperature during the most recent complying performance test	Y	
60.758(c)(2)	Records of continuous flow to control device or monthly inspection records if seal and lock for bypass valves	Y	
60.758(d)	Plot map showing location of all existing and planned collectors with a unique label for each collector (retain for life of collection system)	Y	
60.758(d)(1)	Installation date and location of all newly installed collectors	Y	
60.758(d)(2)	Records of nature, deposition date, amount, and location of asbestos or non-degradable waste excluded from control	Y	
60.758(e)	Records of any exceedance of 60.753, location of exceedance and re-monitoring dates and data (for wellheads and surface). Retain for 5 years.	Y	
60.759	Specifications for Active Collection Systems	Y	
60.759(a)	Active wells and collectors shall be at sufficient density	Y	
60.759(a)(1)	Collection System in refuse shall be certified by PE to achieve comprehensive control of surface gas emissions	Y	

IV. Source-Specific Applicable Requirements

Table IV - A
Source-Specific Applicable Requirements
S-1: LANDFILL WITH GAS COLLECTION SYSTEM AND
A-3: LANDFILL GAS FLARE

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
60.759(a)(2)	Collection Systems (active or passive) outside of refuse shall address migration control	Y	
60.759(a)(3)	All gas producing areas shall be controlled except as described below (i-iii).	Y	
60.759 (a)(3)(i)	Any segregated area of asbestos or non-degradable material only may be excluded, if documented adequately per 60.758(d).	Y	
60.759 (a)(3)(ii)	Any non-productive areas may be excluded from control, provided total NMOC emissions from all excluded areas is < 1% of total NMOC emissions from landfill. Document amount, location, and age of waste and all calculations for each excluded area.	Y	
60.759 (a)(3)(iii)	For calculating NMOC emissions, values for k and concentration of NMOC that have been previously approved shall be used or defaults if no values were approved. All non-degradable wastes that are being subtracted from total wastes for NMOC calculations must be documented adequately.	Y	
60.759(b)	Gas Collection System Components	Y	
60.759(b)(1)	Must be constructed of PVC, HDPE, fiberglass, stainless steel, or other approved material and of suitable dimensions to convey projected gas amounts and withstand settling, traffic, etc.	Y	
60.759(b)(2)	Collectors shall not endanger liner, shall manage condensate and leachate, and shall prevent air intrusion and surface leaks.	Y	
60.759(b)(3)	Header connection assemblies shall include positive closing throttle valve, seals and couplings to prevent leaks, at least one sampling port, and shall be constructed of PVC, HDPE, fiberglass, stainless steel, or other approved materials.	Y	
60.759(c)	Gas Mover Equipment shall be sized to handle maximum expected gas generation rate over the intended period of use.	Y	
60.759(c)(1)	For existing systems, flow data shall be used to project maximum flow rate.	Y	
60.759(c)(2)	For new systems, shall be calculated per 60.755(a)(1)	Y	

IV. Source-Specific Applicable Requirements

Table IV - A
Source-Specific Applicable Requirements
S-1: LANDFILL WITH GAS COLLECTION SYSTEM AND
A-3: LANDFILL GAS FLARE

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
40 CFR Part 63, Subpart A	National Emission Standards for Hazardous Air Pollutants: General Provisions (3/16/94)		
63.4	Prohibited activities and circumvention	Y	
63.5(b)	Requirements for existing, newly constructed, and reconstructed sources	Y	
63.6(e)	Operation and maintenance requirements and SSM Plan	Y	
63.6(f)	Compliance with non-opacity emission standards	Y	
63.10(b)(2)(i-v)	Records for startup, shutdown, malfunction, and maintenance	Y	
63.10(d)(5)	Startup, Shutdown, and Malfunction (SSM) Reports	Y	
40 CFR Part 63, Subpart AAAA	National Emission Standards for Hazardous Air Pollutants: Municipal Solid Waste Landfills (1/16/03)		
63.1945	When do I have to comply with this subpart?	Y	
63.1945(b)	Compliance date for existing affected landfills	Y	
63.1955	What requirements must I meet?	Y	
63.1955(a)(1)	Comply with 40 CFR Part 60, Subpart WWW	Y	
63.1955(b)	Comply with 63.1960-63.1985, if a collection and control system is required by 40 CFR Part 60, Subpart WWW or a State Plan implementing 40 CFR Part 60, Subpart Cc	Y	
63.1955(c)	Comply with all approved alternatives to standards for collection and control systems plus all SSM requirements and 6 month compliance reporting requirements	Y	
63.1960	How is compliance determined?	Y	
63.1965	What is a deviation?	Y	
63.1975	How do I calculate the 3-hour block average used to demonstrate compliance?	Y	
63.1980	What records and reports must I keep and submit?	Y	
63.1980(a)	Comply with all record keeping and reporting requirements in 40 CFR Part 60, Subpart WWW or the State Plan implementing 40 CFR Part 60, Subpart Cc, except that the annual report required by 40 CFR 60.757(f) must be submitted every 6 months	Y	

IV. Source-Specific Applicable Requirements

Table IV - A
Source-Specific Applicable Requirements
S-1: LANDFILL WITH GAS COLLECTION SYSTEM AND
A-3: LANDFILL GAS FLARE

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
63.1980(b)	Comply with all record keeping and reporting requirements in 40 CFR Part 60, Subpart A and 40 CFR Part 63, Subpart A, including SSM Plans and Reports	Y	
BAAQMD Condition #8366			
Part 1	Permitted Refuse Capacity (Cumulative Increase, Offsets, and Toxic Risk Management Policy)	Y	
Part 2	Number of Authorized Wells in Gas Collection System (Regulations 2-1-301, 8-34-301.1, and 8-34-305)	Y	
Part 3	Refuse Disposal Records (Cumulative Increase and Regulations 2-6-501 and 8-34-304)	Y	
Part 4	Landfill Gas Collection System – Continuous Operation (Regulations 8-34-301 and 8-34-305)	Y	
Part 5	Abatement Requirement for Collected Landfill Gas (Regulation 8-34-301)	Y	
Part 6	Flare Temperature Requirements (Regulation 8-34-301, Toxic Risk Management Policy, RACT, and 40 CFR 60.758(c)(1)(i))	Y	
Part 7	Temperature Monitor for Flare (Regulation 8-34-507)	N	
Part 8	NOx Emissions Limit (RACT and Offsets)	Y	
Part 9	CO Emissions Limit (RACT and Offsets)	Y	
Part 10	Annual Source Test Requirements (Regulations 8-34-301.3 and 8-34-412 and 40 CFR 60.752(b)(2)(iii)(B))	Y	
Part 11	Flare Heat Input Limits (Regulation 2-1-301)	Y	
Part 12	Surrogate SO2 Monitoring (Regulations 9-1-302 and 2-6-503)	Y	
Part 13	Dust Control Watering Requirements (Regulations 6-301 and 1-301)	Y	
Part 14	Requirement to Keep Paved Roadways Clean (Regulations 6-301 and 1-301)	Y	
Part 15	Visible Emissions – Particulate Fallout Restrictions (Regulations 6-301 and 1-301)	Y	
Part 16	Site Watering – Road Cleaning Records (Regulation 2-6-501)	Y	
Part 17	Low VOC laden soils for landfill cover (Regulations 8-40-205 and 8-40-604)	Y	

IV. Source-Specific Applicable Requirements

Table IV - A
Source-Specific Applicable Requirements
S-1: LANDFILL WITH GAS COLLECTION SYSTEM AND
A-3: LANDFILL GAS FLARE

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
Part 18	Handling Procedures for Soil Containing Volatile Organic Compounds (Regulations 8-40-301, 8-40-304, and 8-40-305)	Y	
Part 19	Reporting periods and report submittal due dates for the Regulation 8, Rule 34 report (Regulation 8-34-411 and 40 CFR 63.1980(a))	Y	

1. This section has been removed from BAAQMD Regulations because it has been superseded. Nevertheless, the source must comply with this regulation until US EPA has reviewed and approved (or disapproved) the District's revision of the regulation.

Table IV - B
Source-Specific Applicable Requirements
S-5: WOOD WASTE STOCKPILES

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
BAAQMD Regulation 6	Particulate Matter and Visible Emissions (12/19/90)		
6-301	Ringelmann No. 1 Limitation	Y	
6-305	Visible Particles	Y	
6-401	Appearance of Emissions	Y	
BAAQMD Condition #15022			
Part 1	Particulate Abatement Requirements (Regulations 6-301 and 1-301)	Y	
Part 2	Visible Emissions – Particulate Fallout Restrictions (Regulations 6-301 and 1-301)	Y	
Part 3	Observation of Emissions Source (Regulations 6-301, 6-305, and 2-1-403)	Y	

IV. Source-Specific Applicable Requirements

Table IV--C
Source-Specific Applicable Requirements
S-9: PORTABLE DIESEL ENGINE

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
BAAQMD Regulation 6	Particulate Matter and Visible Emissions (12/19/90)		
6-303	Ringelmann No. 2 Limitation	Y	
6-303.1	Internal combustion engines below 1500 cubic inches displacement or standby engines	Y	
6-310	Particulate Weight Limitation	Y	
6-401	Appearance of Emissions	Y	
BAAQMD Regulation 9, Rule 1	Inorganic Gaseous Pollutants—Sulfur Dioxide (3/15/95)		
9-1-301	Limitations on Ground Level Concentrations	Y	
9-1-304	Liquid and Solid Fuels	Y	
BAAQMD Condition #17680			
Part 1	Low Sulfur Fuel Requirement, Demonstration of Sulfur Content (Regulation 9-1-304)	Y	
Part 2	Observation of Emissions Source (Regulations 2-1-403 and 6-303)	Y	

Table IV - DC
Source-Specific Applicable Requirements
S-10: PARTS CLEANER

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
BAAQMD Regulation 8, Rule 1	Organic Compounds – General Provisions (6/15/94)		
8-1-320	Storage and Disposal of Solvent Impregnated Cloth or Paper	Y	
8-1-321	Closed Containers for Spent or Fresh Organic Solvents	Y	

IV. Source-Specific Applicable Requirements

Table IV - DC
Source-Specific Applicable Requirements
S-10: PARTS CLEANER

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
BAAQMD Regulation 8, Rule 16	Organic Compounds – Solvent Cleaning Operations (10/16/02)		
8-16-121	Limited Exemption, Single Cold Cleaner	Y	
8-16-122	Limited Exemption, Permitted Cold Cleaners	Y	
8-16-303	Cold Cleaner Requirements	Y	
8-16-303.1	General Operating Requirements	Y	
8-16-303.1.2	Leak Repair Requirement	Y	
8-16-303.1.3	Solvent Storage or Disposal – Evaporation Prevention	Y	
8-16-303.1.4	Waste Solvent Disposal	Y	
8-16-303.1.4(a)	Covered Containers for Waste Solvent Awaiting Pick-up	Y	
8-16-303.1.4(b)	On-site Waste Treatment	Y	
8-16-303.1.5	Solvent Evaporation Minimization Devices shall not be Removed	Y	
8-16-303.1.6	Solvent Spray Requirements	Y	
8-16-303.2	Cold Cleaner Operating Requirements	Y	
8-16-303.2.1	Solvent shall be Drained from Cleaned Parts	Y	
8-16-303.2.2	Solvent Agitation	Y	
8-16-303.2.3	Solvent Cleaning of Porous or Absorbent Materials is Prohibited	Y	
8-16-303.3	Cold Cleaner General Equipment Requirements	Y	
8-16-303.3.1	Container	Y	
8-16-303.3.2	Solvent Evaporation Reduction for Idle Equipment	Y	
8-16-303.3.3	Used Solvent Returned to Container	Y	
8-16-303.3.4	Label Stating Operating Requirements	Y	
8-16-303.4	Control Device (one of the following)	Y	
8-16-303.4.1	Freeboard Ratio ≥ 0.75	Y	
8-16-303.4.2	Water Cover	Y	
8-16-303.4.3	Freeboard Chiller	Y	
8-16-303.4.4	Approved Emission Control Device	Y	
8-16-303.4.5	Enclosed Design	Y	
8-16-501	Solvent Records	Y	
8-16-501.2	Facility-wide Annual Solvent Usage Records	Y	
8-16-501.5	Records Retained for Previous 24 Month Period	Y	

IV. Source-Specific Applicable Requirements

**Table IV - ~~DC~~
 Source-Specific Applicable Requirements
 S-10: PARTS CLEANER**

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
8-16-501.6	Records to Demonstrate Compliance with the Single Cold Cleaner Exemption	Y	
BAAQMD Condition #17682			
Part 1	Solvent Usage Limit (Cumulative Increase)	Y	
Part 2	Monthly Solvent Usage Records (Regulation 2-6-501)	Y	

**Table IV - ~~ED~~
 Source-specific Applicable Requirements
S-9, S-14, S-15, S-16, S-17: SMALL DIESEL IC ENGINES**

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
BAAQMD Regulation 6	Particulate Matter and Visible Emissions (12/19/90)		
6-303	Ringelmann No. 2 Limitation	Y	
6-303.1	Internal combustion engines below 1500 cubic inches displacement or standby engines	Y	
6-310	Particulate Weight Limitation	Y	
6-401	Appearance of Emissions	Y	
BAAQMD Regulation 9, Rule 1	Inorganic Gaseous Pollutants – Sulfur Dioxide (3/15/95)		
9-1-301	Limitations on Ground Level Concentrations	Y	
9-1-304	Liquid and Solid Fuels	Y	
<u>CCR Title 17, Section 93116</u>	<u>Airborne Toxic Control Measure for Diesel Particulate Matter from Portable Engines Rated at 50 Horsepower and Greater (2/26/04)</u>		
<u>93116.3(a)</u>	<u>Fuel Requirements, Portable Diesel Engines</u>	<u>N</u>	
<u>93.116.3(b)</u> <u>(1)</u>	<u>Diesel PM Standards for engines permitted before January 1, 2006</u>	<u>N</u>	<u>1/1/2010</u>

IV. Source-Specific Applicable Requirements

Table IV - ED
Source-specific Applicable Requirements
S-9, S-14, S-15, S-16, S-17: SMALL DIESEL IC ENGINES

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
BAAQMD Condition #21617			
Part 1	Limit on hours of operation (Offsets)	Y	
Part 2	Low sulfur fuel requirement, demonstration of sulfur content (Regulation 9-1-304) CARB Diesel Fuel (Low sulfur fuel) requirement, demonstration of sulfur content (CCR Section 93116.3(a))	Y	
Part 3	Observation of emissions source (Regulation 6-303.1, Regulation 2-1-403)	Y	
Part 4	Recordkeeping requirements (CCR Section 93116.3(a), Offsets, Regulation 9-1-304)	Y	

Table IV - F
Source-specific Applicable Requirements
S-18, S-19, S-20 IC ENGINE GENERATOR SETS

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
BAAQMD Regulation 1	General Provisions and Definitions (5/2/01)		upon start-up
1-523	Parametric Monitoring and Recordkeeping Procedures	N	
1-523.1	Parametric monitor periods of inoperation	Y	
1-523.2	Limit on periods of inoperation	Y	
1-523.3	Reports of Violations	N	
1-523.4	Records	Y	
SIP Regulation 1	General Provisions and Definitions (6/28/99)		upon start-up
1-523	Parametric Monitoring and Recordkeeping Procedures	Y ⁺	
1-523.3	Reports of Violations	Y ⁺	
BAAQMD Regulation 6	Particulate Matter and Visible Emissions (12/19/90)		upon start-up
6-301	Ringelmann No. 1 Limitation	Y	

IV. Source-Specific Applicable Requirements

Table IV – F
Source-specific Applicable Requirements
S-18, S-19, S-20 – IC ENGINE GENERATOR SETS

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
6-305	Visible Particles	Y	
6-310	Particle Weight Limitation	Y	
6-401	Appearance of Emissions	Y	
BAAQMD Regulation 8, Rule 34	Organic Compounds – Solid Waste Disposal Sites (10/6/99)		upon start-up
8-34-113	Limited Exemption, Inspection and Maintenance	Y	
8-34-113.1	— Emission Minimization Requirement	Y	
8-34-113.2	— Shutdown Time Limitation	Y	
8-34-113.3	— Recordkeeping Requirement	Y	
8-34-301	Landfill Gas Collection and Emission Control System Requirements	Y	
8-34-301.1	— Continuous Operation	Y	
8-34-301.2	— Collection and Control Systems Leak Limitations	Y	
8-34-301.4	— Limits for Other Emission Control Systems	Y	
8-34-411	Annual Report	Y	
8-34-412	Compliance Demonstration Tests	Y	
8-34-413	Performance Test Report	Y	
8-34-501	Operating Records	Y	
8-34-501.2	— Emission Control System Downtime	Y	
8-34-501.4	— Testing	Y	
8-34-501.6	— Leak Discovery and Repair Records	Y	
8-34-501.10	— Gas Flow Rate Records for All Emission Control Systems	Y	
8-34-501.11	— Records of Key Emission Control System Operating Parameters	Y	
8-34-501.12	— Records Retention for 5 Years	Y	
8-34-503	Landfill Gas Collection and Emission Control System Leak Testing	Y	
8-34-504	Portable Hydrocarbon Detector	Y	
8-34-509	Key Emission Control System Operating Parameters	Y	
8-34-508	Gas Flow Meter	Y	
BAAQMD Regulation 9, Rule 1	Inorganic Gaseous Pollutants – Sulfur Dioxide (3/15/95)		upon start-up
9-1-301	Limitations on Ground Level Concentrations	Y	
9-1-302	General Emission Limitations	Y	

IV. Source-Specific Applicable Requirements

Table IV – F
Source-specific Applicable Requirements
S-18, S-19, S-20 – IC ENGINE GENERATOR SETS

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
BAAQMD Regulation 9, Rule 2	Inorganic Gaseous Pollutants – Hydrogen Sulfide (10/6/99)		upon start-up
9-2-301	Limitations on Hydrogen Sulfide	N	
BAAQMD Regulation 9 Rule 8	Inorganic Gaseous Pollutants – Nitrogen Oxides and Carbon Monoxide from Stationary Internal Combustion Engines (1/20/93)		upon start-up
9-8-301	Emission Limits – Fossil Derived Fuel Gas	Y	
9-8-301.2	— Lean Burn Engines: NOx Emission Limit	Y	
9-8-301.3	— CO Emission Limit	Y	
9-8-302	Emission Limits – Waste Derived Fuel Gas	Y	
9-8-302.1	— Lean Burn Engines: NOx Emission Limit	Y	
9-8-302.3	— CO Emission Limit	Y	
40 CFR Part 60, Subpart A	Standards of Performance for New Stationary Sources – General Provisions (5/4/98)		upon start-up
60.4(b)	Requires Submission of Requests, Reports, Applications, and Other Correspondence to the Administrator	Y	
60.7	Notification and Recordkeeping	Y	
60.8	Performance Tests	Y	
60.11	Compliance with Standards and Maintenance Requirements	Y	
60.11(a)	— Compliance determined by performance tests	Y	
60.11(d)	— Good air pollution control practice	Y	
60.12	Circumvention	Y	
60.13	Monitoring Requirements	Y	
60.13(a)	— Applies to all continuous monitoring systems	Y	
60.13(b)	— Monitors shall be installed and operation before Performance Tests	Y	
60.13(e)	— Continuous monitors shall operate continuously	Y	
60.13(f)	— Monitors shall be installed in proper locations	Y	
60.13(g)	— Requires multiple monitors for multiple stacks	Y	
60.14	Modification	Y	
60.15	Reconstruction	Y	
60.19	General Notification and Reporting Requirements	Y	

IV. Source-Specific Applicable Requirements

Table IV – F
Source-specific Applicable Requirements
S-18, S-19, S-20 – IC ENGINE GENERATOR SETS

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
40 CFR Part 60, Subpart WWW	Standards of Performance for New Stationary Sources – Standards of Performance for Municipal Solid Waste Landfills (2/24/99)		upon start-up
60.752	Standards for Air Emissions from Municipal Solid Waste Landfills	Y	
60.752(b)	— Comply with paragraph (b)(2) or calculate NMOC emission rate	Y	
60.752(b)(2)	— Comply with all requirements in sections (b)(2)(i through iv)	Y	
60.752 (b)(2)(i)	— Submit a collection and control system design plan	Y	
60.752 (b)(2)(ii)	— Install a collection and control system	Y	
60.752 (b)(2)(iii)	— Route collected gases to a control system	Y	
60.752 (b)(2)(iii)(B)	— Reduce NMOC emissions by 98% by weight or reduce NMOC outlet concentration to less than 20 ppmv as hexane at 3% O ₂ , dry basis	Y	
60.752 (b)(2)(iv)	— Operate in accordance with 60.753, 60.755, and 60.756	Y	
60.753	Operational Standards for Collection and Control Systems	Y	
60.753(e)	— Vent all collected gases to a control system complying with 60.752(b)(2)(iii)	Y	
60.753(f)	— Operate the control system at all times when collected gas is routed to the control system	Y	
60.754	Test Methods and Procedures	Y	
60.754(d)	— Test Methods for Performance Test (Method 18 or 25C)	Y	
60.755	Compliance Provisions	Y	
60.755(e)	— Provisions apply at all times except during startup, shutdown, or malfunction, provided the duration of these shall not exceed 5 days for collection systems or 1 hour for control systems	Y	
60.756	Monitoring of Operations	Y	
60.756(d)	— Approval of other control devices	Y	
60.756(e)	— Procedures for requesting alternative monitoring parameters	Y	
60.757	Reporting Requirements	Y	
60.757(e)	— Submit a Collection and Control System Design Plan	Y	

IV. Source-Specific Applicable Requirements

Table IV – F
Source-specific Applicable Requirements
S-18, S-19, S-20 – IC ENGINE GENERATOR SETS

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
60.757(e)	— Submit Equipment Removal Report 30 days prior to removal or cessation of operation of the control equipment	Y	
60.757(f)	— Submit Annual Reports containing information required by (f)(1), (f)(2), and (f)(3)	Y	
60.757(f)(1)	— Value and length of time for exceedance of parameters monitored per 60.756(b) or (e)	Y	
60.757(f)(2)	— Description and duration of all periods when gas is diverted from the control device by a by pass line	Y	
60.757(f)(3)	— Description and duration of all periods when control device was not operating for more than 1 hour	Y	
60.758	Recordkeeping Requirements	Y	
60.758(b)	— Control Equipment Records	Y	
60.758(b)(2)	— Performance test data for enclosed combustors other than boilers or process heaters (greater than 44 MW heat input)		
60.758(e)	— Records of parameters monitored pursuant to 60.756 (e)	Y	
60.758(e)	— Records of any exceedance of 60.753(e) or (f)	Y	
40 CFR Part 63, Subpart A	National Emission Standards for Hazardous Air Pollutants: General Provisions (3/16/94)		upon start-up
63.4	Prohibited activities and circumvention	Y	
63.5(b)	Requirements for existing, newly constructed, and reconstructed sources	Y	
63.6(e)	Operation and maintenance requirements and SSM Plan	Y	
63.6(f)	Compliance with non opacity emission standards	Y	
63.10(b)(2) (i-v)	Records for startup, shutdown, malfunction, and maintenance	Y	
63.10(d)(5)	Startup, Shutdown, and Malfunction (SSM) Reports	Y	
40 CFR Part 63, Subpart AAAAA	National Emission Standards for Hazardous Air Pollutants: Municipal Solid Waste Landfills (1/16/03)		upon start-up
63.1945	When do I have to comply with this subpart?	Y	
63.1945(b)	Compliance date for existing affected landfills	Y	
63.1955	What requirements must I meet?	Y	
63.1955(a)(2)	Comply with State Plan that implements 40 CFR Part 60, Subpart Ce	Y	

IV. Source-Specific Applicable Requirements

Table IV – F
Source-specific Applicable Requirements
S-18, S-19, S-20 – IC ENGINE GENERATOR SETS

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
63.1955(b)	Comply with 63.1960-63.1985, if a collection and control system is required by 40 CFR Part 60, Subpart WWW or a State Plan implementing 40 CFR Part 60, Subpart Cc	Y	
63.1955(e)	Comply with all approved alternatives to standards for collection and control systems plus all SSM requirements and 6-month compliance reporting requirements	Y	
63.1960	How is compliance determined?	Y	
63.1965	What is a deviation?	Y	
63.1975	How do I calculate the 3-hour block average used to demonstrate compliance?	Y	
63.1980	What records and reports must I keep and submit?	Y	
63.1980(a)	Comply with all record keeping and reporting requirements in 40 CFR Part 60, Subpart WWW or the State Plan implementing 40 CFR Part 60, Subpart Cc, except that the annual report required by 40 CFR 60.757(f) must be submitted every 6 months	Y	
63.1980(b)	Comply with all record keeping and reporting requirements in 40 CFR Part 60, Subpart A and 40 CFR Part 63, Subpart A, including SSM Plans and Reports	Y	
BAAQMD Condition #21619			upon start-up
Part 1	Control requirement for collected landfill gas (Regulation 8-34-301)	Y	
Part 2	Fuel requirements (Cumulative Increase)	Y	
Part 3	Engine heat input limits (Regulation 2-1-301)	Y	
Part 4	Landfill gas flow meter and automatic control valve (Regulations 8-34-301, 8-34-508)	Y	
Part 5	NOx emission limit (BACT, Cumulative Increase)	Y	
Part 6	CO emission limit (BACT, Cumulative Increase)	Y	
Part 7	NMOC emission limit (Cumulative Increase, Regulation 8-34-301.4)	Y	
Part 8	Key emission control system operating parameters (Regulations 8-34-301.4, 8-34-509)	Y	
Part 9	Source test requirements (BACT, Cumulative Increase, Regulations 8-34-301.4, 8-34-412, 9-8-302.1, 9-8-302.3)	Y	
Part 10	Recordkeeping requirements (BACT, Cumulative Increase, Regulation 8-34-501)	Y	

IV. Source-Specific Applicable Requirements

- ~~1. This section has been removed from BAAQMD Regulations because it has been superseded. Nevertheless, the source must comply with this regulation until US EPA has reviewed and approved (or disapproved) the District's revision of the regulation.~~

V. SCHEDULE OF COMPLIANCE

The permit holder shall comply with all applicable requirements cited in this permit. The permit holder shall also comply with applicable requirements that become effective during the term of this permit on a timely basis.

VI. PERMIT CONDITIONS

Any condition that is preceded by an asterisk is not federally enforceable.

Condition # 8366

FOR S-1: LANDFILL WITH GAS COLLECTION SYSTEM AND A-3: LANDFILL GAS FLARE

1. The TriCities Landfill S-1 is permitted for a total refuse capacity of 19,271,000 cubic yards (approximately 13,489,700 tons), with a maximum refuse acceptance rate of 2,628 tons/day. Prior to increasing the design capacity of the landfill, the owner/operator of this site shall first apply for and receive from the District a modified permit to operate. (Basis: Cumulative Increase, Offsets, and Toxic Risk Management Policy)
2. The Permit Holder shall apply for and receive an Authority to Construct before modifying the landfill gas collection system described. Increasing or decreasing the number of wells or collectors, or significantly changing the length of collectors or the locations of wells or collectors are modifications that are subject to the Authority to Construct requirement.

The Permit Holder has been issued a Permit to Operate for the landfill gas collection system components listed below. Well and collector locations, depths, and lengths are as described in detail in Permit Applications # 3515 and 10998.

	<u>Required Components</u>
Total Number of Vertical Wells:	25

In addition, the Permit Holder has been issued an Authority to Construct for modifications to the gas collection system, the details of which are included in Permit Application #15345. The landfill is now authorized for up to a total of 38 vertical gas extraction wells. (Basis: Regulations 2-1-301, 8-34-301.1, and 8-34-305)

3. In order to demonstrate compliance with the above requirements, the S-1 Permit Holder shall maintain the following records:
 - a. Monthly records of the quantity of refuse accepted and placed in the landfill.
 - b. For areas of the landfill not controlled by a landfill gas collection system, the Permit Holder shall maintain a record of the date that waste was initially placed in the area or cell.
 - c. The cumulative amount of waste placed in each uncontrolled area or cell on a monthly basis.

VI. Permit Conditions

Condition # 8366

FOR S-1: LANDFILL WITH GAS COLLECTION SYSTEM AND A-3: LANDFILL GAS FLARE

- d. If the Permit Holder plans to exclude an uncontrolled area or cell from the collection system requirement, the types and amounts of all non-decomposable waste placed in the area or cell shall be recorded. If non-decomposable waste makes up less than 100% of the contents of a given cell, that percentage shall be noted.
- e. The initial operation date for each new landfill gas well and collector.
- f. An accurate map of the landfill that indicates the locations of all refuse boundaries and the locations of all wells and collectors as identified in the Collection and Control System Design Plan. Any areas containing only non-decomposable waste shall be clearly identified. This map shall be updated at least every six months to indicate changes in refuse boundaries and to include any newly installed wells and collectors.

These records shall be kept on-site and be made available for inspection to District personnel upon request for a period of five years from the date on which a record was made. (Basis: Cumulative Increase and Regulations 2-6-501 and 8-34-304)

- 4. The landfill gas collection system described in Part 2 above shall be operated continuously. Wells shall not be disconnected or removed from operation nor shall isolation or adjustment valves be closed without written authorization from the District, unless the Permit Holder complies with all applicable requirements of Regulation 8, Rule 34, Sections 113, 116, 117, and 118. (Basis: Regulations 8-34-301 and 8-34-305)
- 5. All landfill gas collected by the gas collection system for S-1 shall be abated at all times by the Landfill Gas Flare A-3 ~~or the IC Engine Generator Sets S-18, S-19, and S-20 (operation of the IC Engines is subject to Permit Condition #21619).~~ Under no circumstances shall raw landfill gas be vented to the atmosphere. This limitation does not apply to unavoidable landfill gas emissions that occur during collection system installation, maintenance, or repair performed in compliance with Regulation 8, Rule 34, Sections 113, 116, 117, or 118 or to inadvertent component or surface leaks that do not exceed the limits specified in 8-34-301.2 or 8-34-303. (Basis: Regulation 8-34-301)

VI. Permit Conditions

Condition # 8366

FOR S-1: LANDFILL WITH GAS COLLECTION SYSTEM AND A-3: LANDFILL GAS FLARE

6. The combustion zone temperature of the flare shall be maintained at a minimum temperature of 1450 degrees F, averaged over any 3-hour period. If a source test demonstrates compliance with all applicable requirements at a different temperature, the APCO may revise this minimum temperature limit in accordance with the procedures identified in Regulation 2-6-414 or 2-6-415, based on the following criteria. The minimum combustion zone temperature for the flare shall be equal to the average combustion zone temperature determined during the most recent complying source test minus 50 degrees F, provided that the minimum combustion zone temperature is not less than 1400 degrees F. (Basis: Regulation 8-34-301, Toxic Risk Management Policy, RACT, and 40 CFR 60.758(c)(1)(i))
7. The Landfill Gas Flare A-3 shall be equipped with a combustion temperature readout monitor and continuous recorder to measure and record the temperature in the combustion zone. (Basis: Regulation 8-34-507)
8. Emissions of Nitrogen Oxides (NO_x) from the Flare A-3 shall not exceed 0.06 pounds per million BTU (calculated as NO₂). (basis: RACT and Offsets)
9. Emissions of Carbon Monoxide (CO) from the Flare A-3 shall not exceed 0.3 pounds per million BTU. (basis: RACT and Offsets).
10. In order to demonstrate compliance with Regulation 8, Rule 34, Section 301.3, Regulation 9, Rule 1, Section 302, 40 CFR 60 .752(b)(2)(iii)(B), and the above requirements, the Permit Holder shall ensure that a District approved source test is conducted annually on the Landfill Gas Flare (A-3). The annual source test shall determine the following:
 - a. Landfill gas flow rate to the flare (dry basis)
 - b. Concentrations (dry basis) of methane (CH₄) and total non-methane organic compounds (NMOC) in the landfill gas;
 - c. Stack gas flow rate from the flare (dry basis)
 - d. Concentrations (dry basis) of nitrogen oxides (NO_x), carbon monoxide (CO), CH₄, NMOC, and O₂ in the flare stack gas
 - e. The NMOC destruction efficiency achieved by the flare
 - f. The average combustion temperature in the flare during the test period.

VI. Permit Conditions

Condition # 8366

FOR S-1: LANDFILL WITH GAS COLLECTION SYSTEM AND A-3: LANDFILL GAS FLARE

Annual source tests shall be conducted no sooner than 9 months and no later than 12 months after the previous source test. The Source Test Section of the District shall be contacted to obtain its approval of the source test procedures at least 14 days in advance of each source test. The Source Test Section shall be notified of the scheduled test date at least 7 days in advance of each source test. The source test report shall be submitted to the Compliance and Enforcement Division within 60 days after the test date. (Basis: Regulations 8-34-301.3 and 8-34-412 and 40 CFR 60.752(b)(2)(iii)(B))

11. The heat input to the A-3 Flare shall not exceed 1,800 million BTU per day or 657,000 million BTU per year. In order to demonstrate compliance with this part, the Permit Holder shall calculate and record on a monthly basis the maximum daily and total monthly heat input to the flare based on the landfill gas flow rate recorded pursuant to Part10, the average methane concentration in the landfill gas based on the most recent source test, and a high heating value for methane of 1013 BTU/scf. The records shall be retained for five years and shall be made available to the District staff upon request. (Basis: Regulation 2-1-301)
12. Total reduced sulfur compounds in the collected landfill gas shall be monitored as a surrogate for monitoring sulfur dioxide in control systems exhaust. The concentration of total reduced sulfur compounds in the collected landfill gas shall not exceed 1300 ppmv (dry). In order to demonstrate compliance with this part, the Permit Holder shall measure the total sulfur content in collected landfill gas on a quarterly basis using a draeger tube. The landfill gas sample shall be taken from the main landfill gas header. The Permit Holder shall follow the manufacturer's recommended procedures for using the draeger tube and interpreting the results. The Permit Holder shall conduct the first draeger tube test no later than 3 months after the issue date of the MFR Permit and quarterly thereafter.
(Basis: Regulations 9-1-302 and 2-6-503)
13. On rainless operating days, water shall be applied as necessary and at least 2 times per full operational day to all unpaved roadways and active soil removal and fill areas associated with this facility to suppress dust emissions. On operating days when rain has fallen in the last 24 hours, water shall be applied as necessary to prevent visible dust emissions. (Basis: Regulations 6-301 and 1-301)
14. Paved roadways at the facility shall be kept sufficiently clear of dirt and debris as to prevent visible particulate emissions from vehicle traffic or wind. (Basis: Regulations 6-301 and 1-301)

VI. Permit Conditions

Condition # 8366

FOR S-1: LANDFILL WITH GAS COLLECTION SYSTEM AND A-3: LANDFILL GAS FLARE

15. Visible dust emissions from any part of the facility shall not exceed Ringelmann 1.0 or result in fallout on adjacent property in such quantities as to cause a public nuisance. (Basis: Regulations 6-301 and 1-301)
16. In order to demonstrate compliance with Parts 13 and 14, the operator of this facility shall keep records of all site watering and road cleaning activities in a District approved log. These records shall be kept on-site and be made available for inspection to District personnel upon request for a period of five years from the date on which the record was made. (Basis: Regulation 2-6-501)
- ~~17. Low VOC soil (soil that contains 50 ppmw or less of VOC) is not considered to be "contaminated soil" and may be used as daily, intermediate, or final cover material for landfill waste operations if the organic concentration above the soil does not exceed 50 ppmv (expressed as methane, C1). To demonstrate compliance with this requirement, each lot of soil to be used as cover material shall be randomly screened for VOC surface emissions (in such a manner as to be representative of the entire lot) using the testing procedures outlined in Regulation 8-40-604. The Permit Holder shall keep the following records for each lot of soil subject to this requirement:
 - a. The soil lot number as established in part 18m.i. (below).
 - b. The time and date of the soil screening.
 - c. The name and affiliation of the person performing the monitoring.
 - d. The results of the screening and an acknowledgement that the procedures outlined in Regulation 8-40-604 were used.~~Soil presumed to be low VOC soil that is found to have a surface VOC concentration greater than 50 ppmv as described above shall be considered contaminated soil and will be subject to the requirements of part 2 of these conditions. (basis: Regulations 8-40-205, 8-40-604)~~~~

VI. Permit Conditions

Condition # 8366

FOR S-1: LANDFILL WITH GAS COLLECTION SYSTEM AND A-3: LANDFILL GAS FLARE

17. Contaminated soil as defined by Regulation 8-40-205 shall not be used as daily, intermediate, or final cover material for landfill waste operations. Soil that contains small amounts of volatile organic compounds (VOC), but does not meet the definition of “contaminated soil” is considered to be “VOC laden soil” and may be used as cover material providing that the Permit Holder complies with the limits and monitoring procedures identified in either subpart a or subpart b below. (basis: Regulation 8-2-301, Regulation 8-40-301)

a. Randomly screen each lot of VOC laden soil to be used as cover material for VOC surface emissions (in such a manner as to be representative of the entire lot) using the testing procedures outlined in Regulation 8-40-604. The Permit Holder shall keep the following records for each lot of soil subject to this requirement:

i. The soil lot number as established in part 18m.i. (below).

ii. The time and date of the soil screening.

iii. The name and affiliation of the person performing the monitoring.

iv. The results of the screening and an acknowledgement that the procedures outlined in Regulation 8-40-604 were used.

b. Limit the quantity of VOC laden soil used as cover material to 150 tons/day. To demonstrate compliance with this limit, the permit holder shall maintain daily records of the amount (tons) and VOC content (as determined using the testing procedures outlined in Regulation 8-40-602) of all VOC laden soils subject to this requirement.

Records shall be maintained on site in a District approved log and shall be made readily available to District staff upon request for at least 5 years from the date on which a record was made.

18. Handling Procedures for Soil Containing Volatile Organic Compounds

a. The procedures listed below in subparts b-1 do not apply if the following criteria are satisfied. However, the record keeping requirements in subpart m, below, are applicable.

i. The Permit Holder has appropriate documentation demonstrating that either the organic content of the soil or the organic concentration above the soil is below the “contaminated” level (as defined in Regulation 8, Rule 40, Sections 205, 207, and 211). The handling of soil containing VOCs in concentrations below the “contaminated” level is subject to Part 17 above.

ii. The Permit Holder has no documentation to prove that soil is not contaminated, but source of the soil is known and there is no reason to suspect that the soil might contain organic compounds.

Condition # 8366

VI. Permit Conditions

FOR S-1: LANDFILL WITH GAS COLLECTION SYSTEM AND A-3: LANDFILL GAS FLARE

- b. The Permit Holder shall provide notification to the Compliance and Enforcement Division of the Permit Holder's intention to accept contaminated soil at the facility at least 24 hours in advance of receiving the contaminated soil. The Permit Holder shall provide an estimate of the amount of contaminated soil to be received, the degree of contamination (range and average VOC Content), and the type or source of contamination.
- c. Any soil received at the facility that is known or suspected to contain volatile organic compounds (VOCs) shall be handled as if the soil were contaminated, unless the Permit Holder receives test results proving that the soil is not contaminated. To prove that the soil is not contaminated, the Permit Holder shall collect soil samples in accordance with Regulation 8-40-601 within 24 hours of receipt of the soil by the facility. The organic content of the collected soil samples shall be determined in accordance with Regulation 8-40-602.
 - i. If these test results indicate that the soil is still contaminated or if the soil was not sampled within 24 hours of receipt by the facility, the Permit Holder must continue to handle the soil in accordance with the procedures set forth in subparts e.-l. below, until the soil has completed treatment or has been placed in a final disposal location and adequately covered. Storing soil in a temporary stockpile or pit is not considered treatment. Co-mingling, blending, or mixing of soil lots is not considered treatment.
 - ii. If these test results indicate that the soil – as received at the facility – has an organic content of 50 ppmw or less, then the soil may be considered to be not contaminated and need not be handled in accordance with the procedures listed in subparts e.-l. below.
- d. Any contaminated soil received at the facility shall be clearly identified as contaminated soil, shall be handled in accordance with subparts e.-l. below, and shall be segregated from non-contaminated soil. Contaminated soil lots may not be co-mingled, blended, or otherwise mixed with non-contaminated soil lots prior to treatment, reuse, or disposal. Mixing soil lots in an attempt to reduce the overall concentration of the contaminated soil or to circumvent any requirements or limits is strictly prohibited.

VI. Permit Conditions

Condition # 8366

FOR S-1: LANDFILL WITH GAS COLLECTION SYSTEM AND A-3: LANDFILL GAS FLARE

- e. On-site handling of contaminated soil shall be limited to no more than 2 on-site transfers per soil lot. For instance, unloading soil from off-site transport vehicles into a temporary storage pile is 1 transfer. Moving soil from a temporary storage to a staging area is 1 transfer. Moving soil from a temporary storage pile to a final disposal site is 1 transfer. Moving soil from a staging area to a final disposal site is 1 transfer. Therefore, unloading soil from off-site transport into a temporary storage pile and then moving the soil from that temporary storage pile to the final disposal site is allowed. Unloading soil from off-site transport into a staging area and then moving the soil from that staging area to the final disposal site is allowed. However, unloading soil from off-site transport to a temporary storage pile, moving this soil to a staging area, and then moving the soil again to a final disposal site is 3 on-site transfers and is not allowed.
- f. If the contaminated soil has an organic content of less than 500 ppmw, the contaminated soil shall be treated, deposited in a final disposal site, or transported off-site for treatment within 90 days of receipt at the facility.
- g. If the contaminated soil has an organic content 500 ppmw or more, the contaminated soil shall be treated, deposited in a final disposal site, or transported off-site for treatment within 45 days of receipt at the facility.
- h. All active storage piles shall meet the requirements of Regulation 8-40-304 by using water sprays, vapor suppressants or approved coverings to minimize emissions. The exposed surface area of any active storage pile (including the active face at a landfill) shall be limited to 6000 ft². The types of storage piles that may become subject to these provisions include (but are not limited to) truck unloading areas, staging areas, temporary stockpiles, soil on conveyors, bulldozers or trucks, the active face of a landfill, or other permanent storage pile at the final disposal location.
- i. All inactive storage piles shall meet the requirements of Regulation 8-40-305 including the requirement to cover contaminated soil during periods of inactivity longer than one hour. The types of storage piles that may become subject to these provisions include (but are not limited to) soil on trucks or other on-site equipment, staging areas, temporary stockpiles, and the permanent storage pile at the final disposal location. District approved coverings for inactive storage piles include continuous heavy-duty plastic sheeting (in good condition, joined at the seams, and securely anchored) or encapsulating vapor suppressants (with re-treatment as necessary to prevent emissions).

VI. Permit Conditions

Condition # 8366

FOR S-1: LANDFILL WITH GAS COLLECTION SYSTEM AND A-3: LANDFILL GAS FLARE

- j. The Permit Holder must:
 - i. Keep contaminated soil covered with continuous heavy-duty plastic sheeting (in good condition, joined at the seams, and securely anchored) whenever soil is to be stored in temporary stockpiles or during on-site transport in trucks. Soil in trucks shall not be left uncovered for more than 1 hour.
 - ii. Establish a tipping area for contaminated soils near the active face that is isolated from the tipping area for other wastes.
 - iii. Spray contaminated soil with water or vapor suppressant immediately after dumping the soil from a truck at the tipping area.
 - iv. Ensure that all contaminated soil is transferred from the tipping area to the active face immediately after spraying with water or vapor suppressant.
 - v. Ensure that contaminated soil in the tipping area is not disturbed by subsequent trucks. Trucks shall not drive over contaminated soil in the tipping area or track contaminated soil out of the tipping area on their wheels.
 - vi. Spray contaminated soil on the active face with water or vapor suppressant (to keep the soil visibly moist) until the soil can be covered with an approved covering.
 - vii. Limit the area of exposed soil on the active face to no more than 6000 ft².
 - viii. Ensure that contaminated soil spread on the active face is completely covered on all sides with one of the following approved coverings: at least 6 inches of clean compacted soil, at least 12 inches of compacted garbage, or at least 12 inches of compacted green waste.
 - ix. Ensure that covering of soil on the active face is completed within one hour of the time that the soil was first dumped from a truck at the tipping area.
- k. Contaminated soil shall not be used as daily, intermediate, or final cover material for landfill waste operations unless the requirements of Regulation 8, Rule 40, Sections 116 or 117 have been satisfied.
- l. Contaminated soil is considered to be a decomposable solid waste pursuant to Regulation 8, Rule 34. All contaminated soil disposed of at a site shall be included in any calculations of the amount of decomposable waste in place that are necessary for annual reporting requirements or for purposes of 8-34-111 or 8-34-304.

VI. Permit Conditions

Condition # 8366

FOR S-1: LANDFILL WITH GAS COLLECTION SYSTEM AND A-3: LANDFILL GAS FLARE

- m. The Permit Holder shall keep the following records for each lot of soil received, in order to demonstrate on-going compliance with the applicable provisions of Regulation 8, Rule 40.
 - i. For all soil received by the facility (including soil with no known contamination), record the arrival date at the facility, the soil lot number, the amount of soil in the lot, the organic content or organic concentration of the lot (if known), the type of contamination (if any), and keep copies of any test data or other information that documents whether the soil is contaminated (as defined in 8-40-205) or not contaminated, with what, and by how much.
 - ii. If the soil is tested for organic content after receipt by the facility, a report with the sampling date, test results, and the date results were received.
 - iii. For all on-site handling of contaminated soil, use a checklist or other approved method to demonstrate that appropriate procedures were followed during all on-site handling activities. One checklist shall be completed for each day and for each soil lot (if multiple lots are handled per day).
 - iv. For soil aerated in accordance with 8-40-116 or 117 record the soil lot number, the amount of soil in the lot, the organic content, the final placement date, the final placement location, and describe how the soil was handled or used on-site.
 - v. For final disposal at a landfill, record on a daily basis the soil lot number, the amount of soil placed in the landfill, the disposal date, and the disposal location.

All records shall be retained for at least 5 years from the date of entry and shall be made available for District inspection upon request.

(Basis: Regulations 8-40-301, 8-40-304 and 8-40-305)

VI. Permit Conditions

Condition # 8366

FOR S-1: LANDFILL WITH GAS COLLECTION SYSTEM AND A-3: LANDFILL GAS FLARE

19. The annual report required by BAAQMD Regulation 8-34-411 shall be submitted in two semi-annual increments. The reporting periods and report submittal due dates for the semi-annual increments of the Regulation 8-34-411 report and the MSW Landfill NESHAP report, which is required pursuant to 40 CFR Part 63.1980(a), shall be synchronized with the reporting periods and report submittal due dates for the semi-annual MFR Permit monitoring reports that are required by Section I.F of the MFR Permit for this site. A single report may be submitted to satisfy the requirements of Section I.F, Regulation 8-34-411, and 40 CFR Part 63.1980(a), provided that all items required by each applicable reporting requirement are included in the single report.
(Basis: Regulation 8-34-411 and 40 CFR Part 63.1980(a))

Condition # 15022

FOR S-5: WOOD WASTE STOCKPILES

1. Water spray (A-1), minimized drop height, and other particulate reducing techniques shall be used as necessary to minimize particulate emissions from the wood debris stockpiling operations. (Basis: Regulations 6-301 and 1-301)
2. Visible emissions shall not exceed Ringelmann 1.0 nor shall it result in fallout on adjacent properties in sufficient quantities as to cause a public nuisance per Regulation 1-301. (Basis: Regulations 6-301 and 1-301)
3. Observation for visible particulate emissions is required each time material to added to or removed from the Wood Waste Stockpiles. If visible emissions are detected, the operator of the source shall take the necessary corrective action to stop the emissions. (Basis: Regulations 6-301, 6-305, and 2-1-403)

Condition # 17680

~~FOR S-9: PORTABLE DIESEL ENGINE~~

- ~~1. Only low sulfur fuel (<0.5% sulfur by weight) shall be combusted at S-9. The maximum sulfur content of the fuel shall be demonstrated by vendor certification. (Basis: Regulation 9-1-304)~~
- ~~2. The exhaust of the Portable Diesel Engine for shall be observed for visible smoke during all periods of operation. If persistent smoke is detected, the operator of the~~

VI. Permit Conditions

~~source shall take the necessary corrective action to stop the emissions. (Basis: Regulations 2-1-403 and 6-303)~~

Condition # 17682

FOR S-10: PARTS CLEANER

1. The net solvent usage at the Parts Cleaner S-10 shall not exceed 150 gallons during any consecutive 12-month period. (Basis: Cumulative Increase).
2. In order to demonstrate compliance with part #1 of this condition, monthly records of the amount of make-up solvent added to S-10 shall be recorded in a District approved log. These records shall be kept on site and be available for District inspection for a period of at least 5 years from the date on which the record was made. (Basis: Regulation 2-6-501)

Condition # 21617

For S-9, S-14, S-15, S-16, S-17: ~~Small-Portable~~ Diesel IC Engines

1. The Diesel Engines S-9, S-14, S-15, S-16, and S-17 shall each be limited to 1,456 hours per year of operation. Each engine shall be equipped with a non-resettable totalizing meter that measures and records the hours of operation for the engine. (basis: Offsets)
2. ~~Only low sulfur fuel (<0.5% sulfur by weight) shall be combusted at these engines. The maximum sulfur content of the fuel shall be demonstrated by vendor certification. (basis: Regulation 9-1-304)~~Only CARB Diesel Fuel (<0.05% sulfur by weight) or approved alternative shall be combusted by these engines. The maximum sulfur content of the fuel shall be demonstrated by vendor certification. (basis: CCR Section 93116.3(a))

VI. Permit Conditions

Condition # 21617

For S-9, S-14, S-15, S-16, S-17: ~~Small Portable~~ Diesel IC Engines

3. The exhaust of these engines shall be observed for visible smoke during all periods of operation. If persistent smoke is detected, the operator of the source shall take the necessary corrective action to stop the emissions. (basis: Regulation 6-303.1, Regulation 2-1-403)
4. In order to demonstrate compliance with the above requirements, the operator of these engines shall keep the following records in a District approved log. These records shall be updated on at least a monthly basis, kept on-site, and be available for District inspection for at least 5 years from the date on which a record was made. (basis: CCR Section 93116.3(a), Offsets, Regulation ~~9-1-304~~ 1-441)
 - a. operating hours for each engine
 - b. fuel usage
 - ~~b.c.~~ vendor certified fuel sulfur content

Condition # 21619

For S-18, S-19, S-20: IC Engine Generator Sets

- ~~1. All collected landfill gas shall be vented to properly operating abatement equipment including the IC Engines S-18, S-19, and S-20 and/or the Landfill Gas Flare A-3. Raw landfill gas shall not be vented to the atmosphere, except for unavoidable landfill gas emissions that occur during control system installation, maintenance, or repair that is performed in compliance with Regulation 8, Rule 34, Sections 113, 116, 117, or 118 and for inadvertent component or surface leaks that do not exceed the limits specified in 8-34-301.2 or 8-34-303. (basis: Regulation 8-34-301)~~
- ~~2. The IC Engines S-18, S-19, and S-20 shall be fired on landfill gas. If required, natural gas can be used as a supplemental fuel, but it shall not reduce or replace landfill gas available for use in this engine. Natural gas shall not be used as supplemental fuel when the A-3 Flare is operating concurrently with these engines. (basis: Cumulative Increase)~~

VI. Permit Conditions

Condition # 21619

For S-18, S-19, S-20: IC Engine Generator Sets

- ~~3. The Heat Input to each of the IC Engines S-18, S-19, and S-20 shall not exceed 252 million BTU per day and shall not exceed 91,980 million BTU per year. In order to demonstrate compliance with this part, the Permit Holder shall calculate and record on a monthly basis the maximum daily and total monthly heat input to the engine based on (a) the landfill gas flow rate recorded pursuant to part 4, (b) the average methane concentration in the landfill gas based on the most recent source test, and (c) a high heating value for methane of 1013 BTU/cubic foot at 60 degrees F. (basis: Regulation 2-1-301)~~
- ~~4. A District approved flow meter, to measure and record the landfill gas flow into each engine, shall be installed prior to any operation and maintained in good working condition. An automatically controlled landfill gas valve shall be installed, and maintained to ensure that landfill gas is immediately made available for flaring to the A-3 Landfill Gas Flare when the engine is down. (basis: Regulation 8-34-301, Regulation 8-34-508)~~
- ~~5. Emissions of Nitrogen Oxides (NO_x) from each of the IC Engines S-18, S-19, and S-20 shall not exceed either 0.6 grams of NO_x, calculated as NO₂/ per brake horsepower-hour or 37 ppmv of NO_x, @ 15% oxygen, dry basis. (basis: BACT, Cumulative Increase)~~
- ~~6. Emissions of Carbon Monoxide (CO) from each of the IC Engines S-18, S-19, and S-20 shall not exceed either 2.1 grams of CO/ per brake horsepower hour or 215 ppmv of CO @ 15% oxygen, dry basis. (basis: BACT, Cumulative Increase)~~
- ~~7. Emissions of Non-Methane Organic Compounds (NMOC) from each of the IC Engines S-18, S-19, and S-20 shall be less than 120 ppm by volume (dry), expressed as methane @ 3% oxygen. (basis: Cumulative Increase, Regulation 8-34-301.4)~~

VI. Permit Conditions

Condition # 21619

For S-18, S-19, S-20: IC Engine Generator Sets

- ~~8. In order to demonstrate compliance with part 7, the permit holder of these IC Engines shall determine key emission control system operating parameter(s) that are indicative of NMOC destruction efficiency and that can be monitored. The permit holder shall submit a proposal for the key emission control system operating parameter(s) that will be measured during the initial source test and monitored during subsequent engine operation to the Source Test Section and to the Permit Services Division at least 14 days prior to conducting the initial source test required by Part 9. The specific operating parameter, allowable operating range, type and location of monitors, and monitoring frequency shall be added to this part via a minor permit revision after the District has received the results of the initial source test. Within 105 days of start-up of S-18, S-19, and S-20, the key emission control system operating parameter(s) shall be maintained within the range established by the most recent source test, during all times that the IC Engine is operated. (basis: Regulations 8-34-301.4 and 8-34-509)~~

- ~~9. In order to demonstrate compliance with parts 5, 6 and 7 above and Regulations 8-34-301.4, 9-8-302.1 and 9-8-302.3, the permit holder shall conduct source testing of S-18, S-19, and S-20 to determine the emissions of NO_x, CO, and NMOC and the destruction efficiency for NMOC. In addition, the operating range for each key emission control system operating parameter required by part 8 shall be determined by each test. An initial source test shall be performed within 60 days of startup, followed by annual source tests thereafter. All source testing shall be performed in accordance with the Manual of Procedures. The facility shall obtain prior approval from the Source Test Manager for the location of sampling ports and source testing procedures. The Source Test Section shall be notified of the scheduled test date at least 7 days in advance of each source test. All source test results shall be delivered to the Compliance and Enforcement Division and to the Source Test Section within 45 days of the date of the test. The time interval between source testing shall not exceed 12 months. (basis: BACT, Cumulative Increase, Regulations 8-34-301.4, 8-34-412, 9-8-302.1, and 9-8-302.3)~~

VI. Permit Conditions

Condition # 21619

~~For S-18, S-19, S-20: IC Engine Generator Sets~~

- ~~10. The owner/operator of the IC Engines S-18, S-19, and S-20 shall maintain the following records in a District approved log:~~
- ~~a. The times and dates of all startups and shutdowns for each engine and the reason for each shutdown.~~
 - ~~b. The total landfill gas and natural gas throughput to each engine on a monthly basis.~~
 - ~~c. Records of key emission control system operating parameters for each engine on at least a monthly basis.~~
 - ~~d. All source test results.~~
 - ~~e. The operating times and the landfill gas flow rate to each engine on a daily basis, summarized monthly.~~
 - ~~f. The heat input to each engine, pursuant to part 3 above.~~
- ~~All records shall be maintained on site for a minimum of 5 years and shall be made available for inspection by District personnel upon request. (basis: BACT, Cumulative Increase, Regulation 8-34-501)~~

VII. APPLICABLE LIMITS & COMPLIANCE MONITORING REQUIREMENTS

This section has been included only to summarize the applicable emission limits contained in Section IV, Source-Specific Applicable Requirements, of this permit. The following tables show the relationship between each emission limit and the associated compliance monitoring provisions, if any. The monitoring frequency column indicates whether periodic (P) or continuous (C) monitoring is required. For periodic monitoring, the frequency of the monitoring has also been shown, using the following codes: annual (A), quarterly (Q), monthly (M), weekly (W), daily (D), or on an event basis (E). No monitoring (N) has been required if the current applicable rule or regulation does not require monitoring, and the operation is unlikely to deviate from the applicable emission limit based upon the nature of the operation.

This section is only a summary of the limits and monitoring requirements. In the case of a conflict with any requirement in Sections I-VI, the preceding sections take precedence over Section VII.

Table VII – A
Applicable Limits and Compliance Monitoring Requirements
S-1: LANDFILL WITH GAS COLLECTION SYSTEM AND
A-3: LANDFILL GAS FLARE

Type of Limit	Citation of Limit	FE Y/N	Future Effective Date	Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
Collection System Installation Dates	BAAQMD 8-34-304.1	Y		For Inactive/Closed Areas: collection system components must be installed and operating by 2 years + 60 days after initial waste placement	BAAQMD 8-34-501.7 and 501.8 and BAAQMD Condition #8366, Part 3	P/E	Records
Collection System Installation Dates	BAAQMD 8-34-304.2	Y		For Active Areas: Collection system components must be installed and operating by 5 years + 60 days after initial waste placement	BAAQMD 8-34-501.7 and 501.8 and BAAQMD Condition #8366, Part 3	P/E	Records

VII. Applicable Limits and Compliance Monitoring Requirements

Table VII – A
Applicable Limits and Compliance Monitoring Requirements
S-1: LANDFILL WITH GAS COLLECTION SYSTEM AND
A-3: LANDFILL GAS FLARE

Type of Limit	Citation of Limit	FE Y/N	Future Effective Date	Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
Collection System Installation Dates	BAAQMD 8-34-304.3	Y		For Any Uncontrolled Areas or Cells: collection system components must be installed and operating within 60 days after the uncontrolled area or cell accumulates 1,000,000 tons of decomposable waste	BAAQMD 8-34-501.7 and 501.8 and BAAQMD Condition #8366, Part 3	P/E	Records
Collection System Installation Dates	40 CFR 60.753 (a)(2) and 60.755 (b)(2)	Y		For Inactive/Closed Areas: collection system components must be installed and operating by 2 years + 60 days after initial waste placement	40 CFR 60.758(a), (d)(1) and (d)(2), and 60.759(a)(3)	P/E	Records
Collection System Installation Dates	40 CFR 60.753 (a)(1) and 60.755 (b)(1)	Y		For Active Areas: Collection system components must be installed and operating by 5 years + 60 days after initial waste placement	40 CFR 60.758(a), (d)(1) and (d)(2)	P/E	Records
Gas Flow	BAAQMD 8-34-301 and 301.1 and BAAQMD Condition #8366, Parts 4, 5	Y		Landfill gas collection system shall operate continuously and all collected gases shall be vented to a properly operating control system	BAAQMD 8-34-501.1, 501.2	P/E	Records of Collection and Control System Downtime

VII. Applicable Limits and Compliance Monitoring Requirements

Table VII – A
Applicable Limits and Compliance Monitoring Requirements
S-1: LANDFILL WITH GAS COLLECTION SYSTEM AND
A-3: LANDFILL GAS FLARE

Type of Limit	Citation of Limit	FE Y/N	Future Effective Date	Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
Gas Flow	BAAQMD 8-34-301 and 301.1	Y		Landfill gas collection system shall operate continuously and all collected gases shall be vented to a properly operating control system	BAAQMD 8-34-501.10 and 508	C	Gas Flow Meter and Recorder (every 15 minutes)
Gas Flow	40 CFR 60.753(a) and (e)	Y		Operate a Collection System in each area or cell and vent all collected gases to a properly operating control system	40 CFR 60.756(b)(2) (i or ii) and 60.758(c)(2)	C or P/M	Gas Flow Meter and Recorder (every 15 minutes) or Monthly Inspection of Bypass Valve and Lock and Records
Collection and Control Systems Shutdown Time	BAAQMD 8-34-113.2	Y		240 hours/year nor 5 consecutive days	BAAQMD 8-34-501.1	P/D	Operating Records
Collection System Startup Shutdown or Malfunction	40 CFR 60.755(e)	Y		5 days per event	40 CFR 60.7(b), 60.757(f)(2) and (f)(4)	P/D	Operating Records (all occurrences and duration of each)

VII. Applicable Limits and Compliance Monitoring Requirements

Table VII – A
Applicable Limits and Compliance Monitoring Requirements
S-1: LANDFILL WITH GAS COLLECTION SYSTEM AND
A-3: LANDFILL GAS FLARE

Type of Limit	Citation of Limit	FE Y/N	Future Effective Date	Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
Startup Shutdown or Mal-function Pro-cedures	40 CFR 63.6(e)	Y		Minimize Emissions by Implementing SSM Plan	40 CFR 63.1980(a-b)	P/E	Records (all occurrences, duration of each, corrective actions)
Periods of Inopera-tion for Para-metric Monitors	BAAQMD 1-523.2	Y		15 consecutive days/incident and 30 calendar days/12 month period	BAAQMD 1-523.4	P/D	Operating Records for All Parametric Monitors
Contin-uous Monitors	40 CFR 60.13(e)	Y		Requires Continuous Operation except for breakdowns, repairs, calibration, and required span adjustments	40 CFR 60.7(b)	P/D	Operating Records for All Continuous Monitors
Wellhead Pressure	BAAQMD 8-34-305.1	Y		< 0 psig	BAAQMD 8-34-414, 501.9 and 505.1	P/M	Monthly Inspection and Records
Wellhead Pressure	40 CFR 60.753(b)	Y		< 0 psig	40 CFR 60.755(a)(3), 60.756(a)(1), and 60.758(c) and (e)	P/M	Monthly Inspection and Records
Temper-ature of Gas at Wellhead	BAAQMD 8-34-305.2	Y		< 55 °C	BAAQMD 8-34-414, 501.9 and 505.2	P/M	Monthly Inspection and Records

VII. Applicable Limits and Compliance Monitoring Requirements

Table VII – A
Applicable Limits and Compliance Monitoring Requirements
S-1: LANDFILL WITH GAS COLLECTION SYSTEM AND
A-3: LANDFILL GAS FLARE

Type of Limit	Citation of Limit	FE Y/N	Future Effective Date	Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
Temperature of Gas at Wellhead	40 CFR 60.753(c)	Y		< 55 °C	40 CFR 60.755(a)(5), 60.756(a)(3), and 60.758(c) and (e)	P/M	Monthly Inspection and Records
Gas Concentrations at Wellhead	BAAQMD 8-34-305.3 or 305.4	Y		N ₂ < 20% OR O ₂ < 5%	BAAQMD 8-34-414, 501.9 and 505.3 or 505.4	P/M	Monthly Inspection and Records
Gas Concentrations at Wellhead	40 CFR 60.753(c)	Y		N ₂ < 20% OR O ₂ < 5%	40 CFR 60.755(a)(5), 60.756(a)(2), and 60.758(c) and (e)	P/M	Monthly Inspection and Records
Well Shutdown Limits	BAAQMD 8-34-116.2	Y		No more than 5 wells at a time or 10% of total collection system, whichever is less	BAAQMD 8-34-116.5 and 501.1	P/D	Records
Well Shutdown Limits	BAAQMD 8-34-116.3	Y		24 hours per well	BAAQMD 8-34-116.5 and 501.1	P/D	Records
Well Shutdown Limits	BAAQMD 8-34-117.4	Y		No more than 5 wells at a time or 10% of total collection system, whichever is less	BAAQMD 8-34-117.6 and 501.1	P/D	Records
Well Shutdown Limits	BAAQMD 8-34-117.5	Y		24 hours per well	BAAQMD 8-34-117.6 and 501.1	P/D	Records

VII. Applicable Limits and Compliance Monitoring Requirements

Table VII – A
Applicable Limits and Compliance Monitoring Requirements
S-1: LANDFILL WITH GAS COLLECTION SYSTEM AND
A-3: LANDFILL GAS FLARE

Type of Limit	Citation of Limit	FE Y/N	Future Effective Date	Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
TOC (Total Organic Compounds Plus Methane)	BAAQMD 8-34-301.2	Y		1000 ppmv as methane (component leak limit)	BAAQMD 8-34-501.6 and 503	P/Q	Quarterly Inspection of collection and control system components with OVA and Records
TOC	BAAQMD 8-34-303	Y		500 ppmv as methane at 2 inches above surface	BAAQMD 8-34-415, 416, 501.6, 506 and 510	P/M, Q, and E	Monthly Visual Inspection of Cover, Quarterly Inspection with OVA of Surface, Various Reinspec- tion Times for Leaking Areas, and Records

VII. Applicable Limits and Compliance Monitoring Requirements

Table VII – A
Applicable Limits and Compliance Monitoring Requirements
S-1: LANDFILL WITH GAS COLLECTION SYSTEM AND
A-3: LANDFILL GAS FLARE

Type of Limit	Citation of Limit	FE Y/N	Future Effective Date	Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
TOC	40 CFR 60.753(d)	Y		<500 ppmv as methane at 5-10 cm from surface	40 CFR 60.755(c)(1), (4) and (5), 60.756(f), and 60.758(c) and (e)	P/M, Q and E	Monthly Visual Inspection of Cover, Quarterly Inspection with OVA of Surface, Various Reinspection Times for Leaking Areas, and Records
Non-Methane Organic Compounds (NMOC)	BAAQMD 8-34-301.3	Y		98% removal by weight OR < 30 ppmv dry @ 3% O ₂ , expressed as methane	BAAQMD 8-34-412 and 8-34-501.4	P/A	Initial and Annual Source Tests and Records
NMOC	40 CFR 60.752(b)(2)(iii)(B)	Y		98% removal by weight OR < 20 ppmv dry @ 3% O ₂ , expressed as hexane	40 CFR 60.8 and 60.752(b)(2)(iii)(B) and 60.758(b)(2)	P/I	Initial Source Test and Records
Low VOC Soil	BAAQMD Condition # 8366, Part 17	Y		Soil with Organic Vapor Concentration ≤50 ppmv Acceptable as Cover Material	BAAQMD 8-40-604 and BAAQMD Condition # 8366, Part 17	P/E	Surface Organic Vapor Monitoring

VII. Applicable Limits and Compliance Monitoring Requirements

Table VII – A
Applicable Limits and Compliance Monitoring Requirements
S-1: LANDFILL WITH GAS COLLECTION SYSTEM AND
A-3: LANDFILL GAS FLARE

Type of Limit	Citation of Limit	FE Y/N	Future Effective Date	Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
Contaminated Soil Limits	BAAQMD Permit Condition #8366, Part 18	Y		≤ 50 ppmw organics; or ≤ 50 ppmw TPH as gasoline, ≤ 50 ppmw TPH as diesel, and ≤ 50 ppmw TPH as motor oil; or IBP of all organics ≥ 302 degrees F	BAAQMD Permit Condition #8366, Part 18m	P/E	Records of Soil Test Data
Total Aeration Project Emissions	BAAQMD 8-40-118	Y		150 pounds per project and toxic air contaminant emissions per year <BAAQMD Table 2-1-316 limits	BAAQMD Permit Condition #8366, Part 18m	P/E	Records
Amount of Contaminated Soil Aerated or Used as Cover	BAAQMD 8-40-301 and BAAQMD Condition #8366, Part 18k	Y		Prohibited for Soil with Organic Content >50 ppmw unless exempt per BAAQMD 8-40-116, 117, or 118	BAAQMD Permit Condition #8366, Part 18m	P/E	Records
Contaminated Soil Handling	BAAQMD Permit Condition #8366, Part 18e	Y		Limited to 2 on-site transfers per lot of contaminated soil	BAAQMD Permit Condition #8366, Part 18m	P/E	Records
Contaminated Soil On-Site Storage Time	BAAQMD Permit Condition #8366, Part 18f-g	Y		If organic content is: < 500 ppmw, storage time ≤ 90 days; If organic content is: ≥ 500 ppmw, storage time ≤ 45 days	BAAQMD Permit Condition #8366, Part 18m	P/E	Records

VII. Applicable Limits and Compliance Monitoring Requirements

Table VII – A
Applicable Limits and Compliance Monitoring Requirements
S-1: LANDFILL WITH GAS COLLECTION SYSTEM AND
A-3: LANDFILL GAS FLARE

Type of Limit	Citation of Limit	FE Y/N	Future Effective Date	Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
Opacity	BAAQMD 6-301	Y		Ringelmann No. 1 for 3 minutes in any hour (applies to landfill operations)	BAAQMD Permit Condition #8366, Part 16	P/D	Records of Site Watering and Road Cleaning
Opacity	BAAQMD Condition #8366, Part 13	Y		Site Watering: 2 times daily; all unpaved roads and active soil removal and fill areas (rainless operating days only)	BAAQMD Condition #8366, Part 16	P/D	Records
Opacity	BAAQMD Condition #8366, Part 14	Y		Paved Road Cleaning: (as necessary)	BAAQMD Condition #8366, Part 16	P/D	Records
Opacity	BAAQMD 6-301	Y		Ringelmann No. 1 for < 3 minutes/hour (applies to flare)	None	N	NA
FP	BAAQMD 6-310	Y		≤ 0.15 grains/dscf (applies to flare only)	None	N	NA
SO ₂	BAAQMD 9-1-301	Y		Ground Level Concentrations: 0.5 ppm for 3 consecutive minutes, 0.25 ppm averaged over 60 consecutive minutes, 0.05 ppm averaged over 24 hours	None	N	NA
Total Sulfur Content in Landfill Gas	BAAQMD Condition # 8366, Part 12	Y		Total Sulfur Content ≤ 1300 ppmv (dry)	BAAQMD Condition # 8366, Part 12	P/Q	Sulfur Analysis of landfill gas only

VII. Applicable Limits and Compliance Monitoring Requirements

Table VII – A
Applicable Limits and Compliance Monitoring Requirements
S-1: LANDFILL WITH GAS COLLECTION SYSTEM AND
A-3: LANDFILL GAS FLARE

Type of Limit	Citation of Limit	FE Y/N	Future Effective Date	Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
SO ₂	BAAQMD Regulation 9-1-302	Y		≤300 ppm (dry)	BAAQMD Condition # 8366, Part 12	P/Q	Sulfur Analysis of landfill gas as a surrogate for SO ₂ monitoring
Total Sulfur Content in Landfill Gas	BAAQMD Condition # 8366, Part 12	Y		Total Sulfur Content ≤ 1300 ppmv (dry)	BAAQMD Condition # 8366, Part 12	P/Q	Sulfur Analysis of landfill gas only
H ₂ S	BAAQMD 9-2-301	N		Property Line ground level limits ≤ 0.06 ppm Averaged over 3 minutes and ≤ 0.03 ppm Averaged over 60 minutes	None	N	NA
NO _x	BAAQMD Condition #8366, Part 8	Y		≤ 0.06 lb/MMBTU (calculated as NO ₂)	BAAQMD Condition #8366, Part 10	P/A	Annual Source Test
CO	BAAQMD Condition #8366, Part 9	Y		≤ 0.3 lb/MMBTU	BAAQMD Condition #8366, Part 10	P/A	Annual Source Test
Amount of Waste Accepted	BAAQMD Condition # 8366, Part 1	Y		≤ 2628 tons/day and ≤ 19,271,000 yd ³	BAAQMD Condition # 8366, Part 3	P/D	Records
Flare Heat Input	BAAQMD Condition # 8366, Part 11	Y		Input to Flare: ≤ 1,800 MMBTU/hr, ≤ 657,000 MMBTU/yr	BAAQMD Condition # 8366, Part 11	P/D,M	Record Calculated Heat Input to the Flare

VII. Applicable Limits and Compliance Monitoring Requirements

Table VII – B
Applicable Limits and Compliance Monitoring Requirements
S-5: WOODWASTE STOCKPILES

Type of Limit	Citation of Limit	FE Y/N	Future Effective Date	Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
Opacity	BAAQMD Regulation 6-301 and BAAQMD Condition #15022, Part 2			Ringelmann No. 1 for 3 minutes in any hour	BAAQMD Condition #15022, Part 3	P/E	Observation of Operations

VII. Applicable Limits and Compliance Monitoring Requirements

Table VII-C
Applicable Limits and Compliance Monitoring Requirements
S-9: PORTABLE DIESEL ENGINE

Type of Limit	Citation of Limit	FE Y/N	Future Effective Date	Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
Opacity	BAAQMD Regulation 6-303	Y		Ringelmann No. 2 for 3 minutes in any hour	BAAQMD Condition #17680, Part 2	C	Observation for Visible Smoke
FP	BAAQMD Regulation 6-310	Y		0.15 gr/dsef	None	N	NA
SO ₂	BAAQMD Regulation 9-1-301	Y		Ground Level Concentrations: 0.5 ppm for 3 consecutive minutes, 0.25 ppm averaged over 60 consecutive minutes, 0.05 ppm averaged over 24 hours	None	N	NA
SO ₂	BAAQMD Regulation 9-1-304 and BAAQMD Condition #17680, Part 1	Y		Fuel Sulfur Limit 0.5%	BAAQMD Condition #17680, Part 1	P/M	Vendor Certification

VII. Applicable Limits and Compliance Monitoring Requirements

Table VII - ~~DC~~
Applicable Limits and Compliance Monitoring Requirements
S-10: PARTS CLEANER

Type of Limit	Citation of Limit	FE Y/N	Future Effective Date	Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
Usage	BAAQMD Condition #17682, Part 1	Y		150 gallons net solvent usage per 12-month period	BAAQMD Condition #17682, Part 2	P/M	Records
					BAAQMD 8-16-501.2	P/A	Records

Table VII - ~~ED~~
Applicable Limits and Compliance Monitoring Requirements
S-9, S-14, S-15, S-16, S-17: ~~SMALL~~ PORTABLE DIESEL IC ENGINES

Type of Limit	Citation of Limit	FE Y/N	Future Effective Date	Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
Opacity	BAAQMD Regulation 6-303.1	Y		Ringelmann No. 2 for 3 minutes in any hour	BAAQMD Condition #21617, Part 3	C	Observation for Visible Smoke
FP	BAAQMD Regulation 6-310	Y		0.15 gr/dscf	None	N	N/A
<u>Diesel PM</u>	<u>CCR Section 93116.3(b) (1)(A)</u>	<u>N</u>	<u>1/1/2010</u>	<u>Meet "Tier" standards for newly manufactured engines.</u>	<u>CCR Section 93116.3(b) (1)(A)</u>	<u>N</u>	<u>Engine Model Emissions Certification</u>

VII. Applicable Limits and Compliance Monitoring Requirements

Table VII - ED
Applicable Limits and Compliance Monitoring Requirements
S-9, S-14, S-15, S-16, S-17: SMALL-PORTABLE DIESEL IC ENGINES

Type of Limit	Citation of Limit	FE Y/N	Future Effective Date	Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
SO ₂	BAAQMD Regulation 9-1-301	Y		Ground Level Concentrations: 0.5 ppm for 3 consecutive minutes, 0.25 ppm averaged over 60 consecutive minutes, 0.05 ppm averaged over 24 hours	None	N	N/A
SO ₂	BAAQMD Regulation 9-1-304 and BAAQMD Condition #21617, Part 2	Y		Fuel Sulfur Limit 0.5%	BAAQMD Condition #21617, Part 2	P/M	Vendor Certification
<u>SO₂</u>	<u>CCR Section 93116.3(a) and BAAQMD Condition #21617, Part 2</u>	<u>N</u>		<u>CARB Diesel Fuel (0.05% sulfur by weight)</u>	<u>BAAQMD Condition #21617 Part 2</u>	<u>P/M</u>	<u>Vendor Certification</u>
Hours of Operation	BAAQMD Condition #21617, Part 1	Y		1,456 hours per year (each engine)	BAAQMD Condition #21617, Part 4	P/M	Records

VII. Applicable Limits and Compliance Monitoring Requirements

Table VII-F
Applicable Limits and Compliance Monitoring Requirements
S-18, S-19, S-20 – IC ENGINE GENERATOR SETS

Type of limit	Emission Limit Citation	FE Y/N	Future Effective Date	Emission Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
Opacity	BAAQMD 6-301	Y	Upon Start-up	Ringelmann No. 1	None	N	N/A
FP	BAAQMD 6-310	Y	Upon Start-up	0.15 grains/dscf	None	N	N/A
TOC (Total Organic Compounds Plus Methane)	BAAQMD 8-34-301.2	Y	Upon Start-up	1000 ppmv as methane (component leak limit)	BAAQMD 8-34-501.6 and 8-34-503	P/Q	Quarterly Inspection and Records
Non-Methane Organic Compounds (NMOC)	BAAQMD 8-34-301.4	Y	Upon Start-up	98% removal by weight OR <120 ppmv dry @ 3% O ₂ , expressed as methane	BAAQMD 8-34-412, 8-34-501.4, 8-34-501.11, and BAAQMD Condition #21619, Parts 8, 9, and 10	P/M, P/A	Key Emission Control System Operating Parameter Records and Annual Source Test
NMOC	40 CFR 60.752(b)(2)(iii)(B)	Y		98% removal by weight OR <20 ppmv dry @ 3% O ₂ , expressed as hexane	40 CFR 60.8 and 60.752(b)(2)(iii)(B) and 60.758(b)(2)	P/I	Initial Source Test and Records
NMOC	BAAQMD Condition #21619, Part 7	Y	Upon Start-up	<120 ppmv dry @ 3% O ₂ , expressed as methane	BAAQMD Condition #21619, Parts 8, 9, and 10	P/M, P/A	Key Emission Control System Operating Parameter Records and Annual Source Test

VII. Applicable Limits and Compliance Monitoring Requirements

Table VII-F
Applicable Limits and Compliance Monitoring Requirements
S-18, S-19, S-20 – IC ENGINE GENERATOR SETS

Type of limit	Emission Limit Citation	FE Y/N	Future Effective Date	Emission Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
SO ₂	BAAQMD 9-1-301	Y	Upon Start-up	Property Line Ground Level Limits: ≤0.5 ppm for 3 minutes, ≤0.25 ppm for 60 minutes & ≤0.05 ppm for 24 hours	None	N	N/A
SO ₂	BAAQMD Regulation 9-1-302	Y		≤300 ppm (dry)	BAAQMD Condition #8366, Part 12	P/Q	Sulfur Analysis of landfill gas as a surrogate for SO ₂ monitoring
H ₂ S	BAAQMD 9-2-301	N	Upon Start-up	Property Line ground level limits ≤0.06 ppm -Averaged over 3 minutes and ≤0.03 ppm -Averaged over 60 minutes	None	N	N/A
NO _x	BAAQMD 9-8-301.2	Y	Upon Start-up	Fossil Fuel Gas, Lean-Burn 140 ppmv dry @ 15% O ₂	BAAQMD Condition #21619, Part 9	P/A	Annual Source Test
NO _x	BAAQMD 9-8-302.1	Y	Upon Start-up	Waste Fuel Gas, Lean-Burn 140 ppmv dry @ 15% O ₂	BAAQMD Condition #21619, Part 9	P/A	Annual Source Test
NO _x	BAAQMD Condition #21619, Part 5	Y	Upon Start-up	≤0.6 g/bhp-hr -expressed as NO ₂ or 37 ppmv dry @ 15% O ₂	BAAQMD Condition #21619, Part 9	P/A	Annual Source Test
CO	BAAQMD 9-8-301.3	Y	Upon Start-up	Fossil Fuel Gas: 2000 ppmv dry @ 15% O ₂	BAAQMD Condition #21619, Part 9	P/A	Annual Source Test

VII. Applicable Limits and Compliance Monitoring Requirements

Table VII-F
Applicable Limits and Compliance Monitoring Requirements
S-18, S-19, S-20 – IC ENGINE GENERATOR SETS

Type of limit	Emission Limit Citation	FE Y/N	Future Effective Date	Emission Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
CO	BAAQMD 9-8-302.3	Y	Upon Start-up	Waste Fuel Gas: 2000 ppmv dry @ 15% O ₂	BAAQMD Condition #21619, Part 9	P/A	Annual Source Test
CO	BAAQMD Condition #21619, Part 6	Y	Upon Start-up	≤ 2.1 g/bhp-hr or 215 ppmv dry @ 15% O ₂	BAAQMD Condition #21619, Part 9	P/A	Annual Source Test
Heat Input	BAAQMD Condition #21619, Part 3	Y	Upon Start-up	≤ 252 MM BTU per day and ≤ 91,980 MM BTU per year (each engine)	BAAQMD Condition #21619, Parts 3 and 10	P/D	Records
Emission Control System Shutdown Time	BAAQMD 8-34-113.2	Y	Upon Start-up	240 hours/year	BAAQMD 8-34-501.2 and BAAQMD Condition #21619, Part 10a	P/D	Records
Emission Control System Startup Shutdown or Malfunction	40-CFR 60.755(e)	Y		≤ 1 hour per event	40-CFR 60.7(b); 60.757(f)(2) and (f)(3); and 60.758(e)	P/D	Records of occurrence and duration
Startup Shutdown or Malfunction Procedures	40-CFR 63.6(e)	Y		Minimize Emissions by Implementing SSM Plan	40-CFR 63.1980(a-b)	P/E	Records (all occurrences; duration of each; corrective actions)

VII. Applicable Limits and Compliance Monitoring Requirements

Table VII-F
Applicable Limits and Compliance Monitoring Requirements
S-18, S-19, S-20 – IC ENGINE GENERATOR SETS

Type of limit	Emission Limit Citation	FE Y/N	Future Effective Date	Emission Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
Key Emission Control System Operating Parameter (s)	BAAQMD Condition #21619, Part 8	Y	Upon Start-up		BAAQMD 8-34-501.3 and 8-34-509 and BAAQMD Condition #21619, Parts 8 and 10e	P/M	Key Emission Control System Operating Parameter Records
Natural Gas Usage	BAAQMD Condition #21619, Part 2	Y	Upon Start-up	Prohibited when flare is operating and unless it is needed as supplemental fuel	BAAQMD 8-34-501.2 and BAAQMD Condition #21619, Part 10b	P/M	Records
Gas Flow	BAAQMD Condition #21619, Parts 1 & 2	Y	Upon Start-up	Vent all collected gases to a properly operating control system and operate control system continuously.	BAAQMD Condition #21619, Part 4	C	Gas Flow Meter
Gas Flow	BAAQMD 8-34-301 and 301.1	Y	Upon Start-up	Vent all collected gases to a properly operating control system and operate control system continuously.	BAAQMD 8-34-501.10 and 508	C	Gas Flow Meter and Recorder (every 15 minutes)

VIII. TEST METHODS

The test methods associated with the emission limit of a District regulation are generally referenced in Section 600 et seq. of the regulation. The following table indicates only the test methods associated with the emission limits referenced in Section VII, Applicable Emission Limits & Compliance Monitoring Requirements, of this permit.

**Table VIII
 Test Methods**

Applicable Requirement	Description of Requirement	Acceptable Test Methods
BAAQMD 6-301	Ringelmann No. 1 Limitation	Manual of Procedures, Volume I, Evaluation of Visible Emissions
BAAQMD 6-303	Ringelmann No. 2 Limitation	Manual of Procedures, Volume I, Evaluation of Visible Emissions
BAAQMD 6-310	Particulate Weight Limitation	Manual of Procedures, Volume IV, ST-15, Particulate; or USEPA Method 5, Determination of Particulate Matter Emissions from Stationary Sources
BAAQMD 8-2-301	Miscellaneous Operations	Manual of Procedures, Volume IV, ST-7, Organic Compounds; or EPA Reference Method 25 or 25A
BAAQMD 8-34-301.2	Collection and Control System Leak Limitations	EPA Reference Method 21, Determination of Volatile Organic Compound Leaks
BAAQMD 8-34-301.3	Limits for Flares	Manual of Procedures, Volume IV, ST-7, Organic Compounds and ST-14, Oxygen, Continuous Sampling; or EPA Reference Method 18, 25, 25A, or 25C
BAAQMD 8-34-303	Landfill Surface Requirements	EPA Reference Method 21, Determination of Volatile Organic Compound Leaks
BAAQMD 8-34-305.1	Wellhead Gauge Pressure	APCO Approved Device
BAAQMD 8-34-305.2	Wellhead Temperature	APCO Approved Device
BAAQMD 8-34-305.3	Wellhead Nitrogen	EPA Reference Method 3C, Determination of Carbon Dioxide, Methane, Nitrogen, and Oxygen from Stationary Sources
BAAQMD 8-34-305.4	Wellhead Oxygen	EPA Reference Method 3C, Determination of Carbon Dioxide, Methane, Nitrogen, and Oxygen from Stationary Sources

VIII. Test Methods

**Table VIII
 Test Methods**

Applicable Requirement	Description of Requirement	Acceptable Test Methods
BAAQMD 8-34-412	Compliance Demonstration Test	EPA Reference Method 18, Measurement of Gaseous Organic Compound Emissions by Gas Chromatography, Method 25, Determination of Total Gaseous Nonmethane Organic Emissions as Carbon, Method 25A, Determination of Total Gaseous Organic Concentration Using a Flame Ionization Analyzer, or Method 25C, Determination of Nonmethane Organic Compounds (NMOC) in MSW Landfill Gases
BAAQMD 8-40-116.2	Organic Content Limit for Small Volume Exemption	BAAQMD 8-40-601 and EPA Reference Methods 8015B and 8021B
BAAQMD 8-40-301	Limits on Uncontrolled Aeration of Contaminated Soil	BAAQMD 8-40-601 and EPA Reference Methods 8015B and 8021B; or EPA Reference Method 21
BAAQMD 9-1-301	Limitations on Ground Level Concentrations (SO ₂)	Manual of Procedures, Volume VI, Part 1, Ground Level Monitoring for Hydrogen Sulfide and Sulfur Dioxide
BAAQMD 9-1-302	General Emission Limitation (SO ₂)	Manual of Procedures, Volume IV, ST-19A, Sulfur Dioxide, Continuous Sampling
BAAQMD 9-1-304	Fuel Sulfur Content	Manual of Procedures, Volume III, Method 10, Determination of Sulfur in Fuel Oil
BAAQMD 9-2-301	Limitations on Hydrogen Sulfide	Manual of Procedures, Volume VI, Part 1, Ground Level Monitoring for Hydrogen Sulfide and Sulfur Dioxide
40 CFR 60.8	Performance Tests	EPA Reference Method 18, Measurement of Gaseous Organic Compound Emissions by Gas Chromatography, Method 25, Determination of Total Gaseous Nonmethane Organic Emissions as Carbon, Method 25A, Determination of Total Gaseous Organic Concentration Using a Flame Ionization Analyzer, or Method 25C, Determination of Nonmethane Organic Compounds (NMOC) in MSW Landfill Gases
40 CFR 60.752 (b)(2)(iii)(B)	NMOC Outlet Concentration and Destruction Efficiency Limits	EPA Reference Method 18, Measurement of Gaseous Organic Compound Emissions by Gas Chromatography, Method 25, Determination of Total Gaseous Nonmethane Organic Emissions as Carbon, Method 25A, Determination of Total Gaseous Organic Concentration Using a Flame Ionization Analyzer, or Method 25C, Determination of Nonmethane Organic Compounds (NMOC) in MSW Landfill Gases
40 CFR 60.753(b)	Wellhead Pressure	APCO Approved Device

VIII. Test Methods

**Table VIII
 Test Methods**

Applicable Requirement	Description of Requirement	Acceptable Test Methods
40 CFR 60.753(c)	Temperature, N ₂ , and O ₂ concentration in wellhead gas	EPA Reference Method 3C, Determination of Carbon Dioxide, Methane, Nitrogen, and Oxygen from Stationary Sources
40 CFR 60.753(d)	Methane Limit at Landfill Surface	EPA Reference Method 21, Determination of Volatile Organic Compound Leaks
BAAQMD Condition #8366, Part 6	Flare Combustion Temperature Limit	APCO Approved Device
BAAQMD Condition #8366, Part 8	Flare NOx Limit	Manual of Procedures, Volume IV, ST-13A, Oxides of Nitrogen, Continuous Sampling and ST-14, Oxygen, Continuous Sampling
BAAQMD Condition #8366, Part 9	Flare CO Limit	Manual of Procedures, Volume IV, ST-6, Carbon Monoxide, Continuous Sampling and ST-14, Oxygen, Continuous Sampling
BAAQMD Condition #8366, Part 10	Flare Source Test	Flare Outlet: Manual of Procedures, Volume IV, ST-17, Stack Gas Velocity and Volumetric Flow Rate; ST-23 Water Vapor; ST-14, Oxygen, Continuous Sampling; and Manual of Procedures, Volume IV, ST-7, Organic Compounds or EPA Reference Methods 18, 25, 25A, or 25C; Flare Inlet: EPA Reference Method 3C
BAAQMD Condition #8366, Part 11	Heat Input Limit for Flare	APCO approved calculation procedure as described in BAAQMD Condition #8366, Part 11.
BAAQMD Condition #8366, Part 12	Limit for Total Reduced Sulfur Compounds in Landfill Gas	Draeger Tube: used in accordance with manufacturer's recommended procedures.
BAAQMD Condition #8366, Part 15	Ringelmann No. 1 Limitation	Manual of Procedures, Volume I, Evaluation of Visible Emissions
BAAQMD Condition #8366, Part 17	Low VOC (VOC laden) Soils for Landfill Cover	BAAQMD 8-40-601 and EPA Reference Methods 8015B and 8021B; and or 8-40-604, Measurement of Organic Concentration
BAAQMD Condition #8366, Part 18	Acceptance Criteria for VOC Contaminated Soil	EPA Reference Methods 8015B, 8021B, or any method determined to be equivalent by the US EPA and approved by the APCO BAAQMD 8-40-601 and EPA Reference Methods 8015B and 8021B; or 8-40-604, Measurement of Organic Concentration

VIII. Test Methods

**Table VIII
 Test Methods**

Applicable Requirement	Description of Requirement	Acceptable Test Methods
BAAQMD Condition #15022, Part 2	Ringelmann No. 1 Limitation	Manual of Procedures, Volume I, Evaluation of Visible Emissions
BAAQMD Condition #17680, Part 1	Fuel Sulfur Content	Manual of Procedures, Volume III, Method 10, Determination of Sulfur in Fuel Oil
BAAQMD Condition #21617, Part 2	Fuel Sulfur Content	Manual of Procedures, Volume III, Method 10, Determination of Sulfur in Fuel Oil
BAAQMD Condition #21619, Part 3	Heat Input Limits	APCO approved gas flow meter and APCO approved calculation procedure described in BAAQMD Condition # 18696, Part 3
BAAQMD Condition #21619, Part 5	IC Engine NOx Limit	Manual of Procedures, Volume IV, ST 13A, Oxides of Nitrogen, Continuous Sampling and ST 14, Oxygen, Continuous Sampling
BAAQMD Condition #21619, Part 6	IC Engine CO Limit	Manual of Procedures, Volume IV, ST 6, Carbon Monoxide, Continuous Sampling and ST 14, Oxygen, Continuous Sampling
BAAQMD Condition #21619, Part 7	IC Engine NMOC Limit	Manual of Procedures, Volume IV, ST 7, Organic Compounds and ST 14, Oxygen, Continuous Sampling; or EPA Reference Method 18, 25, 25A, or 25C
BAAQMD Condition #21619, Part 8	Key Emission Control System Operating Parameter(s)	APCO Approved Devices and Location

IX. PERMIT SHIELD

A. SUBSUMED REQUIREMENTS

Pursuant to District Regulations 2-6-233.2 and 2-6-409.12, as of the date this permit is issued, the federally enforceable monitoring, recordkeeping, and reporting requirements cited in the following table for the source or group of sources identified at the top of the table are subsumed by the monitoring, recordkeeping, and reporting for more stringent requirements or by a “hybrid” monitoring scheme. The District has determined that compliance with the requirements listed below and elsewhere in this permit will assure compliance with the substantive requirements of the subsumed monitoring requirements. Enforcement actions and litigation may not be initiated against the source or group of sources covered by this shield based on the subsumed monitoring requirements cited.

Table IX-A
S-1 ACTIVE LANDFILL

Subsumed Requirement Citation	Title or Description	Streamlined Requirements	Title or Description
8-2-601	Determination of Compliance (for organic compound emissions as total carbon)	8-40-604	Measurement of Organic Concentration (to classify soil as “contaminated” or “not contaminated”)

The Regulation 8, Rule 2 total carbon test procedure is subsumed by the Regulation 8, Rule 40 VOC test procedure for the Active Landfill (S-1) because testing performed pursuant to Regulation 8-40-604 will rule out the need to test in accordance with Regulation 8-2-601.

Regulation 8, Rule 2 “Miscellaneous Operations” is only applicable to sources of precursor organic compounds that are not otherwise limited by Regulation 8 or Regulation 10 rules. In the case of the Landfill S-1, Regulation 8, Rule 2 would apply only to cover soil that contains some VOC, but is not defined as “contaminated soil” by Regulation 8-40-205. Soil which has an organic content exceeding 50 ppmw or that registers an organic concentration greater than 50 ppmv (expressed as methane, C1) is subject to Regulation 8, Rule 40.

Regulation 8-2-301 limits organic compound emissions (expressed as total carbon) from an operation to 15 pounds per day, if the emission from the operation has an organic compound concentration greater than 300 ppmv (expressed as total carbon, dry basis). Since soil found not to be contaminated using the procedures of

IX. Permit Shield

Regulation 8-40-604 will have a surface VOC concentration of less than 50 ppmv (expressed as methane, C1) it can reasonably be assumed that the concentration is also less than 300 ppmv (total carbon, dry basis) as determined by the procedures of Regulation 8-2-601. Since the operation complies with the 300 ppmv limit, it complies with Regulation 8-2-301.

In summary, measurements conducted under Regulation 8-40-604 that show surface VOC concentrations less than 50 ppmv (expressed as methane, C1) are conclusive to demonstrate compliance with Regulation 8-2-301.

X. REVISION HISTORY

Title V Permit Issuance (Application #17350): **November 28, 2001**

Administrative Permit Amendment (no application): **June 5, 2003**

- Deletion of outdated SIP Requirements

Reopening (Applications #3515 and #8916): **November 1, 2004**

- Correct contact information on the title page.
- Update standard language in Sections I, III, and VIII.
- Correct regulatory references and amendment dates and delete outdated SIP requirements in Section I, Tables III, IV-A, IV-D, VII-A, VII-D, and VIII, and Condition # 8366, Parts 8, 16, and 17.
- Correct collection system description in Table II-A and Condition # 8366, Part 2 (update number of collection wells).
- Expand the description of A-2 in Table II-B and delete references to obsolete limits.
- Add several recently identified generally applicable regulations to Table III. Move Regulation 8-40-116 and 117 from Tables IV-A and VII-A to Table III.
- Add several applicable requirements that were missing from Tables IV-A and VII-A including Regulations 6-310 and 8-34-501.3, and 40 CFR 60.752(b)(2)(iii)(B), 60.756(b)(1), and 60.758(b)(2)(i-ii) for the flare and Regulations 8-34-304.4 and 8-34-408.2 for the landfill.
- Add MSW Landfill NESHAP requirements to Tables IV-A and VII-A.
- Revise Condition # 8366 and Table IV-A by adding Part 17. This part requires semi-annual reports pursuant to the above NESHAP requirements and allows these reports to be combined with the Title V semi-annual monitoring reports.
- Revise Condition # 8336, Part 6 for consistency with MFR permit revision procedures in Regulation 2, Rule 6.
- Revise Condition # 8336, Part 8 to allow 60 days for submitting source test results instead of 45.
- Correct an applicable requirement in Tables IV-C, VII-C, and VIII and the associated basis for Condition # 17860, Part 2. The S-9 Portable Diesel Engine is subject to Regulation 6-303 and not 6-301, because the engine displacement is less than 1500 in³.
- Reword the condition bases for several parts in Condition #8366, #15022, and #17860 and in Tables IV-A, IV-B, and IV-C.
- In Table VIII, add an alternative test method for BAAQMD Regulation 6-310, Particulate Weight Limitation; add missing test method references for Condition # 8366, Part 8; and correct an erroneous reference for Condition # 8366, Part 15.
- Correct and update Section X Revision History.

X. Revision History

- Add and correct several terms in the Section XI Glossary.

Minor Permit Revision (Application #9790):

- Replace existing Landfill Gas Flare A-2 with new Landfill Gas Flare A-3.
- Remove Custom Schedule of Compliance previously added to accommodate the use of a temporary landfill gas flare.

Minor Permit Revision (Application #9222):

- Added existing Diesel IC Engines S-14, S-15, S-16, and S-17 to Title V permit.
- Added proposed Landfill Gas Fired IC Engine Generator Sets S-18, S-19, and S-20.
- Added tables and permit conditions to reflect the additions of permitted and proposed equipment.
- Updated Table VIII to include “Test Methods” for new equipment.
- Modified standard permit text to say that SIP standards are now found on EPA's website and are not included as part of the permit. Part XII. “Applicable State Implementation Plan” was removed from the permit

Significant Permit Revision (Application #9907):

August 16, 2006

- Updated permit content to the current District standard.
- Replaced Permit Condition #8366, part 17 with a condition that does not require a determination of compliance with a 15 lb/day VOC limit.
- Added a Permit Shield that subsumes the monitoring requirements of Regulation 8-2 with those of Regulation 8-40.

Title V Renewal (Application #14588):

2007 |

XI. GLOSSARY

ACT

Federal Clean Air Act

APCO

Air Pollution Control Officer: Head of Bay Area Air Quality Management District

API

American Petroleum Institute

ARB

Air Resources Board (same as CARB)

BAAQMD

Bay Area Air Quality Management District

BACT

Best Available Control Technology

BARCT

Best Available Retrofit Control Technology

Basis

The underlying authority that allows the District to impose requirements.

C5

An Organic chemical compound with five carbon atoms

C6

An Organic chemical compound with six carbon atoms

CAA

The federal Clean Air Act

CAAQS

California Ambient Air Quality Standards

CAPCOA

California Air Pollution Control Officers Association

CARB

California Air Resources Board (same as ARB)

CCR

California Code of Regulations

XI. GLOSSARY

CEC

California Energy Commission

CEQA

California Environmental Quality Act

CEM

A "continuous emission monitor" is a monitoring device that provides a continuous direct measurement of some pollutant (e.g. NOx concentration) in an exhaust stream.

CFR

The Code of Federal Regulations. 40 CFR contains the implementing regulations for federal environmental statutes such as the Clean Air Act. Parts 50-99 of 40 CFR contain the requirements for air pollution programs.

CH4 or CH₄

Methane

CO

Carbon Monoxide

CO2 or CO₂

Carbon Dioxide

CT

Combustion Zone Temperature

Cumulative Increase

The sum of permitted emissions from each new or modified source since a specified date, pursuant to ~~BAAQMD Rule 2-1-403, Permit Conditions (as amended by the District Board on 7/17/91) and SIP Rule 2-1-403, Permit Conditions (as approved by EPA on 6/23/95).~~ Used to determine whether threshold-based requirements are triggered.

District

The Bay Area Air Quality Management District

dscf

Dry Standard Cubic Feet

dscm

Dry Standard Cubic Meter

XI. GLOSSARY

E 6, E9, E12

Very large or very small number values are commonly expressed in a form called scientific notation, which consists of a decimal part multiplied by 10 raised to some power. For example, 4.53 E 6 equals $(4.53) \times (10^6) = (4.53) \times (10 \times 10 \times 10 \times 10 \times 10 \times 10) = 4,530,000$. Scientific notation is used to express large or small numbers without writing out long strings of zeros.

EG

Emission Guidelines

EGT

Exhaust Gas Temperature

EO

Executive Order

EPA

The federal Environmental Protection Agency.

Excluded

Not subject to any District regulations.

Federally Enforceable, FE

All limitations and conditions which are enforceable by the Administrator of the EPA including those requirements developed pursuant to 40 CFR Part 51, subpart I (NSR), Part 52.21 (PSD), Part 60, (NSPS), Part 61, (NESHAPs), Part 63 (HAP), and Part 72 (Permits Regulation, Acid Rain), including limitations and conditions contained in operating permits issued under an EPA-approved program that has been incorporated into the SIP.

FP

Filterable Particulate as measured by BAAQMD Method ST-15, Particulate.

FR

Federal Register

GDF

Gasoline Dispensing Facility

GLC

Ground level concentration.

GLM

Ground Level Monitor

grains

1/7000 of a pound

XI. GLOSSARY

H₂S or H₂S

Hydrogen Sulfide

HAP

Hazardous Air Pollutant. Any pollutant listed pursuant to Section 112(b) of the Act. Also refers to the program mandated by Title I, Section 112, of the Act and implemented by 40 CFR Part 63.

Hg

Mercury

HHV

Higher Heating Value. The quantity of heat evolved as determined by a calorimeter where the combustion products are cooled to 60F and all water vapor is condensed to liquid.

LFG

Landfill gas

LHV

Lower Heating Value. Similar to the higher heating value (see HHV) except that the water produced by the combustion is not condensed but retained as vapor at 60 °F.

Major Facility

A facility with potential emissions of: (1) at least 100 tons per year of regulated air pollutants, (2) at least 10 tons per year of any single hazardous air pollutant, and/or (3) at least 25 tons per year of any combination of hazardous air pollutants, or such lesser quantity of hazardous air pollutants as determined by the EPA administrator.

MAX or Max.

Maximum

MFR

Major Facility Review. The District's term for the federal operating permit program mandated by Title V of the Federal Clean Air Act and implemented by District Regulation 2, Rule 6.

MIN or Min.

Minimum

MOP

The District's Manual of Procedures.

MSDS

Material Safety Data Sheet

MSW

Municipal solid waste

XI. GLOSSARY

MW

Molecular weight

N2 or N₂

Nitrogen

NA

Not Applicable

NAAQS

National Ambient Air Quality Standards

NESHAPS

National Emission Standards for Hazardous Air Pollutants. See in 40 CFR Parts 61 and 63

NMHC

Non-methane Hydrocarbons (Same as NMOC)

NMOC

Non-methane Organic Compounds (Same as NMHC)

NO_x or NO_x

Oxides of nitrogen.

NSPS

Standards of Performance for New Stationary Sources. Federal standards for emissions from new stationary sources. Mandated by Title I, Section 111 of the Federal Clean Air Act, and implemented by 40 CFR Part 60 and District Regulation 10.

NSR

New Source Review. A federal program for pre-construction review and permitting of new and modified sources of pollutants for which criteria have been established in accordance with Section 108 of the Federal Clean Air Act. Mandated by Title I of the Federal Clean Air Act and implemented by 40 CFR Parts 51 and 52 and District Regulation 2, Rule 2. (Note: There are additional NSR requirements mandated by the California Clean Air Act.)

O₂ or O₂

Oxygen

Offset Requirement

A New Source Review requirement to provide federally enforceable emission offsets for the emissions from a new or modified source. Applies to emissions of POC, NO_x, PM₁₀, and SO₂.

Phase II Acid Rain Facility

A facility that generates electricity for sale through fossil-fuel combustion and is not exempted by 40 CFR 72 from Titles IV and V of the Clean Air Act.

XI. GLOSSARY

POC

Precursor Organic Compounds

PM

Particulate Matter

PM10 or PM₁₀

Particulate matter with aerodynamic equivalent diameter of less than or equal to 10 microns

PSD

Prevention of Significant Deterioration. A federal program for permitting new and modified sources of those air pollutants for which the District is classified "attainment" of the National Air Ambient Quality Standards. Mandated by Title I of the Act and implemented by both 40 CFR Part 52 and District Regulation 2, Rule 2.

PV or P/V Valve

Pressure/Vacuum Valve

RMP

Risk Management Plan

S

Sulfur

SCR

A "selective catalytic reduction" unit is an abatement device that reduces NO_x concentrations in the exhaust stream of a combustion device. SCRs utilize a catalyst, which operates at a specific temperature range, and injected ammonia to promote the conversion of NO_x compounds to nitrogen gas.

SIP

State Implementation Plan. State and District programs and regulations approved by EPA and developed in order to attain the National Air Ambient Quality Standards. Mandated by Title I of the Act.

SO₂ or SO₂

Sulfur dioxide

SSM

Startup, Shutdown, or Malfunction

SSM Plan

A plan, which states the procedures that will be followed during a startup, shutdown, or malfunction, that is prepared in accordance with the general NESHAP provisions (40 CFR Part 63, Subpart A) and maintained on site at the facility.

XI. GLOSSARY

TAC

Toxic Air Contaminant (as identified by CARB)

THC

Total Hydrocarbons (NMHC + Methane)

therm

100,000 British Thermal Unit

Title V

Title V of the federal Clean Air Act. Requires a federally enforceable operating permit program for major and certain other facilities.

TOC

Total Organic Compounds (NMOC + Methane, Same as THC)

TPH

Total Petroleum Hydrocarbons

TRMP

Toxic Risk Management Policy

TRS

Total Reduced Sulfur

TSP

Total Suspended Particulate

TVP

True Vapor Pressure

VOC

Volatile Organic Compounds

VMT

Vehicle Miles Traveled

XI. GLOSSARY

Symbols:

<	=	less than
>	=	greater than
≤	=	less than or equal to
≥	=	greater than or equal to

Units of Measure:

bhp	=	brake-horsepower
btu	=	British Thermal Unit
BTU	=	British Thermal Unit
°C	=	degrees Centigrade
cfm	=	cubic feet per minute
dscf	=	dry standard cubic feet
°F	=	degrees Fahrenheit
ft ³	=	cubic feet
g	=	grams
gal	=	gallon
gpm	=	gallons per minute
gr	=	grains (7000 grains = 1 pound)
hp	=	horsepower
hr	=	hour
in	=	inches
kg	=	kilograms
lb	=	pound
lbmol	=	pound-mole
M	=	thousand
m ²	=	square meter
m ³	=	cubic meters
Mg	=	mega-grams (1000 kg)
min	=	minute
mm	=	millimeter
MM	=	million
MMBTU	=	million BTU
MMcf	=	million cubic feet
mm Hg	=	millimeters of mercury (pressure)
MW	=	megawatts
ppb	=	parts per billion
ppbv	=	parts per billion, by volume
ppm	=	parts per million
ppmv	=	parts per million, by volume
ppmw	=	parts per million, by weight

XI. GLOSSARY

psia	=	pounds per square inch, absolute
psig	=	pounds per square inch, gauge
scf	=	standard cubic feet
scfm	=	standard cubic feet per minute
sdcf	=	standard dry cubic feet
sdcfm	=	standard dry cubic feet per minute
therms	=	1 therm = 100,000 BTU
yd	=	yard
yd ³	=	cubic yards
yr	=	year