

Bay Area Air Quality Management District

939 Ellis Street
San Francisco, CA 94109
(415) 771-6000

~~Final~~ Proposed

MAJOR FACILITY REVIEW PERMIT

Issued To:
Keller Canyon Landfill Company
Facility #A4618

Facility Address:
901 Bailey Road
Pittsburg, CA 94565

Mailing Address:
901 Bailey Road
Pittsburg, CA 94565

Responsible Official
Rick King,
General Manager
925-458-9800

Facility Contact
Rick King,
General Manager
925-458-9800

Type of Facility: Municipal Solid Waste Landfill
Primary SIC: 4953
Product: Class II Solid Waste Disposal

BAAQMD Engineering Division Contact:
Carol S. Allen

ISSUED BY THE BAY AREA AIR QUALITY MANAGEMENT DISTRICT

Signed by Jeff McKay for Jack P. Broadbent
Jack P. Broadbent, Executive Officer/Air Pollution Control Officer

January 11, 2012
Date

TABLE OF CONTENTS

I. STANDARD CONDITIONS.....	3
II. EQUIPMENT.....	8
III. GENERALLY APPLICABLE REQUIREMENTS	10
IV. SOURCE-SPECIFIC APPLICABLE REQUIREMENTS.....	13
V. SCHEDULE OF COMPLIANCE.....	32
VI. PERMIT CONDITIONS.....	33
VII. APPLICABLE LIMITS AND COMPLIANCE MONITORING REQUIREMENTS.....	62
VIII. TEST METHODS.....	81
IX. PERMIT SHIELD.....	85
X. REVISION HISTORY	86
XI. GLOSSARY	95

I. STANDARD CONDITIONS

A. Administrative Requirements

The permit holder shall comply with all applicable requirements in the following regulations:

BAAQMD Regulation 1 - General Provisions and Definitions
(as amended by the District Board on 5/4/11);

SIP Regulation 1 - General Provisions and Definitions
(as approved by EPA through 6/28/99);

BAAQMD Regulation 2, Rule 1 - Permits, General Requirements
(as amended by the District Board on ~~3/4/09~~ 4/8/12);

SIP Regulation 2, Rule 1 - Permits, General Requirements
(as approved by EPA through 1/26/99);

BAAQMD Regulation 2, Rule 2 - Permits, New Source Review
(as amended by the District Board on 6/15/05);

SIP Regulation 2, Rule 2 - Permits, New Source Review and Prevention of Significant Deterioration
(as approved by EPA through 1/26/99);

BAAQMD Regulation 2, Rule 4 - Permits, Emissions Banking
(as amended by the District Board on ~~12/21/04~~ 12/19/12);

SIP Regulation 2, Rule 4 - Permits, Emissions Banking
(as approved by EPA through 1/26/99);

BAAQMD Regulation 2, Rule 5 – Permits, New Source Review of Toxic Air Contaminants
(as amended by the District Board on 1/6/10);

BAAQMD Regulation 2, Rule 6 - Permits, Major Facility Review
(as amended by the District Board on 4/16/03); and

SIP Regulation 2, Rule 6 – Permits, Major Facility Review
(as approved by EPA through 6/23/95).

B. Conditions to Implement Regulation 2, Rule 6, Major Facility Review

1. This Major Facility Review Permit was issued on ~~January 3, 2008~~ [enter issuance date] and expires on ~~January 4, 2013~~ [enter 1 year after issuance date]. The permit holder shall submit a complete application for renewal of this Major Facility Review Permit no later than ~~July 4, 2012~~ [enter date, 6 months before expiration date] and no earlier than ~~January 4, 2012~~ [enter date, 1 year before expiration date]. **If a complete application for renewal has not been submitted in accordance with this deadline, the facility may not operate after ~~January 4, 2013~~ [enter expiration date].** If the permit renewal has not been issued by ~~January 4, 2013~~ [enter expiration date], but a complete application for renewal has been submitted in accordance with the above deadlines, the existing permit will continue in force until the District takes final action on the renewal application.

I. Standard Conditions

(Regulation 2-6-307, 404.2, 407, & 409.6; MOP Volume II, Part 3, §4.2)

2. The permit holder shall comply with all conditions of this permit. The permit consists of this document and all appendices. Any non-compliance with the terms and conditions of this permit will constitute a violation of the law and will be grounds for enforcement action; permit termination, revocation and re-issuance, or modification; or denial of a permit renewal application. (Regulation 2-6-307; MOP Volume II, Part 3, §4.11)
3. In the event any enforcement action is brought as a result of a violation of any term or condition of this permit, the fact that it would have been necessary for the permittee to halt or reduce the permitted activity in order to maintain compliance with such term or condition shall not be a defense to such enforcement action. (MOP Volume II, Part 3, §4.11)
4. This permit may be modified, revoked, reopened and reissued, or terminated for cause. (Regulation 2-6-307, 409.8, 415; MOP Volume II, Part 3, §4.11)
5. The filing of a request by the facility for a permit modification, revocation and re-issuance, or termination, or the filing of a notification of planned changes or anticipated non-compliance does not stay the applicability of any permit condition. (Regulation 2-6-409.7; MOP Volume II, Part 3, §4.11)
6. This permit does not convey any property rights of any sort, or any exclusive privilege. (Regulation 2-6-409.7; MOP Volume II, Part 3, §4.11)
7. The permit holder shall supply within 30 days any information that the District requests in writing to determine whether cause exists for modifying, revoking and reissuing, or terminating the permit or to determine compliance with the permit. (Regulation 1-441, Regulation 2-6-409.7 & 501; MOP Volume II, Part 3, §4.11)
8. Any records required to be maintained pursuant to this permit that the permittee considers to contain proprietary or trade secret information shall be prominently designated as such. Copies of any such proprietary or trade secret information which are provided to the District shall be maintained by the District in a locked confidential file, provided, however, that requests from the public for the review of any such information shall be handled in accordance with the District's procedures set forth in Section 11 of the District's Administrative Code. (Regulation 2-6-419; MOP Volume II, Part 3, §4.11)
9. Proprietary or trade secret information provided to EPA will be subject to the requirements of 40 CFR Part 2, Subpart B - Public Information, Confidentiality of Business Information. (40 CFR Part 2)
10. The emissions inventory submitted with the application for this Major Facility Review Permit is an estimate of actual emissions or the potential to emit for the time period stated and is included only as one means of determining applicable requirements for emission sources. It does not establish, or constitute a basis for

I. Standard Conditions

establishing, any new emission limitations. (MOP Volume II, Part 3, §4.11)

11. The responsible official shall certify all documents submitted by the facility pursuant to the major facility review permit. The certification shall state that based on information and belief formed after reasonable inquiry, the statements and information in the document are true, accurate, and complete. The certifications shall be signed by a responsible official for the facility. (Regulation 2-6-409.20, MOP Volume II, Part 3, §4.11)
12. The permit holder is responsible for compliance, and certification of compliance, with all conditions of the permit, regardless whether it acts through employees, agents, contractors, or subcontractors. (Regulation 2-6-307)

C. Requirement to Pay Fees

The permit holder shall pay annual fees in accordance with District Regulation 3, including Schedule P. (Regulation 2-6-402 & 409.13, Regulation 3; MOP Volume II, Part 3, §4.12)

D. Inspection and Entry

Access to Facility: The permit holder shall provide reasonable access to the facility and equipment which is subject to this permit to the APCO and/or to his or her designee. (Regulation 1-440, Regulation 2-6-409.3; MOP Volume II, Part 3, §4.14)

E. Records

1. The permit holder must provide any information, records, and reports requested or specified by the APCO. (Regulation 1-441, Regulation 2-6-409.4)
2. Notwithstanding the specific wording in any requirement, all records for federally enforceable requirements shall be maintained for at least five years from the date of creation of the record. (Regulation 2-6-501, MOP Volume II, Part 3, §4.7)

F. Monitoring Reports

Reports of all required monitoring must be submitted to the District at least once every six months, except where an applicable requirement specifies more frequent reporting. ~~The first reporting period for this permit shall be September 20, 2001 to February 28, 2002. The report shall be submitted by March 31, 2002. Subsequent~~ Reports shall be for the following periods: March 1st through August 31st and September 1st through February 28th or 29th, and are due on the last day of the month after the end of the reporting period. All instances of non-compliance shall be clearly identified in these reports. The reports shall be certified by the responsible official as true, accurate, and complete. In addition, all instances of non-compliance with the

I. Standard Conditions

permit shall be reported in writing to the District's Compliance and Enforcement Division within 10 calendar days of the discovery of the incident. Within 30 calendar days of the discovery of any incident of non-compliance, the facility shall submit a written report including the probable cause of non-compliance and any corrective or preventative actions. The reports shall be sent to the following address:

Director of Compliance and Enforcement
Bay Area Air Quality Management District
939 Ellis Street
San Francisco, CA 94109
Attn: Title V Reports

(Regulation 2-6-502, MOP Volume II, Part 3, §4.7)

G. Compliance Certification

Compliance certifications shall be submitted annually by the responsible official of this facility to the Bay Area Air Quality Management District and to the Environmental Protection Agency. The certification period will be September 1st through August 31st. The certification shall be submitted by September 30th of each year. The certification must list each applicable requirement, the compliance status, whether compliance was continuous or intermittent, the method used to determine compliance, and any other specific information required by the permit. ~~The permit holder may satisfy this requirement through submittal of District-generated Compliance Certification forms.~~ The certification should be directed to the District's Compliance and Enforcement Division at the address above, and a copy of the certification should be sent to the Environmental Protection Agency at the following address:

Director of the Air Division
USEPA, Region IX
75 Hawthorne Street
San Francisco, CA 94105
Attention: Air-3

(MOP Volume II, Part 3, §4.5 and 4.15)

H. Emergency Provisions

1. The permit holder may seek relief from enforcement action in the event of a breakdown, as defined by Regulation 1-208 of the District's Rules and Regulations, by following the procedures contained in Regulations 1-431 and 1-432. The District will thereafter determine whether breakdown relief will be granted in accordance with Regulation 1-433. (MOP Volume II, Part 3, §4.8)

I. Standard Conditions

2. The permit holder may seek relief from enforcement action for a violation of any of the terms and conditions of this permit by applying to the District's Hearing Board for a variance pursuant to Health and Safety Code Section 42350. The Hearing Board will determine after notice and hearing whether variance relief should be granted in accordance with the procedures and standards set forth in Health and Safety Code Section 42350 et seq. (MOP Volume II, Part 3, §4.8)
3. The granting by the District of breakdown relief or the issuance by the Hearing Board of a variance will not provide relief from federal enforcement. (MOP Volume II, Part 3, §4.8)

I. Severability

In the event that any provision of this permit is invalidated by a court or tribunal of competent jurisdiction, or by the Administrator of the EPA, all remaining portions of the permit shall remain in full force and effect. (Regulation 2-6-409.5; MOP Volume II, Part 3, §4.10)

J. Miscellaneous Conditions

1. The maximum capacity for each source as shown in Table II-A is the maximum allowable capacity. Exceedance of the maximum allowable capacity for any source is a violation of Regulation 2, Rule 1, Section 301. (Regulation 2-1-301)

II. EQUIPMENT

A. Permitted Source List

Each of the following sources has been issued a permit to operate pursuant to the requirements of BAAQMD Regulation 2, Permits. The capacities in this table are the maximum allowable capacities for each source, pursuant to Standard Condition I.J and Regulation 2-1-301.

Table II – A
– Permitted Sources

~~Each of the following sources has been issued a permit to operate pursuant to the requirements of BAAQMD Regulation 2, Permits. The capacities in this table are the maximum allowable capacities for each source, pursuant to Standard Condition I.J. and Regulation 2-1-301.~~

S-#	Description	Make or Type	Model	Capacity
S-1	Keller Canyon Landfill – <u>Waste Decomposition Process; equipped</u> with Active Gas Collection System:	Class II Disposal Operations (MSW, commercial, industrial, construction, designated, and special wastes)		Max. Design Capacity (waste and cover, excluding final cover) = 75 million yd ³ (57.3 million m ³) Max. Waste Acceptance Rate = 3500 tons/day Max. Cumulative Waste In-Place = 38.4 million tons (34.8 million Mg)
	Main Gas Collection System			78-95 vertical wells 1 horizontal collector
	<u>Other Components (with Intermittent Vacuum)</u>			<u>1 horizontal collector</u> <u>1 leachate cleanout riser</u>
S-3	Yard and Green Waste Stockpiles	Yard and Green Waste		225 tons/day
<u>S-4</u>	<u>Keller Canyon Landfill – Waste and Cover Material Dumping</u>	<u>Wastes: MSW, commercial, industrial, construction, designated and special wastes</u> <u>Daily Cover Materials: clean soil, non-hazardous VOC-laden soil, and shredded green waste.</u>		<u>Max. Waste Acceptance Rate = 3,500 tons/day</u> <u>Max. Daily Cover Placement Rate = 300 tons/day (estimated by BAAQMD)</u>
<u>S-5</u>	<u>Keller Canyon Landfill – Excavating, Bulldozing, and Compacting Activities</u>			<u>as needed</u>

II. Equipment

B. Abatement Device List

Table II ~~–~~ B ~~–~~
Abatement Devices

A-#	Description	Source(s) Controlled	Applicable Requirement	Operating Parameters	Limit or Efficiency
A-1	Enclosed Ground Flare, burning propane (during start-up only) and landfill gas, 72.7 MM BTU/hour	S-1	BAAQMD 8-34-301.3, See also Table IV-A	Minimum combustion zone temperature of: 1504 °F (3-hour average), See also Table VII-A	Either 98% destruction of NMOC or < 30 ppmv of NMOC, as CH ₄ , at 3% O ₂ , dry, See also Table VII-A
A-2	Enclosed Ground Flare, burning propane (during start-up only) and landfill gas, 76 MM BTU/hour (not constructed yet)	S-1	BAAQMD 8-34-301.3, See also Table IV-A	Minimum combustion zone temperature of: 1400 °F (3-hour average), See also Table VII-A	Either 98% destruction of NMOC or < 30 ppmv of NMOC, as CH ₄ , at 3% O ₂ , dry, See also Table VII-A

III. GENERALLY APPLICABLE REQUIREMENTS

The permit holder shall comply with all applicable requirements, including those specified in the BAAQMD and SIP Rules and Regulations and other federal requirements cited below. These requirements apply in a general manner to the facility and/or to sources exempt from the requirement to obtain a District Permit to Operate. The District has determined that these requirements will not be violated under normal, routine operations, and that no additional periodic monitoring or reporting to demonstrate compliance is warranted. In cases where a requirement, in addition to being generally applicable, is also specifically applicable to one or more sources, the requirement and the source are also included in Section IV, Source-Specific Applicable Requirements, of this permit. This section also contains provisions that may apply to temporary sources.

The dates in parentheses in the Title column identify the versions of the regulations being cited and are, as applicable:

1. BAAQMD regulation(s): The date(s) of adoption or most recent amendment of the regulation by the District Board of Directors
2. Any federal requirement, including a version of a District regulation that has been approved into the SIP: The most recent date of EPA approval of any portion of the rule, encompassing all actions on the rule through that date

The full language of SIP requirements is on EPA Region 9's website. The address is:

<http://yosemite.epa.gov/r9/r9sips.nsf/Agency?ReadForm&count=500&state=California&cat=Bay+Area+Air+Quality+Management+District-Agency-Wide+Provisions>.

NOTE:

There are differences between the current BAAQMD rules and the version of the rules in the SIP. All sources must comply with both versions of the rule until US EPA has reviewed and approved the District's revision of the regulation.

**Table III
 Generally Applicable Requirements**

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)
BAAQMD Regulation 1	General Provisions and Definitions (5/4/11)	N
SIP Regulation 1	General Provisions and Definitions (6/28/99)	Y
BAAQMD Regulation 2, Rule 1	Permits – General Requirements (3/4/09 4/8/12)	N
BAAQMD 2-1-429	Federal Emissions Statement (12/21/04)	N
SIP Regulation 2, Rule 1	Permits – General Requirements (1/26/99)	Y
SIP 2-1-429	Federal Emissions Statement (4/3/95)	Y

III. Generally Applicable Requirements

Table III
Generally Applicable Requirements

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)
BAAQMD Regulation 2, Rule 5	Permits – New Source Review of Toxic Air Contaminants (1/6/10)	N
BAAQMD Regulation 4	Air Pollution Episode Plan (3/20/91)	N
SIP Regulation 4	Air Pollution Episode Plan (8/6/90)	Y
BAAQMD Regulation 5	Open Burning (7/9/08)	N
SIP Regulation 5	Open Burning (9/4/98)	Y
BAAQMD Regulation 6, Rule 1	Particulate Matter – General Requirements (12/5/07)	N
SIP Regulation 6	Particulate Matter and Visible Emissions (9/4/98)	Y
BAAQMD Regulation 7	Odorous Substances (3/17/82)	N
BAAQMD Regulation 8, Rule 1	Organic Compounds – General Provisions (6/15/94)	Y
BAAQMD Regulation 8, Rule 2	Organic Compounds – Miscellaneous Operations (7/20/05)	N
SIP Regulation 8, Rule 2	Organic Compounds – Miscellaneous Operations (3/22/95)	Y
BAAQMD Regulation 8, Rule 3	Organic Compounds – Architectural Coatings (7/1/09)	N
SIP Regulation 8, Rule 3	Organic Compounds – Architectural Coatings (1/2/04)	Y
BAAQMD Regulation 8, Rule 4	Organic Compounds – General Solvent and Surface Coating Operations (10/16/02)	Y
BAAQMD Regulation 8, Rule 15	Organic Compounds – Emulsified and Liquid Asphalts (6/1/94)	Y
BAAQMD Regulation 8, Rule 16	Organic Compounds – Solvent Cleaning Operations (10/16/02)	Y
BAAQMD Regulation 8, Rule 40	Organic Compounds – Aeration of Contaminated Soil and Removal of Underground Storage Tanks (6/15/05)	Y
BAAQMD 8-40-116	Exemption, Small Volume	Y
BAAQMD 8-40-117	Exemption, Accidental Spills	Y
BAAQMD Regulation 8, Rule 47	Organic Compounds – Air Stripping and Soil Vapor Extraction Operations (6/15/05)	N
SIP Regulation 8, Rule 47	Organic Compounds – Air Stripping and Soil Vapor Extraction Operations (4/26/95)	Y
BAAQMD Regulation 8, Rule 49	Organic Compounds – Aerosol Paint Products (12/20/95)	N
SIP Regulation 8, Rule 49	Organic Compounds – Aerosol Paint Products (3/22/95)	Y
BAAQMD Regulation 8, Rule 51	Organic Compounds – Adhesive and Sealant Products (7/17/02)	N
SIP Regulation 8, Rule 51	Organic Compounds – Adhesive and Sealant Products (2/26/02)	Y
BAAQMD Regulation 9, Rule 1	Inorganic Gaseous Pollutants – Sulfur Dioxide (3/15/95)	N
SIP Regulation 9, Rule 1	Inorganic Gaseous Pollutants – Sulfur Dioxide (6/8/99)	Y
BAAQMD Regulation 11, Rule 1	Hazardous Pollutants – Lead (3/17/82)	N
SIP Regulation 11, Rule 1	Hazardous Pollutants – Lead (9/2/81)	Y
BAAQMD Regulation 11, Rule 2	Hazardous Pollutants – Asbestos Demolition, Renovation and Manufacturing (10/7/98)	N

III. Generally Applicable Requirements

**Table III
 Generally Applicable Requirements**

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)
BAAQMD Regulation 11, Rule 14	Hazardous Pollutants – Asbestos Containing Serpentine (7/17/91)	N
BAAQMD Regulation 12, Rule 4	Miscellaneous Standards of Performance – Sandblasting (7/11/90)	N
SIP Regulation 12, Rule 4	Miscellaneous Standards of Performance – Sandblasting (9/2/81)	Y
California Health and Safety Code Section 41750 et seq.	Portable Equipment	N
California Health and Safety Code Section 44300 et seq.	Air Toxics “Hot Spots” Information and Assessment Act of 1987	N
California Code of Regulations Title 17, Section 93105	Asbestos Airborne Toxic Control Measure for Construction, Grading, Quarrying, and Surface Mining Operations (7/26/01)	N
California Code of Regulations Title 17, Section 93106	Asbestos Airborne Toxic Control Measure for Asbestos-Containing Serpentine (7/20/00)	N
California Code of Regulations Title 17, Section 93115	Airborne Toxic Control Measure for Stationary Compression Ignition Engines (5/19/11)	N
California Code of Regulations Title 17, Section 93116	Airborne Toxic Control Measure for Diesel Particulate Matter from Portable Engines Rated at 50 Horsepower and Greater (2/19/11)	N
40 CFR Part 61, Subpart A	National Emission Standards for Hazardous Air Pollutants – General Provisions (9/13/10 16/12)	Y
40 CFR Part 61, Subpart M	National Emission Standards for Hazardous Air Pollutants – National Emission Standard for Asbestos (7/20/04 11/28/06)	Y

IV. SOURCE-SPECIFIC APPLICABLE REQUIREMENTS

The permit holder shall comply with all applicable requirements, including those specified in the BAAQMD and SIP Rules and Regulations and other federal requirements cited below. The requirements cited in the following tables apply in a specific manner to the indicated source(s).

The dates in parentheses in the Title column identify the versions of the regulations being cited and are, as applicable:

1. BAAQMD regulation(s): The date(s) of adoption or most recent amendment of the regulation by the District Board of Directors
2. Any federal requirement, including a version of a District regulation that has been approved into the SIP: The most recent date of EPA approval of any portion of the rule, encompassing all actions on the rule through that date

The full text of each permit condition cited is included in Section VI, Permit Conditions, of this permit. The full language of SIP requirements is on EPA Region 9's website. The address is:

<http://yosemite.epa.gov/r9/r9sips.nsf/Agency?ReadForm&count=500&state=California&cat=Bay+Area+Air+Quality+Management+District-Agency-Wide+Provisions>

All other text may be found in the regulations themselves.

**Table IV – A
 Source-Specific Applicable Requirements**

S-1 KELLER CANYON LANDFILL; – WASTE DECOMPOSITION PROCESS; ABATED BY A-1 LANDFILL GAS FLARE, AND A-2 LANDFILL GAS FLARE; S-4 KELLER CANYON LANDFILL – WASTE AND COVER MATERIAL DUMPING; AND S-5 KELLER CANYON LANDFILL – EXCAVATING, BULLDOZING, AND COMPACTING ACTIVITIES

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
BAAQMD Regulation 1	General Provisions and Definitions (5/4/11)		
1-523	Parametric Monitoring and Recordkeeping Procedures	N	
1-523.1	Reporting requirement for periods of inoperation > 24 hours	Y	
1-523.2	Limit on duration of inoperation	Y	
1-523.3	Reporting requirement for violations of any applicable limits	N	
1-523.4	Records of inoperation, tests, calibrations, adjustments, & maintenance	Y	
1-523.5	Maintenance and calibration	N	

IV. Source-Specific Applicable Requirements

Table IV – A
Source-Specific Applicable Requirements
S-1 KELLER CANYON LANDFILL, – WASTE DECOMPOSITION PROCESS;
ABATED BY A-1 LANDFILL GAS FLARE, AND A-2 LANDFILL GAS FLARE;
S-4 KELLER CANYON LANDFILL – WASTE AND COVER MATERIAL DUMPING; AND
S-5 KELLER CANYON LANDFILL – EXCAVATING, BULLDOZING, AND COMPACTING
ACTIVITIES

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
SIP Regulation 1	General Provisions and Definitions (6/28/99)		
1-523	Parametric Monitoring and Recordkeeping Procedures	Y	
1-523.3	Reports of Violations	Y	
BAAQMD Regulation 6, Rule 1	Particulate Matter – General Requirements (12/5/07)		
6-1-301	Ringelmann No. 1 Limitation	N	
6-1-305	Visible Particles	N	
6-1-310	Particulate Weight Limitation (applies to flares only)	N	
6-1-401	Appearance of Emissions	N	
SIP Regulation 6	Particulate Matter and Visible Emissions (9/4/98)		
6-301	Ringelmann No. 1 Limitation	Y	
6-305	Visible Particles	Y	
6-310	Particulate Weight Limitation (applies to flares only)	Y	
6-401	Appearance of Emissions	Y	
BAAQMD Regulation 8, Rule 2	Organic Compounds – Miscellaneous Operations (7/20/05)		
8-2-301	Miscellaneous Operations	Y	
BAAQMD Regulation 8, Rule 34	Organic Compounds – Solid Waste Disposal Sites (6/15/05)		
8-34-113	Limited Exemption, Inspection and Maintenance	Y	
8-34-113.1	Emission Minimization Requirement	Y	
8-34-113.2	Shutdown Time Limitation	Y	
8-34-113.3	Recordkeeping Requirement	Y	
8-34-116	Limited Exemption, Well Raising	Y	
8-34-116.1	New Fill	Y	
8-34-116.2	Limits on Number of Wells Shutdown	Y	

IV. Source-Specific Applicable Requirements

Table IV – A
Source-Specific Applicable Requirements

S-1 KELLER CANYON LANDFILL; – WASTE DECOMPOSITION PROCESS; ABATED BY A-1 LANDFILL GAS FLARE, AND A-2 LANDFILL GAS FLARE; S-4 KELLER CANYON LANDFILL – WASTE AND COVER MATERIAL DUMPING; AND S-5 KELLER CANYON LANDFILL – EXCAVATING, BULLDOZING, AND COMPACTING ACTIVITIES

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
8-34-116.3	Shutdown Duration Limit	Y	
8-34-116.4	Capping Well Extensions	Y	
8-34-116.5	Well Disconnection Records	Y	
8-34-117	Limited Exemption, Gas Collection System Components	Y	
8-34-117.1	Necessity of Existing Component Repairs/Adjustments	Y	
8-34-117.2	New Components are Described in Collection and Control System Design Plan	Y	
8-34-117.3	Meets Section 8-34-118 Requirements	Y	
8-34-117.4	Limits on Number of Wells Shutdown	Y	
8-34-117.5	Shutdown Duration Limit	Y	
8-34-117.6	Well Disconnection Records	Y	
8-34-118	Limited Exemption, Construction Activities	Y	
8-34-118.1	Construction Plan	Y	
8-34-118.2	Activity is Required to Maintain Compliance with this Rule	Y	
8-34-118.3	Required or Approved by Other Enforcement Agencies	Y	
8-34-118.4	Emission Minimization Requirement	Y	
8-34-118.5	Excavated Refuse Requirements	Y	
8-34-118.6	Covering Requirements for Exposed Refuse	Y	
8-34-118.7	Installation Time Limit	Y	
8-34-118.8	Capping Required for New Components	Y	
8-34-118.9	Construction Activity Records	Y	
8-34-301	Landfill Gas Collection and Emission Control System Requirements	Y	
8-34-301.1	Continuous Operation	Y	
8-34-301.2	Collection and Control Systems Leak Limitations	Y	
8-34-301.3	Limits for Enclosed Flares (applies to flares only)	Y	
8-34-303	Landfill Surface Requirements	Y	
8-34-304	Gas Collection System Installation Requirements	Y	
8-34-304.1	Based on Waste Age For Inactive or Closed Areas	Y	
8-34-304.2	Based on Waste Age For Active Areas	Y	
8-34-304.3	Based on Amount of Decomposable Waste Accepted	Y	
8-34-304.4	Based on NMOC Emission Rate	Y	

IV. Source-Specific Applicable Requirements

Table IV – A
Source-Specific Applicable Requirements
S-1 KELLER CANYON LANDFILL, – WASTE DECOMPOSITION PROCESS;
ABATED BY A-1 LANDFILL GAS FLARE, AND A-2 LANDFILL GAS FLARE;
S-4 KELLER CANYON LANDFILL – WASTE AND COVER MATERIAL DUMPING; AND
S-5 KELLER CANYON LANDFILL – EXCAVATING, BULLDOZING, AND COMPACTING
ACTIVITIES

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
8-34-305	Wellhead Requirements	Y	
8-34-305.1	Wellhead Vacuum Requirement	Y	
8-34-305.2	Wellhead Temperature Limit	Y	
8-34-305.3	Nitrogen Concentration Limit for Wellhead Gas or	Y	
8-34-305.4	Oxygen Concentration Limit for Wellhead Gas (except for wells identified in Condition # 17309, Part 20c(i))	Y	
8-34-404	Less than Continuous Operation Petition	Y	
8-34-405	Design Capacity Reports	Y	
8-34-408	Collection and Control System Design Plan	Y	
8-34-408.2	Sites With Existing Collection and Control Systems	Y	
8-34-411	Annual Report	Y	
8-34-412	Compliance Demonstration Tests	Y	
8-34-413	Performance Test Report	Y	
8-34-414	Repair Schedule for Wellhead Excesses	Y	
8-34-414.1	Records of Excesses	Y	
8-34-414.2	Corrective Action	Y	
8-34-414.3	Collection System Expansion	Y	
8-34-414.4	Operational Due Date for Expansion	Y	
8-34-415	Repair Schedule for Surface Leak Excesses	Y	
8-34-415.1	Records of Excesses	Y	
8-34-415.2	Corrective Action	Y	
8-34-415.3	Re-monitor Excess Location Within 10 Days	Y	
8-34-415.4	Re-monitor Excess Location Within 1 Month	Y	
8-34-415.5	If No More Excesses, No Further Re-Monitoring	Y	
8-34-415.6	Additional Corrective Action	Y	
8-34-415.7	Re-monitor Second Excess Within 10 days	Y	
8-34-415.8	Re-monitor Second Excess Within 1 Month	Y	
8-34-415.9	If No More Excesses, No Further Re-monitoring	Y	
8-34-415.10	Collection System Expansion for Third Excess in a Quarter	Y	
8-34-415.11	Operational Due Date for Expansion	Y	
8-34-416	Cover Repairs	Y	

IV. Source-Specific Applicable Requirements

Table IV – A
Source-Specific Applicable Requirements

S-1 KELLER CANYON LANDFILL, – WASTE DECOMPOSITION PROCESS; ABATED BY A-1 LANDFILL GAS FLARE, AND A-2 LANDFILL GAS FLARE; S-4 KELLER CANYON LANDFILL – WASTE AND COVER MATERIAL DUMPING; AND S-5 KELLER CANYON LANDFILL – EXCAVATING, BULLDOZING, AND COMPACTING ACTIVITIES

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
8-34-501	Operating Records	Y	
8-34-501.1	Collection System Downtime	Y	
8-34-501.2	Emission Control System Downtime (applies to flares only)	Y	
8-34-501.3	Continuous Temperature Records for Enclosed Combustors (applies to flares only)	Y	
8-34-501.4	Testing	Y	
8-34-501.6	Leak Discovery and Repair Records	Y	
8-34-501.7	Waste Acceptance Records	Y	
8-34-501.8	Non-decomposable Waste Records	Y	
8-34-501.9	Wellhead Excesses and Repair Records	Y	
8-34-501.10	Gas Flow Rate Records for All Emission Control Systems	Y	
8-34-501.12	Records Retention for 5 Years	Y	
8-34-503	Landfill Gas Collection and Emission Control System Leak Testing	Y	
8-34-504	Portable Hydrocarbon Detector	Y	
8-34-505	Well Head Monitoring	Y	
8-34-506	Landfill Surface Monitoring	Y	
8-34-507	Continuous Temperature Monitor and Recorder (applies to flares only)	Y	
8-34-508	Gas Flow Meter	Y	
8-34-510	Cover Integrity Monitoring	Y	
BAAQMD Regulation 8, Rule 40	Organic Compounds – Aeration of Contaminated Soil and Removal of Underground Storage Tanks (6/15/05)		
8-40-110	Exemption, Storage Pile	Y	
8-40-112	Exemption, Sampling	Y	
8-40-113	Exemption, Non-Volatile Hydrocarbons	Y	
8-40-116	Exemption, Small Volume	Y	
8-40-116.1	Volume does not exceed 1 cubic yard	Y	
8-40-116.2	Volume does not exceed 8 cubic yards, organic content does not exceed 500 ppmw, may be used only once per quarter	Y	
8-40-117	Exemption, Accidental Spills	Y	
8-40-118	Exemption, Aeration Projects of Limited Impact	Y	

IV. Source-Specific Applicable Requirements

Table IV – A
Source-Specific Applicable Requirements

S-1 KELLER CANYON LANDFILL; – WASTE DECOMPOSITION PROCESS; ABATED BY A-1 LANDFILL GAS FLARE, AND A-2 LANDFILL GAS FLARE; S-4 KELLER CANYON LANDFILL – WASTE AND COVER MATERIAL DUMPING; AND S-5 KELLER CANYON LANDFILL – EXCAVATING, BULLDOZING, AND COMPACTING ACTIVITIES

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
8-40-301	Uncontrolled Contaminated Soil Aeration	Y	
8-40-304	Active Storage Piles	Y	
8-40-305	Inactive Storage Piles	Y	
BAAQMD Regulation 9, Rule 1	Inorganic Gaseous Pollutants – Sulfur Dioxide (3/15/95)		
9-1-301	Limitations on Ground Level Concentrations (applies to flares only)	Y	
9-1-302	General Emission Limitations (applies to flares only)	Y	
BAAQMD Regulation 9, Rule 2	Inorganic Gaseous Pollutants – Hydrogen Sulfide (10/6/99)		
9-2-301	Limitations on Hydrogen Sulfide	N	
40 CFR Part 60, Subpart A	Standards of Performance for New Stationary Sources – General Provisions (9/13/102/16/12)		
60.4	Address	Y	
60.4(b)	Requires Submission of Requests, Reports, Applications, and Other Correspondence to the Administrator	Y	
60.7	Notification and Record Keeping	Y	
60.8	Performance Tests	Y	
60.11	Compliance with Standards and Maintenance Requirements	Y	
60.11(a)	Compliance determined by performance tests	Y	
60.11(d)	Control devices operated using good air pollution control practice	Y	
60.12	Circumvention	Y	
60.13	Monitoring Requirements	Y	
60.13(a)	Applies to all continuous monitoring systems	Y	
60.13(b)	Monitors shall be installed and operational before performing performance tests	Y	
60.13(e)	Continuous monitors shall operate continuously	Y	
60.13(f)	Monitors shall be installed in proper locations	Y	
60.13(g)	Multiple monitors are required for multiple stacks	Y	

IV. Source-Specific Applicable Requirements

Table IV – A
Source-Specific Applicable Requirements
S-1 KELLER CANYON LANDFILL; – WASTE DECOMPOSITION PROCESS;
ABATED BY A-1 LANDFILL GAS FLARE, AND A-2 LANDFILL GAS FLARE;
S-4 KELLER CANYON LANDFILL – WASTE AND COVER MATERIAL DUMPING; AND
S-5 KELLER CANYON LANDFILL – EXCAVATING, BULLDOZING, AND COMPACTING
ACTIVITIES

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
60.14	Modification	Y	
60.15	Reconstruction	Y	
60.19	General Notification and Reporting Requirements	Y	
40 CFR Part 60, Subpart WWW	Standards of Performance for New Stationary Sources – Standards of Performance for Municipal Solid Waste Landfills (9/21/06)		
60.752	Standards for Air Emissions from Municipal Solid Waste Landfills	Y	
60.752(b)	Requirements for MSW Landfills with Design Capacity equal to or greater than 2.5 million Mg and 2.5 million m ³ (Large Designated Facilities)	Y	
60.752(b)(2)	Comply with all requirements in sections (b)(2)(i through iv)	Y	
60.752 (b)(2)(i)	Submit a Collection and Control System Design Plan	Y	
60.752 (b)(2)(i)(A)	The collection and control system in the Design Plan shall comply with 60.752(b)(2)(ii)	Y	
60.752 (b)(2)(i)(B)	Design Plan shall include all proposed alternatives to 60.753 through 60.758	Y	
60.752 (b)(2)(i)(C)	Design Plan shall conform to 60.759 (active collection system) or demonstrate sufficiency of proposed alternatives	Y	
60.752 (b)(2)(ii)	Install a collection and control system	Y	
60.752 (b)(2)(iii)	Route collected gases to a control system.	Y	
60.752 (b)(2)(iii)(B)	Reduce NMOC emissions by 98% by weight or reduce NMOC outlet concentration to less than 20 ppmv as hexane at 3% O ₂ , dry basis, as demonstrated by initial performance test within 180 days of start-up. (applies to flares only)	Y	
60.752 (b)(2)(iii)(C)	Process the collected gas for subsequent sale or use in a treatment system, where any atmospheric vents from this treatment system comply with paragraph (b)(2)(iii)(B) above.	Y	
60.752 (b)(2)(iv)	Operate in accordance with 60.753, 60.755, and 60.756	Y	

IV. Source-Specific Applicable Requirements

Table IV – A
Source-Specific Applicable Requirements
S-1 KELLER CANYON LANDFILL – WASTE DECOMPOSITION PROCESS;
ABATED BY A-1 LANDFILL GAS FLARE, AND A-2 LANDFILL GAS FLARE;
S-4 KELLER CANYON LANDFILL – WASTE AND COVER MATERIAL DUMPING; AND
S-5 KELLER CANYON LANDFILL – EXCAVATING, BULLDOZING, AND COMPACTING
ACTIVITIES

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
60.752(c)	Title V Operating Permit Requirements	Y	
60.752(c)(1)	Subject date is June 10, 1996 for Landfills new or modified between May 30, 1991 and March 12, 1996	Y	
60.753	Operational Standards for Collection and Control Systems	Y	
60.753(a)	Operate a Collection System in each area or cell in which:	Y	
60.753(a)(1)	Active Cell – solid waste in place for 5 years or more	Y	
60.753(a)(2)	Closed/Final Grade – solid waste in place for 2 years or more	Y	
60.753(b)	Operate each wellhead under negative pressure unless:	Y	
60.753(b)(1)	Fire or increased well temperature or to prevent fire	Y	
60.753(b)(2)	Use of geomembrane or synthetic cover (subject to alternative pressure limits)	Y	
60.753(b)(3)	Decommissioned well after approval received for shut-down	Y	
60.753(c)	Operate each wellhead at < 55 °C, and either < 20% N ₂ or < than 5% O ₂ (or other approved alternative levels for wells identified in Condition # 17309, Part 20c(i))	Y	
60.753(c)(1)	N ₂ determined by Method 3C	Y	
60.753(c)(2)	O ₂ determined by 3A and as described in (2)(i-v)	Y	
60.753(d)	Surface Leak Limit is less than 500 ppm methane above background at landfill surface. This section also describes some surface monitoring procedures.	Y	
60.753(e)	Vent all collected gases to a control system complying with 60.752(b)(2)(iii). If collection or control system inoperable, shut down gas mover and close all vents within 1 hour	Y	
60.753(f)	Operate the control system at all times when collected gas is routed to the control system (applies to flares only)	Y	
60.753(g)	If monitoring demonstrates that 60.753(b), (c), or (d) are not being met, corrective action must be taken	Y	
60.754	Test Methods and Procedures	Y	
60.754(a)	NMOC Calculation Procedures for NMOC Emission Rate Reports and Comparison to 50 Mg/Year Standard	Y	
60.754(a)(1)	Calculate NMOC Emission Rate using either or both of the equations in 60.754(a)(1)(i-ii) with the listed default values	Y	

IV. Source-Specific Applicable Requirements

Table IV – A
Source-Specific Applicable Requirements
S-1 KELLER CANYON LANDFILL – WASTE DECOMPOSITION PROCESS;
ABATED BY A-1 LANDFILL GAS FLARE, AND A-2 LANDFILL GAS FLARE;
S-4 KELLER CANYON LANDFILL – WASTE AND COVER MATERIAL DUMPING; AND
S-5 KELLER CANYON LANDFILL – EXCAVATING, BULLDOZING, AND COMPACTING
ACTIVITIES

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
60.754 (a)(1)(i)	Equation for known year-to-year waste acceptance rate	Y	
60.754 (a)(1)(ii)	Equation for unknown year-to-year waste acceptance rate	Y	
60.754(a)(2)	Tier 1 - compare calculated NMOC emission rate to 50 Mg/year	Y	
60.754 (a)(2)(ii)	If NMOC Emission Rate \geq 50 Mg/year, comply with 60.752(b)(2) or determine a site-specific NMOC concentration and follow 60.754(a)(3).	Y	
60.754(c)	For PSD, NMOC emissions shall be calculated using AP-42	Y	
60.754(d)	Test Methods for Performance Test (Method 18 or 25C)	Y	
60.755	Compliance Provisions	Y	
60.755(a)	For Gas Collection Systems	Y	
60.755(a)(1)	Calculation procedures for maximum expected gas generation flow rate	Y	
60.755 (a)(1)(i)	Equation for unknown year-to-year waste acceptance rate	Y	
60.755 (a)(1)(ii)	Equation for known year-to-year waste acceptance rate	Y	
60.755(a)(2)	Vertical wells and horizontal collectors shall be of sufficient density to meet all performance specifications.	Y	
60.755(a)(3)	Measure wellhead pressure monthly. If pressure is positive, take corrective action (final corrective action = expand system within 120 days of initial positive pressure reading)	Y	
60.755(a)(4)	Expansion not required during first 180 days after startup.	Y	
60.755(a)(5)	Monitor wellheads monthly for temperature and either nitrogen or oxygen. If readings exceed limits, take corrective action up to expanding system within 120 days of first excess.	Y	
60.755(b)	Wells shall be placed in cells as described in Design Plan and no later than 60 days after:	Y	
60.755(b)(1)	Five years after initial waste placement in cell, for active cells	Y	
60.755(b)(2)	Two years after initial waste placement in cell, for closed/final grade cells.	Y	

IV. Source-Specific Applicable Requirements

Table IV – A
Source-Specific Applicable Requirements

S-1 KELLER CANYON LANDFILL; – WASTE DECOMPOSITION PROCESS; ABATED BY A-1 LANDFILL GAS FLARE, AND A-2 LANDFILL GAS FLARE; S-4 KELLER CANYON LANDFILL – WASTE AND COVER MATERIAL DUMPING; AND S-5 KELLER CANYON LANDFILL – EXCAVATING, BULLDOZING, AND COMPACTING ACTIVITIES

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
60.755(c)	Procedures for complying with surface methane standard	Y	
60.755(c)(1)	Quarterly monitoring of surface and perimeter	Y	
60.755(c)(2)	Procedure for determining background concentration	Y	
60.755(c)(3)	Method 21 except probe inlet placed 5-10 cm above ground	Y	
60.755(c)(4)	Excess is any reading of 500 ppmv or more. Take corrective action indicated below (i-v).	Y	
60.755(c)(4)(i)	Mark and record location of excess	Y	
60.755(c)(4)(ii)	Repair cover or adjust vacuum. Re-monitor within 10 calendar days.	Y	
60.755(c)(4)(iii)	If still exceeding 500 ppmv, take additional corrective action. Re-monitor within 10 calendar days of 2 nd excess.	Y	
60.755(c)(4)(iv)	Re-monitor within 1 month of initial excess.	Y	
60.755(c)(4)(v)	For any location with 3 monitored excesses in a quarter, additional collectors (or other approved collection system repairs) shall be operational within 120 days of 1 st excess.	Y	
60.755(c)(5)	Monitor cover integrity monthly and repair as needed.	Y	
60.755(d)	Instrumentation and procedures for complying with 60.755(c).	Y	
60.755(d)(1)	Portable analyzer meeting Method 21	Y	
60.755(d)(2)	Calibrated with methane diluted to 500 ppmv in air	Y	
60.755(d)(3)	Use Method 21, Section 4.4 instrument evaluation procedures	Y	
60.755(d)(4)	Calibrate per Method 21, Section 4.2 immediately before monitoring.	Y	
60.755(e)	Provisions apply at all times except during startup, shutdown, or malfunction, provided the duration of these shall not exceed 5 days for collection systems or 1 hour for control systems.	Y	
60.756	Monitoring of Operations	Y	
60.756(a)	For active collection systems, install wellhead sampling port	Y	
60.756(a)(1)	Measure gauge pressure in wellhead on a monthly basis	Y	
60.756(a)(2)	Measure nitrogen or oxygen concentration in wellhead gas on a monthly basis.	Y	

IV. Source-Specific Applicable Requirements

Table IV – A
Source-Specific Applicable Requirements
S-1 KELLER CANYON LANDFILL; – WASTE DECOMPOSITION PROCESS;
ABATED BY A-1 LANDFILL GAS FLARE, AND A-2 LANDFILL GAS FLARE;
S-4 KELLER CANYON LANDFILL – WASTE AND COVER MATERIAL DUMPING; AND
S-5 KELLER CANYON LANDFILL – EXCAVATING, BULLDOZING, AND COMPACTING
ACTIVITIES

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
60.756(a)(3)	Measure temperature of wellhead gas on a monthly basis.	Y	
60.756(b)	Enclosed combustors shall comply with (b)(1) and (b)(2)	Y	
60.756(b)(1)	Temperature monitor and continuous recorder (not required for boilers and process heaters with capacity > 44 MW)	Y	
60.756(b)(2)	Device that records flow to or bypass of the control device (i or ii below)	Y	
60.756(b)(2)(i)	Install, calibrate, and maintain a device that records flow to the control device at least every 15 minutes.	Y	
60.756(e)	Procedures for requesting alternative monitoring parameters	Y	
60.756(f)	Monitor surface on a quarterly basis.	Y	
60.757	Reporting Requirements	Y	
60.757(a)	Submit an Initial Design Capacity Report	Y	
60.757(a)(3)	Amended Design Capacity Report required within 90 days of receiving a permitted increase in design capacity or within 90 days of an annual density calculation that results in a design capacity over the thresholds.	Y	
60.757(b)	Submit Initial and Annual NMOC Emission Rate Report	Y	
60.757(b)(3)	Sites with collection and control systems operating in compliance with this subpart are exempt from (b)(1) and (b)(2) above.	Y	
60.757(c)	Submit a Collection and Control System Design Plan within 1 year of first NMOC emission rate report showing NMOC > 50 MG/year, except as follows	Y	
60.757(f)	Submit Annual Reports containing information required by (f)(1) through (f)(6)	Y	
60.757(f)(1)	Value and length of time for exceedance of parameters monitored per 60.756(a), (b) or (d)	Y	
60.757(f)(2)	Description and duration of all periods when gas is diverted from the control device by a by-pass line	Y	
60.757(f)(3)	Description and duration of all periods when control device was not operating for more than 1 hour	Y	
60.757(f)(4)	All periods when collection system was not operating for more than 5 days.	Y	

IV. Source-Specific Applicable Requirements

Table IV – A
Source-Specific Applicable Requirements
S-1 KELLER CANYON LANDFILL, – WASTE DECOMPOSITION PROCESS;
ABATED BY A-1 LANDFILL GAS FLARE, AND A-2 LANDFILL GAS FLARE;
S-4 KELLER CANYON LANDFILL – WASTE AND COVER MATERIAL DUMPING; AND
S-5 KELLER CANYON LANDFILL – EXCAVATING, BULLDOZING, AND COMPACTING
ACTIVITIES

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
60.757(f)(5)	Location of each surface emission excess and all re-monitoring dates and concentrations.	Y	
60.757(f)(6)	Location and installation dates for any wells or collectors added as a result of corrective action for a monitored excess.	Y	
60.757(g)	Initial Performance Test Report Requirements (g)(1-6)	Y	
60.757(g)(1)	Diagram of collection system showing positions of all existing collectors, proposed positions for future collectors, and areas to be excluded from control.	Y	
60.757(g)(2)	Basis for collector positioning to meet sufficient density req.	Y	
60.757(g)(3)	Documentation supporting percentage of asbestos or non-degradable material claims for areas without a collection system.	Y	
60.757(g)(4)	For areas excluded from collection due to non-productivity, calculations and gas generation rates for each non-productive area and the sum for all nonproductive areas.	Y	
60.757(g)(5)	Provisions for increasing gas mover equipment if current system is inadequate to handle maximum projected gas flow rate.	Y	
60.757(g)(6)	Provisions for control of off-site migration	Y	
60.758	Recordkeeping Requirements	Y	
60.758(a)	Design Capacity and Waste Acceptance Records (retain 5 years)	Y	
60.758(b)	Collection and Control Equipment Records (retain for life of control equipment except 5 years for monitoring data)	Y	
60.758(b)(1)	Collection System Records	Y	
60.758 (b)(1)(i)	Maximum expected gas generation flow rate.	Y	
60.758 (b)(1)(ii)	Density of wells and collectors	Y	
60.758(b)(2)	Control System Records - enclosed combustors other than boilers or process heaters with heat input > 44 MW (applies to flares only)	Y	
60.758 (b)(2)(i)	Combustion temperature measured every 15 minutes and averaged over the same time period as the performance test (applies to flares only)	Y	

IV. Source-Specific Applicable Requirements

Table IV – A
Source-Specific Applicable Requirements
S-1 KELLER CANYON LANDFILL, – WASTE DECOMPOSITION PROCESS;
ABATED BY A-1 LANDFILL GAS FLARE, AND A-2 LANDFILL GAS FLARE;
S-4 KELLER CANYON LANDFILL – WASTE AND COVER MATERIAL DUMPING; AND
S-5 KELLER CANYON LANDFILL – EXCAVATING, BULLDOZING, AND COMPACTING
ACTIVITIES

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
60.758 (b)(2)(ii)	Percent NMOC reduction achieved by the control device (applies to flares only)	Y	
60.758(c)	Records of parameters monitored pursuant to 60.756 and periods of operation when boundaries are exceeded (retain for 5 years).	Y	
60.758(c)(1)	Exceedances subject to record keeping are	Y	
60.758 (c)(1)(i)	All 3-hour periods when average combustion temperature was more than 28 C below the average combustion temperature during the most recent complying performance test (applies to flares only)	Y	
60.758(c)(2)	Records of continuous flow to control device or monthly inspection records if seal and lock for bypass valves	Y	
60.758(d)	Plot map showing location of all existing and planned collectors with a unique label for each collector (retain for life of collection system)	Y	
60.758(d)(1)	Installation date and location of all newly installed collectors	Y	
60.758(d)(2)	Records of nature, deposition date, amount, and location of asbestos or non-degradable waste excluded from control	Y	
60.758(e)	Records of any exceedance of 60.753, location of exceedance and re-monitoring dates and data (for wellheads and surface). Retain for 5 years.	Y	
60.759	Specifications for Active Collection Systems	Y	
60.759(a)	Active wells and collectors shall be at sufficient density	Y	
60.759(a)(1)	Collection System in refuse shall be certified by PE to achieve comprehensive control of surface gas emissions	Y	
60.759(a)(2)	Collection Systems (active or passive) outside of refuse shall address migration control	Y	
60.759(a)(3)	All gas producing areas shall be controlled except as described below (i-iii).	Y	
60.759 (a)(3)(i)	Any segregated area of asbestos or non-degradable material only may be excluded, if documented adequately per 60.758(d).	Y	
60.759 (a)(3)(ii)	Any non-productive areas may be excluded from control, provided total NMOC emissions from all excluded areas is < 1% of total NMOC emissions from landfill. Document amount, location, and age of waste and all calculations for each excluded area.	Y	

IV. Source-Specific Applicable Requirements

Table IV – A
Source-Specific Applicable Requirements
S-1 KELLER CANYON LANDFILL; – WASTE DECOMPOSITION PROCESS;
ABATED BY A-1 LANDFILL GAS FLARE, AND A-2 LANDFILL GAS FLARE;
S-4 KELLER CANYON LANDFILL – WASTE AND COVER MATERIAL DUMPING; AND
S-5 KELLER CANYON LANDFILL – EXCAVATING, BULLDOZING, AND COMPACTING
ACTIVITIES

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
60.759 (a)(3)(iii)	For calculating NMOC emissions, values for k and concentration of NMOC that have been previously approved shall be used or defaults if no values were approved. All non-degradable wastes that are being subtracted from total wastes for NMOC calculations must be documented adequately.	Y	
60.759(b)	Gas Collection System Components	Y	
60.759(b)(1)	Must be constructed of PVC, HDPE, fiberglass, stainless steel, or other approved material and of suitable dimensions to convey projected gas amounts and withstand settling, traffic, etc.	Y	
60.759(b)(2)	Collectors shall not endanger liner, shall manage condensate and leachate, and shall prevent air intrusion and surface leaks.	Y	
60.759(b)(3)	Header connection assemblies shall include positive closing throttle valve, seals and couplings to prevent leaks, at least one sampling port, and shall be constructed of PVC, HDPE, fiberglass, stainless steel, or other approved materials.	Y	
60.759(c)	Gas Mover Equipment shall be sized to handle maximum expected gas generation rate over the intended period of use.	Y	
60.759(c)(1)	For existing systems, flow data shall be used to project maximum flow rate.	Y	
60.759(c)(2)	For new systems, gas generation rate shall be calculated per 60.755(a)(1)	Y	
40 CFR Part 63, Subpart A	National Emission Standards for Hazardous Air Pollutants: General Provisions (9/13/10/2/16/12)		
63.4	Prohibited activities and circumvention	Y	
63.5	Preconstruction review and notification requirements	Y	
63.5(b)	Requirements for existing, newly constructed, and reconstructed sources	Y	
63.6	Compliance with standards and maintenance requirements	Y	
63.6(e)	Operation and maintenance requirements and SSM Plan	Y	
63.6(f)	Compliance with non-opacity emission standards	Y	
63.10	Record keeping and reporting requirements	Y	
63.10(b)	General record keeping requirements	Y	

IV. Source-Specific Applicable Requirements

Table IV – A
Source-Specific Applicable Requirements

S-1 KELLER CANYON LANDFILL; – WASTE DECOMPOSITION PROCESS; ABATED BY A-1 LANDFILL GAS FLARE, AND A-2 LANDFILL GAS FLARE; S-4 KELLER CANYON LANDFILL – WASTE AND COVER MATERIAL DUMPING; AND S-5 KELLER CANYON LANDFILL – EXCAVATING, BULLDOZING, AND COMPACTING ACTIVITIES

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
63.10(b)(2)	For affected sources, maintain relevant records of:	Y	
63.10(b)(2) (i-v)	Records for startup, shutdown, malfunction, and maintenance	Y	
63.10(d)	General reporting requirements	Y	
63.10(d)(5)	Startup, Shutdown, and Malfunction (SSM) Reports	Y	
40 CFR Part 63, Subpart AAAA	National Emission Standards for Hazardous Air Pollutants: Municipal Solid Waste Landfills (4/20/06)		
63.1955	What requirements must I meet?	Y	
63.1955(a)	Comply with either 63.1955(a)(1) or (a)(2)	Y	
63.1955(a)(1)	Comply with 40 CFR Part 60, Subpart WWW	Y	
63.1955(b)	Comply with 63.1960-63.1985, if a collection and control system is required by 40 CFR Part 60, Subpart WWW or a State Plan implementing 40 CFR Part 60, Subpart Cc	Y	
63.1955(c)	Comply with all approved alternatives to standards for collection and control systems plus all SSM requirements and 6 month compliance reporting requirements	Y	
63.1960	How is compliance determined?	Y	
63.1965	What is a deviation?	Y	
63.1975	How do I calculate the 3-hour block average used to demonstrate compliance?	Y	
63.1980	What records and reports must I keep and submit?	Y	
63.1980(a)	Comply with all record keeping and reporting requirements in 40 CFR Part 60, Subpart WWW or the State Plan implementing 40 CFR Part 60, Subpart Cc, except that the annual report required by 40 CFR 60.757(f) must be submitted every 6 months	Y	
63.1980(b)	Comply with all record keeping and reporting requirements in 40 CFR Part 60, Subpart A and 40 CFR Part 63, Subpart A, including SSM Plans and Reports	Y	
BAAQMD Condition #17309			
Part 1	Operating Time Restrictions (Cumulative Increase)	Y	

IV. Source-Specific Applicable Requirements

Table IV – A
Source-Specific Applicable Requirements
S-1 KELLER CANYON LANDFILL – WASTE DECOMPOSITION PROCESS;
ABATED BY A-1 LANDFILL GAS FLARE, AND A-2 LANDFILL GAS FLARE;
S-4 KELLER CANYON LANDFILL – WASTE AND COVER MATERIAL DUMPING; AND
S-5 KELLER CANYON LANDFILL – EXCAVATING, BULLDOZING, AND COMPACTING
ACTIVITIES

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
Part 2	Waste Acceptance Rate Limits (Cumulative Increase and Regulation 2-1-301)	Y	
Part 3	Daily Cover Requirements and Limitations (Regulation 1-301 and Cumulative Increase)	Y	
Part 4	Road Surfacing Requirements for Parking and Maintenance Areas (Cumulative Increase)	Y	
Part 5	Road Surfacing Requirements for On-Site Road Ways (Cumulative Increase)	Y	
Part 6	Speed Limits for Unpaved Roads (Cumulative Increase)	Y	
Part 7	Road Surfacing Requirements for Unpaved Roads (Cumulative Increase)	Y	
Part 8	Minimum Water and Dust Suppressant Application Rates for Unpaved Roads (Cumulative Increase)	Y	
Part 9	Water Truck Requirements (Cumulative Increase)	Y	
Part 10	Watering Requirements for Paved and Aggregate Based Road Ways (Cumulative Increase)	Y	
Part 11	Traffic Volume Limitations (Cumulative Increase)	Y	
Part 12	Trip Length Limitations for Heavy Duty Vehicles (Cumulative Increase)	Y	
Part 13	Watering Requirements for Active Face, Cover Soil Areas, and Off-Road Soil Areas (Cumulative Increase)	Y	
Part 14	Vegetation Requirements for Inactive Cover Soil Stockpiles (CEQA, Dust Mitigation Measures)	N	
Part 15	Vegetation Requirements for Completed Landfill Phases (CEQA, Dust Mitigation Measures)	N	
Part 16	Record Keeping Requirements (Cumulative Increase and Regulation 2-6-501)	Y	
Part 17	Reporting Periods and Report Submittal Due Dates for the Regulation 8, Rule 34 and NESHAP Reports (Regulation 8-34-411 and 40 CFR 63.1980(a))	Y	
Part 18	Landfill Gas Collection System Design and Alteration Requirements (Regulations 2-1-301, 8-34-301.1, 8-34-303, 8-34-304, and 40 CFR 60.755(a) and 60.759)	Y	

IV. Source-Specific Applicable Requirements

Table IV – A
Source-Specific Applicable Requirements

S-1 KELLER CANYON LANDFILL – WASTE DECOMPOSITION PROCESS; ABATED BY A-1 LANDFILL GAS FLARE, AND A-2 LANDFILL GAS FLARE; S-4 KELLER CANYON LANDFILL – WASTE AND COVER MATERIAL DUMPING; AND S-5 KELLER CANYON LANDFILL – EXCAVATING, BULLDOZING, AND COMPACTING ACTIVITIES

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
Part 19	Operating Requirements for Landfill Gas Collection System and Collection System Components (Regulations 8-34-301, 8-34-305, and 8-34-404, and 40 CFR 60.753(b and c) and 60.755(e))	Y	
Part 20	Control Requirements for Collected Landfill Gas (Regulations 8-34-301 and 8-34-303 and 40 CFR 60.752(b)(2)(ii-iii), 60.753(d-f) and 60.755(e))	Y	
Part 21	Continuous Operation Requirement for Flares (Regulation 8-34-301 and 40 CFR 60.752(b)(2)(iii), 60.753(e), and 60.755(e))	Y	
Part 22	Temperature Monitoring and Recording Requirements for Flares (Regulations 2-6-501 and 8-34-501 and 40 CFR 60.756(b))	Y	
Part 23	Minimum Temperature Requirement for Flares (RACT, Regulations 2-5-301 and 8-34-301, and 40 CFR 60.758(c)(1)(i))	Y	
Part 24	Nitrogen Oxide Emission Limit for Flares (RACT)	Y	
Part 25	Carbon Monoxide Emission Limit for Flares (RACT)	Y	
Part 26	[deleted]		
Part 27	Gas Flow Meter Requirement (Regulation 8-34-508 and 40 CFR 60.756(b))	Y	
Part 28	Alarm and Automated Control Requirements for Flares (Regulation 8-34-301)	Y	
Part 29	[deleted]		
Part 30	Annual Source Testing Requirement (RACT, Regulation 8-34-301.3, and 40 CFR 60.752(b)(2)(iii))	Y	
Part 31	Annual Landfill Gas Characterization Test (Air Toxics Hot Spots Act, Regulations 2-5-501, 8-34-301 and 9-1-302, and 40 CFR 60.754(d))	Y	
Part 32	Limits on Toxic Air Contaminants in Landfill Gas (Air Toxics Hot Spots Act and Regulation 2-5-302)	N	
Part 33	Precursor Organic Compound Emission Limit and Calculation Procedures (Offsets)	Y	
Part 34	Landfill Gas Sulfur Content Limit and Testing Procedures (Cumulative Increase and Regulations 9-1-302 and 2-6-503)	Y	
Part 35	Heat Input Limits for Flares (Offsets, Cumulative Increases, and Regulation 2-1-301)	Y	
Part 36	Contaminated Soil Throughput Limit and Records (Regulation 8-2-301)	Y	

IV. Source-Specific Applicable Requirements

Table IV – A
Source-Specific Applicable Requirements
S-1 KELLER CANYON LANDFILL; – WASTE DECOMPOSITION PROCESS;
ABATED BY A-1 LANDFILL GAS FLARE, AND A-2 LANDFILL GAS FLARE;
S-4 KELLER CANYON LANDFILL – WASTE AND COVER MATERIAL DUMPING; AND
S-5 KELLER CANYON LANDFILL – EXCAVATING, BULLDOZING, AND COMPACTING
ACTIVITIES

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
Part 37	Handling Procedures for Soil Containing Volatile Organic Compounds (Regulations 2-1-403, 8-40-301, 8-40-304, and 8-40-305)	Y	

IV. Source-Specific Applicable Requirements

Table IV – B
Source-Specific Applicable Requirements
S-3 YARD AND GREEN WASTE STOCKPILES

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
BAAQMD Regulation 6, Rule 1	Particulate Matter – General Requirements (12/5/07)		
6-1-301	Ringelmann No. 1 Limitation	N	
6-1-305	Visible Particles	N	
6-1-401	Appearance of Emissions	N	
SIP Regulation 6	Particulate Matter and Visible Emissions (9/4/98)		
6-301	Ringelmann No. 1 Limitation	Y	
6-305	Visible Particles	Y	
6-401	Appearance of Emissions	Y	
BAAQMD Condition #16462			
Part 1	Limit on Yard and Green Waste Received (Cumulative Increase)	Y	
Part 2	Watering Requirements (Regulations 6-1-301 , 6-1-305, and 2-6-503)	Y	
Part 3	Maximum Storage Time for Incoming Waste Prior to Processing (Regulation 1-301)	N	
Part 4	Maximum Storage Time for “Odorous” Stockpile (Regulation 1-301)	N	
Part 5	Public Nuisance Control Measures (Regulation 1-301)	N	
Part 6	Record Keeping Requirements (Cumulative Increase and Regulations 1-301, 2-6-501, 6-1-301 and 6-1-305)	Y	

V. SCHEDULE OF COMPLIANCE

The permit holder shall comply with all applicable requirements cited in this permit. The permit holder shall also comply with applicable requirements that become effective during the term of this permit on a timely basis.

VI. PERMIT CONDITIONS

Any condition that is preceded by an asterisk is not federally enforceable.

Condition # 16462

For S-3 YARD AND GREEN WASTE STOCKPILES:

1. The total amount of yard and green waste received at S-3 shall not exceed 1000 tons during any day nor 70,200 tons during any consecutive 12-month period. (Basis: Cumulative Increase)
2. The yard and green waste stockpiles shall be watered down as necessary to prevent visible dust emissions during loading or unloading. Dry, dusty material shall be watered down before unloading from truck beds as necessary to prevent visible emissions. To ensure compliance with this part, the Permit Holder shall visually observe all unloading, stockpiling, and loading operations and shall immediately initiate corrective actions if any visible dust emissions are detected. (Basis: Regulations 6-1-301, 6-1-305, and 2-6-503)
- *3. Yard and green waste shall be removed from the stockpiles within 4 days of the time it is received to prevent decomposition and odors. If any stockpiles are deemed to be odorous by a District inspector, the allowable stockpile storage time shall be reduced from 4 days to 72 hours. (Basis: Regulation 1-301)
- *4. Any stockpile that is deemed to be odorous by a District inspector shall be removed within 24 hours. (Basis: Regulation 1-301)
- *5. If the plant receives two or more Violation Notices from the District for "Public Nuisance" in any consecutive 12 month period, the owner/operator of this facility shall submit to the District, within 30 days, an application to modify the Permit to Operate to include the following control measures, as applicable, or any other measures that the District deems necessary and appropriate.
 - a. Require the application of odor inhibitor solutions,
 - b. Reduce the allowable stockpile time, or
 - c. Discontinue use of green waste stockpiles during the ozone season or other appropriate time period.(Basis: Regulation 1-301)

VI. Permit Conditions

Condition # 16462

For S-3 YARD AND GREEN WASTE STOCKPILES:

6. In order to demonstrate compliance with Parts 1, 2 and 3, the owner/operator shall maintain the following records:
 - a. Record the date, time, and amount of yard and green waste received at a stockpile.
 - b. Summarize the amount of yard and green waste received on a monthly basis.
 - c. Record the date, time, and amount of yard and green waste removed from the stockpile.
 - d. Record the date and time that water was applied to the stockpiles or associated loading or unloading operations.

All records shall be kept on site for a minimum of 5 years from the date of entry and shall be made available to District staff upon request. (Basis: Cumulative Increase and Regulations 2-6-501, 6-1-301, and 6-1-305)

VI. Permit Conditions

Condition # 17309

For S-1 KELLER CANYON LANDFILL – WASTE DECOMPOSITION PROCESS, ABATED BY:
A-1 LANDFILL GAS FLARE; AND A-2 LANDFILL GAS FLARE
S-4 KELLER CANYON LANDFILL – WASTE AND COVER MATERIAL DUMPING; AND
S-5 KELLER CANYON LANDFILL – EXCAVATING, BULLDOZING, AND COMPACTING
ACTIVITIES:

1. All landfill operations, including the acceptance and placement of waste and earthmoving and construction activities, shall be restricted to six days per week, Monday through Saturday. No operation shall take place on Sunday. (Basis: Cumulative Increase)
2. The Permit Holder shall apply for and receive written authorization from the District (in the form of an MFR Permit Revision and either a District Authority to Construct or Change of Permit Conditions) prior to exceeding any of the waste acceptance or waste disposal limits listed in subparts a-c below, unless the subpart below specifically states otherwise. Any changes in waste acceptance rates, types of waste accepted, or other practices that will result in emissions increases above the maximum permitted emission rates at the Keller Canyon Landfill (S-1) or the Landfill Gas Flares (A-1 and A-2) shall be considered a modification of S-1, A-1, or A-2 as defined in Regulation 2-1-234. (Basis: Cumulative Increase and Regulation 2-1-301)
 - a. Total waste accepted and placed at the landfill shall not exceed 3,500 tons in any single day (except during temporary emergency situations approved by the Local Enforcement Agency).
 - b. The total cumulative amount of all wastes placed in the landfill shall not exceed 38.4 million tons. However, an exceedance of this amount is not a violation of the permit and does not trigger the requirement to obtain an NSR permit, if the Permit Holder provides documentation to the District, within 30 days of the date of discovery of the exceedance, that demonstrates to the satisfaction of the APCO that the higher cumulative tonnage in place will not result in an increase of the Part 33 emission limit.
 - c. The maximum design capacity of the landfill (total volume of all wastes and cover materials placed in the landfill, excluding final cover) shall not exceed 75 million cubic yards.
3. All waste shall be covered on a daily basis with suitable cover material meeting the requirements of the California Integrated Waste Management Board (CIWMB). This cover frequency shall be increased as necessary for the control of odors and litter. Approved daily cover materials for this site include:
 - a. Clean soil compacted to a depth of least 6 inches,
 - b. Green waste compacted to a depth of at least 6 inches, but not exceeding an average depth of 12 inches, and

VI. Permit Conditions

Condition # 17309

For S-1 KELLER CANYON LANDFILL – WASTE DECOMPOSITION PROCESS, ABATED BY:
A-1 LANDFILL GAS FLARE; AND A-2 LANDFILL GAS FLARE
S-4 KELLER CANYON LANDFILL – WASTE AND COVER MATERIAL DUMPING; AND
S-5 KELLER CANYON LANDFILL – EXCAVATING, BULLDOZING, AND COMPACTING
ACTIVITIES:

- c. Geosynthetic blankets, provided that the working face is covered with clean soil at least once a week.
- d. Upon receiving written approval from the District (in the form of a letter or email concurring that no permit revisions are required), the owner/operator of S-1 may use other Alternative Daily Cover (ADC) materials that have been approved by CIWMB, provided that the use of these ADC materials do not result in odors, emission increases of any pollutant, the emission of any new pollutants, or contribute to a public nuisance. The owner/operator of S-1 shall apply for and receive an Authority to Construct before using any ADC materials that may result in odors, emission increases, the emission of any new pollutants, or that could contribute to a public nuisance.

(Basis: Regulation 1-301 and Cumulative Increase)

4. All on-site parking and maintenance areas for vehicles and mobile equipment shall either be paved, or provided with a gravel surface, except parking areas for landfill operation employees located directly adjacent to the working face. (Basis: Cumulative Increase)
5. All on-site roadways shall be paved, with the following exceptions:
 - a. A segment not exceeding 3,000' in length leading from the cover stockpiles to the midpoint of the working face.
 - b. A segment not exceeding 400' in length leading from the end of the main access haul road to the midpoint of the working face.
 - c. A segment not exceeding 750' in length leading from the end of the paved entrance roadway to the beginning of the unpaved 400' segment (exception b. above). This segment shall consist of a minimum of 12 inches of compacted gravel or crushed asphalt.
 - d. A segment not exceeding 1400' in length consisting of a secondary fire-access road southerly from the sedimentation basin perimeter roadway, starting from the graveled roadway surface to its southernmost point. Use of the roadway for maintenance and site patrol purposes shall not exceed an average of two vehicle trips per day.

(Basis: Cumulative Increase)

VI. Permit Conditions

Condition # 17309

For S-1 KELLER CANYON LANDFILL – WASTE DECOMPOSITION PROCESS, ABATED BY:
-A-1 LANDFILL GAS FLARE; AND A-2 LANDFILL GAS FLARE
S-4 KELLER CANYON LANDFILL – WASTE AND COVER MATERIAL DUMPING; AND
S-5 KELLER CANYON LANDFILL – EXCAVATING, BULLDOZING, AND COMPACTING
ACTIVITIES:

6. Speed of vehicles on unpaved roads shall not exceed 10 miles per hour. This speed limit shall be posted and enforced on unpaved roads at all times. Speed of vehicles on the fire access road shall not exceed 25 miles per hour. (Basis: Cumulative Increase)
7. All unpaved roads shall be provided with a gravel surface, excluding the fire access road, the 400 foot section of roadway from the end of the main access haul road to the working face, and the 3,000 foot scraper haul road segment from the working face to the soil stockpile area. (Basis: Cumulative Increase)
8. Operator shall control dust emissions from all unpaved roads, excluding the fire access road, by applying water as necessary and chemical dust suppressants at the following frequency and intensity:
 - a. Except as provided below, all applications of dust suppressant shall consist of 0.5 gallons per square yard of 10% MgCl₂ applied along the entire length of all unpaved roads.
 - b. Beginning May 1st and ending November 1st, dust suppressants shall be applied every 30 days.
 - c. From November 1 through May 1, dust suppressants shall be applied following any 30 consecutive dry days. For the purposes of this permit, a dry operating day shall be defined as any 24-hour period, midnight to midnight, with less than 0.09 inches of rain.
 - d. Upon written request of the operator, the above dust suppression program may be modified to allow for the use of dust suppressants other than MgCl₂ provided an 85% control efficiency for TSP can be demonstrated to the satisfaction of the APCO. All such changes must be approved by the APCO in writing (in the form of a letter or email concurring that no permit revisions are required) prior to implementation.
(Basis: Cumulative Increase)
9. Operator shall maintain a fleet of at least two water trucks at all times to wash down paved roadway surfaces and wet unpaved roads (excluding the fire access road) and work areas. (Basis: Cumulative Increase)

VI. Permit Conditions

Condition # 17309

For S-1 KELLER CANYON LANDFILL – WASTE DECOMPOSITION PROCESS, ABATED BY:
A-1 LANDFILL GAS FLARE; AND A-2 LANDFILL GAS FLARE
S-4 KELLER CANYON LANDFILL – WASTE AND COVER MATERIAL DUMPING; AND
S-5 KELLER CANYON LANDFILL – EXCAVATING, BULLDOZING, AND COMPACTING
ACTIVITIES:

10. On all dry operating days, all paved and AB roads shall be completely washed down at regular intervals throughout operating hours. Rinsing frequency shall average once every fifth heavy-duty vehicle (gross weight > 5 tons) pass, excluding water trucks. Averaging shall be done on a daily basis. (Basis: Cumulative Increase)
11. On-site traffic volume of the following heavy duty vehicles shall not exceed the following number of round trips in any single day, calculated on an annual basis, except as otherwise provided in this permit:
 - a. 175 transfer truck trips
 - b. 4 leachate transfer truck trips
 - c. 45 scraper trips
 - d. For all heavy-duty vehicles, such other on-site travel as may be approved in writing by the APCO.'Annual Basis' shall be calculated by dividing the number of total truck trips by the number of operating days in any 365-day period. (Basis: Cumulative Increase)
12. For the following heavy-duty vehicles, one-way on-site trip length shall not exceed the following distances at any time during the life of the landfill except as otherwise provided by this permit:
 - a. Transfer trucks: 7,800 feet (7,400 feet paved and AB)
 - b. Leachate trucks: 3,600 feet (all paved)
 - c. Scrapers: 3,000 feet (all unpaved)A map shall be kept on site at all times identifying the paved and AB roads, clearly stating their length and the type of vehicles that use them. (Basis: Cumulative Increase)
13. On all dry operating days, all off-road soil areas, including the active face area and the active portion of the cover stockpiles, trafficked or otherwise disturbed by vehicles, equipment or operations shall be wetted down with 0.5 gallons of water per square yard or 2,420 gallons of water per acre, at least twice per day. (Basis: Cumulative Increase)
- *14. All inactive portions of the cover stockpiles shall either be covered by a latex sealer or revegetated. (Basis: CEQA, Dust Mitigation Measures)

VI. Permit Conditions

Condition # 17309

For S-1 KELLER CANYON LANDFILL – WASTE DECOMPOSITION PROCESS, ABATED BY:
A-1 LANDFILL GAS FLARE; AND A-2 LANDFILL GAS FLARE
S-4 KELLER CANYON LANDFILL – WASTE AND COVER MATERIAL DUMPING; AND
S-5 KELLER CANYON LANDFILL – EXCAVATING, BULLDOZING, AND COMPACTING
ACTIVITIES:

- *15. All completed landfill phases shall be revegetated as soon as possible. (Basis: CEQA, Dust Mitigation Measures)
16. In order to demonstrate compliance with the above parts, the owner/operator of S-1 shall maintain the following records:
- a. Daily records of the quantity of waste accepted and placed in the landfill.
 - b. Summarize the daily waste acceptance records for each calendar month.
 - c. Summarize monthly waste acceptance records for each preceding 12-month period.
 - d. For each area or cell that is not controlled by a landfill gas collection system, maintain a record of the date that waste was initially placed in the area or cell.
 - e. Record the cumulative amount of waste placed in each uncontrolled area or cell on a monthly basis.
 - f. If the Permit Holder plans to exclude an uncontrolled area or cell from the collection system requirement, the Permit Holder shall also record the types and amounts of all non-decomposable waste placed in the area and the percentage (if any) of decomposable waste placed in the area.
 - g. Record the initial operation date for each new landfill gas well and collector.
 - h. Maintain an accurate map of the landfill, which indicates the locations of all refuse boundaries and the locations of all wells and collectors (using unique identifiers). Any areas containing only non-decomposable waste shall be clearly identified. This map shall be updated at least every six months to indicate changes in refuse boundaries and to include any newly installed wells and collectors.
 - i. Daily records of the number of site trips made by heavy-duty vehicles by type of vehicle (transfer trucks, leachate trucks, scrapers, etc.)
 - j. Daily records of the number of water truck rinses on paved and unpaved roads. Alternatively, the Permit Holder may maintain daily checklists instead of the records required by this subpart, provided the Permit Holder has received written approval from the District for the site's dust control plan, checklists, and implementation procedures.

VI. Permit Conditions

Condition # 17309

For S-1 KELLER CANYON LANDFILL – WASTE DECOMPOSITION PROCESS, ABATED BY: -A-1 LANDFILL GAS FLARE, AND A-2 LANDFILL GAS FLARE S-4 KELLER CANYON LANDFILL – WASTE AND COVER MATERIAL DUMPING; AND S-5 KELLER CANYON LANDFILL – EXCAVATING, BULLDOZING, AND COMPACTING ACTIVITIES:

- k. Records of all chemical dust suppressant applications including the date of treatment, length of roads treated, and amount of dust suppressant applied. Alternatively, the Permit Holder may maintain daily checklists instead of the records required by this subpart, provided the Permit Holder has received written approval from the District for the site's dust control plan, checklists, and implementation procedures.
- l. Daily records of all water applications to the working face, cover soil stockpiles, or other areas including the number of times that water was applied and the amount of water applied. Alternatively, the Permit Holder may maintain daily checklists instead of the records required by this subpart, provided the Permit Holder has received written approval from the District for the site's dust control plan, checklists, and implementation procedures.

All records required to be kept under the provisions of this permit must be maintained on site for a period of five years from the date of entry, and be available for inspection by District staff upon request. (Basis: Cumulative Increase and Regulation 2-6-501)

17. The annual report required by BAAQMD Regulation 8-34-411 shall be submitted in two semi-annual increments. The reporting periods and report submittal due dates for the semi-annual increments of the Regulation 8-34-411 report and the MSW Landfill NESHAP report shall be synchronized with the reporting periods and report submittal due dates for the semi-annual MFR Permit monitoring reports that are required by Section I.F of the MFR Permit for this site. A single report may be submitted to satisfy the requirements of Section I.F, Regulation 8-34-411, and 40 CFR Part 63.1980(a), provided that all items required by each applicable reporting requirement are included in the single report. (Basis: Regulation 8-34-411 and 40 CFR Part 63.1980(a))
18. Landfill Gas Collection System Design and Alteration Requirements:
The Permit Holder shall have a properly operated and properly maintained active landfill gas collection system at the S-1 Keller Canyon Landfill that complies with the design and alteration requirements listed below. (Basis: Regulations 2-1-301, 8-34-301.1, 8-34-303, 8-34-304, 40 CFR 60.755(a) and 60.759)

VI. Permit Conditions

Condition # 17309

For S-1 KELLER CANYON LANDFILL – WASTE DECOMPOSITION PROCESS, ABATED BY:
A-1 LANDFILL GAS FLARE; AND A-2 LANDFILL GAS FLARE
S-4 KELLER CANYON LANDFILL – WASTE AND COVER MATERIAL DUMPING; AND
S-5 KELLER CANYON LANDFILL – EXCAVATING, BULLDOZING, AND COMPACTING
ACTIVITIES:

- a. The Permit Holder has been issued a Permit to Operate for the landfill gas collection system components listed below. Well and collector locations, depths, and lengths of associated piping are as described in detail in Permit Application #23460. The authorized number of landfill gas collection system components is the baseline count listed below plus any components installed and minus any components permanently decommissioned pursuant to Part 18b, as evidenced by start-up and decommissioning notification letters submitted to the District.
- i. The following components constitute the main landfill gas collection system.

Well Station	Vertical Wells
A	12
B	8
D	6
E	9
K	11
L	3
M	7
O	0
Q	10
R	9
S	3
A-S	36
EW	59

- ii. The following components have been installed to prevent or control landfill gas migration and are not part of the main landfill gas collection and control system.

ID	Horizontal Collectors
HC-2	1
HC 1	1
HC-3	1
LCRS-1	1

VI. Permit Conditions

Condition # 17309

For S-1 KELLER CANYON LANDFILL – WASTE DECOMPOSITION PROCESS, ABATED BY:
A-1 LANDFILL GAS FLARE; AND A-2 LANDFILL GAS FLARE
S-4 KELLER CANYON LANDFILL – WASTE AND COVER MATERIAL DUMPING; AND
S-5 KELLER CANYON LANDFILL – EXCAVATING, BULLDOZING, AND COMPACTING
ACTIVITIES:

- b. The Permit Holder has been authorized to conduct the landfill gas collection system alterations listed below pursuant to Application #23460. All collection system alterations shall comply with subparts i-vii below. Components installed or decommissioned pursuant to Part 18b shall be added to or removed from Part 18a(i) in accordance with the procedures identified in Regulations 2-6-414 or 2-6-415.
- i. The authorized collection system alterations are:
- Install up to ~~400-38~~ vertical gas collection wells.
 - Permanently decommission up to ~~60-15~~ vertical wells.
 - Install up to 2 wellhead stations that will provide flow rate control and monitoring points for recently installed wells.
- ii. The Permit Holder shall apply for and receive a Change of Conditions from the District before implementing any changes to the landfill gas collection system described in Part 18a, other than those authorized by Part 18b. Installing, decommissioning, and relocating vertical wells and horizontal collectors are alterations that are subject to this requirement, unless this change constitutes a replacement as defined in subpart iii below.
- iii. Replacement of landfill gas collection system components with identical or functionally equivalent components will not be deemed an alteration and will not be subject to the Authority to Construct requirement under the following circumstances. If a well or collector will be shut down and replaced by a new well or collector in essentially the same location as the old component and this decommission/installation will be accomplished in accordance with Regulations 8-34-117 and 8-34-118, then this activity shall be considered a component replacement that is not subject to an Authority to Construct or Change of Conditions requirement. For each individual well or collector replacement, this subpart authorizes a maximum vacuum disconnection time of five consecutive days for compliance with Regulation 8-34-117.5. The disconnected component and the new component shall not be counted toward the Part 18b(i) component alteration limits; the numbers of replacement wells and replacement collectors are not limited.

VI. Permit Conditions

Condition # 17309

For S-1 KELLER CANYON LANDFILL – WASTE DECOMPOSITION PROCESS, ABATED BY:
-A-1 LANDFILL GAS FLARE; AND A-2 LANDFILL GAS FLARE
S-4 KELLER CANYON LANDFILL – WASTE AND COVER MATERIAL DUMPING; AND
S-5 KELLER CANYON LANDFILL – EXCAVATING, BULLDOZING, AND COMPACTING
ACTIVITIES:

Alterations, repairs, or replacements of non-perforated piping sections (such as risers, laterals, or header pipes), piping connectors, or valves are not subject to the Authority to Construct requirement.

- iv. At least three days prior to initiating operation of a well or collector installed pursuant to Part 18b, the Permit Holder shall submit a start-up notice to the District that contains the component ID number for each new well or collector and the anticipated initial start-up date for each new component.
- v. For each well or collector that is permanently decommissioned after April 16, 2007, the Permit Holder shall submit a decommissioning notice to the District within no later than three working days after the component was disconnected from vacuum system. This decommissioning notice shall contain the component ID for each well or collector that was decommissioned, the date and time that each component was disconnected from the vacuum system, and the reason the component was decommissioned.
- vi. Within six months of installing a new component or permanently decommissioning an existing component, the Permit Holder shall prepare an updated map of the landfill gas collection system that identifies the ID numbers and locations of all operable wells and collectors. On this map or in accompanying documentation, the Permit Holder shall summarize all component changes that were made since the last map was prepared. The previous collection system map, the updated collection system map, and the component change summary shall be provided to District staff upon request.
- vii. If the Permit Holder has a net reduction (number of decommissioned components minus the number of installed components) of more than five components within a 120-day period, the Permit Holder shall submit a more comprehensive decommissioning notice to the District.

VI. Permit Conditions

Condition # 17309

For S-1 KELLER CANYON LANDFILL – WASTE DECOMPOSITION PROCESS, ABATED BY:
-A-1 LANDFILL GAS FLARE; AND A-2 LANDFILL GAS FLARE
S-4 KELLER CANYON LANDFILL – WASTE AND COVER MATERIAL DUMPING; AND
S-5 KELLER CANYON LANDFILL – EXCAVATING, BULLDOZING, AND COMPACTING
ACTIVITIES:

In addition to the information required by subpart v, this comprehensive decommissioning notice shall include the maps and documentation required by subpart vi, shall identify all component changes that have occurred but that are not included on the most recently updated map, shall identify any components that are temporarily disconnected from vacuum pursuant to Part 19c, shall provide estimated vacuum reconnection dates for these components, shall include a list of all well installations that are expected to occur within the next 120 days, and shall discuss the reasons why this reduction in gas collection components is not expected to result in surface emission leaks. Upon request, the Permit Holder shall provide wellhead monitoring data, surface leak monitoring data, records of repair attempts made to date, and other information to support the need for a net component reduction of more than five wells. The District may require additional surface monitoring to verify that this net component reduction is not causing landfill surface leaks. The District will notify the Permit Holder in writing of any additional surface monitoring that is required pursuant to this subpart.

19. Operating Requirements for Landfill Gas Collection System and Collection System Components:
 - a. The landfill gas collection system described in Part 18a(i) shall be operated continuously. Each component that is subject to this continuous operation requirement shall not be shut off, disconnected, or removed from operation without prior written authorization from the District, unless the Permit Holder complies with Part 19c or with all applicable requirements of Regulation 8, Rule 34, Sections 113, 116, 117, and 118. (Basis: Regulation 8-34-301, 40 CFR 60.753(b and c) and 60.755(e))

VI. Permit Conditions

Condition # 17309

For S-1 KELLER CANYON LANDFILL – WASTE DECOMPOSITION PROCESS, ABATED BY:
-A-1 LANDFILL GAS FLARE; AND A-2 LANDFILL GAS FLARE
S-4 KELLER CANYON LANDFILL – WASTE AND COVER MATERIAL DUMPING; AND
S-5 KELLER CANYON LANDFILL – EXCAVATING, BULLDOZING, AND COMPACTING
ACTIVITIES:

- i. The components identified in Part 18a(ii) are not required to operate continuously and may be connected to or disconnected from the main vacuum system at the operator's discretion, provided the owner/operator either connects each component to the vacuum system at least once per quarter or inspects each component to determine if vacuum connection is necessary at least once each quarter. The operator shall record the date, time, and reason for each vacuum connection/disconnection event and for each inspection.
- b. Each landfill gas collection system component listed in Part 18a(i) shall be operated in compliance with the wellhead limits of Regulation 8-34-305, unless an alternative wellhead limit has been approved for that component, (as identified in subpart i below), and the Permit Holder complies with all of the additional requirements for that component, as identified in subparts ii-vii below. (Basis: Regulation 8-34-305)
 - i. The nitrogen and oxygen concentration limits in Regulation 8-34-305.3 and 8-34-305.4 shall not apply to the landfill gas collection wells listed below, provided that the oxygen concentration in each of the following wells does not exceed 15% by volume.
E027R, ~~K035R~~, ~~M005R~~, ~~R001(P)~~, ~~R003(P)~~, R004(P), ~~R005(P)~~, R006(P), R007(P)
 - ii. The Permit Holder shall demonstrate compliance with the alternative wellhead oxygen limit in subpart i by monitoring each wellhead for oxygen on a monthly basis, in accordance with the provisions of Regulations 8-34-505 and 8-34-604.
 - iii. All test dates, wellhead oxygen concentration data, any deviations from the subpart i limit, repair actions, repair dates, re-monitoring dates and results, and compliance restoration dates shall be recorded in a District approved log and made available to District staff upon request in accordance with Regulations 8-34-34-501.4, 8-34-501.9, and 8-34-414.

VI. Permit Conditions

Condition # 17309

For S-1 KELLER CANYON LANDFILL – WASTE DECOMPOSITION PROCESS, ABATED BY: -A-1 LANDFILL GAS FLARE, AND A-2 LANDFILL GAS FLARE
S-4 KELLER CANYON LANDFILL – WASTE AND COVER MATERIAL DUMPING; AND
S-5 KELLER CANYON LANDFILL – EXCAVATING, BULLDOZING, AND COMPACTING
ACTIVITIES:

- iv. To demonstrate that the alternative wellhead oxygen limit in subpart i will not cause surface emission leaks, the Permit Holder shall conduct additional surface emission monitoring within a 15 meter vicinity of each component listed in subpart i at the specific locations discussed below. For each component in subpart i, the Permit Holder shall maintain a map showing the location of the buried collection component and identifying the approximate radius of influence for the component. For each component in subpart i, the Permit Holder shall monitor for landfill surface emissions – in accordance with Regulations 8-34-506 and 8-34-607 – at three representative points on the landfill surface that are within the radius of influence of the component and that are not more than 15 meters from the surface location of the component. This additional surface emission monitoring shall be conducted on a monthly basis for a period of at least six consecutive months.
- v. If no excesses of the Regulation 8-34-303 surface emission limit are detected within a 15 meter vicinity of a component for six consecutive months, the Permit Holder may discontinue the additional monthly surface emission monitoring in the vicinity of that component and shall continue with the routine quarterly surface emission monitoring requirements for that component.
- vi. If one or more excesses of the Regulation 8-34-303 surface emission limit are detected within a 15 meter vicinity of a component during a six consecutive month period, the Permit Holder shall follow all applicable requirements for recording and reporting the excess and shall follow the Regulation 8-34-415 repair schedule for landfill surface leak excesses. The additional monthly surface emission monitoring in the vicinity of that component shall continue until either the no surface excess requirements of subpart v have been achieved or the repair and compliance restoration requirements of subpart vii have been satisfied.

VI. Permit Conditions

Condition # 17309

For S-1 KELLER CANYON LANDFILL – WASTE DECOMPOSITION PROCESS, ABATED BY:

-A-1 LANDFILL GAS FLARE; AND A-2 LANDFILL GAS FLARE

S-4 KELLER CANYON LANDFILL – WASTE AND COVER MATERIAL DUMPING; AND

S-5 KELLER CANYON LANDFILL – EXCAVATING, BULLDOZING, AND COMPACTING
ACTIVITIES:

- vii. If excesses of the Regulation 8-34-303 surface emission limit are detected within a 15 meter vicinity of a component for three or more monitoring events during a six consecutive month period, the subpart i alternative wellhead oxygen limit shall be revoked for that component. The Permit Holder shall conduct all necessary repairs to the landfill gas collection well, to any piping associated with the well or the remote wellhead monitoring system, to valves, flanges, or other connectors, and to any test ports or other openings that are necessary to eliminate air intrusion into the well or the monitoring point, to prevent impairment of vacuum application or vacuum adjustment at the collection well, and to restore the collection well and associated monitoring point to proper function. The Permit Holder shall complete all of the above repairs and any necessary landfill surface repairs and shall restore compliance with the Regulation 8-34-303 surface emission limit (at each location where an excess of the surface limit was measured) and the Regulation 8-34-305.4 wellhead oxygen concentration limit by the earlier of the following dates: (a) within 120 days of the date that the first excess was discovered if the three excess events are discovered within a single quarterly period pursuant to the re-monitoring requirements of 8-34-415 or (b) within 60 days of detection of the third excess.
- c. The Permit Holder may temporarily disconnect individual wells or collectors listed in Part 18a(i) from the vacuum system, provided that all requirements of this subpart are satisfied. (Basis: Regulation 8-34-404)
 - i. No more than five (5) landfill gas collection system components (wells or collectors) may be temporarily disconnected from the vacuum system at any one time pursuant to Part 19c.
 - ii. For each individual well or collector that is temporarily disconnected from the vacuum system pursuant to Part 19c, the total vacuum system disconnection time shall not exceed 120 days during any 12-month period.

VI. Permit Conditions

Condition # 17309

For S-1 KELLER CANYON LANDFILL – WASTE DECOMPOSITION PROCESS, ABATED BY:
-A-1 LANDFILL GAS FLARE; AND A-2 LANDFILL GAS FLARE
S-4 KELLER CANYON LANDFILL – WASTE AND COVER MATERIAL DUMPING; AND
S-5 KELLER CANYON LANDFILL – EXCAVATING, BULLDOZING, AND COMPACTING
ACTIVITIES:

- iii. Collection system components that are disconnected from the vacuum system are not subject to wellhead limits (Regulation 8-34-305 or Part 19b) or to monthly wellhead monitoring requirements (Regulation 8-34-505) during this vacuum disconnection time.
- iv. Wells or collectors that are temporarily disconnected from the vacuum system continue to be subject to the component leak limit (Regulation 8-34-301.2) and the quarterly leak testing requirement (Regulation 8-34-503) at all times. In addition, the Permit Holder shall conduct the following component leak monitoring at each component that has been disconnected from the vacuum system pursuant to Part 19c: test for component leaks using the procedures identified in Regulation 8-34-602 within 10 calendar days of disconnection from vacuum and again within 1 month of disconnection from vacuum. If a component leak is detected at the well, the Permit Holder shall take all steps necessary to reduce the leak below the applicable limit, including reconnecting the well to the vacuum system, if no other corrective action measures are successful within the time frames allowed by Rule 34.
- v. For each temporary component disconnection event, the Permit Holder shall record each affected well ID number, all well disconnection dates and times, all well reconnection dates and times, all related monitoring dates and monitoring results in a District approved log. This log shall also include an explanation of why the temporary vacuum disconnection was necessary and shall describe all adjustments or repairs that were made in order to allow this well to operate continuously, to reduce leaks, or to achieve compliance with an applicable limit. All records shall be retained for a minimum of five years and shall be made available to District staff upon request.

VI. Permit Conditions

Condition # 17309

For S-1 KELLER CANYON LANDFILL – WASTE DECOMPOSITION PROCESS, ABATED BY:
A-1 LANDFILL GAS FLARE; AND A-2 LANDFILL GAS FLARE
S-4 KELLER CANYON LANDFILL – WASTE AND COVER MATERIAL DUMPING; AND
S-5 KELLER CANYON LANDFILL – EXCAVATING, BULLDOZING, AND COMPACTING
ACTIVITIES:

20. All landfill gas collected by the gas collection system for S-1 shall be abated at all times by the on-site enclosed flares, A-1 or A-2 or shall be vented off-site to the Ameresco Keller Canyon LLC facility (Site # B7667) for gas processing and control. A sufficient amount of landfill gas shall be collected at all times to prevent violation of the applicable landfill surface leak limits. If only one off-site landfill gas fired engine is operating, at least one on-site flare (A-1 or A-2) must also be operating. If both off-site engines are operating, collected landfill gas may be vented to these off-site engines alone – without concurrent operation of either on-site flare – until January 1, 2013. Effective January 1, 2013 through December 31, 2020, collected gas shall be vented to either: (a) one on-site flare operating alone or (b) one on-site flare and two off-site engines operating concurrently. Effective January 1, 2021, collected landfill gas shall be vented to either: (a) two on-site flares operating concurrently or (b) one on-site flare and two off-site engines operating concurrently. Under no circumstances shall raw landfill gas be vented to the atmosphere. This limitation does not apply to unavoidable landfill gas emissions that occur during collection system installation, maintenance, or repair performed in compliance with Regulation 8, Rule 34 Sections 113, 116, 117, or 118 or to inadvertent component or surface leaks that do not exceed the limits specified in 8-34-301.2 or 8-34-303. (Basis: Regulations 8-34-301, 8-34-303, 40 CFR 60.752(b)(2)(ii-iii), 60.753(d-f), and 60.755(e))
21. Each flare shall be operated continuously during any time that landfill gas is being vented to the flare. (Basis: Regulation 8-34-301, 40 CFR 60.752(b)(2)(iii), 60.753(e), and 60.755(e))
22. A temperature monitor with readout display and continuous recorder shall be installed and maintained on each flare. One or more thermocouples shall be placed in the primary combustion zone of the flare and shall accurately indicate flue gas temperature at all times. Temperature charts shall be retained for five years and made readily available to District Staff upon request. (Basis: Regulations 8-34-501 and 2-6-501 and 40 CFR 60.756(b))

VI. Permit Conditions

Condition # 17309

For S-1 KELLER CANYON LANDFILL – WASTE DECOMPOSITION PROCESS, ABATED BY:
A-1 LANDFILL GAS FLARE; AND A-2 LANDFILL GAS FLARE
S-4 KELLER CANYON LANDFILL – WASTE AND COVER MATERIAL DUMPING; AND
S-5 KELLER CANYON LANDFILL – EXCAVATING, BULLDOZING, AND COMPACTING
ACTIVITIES:

23. The combustion zone temperature of the A-1 Flare shall be maintained at a minimum temperature of 1504 degrees F, averaged over any 3-hour period. The combustion zone temperature of the A-2 Flare shall be maintained at a minimum temperature of 1400 degrees F, averaged over any 3-hour period. If a source test demonstrates compliance with all applicable requirements at a different temperature, the APCO may revise these minimum temperature requirements in accordance with the procedures identified in Regulation 2-6-414 or 2-6-415 and the following criteria. The minimum combustion zone temperature for the flare shall be equal to the average combustion zone temperature determined during the most recent complying source test minus 50 degrees F, provided that the minimum combustion zone temperature is not less than 1400 degrees F. (Basis: Regulations 2-5-301 and 8-34-301, RACT, and 40 CFR 60.758(c)(1)(i))
24. NO_x emissions from either the A-1 Flare or the A-2 Flare shall not exceed 15 ppmv of NO_x, expressed as NO₂ at 15% oxygen on a dry basis. (Basis: RACT)
25. CO emissions from the A-1 Flare shall not exceed 114 ppmv of CO at 15% oxygen on a dry basis. CO emissions from the A-2 Flare shall not exceed 81 ppmv of CO at 15% oxygen on a dry basis. (Basis: RACT)
26. [deleted]
27. A flow meter to measure gas flow into each flare shall be installed prior to operation and maintained in good working condition. (Basis: Regulation 8-34-508 and 40 CFR 60.756(b))
28. Each flare shall be equipped with both local and remote alarms, automatic combustion air control, and automatic start/restart system. (Basis: Regulation 8-34-301)
29. [deleted]

VI. Permit Conditions

Condition # 17309

For S-1 KELLER CANYON LANDFILL – WASTE DECOMPOSITION PROCESS, ABATED BY:
-A-1 LANDFILL GAS FLARE; AND A-2 LANDFILL GAS FLARE
S-4 KELLER CANYON LANDFILL – WASTE AND COVER MATERIAL DUMPING; AND
S-5 KELLER CANYON LANDFILL – EXCAVATING, BULLDOZING, AND COMPACTING
ACTIVITIES:

30. In order to demonstrate compliance with Parts 24 and 25 above, Regulations 8-34-301.3 and 8-34-412, 40 CFR 60.8, and 40 CFR 60.752(b)(2)(iii)(B), the owner/operator shall conduct a source test at each flare once every year. The source tests shall be conducted no sooner than 9 months and no later than 12 months after the previous source test. The first source test for A-2 shall be conducted within 60 days of initial start-up of A-2. The Source Test Section of the District shall be contacted to obtain approval of the source test procedures at least 14 days in advance of each source test. The Source Test Section shall be notified of the scheduled test date at least 7 days in advance of each source test. The source test report shall be submitted to the Compliance and Enforcement Division and the Source Test Section within 60 days of the test date. Each annual source test shall determine the following:
- a. landfill gas flow rate to the flare (dry basis);
 - b. concentrations (dry basis) of carbon dioxide (CO₂), nitrogen (N₂), oxygen (O₂), methane (CH₄), and total non-methane organic compounds (NMOC) in the landfill gas;
 - c. stack gas flow rate from the flare (dry basis);
 - d. concentrations (dry basis) of NO_x, CO, NMOC, and O₂ in the flare stack gas;
 - e. NMOC destruction efficiency achieved by the flare;
 - f. NO_x and CO emission rates from the flare in units of pounds per MM BTU,
 - g. average combustion zone temperature in the flare during the test period.
- (Basis: Regulation 8-34-301.3, RACT, 40 CFR 60.752(b)(2)(iii))

VI. Permit Conditions

Condition # 17309

For S-1 KELLER CANYON LANDFILL – WASTE DECOMPOSITION PROCESS, ABATED BY:
A-1 LANDFILL GAS FLARE; AND A-2 LANDFILL GAS FLARE
S-4 KELLER CANYON LANDFILL – WASTE AND COVER MATERIAL DUMPING; AND
S-5 KELLER CANYON LANDFILL – EXCAVATING, BULLDOZING, AND COMPACTING
ACTIVITIES:

31. The Permit Holder shall conduct a characterization of the landfill gas concurrent with the annual source test required by Part 30 above. The landfill gas sample shall be drawn from the main landfill gas header. In addition to the compounds listed in Part 30b, the landfill gas shall be analyzed for the organic and sulfur compounds listed below. All concentrations shall be reported on a dry basis. The sulfur compound data collected pursuant to this part may be used to determine the total reduced sulfur compound concentration expressed as H₂S (TRS) and the ratio (R) of total reduced sulfur content versus hydrogen sulfide content, where $R = TRS/H_2S$. This ratio (R) may be used in Part 34 below (in place of the default value of $R=1.2$) to calculate TRS based on H₂S measured by the Draeger tube method. The test report shall be submitted to the Compliance and Enforcement Division and the Source Test Section within 60 days of the test date. (Basis: Air Toxics Hot Spots Act, Regulations 2-5-501, 8-34-301, and 9-1-302, and 40 CFR 60.754(d))

Organic Compounds

Acrylonitrile
Benzene
Carbon Tetrachloride
Chloroform
Ethylene Dibromide
Ethylene Dichloride
Methylene Chloride
Perchloroethylene
Trichloroethylene
Vinyl Chloride

Sulfur Compounds

Carbon Disulfide
Carbonyl Sulfide
Dimethyl Sulfide
Ethyl Mercaptan
Hydrogen Sulfide
Methyl Mercaptan

VI. Permit Conditions

Condition # 17309

For S-1 KELLER CANYON LANDFILL – WASTE DECOMPOSITION PROCESS, ABATED BY:
-A-1 LANDFILL GAS FLARE, AND A-2 LANDFILL GAS FLARE
S-4 KELLER CANYON LANDFILL – WASTE AND COVER MATERIAL DUMPING; AND
S-5 KELLER CANYON LANDFILL – EXCAVATING, BULLDOZING, AND COMPACTING
ACTIVITIES:

- *32. If concentrations of toxic air contaminants (TACs) are above the levels listed below, an additional risk screen run at actual concentrations will be required. Depending on the results of such screen, additional permit conditions may be required if health risks are deemed unacceptable. (Basis: Air Toxics Hot Spots Act and Regulation 2-5-302)

<u>Compound</u>	<u>Concentration (ppbv)</u>
Acrylonitrile	500
Benzene	20,000
Carbon Tetrachloride	100
Chloroform	100
Ethylene Dibromide	100
Ethylene Dichloride	400
Methylene Chloride	16,000
Perchloroethylene	3,300
Trichloroethylene	1,500
Vinyl Chloride	1,700

33. The fugitive emissions of Precursor Organic Compounds (POC) from the S-1 Landfill shall not exceed 40.059 tons per year (expressed as methane). Fugitive POC emissions from the landfill shall be determined using the procedures and assumptions described in Parts 33a-f below. POC emissions from the landfill shall be calculated at least once every five years or whenever the capacity of the landfill gas emissions control system, A-1 and A-2 Flares, is expanded, whichever is sooner. (Basis: Offsets)
- The current methane generation rate and uncontrolled POC emissions from the S-1 Landfill shall be calculated using the equations described in the most recent revision of AP-42 Chapter 2.4.
 - The methane generation rate shall be based on the total amount of waste accepted at the landfill to date. The Permit Holder may use either average annual or year-to-year waste acceptance rates.
 - The Permit Holder shall use the AP-42 recommended default values for the methane generation potential and methane generation rate constant. As of April 1, 2005, these default values were:
 $Lo = 100 \text{ m}^3 \text{ CH}_4/\text{Mg}$ and $k = 0.02 \text{ year}^{-1}$.

VI. Permit Conditions

Condition # 17309

For S-1 KELLER CANYON LANDFILL – WASTE DECOMPOSITION PROCESS, ABATED BY:

-A-1 LANDFILL GAS FLARE; AND A-2 LANDFILL GAS FLARE

S-4 KELLER CANYON LANDFILL – WASTE AND COVER MATERIAL DUMPING; AND

S-5 KELLER CANYON LANDFILL – EXCAVATING, BULLDOZING, AND COMPACTING
ACTIVITIES:

- d. When calculating uncontrolled POC emissions (UEPOC, pounds/year of POC), the Permit Holder shall use site specific NMOC, NPOC, and methane concentrations (after correcting for air infiltration) and the site specific landfill gas temperature. The site specific values shall be the average of at least three previous years of data collected pursuant to Part 31 above.
 - e. Total non-methane organic compounds (NMOC) measured in the landfill gas pursuant to Part 31 may be assumed to be 100% POC, or a site specific POC concentration (CPOC) can be calculated using data from Part 33d above, where $CPOC = NMOC - NPOC$ (all concentrations expressed as methane).
 - f. The fugitive POC emissions from the landfill (FEPOC, pounds/year of POC) shall be calculated using the equation below:
$$FEPOC = 0.25 * UEPOC$$
34. Total reduced sulfur (TRS) compounds in the collected landfill gas shall be monitored as a surrogate for monitoring sulfur dioxide in control systems exhaust. The concentration of total reduced sulfur compounds in the collected landfill gas shall not exceed 300 ppmv (dry). In order to demonstrate compliance with this part, the Permit Holder shall measure the hydrogen sulfide (H₂S) content in collected landfill gas on a quarterly basis using the Draeger tube method. The TRS content of the landfill gas shall be calculated according to the following equation: $TRS = R * H_2S$ measured by Draeger tube method, where R is either (a) the ratio of TRS/H₂S that is determined from the sulfur compound data collected pursuant to Part 31 or (b) a default value of 1.2. The annual laboratory analysis for reduced sulfur compounds, which is required by Part 31 above, may be substituted for one quarterly Draeger tube analysis per year. The landfill gas sample shall be taken from the main landfill gas header. The Permit Holder shall follow the manufacturer's recommended procedures for using the Draeger tube and interpreting the results. (Basis: Cumulative Increase and Regulations 9-1-302 and 2-6-503)

VI. Permit Conditions

Condition # 17309

For S-1 KELLER CANYON LANDFILL – WASTE DECOMPOSITION PROCESS, ABATED BY:

-A-1 LANDFILL GAS FLARE; AND A-2 LANDFILL GAS FLARE

S-4 KELLER CANYON LANDFILL – WASTE AND COVER MATERIAL DUMPING; AND

S-5 KELLER CANYON LANDFILL – EXCAVATING, BULLDOZING, AND COMPACTING
ACTIVITIES:

35. The heat input to the flares shall not exceed the following limits: (a) 1744.8 million BTU per day and 636,852 million BTU per year for A-1 and (b) 1824 million BTU per day and 665,760 million BTU per year for A-2. In order to demonstrate compliance with this part, the Permit Holder shall calculate and record on a monthly basis the maximum daily and total monthly heat input to each flare based on the landfill gas flow rate recorded pursuant to Part 27, the average methane concentration in the landfill gas based on the most recent source test, and a high heating value for methane of 1013 BTU/scf. The records shall be retained for five years and shall be made available to the District staff upon request. (Basis: Offsets, Cumulative Increase, and Regulation 2-1-301)

36. The Permit Holder shall limit the quantity of VOC soil handled per day so that no more than 15 pounds of total carbon could be emitted to the atmosphere per day. VOC soil is any soil that contains volatile organic compounds, as defined in Regulation 8-40-213, at a concentration of 50 ppmw or less. Soil containing more than 50 ppmw of VOC is considered to be “contaminated soil” and is subject to Part 37 instead of Part 36. Soil containing only non-volatile hydrocarbons and meeting the requirements of Regulation 8-40-113 is not subject to Part 36. In order to demonstrate compliance with this condition, the Permit Holder shall maintain the following records in a District approved log.

- a. Record on a daily basis the amount of VOC soil handled at the landfill. This total amount (in units of pounds per day) is Q in the equation in subpart c below.
- b. Record on a daily basis the VOC content of all soils handled at the landfill. This VOC Content (C in the equation below) should be expressed as parts per million by weight as total carbon (or C₁).
- c. Calculate and record on a daily basis the VOC Emission Rate (E) using the following equation:

$$E = Q * C / 1E6 \times 10^6$$

All records shall be maintained on site or shall be made readily available to District staff upon request for at least 5 years from the date of entry. (Basis: Regulation 8-2-301)

VI. Permit Conditions

Condition # 17309

For S-1 KELLER CANYON LANDFILL – WASTE DECOMPOSITION PROCESS, ABATED BY:
-A-1 LANDFILL GAS FLARE; AND A-2 LANDFILL GAS FLARE
S-4 KELLER CANYON LANDFILL – WASTE AND COVER MATERIAL DUMPING; AND
S-5 KELLER CANYON LANDFILL – EXCAVATING, BULLDOZING, AND COMPACTING
ACTIVITIES:

- *37. Handling Procedures for Soil Containing Volatile Organic Compounds (Basis: Regulations 2-1-403, 8-40-301, 8-40-304 and 8-40-305)
- a. The procedures listed below in subparts b-l do not apply if the following criteria are satisfied. However, the record keeping requirements in subpart m below are applicable.
 - i. The Permit Holder has appropriate documentation demonstrating that either the organic content of the soil or the organic concentration above the soil is below the “contaminated” level (as defined in Regulation 8, Rule 40, Sections 205, 207, and 211). The handling of soil containing VOCs in concentrations below the “contaminated” level is subject to Part 36 above.
 - ii. The Permit Holder has no documentation to prove that soil is not contaminated, but source of the soil is known and there is no reason to suspect that the soil might contain organic compounds.
 - b. The Permit Holder shall provide notification to the Compliance and Enforcement Division of the Permit Holder’s intention to accept contaminated soil at the facility at least 24 hours in advance of receiving the contaminated soil. The Permit Holder shall provide an estimate of the amount of contaminated soil to be received, the degree of contamination (range and average VOC Content), and the type or source of contamination.
 - c. Any soil received at the facility that is known or suspected to contain volatile organic compounds (VOCs) shall be handled as if the soil were contaminated, unless the Permit Holder receives test results proving that the soil is not contaminated. To prove that the soil is not contaminated, the Permit Holder shall collect soil samples in accordance with Regulation 8-40-601 within 24 hours of receipt of the soil by the facility. The organic content of the collected soil samples shall be determined in accordance with Regulation 8-40-602.

VI. Permit Conditions

Condition # 17309

For S-1 KELLER CANYON LANDFILL – [WASTE DECOMPOSITION PROCESS, ABATED BY:](#)
[-A-1 LANDFILL GAS FLARE;](#) AND [A-2 LANDFILL GAS FLARE](#)
[S-4 KELLER CANYON LANDFILL – WASTE AND COVER MATERIAL DUMPING; AND](#)
[S-5 KELLER CANYON LANDFILL – EXCAVATING, BULLDOZING, AND COMPACTING](#)
[ACTIVITIES:](#)

- i. If these test results indicate that the soil is still contaminated or if the soil was not sampled within 24 hours of receipt by the facility, the Permit Holder must continue to handle the soil in accordance with the procedures subparts d-1 below, until the soil has completed treatment or has been placed in a final disposal location and adequately covered. Storing soil in a temporary stockpile or pit is not considered treatment. Co-mingling, blending, or mixing of soil lots is not considered treatment.
- ii. If these test results indicate that the soil – as received at the facility – has an organic content of 50 ppmw or less, then the soil may be considered to be not contaminated and need not be handled in accordance with the procedures listed in subparts d-1 below, but shall be handled in accordance with Part 36 above.
- d. Any contaminated soil received at the facility shall be clearly identified as contaminated soil, shall be handled in accordance with subparts e-1 below, and shall be segregated from non-contaminated soil. Contaminated soil lots may not be co-mingled, blended, or otherwise mixed with non-contaminated soil lots prior to treatment, reuse, or disposal. Mixing soil lots in an attempt to reduce the overall concentration of the contaminated soil or to circumvent any requirements or limits is strictly prohibited.
- e. On-site handling of contaminated soil shall be limited to no more than 2 on-site transfers per soil lot. For instance, unloading soil from off-site transport vehicles into a temporary storage pile is considered one transfer. Moving soil from a temporary storage to a staging area is considered one transfer. Moving soil from a temporary storage pile to a final disposal site is considered one transfer. Moving soil from a staging area to a final disposal site is considered one transfer. Therefore, unloading soil from off-site transport into a temporary storage pile and then moving the soil from that temporary storage pile to the final disposal site is allowed. Unloading soil from off-site transport into a staging area and then moving the soil from that staging area to the final disposal site would be allowed. However, unloading soil from off-site transport to a temporary storage pile, moving this soil to a staging area, and then moving the soil again to a final disposal site would be 3 on-site transfers and is not allowed.

VI. Permit Conditions

Condition # 17309

For S-1 KELLER CANYON LANDFILL – WASTE DECOMPOSITION PROCESS, ABATED BY:
A-1 LANDFILL GAS FLARE; AND A-2 LANDFILL GAS FLARE
S-4 KELLER CANYON LANDFILL – WASTE AND COVER MATERIAL DUMPING; AND
S-5 KELLER CANYON LANDFILL – EXCAVATING, BULLDOZING, AND COMPACTING
ACTIVITIES:

- f. If the contaminated soil has an organic content of less than 500 ppmw, the contaminated soil shall be either treated or deposited in a final disposal site or transported off-site for treatment, within 90 days of receipt at the facility.
- g. If the contaminated soil has an organic content 500 ppmw or more, the contaminated soil shall be either treated or deposited in a final disposal site or transported off-site for treatment, within 45 days of receipt at the facility.
- h. All active storage piles shall meet the requirements of Regulation 8-40-304 by using water sprays, vapor suppressants or approved coverings to minimize emissions. The exposed surface area of any active storage pile (including the active face at a landfill) shall be limited to 6000 ft². The types of storage piles that may become subject to these provisions include (but are not limited to) truck unloading areas, staging areas, temporary stockpiles, soil on conveyors, bulldozers or trucks, the active face of a landfill, or other permanent storage pile at the final disposal location.
- i. All inactive storage piles shall meet the requirements of Regulation 8-40-305 including the requirement to cover contaminated soil during periods of inactivity longer than one hour. The types of storage piles that may become subject to these provisions include (but are not limited to) soil on trucks or other on-site equipment, staging areas, temporary stockpiles, and the permanent storage pile at the final disposal location. District approved coverings for inactive storage piles include continuous heavy-duty plastic sheeting (in good condition, joined at the seams, and securely anchored) or encapsulating vapor suppressants (with re-treatment as necessary to prevent emissions).
- j. The Permit Holder must:
 - i. Keep contaminated soil covered with continuous heavy-duty plastic sheeting (in good condition, joined at the seams, and securely anchored) whenever soil is to be stored in temporary stockpiles or during on-site transport in trucks. Soil in trucks shall not be left uncovered for more than 1 hour.
 - ii. Establish a tipping area for contaminated soils near the active face that is isolated from the tipping area for other wastes.

VI. Permit Conditions

Condition # 17309

For S-1 KELLER CANYON LANDFILL – WASTE DECOMPOSITION PROCESS, ABATED BY:
-A-1 LANDFILL GAS FLARE; AND A-2 LANDFILL GAS FLARE
S-4 KELLER CANYON LANDFILL – WASTE AND COVER MATERIAL DUMPING; AND
S-5 KELLER CANYON LANDFILL – EXCAVATING, BULLDOZING, AND COMPACTING
ACTIVITIES:

- iii. Spray contaminated soil with water or vapor suppressant immediately after dumping the soil from a truck at the tipping area.
- iv. Ensure that all contaminated soil is transferred from the tipping area to the active face immediately after spraying with water or vapor suppressant.
- v. Ensure that contaminated soil in the tipping area is not disturbed by subsequent trucks. Trucks shall not drive over contaminated soil in the tipping area or track contaminated soil out of the tipping area on their wheels.
- vi. Spray contaminated soil on the active face with water or vapor suppressant (to keep the soil visibly moist) until the soil can be covered with an approved covering.
- vii. Limit the area of exposed soil on the active face to no more than 6000 ft².
- viii. Ensure that contaminated soil spread on the active face is completely covered on all sides with one of the following approved coverings: at least 6 inches of clean compacted soil, at least 12 inches of compacted garbage, or at least 12 inches of compacted green waste.

VI. Permit Conditions

Condition # 17309

For S-1 KELLER CANYON LANDFILL – WASTE DECOMPOSITION PROCESS, ABATED BY:
A-1 LANDFILL GAS FLARE; AND A-2 LANDFILL GAS FLARE
S-4 KELLER CANYON LANDFILL – WASTE AND COVER MATERIAL DUMPING; AND
S-5 KELLER CANYON LANDFILL – EXCAVATING, BULLDOZING, AND COMPACTING
ACTIVITIES:

- ix. Ensure that covering of soil on the active face is completed within one hour of the time that the soil was first dumped from a truck at the tipping area.
- k. Contaminated soil shall not be used as daily, intermediate, or final cover material for landfill waste operations unless the requirements of Regulation 8, Rule 40, Sections 116 or 117 have been satisfied.
- l. Contaminated soil is considered to be a decomposable solid waste pursuant to Regulation 8, Rule 34. All contaminated soil disposed of at a site shall be included in any calculations of the amount of decomposable waste in place for annual reporting requirements or for purposes of 8-34-111 or 8-34-304.
- m. The Permit Holder shall keep the following records for each lot of soil received, in order to demonstrate on-going compliance with the applicable provisions of Regulation 8, Rule 40.
 - i. For all soil received by the facility (including soil with no known contamination), record the arrival date at the facility, the soil lot number, the amount of soil in the lot, the organic content or organic concentration of the lot (if known), the type of contamination (if any), and keep copies of any test data or other information that documents whether the soil is contaminated (as defined in 8-40-205) or not contaminated, with what, and by how much.
 - ii. If the soil is tested for organic content after receipt by the facility, a report with the sampling date, test results, and the date results were received.
 - iii. For all on-site handling of contaminated soil, use a checklist or other approved method to demonstrate that appropriate procedures were followed during all on-site handling activities. One checklist shall be completed for each day and for each soil lot (if multiple lots are handled per day).
 - iv. For soil aerated in accordance with 8-40-116 or 117 record the soil lot number, the amount of soil in the lot, the organic content, the final placement date, the final placement location, and describe how the soil was handled or used on-site.

VI. Permit Conditions

Condition # 17309

For S-1 KELLER CANYON LANDFILL – WASTE DECOMPOSITION PROCESS, ABATED BY:

-A-1 LANDFILL GAS FLARE; AND A-2 LANDFILL GAS FLARE

S-4 KELLER CANYON LANDFILL – WASTE AND COVER MATERIAL DUMPING; AND

S-5 KELLER CANYON LANDFILL – EXCAVATING, BULLDOZING, AND COMPACTING
ACTIVITIES:

- v. For final disposal at a landfill, record on a daily basis the soil lot number, the amount of soil placed in the landfill, the disposal date, and the disposal location.

All records shall be retained for at least 5 years from the date of entry and shall be made available for District inspection upon request.

VII. APPLICABLE LIMITS AND COMPLIANCE MONITORING REQUIREMENTS

This section has been included only to summarize the applicable emission limits contained in Section IV, Source-Specific Applicable Requirements, of this permit. The following tables show the relationship between each emission limit and the associated compliance monitoring provisions, if any. The monitoring frequency column indicates whether periodic (P) or continuous (C) monitoring is required. For periodic monitoring, the frequency of the monitoring has also been shown using the following codes: annual (A), quarterly (Q), monthly (M), weekly (W), daily (D), or on an event basis (E). No monitoring (N) has been required if the current applicable rule or regulation does not require monitoring, and the operation is unlikely to deviate from the applicable emission limit based upon the nature of the operation.

This section is only a summary of the limits and monitoring requirements. In the case of a conflict with any requirement in Sections I-VI, the preceding sections take precedence over Section VII.

Table VII – A
Applicable Limits and Compliance Monitoring Requirements
S-1 KELLER CANYON LANDFILL – WASTE DECOMPOSITION PROCESS;
ABATED BY: A-1 LANDFILL GAS FLARE; AND A-2 LANDFILL GAS FLARE;
S-4 KELLER CANYON LANDFILL – WASTE AND COVER MATERIAL DUMPING; AND
S-5 KELLER CANYON LANDFILL – EXCAVATING, BULLDOZING, AND COMPACTING
ACTIVITIES

Type of Limit	Citation of Limit	FE Y/N	Future Effective Date	Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
Collection System Installation Dates	BAAQMD 8-34-304.1	Y		For Inactive/Closed Areas: collection system components must be installed and operating by 2 years + 60 days after initial waste placement	BAAQMD 8-34-501.7 and 501.8 and BAAQMD Condition # 17309, Part 16d-h	P/E	Records

VII. Applicable Limits and Compliance Monitoring Requirements

Table VII – A
Applicable Limits and Compliance Monitoring Requirements
S-1 KELLER CANYON LANDFILL – WASTE DECOMPOSITION PROCESS;
ABATED BY: A-1 LANDFILL GAS FLARE; AND A-2 LANDFILL GAS FLARE;
S-4 KELLER CANYON LANDFILL – WASTE AND COVER MATERIAL DUMPING; AND
S-5 KELLER CANYON LANDFILL – EXCAVATING, BULLDOZING, AND COMPACTING
ACTIVITIES

Type of Limit	Citation of Limit	FE Y/N	Future Effective Date	Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
Collection System Installation Dates	BAAQMD 8-34-304.2 and BAAQMD Condition # 17309, Part 18b	Y		For Active Areas: Collection system components must be installed and operating by 5 years + 60 days after initial waste placement	BAAQMD 8-34-501.7 and 501.8 and BAAQMD Condition # 17309, Part 16d-h	P/E	Records
Collection System Installation Dates	BAAQMD 8-34-304.3 and BAAQMD Condition # 17309, Part 18b	Y		For Any Uncontrolled Areas or Cells: collection system components must be installed and operating within 60 days after the uncontrolled area or cell accumulates 1,000,000 tons of decomposable waste	BAAQMD 8-34-501.7 and 501.8 and BAAQMD Condition # 17309, Part 16d-h	P/E	Records
Collection System Installation Dates	40 CFR 60.753 (a)(2) and 60.755 (b)(2)	Y		For Inactive/Closed Areas: collection system components must be installed and operating by 2 years + 60 days after initial waste placement	40 CFR 60.758(a), (d)(1) and (d)(2), and 60.759(a)(3)	P/E	Records

VII. Applicable Limits and Compliance Monitoring Requirements

Table VII – A
Applicable Limits and Compliance Monitoring Requirements
S-1 KELLER CANYON LANDFILL – WASTE DECOMPOSITION PROCESS;
ABATED BY: A-1 LANDFILL GAS FLARE; AND A-2 LANDFILL GAS FLARE;
S-4 KELLER CANYON LANDFILL – WASTE AND COVER MATERIAL DUMPING; AND
S-5 KELLER CANYON LANDFILL – EXCAVATING, BULLDOZING, AND COMPACTING
ACTIVITIES

Type of Limit	Citation of Limit	FE Y/N	Future Effective Date	Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
Collection System Installation Dates	40 CFR 60.753 (a)(1) and 60.755 (b)(1)	Y		For Active Areas: Collection system components must be installed and operating by 5 years + 60 days after initial waste placement	40 CFR 60.758(a), (d)(1) and (d)(2)	P/E	Records
Gas Flow	BAAQMD 8-34-301 and 301.1 and BAAQMD Condition # 17309, Parts 19, 20, 21	Y		Landfill gas collection system shall operate continuously, all collected gases shall be vented to a properly operating control system, and control system shall operate continuously	BAAQMD 8-34-501.10 and 508 and BAAQMD Condition # 17309, Parts 27 and 28	C	Gas Flow Meter and Recorder (every 15 minutes), Records and Alarms
Gas Flow	40 CFR 60.752 (b)(2)(iii) and 40 CFR 60.753(a) and (e)	Y		Operate a collection system in each area or cell, vent all collected gases to a properly operating control system, and operate control system at all times when gas is vented to it	40 CFR 60.756(b)(2) (i or ii) and 60.758(c)(2)	C or P/M	Gas Flow Meter and Recorder (every 15 minutes) or Monthly Inspection of Bypass Valve and Lock and Records
Collection and Control Systems Shutdown Time	BAAQMD 8-34-113.2	Y		For Collection and Control Systems: ≤ 240 hours/year and ≤ 5 consecutive days	BAAQMD 8-34-501.1 and 501.2	P/D	Operating Records (all occurrences and duration of each)

VII. Applicable Limits and Compliance Monitoring Requirements

Table VII – A
Applicable Limits and Compliance Monitoring Requirements
S-1 KELLER CANYON LANDFILL – WASTE DECOMPOSITION PROCESS;
ABATED BY: A-1 LANDFILL GAS FLARE; AND A-2 LANDFILL GAS FLARE;
S-4 KELLER CANYON LANDFILL – WASTE AND COVER MATERIAL DUMPING; AND
S-5 KELLER CANYON LANDFILL – EXCAVATING, BULLDOZING, AND COMPACTING
ACTIVITIES

Type of Limit	Citation of Limit	FE Y/N	Future Effective Date	Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
Collection and Control Systems Startup Shutdown or Malfunction	40 CFR 60.755(e)	Y		For Collection System: ≤ 5 days per event and For Control System: ≤ 1 hour per event	40 CFR 60.7(b), 60.757(f)(2-4)	P/D	Operating Records (all occurrences and duration of each)
Startup Shutdown or Malfunction Procedures	40 CFR 63.6(e)	Y		Minimize Emissions by Implementing SSM Plan	40 CFR 63.1980(a-b)	P/E	Records (all occurrences, duration of each, corrective actions)
Periods of Inoperation for Parametric Monitors	BAAQMD 1-523.2	Y		≤ 15 consecutive days per incident and ≤ 30 calendar days per 12 month period	BAAQMD 1-523.4	P/D	Operating Records for All Parametric Monitors
Continuous Monitors	40 CFR 60.13(e)	Y		Requires Continuous Operation except for breakdowns, repairs, calibrations, and required span adjustments	40 CFR 60.7(b)	P/D	Operating Records for All Continuous Monitors
Wellhead Pressure	BAAQMD 8-34-305.1	Y		< 0 psig (Applies to all wells that are connected to the vacuum system)	BAAQMD 8-34-414, 501.9 and 505.1	P/M	Monthly Inspection and Records

VII. Applicable Limits and Compliance Monitoring Requirements

Table VII – A
Applicable Limits and Compliance Monitoring Requirements
S-1 KELLER CANYON LANDFILL – WASTE DECOMPOSITION PROCESS;
ABATED BY: A-1 LANDFILL GAS FLARE; AND A-2 LANDFILL GAS FLARE;
S-4 KELLER CANYON LANDFILL – WASTE AND COVER MATERIAL DUMPING; AND
S-5 KELLER CANYON LANDFILL – EXCAVATING, BULLDOZING, AND COMPACTING
ACTIVITIES

Type of Limit	Citation of Limit	FE Y/N	Future Effective Date	Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
Wellhead Pressure	40 CFR 60.753(b)	Y		< 0 psig (Applies to all wells that are connected to the vacuum system)	40 CFR 60.755(a)(3), 60.756(a)(1), and 60.758(c) and (e)	P/M	Monthly Inspection and Records
Temperature of Gas at Wellhead	BAAQMD 8-34-305.2	Y		< 55 °C (Applies to all wells that are connected to the vacuum system)	BAAQMD 8-34-414, 501.9 and 505.2	P/M	Monthly Inspection and Records
Temperature of Gas at Wellhead	40 CFR 60.753(c)	Y		< 55 °C (Applies to all wells that are connected to the vacuum system)	40 CFR 60.755(a)(5), 60.756(a)(3), and 60.758(c) and (e)	P/M	Monthly Inspection and Records
Gas Concentrations at Wellhead	BAAQMD 8-34-305.3 or 305.4	Y		N ₂ < 20% OR O ₂ < 5% (Applies to all wells that are connected to the vacuum system, except for wells identified in Condition # 17309, Part 19b(i))	BAAQMD 8-34-414, 501.9 and 505.3 or 505.4	P/M	Monthly Inspection and Records
Gas Concentrations at Wellhead	40 CFR 60.753(c)	Y		N ₂ < 20% OR O ₂ < 5% (Applies to all wells that are connected to the vacuum system, except for wells identified in Condition # 17309, Part 19b(i))	40 CFR 60.755(a)(5), 60.756(a)(2), and 60.758(c) and (e)	P/M	Monthly Inspection and Records

VII. Applicable Limits and Compliance Monitoring Requirements

Table VII – A
Applicable Limits and Compliance Monitoring Requirements
S-1 KELLER CANYON LANDFILL – WASTE DECOMPOSITION PROCESS;
ABATED BY: A-1 LANDFILL GAS FLARE; AND A-2 LANDFILL GAS FLARE;
S-4 KELLER CANYON LANDFILL – WASTE AND COVER MATERIAL DUMPING; AND
S-5 KELLER CANYON LANDFILL – EXCAVATING, BULLDOZING, AND COMPACTING
ACTIVITIES

Type of Limit	Citation of Limit	FE Y/N	Future Effective Date	Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
Gas Concentrations at Wellhead	BAAQMD Condition # 17309, Part 19b(i)	Y		O ₂ ≤ 15% (Applies to wells identified in Condition # 17309, Part 19b(i) that are connected to the vacuum system)	BAAQMD Condition # 17309, Part 19b(ii and iii)	P/M	Monthly Inspection and Records
Well Shutdown Limits	BAAQMD 8-34-116.2	Y		No more than 5 wells at a time or 10% of total collection system, whichever is less	BAAQMD 8-34-116.5 and 501.1	P/D	Records
Well Shutdown Limits	BAAQMD 8-34-116.3	Y		≤ 24 hours per well	BAAQMD 8-34-116.5 and 501.1	P/D	Records
Well Shutdown Limits	BAAQMD 8-34-117.4	Y		No more than 5 wells at a time or 10% of total collection system, whichever is less	BAAQMD 8-34-117.6 and 501.1	P/D	Records
Well Shutdown Limits	BAAQMD 8-34-117.5	Y		≤ 24 hours per well or ≤ 5 days per well for component replacements	BAAQMD 8-34-117.6 and 501.1	P/D	Records

VII. Applicable Limits and Compliance Monitoring Requirements

Table VII – A
Applicable Limits and Compliance Monitoring Requirements
S-1 KELLER CANYON LANDFILL – WASTE DECOMPOSITION PROCESS;
ABATED BY: A-1 LANDFILL GAS FLARE; AND A-2 LANDFILL GAS FLARE;
S-4 KELLER CANYON LANDFILL – WASTE AND COVER MATERIAL DUMPING; AND
S-5 KELLER CANYON LANDFILL – EXCAVATING, BULLDOZING, AND COMPACTING
ACTIVITIES

Type of Limit	Citation of Limit	FE Y/N	Future Effective Date	Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
Well Shutdown Limits	BAAQMD Condition # 17309, Parts 19c (i and ii)	Y		For individual components that are temporarily disconnected from the vacuum system: ≤ 5 components disconnected at any one time and ≤ 120 days of vacuum disconnection time during any 12-month period for each individual component	BAAQMD Condition # 17309, Part 19c(v)	P/E	Records
TOC (Total Organic Compounds Plus Methane)	BAAQMD 8-34-301.2 and BAAQMD Condition # 17309, Part 19c(iv)	Y		Component Leak Limit: ≤ 1000 ppmv as methane	BAAQMD 8-34-501.6 and 503 and BAAQMD Condition # 17309, Part 19c(iv and v)	P/Q P/E	Quarterly Inspection of collection and control system components with OVA, Additional Inspection of Temporarily Disconnected Components, and Records

VII. Applicable Limits and Compliance Monitoring Requirements

Table VII – A
Applicable Limits and Compliance Monitoring Requirements
S-1 KELLER CANYON LANDFILL – WASTE DECOMPOSITION PROCESS;
ABATED BY: A-1 LANDFILL GAS FLARE; AND A-2 LANDFILL GAS FLARE;
S-4 KELLER CANYON LANDFILL – WASTE AND COVER MATERIAL DUMPING; AND
S-5 KELLER CANYON LANDFILL – EXCAVATING, BULLDOZING, AND COMPACTING
ACTIVITIES

Type of Limit	Citation of Limit	FE Y/N	Future Effective Date	Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
TOC	BAAQMD 8-34-303	Y		Surface Leak Limit: ≤ 500 ppmv as methane at 2 inches above surface	BAAQMD 8-34-415, 416, 501.6, 506 and 510	P/M, Q, and E	Monthly Visual Inspection of Cover, Quarterly Inspection with OVA of Surface, Various Reinspection Times for Leaking Areas, and Records
TOC	BAAQMD 8-34-303 and BAAQMD Condition # 17309, Part 19b(iv)	Y		Surface Leak Limit: ≤ 500 ppmv as methane at 2 inches above surface (Applies to surface vicinity near wells identified in Condition # 17309, Part 19b(i) that are complying with an alternative wellhead oxygen standard instead of the 8-34-305.4 limit)	Condition # 17309, Part 19b(iv-vi)	P/M	Monthly Inspection with OVA of Surface (3 points within 15 m of well), Various Reinspection Times for Leaking Areas, and Records

VII. Applicable Limits and Compliance Monitoring Requirements

Table VII – A
Applicable Limits and Compliance Monitoring Requirements
S-1 KELLER CANYON LANDFILL – WASTE DECOMPOSITION PROCESS;
ABATED BY: A-1 LANDFILL GAS FLARE; AND A-2 LANDFILL GAS FLARE;
S-4 KELLER CANYON LANDFILL – WASTE AND COVER MATERIAL DUMPING; AND
S-5 KELLER CANYON LANDFILL – EXCAVATING, BULLDOZING, AND COMPACTING
ACTIVITIES

Type of Limit	Citation of Limit	FE Y/N	Future Effective Date	Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
TOC	40 CFR 60.753(d)	Y		Surface Leak Limit: ≤ 500 ppmv as methane at 5-10 cm from surface	40 CFR 60.755(c)(1), (4) and (5), 60.756(f), and 60.758(c) and (e)	P/M, Q and E	Monthly Visual Inspection of Cover, Quarterly Inspection with OVA of Surface, Various Reinspection Times for Leaking Areas, and Records
Non-Methane Organic Compounds (NMOC)	BAAQMD 8-34-301.3	Y		<u>For Flares:</u> $\geq 98\%$ removal by weight OR ≤ 30 ppmvd @ 3% O ₂ , expressed as methane	BAAQMD 8-34-412 and 8-34-501.4 and BAAQMD Condition # 17309, Parts 30 and 31	P/A	Initial and Annual Source Tests
NMOC	40 CFR 60.752(b) (2)(iii)(B)	Y		<u>For Flares:</u> $\geq 98\%$ removal by weight OR ≤ 20 ppmvd @ 3% O ₂ , expressed as hexane	40 CFR 60.8 and 60.752(b) (2)(iii)(B) and 60.758 (b)(2)(ii)	P/E	Initial Source Test and Records

VII. Applicable Limits and Compliance Monitoring Requirements

Table VII – A
Applicable Limits and Compliance Monitoring Requirements
S-1 KELLER CANYON LANDFILL – WASTE DECOMPOSITION PROCESS;
ABATED BY: A-1 LANDFILL GAS FLARE; AND A-2 LANDFILL GAS FLARE;
S-4 KELLER CANYON LANDFILL – WASTE AND COVER MATERIAL DUMPING; AND
S-5 KELLER CANYON LANDFILL – EXCAVATING, BULLDOZING, AND COMPACTING
ACTIVITIES

Type of Limit	Citation of Limit	FE Y/N	Future Effective Date	Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
Temperature of Combustion Zone (CT)	BAAQMD Condition # 17309, Part 23	Y		For A-1 Flare: CT \geq 1504 °F (3-hour average) For A-2 Flare: CT \geq 1400 °F (3-hour average)	BAAQMD 8-34-501.3 and 507, and BAAQMD Condition # 17309, Part 22	C	Temperature Sensor and Recorder (continuous)
Temperature of Combustion Zone (CT)	40 CFR 60.758 (c)(1)(i)	Y		For A-1 Flare: CT \geq 1504 °F (3-hour average) from (CT \geq CT _{PF} – 28 °C), where CT _{PF} is the average combustion temperature during the most recent complying performance test, CT _{PF} was 1554 °F during 10/13/04 test For A-2 Flare: CT will be determined during initial performance test	40 CFR 60.756(b)(1) and 60.758 (b)(2)(i)	C	Temperature Sensor and Recorder (measured every 15 minutes and averaged over performance test time period and 3-hours)
POC	BAAQMD Condition # 17309, Part 33	Y		\leq 40.059 tons per year (fugitive POC from all landfill operations)	BAAQMD Condition # 17309, Part 33	P/E	Calculation Procedure (once every 5 years)

VII. Applicable Limits and Compliance Monitoring Requirements

Table VII – A
Applicable Limits and Compliance Monitoring Requirements
S-1 KELLER CANYON LANDFILL – WASTE DECOMPOSITION PROCESS;
ABATED BY: A-1 LANDFILL GAS FLARE; AND A-2 LANDFILL GAS FLARE;
S-4 KELLER CANYON LANDFILL – WASTE AND COVER MATERIAL DUMPING; AND
S-5 KELLER CANYON LANDFILL – EXCAVATING, BULLDOZING, AND COMPACTING
ACTIVITIES

Type of Limit	Citation of Limit	FE Y/N	Future Effective Date	Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
Total Carbon	BAAQMD 8-2-301	Y		≤ 15 pounds/day or ≤ 300 ppm, dry basis only for aeration of or use as cover soil of soil containing ≤ 50 ppmw of volatile organic compounds	BAAQMD Condition # 17309, Part 36a-c	P/E	Records
Amount of Contaminated Soil Aerated or Used as Cover	BAAQMD 8-40-116.1	Y		< 1 cubic yard per project	BAAQMD Condition # 17309, Parts 36a-c and 37m	P/E	Records
Amount of Contaminated Soil Aerated or Used as Cover	BAAQMD 8-40-116.2	Y		≤ 8 cubic yards per project, provided organic content ≤ 500 ppmw and limited to 1 exempt project per 3 month period	BAAQMD 8-40-116.2 and BAAQMD Condition # 17309, Parts 36a-c and 37m	P/E	Records
Amount of Accidental Spillage	BAAQMD 8-40-117	Y		Soil Contaminated by Accidental Spillage of ≤ 5 gallons of Liquid Organic Compounds	None	N	NA
Total Aeration Project Emissions	BAAQMD 8-40-118	Y		≤ 150 pounds per project and toxic air contaminant emissions per year < BAAQMD Table 2-5-1 limits	BAAQMD Condition # 17309, Part 37m	P/E	Records

VII. Applicable Limits and Compliance Monitoring Requirements

Table VII – A
Applicable Limits and Compliance Monitoring Requirements
S-1 KELLER CANYON LANDFILL – WASTE DECOMPOSITION PROCESS;
ABATED BY: A-1 LANDFILL GAS FLARE; AND A-2 LANDFILL GAS FLARE;
S-4 KELLER CANYON LANDFILL – WASTE AND COVER MATERIAL DUMPING; AND
S-5 KELLER CANYON LANDFILL – EXCAVATING, BULLDOZING, AND COMPACTING
ACTIVITIES

Type of Limit	Citation of Limit	FE Y/N	Future Effective Date	Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
Amount of Contaminated Soil Aerated or Used as Cover	BAAQMD 8-40-301 and BAAQMD Condition # 17309, Part 37k	Y		Prohibited for Soil with Organic Content > 50 ppmw unless exempt per BAAQMD 8-40-116, 117, or 118	BAAQMD Condition # 17309, Parts 36a-c and 37m	P/E	Calculations and Records
Contaminated Soil Handling	BAAQMD Condition # 17309, Part 37e	Y		Limited to 2 on-site transfers per lot of contaminated soil	BAAQMD Condition # 17309, Part 37m	P/E	Records
Contaminated Soil On-Site Storage Time	BAAQMD Condition # 17309, Part 37f-g	Y		If organic content is: < 500 ppmw, storage time ≤ 90 days; If organic content is: ≥ 500 ppmw, storage time ≤ 45 days	BAAQMD Condition # 17309, Part 37m	P/E	Records
SO ₂	BAAQMD 9-1-301	Y		Property Line Ground Level Limits: ≤ 0.5 ppm for 3 minutes, ≤ 0.25 ppm for 60 minutes, and ≤ 0.05 ppm for 24 hours	None	N	NA
SO ₂	BAAQMD 9-1-302	Y		In Exhaust Gases From Flares: ≤ 300 ppm (dry)	BAAQMD Condition # 17309, Parts 31 and 34	P/Q	Sulfur Analysis of Landfill Gas

VII. Applicable Limits and Compliance Monitoring Requirements

Table VII – A
Applicable Limits and Compliance Monitoring Requirements
S-1 KELLER CANYON LANDFILL – WASTE DECOMPOSITION PROCESS;
ABATED BY: A-1 LANDFILL GAS FLARE; AND A-2 LANDFILL GAS FLARE;
S-4 KELLER CANYON LANDFILL – WASTE AND COVER MATERIAL DUMPING; AND
S-5 KELLER CANYON LANDFILL – EXCAVATING, BULLDOZING, AND COMPACTING
ACTIVITIES

Type of Limit	Citation of Limit	FE Y/N	Future Effective Date	Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
H ₂ S	BAAQMD 9-2-301	N		Property Line Ground Level Limits: ≤ 0.06 ppm averaged over 3 minutes and ≤ 0.03 ppm averaged over 60 minutes	None	N	NA
Total Reduced Sulfur (TRS) Com-pounds	BAAQMD Condition # 17309, Part 34	Y		In Collected Landfill Gas: ≤ 300 ppmv (dry)	BAAQMD Condition # 17309, Parts 31 and 34	P/Q	Sulfur Analysis of Landfill Gas
Opacity	BAAQMD 6-1-301 and SIP 6-301	Y		For Landfill Operations: ≤ Ringelmann No. 1 for 3 minutes in any hour	BAAQMD Condition # 17309, Part 16j-1	P/D	Records of Water and Dust Suppressant Application
Opacity	BAAQMD 6-1-301 and SIP 6-301	Y		For Flares: ≤ Ringelmann No. 1 for 3 minutes in any hour	BAAQMD 8-34-501.3 and 507, and BAAQMD Condition # 17309, Part 22	C	Temperature Sensor and Recorder (continuous)
FP	BAAQMD 6-1-310 and SIP 6-310	Y		For Flares: ≤ 0.15 grains/dscf	None	N	NA

VII. Applicable Limits and Compliance Monitoring Requirements

Table VII – A
Applicable Limits and Compliance Monitoring Requirements
S-1 KELLER CANYON LANDFILL – WASTE DECOMPOSITION PROCESS;
ABATED BY: A-1 LANDFILL GAS FLARE; AND A-2 LANDFILL GAS FLARE;
S-4 KELLER CANYON LANDFILL – WASTE AND COVER MATERIAL DUMPING; AND
S-5 KELLER CANYON LANDFILL – EXCAVATING, BULLDOZING, AND COMPACTING
ACTIVITIES

Type of Limit	Citation of Limit	FE Y/N	Future Effective Date	Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
Operating Time	BAAQMD Condition # 17309, Part 1	Y		Monday through Friday	BAAQMD Condition # 17309, Parts 16a and 16i	P/D	Records of Waste Received and Truck Traffic
Waste Received	BAAQMD Condition # 17309, Part 2a	Y		≤ 3500 tons per day	BAAQMD Condition # 17309, Part 16a	P/D	Records of Waste Received
Cumulative Waste In-Place	BAAQMD Condition # 17309, Part 2b	Y		≤ 38.4 million tons (≤ 34.8 million Mg)	BAAQMD Condition # 17309, Part 16a	P/D	Records of Waste Placed in Landfill
Design Capacity	BAAQMD Condition # 17309, Part 2c	Y		≤ 75 million yd ³ (≤ 57.3 million m ³) of all wastes and cover materials (excluding final cover)	BAAQMD Condition # 17309, Parts 16a, 36a, and 37m	P/D	Records of Materials Placed in Landfill
Unpaved Road Length	BAAQMD Condition # 17309, Part 5a	Y		≤ 3000 feet from cover stockpile to working face midpoint	BAAQMD Condition # 17309, Part 12	P/E	Site Maps
Unpaved Road Length	BAAQMD Condition # 17309, Part 5b	Y		≤ 400 feet from end of main access road to working face midpoint	BAAQMD Condition # 17309, Part 12	P/E	Site Maps

VII. Applicable Limits and Compliance Monitoring Requirements

Table VII – A
Applicable Limits and Compliance Monitoring Requirements
S-1 KELLER CANYON LANDFILL – WASTE DECOMPOSITION PROCESS;
ABATED BY: A-1 LANDFILL GAS FLARE; AND A-2 LANDFILL GAS FLARE;
S-4 KELLER CANYON LANDFILL – WASTE AND COVER MATERIAL DUMPING; AND
S-5 KELLER CANYON LANDFILL – EXCAVATING, BULLDOZING, AND COMPACTING
ACTIVITIES

Type of Limit	Citation of Limit	FE Y/N	Future Effective Date	Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
Unpaved Road Length	BAAQMD Condition # 17309, Part 5c	Y		≤ 750 feet from end of paved road to end of main access road (this section must have 12 inches of gravel or crushed asphalt)	BAAQMD Condition # 17309, Part 12	P/E	Site Maps
Unpaved Road Length	BAAQMD Condition # 17309, Part 5d	Y		< 1400 feet of fire access roads	BAAQMD Condition # 17309, Part 12	P/E	Site Maps
Vehicle Speed	BAAQMD Condition # 17309, Part 6	Y		≤ 10 mph on unpaved roads and ≤ 25 mph on fire access roads	BAAQMD Condition # 17309, Part 6	P/E	Posted Signs and Enforcement if Necessary
Dust Suppressant Application Rate for Unpaved Roads	BAAQMD Condition # 17309, Part 8a-c	Y		≥ 0.5 gallons per square yard of 10% magnesium chloride applied once every 30 days between May 1 and November 1 and once every 30 consecutive dry days between November 1 and May 1	BAAQMD Condition # 17309, Part 16k	P/D	Records
Water Application Rate for Roads	BAAQMD Condition # 17309, Parts 8 and 10	Y		Once every fifth heavy duty vehicle and more often as necessary	BAAQMD Condition # 17309, Part 16i-j	P/D	Records

VII. Applicable Limits and Compliance Monitoring Requirements

Table VII – A
Applicable Limits and Compliance Monitoring Requirements
S-1 KELLER CANYON LANDFILL – WASTE DECOMPOSITION PROCESS;
ABATED BY: A-1 LANDFILL GAS FLARE; AND A-2 LANDFILL GAS FLARE;
S-4 KELLER CANYON LANDFILL – WASTE AND COVER MATERIAL DUMPING; AND
S-5 KELLER CANYON LANDFILL – EXCAVATING, BULLDOZING, AND COMPACTING
ACTIVITIES

Type of Limit	Citation of Limit	FE Y/N	Future Effective Date	Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
Water Application Rate for Active face and Soil Areas	BAAQMD Condition # 17309, Part 13	Y		≥ 0.5 gallons per square yard twice per day on all dry days	BAAQMD Condition # 17309, Part 16 l	P/D	Records
Truck Traffic Volume	BAAQMD Condition # 17309, Part 11a	Y		≤ 175 transfer truck trips per annual average day	BAAQMD Condition # 17309, Part 16i	P/D	Records
Truck Traffic Volume	BAAQMD Condition # 17309, Part 11b	Y		≤ 4 leachate truck trips per annual average day	BAAQMD Condition # 17309, Part 16i	P/D	Records
Truck Traffic Volume	BAAQMD Condition # 17309, Part 11c	Y		≤ 45 scraper trips per annual average day	BAAQMD Condition # 17309, Part 16i	P/D	Records
Truck Traffic Trip Length	BAAQMD Condition # 17309, Part 12a	Y		≤ 7800 feet for transfer trucks	BAAQMD Condition # 17309, Part 12	P/E	Site Maps and Records
Truck Traffic Trip Length	BAAQMD Condition # 17309, Part 12b	Y		≤ 3600 feet for leachate trucks	BAAQMD Condition # 17309, Part 12	P/E	Site Maps and Records
Truck Traffic Trip Length	BAAQMD Condition # 17309, Part 12c	Y		≤ 3000 feet for scrapers	BAAQMD Condition # 17309, Part 12	P/E	Site Maps and Records

VII. Applicable Limits and Compliance Monitoring Requirements

Table VII – A
Applicable Limits and Compliance Monitoring Requirements
S-1 KELLER CANYON LANDFILL – WASTE DECOMPOSITION PROCESS;
ABATED BY: A-1 LANDFILL GAS FLARE; AND A-2 LANDFILL GAS FLARE;
S-4 KELLER CANYON LANDFILL – WASTE AND COVER MATERIAL DUMPING; AND
S-5 KELLER CANYON LANDFILL – EXCAVATING, BULLDOZING, AND COMPACTING
ACTIVITIES

Type of Limit	Citation of Limit	FE Y/N	Future Effective Date	Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
NO _x	BAAQMD Condition # 17309, Part 24	Y		For both A-1 Flare and A-2 Flare: ≤ 15 ppmv of NO _x , expressed as NO ₂ at 15% O ₂ , dry	BAAQMD Condition # 17309, Part 30	P/A	Annual Source Test
CO	BAAQMD Condition # 17309, Part 25	Y		For A-1 Flare: ≤ 114 ppmv of CO at 15% O ₂ , dry For A-2 Flare: ≤ 81 ppmv of CO at 15% O ₂ , dry	BAAQMD Condition # 17309, Part 30	P/A	Annual Source Test
Acrylonitrile	BAAQMD Condition # 17309, Part 32	N		Concentration in Landfill Gas: ≤ 500 ppbv	BAAQMD Condition # 17309, Part 31	P/A	Annual Laboratory Analysis
Benzene	BAAQMD Condition # 17309, Part 32	N		Concentration in Landfill Gas: ≤ 20,000 ppbv	BAAQMD Condition # 17309, Part 31	P/A	Annual Laboratory Analysis
Carbon Tetrachloride	BAAQMD Condition # 17309, Part 32	N		Concentration in Landfill Gas: ≤ 100 ppbv	BAAQMD Condition # 17309, Part 31	P/A	Annual Laboratory Analysis
Chloroform	BAAQMD Condition # 17309, Part 32	N		Concentration in Landfill Gas: ≤ 100 ppbv	BAAQMD Condition # 17309, Part 31	P/A	Annual Laboratory Analysis
Ethylene Dibromide	BAAQMD Condition # 17309, Part 32	N		Concentration in Landfill Gas: ≤ 100 ppbv	BAAQMD Condition # 17309, Part 31	P/A	Annual Laboratory Analysis

VII. Applicable Limits and Compliance Monitoring Requirements

Table VII – A
Applicable Limits and Compliance Monitoring Requirements
S-1 KELLER CANYON LANDFILL – WASTE DECOMPOSITION PROCESS;
ABATED BY: A-1 LANDFILL GAS FLARE; AND A-2 LANDFILL GAS FLARE;
S-4 KELLER CANYON LANDFILL – WASTE AND COVER MATERIAL DUMPING; AND
S-5 KELLER CANYON LANDFILL – EXCAVATING, BULLDOZING, AND COMPACTING
ACTIVITIES

Type of Limit	Citation of Limit	FE Y/N	Future Effective Date	Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
Ethylene Di-chloride	BAAQMD Condition # 17309, Part 32	N		Concentration in Landfill Gas: ≤ 400 ppbv	BAAQMD Condition # 17309, Part 31	P/A	Annual Laboratory Analysis
Methylene Chloride	BAAQMD Condition # 17309, Part 32	N		Concentration in Landfill Gas: ≤ 16,000 ppbv	BAAQMD Condition # 17309, Part 31	P/A	Annual Laboratory Analysis
Perchloro-ethylene	BAAQMD Condition # 17309, Part 32	N		Concentration in Landfill Gas: ≤ 3,300 ppbv	BAAQMD Condition # 17309, Part 31	P/A	Annual Laboratory Analysis
Trichloro-ethylene	BAAQMD Condition # 17309, Part 32	N		Concentration in Landfill Gas: ≤ 1,500 ppbv	BAAQMD Condition # 17309, Part 31	P/A	Annual Laboratory Analysis
Vinyl Chloride	BAAQMD Condition # 17309, Part 32	N		Concentration in Landfill Gas: ≤ 1,700 ppbv	BAAQMD Condition # 17309, Part 31	P/A	Annual Laboratory Analysis
Heat Input	BAAQMD Condition # 17309, Part 35	Y		For A-1 Flare: ≤ 1744.8 MM BTU per day and ≤ 636,852 MM BTU per year For A-2 Flare: ≤ 1824 MM BTU per day and ≤ 665,760 MM BTU per year	BAAQMD Condition # 17309, Part 35	P/M	Records

VII. Applicable Limits and Compliance Monitoring Requirements

Table VII – B
Applicable Limits and Compliance Monitoring Requirements
S-3 YARD AND GREEN WASTE STOCKPILES

Type of Limit	Citation of Limit	FE Y/N	Future Effective Date	Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
Opacity	BAAQMD 6-1-301 and SIP 6-301	Y		≤ Ringelmann No. 1 for 3 minutes in any hour	BAAQMD Condition # 16462, Part 2	C	Visual Observation of Source in Operation
Waste Received	BAAQMD Condition # 16462, Part 1	Y		≤ 225 tons per day and ≤ 70,200 tons per 12-month period	BAAQMD Condition # 16462, Part 6a and b	P/E	Records of Amount of Waste Received
Waste Storage Time	BAAQMD Condition # 16462, Part 3	N		≤ 4 days from receipt of waste	BAAQMD Condition # 16462, Part 6a and c	P/E	Records of Date and Time for Waste Receipt and Processing
Odorous Stockpile Storage Time	BAAQMD Condition # 16462, Part 4	N		≤ 24 hours from the time the stockpile is deemed “odorous”	BAAQMD Condition # 16462, Part 6a and c	P/E	Records of Date and Time for Waste Receipt and Processing

VIII. TEST METHODS

The test methods associated with the emission limit of a District regulation are generally found in Section 600 et seq. of the regulation. The following table indicates only the test methods associated with the emission limits included in Section VII, Applicable Emission Limits & Compliance Monitoring Requirements, of this permit.

**Table VIII
 Test Methods**

Applicable Requirement	Description of Requirement	Acceptable Test Methods
BAAQMD 6-1-301 and SIP 6-301	Ringelmann No. 1 Limitation	Manual of Procedures, Volume I, Evaluation of Visible Emissions or US EPA Reference Method 9, Visual Determination of the Opacity of Emissions from Stationary Sources
BAAQMD 6-1-310 and SIP 6-310	Particulate Weight Limitation	Manual of Procedures, Volume IV, ST-15, Particulates Sampling ; or For Combustion Equipment: US EPA Reference Method 5 Determination of Particulate Matter Emissions from Stationary Sources for combustion sources
BAAQMD 8-2-301 and SIP 8-2-301	TOC Limit for Miscellaneous Operations	Manual of Procedures, Volume IV, ST-7, Organic Compounds; or US EPA Reference Method 25, Determination of Total Gaseous Nonmethane Organic Emissions as Carbon , or US EPA Reference Method 25A, Determination of Total Gaseous Organic Concentration Using a Flame Ionization Analyzer
BAAQMD 8-34-301.2	Collection and Control System Component Leak Limitation	US EPA Reference Method 21, Determination of Volatile Organic Compound Leaks
BAAQMD 8-34-301.3	NMOC Limits for Flares	Manual of Procedures, Volume IV, ST-7, Organic Compounds and ST-14, Oxygen, Continuous Sampling; or US EPA Reference Method 18, 25, 25A, or 25C
BAAQMD 8-34-303	Landfill Surface Leak Limit	US EPA Reference Method 21, Determination of Volatile Organic Compound Leaks
BAAQMD 8-34-305.1	Wellhead Gauge Pressure Limit	APCO Approved Device
BAAQMD 8-34-305.2	Wellhead Temperature Limit	APCO Approved Device
BAAQMD 8-34-305.3	Wellhead Nitrogen Limit	US EPA Reference Method 3C, Determination of Carbon Dioxide, Methane, Nitrogen, and Oxygen from Stationary Sources
BAAQMD 8-34-305.4	Wellhead Oxygen Limit	US EPA Reference Method 3C, Determination of Carbon Dioxide, Methane, Nitrogen, and Oxygen from Stationary Sources

VIII. Test Methods

Table VIII
Test Methods

Applicable Requirement	Description of Requirement	Acceptable Test Methods
BAAQMD 8-34-412	Compliance Demonstration Test	US EPA Reference Method 18, Measurement of Gaseous Organic Compound Emissions by Gas Chromatography, Method 25, Determination of Total Gaseous Nonmethane Organic Emissions as Carbon, Method 25A, Determination of Total Gaseous Organic Concentration Using a Flame Ionization Analyzer, or Method 25C, Determination of Nonmethane Organic Compounds (NMOC) in MSW Landfill Gases
BAAQMD 8-40-116.2	Organic Content Limit for Small Volume Exemption	BAAQMD 8-40-601 and US EPA Reference Methods 8015B and 8021B
BAAQMD 8-40-301	Limits on Uncontrolled Aeration of Contaminated Soil	BAAQMD 8-40-601 and US EPA Reference Methods 8015B and 8021B; or EPA Reference Method 21
BAAQMD 9-1-301	Limitations on Ground Level Concentrations (SO ₂)	Manual of Procedures, Volume VI, Part 1, Ground Level Monitoring for Hydrogen Sulfide and Sulfur Dioxide
BAAQMD 9-1-302	General Emission Limitation (SO ₂)	Manual of Procedures, Volume IV, ST-19A, Sulfur Dioxide, Continuous Sampling
BAAQMD 9-2-301	Limitations on Hydrogen Sulfide	Manual of Procedures, Volume VI, Part 1, Ground Level Monitoring for Hydrogen Sulfide and Sulfur Dioxide
40 CFR 60.8	Performance Tests	US EPA Reference Method 18, Measurement of Gaseous Organic Compound Emissions by Gas Chromatography, Method 25, Determination of Total Gaseous Nonmethane Organic Emissions as Carbon, Method 25A, Determination of Total Gaseous Organic Concentration Using a Flame Ionization Analyzer, or Method 25C, Determination of Nonmethane Organic Compounds (NMOC) in MSW Landfill Gases
40 CFR 60.752 (b)(2)(iii)(B)	NMOC Outlet Concentration and Destruction Efficiency Limits	US EPA Reference Method 18, Measurement of Gaseous Organic Compound Emissions by Gas Chromatography, Method 25, Determination of Total Gaseous Nonmethane Organic Emissions as Carbon, Method 25A, Determination of Total Gaseous Organic Concentration Using a Flame Ionization Analyzer, or Method 25C, Determination of Nonmethane Organic Compounds (NMOC) in MSW Landfill Gases
40 CFR 60.753(b)	Wellhead Pressure Limit	APCO Approved Device
40 CFR 60.753(c)	Temperature, N ₂ , and O ₂ Concentration Limits in Wellhead Gas	US EPA Reference Method 3C, Determination of Carbon Dioxide, Methane, Nitrogen, and Oxygen from Stationary Sources
40 CFR 60.753(d)	Methane Limit at Landfill Surface	US EPA Reference Method 21, Determination of Volatile Organic Compound Leaks

VIII. Test Methods

Table VIII
Test Methods

Applicable Requirement	Description of Requirement	Acceptable Test Methods
BAAQMD Condition # 17309, Part 19b(i)	Alternative Wellhead Oxygen Limit	US EPA Reference Method 3C, Determination of Carbon Dioxide, Methane, Nitrogen, and Oxygen from Stationary Sources
BAAQMD Condition # 17309, Part 19b(iv)	Landfill Surface Leak Limit in the Vicinity of Components Subject to Alternative Wellhead Standard	US EPA Reference Method 21, Determination of Volatile Organic Compound Leaks
BAAQMD Condition # 17309, Part 19c(iv)	Component Leak Limit for Temporarily Disconnected Components	US EPA Reference Method 21, Determination of Volatile Organic Compound Leaks
BAAQMD Condition # 17309, Part 23	Combustion Temperature Limits for Flares	APCO Approved Device
BAAQMD Condition # 17309, Part 24	NO _x Limit for Flares	Manual of Procedures, Volume IV, Oxides of Nitrogen, Continuous Sampling, and ST-14, Oxygen, Continuous Sampling; or US EPA Reference Method 20
BAAQMD Condition # 17309, Part 25	CO Limit for Flares	Manual of Procedures, Volume IV, ST-6, Carbon Monoxide, Continuous Sampling, and ST-14, Oxygen, Continuous Sampling; or EPA Reference Method 10
BAAQMD Condition # 17309, Part 32	Limits for Specified Toxic Air Contaminants (Acrylonitrile, Benzene, Carbon Tetrachloride, Ethylene Dibromide, Ethylene Dichloride, Methylene Chloride, Perchloroethylene, Trichloroethylene, and Vinyl Chloride) in Landfill Gas	US EPA Reference Method 18, Measurement of Gaseous Organic Compound Emissions by Gas Chromatography
BAAQMD Condition # 17309, Part 33	Fugitive POC Emission Limit for Landfill	Calculation Procedure Described in BAAQMD Condition # 17309, Part 33

VIII. Test Methods

**Table VIII
 Test Methods**

Applicable Requirement	Description of Requirement	Acceptable Test Methods
BAAQMD Condition # 17309, Part 34	Limit for Total Reduced Sulfur Compounds in Landfill Gas	Draeger Tube Method for H ₂ S, used in accordance with manufacturer's recommended procedures, and calculation procedures described in BAAQMD, Condition # 17309, Part 34; OR Manual of Procedures, Volume III, Method 5 Determination of Total Mercaptans in Effluents and Method 25 Determination of Hydrogen Sulfide in Effluents, or Method 44 Determination of Reduced Sulfur Gases and Sulfur Dioxide in Effluent Samples by Gas Chromatographic Methods
BAAQMD Condition # 17309, Part 35	Heat Input Limits for Flares	APCO approved calculation procedure as described in BAAQMD Condition # 17309, Part 35
BAAQMD Condition # 17309, Part 36	Total Carbon Emission Limit for Use or Disposal of Soil Containing VOCs	VOC Content as determined by EPA Reference Methods 8015B, 8021B (or any method determined to be equivalent by the US EPA and approved by the APCO) and converted to Total Carbon as defined in BAAQMD Regulation 8-2-202. Total Carbon Emissions determined by APCO approved equation described in BAAQMD Condition #17309, Part 36c
BAAQMD Condition # 17309, Part 37	Limits on Volatile Organic Compounds Concentrations in Soil and Above Soil	US EPA Reference Methods 8015B, 8021B, or any method determined to be equivalent by the US EPA and approved by the APCO

IX. PERMIT SHIELD

Not Applicable

X. REVISION HISTORY

Title V Permit Issuance (Application # 17348):

September 20, 2001

Minor Revision (Application # 7939):

December 17, 2003

- Add and revise text in Section I, III, IV and VII to conform to current standard text.
- Correct and update regulatory dates in Sections I. and III. Include additional applicable requirement citations in Section III.
- Update Table II A to reflect expansion of the landfill gas collection system.
- Update Table II B to conform to data presented for other landfill flares.
- Update minimum combustion zone temperature, in Tables II-B and VII-D, and Condition #17309 Part 23, to reflect the calculated minimum based on the most recent complying performance test (October 30, 2002).
- Update Tables IV-A, IV-B, IV-D, VII-A, VII-B, VII-D, and VIII and delete Condition # 17309, Part 38 to reflect EPA's adoption of BAAQMD Regulation 8, Rules 34, and 40 into the SIP and BAAQMD's subsequent adoption of amendments to Regulation 1-523 and Regulation 8, Rule 16.
- Update Tables IV-A to include applicable NSPS subsections of 60.754, 60.756 and 60.759.
- Update Tables IV-D to include applicable NSPS subsections of 60.752.
- Revise Condition # 16462 to reflect minor wording changes made to Part 1 under application #2379.
- Revise Condition # 17309, Part 11 to update the number of transfer truck and scraper trips as modified in under application #2379
- Delete references in Condition # 17309, Parts 17 and 33 to proposed IC engines that will not be installed,
- Revise Condition # 17309, Part 20 to reflect expansion of the landfill gas collection system.
- Correct test methods referenced in Table VIII by adding optional methods and deleting obsolete methods.
- Add new terms to Section XI.
- SIP rules available on EPA's website

X. Revision History

- Change Responsible Official

Reopening (Application # 10393):

March 16, 2006

- Add the NESHAP General Provisions (40 CFR, Part 63, Subpart A) and the NESHAP for MSW Landfills (40 CFR, Part 63, Subpart AAAAA) to Table IV-A.
- Combine Table IV-A for the S-1 Keller Canyon Landfill and Table IV-D for the A-1 Landfill Gas Flare into a single Table IV-A for S-1 and A-1, and delete Table IV-D.
- Delete an erroneous citation for SIP Regulation 1 from Table IV-A.
- Update the Regulation 8, Rule 34 amendment date in Table IV-A and correct a related citation reference in Table VII-A.
- Delete Regulation 11, Rules 1 and 3 from Tables IV-A, VII-A, and VIII.
- Update amendment dates for federal requirements in Table IV-A.
- In Condition # 17309, Part 2, clarify the NSR applicability requirements for the waste acceptance limits.
- Clarify notification procedures in Condition # 17309, Parts 3 and 8.
- Clarify record keeping procedures in Condition # 17309, Part 16.
- Clarify the basis for Condition # 17309, Part 18.
- Revise the Condition # 17309, Part 19 reporting requirement and revise the basis for Part 19 in Table IV-A.
- Revise the minimum combustion zone temperature limit for A-1 in Table II-B, Condition # 17309, Part 23, and Table VII-A, and correct the temperature revision procedures in Part 23.
- Correct the NO_x limit for A-1 in Condition # 17309, Part 24 and Table VII-A. Clarify the basis for this limit in Part 24 and in Table IV-A.
- Delete the obsolete POC and NMOC limits listed in Condition # 17309, Parts 26 and 29, and delete the associated references to these limits in Part 30 and Tables IV-A, VII-A, and VIII.

X. Revision History

- For the annual source test in Condition # 17309, Part 30, correct the citations of applicable limits, replace the existing notification and reporting requirements with the new standard language, clarify the testing requirements, and correct the basis.
- For the annual landfill gas characterization test in Condition # 17309, Part 31, replace the testing and reporting requirements with the new standard language, which includes a list of the specific organic compounds that the gas needs to be analyzed for.
- Combine Table VII-A for S-1 and Table VII-D for A-1 into a single Table VII-A for S-1 and A-1, and delete Table VII-D.
- For Table VII-A, delete unnecessary or duplicative limits, add symbols and text to clarify limits, and delete an obsolete future effective date.
- Update the Revision History in Section X.
- Add several terms to the Glossary in Section XI.
- Correct the web site address for SIP requirements in Section XII.

Significant Revision (Application # 11385):

March 16, 2006

- Add the new A-2 Landfill Gas Flare and associated requirements, limits, and test methods to Tables II-B, IV-A, VII-A, and VIII.
- In Condition # 17309, Part 17, 21, 22, 27, and 28, add a reference to the new A-2 Flare and clarify the bases for these parts.
- In Condition # 17309, Part 20, add subpart b that describes landfill gas collection equipment that is under constructions and clarify other Part 20 provisions.
- Add the minimum combustion zone temperature limit for A-2 to Condition # 17309, Part 23.
- Add the NO_x, CO, and heat input limits for A-2 to Condition # 17309, Parts 24, 25, and 35, respectively. Correct the basis for Parts 24 and 35.
- Add an initial compliance demonstration test for A-2 to Condition # 17309, Part 30.

X. Revision History

- In Condition # 17309, Part 31 and Table VIII, add a laboratory analysis for six sulfur compounds to the annual landfill gas characterization test, and add a calculation procedure for the TRS/H₂S ratio that will be used in conjunction with the revised TRS calculation procedure listed in Part 34.
- In Condition # 17309, Part 32 and Table VII-A, increase the concentration limits for acrylonitrile, benzene, and ethylene dichloride.
- In Condition # 17309, Part 33 and Table VII-A, delete the A-1 Flare from the combined POC emission limit for S-1 and A-1 in Condition # 17309, Part 33, and revised the POC limit and calculation procedures for fugitive POC emissions from S-1.
- In Condition # 17309, Part 34 and Table VII-A, revise the limit on total reduced sulfur compounds in landfill gas, and correct the basis accordingly in Part 34 and Table IV-A. Clarify that the Draeger tube analysis method measures hydrogen sulfide (H₂S), and add a TRS calculation method to Part 34.

Significant Revision (Application # 13196):

September 20, 2006

- Add an alternative wellhead oxygen standard to Condition # 17309, Part 20c(i) and Table VII-A.
- Identify wells that are subject to this alternative oxygen standard in Table IV-A, Table VII-A, and Condition # 17309, Part 20c(i).
- Add monitoring and record keeping requirements and procedures for wells subject to the alternative wellhead oxygen standard and the surface vicinity near these wells to Table VII-A, Table VIII, and Condition # 17309, Part 20c(ii-vi).
- Identify criteria for revoking the alternative wellhead oxygen standard for a particular well and state corrective measures to be taken in such situations in Condition # 17309, Part 20c(vii).
- In Section X, correct a date citation and update the revision history to include this proposed revision.

Administrative Amendments (Application # 14795):

October 4, 2006

- On the title page and headers, change the facility from Allied Waste Industries, Inc. to Keller Canyon Landfill Company.

X. Revision History

- Delete the S-2 Wipe Cleaning Operation from the permit by amending Table II-A and by deleting Table IV-B, Condition # 9527, and Table VII-B.
- For the S-3 Yard and Green Waste Stockpiles, renumber Tables IV-C and VII-C as Tables IV-B and VII-B.
- For the S-1 Keller Canyon Landfill, modify the TAC concentration limits in Condition # 17309, Part 32 and Table VII-A.
- For S-1, modify the condition bases in Table IV-A and Condition # 17309, Parts 23, 31, and 32.
- Update the Section X Revision History.

Minor Revision (Application # 14656):

March 2, 2007

- Correct the responsible official and plant contact information on the Title Page.
- In Table II-A, change the number of installed and operating landfill gas collection wells from 50 to 88.
- Modify well station descriptions and the number of wells at these well stations in Condition # 17309, Part 20a.
- Describe additional authorized collection system modifications in Condition # 17309, Part 20b.
- Identify additional wells that are subject to the alternative wellhead oxygen limit in Condition # 17309, Part 20c.
- Add the correct approval date for Application # 13196 and update the revision history for Application # 14656.

Renewal (Application # 14306):

January 3, 2008

- Update regulatory amendment dates in Section I.A.
- Correct the bases for standard conditions I.B.1, I.B.11, I.E.2, and I.F, and make other corrections to standard text in Section I.G.
- Add standard condition text to Section I.B.1 concerning the application shield.
- Add standard condition text to Section I.B.12 that identifies the facility's compliance responsibilities for all equipment including equipment operated by contractors or other agents.
- Add standard language to Section III concerning temporary sources.
- Add EPA's web site address for SIP provisions to Sections III and IV.
- In Table III, update regulatory amendment dates for:

X. Revision History

- Regulation 1, Regulation 2, Rule 1, and for Regulation 8, Rules 2 and 40.
- Delete obsolete SIP citations from Table III for: Regulation 8, Rules 3, 4, and 16.
 - Add the following recently adopted or missing requirements to Table III: Regulation 2, Rule 5; Regulation 4; Regulation 8, Rule 15; Regulation 8, Rule 47; Regulation 9, Rule 1; California H&SC requirements for Portable Equipment; California ATCMs for asbestos, stationary IC engines, and portable engines; and 40 CFR, Part 61, Subparts A and M.
 - In Table IV-A update regulatory amendment dates for Regulation 1; Regulation 8, Rules 2 and 40; 40 CFR Part 60, Subparts A and WWW; and 40 CFR Part 63, Subparts A and AAAA.
 - Remove Regulation 11, Rule 14 from Tables IV-A, VII-A, and VIII.
 - Remove an unnecessary citation from Condition # 17309, Part 16h.
 - Rearrange Condition # 17309, Parts 17-20 to improve readability: Part 17 is now Part 20, Part 18 is now Part 19, Part 19 is now Part 17, and Part 20 is now Part 18 except that Part 20c was moved to Part 19b. Make the associated corrections to part number citations in Tables IV-A, VII-A, and VIII.
 - Remove 12 wells from the list of components subject to alternative wellhead standards per the Applicant's request.
 - Add the new standard temporary well disconnection provisions to Condition # 17309, Part 19c. Add the related requirement, Regulation 8-34-404, to Table IV-A. Add the limits on the number and duration of the temporary disconnections to Table VII-A and clarify applicability of wellhead requirements in Table IV-A. Also in Tables VII-A and VIII, reference the additional component leak monitoring requirements and procedures for temporarily disconnected components.
 - Update standard text that describes the gas collection system alteration requirements, the component replacement provisions, and the individual component decommissioning procedures

X. Revision History

in Condition # 17309, Part 18.

- Correct the basis for Condition # 17309, Part 31 in Section VI and in Table IV-A.
- Update standard text in Section VII.
- Clarify SO₂ and TRS limits in Table VII-A.
- In Table VII-B, correct an opacity citation and clarify requirements by adding \leq symbols where appropriate.
- Revise introductory text for Section VIII.
- Clarify the description of the limit for several test method citations in Table VIII.
- Add descriptions of these renewal revisions to Section X
- Add numerous terms to the glossary.
- Delete Section XII.

Administrative Amendment (Application # 18931):

October 9, 2008

- On the title page, change the Responsible Official and Facility Contact from Kevin Chiapello to Lochlin Caffey.
- In Section I.B.1, correct the due dates for the next MFR renewal permit.

Minor Revision (Applications # 20205 and #23461):

January 11, 2012

- On the title page, change the Responsible Official and Facility Contact from Lochlin Caffey to Rick King.
- In Section I.A, update regulatory amendment dates and add BAAQMD Regulation 2, Rule 5 and SIP Regulation 2, Rule 6.
- Correct basis for Section I.B.7.
- In Table II-A, update the description of the main landfill gas collection system.
- In Table III, update regulatory amendment dates and add SIP 2-1-429; BAAQMD Regulation 6, Rule 1; and BAAQMD Regulation 8, Rule 3.
- In Tables IV-A and IV-B, update regulatory amendment dates and add BAAQMD Regulation 6, Rule 1. In Table IV-A, correct description of Regulation 8, Rule 34 requirements and add missing citations from 40 CFR Part 60, Subpart WWW and from 40 CFR Part 63, Subpart AAAA.
- In Condition #16462 (Parts 2 and 6), correct citation references.

X. Revision History

- In Condition #17309 (Parts 18 and 19), update the list of components that are part of the main landfill gas collection and identify other components that may be connected to the vacuum system for different reasons, clarify the separate operating requirements for the main gas collection system components and these other components, and correct typographical errors.
- In Condition #17309 (Part 20), clarify that collected landfill gas may be vented to a new off-site landfill gas energy facility, describe the specific circumstances under which one or more on-site flares must operate concurrently with the engines at this off-site energy facility to ensure that sufficient landfill gas will be collected to prevent surface leaks, and correct the basis of this part.
- In Tables VII-A, VII-B, and VIII, correct citation references.
- Add the descriptions of this minor revision to Section X.
- In Section XI, add text to explain that the BAAQMD Toxic Risk Management Policy has been replaced by BAAQMD Regulation 2, Rule 5.

Renewal (Application # 24616):

[Enter Issue Date]

- Update regulatory amendment dates in Section I.A.
- Update standard text in Sections I.B, I.F, and I.G.
- Update standard text in Section II.A.
- In Table II-A, update description for S-1 and add missing descriptions for S-4 and S-5.
- In Table III, update regulatory amendment dates for: Regulation 2, Rule 1 and 40 CFR, Part 61, Subparts A and M. Remove CCR, Title 17, Section 93115, because these requirements, when applicable, will be identified in Section IV.
- In Table IV-A update subject source list in table title, update regulatory amendment dates, and add a missing section from 40 CFR, Part 60 Subpart A.
- In Section VI, Condition # 17309: update subject source list, update landfill gas collection system description and list of authorized alterations in Parts 18a-b, update list of wells subject to alternative wellhead limits in Part 19b, and clarify equation in Part 36c.
- In Table VII-A, update subject source list and clarify NMOC emission limits for flares.

X. Revision History

- In Table VIII, add US EPA Reference Methods for particulate emission limits and clarify several other test method citations.
- Add descriptions of these renewal revisions to Section X
- Add terms to the glossary in Section XI.

XI. GLOSSARY

ACT

Federal Clean Air Act

AP-42

An EPA Document “Compilation of Air Pollution Emission Factors” that is used to estimate emissions from numerous source types. It is available electronically from EPA’s web site at: <http://www.epa.gov/ttn/chief/ap42/index.html>

APCO

Air Pollution Control Officer: Head of Bay Area Air Quality Management District

API

American Petroleum Institute

ARB

Air Resources Board (same as CARB)

ASTM

American Society for Testing and Materials

ATC

Authority to Construct

ATCM

Airborne Toxic Control Measure

BAAQMD

Bay Area Air Quality Management District

BACT

Best Available Control Technology

BARCT

Best Available Retrofit Control Technology

Basis

The underlying authority that allows the District to impose requirements.

C1

An organic chemical compound with one carbon atom, for example: methane

XI. Glossary

C3

An organic chemical compound with three carbon atoms, for example: propane

C5

An organic chemical compound with five carbon atoms, for example: pentane

C6

An organic chemical compound with six carbon atoms, for example: hexane

CAA

The federal Clean Air Act

CAAQS

California Ambient Air Quality Standards

CAPCOA

California Air Pollution Control Officers Association

CARB

California Air Resources Board (same as ARB)

CCR

California Code of Regulations

CEC

California Energy Commission

~~CEQA~~

~~California Environmental Quality Act~~

CEM

A "continuous emission monitor" is a monitoring device that provides a continuous direct measurement of some pollutant (e.g. NO_x concentration) in an exhaust stream.

CEQA

California Environmental Quality Act

CFR

The Code of Federal Regulations. 40 CFR contains the implementing regulations for federal environmental statutes such as the Clean Air Act. Parts 50-99 of 40 CFR contain the requirements for air pollution programs.

XI. Glossary

CH₄ or CH₄

Methane

CI

Compression Ignition

CIWMB

California Integrated Waste Management Board

CO

Carbon Monoxide

CO₂ or CO₂

Carbon Dioxide

CO₂e

Carbon Dioxide Equivalent. A carbon dioxide equivalent emission rate is the emission rate of a greenhouse gas compound that has been adjusted by multiplying the mass emission rate by the global warming potential of the greenhouse gas compound. These adjusted emission rates for individual compounds are typically summed together, and the total is also referred to as the carbon dioxide equivalent (CO₂e) emission rate.

CT

Combustion Zone Temperature

Cumulative Increase

The sum of permitted emissions from each new or modified source since a specified date pursuant to BAAQMD Rule 2-1-403, Permit Conditions (as amended by the District Board on 7/17/91) and SIP Rule 2-1-403, Permit Conditions (as approved by EPA on 6/23/95). Used to determine whether threshold-based requirements are triggered.

District

The Bay Area Air Quality Management District

E 6, E 9, E 12

Very large or very small number values are commonly expressed in a form called scientific notation, which consists of a decimal part multiplied by 10 raised to some power. For example, 4.53 E 6 equals $(4.53) \times (10^6) = (4.53) \times (10 \times 10 \times 10 \times 10 \times 10 \times 10) = 4,530,000$. Scientific notation is used to express large or small numbers without writing out long strings of zeros.

EG

Emission Guidelines

XI. Glossary

EO

Executive Order

EPA

The federal Environmental Protection Agency.

ETP

Effluent Treatment Plant

Excluded

Not subject to any District Regulations.

Federally Enforceable, FE

All limitations and conditions which are enforceable by the Administrator of the EPA including those requirements developed pursuant to 40 CFR Part 51, subpart I (NSR), Part 52.21 (PSD), Part 60, (NSPS), Part 61, (NESHAPs), Part 63 (HAP), and Part 72 (Permits Regulation, Acid Rain), and also including limitations and conditions contained in operating permits issued under an EPA-approved program that has been incorporated into the SIP.

FP

Filterable particulate as measured by BAAQMD Method ST-15, Particulate.

FR

Federal Register

GDF

Gasoline Dispensing Facility

GHG

Greenhouse Gas

GLM

Ground Level Monitor

grains

1/7000 of a pound

GWP

Global Warming Potential. A comparison of the ability of each greenhouse gas to trap heat in the atmosphere relative to that of carbon dioxide over a specific time period.

XI. Glossary

H₂S or H₂S

Hydrogen Sulfide

H₂SO₄ or H₂SO₄

Sulfuric Acid

H&SC

Health and Safety Code

HAP

Hazardous Air Pollutant. Any pollutant listed pursuant to Section 112(b) of the Act. Also refers to the program mandated by Title I, Section 112, of the Act and implemented by 40 CFR Part 63.

Hg

Mercury

HHV

Higher Heating Value. The quantity of heat evolved as determined by a calorimeter where the combustion products are cooled to 60F and all water vapor is condensed to liquid.

KCLC

Keller Canyon Landfill Company

LEA

Local Enforcement Agency

LFG

Landfill gas

LHV

Lower Heating Value. Similar to the higher heating value (see HHV) except that the water produced by the combustion is not condensed but retained as vapor at 60 °F.

Long ton

2200 pounds

Major Facility

A facility with potential emissions of: (1) at least 100 tons per year of any regulated air pollutant, (2) at least 10 tons per year of any single hazardous air pollutant, and/or (3) at least 25 tons per year of any combination of hazardous air pollutants, or such lesser quantity of hazardous air pollutants as determined by the EPA administrator.

XI. Glossary

MAX or Max.

Maximum

MFR

Major Facility Review. The District's term for the federal operating permit program mandated by Title V of the Federal Clean Air Act and implemented by District Regulation 2, Rule 6.

MIN or Min.

Minimum

MOP

The District's Manual of Procedures.

MSDS

Material Safety Data Sheet

MSW

Municipal solid waste

MTBE

methyl tertiary-butyl ether

MW

Molecular weight

N2 or N₂

Nitrogen

NA

Not Applicable

NAAQS

National Ambient Air Quality Standards

NESHAPs

National Emission Standards for Hazardous Air Pollutants contained in 40 CFR Parts 61 and 63.

NMHC

Non-methane Hydrocarbons (same as NMOC).

XI. Glossary

NMOC

Non-methane Organic Compounds (same as NMHC).

[NO₂ or NO₂](#)

[Nitrogen Dioxide.](#)

NO_x or NO_x

Oxides of nitrogen.

NSPS

Standards of Performance for New Stationary Sources. Federal standards for emissions from new stationary sources. Mandated by Title I, Section 111 of the Federal Clean Air Act, and implemented by both 40 CFR Part 60 and District Regulation 10.

NSR

New Source Review. A federal program for pre-construction review and permitting of new and modified sources of air pollutants for which the District is classified "non-attainment". Mandated by Title I of the Clean Air Act and implemented by 40 CFR Parts 51 and 52 as well as District Regulation 2, Rule 2. (Note: There are additional NSR requirements mandated by the California Clean Air Act.)

O₂ or O₂

Oxygen

Offset Requirement

A New Source Review requirement to provide federally enforceable emission offsets at a specified ratio for the emissions from a new or modified source and any pre-existing cumulative increase minus any onsite contemporaneous emission reduction credits. Applies to emissions of POC, NO_x, PM₁₀, and SO₂.

[PERP](#)

[Portable Equipment Registration Program](#)

Phase II Acid Rain Facility

A facility that generates electricity for sale through fossil-fuel combustion and by virtue of certain other characteristics (defined in Regulation 2, Rule 6) is subject to Titles IV and V of the Clean Air Act.

POC

Precursor Organic Compounds

PM

Total Particulate Matter

XI. Glossary

PM10 or PM₁₀

Particulate matter with aerodynamic equivalent diameter of less than or equal to 10 microns

PM2.5 or PM_{2.5}

Particulate matter with aerodynamic equivalent diameter of less than or equal to 2.5 microns.

PSD

Prevention of Significant Deterioration. A federal program for permitting new and modified sources of air pollutants for which the District is classified "attainment" of the National Air Ambient Quality Standards. Mandated by Title I of the Act and implemented by both 40 CFR Part 52 and District Regulation 2, Rule 2.

PV or P/V Valve or PRV

Pressure/Vacuum Relief Valve

Regulated Organic Liquid

"Regulated organic liquids" are those liquids which require permits, or which are subject to some regulation, when processed at a liquid-handling operation. For example, for refinery marine terminals, regulated organic liquids are defined as "organic liquids" in Regulation 8, Rule 44.

RICE

Reciprocating Internal Combustion Engine

RMP

Risk Management Plan

RWQCB

Regional Water Quality Control Board

S

Sulfur

SCR

A "selective catalytic reduction" unit is an abatement device that reduces NOx concentrations in the exhaust stream of a combustion device. SCRs utilize a catalyst, which operates at a specific temperature range, and injected ammonia to promote the conversion of NOx compounds to nitrogen gas.

XI. Glossary

[Short ton](#)
[2000 pounds](#)

SIP

State Implementation Plan. State and District programs and regulations approved by EPA and developed in order to attain the National Air Ambient Quality Standards. Mandated by Title I of the Act.

SO₂ or SO₂

Sulfur dioxide

SO₃ or SO₃

Sulfur trioxide

SSM

Startup, Shutdown, or Malfunction

SSM Plan

A plan, which states the procedures that will be followed during a startup, shutdown, or malfunction, that is prepared in accordance with the general NESHAP provisions (40 CFR Part 63, Subpart A) and maintained on site at the facility.

TAC

Toxic Air Contaminant (as identified by CARB)

[TBACT](#)

[Best Available Control Technology for Toxics](#)

THC

Total Hydrocarbons includes all NMHC plus methane (same as TOC).

therm

100,000 British Thermal Unit

Title V

Title V of the federal Clean Air Act. Requires a federally enforceable operating permit program for major and certain other facilities.

TOC

Total Organic Compounds includes all NMOC plus methane (same as THC).

TPH

Total Petroleum Hydrocarbons

XI. Glossary

TRMP

Toxic Risk Management Policy: In 1987, BAAQMD adopted a “Toxic Risk Management Policy” to implement the District’s new source review requirements for new and modified sources of toxic air contaminants. The TRMP was replaced by BAAQMD Regulation 2, Rule 5 on June 15, 2005. The previous TRMP and the subsequent rule are not federally enforceable.

TRS

Total Reduced Sulfur, which is a measure of the amount of sulfur-containing compounds in a gas stream, typically a fuel gas stream, including, but not limited to, hydrogen sulfide. The TRS content of a fuel gas determines the concentration of SO₂ that will be present in the combusted fuel gas, since sulfur compounds are converted to SO₂ by the combustion process.

TSP

Total Suspended Particulate

TVP

True Vapor Pressure

VMT

Vehicle Miles Traveled

VOC

Volatile Organic Compounds

Symbols:

<	=	less than
>	=	greater than
≤	=	less than or equal to
≥	=	greater than or equal to

Units of Measure:

atm	=	atmospheres
bbl	=	barrel of liquid (42 gallons)
bhp	=	brake-horsepower
btu	=	British Thermal Unit
BTU	=	British Thermal Unit
°C	=	degrees Centigrade
cfm	=	cubic feet per minute
dscf	=	dry standard cubic feet
°F	=	degrees Fahrenheit
ft ³	=	cubic feet

XI. Glossary

g	=	grams
gal	=	gallon
gpm	=	gallons per minute
gr	=	grains
hp	=	horsepower
hr	=	hour
in	=	inches
kW	=	kilowatts
lb	=	pound
lbmol	=	pound-mole
m ²	=	square meter
m ³	=	cubic meters
Mg	=	mega grams
min	=	minute
mm	=	millimeter
mm Hg	=	millimeters of mercury (pressure)
MM	=	million
MM BTU	=	million BTU
M cf	=	one thousand cubic feet
M scf	=	one thousand standard cubic feet
MM cf	=	one million cubic feet
MM scf	=	one million standard cubic feet
MW	=	megawatts
ppb	=	parts per billion
ppbv	=	parts per billion, by volume
ppm	=	parts per million
ppmv	=	parts per million, by volume
ppmw	=	parts per million, by weight
psia	=	pounds per square inch, absolute
psig	=	pounds per square inch, gauge
scf	=	standard cubic feet
scfm	=	standard cubic feet per minute
sdcf	=	standard dry cubic feet
sdcfm	=	standard dry cubic feet per minute
yd	=	yard
yd ³	=	cubic yards
yr	=	year